

Package ‘snplist’

July 2, 2014

Type Package

Title Tools to create Gene Sets

Version 0.12

Date 2013-11-22

Author Chanhee Yi, Alexander Sibley, and Kouros Owzar

Maintainer Chanhee Yi <chanhee.yi@dm.duke.edu>

Description A set of functions to create SQL tables of gene and SNP information and compose them into a SNP Set, for example for use with the RSNPset package, or to export to a PLINK set.

License GPL-3

Depends R (>= 3.0.0), RSQLite (>= 0.11.4), biomaRt (>= 2.16.0), Rcpp (>= 0.10.5), R.utils (>= 1.27.1)

Suggests knitr

LinkingTo Rcpp

VignetteBuilder knitr

NeedsCompilation yes

Repository CRAN

Date/Publication 2013-11-26 17:02:19

R topics documented:

snplist-package	2
exportPLINKSet	3
getBioMartData	4
makeGeneSet	5
setGeneTable	6
setSNPTable	7

Index	8
--------------	----------

snplist-package

Tools to create Gene Sets

Description

A set of functions to create SQL tables of gene and SNP information and compose them into a SNP Set, for example for use with the RSNPset package, or to export to a PLINK set.

Details

Package: snplist
Type: Package
Version: 0.12
Date: 2013-11-22
License: GPL-3

Please see the example function calls below, or refer to the individual function documentation or the included vignette for more information.

Author(s)

Authors: Chanhee Yi, Alexander Sibley, and Kouros Owzar Maintainer: Chanhee Yi <chanhee.yi@dm.duke.edu>

See Also

RSQLite, [Rcpp](#)

Examples

```
chromosome <- c(1,5,22,"X","Y","MT")

geneNum <- 5
snpNum <- 1200
annoDataNum <- 500

chrLength <- 1000
geneLength <- 100

gene <- paste("gene",1:geneNum,sep="")
chr <- sample(chromosome,geneNum,replace=TRUE)
start <- sample(chrLength,geneNum,replace=TRUE)
d <- sample(geneLength,geneNum,replace=TRUE)
end <- start+d
geneInfo <- data.frame(gene,chr,start,end)

rsid <- paste("rs",1:snpNum,sep="")
chr <- sample(chromosome,snpNum,replace=TRUE)
```

```
pos <- sample(chrLength+geneLength,snpNum,replace=TRUE)
snpInfo <- data.frame(rsid,chr,pos)

annoInfo <- data.frame("rsid"=sample(rsid,annoDataNum))

dim(geneInfo)
dim(snpInfo)
dim(annoInfo)

setGeneTable(geneInfo)
setSNPTable(snpInfo)
geneset <- makeGeneSet(annoInfo)
exportPLINKSet(geneset,"geneSet.set")
file.show("geneSet.set")
```

exportPLINKSet

exportPLINKSet

Description

Simple function using Rcpp to write the gene set to a file in the PLINK set format.

Usage

```
exportPLINKSet(geneSets, fname)
```

Arguments

geneSets	An object created by the makeGeneSet() function.
fname	The name of the PLINK file to be created.

Value

A Boolean indicating if the file was successfully written.

See Also

[makeGeneSet](#)

Examples

```
# Please see the vignette or the package description
# for an example of using this function.
```

getBioMartData	<i>getBioMartData</i>
----------------	-----------------------

Description

A function leveraging the `biomaRt` package to retrieve gene chromosome and start and end positions from Ensembl.

Usage

```
getBioMartData(genes, verbose=FALSE)
```

Arguments

<code>genes</code>	A vector of gene names matching <code>hgnc_symbol</code> in the Ensembl database.
<code>verbose</code>	A Boolean indicating whether to output the functions progress in terms of the dimensions of the <code>data.frame</code> being constructed. Default is <code>FALSE</code> .

Value

A `data.frame` object with columns `'gene'`, `'chr'`, `'start'`, and `'end'`, suitable for input to the `setGeneTable` function.

References

Durinck S., Spellman P.T., Birney E. and Huber W. (2009) Mapping identifiers for the integration of genomic datasets with the R/Bioconductor package `biomaRt`, *Nature Protocols*, **4**, 1184–1191.

See Also

[setGeneTable](#)

Examples

```
# The query may take some time to execute. Example usage:  
# getBioMartData(c("BRCA1", "BRCA2"))
```

makeGeneSet	<i>makeGeneSet</i>
-------------	--------------------

Description

This function uses existing SQLite tables (from `setGeneTable` and `setSNPTable`) to make SNP sets. The SNP Set for each gene is the collection of SNPs located either between the start and end locations of the gene, or within a specified neighborhood around the gene. The SNP Sets are stored in the SQLite database, and returned as a list object.

Usage

```
makeGeneSet(annoInfo=NULL,margin=0,annoTable='anno',geneTable='gene',
            allTable='allchrpos',db='snplistdb',dbCleanup=FALSE)
```

Arguments

<code>annoInfo</code>	A vector of rsIDs, a data.frame with an 'rsid' column, or a file with one rsID per line. The SNP sets will be restricted to contain only the SNPs listed here. Default is NULL, in which case all SNPs present in the SNP table in the SQLite database will be used.
<code>margin</code>	A number, indicating the size of the neighborhood (in base pairs) surrounding a genes start and end positions in which a SNP will be included in that genes SNP set. Default is 0.
<code>annoTable</code>	A string indicating the name of the SQLite table for the rsIDs from <code>annoInfo</code> . Also used in naming the resulting table of SNP sets ('<name>ToGene'). Default is 'anno'.
<code>geneTable</code>	Name of the SQLite table containg chromosome, start and end positions for each gene, as previously created by <code>setGeneTable</code> . Default is 'gene'.
<code>allTable</code>	Name of the SQLite table containg chromosome and position for each SNP, as previously created by <code>setSNPTable</code> . Default is 'allchrpos'.
<code>db</code>	Name of the SQLite database in which to find the gene and SNP tables and create the SNP set table. Default is 'snplistdb'.
<code>dbCleanup</code>	Boolean indicating if the tables and views created by the function should be dropped after the SNP set is returned. Default is FALSE.

Details

Note: This function relies on the prior execution of the `setGeneTable` and `setSNPTable` functions and the SQLite databes and tables they create. If the `table` or `db` argument in either of those functions is changed from the default value, it must also be changed here.

Value

Returns a list of SNP sets of the form:

<gene name> Vector of rsIDs of SNPs within <gene> (or the neighborhood around it)

See Also

[setGeneTable](#), [setSNPTable](#), [snplist-package](#)

Examples

```
# Please see the vignette or the package description
# for an example of using this function.
```

setGeneTable	<i>setGeneTable</i>
--------------	---------------------

Description

Takes a data.frame object with columns 'gene', 'chr', 'start', and 'end', and creates an SQLite table of the information. Returns a count of the number of genes in the table.

Usage

```
setGeneTable(geneInfo, table='gene', db='snplistdb')
```

Arguments

geneInfo	A data.frame object of gene location info with columns 'gene', 'chr', 'start', and 'end'.
table	Name of the SQLite table to be created. Default is 'gene'.
db	Name of the SQLite database in which to create table. Default is 'snplistdb'.

Value

Count of genes included in table.

Examples

```
geneInfo <- cbind(c('BRCA1', 'BRCA2'), c(17, 13), c(41196312, 32889611), c(41277500, 32973805))
colnames(geneInfo) <- c('gene', 'chr', 'start', 'end')
setGeneTable(as.data.frame(geneInfo))
```

setSNPTable	<i>setSNPTable</i>
-------------	--------------------

Description

Takes a file or `data.frame` object with columns `'chr'`, `'pos'`, and `'rsid'`, and creates an SQLite table of the information. Returns a count of the number of SNPs in the table.

Usage

```
setSNPTable(snpInfo, table='allchrpos', db='snplistdb')
```

Arguments

<code>snpInfo</code>	A <code>data.frame</code> object of SNP location info with columns <code>'chr'</code> , <code>'pos'</code> , and <code>'rsid'</code> , or a tab-delimited file with those columns and one record per row.
<code>table</code>	Name of the SQLite table to be created. Default is <code>'allchrpos'</code> .
<code>db</code>	Name of the SQLite database in which to create table. Default is <code>'snplistdb'</code> .

Value

Count of genes included in table.

Examples

```
snpInfo <- cbind(c(17,17,13,13),  
  c(41211653, 41213996, 32890026,32890572),  
  c("rs8176273","rs8176265","rs9562605","rs1799943") )  
colnames(snpInfo) <- c('chr','pos','rsid')  
setSNPTable(as.data.frame(snpInfo))
```

Index

*Topic **database**

getBioMartData, 4

makeGeneSet, 5

setGeneTable, 6

setSNPTable, 7

*Topic **file**

exportPLINKSet, 3

*Topic **package**

snplist-package, 2

exportPLINKSet, 3

getBioMartData, 4

makeGeneSet, 3, 5

Rcpp, 2

setGeneTable, 4, 6, 6

setSNPTable, 6, 7

snplist (snplist-package), 2

snplist-package, 2