

Package ‘CompLognormal’

July 2, 2014

Type Package

Title Functions for actuarial scientists

Version 3.0

Date 2013-8-4

Author Saralees Nadarajah

Maintainer Saralees Nadarajah <Saralees.Nadarajah@manchester.ac.uk>

Depends R (>= 2.15.0), numDeriv

Description Computes the probability density function, cumulative distribution function, quantile function, random numbers of any composite model based on the lognormal distribution.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2013-08-04 10:31:46

R topics documented:

CompLognormal-package	2
dcomplnorm	2
pcomplnorm	3
qcomplnorm	4
rcomplnorm	5

Index	7
--------------	----------

CompLognormal-package *Computes functions for actuarial use*

Description

Computes the probability density function, cumulative distribution function, quantile function, random numbers of any composite model based on the lognormal distribution

Details

Package: CompLognormal
Type: Package
Version: 3.0
Date: 2013-8-4
License: GPL(>=2)

probability density function, cumulative distribution function, quantile function, random numbers

Author(s)

Saralees Nadarajah

Maintainer: Saralees Nadarajah <Saralees.Nadarajah@manchester.ac.uk>

References

S. Nadarajah, S. A. A. Bakar, CompLognormal: An R Package for Composite Lognormal Distributions, submitted

dcomplnorm *Composite lognormal pdf*

Description

Computes the pdf of the composite lognormal distribution

Usage

```
dcomplnorm(x, spec, sigma = 1, theta = 1, log=FALSE, ...)
```

Arguments

x	scale or vector of positive values at which the pdf needs to be computed
sigma	the value of sigma parameter of the lognormal distribution, must be positive
theta	the value of theta parameter, the cutoff point, must be positive
spec	the specific distribution with which the lognormal distribution should be composed with
log	if TRUE then log(pdf) are returned
...	other parameters

Value

An object of the same length as x, giving the pdf values computed at x

Author(s)

Saralees Nadarajah

References

S. Nadarajah, S. A. A. Bakar, CompLognormal: An R Package for Composite Lognormal Distributions, submitted

Examples

```
x=runif(10,min=0,max=1)
y=dcomplnorm(x,"exp",rate=1)
```

pcomplnorm

Composite lognormal cdf

Description

Computes the cdf of the composite lognormal distribution

Usage

```
pcomplnorm(x, spec, sigma = 1, theta = 1, log.p=FALSE, lower.tail=TRUE, ...)
```

Arguments

x	scale or vector of positive values at which the cdf needs to be computed
sigma	the value of sigma parameter of the lognormal distribution, must be positive
theta	the value of theta parameter, the cutoff point, must be positive
spec	the specific distribution with which the lognormal distribution should be composed with

log.p	if TRUE then log(cdf) are returned
lower.tail	if TRUE then cdf are returned else 1-cdf are returned
...	other parameters

Value

An object of the same length as x, giving the cdf values computed at x

Author(s)

Saralees Nadarajah

References

S. Nadarajah, S. A. A. Bakar, CompLognormal: An R Package for Composite Lognormal Distributions, submitted

Examples

```
x=runif(10,min=0,max=1)
y=qcomplnorm(x,"exp",rate=1)
```

qcomplnorm

Composite lognormal quantile

Description

Computes the quantile function of the composite lognormal distribution

Usage

```
qcomplnorm(p, spec, sigma = 1, theta = 1, log.p=FALSE, lower.tail=TRUE, ...)
```

Arguments

p	scale or vector of probabilities at which the quantile function needs to be computed
sigma	the value of sigma parameter of the lognormal distribution, must be positive
theta	the value of theta parameter, the cutoff point, must be positive
spec	the specific distribution with which the lognormal distribution should be composed with
log.p	if TRUE then quantiles are returned for exp(p)
lower.tail	if TRUE then quantiles are returned for p else quantiles are returned for 1-p
...	other parameters

Value

An object of the same length as p , giving the quantile values computed at p

Author(s)

Saralees Nadarajah

References

S. Nadarajah, S. A. A. Bakar, CompLognormal: An R Package for Composite Lognormal Distributions, submitted

Examples

```
p=runif(10,min=0,max=1)
y=qcomplnorm(p,"exp",rate=1)
```

rcomplnorm

Composite lognormal random numbers

Description

Generates random numbers from the composite lognormal distribution

Usage

```
rcomplnorm(n, spec, sigma = 1, theta = 1, ...)
```

Arguments

n	number of random numbers to be generated
sigma	the value of sigma parameter of the lognormal distribution, must be positive
theta	the value of theta parameter, the cutoff point, must be positive
spec	the specific distribution with which the lognormal distribution should be composited with
...	other parameters

Value

An object of the length n , giving the random numbers from the composite lognormal distribution

Author(s)

Saralees Nadarajah

References

S. Nadarajah, S. A. A. Bakar, CompLognormal: An R Package for Composite Lognormal Distributions, submitted

Examples

```
y=rcomplnorm(100,"exp",rate=1)
```

Index

*Topic **Composite lognormal**

dcomplnorm, [2](#)

pcomplnorm, [3](#)

qcomplnorm, [4](#)

rcomplnorm, [5](#)

*Topic **package**

CompLognormal-package, [2](#)

CompLognormal (CompLognormal-package), [2](#)

CompLognormal-package, [2](#)

dcomplnorm, [2](#)

pcomplnorm, [3](#)

qcomplnorm, [4](#)

rcomplnorm, [5](#)