

Package ‘DepthProc’

November 11, 2014

Version 1.0.3

Date 2014-08-18

Title DepthProc

Author Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Maintainer Zygmunt Zawadzki <zawadzkizygmunt@gmail.com>

Description Data depth concept offers a variety of powerful and user friendly tools for robust exploration and inference for multivariate data. The offered techniques may be successfully used in cases of lack of our knowledge on parametric models generating data due to their nonparametric nature. The package consist of among others implementations of several data depth techniques involving multivariate quantile-quantile plots, multivariate scatter estimators, multivariate Wilcoxon tests and robust regressions.

License GPL-2

Depends R (>= 3.0.0), ggplot2, Rcpp (>= 0.11.2), rrcov, methods, MASS,np

Imports lattice, sm, geometry, colorspace,

Suggests mvtnorm, rgl, sn, robustbase, dplyr, RcppArmadillo

LinkingTo Rcpp, RcppArmadillo

Repository CRAN

Repository/R-Forge/Project depthproc

Repository/R-Forge/Revision 64

Repository/R-Forge/DateTimeStamp 2014-11-11 13:11:46

Date/Publication 2014-11-11 17:41:02

NeedsCompilation yes

R topics documented:

abline,RobReg-method	3
as.matrix	4
asymmetryCurve	4
AsymmetryCurve-class	6
BinnDepth2d-class	6
binningDepth2D	7
CovDepthWeighted-class	9
CovLP	9
ddmvnorm	10
ddPlot	12
DDPlot-class	13
deepReg2d	13
DeepReg2d-class	14
depth	15
Depth-class	16
depthContour	17
DepthCurve-class	18
DepthCurveList-class	19
depthDensity	19
DepthDensity-class	20
depthEuclid	20
depthLocal	21
depthLP	23
depthMah	24
depthMBD	25
depthMedian	25
depthPersp	26
depthProjection	27
depthTukey	28
getPlot	29
inf.mort	29
lsdAddContour	30
LSDepth-class	30
LSDepthContour-class	31
lsdGetContour	31
lsdSampleDepthContours	32
lsdSampleMaxDepth	33
maesles.imm	33
mWilcoxonTest	34
plot	35
plot,BinnDepth2d,ANY-method	36
plot,DepthDensity,ANY-method	37
plot,DepthMBD,ANY-method	37
plot,LSDepthContour,ANY-method	38
RobReg-class	38
runifsphere	39

<i>abline,RobReg-method</i>	3
scaleCurve	39
ScaleCurve-class	41
trimProjReg2d	42
TrimReg2d-class	43
under5.mort	43
USLABOUR	43
%+%	44
Index	45

abline,RobReg-method *Add line to plot*

Description

Add fitted line to a plot. This is overloaded function for robust regression methods from package *depthproc*.

Usage

```
## S4 method for signature 'RobReg'
abline(a = NULL, b = NULL, h = NULL, v = NULL,
       reg = NULL, coef = NULL, untf = FALSE, ...)
```

Arguments

<i>a</i>	an object of class <i>RobReg</i>
<i>b</i>	not used.
<i>h</i>	not supported.
<i>v</i>	not supported.
<i>reg</i>	not supported.
<i>coef</i>	not supported.
<i>untf</i>	not supported.
...	Arguments to be passed to methods, such as graphical parameters (see <i>par</i>).

<code>as.matrix</code>	<i>as.matrix method for DepthCurveList.</i>
------------------------	---

Description

Create a matrix from DepthCurve and DepthCurveList.

Usage

```
as.matrix(x, ...)

## S4 method for signature 'DepthCurveList'
as.matrix(x)
```

Arguments

<code>x</code>	an object of class that inherits from DepthCurveList (ScaleCurveList or AsymmetryCurveList).
<code>...</code>	other arguments passed to standard as.matrix function.

<code>asymmetryCurve</code>	<i>Asymmetry curve based on depths</i>
-----------------------------	--

Description

Produces an asymmetry curve estimated from given data.

Usage

```
asymmetryCurve(x, y = NULL, alpha = seq(0, 1, 0.01),
  method = "Projection", movingmedian = FALSE, name = "X", name_y = "Y",
  ...)
```

Arguments

<code>x</code>	The data as a matrix or data frame. If it is a matrix or data frame, then each row is viewed as one multivariate observation.
<code>y</code>	Additional matrix of multivariate data.
<code>alpha</code>	An ordered vector containing indices of central regins used for asymmetry curve calculation.
<code>method</code>	Character string which determines the depth function used. The method can be "Projection" (the default), "Mahalanobis", "Euclidean", "Tukey" or 'LP'. For details see depth .

movingmedian	Logical. For default FALSE only one depth median is used to compute asymmetry norm. If TRUE - for every central area, a new depth median will be used - this approach needs much more time.
name	Name of set X - used in plot legend
name_y	Name of set Y - used in plot legend
...	Any additional parameters for function depth

Details

For sample depth function $D(x, Z^n)$, $x \in R^d$, $d \geq 2$, $Z^n = \{z_1, \dots, z_n\} \subset R^d$, $D_\alpha(Z^n)$ denoting α -central region, we can define the asymmetry curve $AC(\alpha) = (\alpha, \|c^{-1}(\{\bar{z} - med|D_\alpha(Z^n)\})\|) \subset R^2$, for $\alpha \in [0, 1]$ being nonparametric scale and asymmetry functional correspondingly, where c -denotes constant, \bar{z} -denotes mean vector, denotes multivariate median induced by depth function and vol -denotes a volume.

Asymmetrycurve takes uses function `convhulln` from package `geometry` for computing a volume of convex hull containing central region.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

- Serfling R. J. Multivariate Symmetry and Asymmetry, *Encyclopedia of Statistical Science*, S Kotz, C.B. Read, N. Balakrishnan, B. Vidakovic (eds), 2nd, ed., John Wiley.
- Liu, R.Y., Parelius, J.M. and Singh, K. (1999), Multivariate analysis by data depth: Descriptive statistics, graphics and inference (with discussion), *Ann. Statist.*, **27**, 783–858.
- Chaudhuri, P. (1996), On a Geometric Notion of Quantiles for Multivariate Data, *Journal of the American Statistical Association*, 862–872.
- Dyckerhoff, R. (2004), Data Depths Satisfying the Projection Property, *Allgemeines Statistisches Archiv.*, **88**, 163–190.

See Also

[scaleCurve](#), [depth](#)

Examples

```
#EXAMPLE 1
require(sn)
xi = c(0,0)
alpha <- c(2,-5)
Omega <- diag(2)*5

n = 500
X = mvrnorm(n, xi, Omega) # normal distribution
Y = rmst(n, xi, Omega, alpha, nu=1)
```

```

asymmetryCurve(X,Y,name = "NORM",name_y = "S_T(2,-5,10)")

#EXAMPLE 2
data(under5.mort)
data(Inf.mort)
data(maesles.imm)
data1990=cbind(under5.mort[,1],Inf.mort[,1],maesles.imm[,1])
data2011=cbind(under5.mort[,22],Inf.mort[,22],maesles.imm[,22])
as1990=asymmetryCurve(data1990,name='scale curve 1990')
as2011=asymmetryCurve(data2011,name='scale curve 2011')
figure=getPlot(as1990 %+% as2011)+ggtitle('Scale curves')
figure

```

AsymmetryCurve-class *AsymmetryCurve and AsymmetryCurveList*

Description

AsymmetryCurve is a class that stores results of [asymmetryCurve](#) function.

Details

The mechanism of creating plots with multiple curves is shown in [DepthCurve-class](#) (same mechanism is applied for ScaleCurve).

BinnDepth2d-class *BinnDepth2d*

Description

Class that stores result of function `binningDepth2D(...)`

Slots

`freq` Matrix with number of elements in certain bin.

`mid_x` Middle values on x-axis.

`mid_y` Middle values on y-axis.

`breaks_x` Boundaries of bins.

`breaks_y` Boundaries of bins.

`input_data` Binned data.

`max_depth_x` Point with maximum depth on x-axis.

`max_depth_y` Point with maximum depth on y-axis.

binningDepth2D	<i>2d Binning</i>
----------------	-------------------

Description

A robust method of decreasing a sample size and therefore a complexity of a statistical procedure. The method may be used within a kernel density or a predictive distribution estimation.

Usage

```
binningDepth2D(x, binmethod = "LocDepth", nbins = 8, k = 1,
  remove_borders = FALSE, ...)
```

Arguments

x	bivariate matrix containing data. Each row is viewed as one two-dimensional observation.
binmethod	A method for calculation center and dispersion measures. "LocDepth" uses location-scale depth, "MAD" uses median and MAD in each dimension.
nbins	number of bins in each dimension
k	responsible for tightness of bins.
remove_borders	Logical, include or not marginal bins
...	other arguments passed to depthMedian

Details

Let us recall, that binning is a popular method of decreasing a sample size. To bin a window of n points $W_{i,n} = \{X_{i-n+1}, \dots, X_i\}$ to a grid X'_1, \dots, X'_m we simply assign each sample point X_i to the nearest grid point X'_j . When binning is completed, each grid point X'_j has an associated number c_j , which is the sum of all the points that have been assigned to X'_j . This procedure replaces the data $W_{i,n} = \{X_{i-n+1}, \dots, X_i\}$ with the smaller set $W'_{j,m} = \{X'_{j-m+1}, \dots, X'_j\}$. Although simple binning can speed up the computation, it is criticized for a lack of a precise approximate control over the accuracy of the approximation. Robust binning however stresses properties of the majority of the data and decreases the computational complexity of the DSA at the same time.

For a 1D window $W_{i,n}$, let $Z_{i,n-k}$ denote a 2D window created basing on $W_{i,n}$ and consisted of $n - k$ pairs of observations and the k lagged observations $Z_{i,n-k} = \{(X_{i-n-k}, X_{i-n+1})\}$, $1 \leq i \leq n - k$. Robust 2D binning of the $Z_{i,n-p}$ is a very useful technique in a context of robust estimation of the predictive distribution of a time series (see Kosiorowski:2013b).

Assume we analyze a data stream $\{X_t\}$ using a moving window of a fixed length n , i.e., $W_{i,n}$ and the derivative window $Z_{i,n-1}$. In a first step we calculate the weighted sample L^p depth for $W_{i,n}$. Next we choose equally spaced grid of points l_1, \dots, l_m in this way that $[l_1, l_m] \times [l_1, l_m]$ covers fraction of the β central points of $Z_{i,n-1}$ w.r.t. the calculated L^p depth, i.e., it covers $R^\beta(Z_{i,n-1})$ for certain prefixed threshold $\beta \in (0, 1)$. For both X_t and X_{t-1} we perform a simple binning using following bins: $(-\infty, l_1), (l_1, l_2), \dots, (l_m, \infty)$.

For robust binning we reject "border" classes and further use only midpoints and binned frequencies for classes (l_1, l_2) , (l_2, l_3) , ..., (l_{m-1}, l_m) .

Value

freq: a matrix containing the binned frequencies
 mid_x: mid points for x
 mid_y: mid points for y
 breaks_x: breaks for x
 breaks_y: breaks for y
 input_data: max_depth_x and max_depth_y:

Author(s)

Daniel Kosiorowski and Zygmunt Zawadzki from Cracow University of Economics.

References

Hall, P., Wand, M. P. (1996) On the Accuracy of Binned Kernel Density Estimators, Journal of Multivariate Analysis archive, Volume 56 Issue 2, 165 - 184

Holmstrom, L. (2000) The Accuracy and the Computational Complexity of a Multivariate Binned Kernel Density Estimator, Journal of Multivariate Analysis, Volume 72, Issue 2, 264-309, <http://dx.doi.org/10.1006/jmva.1999.1999> (<http://www.sciencedirect.com/science/article/pii/S0047259X99918638>)

See Also

[depth](#)

Examples

```
#EXAMPLE 1
Sigma1 = matrix(c(10,3,3,2),2,2)
X1 = mvrnorm(n= 8500, mu= c(0,0),Sigma1)
Sigma2 = matrix(c(10,0,0,2),2,2)
X2 = mvrnorm(n= 1500, mu= c(-10,6),Sigma2)
BALLOT = rbind(X1,X2)
train = sample(1:10000, 500)
data =BALLOT[train,]
plot(data)

b1=binningDepth2D(data, remove_borders = FALSE, nbins = 12, k = 1 )
b2=binningDepth2D(data, nbins = 12, k = 1,remove_borders = TRUE )
plot(b1)
plot(b2)

#EXAMPLE 2
data(under5.mort)
data(maesles.imm)
data2011=cbind(under5.mort[,22],maesles.imm[,22])
plot(binningDepth2D(data2011, nbins = 8, k = 0.5,remove_borders = TRUE ))
```

CovDepthWeighted-class
CovLP

Description

CovLP

CovLP *CovLp*

Description

Weighted by L^p depth (outlyingness) multivariate location and scatter estimators.

Usage

CovLP(x, pdim = 2, la = 1, lb = 1)

Arguments

x	The data as a matrix or data frame. If it is a matrix or data frame, then each row is viewed as one multivariate observation.
pdim	The parameter of the weighted $L^p dim$ depth
la	parameter of a simple weight function $w=a*x+b$
lb	parameter of a simple weight function $w=a*x+b$

Details

Using depth function one can define a depth-weighted location and scatter estimators. In case of location estimator we have

$$L(F) = \int x w_1(D(x, F)) dF(x) / \int w_1(D(x, F)) dF(x),$$

Subsequently, a depth-weighted scatter estimator is defined as

$$S(F) = \frac{\int (x - L(F))(x - L(F))^T w_2(D(x, F)) dF(x)}{\int w_2(D(x, F)) dF(x)},$$

where $w_2(\cdot)$ is a suitable weight function that can be different from $w_1(\cdot)$.

The **DepthProc** package offers these estimators for weighted L^p depth. Note that $L(\cdot)$ and $S(\cdot)$ include multivariate versions of trimmed means and covariance matrices. Their sample counterparts take the form

$$T_{WD}(X^n) = \sum_{i=1}^n d_i X_i / \sum_{i=1}^n d_i,$$

$$DIS(X^n) = \frac{\sum_{i=1}^n d_i (X_i - T_{WD}(X^n)) (X_i - T_{WD}(X^n))^T}{\sum_{i=1}^n d_i},$$

where d_i are sample depth weights, $w_1(x) = w_2(x) = x$.

Value

loc: Robust Estimate of Location:

cov: Robust Estimate of Covariance:

Returns depth weighted covariance matrix.

Author(s)

Daniel Kosiorowski and Zygmunt Zawadzki from Cracow University of Economics.

See Also

[depthContour](#) and [depthPersp](#) for depth graphics.

Examples

```
x = mvrnorm(n = 100, mu = c(0,0), Sigma = 3*diag(2))
cov_x = CovLP(x, 2, 1, 1)

# EXAMPLE 2
data(under5.mort,inf.mort,maesles.imm)
data1990 = na.omit(cbind(under5.mort[,1],inf.mort[,1],maesles.imm[,1]))
CovLP(data1990)
```

ddmnorm

Normal depth versus depth plot

Description

Produces a normal DD plot of a multivariate dataset.

Usage

```
ddMvnorm(x, size = nrow(x), robust = FALSE, alpha = 0.05,
  title = "ddMvnorm", ...)
```

Arguments

<code>x</code>	The data sample for DD plot.
<code>size</code>	size of theoretical set
<code>robust</code>	Logical. Default FALSE. If TRUE, robust measures are used to specify the parameters of theoretical distribution.
<code>alpha</code>	cutoff point for robust measure of covariance.
<code>title</code>	title of a plot.
<code>...</code>	Parameters passed to <code>depth</code>

Details

In the first step the location and scale of `x` are estimated and theoretical sample from normal distribution with those parameters is generated. The plot presents the depth of empirical points with respect to dataset `x` and with respect to the theoretical sample.

Value

Returns the normal depth versus depth plot of multivariate dataset `x`.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

Liu, R.Y., Parelius, J.M. and Singh, K. (1999), Multivariate analysis by data depth: Descriptive statistics, graphics and inference (with discussion), *Ann. Statist.*, 27, 783-858.

Liu, R.Y., Singh K. (1993), A Quality Index Based on Data Depth and Multivariate Rank Test, *Journal of the American Statistical Association* vol. 88.

See Also

[ddPlot](#) to generate `ddPlot` to compare to datasets or to compare a dataset with other distributions.

Examples

```
# EXAMPLE 1
norm = mvrnorm(1000, c(0,0,0), diag(3))
con = mvrnorm(100, c(1,2,5), 3*diag(3))
sample = rbind(norm, con)
ddMvnorm(sample, robust=TRUE)

# EXAMPLE 2
data(under5.mort, inf.mort, maesles.imm)
data1990=na.omit(cbind(under5.mort[,1], inf.mort[,1], maesles.imm[,1]))
ddMvnorm(data1990, robust=FALSE)
```

ddPlot *Depth versus depth plot*

Description

Produces a DD plot which allows to compare two multivariate datasets or to compare a subject dataset with theoretical distribution.

Usage

```
ddPlot(x, y, scale = FALSE, location = FALSE, name_x = "X",
       name_y = "Y", title = "Depth vs. depth plot", ...)
```

Arguments

x	The first or only data sample for ddPlot.
y	The second data sample. x and y must be of the same space.
scale	logical. determines whether the dispersion is to be aligned.
location	determines whether the location is to be aligned to 0 vector with depth median.
name_x	name for data set x. It will be passed to drawing function.
name_y	name for data set y.
title	title of the plot.
...	Parameters passed to depth function

Details

For two probability distributions F and G , both in R^d , we can define depth vs. depth plot being very useful generalization of the one dimensional quantile-quantile plot:

$$DD(F, G) = \{(D(z, F), D(z, G)), z \in R^d\}$$

Its sample counterpart calculated for two samples $X^n = \{X_1, \dots, X_n\}$ from F , and $Y^m = \{Y_1, \dots, Y_m\}$ from G is defined as

$$DD(F_n, G_m) = \{(D(z, F_n), D(z, G_m)), z \in \{X^n \cup Y^m\}\}$$

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

Liu, R.Y., Parelius, J.M. and Singh, K. (1999), Multivariate analysis by data depth: Descriptive statistics, graphics and inference (with discussion), *Ann. Statist.*, **27**, 822–831.
 Liu, R.Y., Singh K. (1993), A Quality Index Based on Data Depth and Multivariate Rank Test, *Journal of the American Statistical Association* vol. 88.

Examples

```

require(sn)
require(mvtnorm)

# EXAMPLE 1: Location difference
standard = mvrnorm(1000, c(0,0), diag(2))
shift    = mvrnorm(1000, c(0.5, 0), diag(2))
ddPlot(x = standard, y = shift, title = "Difference in position")
ddPlot(x = standard, y = shift, location = TRUE, title = "Location aligned")

## EXAMPLE 2: Scale difference
standard <- mvrnorm(1000, c(0,0), diag(2))
scale <- mvrnorm(1000, c(0,0), 4*diag(2))
ddPlot(x=standard, y=scale)
ddPlot(x=standard, y=scale, scale=TRUE)

```

DDPlot-class*DDPlot*

Description

Class fro DDPlot

Slots

X Object of class [Depth-class](#).
Y Object of class [Depth-class](#).
title title of a plot.

deepReg2d*Simple deepest regression method.*

Description

This function calculates deepest regression estimator for simple regression.

Usage

deepReg2d(x, y)

Arguments

x Independent variable.
y Dependent variable.

Details

Function originates from an original algorithm proposed by Rousseeuw and Hubert. Let $Z^n = (x_1, y_1), \dots, (x_n, y_n) \subset R^d$ denotes a sample considered from a following semiparametric model: $y_l = a_0 + a_1 x_{1l} + \dots + a_{(d-1)l} x_{(d-1)l} + \varepsilon_l$, $l = 1, \dots, n$, we calculate a depth of a fit $\alpha = (a_0, \dots, a_{d-1})$ as $RD(\alpha, Z^n) = u \neq 0 \min \#l : \frac{r_l(\alpha)}{u^T x_l} < 0$, $l = 1, \dots, n$, where $r(\cdot)$ denotes the regression residual, $\alpha = (a_0, \dots, a_{d-1})$, $u^T x_l \neq 0$. The deepest regression estimator $DR(\alpha, Z^n)$ is defined as

$$DR(\alpha, Z^n) = \alpha \neq 0 \arg \max RD(\alpha, Z^n)$$

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

Rousseeuw J.P., Hubert M. (1998), Regression Depth, *Journal of The American Statistical Association*, vol.94.

Examples

```
data(pension)
plot(pension)
abline(lm(Reserves~Income,data = pension), lty = 3, lwd = 2) #lm
abline(deepReg2d(pension[,1],pension[,2]), lwd = 2) #deepreg2d
#EXAMPLE 2
data(under5.mort)
data(Inf.mort)
data(maesles.imm)
data2011=na.omit(cbind(under5.mort[,22],Inf.mort[,22],maesles.imm[,22]))
x<-data2011[,3]
y<-data2011[,2]
plot(x,y,cex=1.2, ylab="infant mortality rate per 1000 live birth",
xlab="against masles immunized #' percentage",
main='Projection Depth Trimmed vs. LS regressions')
abline(lm(x~y,data = pension), lwd = 2, col='black') #lm
abline(deepReg2d(x,y), lwd = 2,col='red') #trimmed reg
legend("bottomleft",c("LS","DeepReg"),fill=c("black","red"),cex=1.4,bty="n")
```

DeepReg2d-class

DeepReg2d

Description

Class for robust regression methods from depthproc package

Slots

coef coefficients of fitted model
 depth regression depth of the fitted values

depth *Depth calculation*

Description

Depth calculation

Usage

```
depth(u, X, method = "Projection", name = "X", threads = -1, ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
method	Character string which determines the depth function. method can be "Projection" (the default), "Mahalanobis", "Euclidean" or "Tukey". For details see depth .
name	name for this data set - it will be used on plots.
threads	number of threads used in parallel computations. Default value -1 means that all possible cores will be used.
...	parameters specific to method - see depthEuclid

Details

Calculate depth functions.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

- Liu, R.Y., Parelius, J.M. and Singh, K. (1999), Multivariate analysis by data depth: Descriptive statistics, graphics and inference (with discussion), *Ann. Statist.*, 27, 783-858.
- Mosler K (2013). Depth statistics. In C Becker, R Fried, K S (eds.), *Robustness and Complex Data Structures*, Festschrift in Honour of Ursula Gather, pp. 17-34. Springer.
- Rousseeuw, P.J. and Struyf, A. (1998), Computing location depth and regression depth in higher dimensions, *Stat. Comput.*, 8, 193-203.
- Zuo, Y. and Serfling, R. (2000), General Notions of Statistical Depth Functions, *Ann. Statist.*, 28, no. 2, 461-482.

See Also

[depthContour](#) and [depthPersp](#) for depth graphics.

Examples

```
require(robustbase)

## Calculation of Projection depth
data(starsCYG, package = "robustbase")
depth(t(colMeans(starsCYG)), starsCYG)

#Aslo for matrices
depth(starsCYG, starsCYG)

## Projection depth applied to a large bivariate data set
x = matrix(rnorm(9999), nc = 3)
depth(x, x)
```

Depth-class

Depth

Description

Virtual class with structure for every depth class from depthproc package.

Slots

- u data set.
- X reference set.
- method depth type.
- name name that will be used on plots.

depthContour *Approximate depth contours*

Description

Draws an approximate contours of depth for bivariate data.

Usage

```
depthContour(x, xlim = extendrange(x[, 1], f = 0.1), ylim = extendrange(x[,
  2], f = 0.1), n = 50, pmean = TRUE, mcol = "blue", pdmedian = TRUE,
  mecol = "brown", legend = TRUE, points = FALSE, colors = heat_hcl,
  levels = 10, ...)
```

Arguments

x	Bivariate data
xlim	Determines the width of x-axis.
ylim	Determines the width of y-axis.
n	Number of points in each coordinate direction to be used in contour plot.
pmean	Logical. If TRUE mean will be marked.
mcol	Determines the color of lines describing the mean.
pdmedian	Logical. If TRUE depth median will be marked.
mecol	Determines the color of lines describing the depth median.
legend	Logical. If TRUE legend for mean and depth median will be drawn.
points	Logical. If TRUE points from matrix x will be drawn.
colors	function for colors pallete (e.g. gray.colors).
levels	number of levels for color scale.
...	Any additional parameters for function depth (such as method) or graphical parameters (e.g. lwd, lty, main).

Details

The set of all points that have depth at least α is called α - trimmed region. The α - trimmed region w.r.t. F is denoted by $D_\alpha(F)$, i.e.,

$$D_\alpha(F) = \{z \in R^d : D(z, F) \geq \alpha\}$$

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

See Also[depthPersp](#)**Examples**

```
# EXAMPLE 1
x = mvrnorm(1000,c(0,0),diag(2))
depthContour(x, colors = gray.colors)
#with points
depthContour(x, points = TRUE)
depthContour(x, points = FALSE, levels = 10)

#EXAMPLE 2
data(inf.mort,maesles.imm)
data1990=na.omit(cbind(inf.mort[,1],maesles.imm[,1]))
depthContour(data1990, n = 50, pmean = TRUE, mcol = "blue",
pdmedian = TRUE, mecol = "brown", legend = TRUE, points = TRUE,
xlab="infant mortality rate per 1000 live birth",
ylab="against masles immunized percentage", main='L2 depth,
UN Fourth Goal 2011 year',method = "LP")
```

DepthCurve-class

*DepthCurve***Description**

This page describes mechanism behavior of ScaleCurve and AsymmetryCurve

Details

DepthCurve is a virtual class that contains methods (getPlot(...) and plot(...)) for rendering single curve such as ScaleCurve or AsymmetryCurve. Such object can be added by overloaded operator ' + '

Slots

depth object of [Depth-class](#)

title title of a plot

alpha central area values

Examples

```
require(mvtnorm)
x = mvrnorm(n = 100, mu = c(0,0), Sigma = 2*diag(2))
y = rmvt(n = 100, sigma = diag(2), df = 4)
s1 = scaleCurve(x, method = "Projection", plot = FALSE)
s2 = scaleCurve(y, method = "Projection", plot = FALSE, name = "Set2")
```

```

sc_list = s1 %+% s2 # Add one curve to another

plot(sc_list) # Draw plot with two curves

z = mvrnorm(n = 100, mu = c(0,0), Sigma = 1*diag(2))
s3 = scaleCurve(z, method = "Projection", plot = FALSE)
plot(sc_list%+%s3) # Add third curve and draw a plot

```

DepthCurveList-class *DepthCurveList*

Description

DepthCurveList is a special container for DepthCurve objects. See [DepthCurve-class](#)

depthDensity *Depth weighted density estimator*

Description

Depth weighted density estimator

Usage

```
depthDensity(x, y, nx = 5, ny = 32, xg = NULL, yg = NULL, ...)
```

Arguments

x	numeric vector
y	numeric vector
nx	the number of equally spaced points at which the density is to be estimated in x-dimension.
ny	the number of equally spaced points at which the density is to be estimated in y-dimension.
xg	vector of point at which the density is to be estimated.
yg	vector of point at which the density is to be estimated.
...	arguments passed to depthLocal.

References

Kosiorowski D. and Zawadzki Z. (2014) Notes on optimality of predictive distribution pseudo-estimators in the CHARME models and automatic trading strategies, FindEcon2014, submitted

Examples

```
## Not run:
# .sampleData is special function for creating
# data for testing conditional density estimators
data = DepthProc::.sampleData(1:5, 100)
x = data[,1]; y = data[,2]
plot(x,y)
dep = depthDensity(x,y)
plot(dep, type = "raw")
plot(dep, type = "depth")

## End(Not run)
```

DepthDensity-class *DepthDensity*

Description

Class for depth based density estimator.

Details

[depthDensity](#)

depthEuclid *Euclidean Depth*

Description

Computes the euclidean depth of a point or vectors of points with respect to a multivariate data set.

Usage

```
depthEuclid(u, X, name = "X", ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
name	name for this data set - it will be used on plots from depthproc.
...	currently not supported.

Details

Calculation of Euclidean depth is exact.

Returns the depth of multivariate point u with respect to data set X .

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x <- matrix(rnorm(9999), nc = 3)
depthEuclid(x, x)
```

depthLocal	<i>Local depth</i>
------------	--------------------

Description

Computes local version of depth according to proposals of Paindaveine and Van Bever - see references.

Usage

```
depthLocal(u, X, beta = 0.5, depth1 = "Projection", depth2 = depth1,
  name = "X", ...)
```

Arguments

<code>u</code>	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
<code>X</code>	The data as a matrix, data frame. If it is a matrix or data frame, then each row is viewed as one multivariate observation.
<code>beta</code>	cutoff value for neighbourhood
<code>depth1</code>	depth method for symmetrised data
<code>depth2</code>	depth method for calculation depth of given point
<code>name</code>	name for this data set - it will be used on plots.
<code>...</code>	additional parameters passed to <code>depth1</code> and <code>depth2</code>

Details

A successful concept of local depth was proposed by Paidaveine and Van Bever (2012). For defining a neighbourhood of a point authors proposed using idea of symmetrisation of a distribution (a sample) with respect to a point in which depth is calculated. In their approach instead of a distribution P^X , a distribution $P_x = 1/2P^X + 1/2P^{2x-X}$ is used. For any $\beta \in [0, 1]$, let us introduce the smallest depth region bigger or equal to β ,

$$R^\beta(F) = \bigcap_{\alpha \in A(\beta)} D_\alpha(F),$$

where $A(\beta) = \{\alpha \geq 0 : P[D_\alpha(F)] \geq \beta\}$. Then for a locality parameter β we can take a neighbourhood of a point x as $R_x^\beta(P)$.

Formally, let $D(\cdot, P)$ be a depth function. Then the local depth with the locality parameter β and w.r.t. a point x is defined as

$$LD^\beta(z, P) : z \rightarrow D(z, P_x^\beta),$$

where $P_x^\beta(\cdot) = P(\cdot | R_x^\beta(P))$ is cond. distr. of P conditioned on $R_x^\beta(P)$.

References

Paindaveine, D., Van Bever, G. (2013) From depth to local depth : a focus on centrality. Journal of the American Statistical Association 105, 1105-1119 (2013).

Examples

```
## Not run:
# EXAMPLE 1
data = mvrnorm(100, c(0,5), diag(2)*5)
#by default depth2 = depth1
depthLocal(data, data, depth1 = "LP")
depthLocal(data, data, depth1 = "LP", depth2 = "Projection")
## Depthcontour
depthContour(data, method = "Local", depth1 = "LP")
# EXAMPLE 2
data(inf.mort,maesles.imm)
data1990=na.omit(cbind(inf.mort[,1],maesles.imm[,1]))
depthContour(data1990, method = "Local", depth1 = "LP",beta=0.3)

#EXAMPLE 3
Sigma1 = matrix(c(10,3,3,2),2,2)
X1 = mvrnorm(n= 8500, mu= c(0,0),Sigma1)
Sigma2 = matrix(c(10,0,0,2),2,2)
X2 = mvrnorm(n= 1500, mu= c(-10,6),Sigma2)
BALLOT=rbind(X1,X2)

train <- sample(1:10000, 100)
data<-BALLOT[train,]
depthContour(data, method = "Local", depth1 = "Projection",beta=0.3)

## End(Not run)
```

depthLP	<i>LP Depth</i>
---------	-----------------

Description

Computes the LP depth of a point or vectors of points with respect to a multivariate data set.

Usage

```
depthLP(u, X, pdim = 2, la = 1, lb = 1, name = "X", threads = -1,
        func = NULL, ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
pdim	dimension used in calculating depth function.
la	slope the weighing function.
lb	intercept in the weighing function.
name	name for this data set - it will be used on plots from depthproc.
threads	number of threads used in parallel computations. Default value -1 means that all possible cores will be used.
func	the weighing function. Currently it is not supported.
...	currently not supported.

Details

Returns the depth of multivariate point u with respect to data set X.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x = matrix(rnorm(3000), ncol = 3)

#Same results
depthLP(x, x, ndir = 2000, pdim = 2)
```

 depthMah

Mahalanobis Depth

Description

Computes the mahalanobis depth of a point or vectors of points with respect to a multivariate data set.

Usage

```
depthMah(u, X, name = "X", cov = NULL, mean = NULL, threads = -1, ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
name	name for this data set - it will be used on plots.
cov	custom covariance matrix passed. If NULL standard calculations will be based on standard covariance estimator.
mean	custom mean vector. If null mean average will be used.
threads	number of threads used in parallel computations. Default value -1 means that all possible cores will be used.
...	currently not supported.

Details

Calculation of Mahalanobis depth is exact.

Returns the depth of multivariate point u with respect to data set X.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x <- matrix(rnorm(9999), nc = 3)
depthMah(x, x)
```

depthMBD	<i>Modified band depth</i>
----------	----------------------------

Description

Computes the modified band depth.

Usage

```
depthMBD(u, X, name = "X", ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
name	for this data set - it will be used on plots from depthproc.
...	currently not supported.

Examples

```
x = matrix(rnorm(600), nc = 20)
depthMBD(x)
```

depthMedian	<i>Depth median</i>
-------------	---------------------

Description

Return point with maximum depth function value. If multiple points have the same value, mean average of them will be returned.

Usage

```
depthMedian(x, ...)

## S4 method for signature 'matrix'
depthMedian(x, ...)

## S4 method for signature 'data.frame'
depthMedian(x, ...)

## S4 method for signature 'Depth'
depthMedian(x)
```

Arguments

x object of class Depth or matrix.
 ... arguments passed to `depth` function (e.g method).

Examples

```
# depthMedian for matrix
x = matrix(rnorm(600), nc = 3)
depthMedian(x)

# depthMedian works with object of class Depth
dp = depth(x)
depthMedian(dp)
```

 depthPersp

Perspective plot for depth functions

Description

Draws a perspective plot of depth function over x-y plane.

Usage

```
depthPersp(x, plot_method = "lattice", xlim = extendrange(x[, 1], f = 0.1),
  ylim = extendrange(x[, 2], f = 0.1), n = 50, xlab = "x", ylab = "y",
  plot_title = NULL, colors = heat_hcl, ...)
```

Arguments

x bivariate data
 plot_method there are two options "lattice", and "rgl" - see details
 xlim limits for x-axis
 ylim limits for y-axis
 n number of points that will be used to create plot (n^2)
 xlab description of x-axis
 ylab description of y-axis
 plot_title plot title (default NULL means `paste(method, "depth")`)
 colors function for colors pallete (e.g. `gray.colors`).
 ... arguments passed to depth function

Details

`plot_method = rgl` package is not in depends list because it may cause problems when OpenGL is not supported. To use `plot_method = "rgl"` you must load this package on your own.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x = mvrnorm(100,c(0,0),diag(2))
depthPersp(x, method = "Euclidean")

# EXAMPLE 2
data(inf.mort,maesles.imm)
data1990=na.omit(cbind(inf.mort[,1],maesles.imm[,1]))

## Not run:
require(rgl)
depthPersp(data1990, method = "Projection",plot_method= "rgl")

## End(Not run)
```

depthProjection	<i>Projection Depth</i>
-----------------	-------------------------

Description

Computes the Projection depth of a point or vectors of points with respect to a multivariate data set.

Usage

```
depthProjection(u, X, ndir = 1000, name = "X", threads = -1, ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
ndir	number of directions used in computations
name	name for this data set - it will be used on plots from depthproc.
threads	number of threads used in parallel computations. Default value -1 means that all possible cores will be used.
...	currently not supported.

Details

Irrespective of dimension, Projection and Tukey's depth is obtained by approximate calculation. Returns the depth of multivariate point u with respect to data set X.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x = matrix(rnorm(3000), nc = 3)
a = depthProjection(x, x, ndir = 2000)
```

 depthTukey

Tukey Depth

Description

Computes the Tukey depth of a point or vectors of points with respect to a multivariate data set.

Usage

```
depthTukey(u, X, ndir = 1000, name = "X", threads = -1, exact = FALSE,
  ...)
```

Arguments

u	Numerical vector or matrix whose depth is to be calculated. Dimension has to be the same as that of the observations.
X	The data as a matrix, data frame or list. If it is a matrix or data frame, then each row is viewed as one multivariate observation. If it is a list, all components must be numerical vectors of equal length (coordinates of observations).
ndir	number of directions used in computations
name	name for this data set - it will be used on plots from depthproc.
threads	number of threads used in parallel computations. Default value -1 means that all possible cores will be used.
exact	if TRUE exact algorithm will be used . Currently it works only for 2 dimensional data set.
...	currently not supported.

Details

Irrespective of dimension, Projection and Tukey's depth is obtained by approximate calculation.

Returns the depth of multivariate point u with respect to data set X.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
## Not run:
x = matrix(rnorm(3000), nc = 3)
depthTukey(x, ndir = 2000)

## End(Not run)

# Exact algorithm in 2d
x = matrix(rnorm(2000), nc = 2)
depthTukey(x, exact = TRUE)
```

getPlot	<i>Create ggplot object from DepthCurve, DepthCurveList and DDPlot classes.</i>
---------	---

Description

Create an object of class ggplot from DepthCurve and DepthCurveList.

Usage

```
getPlot(object)

## S4 method for signature 'AsymmetryCurveList'
getPlot(object)

## S4 method for signature 'DDPlot'
getPlot(object)

## S4 method for signature 'ScaleCurveList'
getPlot(object)
```

Arguments

object a DDPlot ScaleCurve or AsymmetryCurve object class.

inf.mort	<i>Infant mortality rate (0-1 year) per 1,000 live births</i>
----------	---

Description

Infant mortality rate (0-1 year) per 1,000 live births

Usage

```
data(inf.mort)
```

Format

A data frame with 654 rows and 4 variables

Source

<http://mdgs.un.org/unsd/mdg/Data.aspx>

lsdAddContour	<i>Adds location scale depth contour to a plot.</i>
---------------	---

Description

Adds location scale depth contour to a plot.

Usage

```
lsdAddContour(x, cont = NULL, ...)

## S4 method for signature 'LSDepthContour'
lsdAddContour(x, cont = NULL, ...)
```

Arguments

x	object of class LSDepthContour
cont	depth of contour to plot
...	other arguments passed to polygon function

Examples

```
smp = rf(100,5,10)
x = lsdSampleDepthContours(smp)
plot(x)
lsdAddContour(x,0.1, col = "grey50")
lsdAddContour(x,0.3, col = "grey10", border = "red", lwd = 4)
```

LSDepth-class	<i>Location-Scale depth class</i>
---------------	-----------------------------------

Description

Location-Scale depth class

LSDepthContour-class *Location-Scale depth contour class*

Description

Location-Scale depth contour class

lsdGetContour *Get location-scale contour from LSDepthContour object*

Description

Get location-scale contour from LSDepthContour object

Usage

```
lsdGetContour(x, cont)

## S4 method for signature 'LSDepthContour'
lsdGetContour(x, cont)
```

Arguments

x object of class LSDepthContour
cont single numeric - depth of contour to return

Details

Calculations are based on lsdepth algorithm written by Ch. Muller.

Examples

```
dcont = lsdSampleDepthContours(rf(200,4,7), depth = c(0.1,0.2))

# get contour that is present in dcont object
lsdGetContour(dcont,0.1)

# get contour that is not present in dcont
# it will be automatically calculated
lsdGetContour(dcont,0.3)
```

`lzdSampleDepthContours`*Calculate sample Mizera and Muller Student depth contours*

Description

Calculate sample Mizera and Muller Student depth contours

Usage

```
lzdSampleDepthContours(x, depth = c(0.1, 0.2, 0.3, 0.4), lengthmu = 1000)
```

Arguments

<code>x</code>	one dimensional vector with sample
<code>depth</code>	depth level for contours
<code>lengthmu</code>	number of points to evaluate depth

Details

Calculations are based on `ldepth` algorithm written by Ch. Muller.

References

Mizera, I., Muller, C. H., 2004. Location-scale depth (with discussion). *Journal of the American Statistical Association* 99, 949-966.

Examples

```
## EXAMPLE 1 for F-distribution
dcont = lzdSampleDepthContours(rf(200,4,7))
plot(dcont)

## EXAMPLE 2 for normal distribution
## - more contours calculated
dcont_norm = lzdSampleDepthContours(rnorm(100),seq(0.05,0.4,0.05))
plot(dcont_norm)
```

lsdSampleMaxDepth	<i>Calculates the maximum sample location-scale depth</i>
-------------------	---

Description

Calculates the maximum Student depth estimator of location and scale for one dimensional data (an alternative for MED and MAD or for the mean and standard deviation).

Usage

```
lsdSampleMaxDepth(x, iter = 100, eps = 1e-04, p_length = 10)
```

Arguments

x	one dimensional vector with sample
iter	maximum number of iterations in algorithm for calculation Location-Scale Depth
eps	tolerance level
p_length	is the maximum length of the precision step at the end

Details

Calculations are based on lsdepth algorithm written by Ch. Muller.

References

Mizera, I., Muller, C. H., 2004. Location-scale depth (with discussion). Journal of the American Statistical Association 99, 949 - 966.

Examples

```
x = rnorm(100)
lsdSampleMaxDepth(x)
y = rf(100, 4,10)
lsdSampleMaxDepth(y)
```

maesles.imm	<i>Children 1 year old immunized against measles, percentage</i>
-------------	--

Description

Children 1 year old immunized against measles, percentage

Usage

```
data(maesles.imm)
```

Format

A data frame with 654 rows and 4 variables

Source

<http://mdgs.un.org/unsd/mdg/Data.aspx>

mWilcoxonTest

Depth based multivariate Wilcoxon test for a scale difference.

Description

Depth based multivariate Wilcoxon test for a scale difference.

Usage

```
mWilcoxonTest(x, y, alternative = "two.sided", ...)
```

Arguments

x	data matrix
y	data matrix
alternative	a character string specifying the alternative hypothesis, must be one of "two.sided" (default), "greater" or "less".
...	arguments passed to depth function(e.g. method)

Details

Having two samples X^n and Y^m using any depth function, we can compute depth values in a combined sample $Z^{n+m} = X^n \cup Y^m$, assuming the empirical distribution calculated basing on all observations, or only on observations belonging to one of the samples X^n or Y^m .

For example if we observe X_i 's depths are more likely to cluster tightly around the center of the combined sample, while Y_i 's depths are more likely to scatter outlying positions, then we conclude Y^m was drawn from a distribution with larger scale.

Properties of the DD plot based statistics in the i.i.d setting were studied by Li & Liu (2004). Authors proposed several DD-plot based statistics and presented bootstrap arguments for their consistency and good effectiveness in comparison to Hotelling T^2 and multivariate analogues of Ansari-Bradley and Tukey-Siegel statistics. Asymptotic distributions of depth based multivariate Wilcoxon rank-sum test statistic under the null and general alternative hypotheses were obtained by Zuo & He (2006). Several properties of the depth based rang test involving its unbiasedness was critically discussed by Jureckova & Kalina (2012). Basing on DD-plot object, which is available within the **DepthProc** it is possible to define several multivariate generalizations of one-dimensional rank and order statistics in an easy way. These generalizations cover well known Wilcoxon rang-sum statistic.

The depth based multivariate Wilcoxon rang sum test is especially useful for the multivariate scale changes detection and was introduced among other by Liu & Singh (2003) and intensively studied by Jureckowa & Kalina (2012) and Zuo & He (2006) in the i.i.d. setting.

For the samples $X^m = \{X_1, \dots, X_m\}$, $Y^n = \{Y_1, \dots, Y_n\}$, their $d_1^X, \dots, d_m^X, d_1^Y, \dots, d_n^Y$, depths w.r.t. a combined sample $Z = X^n \cup Y^m$ the Wilcoxon statistic is defined as $S = \sum_{i=1}^m R_i$, where R_i denotes the rang of the i -th observation, $i = 1, \dots, m$ in the combined sample $R(y_l) = \#\{z_j \in Z : D(z_j, Z) \leq D(y_l, Z)\}, l = 1, \dots, m$.

The distribution of S is symmetric about $E(S) = 1/2m(m+n+1)$, its variance is $D^2(S) = 1/12 mn(m+n+1)$.

References

Jureckova J, Kalina J (2012). Nonparametric multivariate rank tests and their unbiasedness. *Bernoulli*, 18(1), 229-251. Li J, Liu RY (2004). New nonparametric tests of multivariate locations and scales using data depth. *Statistical Science*, 19(4), 686-696. Liu RY, Singh K (1995). A quality index based on data depth and multivariate rank tests. *Journal of American Statistical Association*, 88, 252-260. Zuo Y, He X (2006). On the limiting distributions of multivariate depth-based rank sum statistics and related tests. *The Annals of Statistics*, 34, 2879-2896.

Examples

```
x = mvrnorm(100, c(0,0), diag(2))
y = mvrnorm(100, c(0,0), diag(2)*1.4)
mWilcoxonTest(x,y)
mWilcoxonTest(x,y, method = "LP")

#EXAMPLE 2
data(under5.mort)
data(under5.mort)
data(maesles.imm)
data2011=na.omit(cbind(under5.mort[,22],inf.mort[,22],maesles.imm[,22]))
data1990=na.omit(cbind(under5.mort[,1],inf.mort[,1],maesles.imm[,1]))
mWilcoxonTest(data2011,data1990)
```

plot

Method for plotting DepthCurve and DDPlot object.

Description

Plot Depth curve

Usage

```
plot(x, y, ...)
```

S4 method for signature 'DDPlot,ANY'

```
plot(x)
```

```
## S4 method for signature 'DepthCurve,ANY'
plot(x)

## S4 method for signature 'DepthCurveList,ANY'
plot(x)
```

Arguments

x	object that inherits from DepthCurve class (ScaleCurve or AsymmetryCurve), or DDPlot class.
y	not supported.
...	not supported.

Examples

```
x = mvrnorm(n = 100, mu = c(0,0), Sigma = 3*diag(2))
sc = scaleCurve(x)
plot(sc)
```

plot,BinnDepth2d,ANY-method
2d Binning plot

Description

Binning 2d

Usage

```
## S4 method for signature 'BinnDepth2d,ANY'
plot(x, ..., alpha = 0.1, bg_col = "red",
      add_mid = TRUE)
```

Arguments

x	object of class BinnDepth2d
...	graphical parameters passed to plot
alpha	alpha value for rgb function
bg_col	background color
add_mid	logical. If TRUE centers of binns will be marked.

See Also

[depth](#)

Examples

```
tmp = binningDepth2D(x = mvrnorm(100,rep(0,2),diag(2)))
plot(tmp)
```

plot,DepthDensity,ANY-method

Plot function for DepthDensity

Description

Plot function for DepthDensity

Usage

```
## S4 method for signature 'DepthDensity,ANY'
plot(x, type = "depth", ...)
```

Arguments

x	object of class DepthDensity
type	type of density that will be plotted. 'depth' is a depth scaled density, and 'raw' is density without scaling.
...	graphical arguments.

plot,DepthMBD,ANY-method

Functional boxplot based on Modified Band Depth

Description

Functional boxplot based on Modified Band Depth

Usage

```
## S4 method for signature 'DepthMBD,ANY'
plot(x, band_lim = c(0, 0.5), colors = NULL,
     add_lines = TRUE, lwd = 1, alpha = 0.5, ...)
```

Arguments

x	object of class DepthMBD
band_lim	limits for bands
colors	color set
add_lines	Logical. If TRUE, all lines from data will be plotted.
lwd	lines width
alpha	transparency for band area.
...	other arguments passed to matplot

Examples

```
x = depthMBD(matrix(rnorm(200), ncol = 10))
plot(x)
```

```
plot,LSDepthContour,ANY-method
```

Plot Location-Scale depth contours.

Description

Plot Location-Scale depth contours.

Usage

```
## S4 method for signature 'LSDepthContour,ANY'
plot(x, cont = NULL, ratio = 1,
     mu_min = NULL, mu_max = NULL, col = NULL, border = NULL, ...)
```

Arguments

x	object of class LSDepthContour
cont	plotted contours. Default NULL means that all contours stored in x will be plotted
ratio	ratio
mu_min	mu_min
mu_max	mu_max
col	vectors with area colors passed to polygon function
border	vector with colors for borders
...	other parameters passed to polygon

Examples

```
smp = rf(100,5,10)
x = lsdSampleDepthContours(smp)
plot(x, col = paste0("grey", col = rev(seq(10,40,10))))
```

```
RobReg-class
```

```
RobReg
```

Description

Virtual class for robust regression methods from depthproc package

Slots

coef coefficients of fitted model

runifsphere	<i>Random number generation from unit sphere.</i>
-------------	---

Description

This function generates random numbers from p-dimensional unit sphere.

Usage

```
runifsphere(n, p = 2)
```

Arguments

n	number of random samples.
p	dimension of the unit sphere.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
x = runifsphere(n=100)
plot(x)
```

scaleCurve	<i>Scale curve</i>
------------	--------------------

Description

Draws a scale curve: measure of dispersion.

Usage

```
scaleCurve(x, y = NULL, alpha = seq(0, 1, 0.01), method = "Projection",
  name = "X", name_y = "Y", title = "Scale Curve", ...)
```

Arguments

x	Multivariate data as a matrix.
y	Additional matrix with multivariate data.
alpha	Vector with values of central area to be used in computation.
method	Character string which determines the depth function used. method can be "Projection" (the default), "Mahalanobis", "Euclidean" or "Tukey". For details see depth .
name	Name of matrix X used in legend.
name_y	Name of matrix Y used in legend.
title	title of the plot.
...	Any additional parameters for function depth.

Details

For sample depth function $D(x, Z^n)$, $x \in R^d$, $d \geq 2$, $Z^n = \{z_1, \dots, z_n\} \subset R^d$, $D_\alpha(Z^n)$ denoting α -central region, we can define the scale curve

$$SC(\alpha) = (\alpha, vol(D_\alpha(Z^n)) \subset R^2, for \alpha \in [0, 1]$$

The scale curve is a two-dimensional method of describing the dispersion of random vector around the depth induced median.

Function scalecurve for determining the volumes of the convex hull containing points from alpha central regions, uses function convhulln from geometry package.

The minimal dimension of data in X or Y is 2.

ggplot2 package is used to draw a plot.

Value

Returns the volume of the convex hull containing subsequent central points of X.

Author(s)

Daniel Kosiorowski, Mateusz Bocian, Anna Wegrzynkiewicz and Zygmunt Zawadzki from Cracow University of Economics.

References

Liu, R.Y., Parelius, J.M. and Singh, K. (1999), Multivariate analysis by data depth: Descriptive statistics, graphics and inference (with discussion), *Ann. Statist.*, **27**, 783–858.

Chaudhuri, P. (1996), On a Geometric Notion of Quantiles for Multivariate Data, *Journal of the American Statistical Association*, 862–872.

Dyckerhoff, R. (2004), Data Depths Satisfying the Projection Property, *Allgemeines Statistisches Archiv.*, **88**, 163–190.

See Also

[depthContour](#) and [depthPersp](#) for depth graphics.

Examples

```

require(mvtnorm)
x = mvrnorm(n = 100, mu = c(0,0), Sigma = 3*diag(2))
y = rmvt(n = 100, sigma = diag(2), df = 2)
scaleCurve(x, y, method = "Projection", plot = TRUE)
## comparing of two scale curves - normal distribution and mixture of normal distributions
x = mvrnorm(100, c(0,0), diag(2))
y = mvrnorm(80, c(0,0), diag(2))
z = mvrnorm(20, c(5,5), diag(2))
scaleCurve(x, rbind(y,z), method = "Projection", name = "N", name_y = "Mixture of N")

```

ScaleCurve-class

ScaleCurve and ScaleCurveList

Description

ScaleCurve is a class that stores results of [scaleCurve](#) function.

Details

ScaleCurve inherits behaviour from numeric vector, so raw values of ScaleCurve can be accessed via `as.numeric(...)`.

The mechanism of creating plots with multiple curves is shown in [DepthCurve-class](#) (same mechanism is applied for [AsymmetryCurve](#)).

Examples

```

require(mvtnorm)
x = mvrnorm(n = 100, mu = c(0,0), Sigma = 2*diag(2))
y = rmvt(n = 100, sigma = diag(2), df = 4)
s1 = scaleCurve(x, method = "Projection", plot = FALSE)
s2 = scaleCurve(y, method = "Projection", plot = FALSE, name = "Set2")

sc_list = s1 %+% s2 # Add one curve to another

plot(sc_list) # Draw plot with two curves

z = mvrnorm(n = 100, mu = c(0,0), Sigma = 1*diag(2))
s3 = scaleCurve(z, method = "Projection", plot = FALSE)
plot(sc_list%+%s3) # Add third curve and draw a plot

```

 trimProjReg2d

trimProjReg2d

Description

Computes projection trimmed regression in 2 dimensions.

Usage

```
trimProjReg2d(x, y, alpha = 0.1)
```

Arguments

x	Independent variable
y	Dependent variable
alpha	Percentage of trimmed observations

Author(s)

Zygmunt Zawadzki from Cracow University of Economics.

Examples

```
#EXAMPLE 1
data(pension)
plot(pension)
abline(lm(Reserves~Income,data = pension), lty = 3, lwd = 2) #lm
abline(trimProjReg2d(pension[,1],pension[,2]), lwd = 2) #trimprojreg2d
legend("bottomright", c("OLS","TrimLS"), lty = 1:2)

#EXAMPLE 2
data(under5.mort)
data(under5.mort)
data(maesles.imm)

data2011=na.omit(cbind(under5.mort[,22],inf.mort[,22],maesles.imm[, 22]))
x<-data2011[,3]
y<-data2011[,2]
plot(x,y,cex=1.2, ylab="infant mortality rate per 1000 live birth",
xlab="against masles immunized #
percentage", main='Projection Depth Trimmed vs. LS regressions')
abline(lm(x~y,data = pension), lwd = 2, col='black') #lm
abline(trimProjReg2d(x,y), lwd = 2,col='red') #trimmed reg
legend("bottomleft",c("LS","TrimReg"),fill=c("black","red"),cex=1.4,bty="n")
```

TrimReg2d-class	<i>TrimReg2d</i>
-----------------	------------------

Description

Class for robust regression methods from depthproc package

under5.mort	<i>Children under 5 months mortality rate per 1,000 live births</i>
-------------	---

Description

Children under 5 months mortality rate per 1,000 live births

Usage

```
data(under5.mort)
```

Format

A data frame with 654 rows and 4 variables

Source

<http://mdgs.un.org/unsd/mdg/Data.aspx>

USLABOUR	<i>US Labour dataset</i>
----------	--------------------------

Description

US Labour dataset

Usage

```
data(USLABOUR)
```

Format

A data frame with 654 rows and 4 variables

Source

U.S.Department of Labor - Bureau of Labour Statistics FRED

%+%

Adds plots

Description

Adds plots

Usage

```
e1 %+% e2
```

```
## S4 method for signature 'DepthCurveList,DepthCurve'  
e1 %+% e2
```

```
## S4 method for signature 'DepthCurve,DepthCurveList'  
e1 %+% e2
```

```
## S4 method for signature 'DepthCurve,DepthCurve'  
e1 %+% e2
```

Arguments

e1	object
e2	object

Details

See [DepthCurve-class](#) for description.

Index

- *Topic **asymmetry**
 - asymmetryCurve, 4
- *Topic **contour**
 - depthContour, 17
- *Topic **curve**
 - scaleCurve, 39
- *Topic **datasets**
 - inf.mort, 29
 - maesles.imm, 33
 - under5.mort, 43
 - USLABOUR, 43
- *Topic **depth**
 - asymmetryCurve, 4
 - binningDepth2D, 7
 - CovLP, 9
 - depth, 15
 - depthContour, 17
 - depthEuclid, 20
 - depthLP, 23
 - depthMah, 24
 - depthProjection, 27
 - depthTukey, 28
 - plot,BinnDepth2d,ANY-method, 36
 - scaleCurve, 39
- *Topic **function**
 - asymmetryCurve, 4
 - binningDepth2D, 7
 - CovLP, 9
 - depth, 15
 - depthEuclid, 20
 - depthLP, 23
 - depthMah, 24
 - depthProjection, 27
 - depthTukey, 28
 - plot,BinnDepth2d,ANY-method, 36
 - scaleCurve, 39
- *Topic **multivariate**
 - asymmetryCurve, 4
 - binningDepth2D, 7
 - CovLP, 9
 - depth, 15
 - depthEuclid, 20
 - depthLP, 23
 - depthMah, 24
 - depthProjection, 27
 - depthTukey, 28
 - plot,BinnDepth2d,ANY-method, 36
 - scaleCurve, 39
- *Topic **nonparametric**
 - asymmetryCurve, 4
 - binningDepth2D, 7
 - CovLP, 9
 - depth, 15
 - depthEuclid, 20
 - depthLP, 23
 - depthMah, 24
 - depthProjection, 27
 - depthTukey, 28
 - plot,BinnDepth2d,ANY-method, 36
 - scaleCurve, 39
- *Topic **robust**
 - asymmetryCurve, 4
 - binningDepth2D, 7
 - CovLP, 9
 - depth, 15
 - plot,BinnDepth2d,ANY-method, 36
 - scaleCurve, 39
- *Topic **scale**
 - scaleCurve, 39
- %+%, DepthCurve, DepthCurve-method (%+%), 44
- %+%, DepthCurve, DepthCurveList-method (%+%), 44
- %+%, DepthCurveList, DepthCurve-method (%+%), 44
- %+%, 44
- abline, RobReg-method, 3
- as.matrix, 4

- as.matrix,DepthCurveList (as.matrix), 4
- as.matrix,DepthCurveList-method (as.matrix), 4
- asymmetryCurve, 4, 6
- AsymmetryCurve-class, 6

- BinnDepth2d-class, 6
- binningDepth2D, 7

- CovDepthWeighted-class, 9
- CovLP, 9

- ddMvnorm (ddmvnorm), 10
- ddmvnorm, 10
- ddPlot, 11, 12
- DDPlot-class, 13
- deepReg2d, 13
- DeepReg2d-class, 14
- depth, 4, 5, 8, 15, 15, 26, 36, 40
- Depth-class, 13, 16, 18
- depthContour, 10, 16, 17, 40
- DepthCurve-class, 6, 18, 19, 41
- DepthCurveList-class, 19
- depthDensity, 19, 20
- DepthDensity-class, 20
- DepthEuclid (Depth-class), 16
- depthEuclid, 15, 20
- DepthLocal (Depth-class), 16
- depthLocal, 21
- DepthLP (Depth-class), 16
- depthLP, 23
- depthMah, 24
- DepthMahalanobis (Depth-class), 16
- depthMBD, 25
- depthMedian, 25
- depthMedian,data.frame (depthMedian), 25
- depthMedian,data.frame-method (depthMedian), 25
- depthMedian,Depth (depthMedian), 25
- depthMedian,Depth-method (depthMedian), 25
- depthMedian,matrix (depthMedian), 25
- depthMedian,matrix-method (depthMedian), 25
- depthPersp, 10, 16, 18, 26, 40
- DepthProjection (Depth-class), 16
- depthProjection, 27
- DepthTukey (Depth-class), 16
- depthTukey, 28

- getPlot, 29
- getPlot,AsymmetryCurveList (getPlot), 29
- getPlot,AsymmetryCurveList-method (getPlot), 29
- getPlot,DDPlot (getPlot), 29
- getPlot,DDPlot-method (getPlot), 29
- getPlot,ScaleCurveList (getPlot), 29
- getPlot,ScaleCurveList-method (getPlot), 29
- grapes-plus-grapes-methods,DepthCurve,DepthCurve (%+%), 44
- grapes-plus-grapes-methods,DepthCurve,DepthCurveList (%+%), 44
- grapes-plus-grapes-methods,DepthCurveList,DepthCurve (%+%), 44

- inf.mort, 29

- lsdAddContour, 30
- lsdAddContour,LSDepthContour (lsdAddContour), 30
- lsdAddContour,LSDepthContour-method (lsdAddContour), 30
- LSDepth-class, 30
- LSDepthContour-class, 31
- lsdGetContour, 31
- lsdGetContour,LSDepthContour (lsdGetContour), 31
- lsdGetContour,LSDepthContour-method (lsdGetContour), 31
- lsdSampleDepthContours, 32
- lsdSampleMaxDepth, 33

- maesles.imm, 33
- mWilcoxonTest, 34

- plot, 35
- plot,BinnDepth2d,ANY-method, 36
- plot,DDPlot (plot), 35
- plot,DDPlot,ANY-method (plot), 35
- plot,DepthCurve (plot), 35
- plot,DepthCurve,ANY-method (plot), 35
- plot,DepthCurveList (plot), 35
- plot,DepthCurveList,ANY-method (plot), 35
- plot,DepthDensity,ANY-method, 37
- plot,DepthMBD,ANY-method, 37
- plot,LSDepthContour,ANY-method, 38

- RobReg-class, 38

runifsphere, [39](#)

scaleCurve, [5](#), [39](#), [41](#)

ScaleCurve-class, [41](#)

trimProjReg2d, [42](#)

TrimReg2d-class, [43](#)

under5.mort, [43](#)

USLABOUR, [43](#)