

Package ‘RSAGA’

July 2, 2014

Type Package

Title SAGA Geoprocessing and Terrain Analysis in R

Version 0.93-6

Date 2013-07-23

Author Alexander Brenning

Maintainer Alexander Brenning <brenning@uwaterloo.ca>

Description RSAGA provides access to geocomputing and terrain analysis functions of SAGA from within R by running the command line version of SAGA. RSAGA furthermore provides several R functions for handling ASCII grids, including a flexible framework for applying local functions (including predict methods of fitted models) and focal functions to multiple grids. SAGA GIS is available under GPLv2 / LGPLv2 licence from <http://sourceforge.net/projects/saga-gis/>.

License GPL-2

SystemRequirements SAGA GIS (2.0.4 - 2.1.0)

Depends gstat, shapefiles, plyr

LazyLoad yes

Collate 'gridtools.R' 'RSAGA-core.R' 'RSAGA-modules.R' 'RSAGA-utils.R' 'RSAGA-package.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2013-07-24 09:02:34

R topics documented:

RSAGA-package	3
centervalue	4
create.variable.name	4
focal.function	5
grid.predict	8
grid.to.xyz	10
match.arg.ext	11
multi.focal.function	13
pick.from.shapefile	17
read.ascii.grid	21
relative.position	24
resid.median	25
rsaga.add.grid.values.to.points	26
rsaga.close.gaps	27
rsaga.contour	28
rsaga.copy.sgrd	29
rsaga.default.path	29
rsaga.env	30
rsaga.esri.to.sgrd	33
rsaga.esri.wrapper	34
rsaga.fill.sinks	35
rsaga.filter.gauss	37
rsaga.filter.simple	38
rsaga.geoprocessor	39
rsaga.get.modules	42
rsaga.get.usage	44
rsaga.get.version	45
rsaga.grid.calculus	46
rsaga.grid.to.points	48
rsaga.hillshade	49
rsaga.html.help	50
rsaga.import.gdal	51
rsaga.insolation	55
rsaga.inverse.distance	57
rsaga.lib.prefix	58
rsaga.local.morphometry	59
rsaga.parallel.processing	62
rsaga.pisr	64
rsaga.sgrd.to.esri	67
rsaga.sink.removal	68
rsaga.sink.route	69
rsaga.solar.radiation	70
rsaga.target	72
rsaga.wetness.index	73
set.file.extension	75
wind.shelter	76

Description

RSAGA provides direct access to SAGA GIS functions including, for example, a comprehensive set of terrain analysis algorithms for calculating local morphometric properties (slope, aspect, curvature), hydrographic characteristics (size, height, and aspect of catchment areas), and other process-related terrain attributes (potential incoming solar radiation, topographic wetness index, and more). In addition, (R)SAGA provides functions for importing and exporting different grid file formats, and tools for preprocessing grids, e.g. closing gaps or filling sinks.

Details

RSAGA adds a framework for creating custom-defined focal functions, e.g. specialized filter and terrain attributes such as the topographic wind shelter index, within R. This framework can be used to apply predict methods of fitted statistical models to stacks of grids representing predictor variables. Furthermore, functions are provided for conveniently picking values at point locations from a grid using kriging or nearest neighbour interpolation.

RSAGA requires SAGA GIS (versions 2.0.4 - 2.1.0 are currently supported) and its user-contributed modules to be available on your computer. These can be downloaded under GPL from <http://sourceforge.net/projects/saga-gis/>. Please check the help page for `rsaga.env` to make sure that RSAGA can find your local installation of SAGA. You may need to 'tell' RSAGA where to find SAGA GIS.

Thanks to Olaf Conrad, Andre Ringeler and all the other SAGA GIS developers and contributors of this excellent geocomputing tool! Thanks to Rainer Hurling, Johan van de Wauw, Massimo Di Stefano and others for helping to adapt SAGA to and test it on unix and Max OSX.

Author(s)

Alexander Brenning

References

Brenning, A., 2008. Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In J. Boehner, T. Blaschke and L. Montanarella (eds.), *SAGA - Seconds Out (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie, vol. 19)*, p. 23-32.

centervalue *Pick Center Value from Matrix*

Description

Pick the value in the center of a square matrix. Auxiliary function to be used by functions called by [focal.function](#).

Usage

```
centervalue(x)
```

Arguments

x a square matrix

Details

See for example the code of [resid.median](#).

See Also

[focal.function](#), [resid.median](#)

Examples

```
( m <- matrix( round(runif(9,1,10)), ncol=3 ) )
centervalue(m)
```

create.variable.name *Convert file name to variable name*

Description

Convert a file name into a variable name

Usage

```
create.variable.name(filename, prefix = NULL,
  fsep = .Platform$file.sep)
```

Arguments

filename character string
 prefix character string: optional prefix to be added
 fsep character used to separate path components

Examples

```
## Not run:
create.variable.name("C:/my-path/my-file-name.Rd",prefix="res")

## End(Not run)
```

focal.function

Local and Focal Grid Functions

Description

focal.function cuts out square or circular moving windows from a grid (matrix) and applies a user-defined matrix function to calculate e.g. a terrain attribute or filter the grid. The function is suitable for large grid files as it can process them row by row. local.function represents the special case of a moving window of radius 1. Users can define their own functions operating on moving windows, or use simple functions such as median to define filters.

Usage

```
focal.function(in.grid, in.factor.grid, out.grid.prefix,
  path = NULL, in.path = path, out.path = path, fun,
  varnames, radius = 0, is.pixel.radius = TRUE,
  na.strings = "NA", valid.range = c(-Inf, Inf),
  nodata.values = c(), out.nodata.value,
  search.mode = c("circle", "square"), digits = 4,
  hdr.digits = 10, dec = ".", quiet = TRUE, nlines = Inf,
  mw.to.vector = FALSE, mw.na.rm = FALSE, ...)
```

```
gapply(in.grid, fun, varnames, mw.to.vector = TRUE,
  mw.na.rm = TRUE, ...)
```

```
local.function(...)
```

Arguments

in.grid	file name of input ASCII grid, relative to in.path
in.factor.grid	optional file name giving a gridded categorical variables defining zones; zone boundaries are used as breaklines for the moving window (see Details)
out.grid.prefix	character string (optional), defining a file name prefix to be used for the output file names; a dash (-) will separate the prefix and the varnames
path	path in which to look for in.grid and write output grid files; see also in.path and out.path, which overwrite path if they are specified
in.path	path in which to look for in.grid (defaults to path)
out.path	path in which to write output grid files; defaults to path

fun	a function, or name of a function, to be applied on the moving window; see Details
varnames	character vector specifying the names of the variable(s) returned by fun; if missing, focal.function will try to determine the varnames from fun itself, or from a call to fun if this is a function (see Details)
radius	numeric value specifying the (circular or square) radius of the moving window; see is.pixel.radius and search.mode; note that all data within distance \leq radius will be included in the moving window, not $<$ radius.
is.pixel.radius	logical: if TRUE (default), the radius will be interpreted as a (possibly non-integer) number of pixels; if FALSE, it is interpreted as a radius measured in the grid (map) units.
valid.range	numeric vector of length 2, specifying minimum and maximum valid values read from input file; all values $<$ valid.range[1] or $>$ valid.range[1] will be converted to NA.
nodata.values	numeric vector: any values from the input grid file that should be converted to NA, in addition to the nodata value specified in the grid header
out.nodata.value	numeric: value used for storing NAs in the output file(s); if missing, use the same nodata value as specified in the header of the input grid file
na.strings	passed on to scan
search.mode	character, either "circle" (default) for a circular search window, or "square" for a squared one.
digits	numeric, specifying the number of digits to be used for output grid file.
hdr.digits	numeric, specifying the number of digits to be used for the header of the output grid file (default: 10; see write.ascii.grid.header).
dec	character, specifying the decimal mark to be used for input and output.
quiet	If TRUE, gives some output ("*") after every 10th line of the grid file and when the job is done.
nlines	Number of lines to be processed; useful for testing purposes.
mw.to.vector	logical: Should the content of the moving window be coerced (from a matrix) to a vector?
mw.na.rm	logical: Should NAs be removed from moving window prior to passing the data to fun? Only applicable when mw.to.vector=TRUE.
...	Arguments to be passed to fun; local.function: arguments to be passed to focal.function.

Details

focal.function passes a square matrix of size $2 \times \text{radius} + 1$ to the function fun if mw.to.vector=FALSE (default), or a vector of length $\leq (2 \times \text{radius} + 1)^2$ if mw.to.vector=TRUE. This matrix or vector will contain the content of the moving window, which may possibly contain NAs even if the in.grid has no nodata values, e.g. due to edge effects. If search.mode="circle", values more than radius units (pixels or grid units, depending on is.pixel.radius) away from the center pixel / matrix

entry will be set to NA. In addition, `valid.range`, `nodata.values`, and the `nodata` values specified in the `in.grid` are checked to assign further NAs to pixels in the moving window. Finally, if `in.factor.grid` specifies zones, all pixels in the moving window that belong to a different zone than the center pixel are set to NA, or, in other words, zone boundaries are used as breaklines.

The function `fun` should return a single numeric value or a numeric vector. As an example, the function `resid.minmedmax` returns the minimum, median and maximum of the difference between the values in the moving window and the value in the center grid cell. In addition to the (first) argument receiving the moving window data, `fun` may have additional arguments; the `...` argument of `focal.function` is passed on to `fun`. `resid.quantile` is a function that uses this feature.

Optionally, `fun` should support the following feature: If no argument is passed to it, then it should return a character vector giving variable names to be used for naming the output grids. The call `resid.minmedmax()`, for example, returns `c("rmin", "rmed", "rmax")`; this vector must have the same length as the numeric vector returned when moving window data is passed to the function. This feature is only used if no `varnames` argument is provided. Note that the result is currently being `abbreviated` to a length of 6 characters.

Input and output file names are built according to the following schemes:

Input: [`<in.path>/`]`<in.grid>`

Zones: [`<in.path>/`]`<in.factor.grid>` (if specified)

Output: [`<out.path>/`]`<out.grid.prefix>-``<varnames>.asc`

For the input files, `.asc` is used as the default file extension, if it is not specified by the user.

Value

`focal.function` and `local.function` return the character vector of output file names.

Note

These functions are not very efficient ways of calculating e.g. (focal) terrain attributes compared to for example the SAGA modules, but the idea is that you can easily specify your own functions without starting to mess around with C code. For example try implementing a median filter as a SAGA module... or just use the code shown in the example!

Author(s)

Alexander Brenning

References

Brenning, A. (2008): Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In: J. Boehner, T. Blaschke, L. Montanarella (eds.), *SAGA - Seconds Out (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie*, 19), 23-32. <http://www.environment.uwaterloo.ca/u/brenning/Brenning-2008-RSAGA.pdf>

See Also

[multi.focal.function](#), [multi.local.function](#), [resid.median](#), [resid.minmedmax](#), [relative.position](#), [resid.quantile](#), [resid.quartiles](#), [relative.rank](#), [wind.shelter](#), [create.variable.name](#)

Examples

```
## Not run:
# A simple median filter applied to dem.asc:
gapply("dem", "median", radius=3)
# Same:
#focal.function("dem", fun="median", radius=3, mw.to.vector=TRUE, mw.na.rm=TRUE)
# See how the filter has changed the elevation data:
d1 = as.vector(read.ascii.grid("dem")$data)
d2 = as.vector(read.ascii.grid("median")$data)
hist(d1-d2, br=50)

## End(Not run)
# Wind shelter index used by Plattner et al. (2004):
## Not run:
ctrl = wind.shelter.prep(6, -pi/4, pi/12, 10)
focal.function("dem", fun=wind.shelter, control=ctrl,
              radius=6, search.mode="circle")

## End(Not run)
# Or how about this, if "aspect" is local terrain exposure:
## Not run:
gapply("aspect", "cos") # how "northerly-exposed" is a pixel?
gapply("aspect", "sin") # how "easterly-exposed" is a pixel?
# Same result, but faster:
focal.function("aspect", fun=function(x) c(cos(x), sin(x)), varnames=c("cos", "sin"))

## End(Not run)
```

grid.predict

Helper function for applying predict methods to stacks of grids.

Description

This function can be used to apply the predict method of hopefully any fitted predictive model pixel by pixel to a stack of grids representing the explanatory variables. It is intended to be called primarily by [multi.local.function](#) or [multi.focal.function](#).

Usage

```
grid.predict(fit, predfun, trafo, control.predict,
            predict.column, trace = 0, location, ...)
```

Arguments

fit	a model object for which prediction is desired
predfun	optional prediction function; if missing, the fit's predict method is called. In some cases it may be convenient to define a wrapper function for the predict method that may be passed as predfun argument.

trafo	an optional function(x) that takes a data.frame x and returns a data.frame with the same number of rows; this is intended to perform transformations on the input variables, e.g. derive a log-transformed variable from the raw input read from the grids, or more complex variables such as the NDVI etc.; the data.frame resulting from a call to trafo (if provided) is passed to predfun
control.predict	an optional list of arguments to be passed on to predfun; this may be e.g. type="response" to obtain probability prediction maps from a logistic regression model
predict.column	optional character string: Some predict methods (e.g. predict.lda) return a data.frame with several columns, e.g. one column per class in a classification problem. predict.column is used to pick the one that is of interest
trace	integer >=0: positive values give more (=2) or less (=1) information on predictor variables and predictions
location	optional location data received from multi.focal.function; is added to the newdata object that is passed on to predfun.
...	these arguments are provided by the calling function, usually multi.local.function or multi.focal.function . They contain the explanatory (predictor) variables required by the fit model.

Details

grid.predict is a simple wrapper function. First it binds the arguments in ... together in a data.frame with the raw predictor variables that have been read from their grids by the caller, [multi.local.function](#) (or [multi.focal.function](#)). Then it calls the optional trafo function to transform or combine predictor variables (e.g. perform log transformations, ratioing, arithmetic operations such as calculating the NDVI). Finally the predfun (or, typically, the default [predict](#) method of fit) is called, handing over the fit, the predictor data.frame, and the optional control.predict arguments.

Value

grid.predict returns the result of the call to predfun or the default [predict](#) method.

Note

Though grid.predict can in principle deal with predict methods returning factor variables, its usual caller [multi.local.function](#) / [multi.focal.function](#) cannot; classification models should be dealt with by setting a type="prob" (for rpart) or type="response" (for logistic regression and logistic additive model) argument, for example (see second Example below).

Author(s)

Alexander Brenning

References

Brenning, A. (2008): Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In: J. Boehner, T. Blaschke, L. Montanarella (eds.), SAGA - Seconds Out (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie, 19), 23-32. <http://www.environment.uwaterloo.ca/u/brenning/Brenning-2008-RSAGA.pdf>

See Also

[focal.function](#), [multi.local.function](#), [multi.focal.function](#)

Examples

```
## Not run:
# Assume that d is a data.frame with point observations
# of a numerical response variable y and predictor variables
# a, b, and c.
# Fit a generalized additive model to y,a,b,c.
# We want to model b and c as nonlinear terms:
require(gam)
fit <- gam(y ~ a + s(b) + s(c), data = d)
multi.local.function(in.grids = c("a", "b", "c"),
  out.varnames = "pred",
  fun = grid.predict, fit = fit )
# Note that the 'grid.predict' uses by default the
# predict method of 'fit'.
# Model predictions are written to a file named pred.asc

## End(Not run)

## Not run:
# A fake example of a logistic additive model:
require(gam)
fit <- gam(cl ~ a + s(b) + s(c), data = d, family = binomial)
multi.local.function(in.grids = c("a", "b", "c"),
  out.varnames = "pred",
  fun = grid.predict, fit = fit,
  control.predict = list(type = "response") )
# 'control.predict' is passed on to 'grid.predict', which
# dumps its contents into the arguments for 'fit''s
# 'predict' method.
# Model predictions are written to a file named pred.asc

## End(Not run)
```

Description

Convert a grid matrix to a (x,y,z) data.frame.

Usage

```
grid.to.xyz(data, header, varname = "z",
            colnames = c("x", "y", varname))
```

Arguments

data	grid data: either a grid data matrix, or a list with components <code>data</code> (a matrix with the grid data) and <code>header</code> (the grid header information); see read.ascii.grid for details
header	optional list giving grid header information; see read.ascii.grid for details
varname	character: name to be assigned to the column with the z values in the output data.frame
colnames	names to be given to the columns corresponding to the x and y coordinates and the grid variable in the output data.frame

Value

a data.frame with three columns (names are specified in the `colnames` argument) giving the x and y coordinates and the attribute values at the locations given by the grid data.

See Also

[read.ascii.grid](#), [pick.from.ascii.grid](#)

Examples

```
## Not run:
d = read.ascii.grid("dem")
xyz = grid.to.xyz(d, varname="elevation")
str(xyz)

## End(Not run)
```

Description

`match.arg.ext` matches `arg` against a set of candidate values as specified by `choices`; it extends [match.arg](#) by allowing `arg` to be a numeric identifier of the choices.

Usage

```
match.arg.ext(arg, choices, base = 1, several.ok = FALSE,  
             numeric = FALSE, ignore.case = FALSE)
```

Arguments

arg	a character string or numeric value
choices	a character vector of candidate values
base	numeric value, specifying the numeric index assigned to the first element of choices
several.ok	logical specifying if arg should be allowed to have more than one element
numeric	logical specifying if the function should return the numerical index (counting from base) of the matched argument, or, by default, its name
ignore.case	logical specifying if the matching should be case sensitive

Details

When choices are missing, they are obtained from a default setting for the formal argument arg of the function from which `match.arg.ext` was called.

Matching is done using `pmatch` (indirectly through a call to `match.arg`, so arg may be abbreviated.

If arg is numeric, it may take values between base and `length(choices)+base-1`. `base=1` will give standard 1-based R indices, `base=0` will give indices counted from zero as used to identify SAGA modules in library RSAGA.

Value

If `numeric` is false and arg is a character string, the function returns the unabbreviated version of the unique partial match of arg if there is one; otherwise, an error is signalled if `several.ok` is false, as per default. When `several.ok` is true and there is more than one match, all unabbreviated versions of matches are returned.

If `numeric` is false but arg is numeric, `match.arg.ext` returns name of the match corresponding to this index, counting from base; i.e. `arg=base` corresponds to `choices[1]`.

If `numeric` is true, the function returns the numeric index(es) of the partial match of arg, counted from base to `length(choices)+base-1`. If arg is already numeric, the function only checks whether it falls into the valid range from arg to `length(choices)+base-1` and returns arg.

Author(s)

Alexander Brenning

See Also

[match.arg](#), [pmatch](#)

Examples

```
# Based on example from 'match.arg':
require(stats)
center <- function(x, type = c("mean", "median", "trimmed")) {
  type <- match.arg.ext(type,base=0)
  switch(type,
    mean = mean(x),
    median = median(x),
    trimmed = mean(x, trim = .1))
}
x <- rcauchy(10)
center(x, "t")      # Works
center(x, 2)       # Same, for base=0
center(x, "med")   # Works
center(x, 1)       # Same, for base=0
try(center(x, "m")) # Error
```

multi.focal.function *Local and Focal Grid Function with Multiple Grids as Inputs*

Description

multi.focal.function cuts out square or circular moving windows from a stack of grids (matrices) and applies a user-defined matrix function that takes multiple arguments to this data. multi.local.function is a more efficiently coded special case of moving windows of size 0, i.e. functions applied to individual grid cells of a stack of grids. This is especially useful for applying predict methods of statistical models to a stack of grids containing the explanatory variables (see Examples and [grid.predict](#)). The function is suitable for large grid files as it can process them row by row; but it may be slow because one call to the focal function is generated for each grid cell.

Usage

```
multi.focal.function(in.grids, in.grid.prefix,
  in.factor.grid, out.grid.prefix, path = NULL,
  in.path = path, out.path = path, fun, in.varnames,
  out.varnames, radius = 0, is.pixel.radius = TRUE,
  na.strings = "NA", valid.ranges, nodata.values = c(),
  out.nodata.value, search.mode = c("circle", "square"),
  digits = 4, hdr.digits = 10, dec = ".", quiet = TRUE,
  nlines = Inf, mw.to.vector = FALSE, mw.na.rm = FALSE,
  pass.location = FALSE, ...)
```

```
multi.local.function(in.grids, in.grid.prefix,
  out.grid.prefix, path = NULL, in.path = path,
  out.path = path, fun, in.varnames, out.varnames,
  na.strings = "NA", valid.ranges, nodata.values = c(),
  out.nodata.value, digits = 4, hdr.digits = 10,
  dec = ".", quiet = TRUE, nlines = Inf,
  na.action = na.exclude, pass.location = FALSE, ...)
```

Arguments

<code>in.grids</code>	character vector: file names of input ASCII grids, relative to <code>in.path</code> ; <code>in.grid.prefix</code> will be used as a prefix to the file name if specified; default file extension: <code>.asc</code>
<code>in.factor.grid</code>	optional file name giving a gridded categorical variables defining zones; zone boundaries are used as breaklines for the moving window (see Details)
<code>in.grid.prefix</code>	character string (optional), defining a file name prefix to be used for the input file names; a dash (-) will separate the prefix and the <code>in.varnames</code>
<code>out.grid.prefix</code>	character string (optional), defining a file name prefix to be used for the output file names; a dash (-) will separate the prefix and the <code>out.varnames</code>
<code>path</code>	path in which to look for <code>in.grids</code> and write output grid files; see also <code>in.path</code> and <code>out.path</code> , which overwrite <code>path</code> if they are specified
<code>in.path</code>	path in which to look for <code>in.grids</code> (defaults to <code>path</code>)
<code>out.path</code>	path in which to write output grid files; defaults to <code>path</code>
<code>fun</code>	a function, or name of a function, to be applied on the moving window; see Details; <code>fun</code> is expected to accept named arguments with the names given by <code>in.varnames</code> ; <code>grid.predict</code> is a wrapper function that can be used for applying a model's <code>predict</code> method to a stack of grids; see Details. In <code>multi.local.function</code> , <code>fun</code> must be able to process arguments that are vectors of equal length (e.g., a vector of 50 slope angles, another vector of 50 elevation values, etc.).
<code>in.varnames</code>	character vector: names of the variables corresponding to the <code>in.grids</code> ; if missing, same as <code>in.grids</code> ; if specified, must have the same length and order as <code>in.grids</code>
<code>out.varnames</code>	character vector specifying the name(s) of the variable(s) returned by <code>fun</code> ; if missing, <code>multi.focal.function</code> will try to determine the <code>varnames</code> from <code>fun</code> itself, or from a call to <code>fun</code> if this is a function (see Details)
<code>radius</code>	numeric value specifying the (circular or square) radius of the moving window; see <code>is.pixel.radius</code> and <code>search.mode</code> ; note that all data within distance $\leq \text{radius}$ will be included in the moving window, not $< \text{radius}$.
<code>is.pixel.radius</code>	logical: if TRUE (default), the <code>radius</code> will be interpreted as a (possibly non-integer) number of pixels; if FALSE, it is interpreted as a radius measured in the grid (map) units.
<code>valid.ranges</code>	optional list of length <code>length(in.grids)</code> with numeric vector of length 2, specifying minimum and maximum valid values read from input file; all values <code><valid.ranges[[i]][1]</code> or <code>>valid.ranges[[i]][1]</code> will be converted to NA.
<code>nodata.values</code>	numeric vector: any values from the input grid file that should be converted to NA, in addition to the <code>nodata</code> value specified in the grid header
<code>out.nodata.value</code>	numeric: value used for storing NAs in the output file(s); if missing, use the same <code>nodata</code> value as specified in the header of the input grid file
<code>search.mode</code>	character, either "circle" (default) for a circular search window, or "square" for a squared one.

<code>digits</code>	numeric, specifying the number of digits to be used for output grid file.
<code>hdr.digits</code>	numeric, specifying the number of digits to be used for the header of the output grid file (default: 10; see write.ascii.grid.header).
<code>dec</code>	character, specifying the decimal mark to be used for input and output.
<code>quiet</code>	If FALSE, gives some output ("*") after every 10th line of the grid file and when the job is done.
<code>nlines</code>	Number of lines to be processed; useful for testing purposes.
<code>na.action</code>	function: determines if/how NA values are omitted from the stack of input variables; use na.exclude (default) or na.pass if fun can handle NA values correctly
<code>mw.to.vector</code>	logical: Should the content of the moving window be coerced (from a matrix) to a vector?
<code>mw.na.rm</code>	logical: Should NAs be removed from moving window prior to passing the data to fun? Only applicable when <code>mw.to.vector=TRUE</code> .
<code>pass.location</code>	logical: Should the x,y coordinates of grid points (center of grid cells) be passed to fun? If TRUE, two additional arguments named arguments x and y are passed to fun; NOTE: This currently only works for <code>radius=0</code> , otherwise a warning is produced and <code>pass.location</code> is reset to FALSE.
<code>na.strings</code>	passed on to scan
<code>...</code>	Arguments to be passed to fun; <code>local.function</code> : arguments to be passed to <code>focal.function</code> .

Details

`multi.local.function` is probably most useful for applying the `predict` method of a fitted model to a grids representing the predictor variables. An example is given below and in more detail in Brenning (2008) (who used `multi.focal.function` for the same purpose); see also [grid.predict](#).

`multi.local.function` is essentially the same as `multi.focal.function` for `radius=0`, but coded MUCH more efficiently. (The relevant code will eventually migrate into `multi.focal.function` as well, but requires further testing.) Applying a GAM to the data set of Brenning (2008) takes about 1/100th the time with `multi.local.function` compared to `multi.focal.function`.

`multi.focal.function` extends [focal.function](#) by allowing multiple input grids to be passed to the focal function `fun` operating on moving windows. It passes square matrices of size $2*\text{radius}+1$ to the function `fun` if `mw.to.vector=FALSE` (default), or a vector of length $\leq (2*\text{radius}+1)^2$ if `mw.to.vector=TRUE`; one such matrix or vector per input grid will be passed to `fun` as an argument whose name is specified by `in.varnames`.

These matrices or vectors will contain the content of the moving window, which may possibly contain NAs even if the `in.grid` has no `nodata` values, e.g. due to edge effects. If `search.mode="circle"`, values more than `radius` units (pixels or grid units, depending on `is.pixel.radius`) away from the center pixel / matrix entry will be set to NA. In addition, `valid.range`, `nodata.values`, and the `nodata` values specified in the `in.grid` are checked to assign further NAs to pixels in the moving window. Finally, if `in.factor.grid` specifies zones, all pixels in the moving window that belong to a different zone than the center pixel are set to NA, or, in other words, zone boundaries are used as breaklines.

The function `fun` should return a single numeric value or a numeric vector, such as a regression result or a vector of class probabilities returned by a soft classifier. In addition to the named arguments receiving the moving window data, `fun` may have additional arguments; the `...` argument of `focal.function` is passed on to `fun`. `grid.predict` uses this feature.

Optionally, `fun` should support the following feature: If no argument is passed to it, then it should return a character vector giving variable names to be used for naming the output grids.

For the input files, `.asc` is used as the default file extension, if it is not specified by the user.

See `focal.function` for details.

Value

`multi.focal.function` returns the character vector of output file names.

Note

`multi.focal.function` can do all the things `focal.function` can do.

Author(s)

Alexander Brenning

References

Brenning, A. (2008): Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In: J. Boehner, T. Blaschke, L. Montanarella (eds.), *SAGA - Seconds Out* (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie, 19), 23-32. <http://www.environment.uwaterloo.ca/u/brenning/Brenning-2008-RSAGA.pdf>

See Also

`focal.function`, `grid.predict`

Examples

```
## Not run:
# Assume that d is a data.frame with point observations
# of a numerical response variable y and predictor variables
# a, b, and c.
# Fit a generalized additive model to y,a,b,c.
# We want to model b and c as nonlinear terms:
require(gam)
fit <- gam(y ~ a + s(b) + s(c), data = d)
multi.local.function(in.grids = c("a", "b", "c"),
  out.varnames = "pred",
  fun = grid.predict, fit = fit )
# Note that the 'grid.predict' uses by default the
# predict method of 'fit'.
# Model predictions are written to a file named pred.asc
```



```
## End(Not run)

## Not run:
# A fake example of a logistic additive model:
require(gam)
fit <- gam(cl ~ a + s(b) + s(c), data = d, family = binomial)
multi.local.function(in.grids = c("a", "b", "c"),
  out.varnames = "pred",
  fun = grid.predict, fit = fit,
  control.predict = list(type = "response") )
# 'control.predict' is passed on to 'grid.predict', which
# dumps its contents into the arguments for 'fit's
# 'predict' method.
# Model predictions are written to a file named pred.asc

## End(Not run)
```

pick.from.shapefile *Pick Variable from Spatial Dataset*

Description

These functions pick (i.e. interpolate without worrying too much about theory) values of a spatial variables from a data stored in a data.frame, a point shapefile, or an ASCII or SAGA grid, using nearest neighbor or kriging interpolation. `pick.from.points` and `[internal.]pick.from.ascii.grid` are the core functions that are called by the different wrappers.

Usage

```
pick.from.shapefile(data, shapefile, X.name = "x",
  Y.name = "y", ...)
```

```
pick.from.points(data, src, pick,
  method = c("nearest.neighbour", "krige"),
  set.na = FALSE, radius = 200, nmin = 0, nmax = 100,
  sill = 1, range = radius, nugget = 0,
  model = vgm(sill - nugget, "Sph", range = range, nugget = nugget),
  log = rep(FALSE, length(pick)), X.name = "x",
  Y.name = "y", cbind = TRUE)
```

```
internal.pick.from.ascii.grid(data, file, path = NULL,
  varname = NULL, prefix = NULL,
  method = c("nearest.neighbour", "krige"),
  nodata.values = c(-9999, -99999), at.once,
  quiet = TRUE, X.name = "x", Y.name = "y", nlines = Inf,
  cbind = TRUE, range, radius, na.strings = "NA", ...)
```

```
pick.from.ascii.grids(data, file, path = NULL,
```

```
varname = NULL, prefix = NULL, cbind = TRUE,
quiet = TRUE, ...)
```

```
pick.from.ascii.grid(data, file, path = NULL,
varname = NULL, prefix = NULL,
method = c("nearest.neighbour", "krige"), cbind = TRUE,
parallel = FALSE, nsplit, quiet = TRUE, ...)
```

```
pick.from.saga.grid(data, filename, path, varname,
prec = 7, show.output.on.console = FALSE,
env = rsaga.env(), ...)
```

Arguments

<code>data</code>	data.frame giving the coordinates (in columns specified by <code>X.name</code> , <code>Y.name</code>) of point locations at which to interpolate the specified variables or grid values
<code>src</code>	data.frame
<code>shapefile</code>	point shapefile
<code>pick</code>	variables to be picked (interpolated) from <code>src</code> ; if missing, use all available variables, except those specified by <code>X.name</code> and <code>Y.name</code>
<code>method</code>	interpolation method to be used; uses a partial match to the alternatives <code>"nearest.neighbor"</code> (currently the default) and <code>"krige"</code>
<code>set.na</code>	logical: if a column with a name specified in <code>pick</code> already exists in <code>data</code> , how should it be dealt with? <code>set.na=FALSE</code> (default) only overwrites existing data if the interpolator yields a non-NA result; <code>set.na=TRUE</code> passes NA values returned by the interpolator on to the results data.frame
<code>radius</code>	numeric value specifying the radius of the local neighborhood to be used for interpolation; defaults to 200 map units (presumably meters), or, in the functions for grid files, $2.5 * \text{cellsize}$.
<code>nmin</code>	numeric, for <code>method="krige"</code> only: see krige function in package gstat
<code>nmax</code>	numeric, for <code>method="krige"</code> only: see krige function in package gstat
<code>sill</code>	numeric, for <code>method="krige"</code> only: the overall sill parameter to be used for the variogram
<code>range</code>	numeric, for <code>method="krige"</code> only: the variogram range
<code>nugget</code>	numeric, for <code>method="krige"</code> only: the nugget effect
<code>model</code>	for <code>method="krige"</code> only: the variogram model to be used for interpolation; defaults to a spherical variogram with parameters specified by the <code>range</code> , <code>sill</code> , and <code>nugget</code> arguments; see vgm in package gstat for details
<code>log</code>	logical vector, specifying for each variable in <code>pick</code> if interpolation should take place on the logarithmic scale (default: <code>FALSE</code>)
<code>X.name</code>	name of the variable containing the x coordinates
<code>Y.name</code>	name of the variable containing the y coordinates
<code>cbind</code>	logical: should the new variables be added to the input data.frame (<code>cbind=TRUE</code> , the default), or should they be returned as a separate vector or data.frame? <code>cbind=FALSE</code>

file	file name (relative to path, default file extension .asc) of an ASCII grid from which to pick a variable, or an open connection to such a file
path	optional path to file
varname	character string: a variable name for the variable interpolated from grid file in pick.from.*.grid; if missing, variable name will be determined from filename by a call to create.variable.name
prefix	an optional prefix to be added to the varname
nodata.values	numeric vector specifying grid values that should be converted to NA; in addition to the values specified here, the nodata value given in the input grid's header will be used
at.once	logical: should the grid be read as a whole or line by line? at.once=FALSE is useful for processing large grids that do not fit into memory; the argument is currently by default FALSE for method="nearest.neighbour", and it currently MUST be TRUE for all other methods (in these cases, TRUE is the default value); piecewise processing with at.once=FALSE is always faster than processing the whole grid at.once
quiet	logical: provide information on the progress of grid processing on screen? (only relevant if at.once=FALSE and method="nearest.neighbour")
nlines	numeric: stop after processing nlines lines of the input grid; useful for testing purposes
filename	character: name of a SAGA grid file, default extension .sgrd
prec	numeric, specifying the number of digits to be used in converting a SAGA grid to an ASCII grid in pick.from.saga.grid
na.strings	passed on to scan
env	list: RSAGA geoprocessing environment created by rsaga.env
show.output.on.console	a logical (default: FALSE), indicates whether to capture the output of the command and show it on the R console (see system , rsaga.geoprocessor).
nsplit	split the data.frame data in nsplit disjoint subsets in order to increase efficiency by using ddply in package plyr . The default seems to perform well in many situations.
parallel	logical (default: FALSE): enable parallel processing; requires additional packages such as doSNOW or doMC . See example below and ddply
...	arguments to be passed to pick.from.points, and to internal.pick.from.ascii.grid in the case of pick.from.ascii.grid

Details

pick.from.points interpolates the variables defined by pick in the src data.frame to the locations provided by the data data.frame. Only nearest neighbour and ordinary kriging interpolation are currently available. This function is intended for 'data-rich' situations in which not much thought needs to be put into a geostatistical analysis of the spatial structure of a variable. In particular, this function is supposed to provide a simple, 'quick-and-dirty' interface for situations where the src data points are very densely distributed compared to the data locations.

`pick.from.shapefile` is a front-end of `pick.from.points` for point shapefiles.

`pick.from.ascii.grid` retrieves data values from an ASCII raster file using either nearest neighbour or ordinary kriging interpolation. The latter may not be possible for large raster data sets because the entire grid needs to be read into an R matrix. Split-apply-combine strategies are used to improve efficiency and allow for parallelization.

The optional parallelization of `pick.from.ascii.grid` computation requires the use of a *parallel backend* package such as **doSNOW** or **doMC**, and the parallel backend needs to be registered before calling this function with `parallel=TRUE`. The example section provides an example using **doSNOW** on Windows. I have seen 25-40 reduction in processing time by parallelization in some examples that I ran on a dual core Windows computer.

`pick.from.ascii.grids` performs multiple `pick.from.ascii.grid` calls. File path and prefix arguments may be specific to each file (i.e. each may be a character vector), but all interpolation settings will be the same for each file, limiting the flexibility a bit compared to individual `pick.from.ascii.grid` calls by the user. `pick.from.ascii.grids` currently processes the files sequentially (i.e. parallelization is limited to the `pick.from.ascii.grid` calls within this function).

`pick.from.saga.grid` is the equivalent to `pick.from.ascii.grid` for SAGA grid files. It simply converts the SAGA grid file to a (temporary) ASCII raster file and applies `pick.from.ascii.grid`.

`internal.pick.from.ascii.grid` is an internal 'workhorse' function that by itself would be very inefficient for large data sets data. This function is called by `pick.from.ascii.grid`, which uses a split-apply-combine strategy implemented in the **plyr** package.

Value

If `cbind=TRUE`, columns with the new, interpolated variables are added to the input `data.frame` data.

If `cbind=FALSE`, a `data.frame` only containing the new variables is returned (possibly coerced to a vector if only one variable is processed).

Note

`method="krige"` requires the **gstat** package.

`pick.from.shapefile` requires the **shapefiles** package.

The nearest neighbour interpolation currently randomly breaks ties if `pick.from.points` is used, and in a deterministic fashion (rounding towards greater grid indices, i.e. toward south and east) in the grid functions.

Author(s)

Alexander Brenning

References

Brenning, A. (2008): Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In: J. Boehner, T. Blaschke, L. Montanarella (eds.), *SAGA - Seconds Out (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie, 19)*, 23-32. <http://www.environment.uwaterloo.ca/u/brenning/Brenning-2008-RSAGA.pdf>

See Also

[grid.to.xyz](#), [krige](#), [read.ascii.grid](#), [write.ascii.grid](#)

Examples

```
## Not run:
# assume that 'dem' is an ASCII grid and d a data.frame with variables x and y
pick.from.ascii.grid(d, "dem")
# parallel processing on Windows using the doSNOW package:
require(doSNOW)
registerDoSNOW(cl <- makeCluster(2, type = "SOCK")) # DualCore processor
pick.from.ascii.grid(d, "dem", parallel = TRUE)
# produces two (ignorable) warning messages when using doSNOW
# typically 25-40% faster than the above on my DualCore notebook
stopCluster(cl)

## End(Not run)

## Not run:
# use the meuse data for some tests:
require(gstat)
data(meuse)
data(meuse.grid)
meuse.nn = pick.from.points(data=meuse.grid, src=meuse,
  pick=c("cadmium", "copper", "elev"), method="nearest.neighbour")
meuse.kr = pick.from.points(data=meuse.grid, src=meuse,
  pick=c("cadmium", "copper", "elev"), method="krige", radius=100)
# it does make a difference:
plot(meuse.kr$cadmium, meuse.nn$cadmium)
plot(meuse.kr$copper, meuse.nn$copper)
plot(meuse.kr$elev, meuse.nn$elev)

## End(Not run)
```

read.ascii.grid

Read/write ASCII, SAGA and Rd Grid Files

Description

These functions provide simple interfaces for reading and writing grids from/to ASCII grids and Rd files. Grids are stored as matrices, their headers in lists.

Usage

```
read.ascii.grid(file, return.header = TRUE, print = 0,
  nodata.values = c(), at.once = TRUE, na.strings = "NA")

read.ascii.grid.header(file, ...)
```

```
write.ascii.grid.header(file, header, georef, dec = ".",
  hdr.digits = 10)
```

```
read.Rd.grid(fname, return.header = TRUE)
```

```
write.ascii.grid(data, file, header = NULL,
  write.header = TRUE, digits, hdr.digits = 10,
  dec = ".", georef = "corner")
```

```
write.Rd.grid(data, file, header = NULL,
  write.header = TRUE, compress = TRUE)
```

```
read.sgrd(fname, return.header = TRUE, print = 0,
  nodata.values = c(), at.once = TRUE, prec = 7, ...)
```

```
write.sgrd(data, file, header = NULL, prec = 7,
  hdr.prec = 10, georef = "corner", ...)
```

Arguments

<code>file</code>	file name of an ASCII grid (extension defaults to <code>.asc</code> if not specified), or a connection open for reading or writing, as required
<code>fname</code>	file name of a grid stored as an R (<code>.Rd</code>) file; extension defaults to <code>.Rd</code>
<code>return.header</code>	logical: should the grid header be returned (default), or just the grid data matrix? In the former case, <code>read.ascii.grid</code> returns a list with two components named <code>data</code> and <code>header</code> .
<code>print</code>	numeric, specifying how detailed the output reporting the progress should be (currently 0 to 2, 0 being minimum output).
<code>nodata.values</code>	optional numeric vector specifying nodata values to be used in addition to the nodata value specified in the grid header; nodata values are converted to NA.
<code>at.once</code>	logical: if TRUE, read the whole grid with one scan command; if FALSE, read it row by row using <code>scan</code> with option <code>nlines=1</code> .
<code>data</code>	grid data: a data matrix, or a list with components <code>data</code> (the grid data matrix) and <code>header</code> (the grid header information).
<code>header</code>	optional list argument specifying the grid header information as returned by the <code>read.ascii.grid</code> or <code>read.ascii.grid.header</code> function; see Details
<code>write.header</code>	logical: should the header be written with the grid data? (default: TRUE)
<code>digits</code>	numeric: if not missing, write data rounded to this many decimal places
<code>hdr.digits</code>	numeric: see <code>hdr.prec</code>
<code>hdr.prec</code>	numeric: write (non-integer) header data with this many decimal places; a value of 9 or higher is recommended for compatibility with SAGA GIS (default: 10)
<code>dec</code>	character (default: <code>"."</code>): decimal mark used in input or output file
<code>georef</code>	character: specifies whether the output grid should be georeferenced by the "center" or "corner" of its lower left grid cell; defaults to "corner".

compress	logical: should the .Rd file written by write.Rd.file be compressed? (default: TRUE)
prec	integer: number of digits of temporary ASCII grid used for importing or exporting a SAGA grid
na.strings	passed on to scan .
...	read.sgrd, write.sgrd: additional arguments to be passed to rsaga.geoprocessor

Value

The read.* functions return either a list with components data (the grid data matrix) and header (the grid header information, see below), if return.header=TRUE, or otherwise just the grid data matrix return.header=FALSE.

The grid data matrix is a numeric matrix whose first column corresponds to the first (i.e. northern-most) row of the grid. Columns run from left = West to right = East.

The header information returned by the read.ascii.grid[.header] functions (if return.header=TRUE) is a list with the following components:

ncols	Number of grid columns.
nrows	Number of grid rows.
xllcorner	x coordinate of the corner of the lower left grid cell.
yllcorner	y coordinate of the corner of the lower left grid cell.
cellsize	Single numeric value specifying the size of a grid cell or pixel in both x and y direction.
nodata_value	Single numeric value being interpreted as NA (typically -9999).
xllcenter	x coordinate of the center of the lower left grid cell
yllcenter	y coordinate of the center of the lower left grid cell

Note: The order of the components, especially of ?llcorner and ?llcenter, may change, depending on the order in which they appear in the grid header and on the georeferencing method (center or corner) used for the grid. The ?llcorner and ?llcenter attributes differ only by cellsize/2.

Note

read.sgrd and write.sgrd import/export grids indirectly by creating temporary ASCII grid files (this explains why write.sgrd has prec and hdr.prec arguments). Consider using readGDAL and writeGDAL in package rgdal instead, which are likely more efficient but may require coercion of your gridded data to/from a Spatial...DataFrame-class.

The read.Rd.grid and write.Rd.grid functions use the load and save commands to store a grid. The variable name used is data, which is either a numeric matrix or a list with components data (the grid data matrix) and header (the grid header information).

Author(s)

Alexander Brenning

See Also

readGDAL and [writeGDAL](#) in package `rgdal`, and `readAsciiGrid` and [writeAsciiGrid](#) in package `mapproj`

relative.position *Relative Topographic Position*

Description

`relative.position` and `relative.rank` are used with [focal.function](#) to determine the relative value of a grid cell compared to its surroundings, either on a metric scale or based on ranks.

Usage

```
relative.position(x)

relative.rank(x, ties.method = "average")
```

Arguments

<code>x</code>	a square matrix with the grid data from the moving window, possibly containing NA values
<code>ties.method</code>	see rank

Value

If `x` is provided, a numeric value in the interval [0,1] is returned.

If `x` is missing, a character vector of same length giving suggested variable (or file) names, here "relpos" and "relrank", respectively. See [focal.function](#) for details.

See Also

[focal.function](#), [rank](#), [centvalue](#)

Examples

```
m = matrix( round(runif(9,1,10)), ncol=3 )
print(m)
relative.position(m)
relative.rank(m)
## Not run:
focal.function("dem", fun=relative.rank, radius=5)
focal.function("dem", fun=relative.position, radius=5)
relrank = as.vector(read.ascii.grid("relrank")$data)
relpos = as.vector(read.ascii.grid("relpos")$data)
plot(relpos, relrank, pch=".")
cor(relpos, relrank, use="complete.obs", method="pearson")

## End(Not run)
```

`resid.median`*Residual Median and Quantile Filters for Grids*

Description

These functions use the median and other quantiles to describe the difference between a grid value and its neighborhood. They are designed for use with [focal.function](#).

Usage`resid.median(x)``resid.minmedmax(x)``resid.quantile(x, probs)``resid.quartiles(x)`**Arguments**

<code>x</code>	a square matrix with the grid data from the moving window, possibly containing NA values
<code>probs</code>	numeric vector of probabilities in [0,1] to be passed to quantile

Details

These functions are designed for being called by [focal.function](#), which repeatedly passes the contents of a square or circular moving window to these functions.

The `resid.median` function rests the value of the central grid cell from the median of the whole moving window. Thus, in terms of topography, a positive residual median indicates that this grid cell stands out compared to its surroundings. `resid.quantile` gives more flexibility in designing such residual attributes.

Value

If `x` is provided, a numeric vector of length 1 (`resid.median`), 3 (`resid.minmedmax` and `resid.quartiles`), or `length(probs)` (`resid.quantile`).

If `x` is missing, a character vector of same length giving suggested variable (or file) names, such as "rmed". See [focal.function](#) for details.

See Also

[focal.function](#), [quantile](#), [median](#), [centervalue](#)

```
rsaga.add.grid.values.to.points
```

Add Grid Values to Point Shapefile

Description

Pick values from SAGA grids and attach them as a new variables to a point shapefile.

Usage

```
rsaga.add.grid.values.to.points(in.shapefile, in.grids,  
  out.shapefile,  
  method = c("nearest.neighbour", "bilinear", "idw", "bicubic.spline", "b.spline"),  
  ...)
```

Arguments

<code>in.grids</code>	Input: character vector with names of (one or more) SAGA GIS grid files to be converted into a point shapefile.
<code>in.shapefile</code>	Input point shapefile (default extension: .shp).
<code>out.shapefile</code>	Output point shapefile (default extension: .shp).
<code>method</code>	interpolation method to be used; choices: nearest neighbour interpolation (default), bilinear interpolation, inverse distance weighting, bicubic spline interpolation, B-splines.
<code>...</code>	Optional arguments to be passed to rsaga.geoprocessor , including the env RSAGA geoprocessing environment.

Details

Retrieves information from the selected grids at the positions of the points of the selected points layer and adds it to the resulting layer.

Note

This function uses module `Add Grid Values to Points` in SAGA GIS library `shapes_grid`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA modules)

See Also

[pick.from.points](#), [pick.from.ascii.grid](#), [pick.from.saga.grid](#), [rsaga.grid.to.points](#)

rsaga.close.gaps *SAGA Modules Close Gaps and Close One Cell Gaps*

Description

Close (Interpolate) Gaps

Usage

```
rsaga.close.gaps(in.dem, out.dem, threshold = 0.1, ...)
```

```
rsaga.close.one.cell.gaps(in.dem, out.dem, ...)
```

Arguments

in.dem	input: digital elevation model (DEM) as SAGA grid file (default file extension: .sgrd)
out.dem	output: DEM grid file without no-data values (gaps). Existing files will be overwritten!
threshold	tension threshold for adjusting the interpolator (default: 0.1)
...	optional arguments to be passed to rsaga.geoprocessor , including the env RSAGA geoprocessing environment

Details

`rsaga.close.one.cell.gaps` only fill gaps whose neighbor grid cells have non-missing data.

In `rsaga.close.gaps`, larger tension thresholds can be used to reduce overshoots and undershoots in the surfaces used to fill (interpolate) the gaps.

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

This function uses modules 7 (`rsaga.close.gaps` and 6 `rsaga.close.one.cell.gaps` from the SAGA library `grid_tools`.

SAGA GIS 2.0.5+ has a new additional module `Close Gaps with Spline`, which can be accessed using [rsaga.geoprocessor](#) (currently no R wrapper available). See `rsaga.get.usage("grid_tools", "Close Gaps with Spline")` or in version 2.1.0+ call `rsaga.html.help("grid_tools", "Close Gaps with Spline")`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# using SAGA grids:
rsaga.close.gaps("rawdem.sgrd","dem.sgrd")
# using ASCII grids:
rsaga.esri.wrapper(rsaga.close.gaps,in.dem="rawdem",out.dem="dem")

## End(Not run)
```

rsaga.contour

Contour Lines from a Grid

Description

Creates a contour lines shapefile from a grid file in SAGA grid format.

Usage

```
rsaga.contour(in.grid, out.shapefile, zstep, zmin, zmax,
...)
```

Arguments

<code>in.grid</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: .sgrd)
<code>out.shapefile</code>	output: contour line shapefile. Existing files will be overwritten!
<code>zstep, zmin, zmax</code>	lower limit, upper limit, and equidistance of contour lines
<code>...</code>	arguments to be passed to rsaga.geoprocessor

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.geoprocessor](#)

rsaga.copy.sgrd	<i>Create a copy of a SAGA grid file</i>
-----------------	--

Description

Creates a copy of a SAGA grid file, optionally overwriting the target file if it already exists. Intended mainly for internal use by RSAGA functions, currently in particular [rsaga.inverse.distance](#).

Usage

```
rsaga.copy.sgrd(in.grid, out.grid, overwrite = TRUE,
               env = rsaga.env())
```

Arguments

in.grid	name of a SAGA GIS grid file; file extension can be omitted
out.grid	name of a SAGA GIS grid file; file extension can be omitted
overwrite	logical; if TRUE (the default), overwrite out.grid if it already exists; if FALSE and the out.grid already exists, copying will be skipped without causing an error.
env	a SAGA geoprocessing environment as created by rsaga.env

Note

SAGA grid files consist of three (or more) individual files with file extensions .mgrd, .sgrd and .sdat. The files with these three file extensions are copied, any additional files (e.g. a history file) are ignored.

rsaga.default.path	<i>Determine SAGA GIS default paths</i>
--------------------	---

Description

Internal functions that determine OS-specific default paths in which SAGA GIS binaries and modules might be located.

Usage

```
rsaga.default.path(sysname = Sys.info()["sysname"])

rsaga.default.modules.path(sysname = Sys.info()["sysname"],
                           saga.path = rsaga.default.path(sysname))
```

Arguments

sysname	character: name of the operating system, determined by default by Sys.info : e.g., "Windows", "Linux", "Darwin" (for Mac OSX), or "FreeBSD"
saga.path	character: path with SAGA GIS binaries, as determined (e.g.) by <code>rsaga.default.path</code>

Details

These functions are used internally by [rsaga.env](#). On Windows systems, the guess made by `rsaga.default.path` is "C:/Progra~1/SAGA-GIS", and for the modules, it is the "modules" subfolder of the path with the binaries.

On non-Windows systems, `rsaga.default.path` submits a which `saga_cmd` call to the operating system to find the binaries, usually in `/usr/local/bin` or in `/usr/bin`. To find the modules, `rsaga.default.modules.path` first checks if a `SAGA_MLB` environment variable exists. If not, it will replace the `/bin` part (if present) with `/lib/saga` or otherwise it just guesses that it's `/usr/local/lib/saga`.

See Also

[rsaga.env](#)

rsaga.env

Set up the RSAGA Geoprocessing Environment

Description

`rsaga.env` creates a list with system-dependent information on SAGA path, module path and data (working) directory. This kind of a list is required by most RSAGA geoprocessing functions and is referred to as the 'RSAGA geoprocessing environment.'

Usage

```
rsaga.env(workspace = ".",
  cmd = ifelse(Sys.info()["sysname"] == "Windows", "saga_cmd.exe", "saga_cmd"),
  path, modules, version, cores, parallel = FALSE,
  check.libpath = TRUE, check.SAGA = TRUE,
  check.PATH = Sys.info()["sysname"] == "Windows",
  check.os.default = TRUE,
  os.default.path = rsaga.default.path(), lib.prefix)
```

Arguments

workspace	path of the working directory for SAGA; defaults to the current directory ("").
cmd	name of the SAGA command line program; defaults to <code>saga_cmd.exe</code> , its name under Windows
path	path in which to find <code>cmd</code> ; <code>rsaga.env</code> is usually able to find SAGA on your system if it is installed; see Details.

modules	path in which to find SAGA libraries; see Details
version	optional character string: SAGA GIS (API) version, e.g. "2.0.8"; if missing, a call to <code>rsaga.get.version</code> is used to determine version number of SAGA API
cores	optional numeric argument, or NA: number of cores used by SAGA GIS; supported only by SAGA GIS 2.1.0 (and higher), ignored otherwise (with a warning). Multicore-enabled SAGA GIS modules such as the one used by <code>rsaga.pisr</code> seem to run in multicore mode by default when this argument is not specified, therefore cores should only be specified to use a smaller number of cores than available on a machine.
parallel	optional logical argument (default: FALSE): if TRUE, run RSAGA functions that are capable of parallel processing in parallel mode; note that this is completely independent of the behaviour of SAGA GIS (which can be controlled using the cores argument); currently only some RSAGA functions support parallel processing (e.g., <code>pick.from.ascii.grid</code> or <code>rsaga.get.modules</code>). <code>parallel=TRUE</code> requires that a parallel backend such as <code>doSNOW</code> or <code>doMC</code> is available and has been started prior to calling any parallelized RSAGA function, otherwise warnings may be generated
check.libpath	if TRUE (default), first look for SAGA GIS in the folder where the RSAGA package is installed
check.SAGA	if TRUE (default), next check the path given by the environment variable SAGA, if it exists
check.PATH	if TRUE (default on Windows), next look for SAGA GIS in all the paths in the PATH environment variable; defaults to FALSE on non-Windows OS
check.os.default	if TRUE, look for SAGA GIS in the folder specified by <code>os.default.path</code> .
os.default.path	on Windows, C:/Program Files/SAGA-GIS; on unix, an attempt is made to locate <code>saga_cmd</code>
lib.prefix	character string: a possible (platform-dependent) prefix for SAGA GIS library names; if missing (recommended), a call to <code>rsaga.lib.prefix</code> tries to determine the correct prefix, e.g. "" on Windows systems and "lib" on non-Windows systems with SAGA GIS pre-2.1.0. Try specifying "" or "lib" manually if this causes problems, and contact the package maintainer if the detection mechanism fails on your system (indicate your <code>Sys.info()["sysname"]</code> and your SAGA GIS version)

Details

IMPORTANT: Unlike R functions such as `options`, which changes and saves settings somewhere in a global variable, `rsaga.env` does not actually 'save' any settings, it simply creates a list that can (and has to) be passed to other `rsaga.*` functions. See example below.

I strongly recommend to install SAGA GIS in "C:/Program Files/SAGA-GIS" in the case of English-language Windows platforms (the equivalent non-English installation folder in the case of non-English Windows versions seems to work as well). If this is the only SAGA GIS copy on the computer and you do *not* define a Windows environment variable SAGA, then RSAGA should normally be able to find your SAGA GIS installation in this folder.

rsaga.env tries to collect information on the (R)SAGA environment. If path is missing, rsaga.env first looks for an environment variable SAGA; if this is undefined, it checks the current working directory, then the paths given in the PATH environment variable, and finally the function's guess is "C:/Program~1/SAGA-GIS" (or "/usr/local/bin" on non-Windows systems).

The default modules folder on Windows systems is the modules subfolder of the SAGA binaries' folder. The SAGA_MLB environment variable is *not* checked by rsaga.env.

On Unix (and Mac OS X) systems, the default modules folder is as specified in the SAGA_MLB environment variable. If this is empty / not set, then the following backup path is used. If path ends with "/bin", then "/bin" is changed to "/lib/saga" and taken as the modules path; otherwise, /usr/local/lib/saga is used.

Value

A list with components workspace, cmd, path, modules, version, cores and parallel with values as passed to rsaga.env or default values as described in the Details section.

Note

Note that the default workspace is ".", not getwd(); i.e. the default SAGA workspace folder is not fixed, it changes each time you change the R working directory using setwd.

Author(s)

Alexander Brenning

See Also

[rsaga.get.version](#)

Examples

```
## Not run:
# Check the default RSAGA environment on your computer:
myenv <- rsaga.env()
myenv
# SAGA data in C:/sagadata, binaries in C:/SAGA-GIS, modules in C:/SAGA-GIS/modules:
myenv <- rsaga.env(workspace="C:/sagadata", path="C:/SAGA-GIS")
# Unix: SAGA in /usr/bin (instead of the default /usr/local/bin),
# and modules in /usr/lib/saga:
# myenv <- rsaga.env(path="/usr/bin")
# Use the 'myenv' environment for SAGA geoprocessing:
rsaga.hillshade("dem", "hillshade", env=myenv)
# ...creates (or overwrites) grid "C:/sagadata/hillshade.sgrd"
# derived from digital elevation model "C:/sagadata/dem.sgrd"

# Same calculation with different SAGA version:
# (I keep several versions in SAGA-GIS_2.0.x folders:)
myenv05 = rsaga.env(path = "C:/Program~1/SAGA-GIS_2.0.5")
rsaga.hillshade("dem", "hillshade205", env=myenv05)

## End(Not run)
```

rsaga.esri.to.sgrd *Convert ESRI ASCII/binary grids to SAGA grids*

Description

rsaga.esri.to.sgrd converts grid files from ESRI's ASCII (.asc) and binary (.flt) format to SAGA's (version 2) grid format (.sgrd).

Usage

```
rsaga.esri.to.sgrd(in.grids,
  out.sgrds = set.file.extension(in.grids, ".sgrd"),
  in.path, ...)
```

Arguments

in.grids	character vector of ESRI ASCII/binary grid files (default file extension: .asc); files should be located in folder in.path
out.sgrds	character vector of output SAGA grid files; defaults to in.grids with file extension being replaced by .sgrd, which is also the default extension if file names without extension are specified; files will be placed in the current SAGA workspace (default: <code>rsaga.env()</code> \$workspace, or <code>env\$workspace</code> if an env argument is provided)
in.path	folder with in.grids
...	optional arguments to be passed to <code>rsaga.geoprocessor</code> , including the env RSAGA geoprocessing environment

Value

The type of object returned depends on the intern argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

If multiple in.grids are converted, the result will be a vector of numerical error codes of the same length, or the combination of the console outputs with `c()`.

Note

This function uses module 1 from the SAGA library `io_grid`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.esri.wrapper](#) for an efficient way of applying RSAGA to ESRI ASCII/binary grids; [rsaga.env](#)

rsaga.esri.wrapper *Use RSAGA functions for ESRI grids*

Description

This wrapper converts input grid files provided in ESRI binary (.flt) or ASCII (.asc) formats to SAGA's (version 2) grid format, calls the RSAGA geoprocessing function, and converts the output grids back to the ESRI grid format. Conversion can also be limited to either input or output grids.

Usage

```
rsaga.esri.wrapper(fun, in.esri = TRUE, out.esri = TRUE,
  env = rsaga.env(), esri.workspace = env$workspace,
  format = "ascii", georef = "corner", prec = 5,
  esri.extension, condensed.res = TRUE, clean.up = TRUE,
  intern = TRUE, ...)
```

Arguments

fun	function: one of the RSAGA geoprocessing functions, such as rsaga.close.gaps or rsaga.hillshade etc.
in.esri	logical: are input grids provided as ESRI grids (in.esri=TRUE) or as SAGA grids?
out.esri	logical: should output grids be converted to ESRI grids?
env	RSAGA environment as returned by rsaga.env
esri.workspace	directory for the input and output ESRI ASCII/binary grids
format	output file format, either "ascii" (default; equivalent: format=1) for ASCII grids or "binary" (equivalent: 0) for binary ESRI grids (.flt).
georef	character: "corner" (equivalent numeric code: 0) or "center" (default; equivalent: 1). Determines whether the georeference will be related to the center or corner of its extreme lower left grid cell.
prec	number of digits when writing floating point values to ASCII grid files (only relevant if out.esri=TRUE).
esri.extension	extension for input/output ESRI grids: defaults to .asc for format="ascii", and to .flt for format="binary"
condensed.res	logical: return only results of the RSAGA geoprocessing function fun (condensed.res=TRUE), or include the results of the import and export operations, i.e. the calls to rsaga.esri.to.sgrd and rsaga.sgrd.to.esri ? (see Value)
clean.up	logical: delete intermediate SAGA grid files?
intern	intern argument to be passed to rsaga.geoprocessor ; see Value
...	additional arguments for fun; NOTE: ESRI ASCII/float raster file names should NOT include the file extension (.asc, .flt); the file extension is defined by the esri.extension and format arguments!

Details

ESRI ASCII/float raster file names should NOT include the file extension (.asc, .flt); the file extension is defined by the `esri.extension` and `format` arguments!

Value

The object returned depends on the `condensed.res` arguments and the `intern` argument passed to the [rsaga.geoprocessor](#).

If `condensed.res=TRUE` and `intern=FALSE`, a single numerical error code (0: success) is returned. If `condensed.res=TRUE` and `intern=TRUE` (default), a character vector with the module's console output is returned (invisibly).

If `condensed.res=FALSE` the result is a list with components `in.res`, `geoproc.res` and `out.res`. Each of these components is either an error code (for `intern=FALSE`) or (for `intern=TRUE`) a character vector with the console output of the input ([rsaga.esri.to.sgrd](#)), the geoprocessing (`fun`), and the output conversion ([rsaga.sgrd.to.esri](#)) step, respectively. For `in.esri=FALSE` or `out.esri=FALSE`, the corresponding component is `NULL`.

Note

Note that the intermediate grids as well as the output grids may overwrite existing files with the same file names without prompting the user. See example below.

See Also

[rsaga.esri.to.sgrd](#), [rsaga.sgrd.to.esri](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
rsaga.esri.wrapper(rsaga.hillshade,in.dem="dem",out.grid="hshd",condensed.res=FALSE,intern=FALSE)
# if successful, returns list(in.res=0,geoproc.res=0,out.res=0),
# and writes hshd.asc; intermediate files dem.sgrd, dem.hgrd, dem.sdat,
# hshd.sgrd, hshd.hgrd, and hshd.sdat are deleted.
# hshd.asc is overwritten if it already existed.

## End(Not run)
```

rsaga.fill.sinks

Fill Sinks

Description

Several methods for filling closed depressions in digital elevation models that would affect hydrological modeling.

Usage

```
rsaga.fill.sinks(in.dem, out.dem,
  method = "planchon.darboux.2001", out.flowdir,
  out.wshed, minslope, ...)
```

Arguments

<code>in.dem</code>	Input: digital elevation model (DEM) as SAGA grid file (default extension: <code>.sgrd</code>).
<code>out.dem</code>	Output: filled, depression-free DEM (SAGA grid file). Existing files will be overwritten!
<code>method</code>	The depression filling algorithm to be used (character). One of <code>"planchon.darboux.2001"</code> (default), <code>"wang.liu.2006"</code> , or <code>"xxl.wang.liu.2006"</code> .
<code>out.flowdir</code>	(only for <code>"wang.liu.2001"</code>): Optional output grid file for computed flow directions (see Notes).
<code>out.wshed</code>	(only for <code>"wang.liu.2001"</code>): Optional output grid file for watershed basins.
<code>minslope</code>	Minimum slope angle (in degree) preserved between adjacent grid cells (default value of <code>0.01</code> only for <code>method="planchon.darboux.2001"</code> , otherwise no default).
<code>...</code>	Optional arguments to be passed to rsaga.geoprocessor , including the env RSAGA geoprocessing environment.

Details

This function bundles three SAGA modules for filling sinks using three different algorithms (`method` argument).

`"planchon.darboux.2001"`: The algorithm of Planchon and Darboux (2001) consists of increasing the elevation of pixels in closed depressions until the sink disappears and a minimum slope angle of `minslope` (default: `0.01` degree) is established.

`"wang.liu.2006"`: This module uses an algorithm proposed by Wang and Liu (2006) to identify and fill surface depressions in DEMs. The method was enhanced to allow the creation of hydrologically sound elevation models, i.e. not only to fill the depressions but also to preserve a downward slope along the flow path. If desired, this is accomplished by preserving a minimum slope gradient (and thus elevation difference) between cells. This is the fully featured version of the module creating a depression-free DEM, a flow path grid and a grid with watershed basins. If you encounter problems processing large data sets (e.g. LIDAR data) with this module try the basic version (`xxl.wang.lui.2006`).

`"xxl.wang.liu.2006"`: This modified algorithm after Wang and Liu (2006) is designed to work on large data sets.

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

The function writes SAGA grid files containing of the depression-free preprocessed DEM, and optionally the flow directions and watershed basins.

Note

The flow directions are coded as 0 = north, 1 = northeast, 2 = east, ..., 7 = northwest.

If minslope=0, depressions will only be filled until a horizontal surface is established, which may not be helpful for hydrological modeling.

Author(s)

Alexander Brenning (R interface), Volker Wichmann (SAGA module)

References

Planchon, O., and F. Darboux (2001): A fast, simple and versatile algorithm to fill the depressions of digital elevation models. *Catena* 46: 159-176.

Wang, L. & H. Liu (2006): An efficient method for identifying and filling surface depressions in digital elevation models for hydrologic analysis and modelling. *International Journal of Geographical Information Science*, Vol. 20, No. 2: 193-213.

See Also

[rsaga.sink.removal](#), [rsaga.sink.route](#).

rsaga.filter.gauss *Gauss Filter*

Description

Smooth a grid using a Gauss filter.

Usage

```
rsaga.filter.gauss(in.grid, out.grid, sigma,  
                  radius = ceiling(2 * sigma), ...)
```

Arguments

in.grid	input: SAGA GIS grid file (default file extension: .sgrd)
out.grid	output: SAGA GIS grid file
sigma	numeric, >0.0001: standard deviation parameter of Gauss filter
radius	positive integer: radius of moving window
...	optional arguments to be passed to rsaga.geoprocessor , including the env RSAGA geoprocessing environment

Value

The type of object returned depends on the `intern` argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.filter.simple](#)

rsaga.filter.simple *Simple Filters*

Description

Apply a smoothing, sharpening or edge filter to a SAGA grid.

Usage

```
rsaga.filter.simple(in.grid, out.grid, mode = "circle",
  method = c("smooth", "sharpen", "edge"), radius, ...)
```

Arguments

<code>in.grid</code>	input: SAGA grid file (default file extension: <code>.sgrd</code>)
<code>out.grid</code>	output: SAGA grid file
<code>mode</code>	character or numeric: shape of moving window, either "square" (=0) or "circle" (=1, default)
<code>method</code>	character or numeric: "smooth" (=0), "sharpen" (=1), or "edge" (=2)
<code>radius</code>	positive integer: radius of moving window
<code>...</code>	optional arguments to be passed to <code>rsaga.geoprocessor</code> , including the env <code>RSAGA</code> geoprocessing environment

Value

The type of object returned depends on the `intern` argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also[rsaga.filter.gauss](#)**Examples**

```
## Not run: rsaga.filter.simple("dem","dem-smooth",radius=4)
```

```
rsaga.geoprocessor      Generic R interface for SAGA modules
```

Description

This function is the workhorse of the R–SAGA interface: It calls the SAGA command line tool to run SAGA modules and pass arguments.

Usage

```
rsaga.geoprocessor(lib, module = NULL, param = list(),
  show.output.on.console = TRUE, invisible = TRUE,
  intern = TRUE, prefix = NULL,
  flags = ifelse(show.output.on.console, "q", "s"),
  cores, env = rsaga.env(), display.command = FALSE,
  reduce.intern = TRUE, check.module.exists = TRUE,
  warn = options("warn")$warn, argsep = " ", ...)
```

Arguments

<code>lib</code>	Name of the SAGA library to be called (see Details).
<code>module</code>	Number ($>=0$) or name of the module to called within the library <code>lib</code> (see Details).
<code>param</code>	A list of named arguments to be passed to the SAGA module (see Examples).
<code>show.output.on.console</code>	a logical (default: TRUE), indicates whether to capture the output of the command and show it on the R console (see system).
<code>invisible</code>	a logical, indicates whether the command window should be visible on the screen.
<code>intern</code>	a logical, indicates whether to make the output of the command an R object
<code>prefix</code>	optional character string: prefix such as <code>"-h"</code> used in the <code>saga_cmd</code> call; mostly for internal purposes; call <code>saga_cmd -h</code> from the command line for details; see also <code>flags</code>
<code>flags</code>	optional character string indicating any command line flags; supported only by SAGA GIS 2.1.0 (and higher), quietly ignored otherwise: <code>"q"</code> : no progress report (the default for <code>show.output.on.console=TRUE</code>); <code>"r"</code> : no messages report; <code>"s"</code> : silent mode, i.e. no progress and no messages report (the default for <code>show.output.on.console=FALSE</code>); other flag options probably not relevant within RSAGA

cores	optional numeric argument, or NA: number of cores used by SAGA GIS; supported only by SAGA GIS 2.1.0 (and higher), ignored otherwise (with a warning); overwrites the cores setting specified in the env argument (see rsaga.env). Multicore-enabled SAGA GIS modules such as the one used by rsaga.pisr seem to run in multicore mode by default when this argument is not specified, therefore cores should only be specified to use a smaller number of cores than available on a machine.
env	A SAGA geoprocessing environment, i.e. a list with information on the SAGA and SAGA modules paths and the name of the working directory in which to look for input and output files. (Defaults: see rsaga.env .)
display.command	Display the DOS command line for executing the SAGA module (including all the arguments to be passed). Default: FALSE.
reduce.intern	If intern=TRUE, reduce the text output of SAGA returned to R by eliminating redundant lines showing the progress of module execution etc. (default: TRUE).
check.module.exists	logical (default: TRUE): call rsaga.module.exists to determine if the specified module can be called in the current SAGA installation
warn	logical (default: TRUE): for internal purposes - can be used to suppress warning messages generated by failed SAGA_CMD calls; currently used by rsaga.get.lib.modules and related functions; see options argument warn for details
argsep	character (default: " "); currently for internal use): defines the character symbol used as a separator between each argument name and argument value passed to <code>saga_cmd</code> . SAGA GIS 2.1.0 (RC1) seems to move toward "=" as a separator, but " " still works and some modules (e.g. the used by rsaga.pisr) don't seem to work with <code>argsep="=</code> ". Future releases of RSAGA may change the default <code>argsep</code> value and/or delete or ignore this argument and/or move it to rsaga.env .
...	Additional arguments to be passed to system .

Details

This workhorse function establishes the interface between the SAGA command line program and R by submitting a system call. This is a low-level function that may be used for directly accessing SAGA; specific functions such as [rsaga.hillshade](#) are intended to be more user-friendly interfaces to the most frequently used SAGA modules. These higher-level interfaces support default values for the arguments and perform some error checking; they should therefore be preferred if available.

A warning is issued if the RSAGA version is not one of 2.0.4, 2.0.5, 2.0.6, 2.0.7, 2.0.8 or 2.1.0.

Value

The type of object returned depends on the `intern` argument passed to [system](#).

If `intern=FALSE`, a numerical error/success code is returned, where a value of 0 corresponds to success and a non-zero value indicates an error. Note however that the function always returns a success value of 0 if `wait=FALSE`, i.e. if it does not wait for SAGA to finish.

If `intern=TRUE` (default), the console output of SAGA is returned as a character vector. This character vector lists the input file names and modules arguments, and gives a more or less detailed report of the function's progress. Redundant information can be cancelled out by setting `reduce.intern=TRUE`.

Note

Existing output files will be overwritten by SAGA without prompting!

If a terrain analysis function is not directly interfaced by one of the RSAGA functions, you might still find it in the growing set of SAGA libraries and modules. The names of all libraries available in your SAGA installation can be obtained using `rsaga.get.libraries` (or by checking the directory listing of the `modules` folder in the SAGA directory). The names and numeric codes of all available modules (globally or within a specific library) are retrieved by `rsaga.get.modules`. Full-text search in library and module names is performed by `rsaga.search.modules`. For information on the usage of SAGA command line modules, see `rsaga.get.usage`, or the RSAGA interface function if available.

`display.command=TRUE` is mainly intended for debugging purposes to check if all arguments are passed correctly to SAGA CMD.

Author(s)

Alexander Brenning (R interface); Olaf Conrad and the SAGA development team (SAGA development)

References

Brenning, A., 2008. Statistical geocomputing combining R and SAGA: The example of landslide susceptibility analysis with generalized additive models. In J. Boehner, T. Blaschke and L. Montanarella (eds.), SAGA - Seconds Out (= Hamburger Beitrage zur Physischen Geographie und Landschaftsoekologie, vol. 19), p. 23-32.

See Also

`rsaga.env`, `rsaga.get.libraries`, `rsaga.get.modules`, `rsaga.search.modules`, `rsaga.get.usage`; `rsaga.esri.wrapper` for a wrapper for ESRI ASCII/binary grids; `rsaga.hillshade` and other higher-level functions.

Examples

```
## Not run:
rsaga.hillshade("dem","hillshade",exaggeration=2)
# using the RSAGA geoprocessor:
rsaga.geoprocessor("ta_lighting",0,list(ELEVATION="dem.sgrd",SHADE="hillshade",EXAGGERATION=2))
# equivalent DOS command line call:
# saga_cmd.exe ta_lighting 0 -ELEVATION dem.sgrd -SHADE hillshade -EXAGGERATION 2

## End(Not run)
```

rsaga.get.modules *Find SAGA libraries and modules*

Description

These functions list the SAGA libraries (`rsaga.get.libraries`) and modules (`rsaga.get.lib.modules`, `rsaga.get.modules`) available in a SAGA installation, and allow to perform a full-text search among these functions.

Usage

```
rsaga.get.modules(libs, env = rsaga.env(),
  interactive = FALSE, parallel = env$parallel)

rsaga.get.libraries(path = rsaga.env()$modules, dll)

rsaga.get.lib.modules(lib, env = rsaga.env(),
  interactive = FALSE)

rsaga.module.exists(libs, module, env = rsaga.env(), ...)

rsaga.search.modules(text, modules, search.libs = TRUE,
  search.modules = TRUE, env = rsaga.env(),
  ignore.case = TRUE, ...)
```

Arguments

<code>text</code>	character string to be searched for in the names of available libraries and/or modules
<code>search.libs</code>	logical (default TRUE); see <code>search.modules</code>
<code>search.modules</code>	logical (default TRUE): should text be searched for in library and/or module names?
<code>ignore.case</code>	logical (default FALSE): should the text search in library/module names be case sensitive?
<code>lib</code>	character string with the name of the library in which to look for modules
<code>libs</code>	character vector with the names of libraries in which to look for modules; if missing, all libraries will be processed
<code>module</code>	module name or numeric code
<code>modules</code>	optional list: result of <code>rsaga.get.modules</code> ; if missing, a list of available modules will be retrieved using that function
<code>env</code>	a SAGA geoprocessing environment as created by <code>rsaga.env</code>
<code>path</code>	path of SAGA library files (modules subfolder in the SAGA installation folder); defaults to the path determined by <code>rsaga.env</code> .
<code>dll</code>	file extension of dynamic link libraries

interactive	logical (default FALSE): should modules be returned that can only be executed in interactive mode (i.e. using SAGA GUI)?
parallel	logical (defaults to env\$parallel): if TRUE, run in parallel mode; requires a parallel backend such as doSNOW or doMC
...	currently only interactive to be passed on to rsaga.get.lib.modules

Value

rsaga.get.libraries returns a character vector with the names of all SAGA libraries available in the folder env\$modules.

rsaga.get.lib.modules returns a data.frame with:

- the names of all modules in library lib,
- their numeric identifiers,
- and a logical variable indicating whether a module can only be executed in interactive (SAGA GUI) mode.

rsaga.get.modules returns a list with, for each SAGA library in libs, a data.frame with module information as given by rsaga.get.lib.modules. If libs is missing, all modules in all libraries will be retrieved.

Note

For information on the usage of SAGA command line modules, see [rsaga.get.usage](#), or [rsaga.html.help](#) (in SAGA GIS 2.1.0+), or the RSAGA interface function, if available.

See Also

[rsaga.get.usage](#), [rsaga.html.help](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# make sure that 'rsaga.env' can find 'saga_cmd.exe'
# before running this:
rsaga.get.libraries()
# list all modules in my favorite libraries:
rsaga.get.modules(c("io_grid", "grid_tools", "ta_preprocessor",
  "ta_morphometry", "ta_lighting", "ta_hydrology"))
# list *all* modules (quite a few!):
# rsaga.get.modules(interactive=TRUE)

# find modules that remove sink from DEMs:
rsaga.search.modules("sink")
# find modules that close gaps (no-data areas) in grids:
rsaga.search.modules("gap")

## End(Not run)
```

rsaga.get.usage *Usage of SAGA command line modules*

Description

rsaga.get.usage provides information on the usage of and arguments required by SAGA command line modules.

Usage

```
rsaga.get.usage(lib, module, env = rsaga.env(),
               show = TRUE)
```

Arguments

lib	name of the SAGA library
module	name or numeric identifier of SAGA module in library lib
env	a SAGA geoprocessing environment as created by rsaga.env
show	logical (default: TRUE); display usage in the R console?

Details

This function is intended to provide information required to use the [rsaga.geoprocessor](#) and for writing your own high-level interface function for SAGA modules. R-SAGA interfaces already exist for some SAGA modules, e.g. [rsaga.hillshade](#), [rsaga.local.morphometry](#), but there are many more.

Value

The character vector with usage information is invisibly returned.

See Also

[rsaga.html.help](#), [rsaga.geoprocessor](#), [rsaga.env](#), [rsaga.get.modules](#)

Examples

```
## Not run:
rsaga.get.usage("io_grid",1)
rsaga.get.usage("ta_preprocessor",2)
rsaga.get.usage("ta_morphometry",0)
# in SAGA GIS 2.1.0+, compare:
rsaga.html.help("io_grid",1)
# etc.

## End(Not run)
```

rsaga.get.version	<i>Determine SAGA GIS version</i>
-------------------	-----------------------------------

Description

Determine SAGA GIS version.

Usage

```
rsaga.get.version(env = rsaga.env(version = NA), ...)
```

Arguments

env	list, setting up a SAGA geoprocessing environment as created by rsaga.env . Note that version=NA ensures that rsaga.env won't call <code>rsaga.get.version</code> itself.
...	additional arguments to rsaga.geoprocessor

Details

The function first attempts to determine the SAGA version directly through a system call `saga_cmd --version`, which is supported by SAGA GIS 2.0.8. If this fails, `saga_cmd -h` is called, and it is attempted to extract the version number of the SAGA API from the output generated, which works for 2.0.4+.

Value

A character string defining the SAGA GIS (API) version. E.g., "2.0.8".

See Also

[rsaga.env](#)

Examples

```
## Not run:
myenv <- rsaga.env()
myenv$version
# rsaga.env actually calls rsaga.get.version:
rsaga.get.version()

# I keep several versions of SAGA GIS in SAGA-GIS_2.0.x folders:
myenv05 = rsaga.env(path = "C:/Progra~1/SAGA-GIS_2.0.5", version = NA)
# Check if it's really version 2.0.5 as suggested by the folder name:
rsaga.get.version(env = myenv05)

## End(Not run)
```

 rsaga.grid.calculus *SAGA Module Grid Calculus*

Description

Perform Arithmetic Operations on Grids

Usage

```
rsaga.grid.calculus(in.grids, out.grid, formula,
  env = rsaga.env(), ...)
```

```
rsaga.linear.combination(in.grids, out.grid, coef,
  cf.digits = 16, remove.zeros = FALSE,
  remove.ones = TRUE, env = rsaga.env(), ...)
```

Arguments

<code>in.grids</code>	input character vector: SAGA grid files (default file extension: <code>.sgrd</code>)
<code>out.grid</code>	output: grid file resulting from the cell-by-cell application of 'formula' to the grids. Existing files will be overwritten!
<code>formula</code>	character string of formula specifying the arithmetic operation to be performed on the <code>in.grids</code> (see Details); if this is a formula, only the right hand side will be used.
<code>coef</code>	numeric: coefficient vector to be used for the linear combination of the <code>in.grids</code> . If <code>coef</code> has one more element than <code>in.grids</code> , the first one will be interpreted as an intercept.
<code>cf.digits</code>	integer: number of digits used when converting the coefficients to character strings (trailing zeros will be removed)
<code>remove.zeros</code>	logical: if TRUE, terms (grids) with coefficient (numerically) equal to zero (after rounding to <code>cf.digits</code> digits) will be removed from the formula
<code>remove.ones</code>	logical: if TRUE (the default), factors equal to 1 (after rounding to <code>cf.digits</code> digits) will be removed from the formula
<code>env</code>	RSAGA geoprocessing environment, generated by a call to rsaga.env
<code>...</code>	optional arguments to be passed to rsaga.geoprocessor

Details

The `in.grids` are represented in the formula by the letters a (for `in.grids[1]`), b etc. Thus, if `in.grids[1]` is Landsat TM channel 3 and `in.grids[2]` is channel 4, the NDVI formula $(TM3 - TM4)/(TM3 + TM4)$ can be represented by the character string "(a-b)/(a+b)" (any spaces are removed) or the formula $\sim(a-b)/(a+b)$ in the formula argument.

In addition to +, -, *, and /, the following operators and functions are available for the formula definition:

- \wedge power
- sin(a)sine
- cos(a)cosine
- tan(a)tangent
- asin(a)arc sine
- acos(a)arc cosine
- atan(a)arc tangent
- atan2(a,b)arc tangent of b/a
- abs(a)absolute value
- int(a)convert to integer
- sqrt(a)square root
- ln(a)natural logarithm
- mod(a,b)modulo
- gt(a, b)returns 1 if a greater b
- lt(a, b)returns 1 if a lower b
- eq(a, b)returns 1 if a equal b
- ifelse(switch, x, y)returns x if switch equals 1 else y

Using `remove.zeros=FALSE` might have the side effect that no data areas in the grid with coefficient 0 are passed on to the results grid. (To be confirmed.)

Value

The type of object returned depends on the `intern` argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[local.function](#), [focal.function](#), and [multi.focal.function](#) for a more flexible framework for combining grids or applying local and focal functions; [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# using SAGA grids:
# calculate the NDVI from Landsat TM bands 3 and 4:
rsaga.grid.calculus(c("tm3.sgrd", "tm4.sgrd"), "ndvi.sgrd", ~(a-b)/(a+b))
# apply a linear regression equation to grids:
coefs = c(20, -0.6)
# maybe from a linear regression of mean annual air temperature (MAAT)
```

```
# against elevation - something like:
# coefs = coef( lm( maat ~ elevation ) )
rsaga.linear.combination("elevation.sgrd", "maat.sgrd", coefs)
# equivalent:
rsaga.grid.calculus("elevation.sgrd", "maat.sgrd", "20 - 0.6*a")

## End(Not run)
```

rsaga.grid.to.points *Convert SAGA grid file to point shapefile*

Description

Convert SAGA grid file to point (or polygon) shapefile - either completely or only a random sample of grid cells.

Usage

```
rsaga.grid.to.points(in.grids, out.shapefile,
  in.clip.polygons, exclude.nodata = TRUE,
  type = "nodes", env = rsaga.env(), ...)

rsaga.grid.to.points.randomly(in.grid, out.shapefile,
  freq, ...)
```

Arguments

in.grids	Input: names of (possibly several) SAGA GIS grid files to be converted into a point shapefile.
in.grid	Input: SAGA grid file from which to sample.
out.shapefile	Output: point shapefile (default extension: .shp). Existing files will be overwritten!
in.clip.polygons	optional polygon shapefile to be used for clipping/masking an area
exclude.nodata	logical (default: TRUE): skip 'nodata' grid cells?
type	character string: "nodes": create point shapefile of grid center points; "cells" (only supported by SAGA GIS 2.0.6+): create polygon shapefile with grid cell boundaries
freq	integer >=1: sampling frequency: on average 1 out of 'freq' grid cells are selected
env	RSAGA geoprocessing environment created by rsaga.env ; required by rsaga.grid.to.points to determine version-dependent SAGA module name and arguments
...	Optional arguments to be passed to rsaga.geoprocessor

Note

These functions use modules `Grid Values to Shapes` (pre-2.0.6 name: `Grid Values to Points`) and `Grid Values to Points (randomly)` in SAGA library `shapes_grid`.

The SAGA 2.0.6+ module `Grid Values to Shapes` is more flexible than the earlier versions as it allows to create grid cell polygons instead of center points (see argument type).

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA modules)

See Also

[rsaga.add.grid.values.to.points](#)

Examples

```
## Not run:
# one point per grid cell, exclude nodata areas:
rsaga.grid.to.points("dem", "dempoints")
# take only every 20th point, but to not exclude nodata areas:
rsaga.grid.to.points.randomly("dem", "dempoints20", freq = 20)

## End(Not run)
```

rsaga.hillshade	<i>Analytical hillshading Analytical hillshading calculation.</i>
-----------------	---

Description

Analytical hillshading Analytical hillshading calculation.

Usage

```
rsaga.hillshade(in.dem, out.grid, method = "standard",
  azimuth = 315, declination = 45, exaggeration = 4, ...)
```

Arguments

<code>in.dem</code>	Input digital elevation model (DEM) as SAGA grid file (default extension: <code>.sgrd</code>).
<code>out.grid</code>	Output hillshading grid (SAGA grid file). Existing files will be overwritten!
<code>method</code>	Available choices (character or numeric): <code>"standard"</code> (or <code>0</code> - default), <code>"max90deg.standard"</code> (1), <code>"combined.shading"</code> (2), <code>"ray.tracing"</code> (3). See Details.
<code>azimuth</code>	Direction of the light source, measured in degree clockwise from the north direction; default 315, i.e. northwest.
<code>declination</code>	Declination of the light source, measured in degree above the horizon (default 45).

exaggeration Vertical exaggeration of elevation (default: 4). The terrain exaggeration factor allows to increase the shading contrasts in flat areas.

... Optional arguments to be passed to [rsaga.geoprocessor](#), including the env RSAGA geoprocessing environment.

Details

The Analytical Hillshading algorithm is based on the angle between the surface and the incoming light beams, measured in radians.

Value

The type of object returned depends on the intern argument passed to the [rsaga.geoprocessor](#). For intern=FALSE it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

While the default azimuth of 315 degree (northwest) is not physically meaningful on the northern hemisphere, a northwesterly light source is required to properly depict relief in hillshading images. Physically correct southerly light sources results a hillshade that would be considered by most people as inverted: hills look like depressions, mountain chains like troughs.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.solar.radiation](#), [rsaga.insolation](#)

Examples

```
## Not run: rsaga.hillshade("dem.sgrd","hillshade")
```

rsaga.html.help

HTML help on a SAGA module or library

Description

This function opens SAGA's HTML documentation for the specified library or module. Works with SAGA GIS 2.1.0(+), for earlier versions a web page with the SAGA GIS wiki is displayed.

Usage

```
rsaga.html.help(lib, module = NULL,  
use.program.folder = TRUE, env = rsaga.env(), ...)
```

Arguments

lib	name of the SAGA library, or one of the rsaga. module functions such as rsaga.hillshade
module	name or numeric identifier of SAGA module in library lib; module=NULL takes you to the main help page of the SAGA library lib
use.program.folder	logical; if TRUE (the default), attempt to write SAGA GIS documentation to a "help" subfolder of env\$path; the "help" folder is created if it doesn't exist. If FALSE, create SAGA GIS documentation files in this R session's temporary folder as obtained using tempdir()
env	a SAGA geoprocessing environment as created by rsaga.env
...	additional arguments to browseURL

Details

Requires SAGA GIS 2.1.0(+), with earlier versions use [rsaga.get.usage](#).

See Also

[rsaga.get.usage](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# Requires SAGA GIS 2.1.0+:
rsaga.html.help("io_grid")
rsaga.html.help("io_grid",0)
rsaga.html.help("io_grid","Import ESRI Arc/Info Grid")

## End(Not run)
```

rsaga.import.gdal *Import Grid Files to SAGA grid format using GDAL*

Description

These functions provide simple interfaces for reading and writing grids from/to ASCII grids and Rd files. Grids are stored in matrices, their headers in lists.

Usage

```
rsaga.import.gdal(in.grid, out.grid, env = rsaga.env(),
  ...)
```

Arguments

<code>in.grid</code>	file name of a grid in a format supported by GDAL
<code>out.grid</code>	output SAGA grid file name; defaults to <code>in.grid</code> with the file extension being removed; file extension should not be specified, it defaults to <code>.sgrd</code>
<code>env</code>	RSAGA geoprocessing environment created by rsaga.env
<code>...</code>	additional arguments to be passed to <code>rsaga.geoprocessor</code>

Details

The GDAL Raster Import module of SAGA imports grid data from various file formats using the Geospatial Data Abstraction Library (GDAL) by Frank Warmerdam. As of SAGA GIS 2.0.7, GDAL version 1.8.0 is used. More information is available at <http://www.gdal.org/>.

If `in.grid` has more than one band (e.g. RGB GEOTIFF), then output grids with file names of the form `in.grid_01.sgrd`, `in.grid_02.sgrd` etc. are written, one for each band.

The following raster formats are currently supported. Last updated for SAGA GIS 2.0.7; for an updated list in SAGA GIS 2.1.0 call `rsaga.html.help("io_gdal", "GDAL: Import Raster")`

- VRTVirtual Raster
- GTiffGeoTIFF
- NITFNational Imagery Transmission Format
- RPFTOCRaster Product Format TOC format
- HFAErdas Imagine Images (.img)
- SAR_CEOSCEOS SAR Image
- CEOSCEOS Image
- JAXAPALSARJAXA PALSAR Product Reader (Level 1.1/1.5)
- GFFGround-based SAR Applications Testbed File Format (.gff)
- ELASELAS
- AIGArc/Info Binary Grid
- AAIGridArc/Info ASCII Grid
- SDTSSDTS Raster
- DTEDDTED Elevation Raster
- PNGPortable Network Graphics
- JPEGJPEG JFIF
- MEMIn Memory Raster
- JDEMJapanese DEM (.mem)
- GIFGraphics Interchange Format (.gif)
- BIGGIFGraphics Interchange Format (.gif)
- ESATEnvisat Image Format
- BSBMaptech BSB Nautical Charts
- XPMX11 PixMap Format

- BMPMS Windows Device Independent Bitmap
- DIMAPSPOT DIMAP
- AirSARAirSAR Polarimetric Image
- RS2RadarSat 2 XML Product
- PCIDSKPCIDSK Database File
- PCRasternPCRaster Raster File
- ILWISILWIS Raster Map
- SGISGI Image File Format 1.0
- SRTMHGTSRTMHGT File Format
- LevellerLeveller heightfield
- TerragenTerragen heightfield
- ISIS3USGS Astrogeology ISIS cube (Version 3)
- ISIS2USGS Astrogeology ISIS cube (Version 2)
- PDSNASA Planetary Data System
- TILnEarthWatch .TIL
- ERSnERMMapper .ers Labelled
- L1BNOAA Polar Orbiter Level 1b Data Set
- FITFIT Image
- GRIBGRIdded Binary (.grb)
- RMFRaster Matrix Format
- MSGNEUMETSAT Archive native (.nat)
- RSTIdrisi Raster A.1
- INGRIntergraph Raster
- GSAGGolden Software ASCII Grid (.grd)
- GSBGGolden Software Binary Grid (.grd)
- GS7BGGolden Software 7 Binary Grid (.grd)
- COSARCOSAR Annotated Binary Matrix (TerraSAR-X)
- TSXTerraSAR-X Product
- COASPDRDC COASP SAR Processor Raster
- RnR Object Data Store
- PNMPortable Pixmap Format (netpbm)
- DOQ1nUSGS DOQ (Old Style)
- DOQ2USGS DOQ (New Style)
- ENVInENVI .hdr Labelled
- EHdrESRI .hdr Labelled
- GenBinnGeneric Binary (.hdr Labelled)
- PAuxPCI .aux Labelled

- MFFnVexcel MFF Raster
- MFF2Vexcel MFF2 (HKV) Raster
- FujiBASnFuji BAS Scanner Image
- GSCGSC Geogrid
- FASTnEOSAT FAST Format
- BTVTP .bt (Binary Terrain) 1.3 Format
- LANErdas .LAN/.GIS
- CPGConvair PolGASP
- IDAImage Data and Analysis
- NDFNLAPS Data Format
- EIRnErdas Imagine Raw
- DIPExDIPEX
- LCPFARSITE v.4 Landscape File (.lcp)
- GTXNOAA Vertical Datum .GTX
- LOSLASNADCON .los/.las Datum Grid Shift
- NTV2NTv2 Datum Grid Shift
- RIKSwedish Grid RIK (.rik)
- USGSDEMUSGS Optional ASCII DEM (and CDED)
- GXFGeoSoft Grid Exchange Format
- NWT_GRDNorthwood Numeric Grid Format .grd/.tab
- NWT_GRCNorthwood Classified Grid Format .grc/.tab
- ADRGARC Digitized Raster Graphics
- SRPStandard Raster Product (ASRP/USRP)
- BLXMagellan topo (.blx)
- SAGASAGA GIS Binary Grid (.sdat)
- KMLSUPEROVERLAYKml Super Overlay
- XYZASCII Gridded XYZ
- HF2HF2/HFZ heightfield raster
- OZIOZI

Author(s)

Alexander Brenning (R interface), Olaf Conrad / Andre Ringeler (SAGA module), Frank Warmerdam (GDAL)

References

GDAL website: <http://www.gdal.org/>

See Also

read.ascii.grid, rsaga.esri.to.sgrd, read.sgrd, read.Rd.grid

 rsaga.insolation *Incoming Solar Radiation (Insolation)*

Description

This function calculates the amount of incoming solar radiation (insolation) depending on slope, aspect, and atmospheric properties. Module not available in SAGA GIS 2.0.6 and 2.0.7.

Usage

```
rsaga.insolation(in.dem, in.vapour, in.latitude,
  in.longitude, out.direct, out.diffuse, out.total,
  horizontal = FALSE, solconst = 8.164,
  atmosphere = 12000, water.vapour.pressure = 10,
  type = c("moment", "day", "range.of.days", "same.moment.range.of.days"),
  time.step = 1, day.step = 5, days, moment, latitude,
  bending = FALSE, radius = 6366737.96,
  lat.offset = "user", lat.ref.user = 0,
  lon.offset = "center", lon.ref.user = 0, ...)
```

Arguments

in.dem	Name of input digital elevation model (DEM) grid in SAGA grid format (default extension: .sgrd)
in.vapour	Optional input: SAGA grid file giving the water vapour pressure in mbar
in.latitude	Optional input: SAGA grid file giving for each pixel the latitude in degree
in.longitude	Optional input: SAGA grid file giving for each pixel the longitude in degree
out.direct	Optional output grid file for direct insolation
out.diffuse	Optional output grid file for diffuse insolation
out.total	Optional output grid file for total insolation, i.e. the sum of direct and diffuse insolation
horizontal	logical; project radiation onto a horizontal surface? (default: FALSE, i.e. use the actual inclined surface as a reference area)
solconst	solar constant in Joule; default: 8.164 J/cm ² /min (=1360.7 kWh/m ² ; the more commonly used solar constant of 1367 kWh/m ² corresponds to 8.202 J/cm ² /min)
atmosphere	height of atmosphere in m; default: 12000m
water.vapour.pressure	if no water vapour grid is given, this argument specifies a constant water vapour pressure that is uniform in space; in mbar, default 10 mbar
type	type of time period: "moment" (equivalent: 0) for a single instant, "day" (or 1) for a single day, "range.of.days" (or 2), or "same.moment.range.of.days" (or 3) for the same moment in a range of days; default: "moment"
time.step	time resolution in hours for discretization within a day

<code>day.step</code>	time resolution in days for a range of days
<code>days</code>	numeric vector of length 2, specifying the first and last day of a range of days (for types 2 and 3)
<code>moment</code>	if <code>type="moment"</code> or <code>"same.moment.range.of.days"</code> , <code>moment</code> specifies the time of the day (hour between 0 and 24) for which the insolation is to be calculated
<code>latitude</code>	if no <code>in.latitude</code> grid is given, this will specify a fixed geographical latitude for the entire grid
<code>bending</code>	should planetary bending be modeled? (default: FALSE)
<code>radius</code>	planetary radius
<code>lat.offset</code>	<code>latitude</code> relates to grids "bottom"(equivalent code: 0), "center" (1), "top" (2), or "user"-defined reference (default: "user"); in the latter case, <code>lat.ref.user</code> defines the reference
<code>lat.ref.user</code>	if <code>in.latitude</code> is missing and <code>lat.offset="user"</code> , then this numeric value defines the latitudinal reference (details??)
<code>lon.offset</code>	local time refers to grid's "left" edge (code 0), "center" (1), "right" edge (2), or a "user"-defined reference.
<code>lon.ref.user</code>	if <code>in.longitude</code> is missing and <code>lon.offset="user"</code> , then this numeric value defines the reference of the local time (details??)
<code>...</code>	optional arguments to be passed to rsaga.geoprocessor , including the env RSAGA geoprocessing environment

Details

Calculation of incoming solar radiation (insolation). Based on the SADO (System for the Analysis of Discrete Surfaces) routines developed by Boehner & Trachinow.

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

This function uses module `Insolation` (code: 3) from SAGA library `ta_lighting`. It is available in SAGA GIS 2.0.4 and 2.0.5 but not 2.0.6 and 2.0.7; see [rsaga.pisr](#).

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.solar.radiation](#), [rsaga.pisr](#), [rsaga.hillshade](#)

rsaga.inverse.distance

Spatial Interpolation Methods

Description

Spatial interpolation of point data using inverse distance to a power (inverse distance weighting, IDW), nearest neighbors, or modified quadratic shephard.

Usage

```
rsaga.inverse.distance(in.shapefile, out.grid, field,
                      power = 1, maxdist, nmax = 100, target,
                      env = rsaga.env(), ...)
```

```
rsaga.nearest.neighbour(in.shapefile, out.grid, field,
                       target, env = rsaga.env(), ...)
```

```
rsaga.modified.quadratic.shephard(in.shapefile, out.grid,
                                  field, quadratic.neighbors = 13,
                                  weighting.neighbors = 19, target, env = rsaga.env(),
                                  ...)
```

```
rsaga.triangulation(in.shapefile, out.grid, field,
                   target, env = rsaga.env(), ...)
```

Arguments

in.shapefile	Input: point shapefile (default extension: .shp).
out.grid	Output: filename for interpolated grid (SAGA grid file). Existing files will be overwritten!
field	numeric or character: number or name of attribute in the shapefile's attribute table to be interpolated; the first attribute is represented by a zero.
power	numeric (>0): exponent used in inverse distance weighting (usually 1 or 2)
maxdist	numeric: maximum distance of points to be used for inverse distance interpolation (search radius); no search radius is applied when this argument is missing or equals Inf
nmax	Maximum number of nearest points to be used for interpolation; nmax=Inf is a valid value (no upper limit)
quadratic.neighbors	integer >=5; ??
weighting.neighbors	integer >=3; ??
target	required argument of type list: parameters identifying the target area, e.g. the x/y extent and cellsize, or name of a reference grid; see rsaga.target .

env RSAGA geoprocessing environment created by [rsaga.env](#), required because module(s) depend(s) on SAGA version

... Optional arguments to be passed to [rsaga.geoprocessor](#), including the env RSAGA geoprocessing environment.

Details

These functions use modules from the `grid_gridding` SAGA GIS library. They do not support SAGA GIS 2.0.4, which differs in some argument names and parameterizations. Target grid parameterization by grid file name currently doesn't work with SAGA GIS 2.1.0 Release Candidate 1 (see also [rsaga.target](#)); stay tuned for future updates and fixes.

Note

The 'Inverse Distance Weighted' module of SAGA GIS not only support inverse-distance weighted interpolation, but also exponential and other weighting schemes (command line argument `WEIGHTING`); these are however not accessible through this function, but only through the `rsaga.geoprocessor`, if needed. See `rsaga.get.usage("grid_gridding", "Inverse Distance Weighted")` for details.

See the example section in the help file for [write.shapefile](#) in package `shapefiles` to learn how to apply these interpolation functions to a shapefile exported from a `data.frame`.

Modified Quadratic Shephard method: based on module 660 in TOMS (see references).

Author(s)

Alexander Brenning (R interface), Andre Ringeler and Olaf Conrad (SAGA modules)

References

QSHEP2D: Fortran routines implementing the Quadratic Shepard method for bivariate interpolation of scattered data (see R. J. Renka, ACM TOMS 14 (1988) pp.149-150). Classes: E2b. Interpolation of scattered, non-gridded multivariate data.

See Also

[rsaga.target](#); [idw](#) in package `gstat`.

rsaga.lib.prefix

Determine prefix for SAGA GIS library names

Description

Internal function that determines the possible prefix for SAGA GIS library names - relevant for non-Windows SAGA GIS pre-2.1.0.

Usage

```
rsaga.lib.prefix(env)
```

Arguments

env list, setting up a SAGA geoprocessing environment as created by [rsaga.env](#).

Details

Some non-Windows versions of `saga_cmd` require library names with a "lib" prefix, e.g. `libio_grid` instead of `io_grid`. This function, which is called by [rsaga.env](#) tries to guess this behaviour based on the operating system and SAGA GIS version.

Value

A character string, either "" or "lib".

See Also

[rsaga.env](#)

Examples

```
## Not run:
env = rsaga.env()
# obtained by a call to rsaga.lib.prefix:
env$lib.prefix

# more explicitly:
rsaga.lib.prefix(env=env)

## End(Not run)
```

rsaga.local.morphometry

Local Morphometry

Description

Calculates local morphometric terrain attributes (i.e. slope, aspect and curvatures).

Usage

```
rsaga.local.morphometry(in.dem, out.slope, out.aspect,
  out.curv, out.hcurv, out.vcurv,
  method = "poly2zevenbergen", env = rsaga.env(), ...)
```

```
rsaga.slope(in.dem, out.slope,
  method = "poly2zevenbergen", ...)
```

```
rsaga.aspect(in.dem, out.aspect,
  method = "poly2zevenbergen", ...)
```

```
rsaga.curvature(in.dem, out.curv,
  method = "poly2zevenbergen", ...)
```

```
rsaga.plan.curvature(in.dem, out.hcurv,
  method = "poly2zevenbergen", ...)
```

```
rsaga.profile.curvature(in.dem, out.vcurv,
  method = "poly2zevenbergen", ...)
```

Arguments

<code>in.dem</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: <code>.sgrd</code>)
<code>out.slope</code>	optional output: slope (in radian)
<code>out.aspect</code>	optional output: aspect (in radian; north=0, clockwise angles)
<code>out.curv</code>	optional output: curvature
<code>out.hcurv</code>	optional output: horizontal curvature (plan curvature)
<code>out.vcurv</code>	optional output: vertical curvature (profile curvature)
<code>method</code>	character or numeric: algorithm (see References): Maximum Slope - Travis et al. (1975) ("maxslope", or 0), Max. Triangle Slope - Tarboton (1997) ("maxtriangleslope", or 1), Least Squares Fit Plane - Costa-Cabral and Burgess (1996) ("lsqfitplane", or 2), Fit 2nd Degree Polynomial - Bauer et al. (1985) ("poly2bauer", or 3), Fit 2nd Degree Polynomial - Heerdegen and Beran (1982) ("poly2heerdegen", or 4), default: Fit 2nd Degree Polynomial - Zevenbergen and Thorne (1987) ("poly2zevenbergen", or 5), Fit 3rd Degree Polynomial - Haralick (1983) ("poly3haralick", or 6).
<code>env</code>	list, setting up a SAGA geoprocessing environment as created by rsaga.env
<code>...</code>	further arguments to rsaga.geoprocessor

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

References

General references:

Jones KH (1998) A comparison of algorithms used to compute hill slope as a property of the DEM. *Computers and Geosciences*. 24 (4): 315-323.

References on specific methods:

Maximum Slope:

Travis, M.R., Elsner, G.H., Iverson, W.D., Johnson, C.G. (1975): VIEWIT: computation of seen areas, slope, and aspect for land-use planning. USDA F.S. Gen. Tech. Rep. PSW-11/1975, 70 p. Berkeley, California, U.S.A.

Maximum Triangle Slope:

Tarboton, D.G. (1997): A new method for the determination of flow directions and upslope areas in grid digital elevation models. Water Resources Research, 33(2): 309-319.

Least Squares or Best Fit Plane:

Beasley, D.B., Huggins, L.F. (1982): ANSWERS: User's manual. U.S. EPA-905/9-82-001, Chicago, IL, 54 pp.

Costa-Cabral, M., Burges, S.J. (1994): Digital Elevation Model Networks (DEMON): a model of flow over hillslopes for computation of contributing and dispersal areas. Water Resources Research, 30(6): 1681-1692.

Fit 2nd Degree Polynomial:

Bauer, J., Rohdenburg, H., Bork, H.-R. (1985): Ein Digitales Reliefmodell als Voraussetzung fuer ein deterministisches Modell der Wasser- und Stoff-Fluesse. Landschafts- und Landschaftsoekologie, H. 10, Parametereaufbereitung fuer deterministische Gebiets-Wassermodele, Grundlagenarbeiten zur Analyse von Agrar-Oekosystemen, eds.: Bork, H.-R., Rohdenburg, H., p. 1-15.

Heerdegen, R.G., Beran, M.A. (1982): Quantifying source areas through land surface curvature. Journal of Hydrology, 57.

Zevenbergen, L.W., Thorne, C.R. (1987): Quantitative analysis of land surface topography. Earth Surface Processes and Landforms, 12: 47-56.

Fit 3.Degree Polynom:

Haralick, R.M. (1983): Ridge and valley detection on digital images. Computer Vision, Graphics and Image Processing, 22(1): 28-38.

For a discussion on the calculation of slope by ArcGIS check these links:

<http://forums.esri.com/Thread.asp?c=93&f=1734&t=239914>

http://webhelp.esri.com/arcgisdesktop/9.2/index.cfm?topicname=how_slope_works

See Also

[rsaga.parallel.processing](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# a simple slope algorithm:
rsaga.slope("lican.sgrd", "slope", "maxslope")
# same for ASCII grids (default extension .asc):
rsaga.esri.wrapper(rsaga.slope, in.dem="lican", out.slope="slope", method="maxslope")

## End(Not run)
```

 rsaga.parallel.processing

Parallel Processing

Description

Calculate the size of the local catchment area (contributing area), the catchment height, catchment slope and aspect, and flow path length, using parallel processing algorithms including the recommended multiple flow direction algorithm. This set of algorithms processes a digital elevation model (DEM) downwards from the highest to the lowest cell.

Usage

```
rsaga.parallel.processing(in.dem, in.sinkroute,
  in.weight, out.carea, out.cheight, out.cslope,
  out.caspect, out.flowpath, step, method = "mfd",
  linear.threshold = Inf, convergence = 1.1,
  env = rsaga.env(), ...)
```

Arguments

<code>in.dem</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: <code>.sgrd</code>)
<code>in.sinkroute</code>	optional input: SAGA grid with sink routes
<code>in.weight</code>	optional input: SAGA grid with weights
<code>out.carea</code>	output: catchment area grid
<code>out.cheight</code>	optional output: catchment height grid
<code>out.cslope</code>	optional output: catchment slope grid
<code>out.caspect</code>	optional output: catchment aspect grid
<code>out.flowpath</code>	optional output: flow path length grid
<code>step</code>	integer ≥ 1 : step parameter
<code>method</code>	character or numeric: choice of processing algorithm: Deterministic 8 (" <code>d8</code> " or 0), Rho 8 (" <code>rho8</code> " or 1), Braunschweiger Reliefmodell (" <code>braunschweig</code> " or 2), Deterministic Infinity (" <code>dinf</code> " or 3), Multiple Flow Direction (" <code>mfd</code> " or 4, the default), Multiple Triangular Flow Direction (" <code>mtfd</code> ", or 5).
<code>linear.threshold</code>	numeric (number of grid cells): threshold above which linear flow (i.e. the Deterministic 8 algorithm) will be used; linear flow is disabled for <code>linear.threshold=Inf</code> (the default)
<code>convergence</code>	numeric ≥ 0 : a parameter for tuning convergent/ divergent flow; default value of 1.1 gives realistic results and should not be changed
<code>env</code>	list, setting up a SAGA geoprocessing environment as created by rsaga.env
<code>...</code>	further arguments to rsaga.geoprocessor

Details

Refer to the references for details on the available algorithms.

Value

The type of object returned depends on the `intern` argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Note

This function uses module Parallel Processing (version 2.0.7+: Catchment Area (Parallel) from SAGA library `ta_hydrology`).

The SAGA GIS 2.0.6+ version of the module adds more (optional) input and output grids that are currently not supported by this wrapper function. Use `rsaga.geoprocessor` for access to these options, and see `rsaga.get.usage("ta_hydrology", "Catchment Area (Parallel)")` for information on new arguments.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module), Thomas Grabs (MTFD algorithm)

References

Deterministic 8:

O'Callaghan, J.F., Mark, D.M. (1984): The extraction of drainage networks from digital elevation data. *Computer Vision, Graphics and Image Processing*, 28: 323-344.

Rho 8:

Fairfield, J., Leymarie, P. (1991): Drainage networks from grid digital elevation models. *Water Resources Research*, 27: 709-717.

Braunschweiger Reliefmodell:

Bauer, J., Rohdenburg, H., Bork, H.-R. (1985): Ein Digitales Reliefmodell als Voraussetzung fuer ein deterministisches Modell der Wasser- und Stoff-Fluesse. *Landschafts- und Landschaftsoekologie*, H. 10, Parametereaufbereitung fuer deterministische Gebiets-Wassermodule, Grundlagenarbeiten zu Analyse von Agrar-Oekosystemen, eds.: Bork, H.-R., Rohdenburg, H., p. 1-15.

Deterministic Infinity:

Tarboton, D.G. (1997): A new method for the determination of flow directions and upslope areas in grid digital elevation models. *Water Resources Research*, 33(2): 309-319.

Multiple Flow Direction:

Freeman, G.T. (1991): Calculating catchment area with divergent flow based on a regular grid. *Computers and Geosciences*, 17: 413-22.

Quinn, P.F., Beven, K.J., Chevallier, P., Planchon, O. (1991): The prediction of hillslope flow paths for distributed hydrological modelling using digital terrain models. *Hydrological Processes*, 5: 59-79.

Multiple Triangular Flow Direction:

Seibert, J., McGlynn, B. (2007): A new triangular multiple flow direction algorithm for computing upslope areas from gridded digital elevation models. Water Resources Research, 43, W04501.

See Also

[rsaga.wetness.index](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:
# SAGA GIS 2.0.6+:
rsaga.get.usage("ta_hydrology","Catchment Area (Parallel)")
# earlier versions of SAGA GIS:
#rsaga.get.usage("ta_hydrology","Parallel Processing")
# execute model with typical settings:
rsaga.parallel.processing(in.dem = "dem", out.carea = "carea", out.cslope = "cslope")
# cslope is in radians - convert to degree:
fac = round(180/pi, 4)
formula = paste(fac, "*a", sep = "")
rsaga.grid.calculus("cslope", "cslopedeg", formula)

## End(Not run)
```

rsaga.pisr

Potential incoming solar radiation

Description

This function calculates the potential incoming solar radiation in an area using different atmospheric models; module available in SAGA GIS 2.0.6+.

Usage

```
rsaga.pisr(in.dem, in.svf.grid = NULL,
  in.vapour.grid = NULL, in.latitude.grid = NULL,
  in.longitude.grid = NULL, out.direct.grid,
  out.diffuse.grid, out.total.grid = NULL,
  out.ratio.grid = NULL, out.duration, out.sunrise,
  out.sunset, local.svf = TRUE, latitude,
  unit = c("kWh/m2", "kJ/m2", "J/cm2"), solconst = 1367,
  enable.bending = FALSE, bending.radius = 6366737.96,
  bending.lat.offset = "user", bending.lat.ref.user = 0,
  bending.lon.offset = "center",
  bending.lon.ref.user = 0,
  method = c("height", "components", "lumped"),
  hgt.atmosphere = 12000, hgt.water.vapour.pressure = 10,
  cmp.pressure = 1013, cmp.water.content = 1.68,
  cmp.dust = 100, lmp.transmittance = 70,
```



```
time.range = c(0, 24), time.step = 0.5,
start.date = list(day = 21, month = 3),
end.date = NULL, day.step = 5, env = rsaga.env(), ...)
```

Arguments

<code>in.dem</code>	name of input digital elevation model (DEM) grid in SAGA grid format (default extension: <code>.sgrd</code>)
<code>in.svf.grid</code>	Optional input grid in SAGA format: Sky View Factor; see also <code>local.svf</code>
<code>in.vapour.grid</code>	Optional input grid in SAGA format: Water vapour pressure (mbar); see also argument <code>hgt.water.vapour.pressure</code>
<code>in.latitude.grid</code>	Optional input grid in SAGA format: Latitude (degree) of each grid cell
<code>in.longitude.grid</code>	see <code>in.latitude.grid</code>
<code>out.direct.grid</code>	Output grid: Direct insolation (unit selected by <code>unit</code> argument)
<code>out.diffuse.grid</code>	Output grid: Diffuse insolation
<code>out.total.grid</code>	Optional output grid: Total insolation, i.e. sum of direct and diffuse incoming solar radiation
<code>out.ratio.grid</code>	Optional output grid: Direct to diffuse ratio
<code>out.duration</code>	Optional output grid: Duration of insolation
<code>out.sunrise</code>	Optional output grid: time of sunrise; only calculated if time span is set to single day
<code>out.sunset</code>	Time of sunset; see <code>out.sunrise</code>
<code>local.svf</code>	logical (default: TRUE; if TRUE, use sky view factor based on local slope (after Oke, 1988), if no sky view factor grid is provided in <code>in.svf.grid</code>)
<code>latitude</code>	Geographical latitude in degree North (negative values indicate southern hemisphere)
<code>unit</code>	unit of insolation output grids: "kWh/m2" (default) "kJ/m2", or "J/cm2"
<code>solconst</code>	solar constant, defaults to 1367 W/m2
<code>enable.bending</code>	logical (default: FALSE): incorporate effects of planetary bending?
<code>bending.radius</code>	Planetary radius, default 6366737.96
<code>bending.lat.offset</code>	if bending is enabled: latitudinal reference is "user"-defined (default), or relative to "top", "center" or "bottom" of grid?
<code>bending.lat.ref.user</code>	user-defined lat. reference for bending, see <code>bending.lat.offset</code>
<code>bending.lon.offset</code>	longitudinal reference, i.e. local time, is "user"-defined, or relative to "top", "center" (default) or "bottom" of grid?

bending.lon.ref.user	user-defined reference for local time (Details??)
method	specifies how the atmospheric components should be accounted for: either based on the height of atmosphere and vapour pressure ("height", or numeric code 0), or air pressure, water and dust content ("components", code 1), or lumped atmospheric transmittance ("lumped", code 0)
hgt.atmosphere	Height of atmosphere (in m); default 12000 m
hgt.water.vapour.pressure	Water vapour pressure in mbar (default 10 mbar); This value is used if no vapour pressure grid is given in argument in.vapour.grid
cmp.pressure	atmospheric pressure in mbar, defaults to 1013 mbar
cmp.water.content	water content of a vertical slice of the atmosphere in cm: between 1.5 and 1.7cm, average 1.68cm (default)
cmp.dust	dust factor in ppm; defaults to 100 ppm
lmp.transmittance	transmittance of the atmosphere in percent; usually between 60 (humid areas) and 80 percent (deserts)
time.range	numeric vector of length 2: time span (hours of the day) for numerical integration
time.step	time step in hours for numerical integration
start.date	list of length two, giving the start date in day and month components as numbers; these numbers are one-based (SAGA_CMD uses zero-based numbers internally), i.e. Jan. 1st is list(day=1,month=1)
end.date	see start.date
day.step	if days indicates a range of days, this specifies the time step (number of days) for calculating the incoming solar radiation
env	RSAGA geoprocessing environment obtained with rsaga.env ; this argument is required for version control (see Note)
...	optional arguments to be passed to rsaga.geoprocessor

Details

According to SAGA GIS 2.0.7 documentation, "Most options should do well, but TAPES-G based diffuse irradiance calculation ("Atmospheric Effects" methods 2 and 3) needs further revision!" I.e. be careful with method = "components" and method = "lumped".

Note

This module is computationally very intensive (depending on the size of the grid and the time resolution, of course). The performance seems to have much improved in SAGA GIS 2.1.0, which by default runs this module in multicore mode (at the release candidate 1 for Windows does).

SAGA_CMD uses zero-based days and months, but this R function uses the standard one-based days and months (e.g. day 1 is the first day of the month, month 1 is January) and translates to the SAGA system.

This function uses module Potential Incoming Solar Radiation from SAGA library `ta_lighting` in SAGA version 2.0.6+.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

References

Boehner, J., Antonic, O. (2009): Land surface parameters specific to topo-climatology. In: Hengl, T. and Reuter, H. I. (eds.): Geomorphometry - Concepts, Software, Applications. Elsevier.

Oke, T.R. (1988): Boundary layer climates. London, Taylor and Francis.

Wilson, J.P., Gallant, J.C. (eds.), 2000: Terrain analysis - principles and applications. New York, John Wiley and Sons.

See Also

[rsaga.hillshade](#); for similar modules in older SAGA versions (pre-2.0.6) see [rsaga.solar.radiation](#) and [rsaga.insolation](#)

rsaga.sgrd.to.esri *Convert SAGA grids to ESRI ASCII/binary grids*

Description

rsaga.sgrd.to.esri converts grid files from SAGA's (version 2) grid format (.sgrd) to ESRI's ASCII (.asc) and binary (.flt) format.

Usage

```
rsaga.sgrd.to.esri(in.sgrds, out.grids, out.path,
  format = "ascii", georef = "corner", prec = 5, ...)
```

Arguments

in.sgrds	character vector of SAGA grid files (.sgrd) to be converted; files are expected to be found in folder <code>rsaga.env()\$workspace</code> , or, if an optional env argument is provided, in <code>env\$workspace</code>
out.grids	character vector of ESRI ASCII/float output file names; defaults to in.sgrds with the file extension being replaced by .asc or .flt, depending on format. Files will be placed in folder out.path, existing files will be overwritten
out.path	folder for out.grids
format	output file format, either "ascii" (default; equivalent: format=1) for ASCII grids or "binary" (equivalent: 0) for binary ESRI grids (.flt).
georef	character: "corner" (equivalent numeric code: 0) or "center" (default; equivalent: 1). Determines whether the georeference will be related to the center or corner of its extreme lower left grid cell.

prec number of digits when writing floating point values to ASCII grid files; either a single number (to be replicated if necessary), or a numeric vector of length `length(in.grids)`

... optional arguments to be passed to [rsaga.geoprocessor](#), including the env RSAGA geoprocessing environment

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

This function uses module 0 from the SAGA library `io_grid`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.esri.wrapper](#) for an efficient way of applying RSAGA to ESRI ASCII/binary grids; [rsaga.env](#)

<code>rsaga.sink.removal</code>	<i>Sink Removal Remove sinks from a digital elevation model by deepening drainage routes or filling sinks.</i>
---------------------------------	--

Description

Sink Removal Remove sinks from a digital elevation model by deepening drainage routes or filling sinks.

Usage

```
rsaga.sink.removal(in.dem, in.sinkroute, out.dem,
  method = "fill", ...)
```

Arguments

<code>in.dem</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: <code>.sgrd</code>)
<code>in.sinkroute</code>	optional input: sink route grid file
<code>out.dem</code>	output: modified DEM
<code>method</code>	character string or numeric value specifying the algorithm (partial string matching will be applied): "deepen drainage route" (or 0): reduce the elevation of pixels in order to achieve drainage out of the former sinks "fill sinks" (or 1): fill sinks until none are left

... optional arguments to be passed to [rsaga.geoprocessor](#), including the env RSAGA geoprocessing environment

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

This function uses module 1 from SAGA library `ta_preprocessor`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.sink.route](#), [rsaga.fill.sinks](#)

Examples

```
## Not run: rsaga.sink.route("dem","sinkroute")
rsaga.sink.removal("dem","sinkroute","dem-preproc",method="deepen")
## End(Not run)
```

rsaga.sink.route	<i>Sink Drainage Route Detection</i>
------------------	--------------------------------------

Description

Sink drainage route detection.

Usage

```
rsaga.sink.route(in.dem,out.sinkroute, threshold,
  thrsheight = 100, ...)
```

Arguments

<code>in.dem</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: <code>.sgrd</code>)
<code>out.sinkroute</code>	output: sink route grid file: non-sinks obtain a value of 0, sinks are assigned an integer between 0 and 8 indicating the direction to which flow from this sink should be routed
<code>threshold</code>	logical: use a threshold value?
<code>thrsheight</code>	numeric: threshold value (default: 100)

... optional arguments to be passed to [rsaga.geoprocessor](#), including the env RSAGA geoprocessing environment

Value

The type of object returned depends on the `intern` argument passed to the [rsaga.geoprocessor](#). For `intern=FALSE` it is a numerical error code (0: success), or otherwise (default) a character vector with the module's console output.

Note

I assume that flow directions are coded as 0 = north, 1 = northeast, 2 = east, ..., 7 = northwest, as in [rsaga.fill.sinks](#).

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

See Also

[rsaga.sink.removal](#)

Examples

```
## Not run: rsaga.sink.route("dem","sinkroute")
rsaga.sink.removal("dem","sinkroute","dem-preproc",method="deepen")
## End(Not run)
```

`rsaga.solar.radiation` *Potential incoming solar radiation*

Description

This function calculates the potential incoming solar radiation in an area either using a lumped atmospheric transmittance model or estimating it based on water and dust content. Use [rsaga.pisr](#) instead with SAGA GIS 2.0.6+.

Usage

```
rsaga.solar.radiation(in.dem, out.grid, out.duration,
  latitude, unit = c("kWh/m2", "J/m2"), solconst = 1367,
  method = c("lumped", "components"), transmittance = 70,
  pressure = 1013, water.content = 1.68, dust = 100,
  time.range = c(0, 24), time.step = 1,
  days = list(day = 21, month = 3), day.step = 5,
  env = rsaga.env(), ...)
```

Arguments

<code>in.dem</code>	name of input digital elevation model (DEM) grid in SAGA grid format (default extension: <code>.sgrd</code>)
<code>out.grid</code>	output grid file for potential incoming solar radiation sums
<code>out.duration</code>	Optional output grid file for duration of insolation
<code>latitude</code>	Geographical latitude in degree North (negative values indicate southern hemisphere)
<code>unit</code>	unit of the <code>out.grid</code> output: "kWh/m2" (default) or "J/m2"
<code>solconst</code>	solar constant, defaults to 1367 W/m2
<code>method</code>	specifies how the atmospheric components should be accounted for: either based on a lumped atmospheric transmittance as specified by argument <code>transmittance</code> ("lumped", or numeric code 0; default); or by calculating the components corresponding to water and dust ("components", code 1)
<code>transmittance</code>	transmittance of the atmosphere in percent; usually between 60 (humid areas) and 80 percent (deserts)
<code>pressure</code>	atmospheric pressure in mbar
<code>water.content</code>	water content of a vertical slice of the atmosphere in cm: between 1.5 and 1.7cm, average 1.68cm (default)
<code>dust</code>	dust factor in ppm; defaults to 100ppm
<code>time.range</code>	numeric vector of length 2: time span (hours of the day) for numerical integration
<code>time.step</code>	time step in hours for numerical integration
<code>days</code>	either a list with components <code>day</code> and <code>month</code> specifying a single day of the year for radiation modeling; OR a numeric vector of length 2 specifying the start and end date (see Note below)
<code>day.step</code>	if <code>days</code> indicates a range of days, this specifies the time step (number of days) for calculating the incoming solar radiation
<code>env</code>	RSAGA geoprocessing environment obtained with rsaga.env ; this argument is required for version control (see Note)
<code>...</code>	optional arguments to be passed to rsaga.geoprocessor

Note

This module ceased to exist under SAGA GIS 2.0.6+, which has a similar (but more flexible) module Potential Solar Radiation that is interfaced by [rsaga.pisr](#).

SAGA_CMD uses zero-based days and months, but this R function uses the standard one-based days and months (e.g. day 1 is the first day of the month, month 1 is January) and translates to the SAGA system.

In SAGA 2.0.2, solar radiation sums calculated for a range of days, say `days=c(a,b)` actually calculate radiation only for days `a, ..., b-1` (in steps of `day.step` - I used `day.step=1` in this example). The setting `a=b` however gives the same result as `b=a+1`, and indeed `b=a+2` gives twice the radiation sums and potential sunshine duration that `a=b` and `b=a+1` both give.

The solar radiation module of SAGA 2.0.1 had a bug that made it impossible to pass a range of days of the year or a range of hours of the day (`time.range`) to SAGA. These options work in SAGA 2.0.1.

This function uses module Incoming Solar Radiation from SAGA GIS library `ta_lighting`.

Author(s)

Alexander Brenning (R interface), Olaf Conrad (SAGA module)

References

Wilson, J.P., Gallant, J.C. (eds.), 2000: Terrain analysis - principles and applications. New York, John Wiley & Sons.

See Also

[rsaga.hillshade](#), [rsaga.insolation](#)

Examples

```
## Not run:
# potential solar radiation on Nov 7 in Southern Ontario...
rsaga.solar.radiation("dem", "solrad", "soldur", latitude=43,
  days=list(day=7, month=11), time.step=0.5)

## End(Not run)
```

rsaga.target

Define target grid for interpolation

Description

Define the resolution and extent of a target grid for interpolation by SAGA modules based on (1) user-provided x/y coordinates, (2) an existing SAGA grid file, or (3) the header data of an ASCII grid. Intended to be used with RSAGA's interpolation functions. Currently works with SAGA GIS 2.0.5 - 2.0.8 and partially with SAGA GIS 2.1.0 (not with `target="target.grid"`).

Usage

```
rsaga.target(target = c("user.defined", "target.grid", "header"),
  user.cellsize = 100, user.x.extent, user.y.extent,
  target.grid, header, env = rsaga.env())
```


Arguments

target	character: method used for defining the target grid; note: "target.grid" currently doesn't seem to work in SAGA GIS 2.1.0
user.cellsize	Only for target="user.defined": raster resolution (in the grid's map units)
user.x.extent	See user.y.extent
user.y.extent	Only for target="user.defined": numeric vectors of length 2: minimum and maximum coordinates of grid cell center points
target.grid	Only for target="target.grid": character string giving the name of a SAGA grid file that specifies the extent and resolution of the target grid; this target grid file may be overwritten, depending on the specifics of the SAGA GIS module used.
header	Only for target="header": list: ASCII grid header (as returned e.g. by read.ascii.grid.header) or defined manually; must at least have components ncols, nrows, cellsize, and either x/yllcorner or x/yllcenter.
env	A SAGA geoprocessing environment, see rsaga.env.)

Note

This function is to be used with RSAGA functions [rsaga.inverse.distance](#), [rsaga.nearest.neighbour](#) and [rsaga.modified.quadratic.shephard](#). Note that these are currently only compatible with SAGA GIS 2.0.5 and higher, and that SAGA GIS 2.1.0 has some yet unresolved issues with the target grid parameterization (target="target.grid").

See Also

[read.ascii.grid.header](#)

Examples

```
## Not run:
# IDW interpolation of attribute "z" from the point shapefile
# 'points.shp' to a grid with the same extent and resolution
# as the (pre-existing) geology grid:
rsaga.inverse.distance("points", "dem", field = "z", maxdist = 1000,
  target = rsaga.target(target="target.grid",
    target.grid = "geology"))

## End(Not run)
```

rsaga.wetness.index *SAGA Modules SAGA Wetness Index*

Description

Calculate the SAGA Wetness Index (SWI), a modified topographic wetness index (TWI)

Usage

```
rsaga.wetness.index(in.dem, out.wetness.index, out.carea,
  out.cslope, out.mod.carea, suction, area.type,
  slope.type, slope.min, slope.offset, slope.weight,
  t.param, env = rsaga.env(), ...)
```

Arguments

<code>in.dem</code>	input: digital elevation model (DEM) as SAGA grid file (default file extension: <code>.sgrd</code>)
<code>out.wetness.index</code>	output file (optional): wetness index grid file name. Existing files of the same name will be overwritten!
<code>out.carea</code>	output file (optional): catchment area grid file name
<code>out.cslope</code>	output file (optional): catchment slope grid file name
<code>out.mod.carea</code>	output file (optional): file name of modified catchment area grid
<code>suction</code>	SAGA GIS 2.1.0+: positive numeric value (optional): the lower this value is the stronger is the suction effect; defaults to a value of 10 (more detailed information is currently not available in the SAGA GIS documentation)
<code>area.type</code>	character or numeric (optional): type of area: "absolute" (or numeric code 0): absolute catchment area; "square root" (code 1; the default): square root of catchment area; "specific" (code 2): specific catchment area
<code>slope.type</code>	character or numeric (optional): type of slope: "local" (or numeric code 0): local slope; "catchment" (or code 1; the default): catchment slope.
<code>slope.min</code>	numeric (optional): minimum slope; default: 0
<code>slope.offset</code>	numeric (optional): offset slope; default: 0.1
<code>slope.weight</code>	numeric (optional): weighting factor for slope in index calculation; default: 1
<code>t.param</code>	SAGA GIS up to version 2.0.8: positive numeric value (optional): undocumented
<code>env</code>	A SAGA geoprocessing environment, see rsaga.env()
<code>...</code>	optional arguments to be passed to rsaga.geoprocessor

Details

The SAGA Wetness Index is similar to the Topographic Wetness Index (TWI), but it is based on a modified catchment area calculation (`out.mod.carea`), which does not treat the flow as a thin film as done in the calculation of catchment areas in conventional algorithms. As a result, the SWI tends to assign a more realistic, higher potential soil wetness than the TWI to grid cells situated in valley floors with a small vertical distance to a channel.

This module and its arguments changed substantially from SAGA GIS 2.0.8 to version 2.1.0. It appears to me that the new algorithm is similar (but not identical) to the old one when using `area.type="absolute"` and `slope.type="local"` but I haven't tried out all possible options. This help file will be updated as soon as additional documentation becomes available.

Value

The type of object returned depends on the `intern` argument passed to the `rsaga.geoprocessor`. For `intern=FALSE` it is a numerical error code (0: success), or otherwise (the default) a character vector with the module's console output.

Author(s)

Alexander Brenning (R interface), Juergen Bochner and Olaf Conrad (SAGA module)

References

Bochner, J., Koethe, R. Conrad, O., Gross, J., Ringeler, A., Selige, T. (2002): Soil Regionalisation by Means of Terrain Analysis and Process Parameterisation. In: Micheli, E., Nachtergaele, F., Montanarella, L. (ed.): Soil Classification 2001. European Soil Bureau, Research Report No. 7, EUR 20398 EN, Luxembourg. pp.213-222.

See Also

[rsaga.parallel.processing](#), [rsaga.geoprocessor](#), [rsaga.env](#)

Examples

```
## Not run:  
# using SAGA grids:  
rsaga.wetness.index("dem.sgrd", "swi.sgrd")  
  
## End(Not run)
```

set.file.extension *Determine or modify file name extensions*

Description

Function `get.file.extension` determines the file extension, `set.file.extension` changes it, and `default.file.extension` changes it only if it is not already specified.

Usage

```
set.file.extension(filename, extension,  
  fsep = .Platform$file.sep)  
  
get.file.extension(filename, fsep = .Platform$file.sep)  
  
default.file.extension(filename, extension,  
  force = FALSE)
```

Arguments

filename	character vector: file name(s), possibly including paths and extensions; a file name ending with a "." is interpreted as having extension "", while a file name that doesn't contain a "." is interpreted as having no extension.
extension	character string: file extension, without the dot
fsep	character: separator between paths
force	logical argument to default.file.extension: force the file extension to be extension (same result as set.file.extension), or only set it to extension if it has not been specified?

Value

character vector of same length as filename

Examples

```
fnm = c("C:/TEMP.DIR/temp", "C:/TEMP.DIR/tmp.txt", "tempfile.")
get.file.extension(fnm)
set.file.extension(fnm, extension=".TMP")
default.file.extension(fnm, extension=".TMP")
```

wind.shelter

Wind Shelter Index

Description

wind.shelter is a function to be used with [focal.function](#) to calculate a topographic wind shelter index from a digital elevation model, which is a proxy for snow accumulation on the lee side of topographic obstacles. wind.shelter.prep performs some preparatory calculations to speed up repeated calls to wind.shelter.

Usage

```
wind.shelter(x, prob = NULL, control)

wind.shelter.prep(radius, direction, tolerance,
  cellsize = 90)
```

Arguments

x	square matrix of elevation data
prob	numeric: quantile of slope values to be used in computing the wind shelter index; if NULL, use max (equivalent to prob=1)
control	required argument: the result of a call to wind.shelter.prep
radius	radius (>1) of circle segment to be used (number of grid cells, not necessarily an integer)

direction	wind direction: direction from which the wind originates; North = 0 = 2*pi, clockwise angles.
tolerance	directional tolerance
cellsize	grid cellsize

Details

wind.shelter implements a wind shelter index used by Plattner et al. (2004) for modeling snow accumulation patterns on a glacier in the Austrian Alps. It is a modified version of the algorithm of Winstral et al. (2002). The wind shelter index of Plattner et al. (2004) is defined as:

$$\text{Shelter index}(S) = \arctan(\max((z(x_0) - z(x)) / |x_0 - x| : x \text{ in } S)),$$

where $S = S(x_0, a, da, d)$ is the set of grid nodes within a distance $\leq d$ from x_0 , only considering grid nodes in directions between $a - da$ and $a + da$ from x_0 .

The present implementation generalizes this index by replacing max by the quantile function; the max function is used if prob=NULL, and the same result is obtained for prob=1 using the quantile function.

Value

The function wind.shelter returns the wind shelter index as described above if a numeric matrix x is provided. If it is missing, it returns the character string "windshelter".

wind.shelter.prep returns a list with components mask and dist. Both are square matrices with $2 * (\text{ceiling}(\text{radius}) + 1)$ columns and rows:

mask	indicates which grid cell in the moving window is within the specified circle segment (value FALSE) or not (TRUE)
dist	the precomputed distances of a grid cell to the center of the moving window, in map units

Note

The wind shelter index only makes sense if elevation is measured in the same units as the horizontal map units used for the cellsize argument (i.e. usually meters).

wind.shelter and wind.shelter.prep do not restrict the calculation to a circular area; this is done by focal.function when used in combination with that function (assuming search.mode="circle").

Note that the present definition of the wind shelter index returns negative values for surfaces that are completely exposed toward the specified direction. This may make sense if interpreted as a "wind exposure index", or it might be appropriate to set negative wind shelter values to 0.

Author(s)

Alexander Brenning

References

Plattner, C., Braun, L.N., Brenning, A. (2004): Spatial variability of snow accumulation on Vernagtferner, Austrian Alps, in winter 2003/2004. Zeitschrift fuer Gletscherkunde und Glazialgeologie, 39: 43-57.

Winstral, A., Elder, K., Davis, R.E. (2002): Spatial snow modeling of wind-redistributed snow using terrain-based parameters. Journal of Hydrometeorology, 3: 524-538.

See Also

[focal.function](#), [quantile](#)

Examples

```
# Settings used by Plattner et al. (2004):  
ctrl = wind.shelter.prep(6,-pi/4,pi/12,10)  
## Not run: focal.function("dem.asc", fun=wind.shelter, control=ctrl,  
  radius=6, search.mode="circle")  
## End(Not run)
```

Index

*Topic **file**

- read.ascii.grid, 21
- rsaga.esri.to.sgrd, 33
- rsaga.import.gdal, 51
- rsaga.sgrd.to.esri, 67
- set.file.extension, 75

*Topic **interface**

- read.ascii.grid, 21
- rsaga.add.grid.values.to.points, 26
- rsaga.close.gaps, 27
- rsaga.contour, 28
- rsaga.copy.sgrd, 29
- rsaga.env, 30
- rsaga.esri.to.sgrd, 33
- rsaga.esri.wrapper, 34
- rsaga.fill.sinks, 35
- rsaga.filter.gauss, 37
- rsaga.filter.simple, 38
- rsaga.geoprocessor, 39
- rsaga.get.modules, 42
- rsaga.get.usage, 44
- rsaga.get.version, 45
- rsaga.grid.calculus, 46
- rsaga.grid.to.points, 48
- rsaga.hillshade, 49
- rsaga.html.help, 50
- rsaga.import.gdal, 51
- rsaga.insolation, 55
- rsaga.inverse.distance, 57
- rsaga.lib.prefix, 58
- rsaga.local.morphometry, 59
- rsaga.parallel.processing, 62
- rsaga.pisr, 64
- rsaga.sgrd.to.esri, 67
- rsaga.sink.removal, 68
- rsaga.sink.route, 69
- rsaga.solar.radiation, 70
- rsaga.target, 72

- rsaga.wetness.index, 73

*Topic **spatial**

- focal.function, 5
- grid.predict, 8
- grid.to.xyz, 10
- multi.focal.function, 13
- pick.from.shapefile, 17
- read.ascii.grid, 21
- relative.position, 24
- resid.median, 25
- rsaga.add.grid.values.to.points, 26
- rsaga.close.gaps, 27
- rsaga.contour, 28
- rsaga.copy.sgrd, 29
- rsaga.env, 30
- rsaga.esri.to.sgrd, 33
- rsaga.esri.wrapper, 34
- rsaga.fill.sinks, 35
- rsaga.filter.gauss, 37
- rsaga.filter.simple, 38
- rsaga.geoprocessor, 39
- rsaga.get.modules, 42
- rsaga.get.usage, 44
- rsaga.get.version, 45
- rsaga.grid.calculus, 46
- rsaga.grid.to.points, 48
- rsaga.hillshade, 49
- rsaga.import.gdal, 51
- rsaga.insolation, 55
- rsaga.inverse.distance, 57
- rsaga.lib.prefix, 58
- rsaga.local.morphometry, 59
- rsaga.parallel.processing, 62
- rsaga.pisr, 64
- rsaga.sgrd.to.esri, 67
- rsaga.sink.removal, 68
- rsaga.sink.route, 69
- rsaga.solar.radiation, 70

- rsaga.target, 72
- rsaga.wetness.index, 73
- wind.shelter, 76
- *Topic **utilities**
 - centervalue, 4
 - create.variable.name, 4
 - match.arg.ext, 11
 - rsaga.html.help, 50
 - set.file.extension, 75
- abbreviate, 7
- browseURL, 51
- centervalue, 4, 24, 25
- create.variable.name, 4, 7, 19
- ddply, 19
- default.file.extension
 - (set.file.extension), 75
- focal.function, 4, 5, 10, 15, 16, 24, 25, 47, 76–78
- gapply (focal.function), 5
- get.file.extension
 - (set.file.extension), 75
- grid.predict, 8, 13–16
- grid.to.xyz, 10, 21
- idw, 58
- internal.pick.from.ascii.grid
 - (pick.from.shapefile), 17
- krige, 18, 21
- local.function, 47
- local.function (focal.function), 5
- match.arg, 11, 12
- match.arg.ext, 11
- median, 25
- multi.focal.function, 7–10, 13, 47
- multi.local.function, 7–10
- multi.local.function
 - (multi.focal.function), 13
- na.exclude, 15
- na.pass, 15
- options, 31, 40
- pick.from.ascii.grid, 11, 26, 31
 - (pick.from.shapefile), 17
- pick.from.ascii.grid
 - (pick.from.shapefile), 17
- pick.from.points, 26
- pick.from.points (pick.from.shapefile), 17
- pick.from.saga.grid, 26
- pick.from.saga.grid
 - (pick.from.shapefile), 17
- pick.from.shapefile, 17
- pmatch, 12
- predict, 8, 9
- quantile, 25, 78
- rank, 24
- read.ascii.grid, 11, 21, 21
- read.ascii.grid.header, 73
- read.Rd.grid (read.ascii.grid), 21
- read.sgrd (read.ascii.grid), 21
- relative.position, 7, 24
- relative.rank, 7
- relative.rank (relative.position), 24
- resid.median, 4, 7, 25
- resid.minmedmax, 7
- resid.minmedmax (resid.median), 25
- resid.quantile, 7
- resid.quantile (resid.median), 25
- resid.quartiles, 7
- resid.quartiles (resid.median), 25
- RSAGA-package, 3
- rsaga.add.grid.values.to.points, 26, 49
- rsaga.aspect (rsaga.local.morphometry), 59
- rsaga.close.gaps, 27, 34
- rsaga.close.one.cell.gaps
 - (rsaga.close.gaps), 27
- rsaga.contour, 28
- rsaga.copy.sgrd, 29
- rsaga.curvature
 - (rsaga.local.morphometry), 59
- rsaga.default.modules.path
 - (rsaga.default.path), 29
- rsaga.default.path, 29
- rsaga.env, 3, 19, 28–30, 30, 31, 33–35, 40–48, 51, 52, 58–62, 64, 66–68, 71, 73–75

- rsaga.esri.to.sgrd, [33](#), [34](#), [35](#)
- rsaga.esri.wrapper, [33](#), [34](#), [41](#), [68](#)
- rsaga.fill.sinks, [35](#), [69](#), [70](#)
- rsaga.filter.gauss, [37](#), [39](#)
- rsaga.filter.simple, [38](#), [38](#)
- rsaga.geoprocessor, [19](#), [26–28](#), [33–38](#), [39](#),
[43–48](#), [50](#), [51](#), [56](#), [58](#), [60–64](#), [66](#),
[68–71](#), [74](#), [75](#)
- rsaga.get.lib.modules, [40](#)
- rsaga.get.lib.modules
(rsaga.get.modules), [42](#)
- rsaga.get.libraries, [41](#)
- rsaga.get.libraries
(rsaga.get.modules), [42](#)
- rsaga.get.modules, [31](#), [41](#), [42](#), [44](#)
- rsaga.get.usage, [41](#), [43](#), [44](#), [51](#)
- rsaga.get.version, [31](#), [32](#), [45](#)
- rsaga.grid.calculus, [46](#)
- rsaga.grid.to.points, [26](#), [48](#)
- rsaga.hillshade, [34](#), [41](#), [44](#), [49](#), [51](#), [56](#), [67](#),
[72](#)
- rsaga.html.help, [43](#), [44](#), [50](#)
- rsaga.import.gdal, [51](#)
- rsaga.insolation, [50](#), [55](#), [67](#), [72](#)
- rsaga.inverse.distance, [29](#), [57](#), [73](#)
- rsaga.lib.prefix, [31](#), [58](#)
- rsaga.linear.combination
(rsaga.grid.calculus), [46](#)
- rsaga.local.morphometry, [44](#), [59](#)
- rsaga.modified.quadratic.shephard, [73](#)
- rsaga.modified.quadratic.shephard
(rsaga.inverse.distance), [57](#)
- rsaga.module.exists, [40](#)
- rsaga.module.exists
(rsaga.get.modules), [42](#)
- rsaga.nearest.neighbour, [73](#)
- rsaga.nearest.neighbour
(rsaga.inverse.distance), [57](#)
- rsaga.parallel.processing, [61](#), [62](#), [75](#)
- rsaga.pisr, [31](#), [40](#), [56](#), [64](#), [70](#), [71](#)
- rsaga.plan.curvature
(rsaga.local.morphometry), [59](#)
- rsaga.profile.curvature
(rsaga.local.morphometry), [59](#)
- rsaga.search.modules, [41](#)
- rsaga.search.modules
(rsaga.get.modules), [42](#)
- rsaga.sgrd.to.esri, [34](#), [35](#), [67](#)
- rsaga.sink.removal, [37](#), [68](#), [70](#)
- rsaga.sink.route, [37](#), [69](#), [69](#)
- rsaga.slope (rsaga.local.morphometry),
[59](#)
- rsaga.solar.radiation, [50](#), [56](#), [67](#), [70](#)
- rsaga.target, [57](#), [58](#), [72](#)
- rsaga.triangulation
(rsaga.inverse.distance), [57](#)
- rsaga.wetness.index, [64](#), [73](#)
- scan, [6](#), [15](#), [19](#), [23](#)
- set.file.extension, [75](#)
- Sys.info, [30](#)
- system, [19](#), [39](#), [40](#)
- vgm, [18](#)
- wind.shelter, [7](#), [76](#)
- write.ascii.grid, [21](#)
- write.ascii.grid (read.ascii.grid), [21](#)
- write.ascii.grid.header, [6](#), [15](#)
- write.Rd.grid (read.ascii.grid), [21](#)
- write.sgrd (read.ascii.grid), [21](#)
- write.shapefile, [58](#)
- writeAsciiGrid, [24](#)
- writeGDAL, [23](#), [24](#)