

# Package ‘gamboostLSS’

July 2, 2014

**Type** Package

**Title** Boosting Methods for GAMLSS

**Version** 1.1-2

**Date** 2014-06-25

**Author** Benjamin Hofner, Andreas Mayr, Nora Fenske, Matthias Schmid

**Maintainer** Benjamin Hofner <benjamin.hofner@fau.de>

**Description** Boosting models for fitting generalized additive models for location, shape and scale (GAMLSS) to potentially high dimensional data.

**Depends** R (>= 2.10.0), mboost (>= 2.3-0)

**Suggests** gamlss, BayesX, gamlss.dist, survival

**LazyLoad** yes

**LazyData** yes

**License** GPL-2

**URL** For development versions and source code see  
<http://r-forge.r-project.org/projects/gamboostlss/>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2014-06-26 11:02:48

## R topics documented:

gamboostLSS-package . . . . .	2
as.families . . . . .	3
cvrisk.mboostLSS . . . . .	5
Families . . . . .	9
india . . . . .	13
mboostLSS . . . . .	15
methods . . . . .	19

---

gamboostLSS-package     *Boosting algorithms for GAMLSS*

---

## Description

Boosting methods for fitting generalized additive models for location, scale and shape (GAMLSS).

## Details

This package uses boosting algorithms for fitting GAMLSS (generalized additive models for location, scale and shape). For information on GAMLSS theory see Rigby and Stasinopoulos (2005), or the information provided at <http://gamlss.org>.

The fitting methods `glmboostLSS` and `gamboostLSS`, are alternatives for the algorithms provided with `gamlss` in the `gamlss` package. They offer shrinkage of effect estimates, intrinsic variable selection and model choice for potentially high-dimensional data settings.

`glmboostLSS` (for linear effects) and `gamboostLSS` (for smooth effects) depend on their analogous companions `glmboost` and `gamboost` for generalized additive models (contained in package `mboost`, see Hothorn et al. 2010a, b) and are similar in their usage.

The package includes some pre-defined GAMLSS distributions, but the user can also specify new distributions with `Families`.

A wide range of different base-learners is available for covariate effects (see `baselearners`) including linear (`bo1s`), non-linear (`bbs`), random (`brandom`) or spatial effects (`bspatial` or Markov random fields `bmrf`). Each base-learner can be included separately for each predictor. The selection of base-learners is crucial as it implies the kind of effect the covariate has on each distribution parameter in the final GAMLSS.

## Author(s)

Benjamin Hofner, Andreas Mayr, Nora Fenske, Matthias Schmid

Maintainer: Benjamin Hofner <[benjamin.hofner@imbe.med.uni-erlangen.de](mailto:benjamin.hofner@imbe.med.uni-erlangen.de)>

## References

Mayr, A., Fenske, N., Hofner, B., Kneib, T. and Schmid, M. (2012): Generalized additive models for location, scale and shape for high-dimensional data - a flexible approach based on boosting. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 61(3): 403-427.

M. Schmid, S. Potapov, A. Pfahlberg, and T. Hothorn. Estimation and regularization techniques for regression models with multidimensional prediction functions. *Statistics and Computing*, 20(2):139-150, 2010.

Rigby, R. A. and D. M. Stasinopoulos (2005). Generalized additive models for location, scale and shape (with discussion). *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, 54, 507-554.

Stasinopoulos, D. M. and R. A. Rigby (2007). Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software* 23(7).

Buehlmann, P. and Hothorn, T. (2007). Boosting algorithms: Regularization, prediction and model fitting. *Statistical Science*, 22(4), 477–505.

Hothorn, T., Buehlmann, P., Kneib, T., Schmid, M. and Hofner, B. (2010a). Model-based boosting 2.0. *Journal of Machine Learning Research* 11(Aug), 2109-2113.

Hothorn, T., Buehlmann, P., Kneib, T., Schmid, M. and Hofner, B. (2010b). mboost: Model-based boosting 2.0. R package version 2.0-9. <http://cran.r-project.org/web/packages/mboost>

### See Also

[gamboostLSS](#) and [glmboostLSS](#) for model fitting. Available distributions (families) are documented here: [Families](#).

See also the [mboost](#) package for more on model-based boosting, or the [gamLSS](#) package for the original GAMLSS algorithms provided by Rigby and Stasinopoulos.

### Examples

```
# Generate covariates
x1 <- runif(100)
x2 <- runif(100)
eta_mu <- 2 - 2*x1
eta_sigma <- -1 + 2*x2

# Generate response: Negative Binomial Distribution
y <- numeric(100)
for( i in 1:100) y[i] <- rnbinom(1, size=exp(eta_sigma[i]), mu=exp(eta_mu[i]))

# Model fitting, 300 boosting steps, same formula for both distribution parameters
mod1 <- glmboostLSS( y ~ x1 + x2, families=NBinomialLSS(),
  control=boost_control(mstop=300), center = TRUE)

# Shrinked effect estimates
coef(mod1, off2int=TRUE)

# Empirical risk with respect to mu
plot(risk(mod1)$mu)

# Empirical risk with respect to sigma
plot(risk(mod1)$sigma)
```

---

as.families

*Include gamLSS families in the boosting framework of gamboostLSS*

---

### Description

The function `as.families()` provides an interface to apply the available distributions (families) of the `gamLSS.dist` package for boosting GAMLSS via `gamboostLSS`.

The function automatically builds sub-families for every distribution parameter and uses the constructor function [Families](#) to build a `families` object, which can be then included in the fitting functions [gamboostLSS](#) and [glmboostLSS](#).

**Usage**

```
as.families(fname = "NO", mu = NULL, sigma = NULL,
            nu = NULL, tau = NULL)

## a wrapper to as.families:
gamlss.Families(...)

#### Turn the stability correction on or off:
## use options(gamboostLSS_stab_ngrad = TRUE) ## on
## or options(gamboostLSS_stab_ngrad = FALSE) ## off
```

**Arguments**

fname	name of the distribution in the <code>gamlss</code> framework, as specified in the <code>gamlss.dist</code> package (e.g., "NO" for a normal distribution with parameters <code>mu</code> and <code>sigma</code> ). Alternatively, one can directly specify the function (i.e., <code>NO</code> ) or the evaluated function <code>NO()</code> .
mu	possible offset value for parameter <code>mu</code> .
sigma	possible offset value for parameter <code>sigma</code> .
nu	possible offset value for parameter <code>nu</code> .
tau	possible offset value for parameter <code>tau</code> .
...	same arguments as above.

**Details**

The function aims at providing an interface to include all available GAMLSS distributions which are implemented with the original `gamlss.dist` package in the model-based boosting framework. The user specifies the name of the family (as it is called in `gamlss.dist`), and the function automatically builds the corresponding `mboost`-like sub-families and the final `families` object, which can be then used with the fitting functions `gamboostLSS` and `glmboostLSS`.

To extract the necessary information regarding partial derivatives (for the `ngradient` - see [Family](#) for details) and the log-likelihood (for the loss) the `gamlss.dist` package is loaded. If the package is not installed yet, this will prompt an error message.

The functions `gamlss1parMu`, `gamlss2parMu`, `gamlss2parSigma`, ... , `gamlss4parTau` are called internally to construct the sub-families. For one-parametric distributions, the function will prompt a warning and returns a `mboost` family, which can be then used by the fitting functions of the `mboost` package.

For information on GAMLSS theory see Rigby and Stasinopoulos (2005), lists of available distributions are provided at <http://gamlss.org>. For more on details boosting GAMLSS see Mayr et al., 2012.

**Value**

An object of class `families`. If the user specifies a one-parametric distribution, an object of class `family` is returned.

**Author(s)**

The help of Mikis Stasinopoulos during the work on this function is gratefully acknowledged.

**References**

Mayr, A., Fenske, N., Hofner, B., Kneib, T. and Schmid, M. (2012): Generalized additive models for location, scale and shape for high-dimensional data - a flexible approach based on boosting. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 61(3): 403-427.

Rigby, R. A. and D. M. Stasinopoulos (2005). Generalized additive models for location, scale and shape (with discussion). *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, 54, 507-554.

**See Also**

`gamlss.dist` for available distributions in the `gamlss` framework.

[Families](#) for a documentation of pre-implemented distributions for `gamboostLSS`, as well as possibilities for user-defined distributions.

**Examples**

```
## simulate small example
set.seed(123)
x <- runif(1000)

y <- rnorm(mean = 2 + 3 * x,          # effect on mu
           sd   = exp( 1 - 1 * x ), # effect on sigma
           n    = 1000)

## boosting
glmss <- glmboostLSS(y ~ x, families = as.families("NO"))
## the same:
glmss <- glmboostLSS(y ~ x, families = as.families(NO))
glmss <- glmboostLSS(y ~ x, families = as.families(NO()))

coef(glmss, off2int = TRUE)

## compare to gamlss
library(gamlss)
glmss2 <- gamlss(y ~ x, sigma.formula = ~x, family = "NO")
coef(glmss2)
glmss2$sigma.coef
```

**Description**

Multidimensional cross-validated estimation of the empirical risk for hyper-parameter selection.

**Usage**

```
## S3 method for class 'mboostLSS'
cvrisk(object, folds = cv(model.weights(object)),
        grid = make.grid(mstop(object)), papply = mclapply,
        trace = TRUE, fun = NULL, ...)

make.grid(max, length.out = 10, min = NULL, log = TRUE,
          dense_mu_grid = TRUE)

## S3 method for class 'cvriskLSS'
plot(x, type = c("heatmap", "lines"),
     xlab = NULL, ylab = NULL, ylim = range(x),
     main = attr(x, "type"), ...)
```

**Arguments**

object	an object of class <code>mboostLSS</code> , i.e., a boosted GAMLSS model.
folds	a weight matrix with number of rows equal to the number of observations. The number of columns corresponds to the number of cross-validation runs. Can be computed using function <code>cv</code> from package <b>mboost</b> and defaults to 25 bootstrap samples.
grid	a matrix of stopping parameters the empirical risk is to be evaluated for. Each row represents a parameter combination. The number of columns must be equal to the number of parameters of the GAMLSS family. Per default, <code>make.grid(mstop(object))</code> is used.
papply	(parallel) apply function, defaults to <code>mclapply</code> . Alternatively, <code>parLapply</code> can be used. In the latter case, usually more setup is needed. To run <code>cvrisk</code> sequentially (i.e. not in parallel), one can use <code>lapply</code> .
trace	should status information be printed during cross-validation? Default: TRUE.
fun	if fun is NULL, the out-of-sample risk is returned. fun, as a function of object, may extract any other characteristic of the cross-validated models. These are returned as is.
...	additional arguments passed to <code>mclapply</code> or the plot function depending on the context.
max	a named vector of length equal to the number of parameters of the GAMLSS family (and names equal to the names of families) that determines the maximal values of the grid.
length.out	the number of grid points (default: 10). This can be either a vector of the same length as max (with different values) or a scalar (which is then used as length for all grids).
min	minimal value of the grid. Per default the grid starts at 1 but other values (smaller max) are possible. This can be either a vector of the same length as max (with different values) or a scalar (which is then used as min for all grids).
log	should the grid be on a logarithmic scale? Default: TRUE.

dense_mu_grid	should the grid in the mu component be extended for all values of the mstop values corresponding to mu that are greater or equal to all other parameters in this combination. These values can be computed without or with very little additional computational costs. For details see examples.
x	an object of class cvriskLSS, which results from running cvrisk.
type	should "lines" or a "heatmap" (default) be plotted? See details.
xlab, ylab	user-specified labels for the x-axis and y-axis of the plot (which are usually not needed). The defaults depend on the plot type.
ylim	limits of the y-axis. Only applicable for the line plot.
main	a title for the plots.

### Details

The number of boosting iterations is a hyper-parameter of the boosting algorithms implemented in this package. Honest, i.e., cross-validated, estimates of the empirical risk for different stopping parameters `mstop` are computed by this function which can be utilized to choose an appropriate number of boosting iterations to be applied. For details see [cvrisk.mboost](#).

`make.grid` eases the creation of an equidistant, integer-valued grids, which can be used with `cvrisk`. Per default, the grid is equidistant on a logarithmic scale.

The line plot depicts the average risk for each grid point and additionally shows information on the variability of the risk from fold to fold. The heatmap shows only the average risk but in a nicer fashion.

### Value

An object of class `cvriskLSS` (when `fun` wasn't specified), basically a matrix containing estimates of the empirical risk for a varying number of bootstrap iterations. `plot` and `print` methods are available as well as an `mstop` method.

### See Also

[cvrisk.mboost](#) and [cv](#) (both in package `mboost`)

### Examples

```
## Data generating process:
set.seed(1907)
x1 <- rnorm(1000)
x2 <- rnorm(1000)
x3 <- rnorm(1000)
x4 <- rnorm(1000)
x5 <- rnorm(1000)
x6 <- rnorm(1000)
mu   <- exp(1.5 + 1 * x1 + 0.5 * x2 - 0.5 * x3 - 1 * x4)
sigma <- exp(-0.4 * x3 - 0.2 * x4 + 0.2 * x5 + 0.4 * x6)
y <- numeric(1000)
for( i in 1:1000)
  y[i] <- rbinom(1, size = sigma[i], mu = mu[i])
```

```

dat <- data.frame(x1, x2, x3, x4, x5, x6, y)

## linear model with y ~ . for both components: 100 boosting iterations
model <- glmboostLSS(y ~ ., families = NBinomialLSS(), data = dat,
                    control = boost_control(mstop = 100),
                    center = TRUE)

## set up a grid
grid <- make.grid(mstop(model), length.out = 5, dense_mu_grid = FALSE)
plot(grid)

### a tiny toy example (5-fold bootstrap with maximum stopping value 100)
## (to run it on multiple cores of a Linux or Mac OS computer remove
## set papply = mclapply (default) and set mc.nodes to the
## appropriate number of nodes)
cvr <- cvrisk(model, folds = cv(model.weights(model), B = 5),
              papply = lapply, grid = grid)

cvr
## plot the results
par(mfrow = c(1, 2))
plot(cvr)
plot(cvr, type = "lines")
## extract optimal mstop (here: grid to small)
mstop(cvr)

### a more realistic example
grid <- make.grid(c(mu = 400, sigma = 400), dense_mu_grid = FALSE)
plot(grid)
cvr <- cvrisk(model, grid = grid)
mstop(cvr)
## reset model to mstop values:
model[mstop(cvr)]

### Other grids:
plot(make.grid(mstop(model), length.out = 3, dense_mu_grid = FALSE))
plot(make.grid(c(mu = 400, sigma = 400), log = FALSE, dense_mu_grid = FALSE))
plot(make.grid(c(mu = 400, sigma = 400), length.out = 4,
              min = 100, log = FALSE, dense_mu_grid = FALSE))

### Now use dense mu grids
# standard grid
plot(make.grid(c(mu = 100, sigma = 100), dense = FALSE),
     pch = 20, col = "red")
# dense grid for all mstop_mu values greater than mstop_sigma
grid <- make.grid(c(mu = 100, sigma = 100))
points(grid, pch = 20, cex = 0.2)
abline(0,1)

# now with three parameters
grid <- make.grid(c(mu = 100, sigma = 100, df = 30),
                 length.out = c(5, 5, 2), dense = FALSE)
densegrid <- make.grid(c(mu = 100, sigma = 100, df = 30),

```



```

                                length.out = c(5, 5, 2))
par(mfrow = c(1,2))
# first for df = 1
plot(grid[grid$df == 1, 1:2], main = "df = 1", pch = 20, col = "red")
abline(0,1)
abline(v = 1)
# now expand grid for all mu values greater the corresponding sigma
# value (i.e. below the bisecting line) and above df (i.e. 1)
points(densegrid[densegrid$df == 1, 1:2], pch = 20, cex = 0.2)

# now for df = 30
plot(grid[grid$df == 30, 1:2], main = "df = 30", pch = 20, col = "red")
abline(0,1)
abline(v = 30)
# now expand grid for all mu values greater the corresponding sigma
# value (i.e. below the bisecting line) and above df (i.e. 30)
points(densegrid[densegrid$df == 30, 1:2], pch = 20, cex = 0.2)

```

---

Families

*Families for GAMLSS models*


---

## Description

The package provides some pre-defined GAMLSS families, e.g. NBionomialLSS. Objects of the class families provide a convenient way to specify GAMLSS distributions to be fitted by one of the boosting algorithms implemented in this package. By using the function Families, a new object of the class families can be generated.

## Usage

```

#####
# Families for continuous response

# Gaussian distribution
GaussianLSS(mu = NULL, sigma = NULL)

# Student's t-distribution
StudentTLSS(mu = NULL, sigma = NULL, df = NULL)

#####
# Families for continuous non-negative response

# Gamma distribution
GammaLSS(mu = NULL, sigma = NULL)

#####
# Families for fractions and bounded continuous response

```

```

# Beta distribution
BetaLSS(mu = NULL, phi = NULL)

#####
# Families for count data

# Negative binomial distribution
NBinomialLSS(mu = NULL, sigma = NULL)

# Zero-inflated Poisson distribution
ZIPoLSS(mu = NULL, sigma = NULL)

# Zero-inflated negative binomial distribution
ZINBLSS(mu = NULL, sigma = NULL, nu = NULL)

#####
# Families for survival models (accelerated failure time
# models) for data with right censoring

# Log-normal distribution
LogNormalLSS(mu = NULL, sigma = NULL)

# Log-logistic distribution
LogLogLSS(mu = NULL, sigma = NULL)

# Weibull distribution
WeibullLSS(mu = NULL, sigma = NULL)

#####
# Constructor function for new GAMLSS distributions
Families(..., qfun = NULL, name = NULL)

```

### Arguments

...	sub-families to be passed to constructor.
qfun	quantile function. This function can for example be used to compute (marginal) prediction intervals. See <a href="#">predint</a> .
name	name of the families.
mu	offset value for mu.
sigma	offset value for sigma.
phi	offset value for phi.
df	offset value for df.
nu	offset value for nu.

### Details

The arguments of the families are the offsets for each distribution parameter. Offsets can be either scalar, a vector with length equal to the number of observations or NULL (default). In the latter

case, a scalar offset for this component is computed by minimizing the risk function w.r.t. the corresponding distribution parameter (keeping the other parameters fixed).

Note that `gamboostLSS` is not restricted to three components but can handle an arbitrary number of components (which, of course, depends on the GAMLSS distribution). However, it is important that the names (for the offsets, in the sub-families etc.) are chosen *consistently*.

The ZIPoLSS families can be used to fit zero-inflated Poisson models. Here, `mu` and `sigma` refer to the location parameter of the Poisson component (with log link) and the mean of the zero-generating process (with logit link), respectively.

Similarly, ZINBLSS can be used to fit zero-inflated negative binomial models. Here, `mu` and `sigma` refer to the location and scale parameters (with log link) of the negative binomial component of the model. The zero-generating process (with logit link) is represented by `nu`.

The `Families` function can be used to implement a new GAMLSS distribution which can be used for fitting by `mboostLSS`. Thereby, the function builds a list of sub-families, one for each distribution parameter. The sub-families themselves are objects of the class `boost_family`, and can be constructed via the function `Family` of the `mboost` Package.

Arguments to be passed to `Family`: The loss for every distribution parameter (contained in objects of class `boost_family`) is the negative log-likelihood of the corresponding distribution. The `ngradient` is the negative partial derivative of the loss function with respect to the distribution parameter. For a two-parameter distribution (e.g. `mu` and `sigma`), the user therefore has to specify two sub-families with `Family`. The loss is basically the same function for both parameters, only `ngradient` differs. Both sub-families are passed to the `Families` constructor, which returns an object of the class `families`.

### Value

An object of class `families`.

### Author(s)

BetaLSS for boosting beta regression was implemented by Florian Wickler.

### References

Mayr, A., Fenske, N., Hofner, B., Kneib, T. and Schmid, M. (2012): Generalized additive models for location, scale and shape for high-dimensional data - a flexible approach based on boosting. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 61(3): 403-427.

Rigby, R. A. and D. M. Stasinopoulos (2005). Generalized additive models for location, scale and shape (with discussion). *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, 54, 507-554.

### See Also

`as.families` for applying GAMLSS distributions provided in the framework of the `gamLSS` package.

The functions `gamboostLSS` and `glmboostLSS` can be used for model fitting.

See also the corresponding constructor function `Family` in `mboost`.

**Examples**

```

## Example to define a new distribution:
## Students t-distribution with two parameters, df and mu:

## sub-Family for mu
## -> generate object of the class family from the package mboost
newStudentTMu <- function(mu, df){

  # loss is negative log-Likelihood, f is the parameter to be fitted with
  # id link -> f = mu
  loss <- function(df, y, f) {
    -1 * (lgamma((df + 1)/2) - lgamma(1/2) -
          lgamma(df/2) - 0.5 * log(df) -
          (df + 1)/2 * log(1 + (y - f)^2/(df )))
  }
  # risk is sum of loss
  risk <- function(y, f, w = 1) {
    sum(w * loss(y = y, f = f, df = df))
  }
  # ngradient is the negative derivate w.r.t. mu
  ngradient <- function(y, f, w = 1) {
    (df + 1) * (y - f)/(df + (y - f)^2)
  }

  # use the Family constructor of mboost
  Family(ngradient = ngradient, risk = risk, loss = loss,
         response = function(f) f,
         name = "new Student's t-distribution: mu (id link)")
}

## sub-Family for df
newStudentTDf <- function(mu, df){

  # loss is negative log-Likelihood, f is the parameter to be fitted with
  # log-link: exp(f) = df
  loss <- function( mu, y, f) {
    -1 * (lgamma((exp(f) + 1)/2) - lgamma(1/2) -
          lgamma(exp(f)/2) - 0.5 * f -
          (exp(f) + 1)/2 * log(1 + (y - mu)^2/(exp(f) )))
  }
  # risk is sum of loss
  risk <- function(y, f, w = 1) {
    sum(w * loss(y = y, f = f, mu = mu))
  }
  # ngradient is the negative derivate w.r.t. df
  ngradient <- function(y, f, w = 1) {
    exp(f)/2 * (digamma((exp(f) + 1)/2) - digamma(exp(f)/2)) -
    0.5 - (exp(f)/2 * log(1 + (y - mu)^2 / (exp(f) )) -
          (y - mu)^2 / (1 + (y - mu)^2 / exp(f)) * (exp(-f) + 1)/2)
  }
  # use the Family constructor of mboost
  Family(ngradient = ngradient, risk = risk, loss = loss,

```

```

        response = function(f) exp(f),
        name = "Student's t-distribution: df (log link)")
    }

    ## families object for new distribution
    newStudentT <- Families(mu= newStudentTMu(mu=mu, df=df),
                          df=newStudentTDf(mu=mu, df=df))

    ### usage of the new Student's t distribution:
    library(gamlss)  ## required for rTF
    set.seed(1907)
    n <- 5000
    x1 <- runif(n)
    x2 <- runif(n)
    mu <- 2 -1*x1 - 3*x2
    df <- exp(1 + 0.5*x1 )
    y <- rTF(n = n, mu = mu, nu = df)

    ## model fitting
    model <- glmboostLSS(y ~ x1 + x2, families = newStudentT,
                       control = boost_control(mstop = 100),
                       center = TRUE)
    ## shrunked effect estimates
    coef(model, off2int = TRUE)

    ## compare to pre-defined three parametric t-distribution:
    model2 <- glmboostLSS(y ~ x1 + x2, families = StudentTLSS(),
                       control = boost_control(mstop = 100),
                       center = TRUE)
    coef(model2, off2int = TRUE)

    ## with effect on sigma:
    sigma <- 3+ 1*x2
    y <- rTF(n = n, mu = mu, nu = df, sigma=sigma)
    model3 <- glmboostLSS(y ~ x1 + x2, families = StudentTLSS(),
                       control = boost_control(mstop = 100),
                       center = TRUE)
    coef(model3, off2int = TRUE)

```

**Description**

Data sample from the Standard Demographic and Health Survey, 1998-99, on malnutrition of children in India. The data set contains approximately 12% of the observations in the original data set and only a (very small) subset of variables. Additionally, a boundary file representing the districts of India is provided for spatial analysis.

## Usage

```
data(india)
data(india.bnd)
```

## Format

A data frame with 4000 observations on the following 6 variables:

`stunting` A numeric score for malnutrition which ranges from -600 to 600, where negative values represent malnourished children.

`cbmi` BMI of the child.

`cage` Age of the child in months.

`mbmi` BMI of the mother.

`mage` Age of the mother in years.

`mcdist` The district in India, where mother and child live. A factor encoded to match the map [india.bnd](#).

`mcdist_lab` The district in India, where mother and child live. A factor with actual district names.

## Details

For details on the boundary file see function [read.bnd](#) from package **BayesX**.

## Source

The complete data set is provided by the Monitoring and Evaluation to Assess and Use Results Demographic and Health Surveys (MEASURE DHS) which is funded by the U.S. Agency of International Development (USAID). It can be obtained for research purposes (after registration) from <http://www.measuredhs.com/what-we-do/survey/survey-display-156.cfm> (Data set for All-India, Children's Recode: iakr42dt.zip)

## References

For details on the data set see also:

Fahrmeir L and Kneib T (2011), *Bayesian smoothing and regression for longitudinal, spatial and event history data*, Oxford University Press.

## Examples

```
if (require("BayesX")) {
  ## plot distribution of stunting in India
  drawmap(india, map = india.bnd, regionvar = "mcdist", plotvar = "stunting")
}
```

## Description

Functions for fitting GAMLSS (generalized additive models for location, scale and shape) using boosting techniques. The algorithm iteratively rotates between the distribution parameters, updating one while using the current fits of the others as offsets (for details see Mayr et al., 2012).

## Usage

```
mboostLSS(formula, data = list(), families = GaussianLSS(),
           control = boost_control(), weights = NULL, ...)
glmboostLSS(formula, data = list(), families = GaussianLSS(),
             control = boost_control(), weights = NULL, ...)
gamboostLSS(formula, data = list(), families = GaussianLSS(),
             control = boost_control(), weights = NULL, ...)
blackboostLSS(formula, data = list(), families = GaussianLSS(),
               control = boost_control(), weights = NULL, ...)

## fit function:
mboostLSS_fit(formula, data = list(), families = GaussianLSS(),
              control = boost_control(), weights = NULL,
              fun = mboost, funchar = "mboost", call = NULL, ...)

#####
# Turn the stability correction on or off:
## use options(gamboostLSS_stab_ngrad = TRUE) ## on
## or options(gamboostLSS_stab_ngrad = FALSE) ## off
```

## Arguments

formula	a symbolic description of the model to be fit. See <a href="#">mboost</a> for details. If formula is a single formula, the same formula is used for all distribution parameters. formula can also be a (named) list, where each list element corresponds to one distribution parameter of the GAMLSS distribution. The names must be the same as in the family (see example for details).
data	a data frame containing the variables in the model.
families	an object of class <code>families</code> . It can be either one of the pre-defined distributions that come along with the package or a new distribution specified by the user (see <a href="#">Families</a> for details). Per default, we use the two-parametric <a href="#">GaussianLSS</a> family.
control	a list of parameters controlling the algorithm. For more details see <a href="#">boost_control</a> .
weights	a numeric vector of weights (optional).
fun	fit function. Either <a href="#">mboost</a> , <a href="#">glmboost</a> , <a href="#">gamboost</a> or <a href="#">blackboost</a> . Specified directly via the corresponding LSS function. E.g. <code>gamboostLSS()</code> calls <code>mboostLSS_fit(..., fun = gamb</code>

funchar	character representation of fit function. Either "mboost", "glmboost", "gamboost" or "blackboost". Specified directly via the corresponding LSS function.
call	used to forward the call from mboostLSS, glmboostLSS, gamboostLSS and blackboostLSS. This argument should not be directly specified by users!
...	Further arguments to be passed to mboostLSS_fit. In mboostLSS_fit, ... represent further arguments to be passed to <code>mboost</code> and <code>mboost_fit</code> . So ... can be all arguments of mboostLSS_fit and mboost_fit.

## Details

For information on GAMLSS theory see Rigby and Stasinopoulos (2005) or the information provided at <http://gamlss.org>.

glmboostLSS uses `glmboost` to fit the distribution parameters of a GAMLSS – a linear boosting model is fitted for each parameter.

gamboostLSS uses `gamboost` to fit the distribution parameters of a GAMLSS – an additive boosting model (by default with smooth effects) is fitted for each parameter. With the `formula` argument, a wide range of different base-learners can be specified (see `baselearners`). The base-learners imply the type of effect each covariate has on the corresponding distribution parameter.

mboostLSS uses `mboost` to fit the distribution parameters of a GAMLSS. The type of model (linear, tree-based or smooth) is specified by `fun`.

blackboostLSS uses `blackboost` to fit the distribution parameters of a GAMLSS – a tree-based boosting model is fitted for each parameter.

mboostLSS, glmboostLSS, gamboostLSS and blackboostLSS all call `mboostLSS_fit` while `fun` is the corresponding `mboost` function, i.e., the same function without LSS. For further possible arguments see these functions as well as `mboost_fit`.

In all four fitting functions it is possible to specify one or multiple `mstop` and `nu` values via `boost_control`. In the case of one single value, this value is used for all distribution parameters of the GAMLSS model. Alternatively, a (named) vector or a (named) list with separate values for each component can be used to specify a separate value for each parameter of the GAMLSS model. The names of the list must correspond to the names of the distribution parameters of the GAMLSS family. If no names are given, the order of the `mstop` or `nu` values is assumed to be the same as the order of the components in the families. For one-dimensional stopping, the user therefore can specify, e.g., `mstop = 100` via `boost_control`. For more-dimensional stopping, one can specify, e.g., `mstop = list(mu = 100, sigma = 200)` (see examples).

To (potentially) stabilize the model estimation one can use `options(gamboostLSS_stab_ngrad = TRUE)` in order to standardize the negative gradients. In each step the negative gradient is divided by its median absolute deviation

$$\text{median}_i(|u_{k,i} - \text{median}_j(u_{k,j})|).$$

To turn the stabilization off, use `options(gamboostLSS_stab_ngrad = FALSE)`.

## Value

An object of class `mboostLSS` with corresponding methods to extract information.



## References

- Mayr, A., Fenske, N., Hofner, B., Kneib, T. and Schmid, M. (2012): Generalized additive models for location, scale and shape for high-dimensional data - a flexible approach based on boosting. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 61(3): 403-427.
- Preliminary version: Department of Statistics, Technical Report 98. <http://epub.ub.uni-muenchen.de/11938/>
- M. Schmid, S. Potapov, A. Pfahlberg, and T. Hothorn. Estimation and regularization techniques for regression models with multidimensional prediction functions. *Statistics and Computing*, 20(2):139-150, 2010.
- Rigby, R. A. and D. M. Stasinopoulos (2005). Generalized additive models for location, scale and shape (with discussion). *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, 54, 507-554.
- Buehlmann, P. and Hothorn, T. (2007), Boosting algorithms: Regularization, prediction and model fitting. *Statistical Science*, 22(4), 477–505.

## See Also

[Families](#) for a documentation of available GAMLSS distributions.

The underlying boosting functions [mboost](#), [gamboost](#), [glmboost](#), [blackboost](#) are contained in the [mboost](#) package.

See for example [risk](#) or [coef](#) for methods that can be used to extract information from [mboostLSS](#) objects.

## Examples

```
### Data generating process:
set.seed(1907)
x1 <- rnorm(1000)
x2 <- rnorm(1000)
x3 <- rnorm(1000)
x4 <- rnorm(1000)
x5 <- rnorm(1000)
x6 <- rnorm(1000)
mu   <- exp(1.5 +1 * x1 +0.5 * x2 -0.5 * x3 -1 * x4)
sigma <- exp(-0.4 * x3 -0.2 * x4 +0.2 * x5 +0.4 * x6)
y <- numeric(1000)
for( i in 1:1000)
  y[i] <- rnbinom(1, size = sigma[i], mu = mu[i])
dat <- data.frame(x1, x2, x3, x4, x5, x6, y)

### linear model with y ~ . for both components: 400 boosting iterations
model <- glmboostLSS(y ~ ., families = NBinomialLSS(), data = dat,
                    control = boost_control(mstop = 400),
                    center = TRUE)
coef(model, off2int = TRUE)
```

```

### estimate model with different formulas for mu and sigma:
names(NBinomialLSS())      # names of the family

# Note: Multiple formulas must be specified via a _named list_
#       where the names correspond to the names of the distribution parameters
#       in the family (see above)
model2 <- glmboostLSS(formula = list(mu = y ~ x1 + x2 + x3 + x4,
                                     sigma = y ~ x3 + x4 + x5 + x6),
                      families = NBinomialLSS(), data = dat,
                      control = boost_control(mstop = 400, trace = TRUE),
                      center = TRUE)
coef(model2, off2int = TRUE)

### Offset needs to be specified via the arguments of families object:
model <- glmboostLSS(y ~ ., data = dat,
                    families = NBinomialLSS(mu = mean(mu),
                                             sigma = mean(sigma)),
                    control = boost_control(mstop = 10),
                    center = TRUE)
# Note: mu-offset = log(mean(mu)) and sigma-offset = log(mean(sigma))
#       as we use a log-link in both families
coef(model)
log(mean(mu))
log(mean(sigma))

### use different mstop values for the two distribution parameters
### (two-dimensional early stopping)
### the number of iterations is passed to boost_control via a named list
model3 <- glmboostLSS(formula = list(mu = y ~ x1 + x2 + x3 + x4,
                                     sigma = y ~ x3 + x4 + x5 + x6),
                      families = NBinomialLSS(), data = dat,
                      control = boost_control(mstop = list(mu = 400,
                                                           sigma = 300),
                                             trace = TRUE),
                      center = TRUE)
coef(model3, off2int = TRUE)

### Alternatively we can subset model2:
# here it is assumed that the first element in the vector corresponds to
# the first distribution parameter of model2 etc.
model2[c(400, 300)]
par(mfrow = c(1,2))
plot(model2, xlim = c(0, max(mstop(model2))))
## all.equal(coef(model2), coef(model3)) # same!

### WARNING: Subsetting via model[mstopnew] changes the model directly!
### For the original fit one has to subset again: model[mstop]

```

---

 methods

*Methods for mboostLSS*


---

**Description**

Methods for GAMLSS models fitted by boosting algorithms.

**Usage**

```
## extract coefficients
## S3 method for class 'glmboostLSS'
coef(object, which = NULL,
      aggregate = c("sum", "cumsum", "none"),
      off2int = FALSE, parameter = names(object), ...)
## S3 method for class 'mboostLSS'
coef(object, which = NULL,
      aggregate = c("sum", "cumsum", "none"),
      parameter = names(object), ...)

## plot partial effects
## S3 method for class 'glmboostLSS'
plot(x, main = names(x), parameter = names(x),
     off2int = FALSE, ...)
## S3 method for class 'gamboostLSS'
plot(x, main = names(x), parameter = names(x), ...)

## extract and plot marginal prediction intervals
predint(x, which, pi = 0.9, newdata = NULL, ...)
PI(x, which, pi = 0.9, newdata = NULL, ...)
## S3 method for class 'predint'
plot(x, main = "Marginal Prediction Interval(s)",
     xlab = NULL, ylab = NULL, lty = c("solid", "dashed"),
     lcol = c("black", "black"), log = "", ...)

## extract mstop
## S3 method for class 'mboostLSS'
mstop(object, parameter = names(object), ...)
## S3 method for class 'oobag'
mstop(object, parameter = names(object), ...)
## S3 method for class 'cvriskLSS'
mstop(object, parameter = NULL, ...)

## set mstop
## S3 method for class 'mboostLSS'
x[i, return = TRUE, ...]

## extract risk
```

```

## S3 method for class 'mboostLSS'
risk(object, merge = FALSE, parameter = names(object), ...)

## extract selected base-learners
## S3 method for class 'mboostLSS'
selected(object, parameter = names(object), ...)

## extract fitted values
## S3 method for class 'mboostLSS'
fitted(object, parameter = names(object), ...)

## make predictions
## S3 method for class 'mboostLSS'
predict(object, newdata = NULL,
        type = c("link", "response", "class"), which = NULL,
        aggregate = c("sum", "cumsum", "none"),
        parameter = names(object), ...)

## update weights of the fitted model
## S3 method for class 'mboostLSS'
update(object, weights, oobweights = NULL,
       risk = NULL, mstop = NULL, ...)

## extract model weights
## S3 method for class 'mboostLSS'
model.weights(x, ...)

```

### Arguments

<code>x</code>	an object of the appropriate class (see usage).
<code>object</code>	an object of the appropriate class (see usage).
<code>which</code>	a subset of base-learners to take into account when computing predictions or coefficients. If <code>which</code> is given (as an integer vector or characters corresponding to base-learners), a list or matrix is returned. In <code>plot_PI</code> the argument <code>which</code> must be specified and it must be given as a character string containing the name of the variable.
<code>aggregate</code>	a character specifying how to aggregate predictions or coefficients of single base-learners. The default returns the prediction or coefficient for the final number of boosting iterations. <code>"cumsum"</code> returns a matrix with the predictions for all iterations simultaneously (in columns). <code>"none"</code> returns a list with matrices where the $j$ th columns of the respective matrix contains the predictions of the base-learner of the $j$ th boosting iteration (and zero if the base-learner is not selected in this iteration).
<code>parameter</code>	This can be either a vector of indices or a vector of parameter names which should be processed. See examples for details. Per default all distribution parameters of the GAMLSS family are returned.

<code>off2int</code>	logical indicating whether the offset should be added to the intercept (if there is any) or if the offset is neglected for plotting (default).
<code>merge</code>	logical. Should the risk vectors of the single components be merged to one risk vector for the model in total? Per default ( <code>merge = FALSE</code> ) a (named) list of risk vectors is returned.
<code>i</code>	integer. Index specifying the model to extract. If <code>i</code> is smaller than the initial <code>mstop</code> , a subset is used. If <code>i</code> is larger than the initial <code>mstop</code> , additional boosting steps are performed until step <code>i</code> is reached. One can specify a scalar, a (possibly named) vector or a (possibly named) list with separate values for each component. See the details section of <a href="#">mboostLSS</a> for more information.
<code>return</code>	a logical indicating whether the changed object is returned.
<code>main</code>	a title for the plots.
<code>xlab, ylab</code>	x- and y axis labels for the plots.
<code>pi</code>	the level(s) of the prediction interval(s); Per default a 90% prediction interval is used.
<code>lty</code>	(vector) of line types to be used for plotting the prediction intervals. The vector should contain <code>length(pi) + 1</code> elements. If less elements are specified, the last element is recycled. The first value <code>lty[1]</code> is used for the marginal median, the second value <code>lty[2]</code> is used for the <code>pi[1]</code> prediction interval, etc.
<code>lcol</code>	(vector) of (line) colors to be used for plotting the prediction intervals. The vector should contain <code>length(pi) + 1</code> elements. If less elements are specified, the last element is recycled. The first value <code>lcol[1]</code> is used for the marginal median, the second value <code>lcol[2]</code> is used for the <code>pi[1]</code> prediction interval, etc.
<code>log</code>	a character string which determines if and if so which axis should be logarithmic. See <a href="#">plot.default</a> for details.
<code>newdata</code>	optional; A data frame in which to look for variables with which to predict or with which to plot the marginal prediction intervals.
<code>type</code>	the type of prediction required. The default is on the scale of the predictors; the alternative "response" is on the scale of the response variable. Thus for a binomial model the default predictions are on the log-odds scale (probabilities on logit scale) and <code>type = "response"</code> gives the predicted probabilities. The "class" option returns predicted classes.
<code>weights</code>	a numeric vector of weights for the model
<code>oobweights</code>	an additional vector of out-of-bag weights (used internally by <a href="#">cvrisk</a> . For details see there.).
<code>risk</code>	a character indicating how the empirical risk should be computed for each boosting iteration. Per default <code>risk</code> is set to the risk type specified for model fitting via <a href="#">boost_control</a> . For details and alternatives see there.
<code>mstop</code>	number of boosting iterations.
<code>...</code>	Further arguments to the functions.

## Details

These functions can be used to extract details from fitted models. `print` shows a dense representation of the model fit.

The function `coef` extracts the regression coefficients of linear predictors fitted using the `glmboostLSS` function or additive predictors fitted using `gamboostLSS`. Per default, only coefficients of selected base-learners are returned for all distribution parameters. However, any desired coefficient can be extracted using the `which` argument. Furthermore, one can extract only coefficients for a single distribution parameter via the `parameter` argument (see examples for details).

Analogical, the function `plot` per default displays the coefficient paths for the complete GAMLSS but can be restricted to single distribution parameters or covariates (or subsets) using the `parameter` or `which` arguments, respectively.

The function `predint` (or `PI` which is just an alias) computes marginal prediction intervals and returns a data frame with the predictors used for the marginal prediction interval, the computed median prediction and the marginal prediction intervals. A plot function (`plot.predint`) for the resulting object exists. Note that marginal predictions from AFT models (i.e., families `LogLogLSS`, `LogNormalLSS`, and `WeibullLSS`) represent the predicted “true” survival time and not the observed survival time which is possible subject to censoring. Hence, comparing observed survival times with the marginal prediction interval is only sensible for uncensored observations.

The `predict` function can be used for predictions for the distribution parameters depending on new observations whereas `fitted` extracts the regression fits for the observations in the learning sample. For `predict`, `newdata` can be specified – otherwise the fitted values are returned. If `which` is specified, marginal effects of the corresponding base-learner(s) are returned. The argument `type` can be used to make predictions on the scale of the link (i.e., the linear predictor  $X * \beta$ ), the response (i.e.  $h(X * \beta)$ , where  $h$  is the response function) or the `class` (in case of classification).

The function `update` updates models fit with `gamboostLSS` and is primarily used within `cvrisk`. It updates the weights and refits the model to the altered data. Furthermore, the type of risk and the number of boosting iterations `mstop` can be modified.

The function `model.weights` is a generic version of the same function provided by package `stats`, which is required to make `model.weights` work with `mboostLSS` models.

## Warning

The `[.mboostLSS]` function changes the original object, i.e., `LSSmodel[10]` changes `LSSmodel` directly!

## References

- Mayr, A., Fenske, N., Hofner, B., Kneib, T. and Schmid, M. (2012): Generalized additive models for location, scale and shape for high-dimensional data - a flexible approach based on boosting. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 61(3): 403-427.
- Buehlmann, P. and Hothorn, T. (2007), Boosting algorithms: regularization, prediction and model fitting. *Statistical Science*, 22(4), 477–505.
- Rigby, R. A. and D. M. Stasinopoulos (2005). Generalized additive models for location, scale and shape (with discussion). *Journal of the Royal Statistical Society, Series C (Applied Statistics)*, 54, 507-554.

**See Also**

[glmboostLSS](#), [gamboostLSS](#) and [blackboostLSS](#) for fitting of GAMLSS.

Available distributions (families) are documented here: [Families](#).

See [methods](#) in the `mboost` package for the corresponding methods for `mboost` objects.

**Examples**

```
### generate data
set.seed(1907)
x1 <- rnorm(1000)
x2 <- rnorm(1000)
x3 <- rnorm(1000)
x4 <- rnorm(1000)
x5 <- rnorm(1000)
x6 <- rnorm(1000)
mu <- exp(1.5 + x1^2 + 0.5 * x2 - 3 * sin(x3) - 1 * x4)
sigma <- exp(-0.2 * x4 + 0.2 * x5 + 0.4 * x6)
y <- numeric(1000)
for( i in 1:1000)
  y[i] <- rlnbinom(1, size = sigma[i], mu = mu[i])
dat <- data.frame(x1, x2, x3, x4, x5, x6, y)

### fit a model
model <- gamboostLSS(y ~ ., families = NBinomialLSS(), data = dat,
                    control = boost_control(mstop = 100))

### use a model with more iterations for a better fit
model[400]

### extract coefficients
coef(model)

### only for distribution parameter mu
coef(model, parameter = "mu")

### only for covariate x1
coef(model, which = "x1")

### plot complete model
par(mfrow = c(4, 3))
plot(model)
### plot first parameter only
par(mfrow = c(2, 3))
plot(model, parameter = "mu")
### now plot only effect of x3 of both parameters
par(mfrow = c(1, 2))
plot(model, which = "x3")
### first component second parameter (sigma)
par(mfrow = c(1, 1))
```

```
plot(model, which = 1, parameter = 2)

### plot marginal prediction interval
pi <- predint(model, pi = 0.9, which = "x1")
pi <- predint(model, pi = c(0.8, 0.9), which = "x1")
plot(pi, log = "y") # warning as some y values are below 0
## here it would be better to plot x1 against
## sqrt(y) and sqrt(pi)

### subset model for mstop = 300 (one-dimensional)
model[300]

# WARNING: Subsetting via model[mstopnew] changes the model directly!
# For the original fit one has to subset again: model[mstop]

par(mfrow = c(2, 2))
plot(risk(model, parameter = "mu")[[1]])
plot(risk(model, parameter = "sigma")[[1]])

### get back to original fit
model[400]
plot(risk(model, parameter = "mu")[[1]])
plot(risk(model, parameter = "sigma")[[1]])

### use different mstop values for the components
model[c(100, 200)]
## same as
  model[c(mu = 100, sigma = 200)]
## or
  model[list(mu = 100, sigma = 200)]
## or
  model[list(100, 200)]

plot(risk(model, parameter = "mu")[[1]])
plot(risk(model, parameter = "sigma")[[1]])
```



# Index

- \*Topic **datasets**
  - india, [13](#)
- \*Topic **distributions**
  - as.families, [3](#)
  - Families, [9](#)
- \*Topic **fitting**
  - mboostLSS, [15](#)
- \*Topic **methods**
  - methods, [19](#)
- \*Topic **models**
  - as.families, [3](#)
  - cvrisk.mboostLSS, [5](#)
  - Families, [9](#)
  - mboostLSS, [15](#)
- \*Topic **nonlinear**
  - mboostLSS, [15](#)
- \*Topic **package**
  - gamboostLSS-package, [2](#)
- \*Topic **regression**
  - cvrisk.mboostLSS, [5](#)
- [.mboostLSS (methods), [19](#)
- as.families, [3, 11](#)
- baselearners, [2, 16](#)
- BetaLSS (Families), [9](#)
- BetaMu (Families), [9](#)
- BetaPhi (Families), [9](#)
- blackboost, [15–17](#)
- blackboostLSS, [23](#)
- blackboostLSS (mboostLSS), [15](#)
- boost\_control, [15, 16, 21](#)
- coef, [17](#)
- coef.glmboostLSS (methods), [19](#)
- coef.mboostLSS (methods), [19](#)
- cv, [6, 7](#)
- cvrisk, [21, 22](#)
- cvrisk (cvrisk.mboostLSS), [5](#)
- cvrisk.mboost, [7](#)
- cvrisk.mboostLSS, [5](#)
- Families, [2, 3, 5, 9, 15, 17, 23](#)
- families (Families), [9](#)
- Family, [4, 11](#)
- fitted.mboostLSS (methods), [19](#)
- gamboost, [2, 15–17](#)
- gamboostLSS, [2–4, 11, 22, 23](#)
- gamboostLSS (mboostLSS), [15](#)
- gamboostLSS-package, [2](#)
- gamboostLSS\_stab\_ngrad (mboostLSS), [15](#)
- gamlss, [2, 3](#)
- gamlss.Families (as.families), [3](#)
- gamlss1parMu (as.families), [3](#)
- gamlss2parMu (as.families), [3](#)
- gamlss2parSigma (as.families), [3](#)
- gamlss3parMu (as.families), [3](#)
- gamlss3parNu (as.families), [3](#)
- gamlss3parSigma (as.families), [3](#)
- gamlss4parMu (as.families), [3](#)
- gamlss4parNu (as.families), [3](#)
- gamlss4parSigma (as.families), [3](#)
- gamlss4parTau (as.families), [3](#)
- GammaLSS (Families), [9](#)
- GammaMu (Families), [9](#)
- GammaSigma (Families), [9](#)
- GaussianLSS, [15](#)
- GaussianLSS (Families), [9](#)
- GaussianMu (Families), [9](#)
- GaussianSigma (Families), [9](#)
- glmboost, [2, 15–17](#)
- glmboostLSS, [2–4, 11, 22, 23](#)
- glmboostLSS (mboostLSS), [15](#)
- india, [13](#)
- india.bnd, [14](#)
- lapply, [6](#)
- LogLogLSS, [22](#)

LogLogLSS (Families), 9  
LogLogMu (Families), 9  
LogLogSigma (Families), 9  
LogNormalLSS, 22  
LogNormalLSS (Families), 9  
LogNormalMu (Families), 9  
LogNormalSigma (Families), 9

make.grid (cvrisk.mboostLSS), 5  
mboost, 2–4, 11, 15–17, 23  
mboost\_fit, 16  
mboostLSS, 11, 15, 17, 21  
mboostLSS\_fit (mboostLSS), 15  
mclapply, 6  
methods, 19, 23  
model.weights (methods), 19  
mstop.cvriskLSS (methods), 19  
mstop.mboostLSS (methods), 19  
mstop.oobag (methods), 19

NBinomialLSS (Families), 9  
NBinomialMu (Families), 9  
NBinomialSigma (Families), 9

options (mboostLSS), 15

parLapply, 6  
PI (methods), 19  
plot.cvriskLSS (cvrisk.mboostLSS), 5  
plot.default, 21  
plot.gamboostLSS (methods), 19  
plot.glboostLSS (methods), 19  
plot.predint (methods), 19  
predict.mboostLSS (methods), 19  
predint, 10  
predint (methods), 19

read.bnd, 14  
risk, 17  
risk (methods), 19

selected (methods), 19  
stab\_ngrad (mboostLSS), 15  
stabilize\_ngrad (mboostLSS), 15  
stabilize\_ngradient (mboostLSS), 15  
StudentTDf (Families), 9  
StudentTLSS (Families), 9  
StudentTMu (Families), 9  
StudentTSigma (Families), 9

update.mboostLSS (methods), 19

WeibullLSS, 22  
WeibullLSS (Families), 9  
WeibullMu (Families), 9  
WeibullSigma (Families), 9

ZINBLSS (Families), 9  
ZIPoLSS (Families), 9