

# Package ‘nat.nblast’

September 19, 2014

**Type** Package

**Title** NeuroAnatomy Toolbox (nat) Extension for Assessing Neuron Similarity and Clustering

**Version** 1.5

**Date** 2014-09-18

**Author** Greg Jefferis and James Manton

**Maintainer** James Manton <ajd.manton@googlemail.com>

**Description** Extends package nat (NeuroAnatomy Toolbox) by providing a collection of NBLAST-related functions.

**Depends** R (>= 2.15.1), rgl, methods, nat (>= 1.5.12)

**Imports** nabor, dendroextras, plyr, spam

**Suggests** bigmemory, ff, testthat

**License** GPL-3

**LazyData** yes

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2014-09-19 14:57:33

## R topics documented:

nat.nblast-package . . . . .	2
calc_dists_dotprods . . . . .	4
calc_prob_mat . . . . .	4
calc_score_matrix . . . . .	5
create_scoringmatrix . . . . .	6
diagonal . . . . .	8
fctraces20 . . . . .	8

fill_in_sparse_score_mat . . . . .	9
fill_pairs_sparse_score_mat . . . . .	10
nblast . . . . .	10
nblast_allbyall . . . . .	12
NeuriteBlast . . . . .	14
neuron_pairs . . . . .	15
nhclust . . . . .	15
plot3d.hclust . . . . .	16
show_similarity . . . . .	17
smat.fcwb . . . . .	18
sparse_score_mat . . . . .	19
subset.hclust . . . . .	19
sub_dist_mat . . . . .	20
sub_score_mat . . . . .	21
WeightedNNBasedLinesetMatching . . . . .	21
[ . . . . .	22
<b>Index</b>	<b>24</b>

---

nat.nblast-package      *Neuron similarity, search and clustering tools*

---

## Description

Neuron similarity, search and clustering tools

## Similarity and search

The main entry point for similarity and search functions is `nblast`. Traced neurons will normally be converted to the `dotprops` format for search. When multiple neurons are compared they should be in a `neuronlist` object.

The current `nblast` version (2) depends on a scoring matrix. Default matrices trained using *Drosophila* neurons in the FCWB template brain space are distributed with this package (see `smat.fcwb`); see **Scoring Matrices** section below for creating new scoring matrices.

`nblast` makes use of a more flexible but more complicated function `NeuriteBlast` which includes several additional options. The function `WeightedNNBasedLinesetMatching` provides the primitive functionality of finding the nearest neighbour distances and absolute dot products for two sets of segments. Neither of these functions are intended for end use.

Calculating all by all similarity scores is facilitated by the `nblast_allbyall` function which can take either a `neuronlist` as input or a character vector naming (a subset) of neurons in a (large) `neuronlist`. The `neuronlist` containing the input neurons should be resident in memory i.e. not the `neuronlistfh`

## Clustering

Once an all by all similarity score matrix is available it can be used as the input to a variety of clustering algorithms. `nhclust` provides a convenient wrapper for R's hierarchical clustering function `hclust`. If you wish to use another clustering function, then you can use the `sub_dist_mat` to convert a raw similarity score matrix into a normalised distance matrix (or R `dist` object) suitable for clustering. If you need a similarity matrix or want to modify the normalisation then you can use `sub_score_mat`.

Note that raw nblast scores are not symmetric (i.e.  $S(A,B)$  is not equal to  $S(B,A)$ ) so before clustering we construct a symmetric similarity/distance matrix  $1/2 * ( S(A,B)/S(A,A) + S(B,A)/S(B,B) )$ . See `sub_score_mat`'s documentation for details.

## Cached scores

Although nblast is fast and can be parallelised, it makes sense to cache to disk all by all similarity scores for a group of neurons that will be subject to repeated clustering or other analysis. The matrix can simply be saved to disk and then reloaded using base R functions like `save` and `load`. `sub_score_mat` and `sub_dist_mat` can be used to extract a subset of scores from this raw score matrix. For large matrices, the `bigmemory` or `ff` packages allow matrices to be stored on disk and portions loaded into memory on demand. `sub_score_mat` and `sub_dist_mat` work equally well for regular in-memory matrices and these disk-backed matrices.

To give an example, for 16,129 neurons from the flycircuit.tw dataset, the 260,144,641 comparisons took about 250 hours of compute time (half a day on ~20 cores). When saved to disk as single precision (i.e. 4 bytes per score) `ff` matrix they occupy just over 1Gb.

## Calculating scoring matrices

The nblast algorithm depends on appropriately calibrated scoring matrices. These encapsulate the log odds ratio that a pair of segments come from two structurally related neurons rather than two unrelated neurons, given the observed distance and absolute dot product of the two segments. Scoring matrices can be constructed using the `create_scoringmatrix` function, supplying a set of matching neurons and a set of non-matching neurons. See the `create_scoringmatrix` documentation for links to lower-level functions that provide finer control over construction of the scoring matrix.

## Package Options

There is one package option `nat.nblast.defaultsmat` which is `NULL` by default, but could for example be set to one of the scoring matrices included with the package such as `code"smat.fcwb"` or to a new user-constructed matrix.

## References

Costa, M., Ostrovsky, A.D., Manton, J.D., Prohaska, S., and Jefferis, G.S.X.E. (2014). NBLAST: Rapid, sensitive comparison of neuronal structure and construction of neuron family databases. Biorxiv preprint. doi: [10.1101/006346](https://doi.org/10.1101/006346).

## See Also

`nblast`, `smat.fcwb`, `nhclust`, `sub_dist_mat`, `sub_score_mat`, `create_scoringmatrix`

---

calc\_dists\_dotprods     *Calculate distances and dot products between two sets of neurons*

---

### Description

Calculate distances and dot products between two sets of neurons

### Usage

```
calc_dists_dotprods(query_neurons, target_neurons, subset = NULL,
  ignoreSelf = TRUE, ...)
```

### Arguments

query\_neurons     a [neuronlist](#) to use for calculating distances and dot products.

target\_neurons     a further [neuronlist](#) to use for calculating distances and dot products.

subset             a [data.frame](#) specifying which neurons in query\_neurons and target\_neurons should be compared, with columns specifying query and target neurons by name, with one row for each pair. If unspecified, this defaults to an all-by-all comparison.

ignoreSelf         a Boolean indicating whether to ignore comparisons of a neuron against itself (default TRUE).

...                 extra arguments to pass to [NeuriteBlast](#).

### Details

Distances and dot products are the raw inputs for constructing scoring matrices for the nblast search algorithm.

### Value

A list, one element for for pair of neurons with a 2 column data.frame containing one column of distances and s secon of absolute dot products.

---

calc\_prob\_mat             *Calculate probability matrix from distances and dot products between neuron segments*

---

### Description

Calculate probability matrix from distances and dot products between neuron segments

**Usage**

```
calc_prob_mat(nndists, dotprods, distbreaks, dotprodbreaks = seq(0, 1, by =
  0.1), ReturnCounts = FALSE)
```

**Arguments**

nndists	a list of nearest-neighbour distances or a list of both nearest-neighbour distances and dot products.
dotprods	a list of dot products.
distbreaks	a vector specifying the breaks for distances in the probability matrix.
dotprodbreaks	a vector specifying the breaks for dot products in the probability matrix.
ReturnCounts	a Boolean indicating that counts should be returned instead of the default probabilities.

**Value**

A matrix with columns as specified by dotprodbreaks and rows as specified by distbreaks, containing probabilities (for default value of ReturnCounts=TRUE) or counts (if ReturnCounts=TRUE) for finding neuron segments with the given distance and dot product.

---

calc_score_matrix	<i>Calculate scoring matrix from probability matrices for matching and non-matching sets of neurons</i>
-------------------	---

---

**Description**

Calculate scoring matrix from probability matrices for matching and non-matching sets of neurons

**Usage**

```
calc_score_matrix(matchmat, randmat, logbase = 2, epsilon = 1e-06)
```

**Arguments**

matchmat	a probability matrix given by considering 'matching' neurons.
randmat	a probability matrix given by considering 'non-matching' or 'random' neurons.
logbase	the base to which the logarithm should be taken to produce the final scores.
epsilon	a pseudocount to prevent division by zero when constructing the log odds ratio in the probability matrix.

**Value**

A matrix with with class=c("scoringmatrix", "table"), with columns as specified by dotprodbreaks and rows as specified by distbreaks, containing scores for neuron segments with the given distance and dot product.

---

create\_scoringmatrix *Create a scoring matrix given matching and non-matching sets of neurons*

---

### Description

Calculate a scoring matrix embodying the logarithm of the odds that a matching pair of neurite segments come from a structurally related rather than random pair of neurons. This function embodies sensible default behaviours and is recommended for end users. More control is available by using the individual functions listed in **See Also**.

### Usage

```
create_scoringmatrix(matching_neurons, nonmatching_neurons,
  matching_subset = NULL, non_matching_subset = NULL, ignoreSelf = TRUE,
  distbreaks, dotprodbreaks = seq(0, 1, by = 0.1), logbase = 2,
  epsilon = 1e-06, ...)
```

### Arguments

matching_neurons	a <a href="#">neuronlist</a> of matching neurons.
nonmatching_neurons	a <a href="#">neuronlist</a> of non-matching neurons.
matching_subset, non_matching_subset	data.frames indicating which pairs of neurons in the two input neuron lists should be used to generate the matching and null distributions. See details for the default behaviour when NULL.
ignoreSelf	a Boolean indicating whether to ignore comparisons of a neuron against itself (default TRUE).
distbreaks	a vector specifying the breaks for distances in the probability matrix.
dotprodbreaks	a vector specifying the breaks for dot products in the probability matrix.
logbase	the base to which the logarithm should be taken to produce the final scores.
epsilon	a pseudocount to prevent division by zero when constructing the log odds ratio in the probability matrix.
...	extra arguments to pass to <a href="#">NeuriteBlast</a> or options for the call to <a href="#">mply</a> call that actually iterates over neuron pairs.

### Details

By default create\_scoringmatrix will use all neurons in matching\_neurons to create the matching distribution. This is appropriate if all of these neurons are of a single type. If you wish to use multiple types of neurons then you will need to specify a matching\_subset to indicate which pairs of neurons are of the same type.

By default `create_scoringmatrix` will use a random set of pairs from `non_matching_neurons` to create the null distribution. The number of random pairs will be equal to the number of matching pairs defined by `matching_neurons`. This is appropriate if `non_matching_neurons` contains a large collection of neurons of different types. You may wish to set the random seed using `set.seed` if you want to ensure that exactly the same (pseudo-)random pairs of neurons are used in subsequent calls.

### Value

A matrix with columns as specified by `dotprodbreaks` and rows as specified by `distbreaks`, containing log odd scores for neuron segments with the given distance and dot product.

### See Also

`calc_score_matrix`, `calc_prob_mat`, `calc_dists_dotprods`, `neuron_pairs`

### Examples

```
## Not run:
# calculate scoring matrix
# bring in some mushroom body neurons
library(nat)
data(kcs20)
# convert the (connected) tracings into dotprops (point and vector)
# representation, resampling at 1 micron intervals along neuron
fctraces20.dps=dotprops(fctraces20, resample=1)
# we will use both all kcs vs all fctraces20 and fctraces20 vs fctraces20
# as random_pairs to make the null distribution
random_pairs=rbind(neuron_pairs(fctraces20), neuron_pairs(nat::kcs20, fctraces20))
smat=create_scoringmatrix(kcs20, c(kcs20, fctraces20.dps),
                          non_matching_subset=random_pairs, .progress='text')

# now plot the scoring matrix
distbreaks=attr(smat,'distbreaks')
distbreaks=distbreaks[-length(distbreaks)]
dotprodbreaks=attr(smat,'dotprodbreaks')[-1]
# Create a function interpolating colors in the range of specified colors
jet.colors <- colorRampPalette( c("blue", "green", "yellow", "red") )
# 2d filled contour plot of scoring matrix. Notice that there is a region
# at small distances and large abs dot product with the highest log odds ratio
# i.e. most indicative of a match rather than non-match
filled.contour(x=distbreaks, y=dotprodbreaks, z=smat, col=jet.colors(20),
               main='smat: log odds ratio', xlab='distance /um', ylab='abs dot product')

# 3d perspective plot of the scoring matrix
persp3d(x=distbreaks, y=dotprodbreaks, z=smat, col=jet.colors(20)[cut(smat,20)],
        xlab='distance /um', ylab='abs dot product', zlab='log odds ratio')

## End(Not run)
```

---

diagonal	<i>Extract diagonal terms from a variety of matrix types</i>
----------	--

---

### Description

Extract diagonal terms from a variety of matrix types

### Usage

```
diagonal(x, indices = NULL)
```

```
## Default S3 method:
```

```
diagonal(x, indices = NULL)
```

### Arguments

x	A square matrix
indices	specifies a subset of the diagonal using a character vector of names, a logical vector or integer indices. The default (NULL) implies all elements.

### Details

Insists that input matrix is square. Uses the 'diagonal' attribute when available and has specialised handling of `ff`, `big.matrix`, `dgCMatrix` matrices. Does not check that row and column names are identical for those matrix classes (unlike the base `diag` function, but always uses rownames).

### Value

a named vector containing the diagonal elements.

### Examples

```
m=fill_in_sparse_score_mat(letters[1:5])
diagonal(m)
```

---

fctraces20	<i>20 traced Drosophila neurons from Chiang et al 2011</i>
------------	--

---

### Description

This R list (which has additional class `neuronlist`) contains 15 skeletonized *Drosophila* neurons as `dotprops` objects. Original data is due to Chiang et al. [1], who have generously shared their raw data at <http://flycircuit.tw>. Automated tracing of neuron skeletons was carried out by Lee et al [2]. Image registration and further processing was carried out by Greg Jefferis, Marta Costa and James Manton[3].



## References

- [1] Chiang A.S., Lin C.Y., Chuang C.C., Chang H.M., Hsieh C.H., Yeh C.W., Shih C.T., Wu J.J., Wang G.T., Chen Y.C., Wu C.C., Chen G.Y., Ching Y.T., Lee P.C., Lin C.Y., Lin H.H., Wu C.C., Hsu H.W., Huang Y.A., Chen J.Y., et al. (2011). Three-dimensional reconstruction of brain-wide wiring networks in *Drosophila* at single-cell resolution. *Curr Biol* 21 (1), 1–11.
- [2] P.-C. Lee, C.-C. Chuang, A.-S. Chiang, and Y.-T. Ching. (2012). High-throughput computer method for 3d neuronal structure reconstruction from the image stack of the *Drosophila* brain and its applications. *PLoS Comput Biol*, 8(9):e1002658, Sep 2012. doi: 10.1371/journal.pcbi.1002658.
- [3] NBLAST: Rapid, sensitive comparison of neuronal structure and construction of neuron family databases. Marta Costa, Aaron D. Ostrovsky, James D. Manton, Steffen Prohaska, Gregory S.X.E. Jefferis. bioRxiv doi: <http://dx.doi.org/10.1101/006346>.

---

fill\_in\_sparse\_score\_mat

*Add one or more submatrices to a sparse score matrix*

---

## Description

Add one or more submatrices to a sparse score matrix

## Usage

```
fill_in_sparse_score_mat(sparse_matrix, ..., diag = NULL)
```

## Arguments

sparse_matrix	either an existing (square) sparse matrix or a character vector of names that will be used to define an empty sparse matrix.
...	Additional matrices to insert into sparse_matrix. Row and column names must have matches in sparse_matrix.
diag	optional full diagonal for sparse matrix i.e. self-match scores.

## See Also

sparse\_score\_mat

---

```
fill_pairs_sparse_score_mat
```

*Add forwards, reverse and self scores for a pair of neurons to a sparse score matrix*

---

### Description

Add forwards, reverse and self scores for a pair of neurons to a sparse score matrix

### Usage

```
fill_pairs_sparse_score_mat(sparse_matrix, n1, n2, dense_matrix,
  reverse = TRUE, self = TRUE, reverse_self = (reverse && self))
```

### Arguments

<code>sparse_matrix</code>	the sparse matrix to fill in.
<code>n1</code>	the name of the query neuron.
<code>n2</code>	the name of the target neuron.
<code>dense_matrix</code>	the score matrix from which to extract scores.
<code>reverse</code>	logical indicating that the reverse score should also be filled in (default TRUE).
<code>self</code>	logical indicating that the self-score of the query should also be filled in (used for normalised scores; default TRUE).
<code>reverse_self</code>	logical indicating that the self-score of the target should also be filled in (used for mean scores; default TRUE).

### Value

A sparse matrix (of class `spam`) with the specified score entries filled.

---

```
nblast
```

*Calculate similarity score for neuron morphologies*

---

### Description

Uses the NBLAST algorithm that compares the morphology of two neurons. For more control over the parameters of the algorithm, see the arguments of [NeuriteBlast](#).

### Usage

```
nblast(query, target = getOption("nat.default.neuronlist"), smat = NULL,
  sd = 3, version = c(2, 1), normalised = FALSE, UseAlpha = FALSE,
  OmitFailures = NA, ...)
```

**Arguments**

query	the query neuron.
target	a <a href="#">neuronlist</a> to compare neuron against. Defaults to <code>options("nat.default.neuronlist")</code> . See <a href="#">nat-package</a> .
smat	the scoring matrix to use (see details)
sd	Standard deviation to use in distance dependence of nblast v1 algorithm. Ignored when <code>version=2</code> .
version	the version of the algorithm to use (the default, 2, is the latest).
normalised	whether to divide scores by the self-match score of the query
UseAlpha	whether to consider local directions in the similarity calculation (default: FALSE).
OmitFailures	Whether to omit neurons for which FUN gives an error. The default value (NA) will result in nblast stopping with an error message the moment there is an error. For other values, see details.
...	Additional arguments passed to <code>NeuriteBlast</code> or the function used to compute scores from distances/dot products. (expert use only).

**Details**

when `smat=NULL` `options("nat.nblast.defaultsmat")` will be checked and if NULL, then `smat.fcwb` or `smat_alpha.fcwb` will be used depending on the value of `UseAlpha`.

When `OmitFailures` is not NA, individual nblast calls will be wrapped in `try` to ensure that failure for any single neuron does not abort the whole nblast call. When `OmitFailures=FALSE`, missing values will be left as NA. `OmitFailures=TRUE` is not (yet) implemented. If you want to drop scores for neurons that failed you will need to set `OmitFailures=FALSE` and then use `na.omit` or similar to post-process the scores.

Note that when `OmitFailures=FALSE` error messages will not be printed because the call is wrapped as `try(expr, silent=TRUE)`.

Internally, the [plyr](#) package is used to provide options for parallelising NBLASTs and displaying progress. To display a progress bar as the scores are computed, add `.progress="text"` to the arguments (non-text progress bars are available – see [create\\_progress\\_bar](#)). To parallelise, add `.parallel=TRUE` to the arguments. In order to make use of parallel calculation, you must register a parallel backend that will distribute the computations. There are several possible backends, the simplest of which is the multicore option made available by `doMC`, which spreads the load across cores of the same machine. Before using this, the backend must be registered using `registerDoMC` (see example below).

**Value**

Named list of similarity scores.

**See Also**

[nat-package](#)

**Examples**

```

# load sample Kenyon cell data from nat package
data(kcs20, package='nat')
# search one neuron against all neurons
scores=nblast(kcs20[['GadMARCM-F000142_seg002']], kcs20)
# scores from best to worst, top hit is of course same neuron
sort(scores, decreasing = TRUE)
hist(scores, breaks=25, col='grey')
abline(v=1500, col='red')

# plot query neuron
open3d()
# plot top 3 hits (including self match with thicker lines)
plot3d(kcs20[which(sort(scores, decreasing = TRUE)>1500)], lwd=c(3,1,1))
rest=names(which(scores<1500))
plot3d(rest, db=kcs20, col='grey', lwd=0.5)

# normalised scores (i.e. self match = 1) of all neurons vs each other
# note use of progress bar
scores.norm=nblast(kcs20, kcs20, normalised = TRUE, .progress="text")
hist(scores.norm, breaks=25, col='grey')
# produce a heatmap from normalised scores
jet.colors <- colorRampPalette( c("blue", "green", "yellow", "red") )
heatmap(scores.norm, labCol = with(kcs20,type), col=jet.colors(20), symm = TRUE)

## Not run:
# Parallelise NBLASTing across 4 cores using doMC package
library(doMC)
registerDoMC(4)
scores.norm2=nblast(kcs20, kcs20, normalised=TRUE, .parallel=TRUE)
stopifnot(all.equal(scores.norm2, scores.norm))

## End(Not run)

```

---

nblast\_allbyall

*Wrapper function to compute all by all NBLAST scores for a set of neurons*


---

**Description**

Calls `nblast` to compute the actual scores. Can accept either a neuronlist or neuron names as a character vector. This is a thin wrapper around `nblast` and its main advantage is the option of "mean" normalisation for forward and reverse scores, which is the most sensible input to give to a clustering algorithm as well as the choice of returning a distance matrix.

**Usage**

```
nblast_allbyall(x, ...)
```

```
## S3 method for class 'character'
nblast_allbyall(x, smat = NULL,
  db = getOption("nat.default.neuronlist"), ...)

## S3 method for class 'neuronlist'
nblast_allbyall(x, smat = NULL, distance = FALSE,
  normalisation = c("raw", "normalised", "mean"), ...)
```

### Arguments

x	Input neurons (neuronlist or character vector)
...	Additional arguments for methods or nblast
smat	the scoring matrix to use (see details of <a href="#">nblast</a> for meaning of default NULL value)
db	A neuronlist or a character vector naming one. Defaults to value of options("nat.default.neuronlist")
distance	logical indicating whether to return distances or scores.
normalisation	the type of normalisation procedure that should be carried out, selected from 'raw', 'normalised' or 'mean' (i.e. the average of normalised scores in both directions). If distance=TRUE then this cannot be raw.

### Details

Note that nat already provides a function [nhclust](#) for clustering, which is a wrapper for R's `hclust` function. `nhclust` actually expects **raw** scores as input.

### TODO

It would be a good idea in the future to implement a parallel version of this function.

### See Also

[nblast](#), [sub\\_score\\_mat](#), [nhclust](#)

### Examples

```
library(nat)
kcs20.scoremat=nblast_allbyall(kcs20)
kcs20.hclust=nhclust(scoremat=kcs20.scoremat)
plot(kcs20.hclust)
```

---

 NeuriteBlast

*Produce similarity score for neuron morphologies*


---

### Description

A low-level entry point to the NBLAST algorithm that compares the morphology of a neuron with those of a list of other neurons. For most use cases, one would probably wish to use [nblast](#) instead.

### Usage

```
NeuriteBlast(query, target, targetBinds = NULL, normalised = FALSE,
             OmitFailures = NA, simplify = TRUE, ...)
```

### Arguments

query	either a single query neuron or a <a href="#">neuronlist</a>
target	a <a href="#">neuronlist</a> to compare neuron against.
targetBinds	numeric indices or names with which to subset target.
normalised	whether to divide scores by the self-match score of the query
OmitFailures	Whether to omit neurons for which FUN gives an error. The default value (NA) will result in <a href="#">nblast</a> stopping with an error message the moment there is an error. For other values, see details.
simplify	whether to simplify the scores from a list to a vector. TRUE by default. The only time you might want to set this false is if you are collecting something other than simple scores from the search function. See <a href="#">simplify2array</a> for further details.
...	extra arguments to pass to the distance function.

### Details

For detailed description of the `OmitFailures` argument, see the details section of [nblast](#).

### Value

Named list of similarity scores.

### See Also

[WeightedNNBasedLinesetMatching](#)

---

neuron_pairs	<i>Utility function to generate all or random pairs of neurons</i>
--------------	--

---

**Description**

Utility function to generate all or random pairs of neurons

**Usage**

```
neuron_pairs(query, target, n = NA, ignoreSelf = TRUE)
```

**Arguments**

query, target	either neuronlists or character vectors of names. If target is missing, query will be used as both query and target.
n	number of random pairs to draw. When NA, the default, uses <code>expand.grid</code> to draw all pairs.
ignoreSelf	Logical indicating whether to omit pairs consisting of the same neuron (default TRUE).

**Value**

a data.frame with two character vector columns, query and target.

**See Also**

[calc\\_score\\_matrix](#), [expand.grid](#)

**Examples**

```
neuron_pairs(nat::kcs20, n=20)
```

---

nhclust	<i>Cluster a set of neurons</i>
---------	---------------------------------

---

**Description**

Given a vector of neuron identifiers use `nhclust` to carry out a hierarchical clustering. The default value of `distfun` will handle square distance matrices and R.

**Usage**

```
nhclust(neuron_names, method = "ward", scoremat = NULL, distfun = as.dist,  
..., maxneurons = 4000)
```

**Arguments**

neuron_names	character vector of neuron identifiers.
method	clustering method (default Ward's).
scoremat	score matrix to use (see sub_score_mat for details of default).
distfun	function to convert distance matrix returned by sub_dist_mat into R dist object (default=as.dist).
...	additional parameters passed to hclust.
maxneurons	set this to a sensible value to avoid loading huge (order $N^2$ ) distances directly into memory.

**Value**

An object of class `hclust` which describes the tree produced by the clustering process.

**See Also**

`hclust`, `dist`

Other scoremats: `sub_dist_mat`

**Examples**

```
library(nat)
kcscores=nblast_allbyall(kcs20)
hckcs=nhclust(scoremat=kcscores)
# divide hclust object into 3 groups
library(dendroextras)
dkcs=colour_clusters(hckcs, k=3)
# change dendrogram labels to neuron type, extracting this information
# from type column in the metadata data.frame attached to kcs20 neuronlist
labels(dkcs)=with(kcs20[labels(dkcs)], type)
plot(dkcs)
# 3d plot of neurons in those clusters (with matching colours)
open3d()
plot3d(hckcs, k=3, db=kcs20)
# names of neurons in 3 groups
subset(hckcs, k=3)
```

---

plot3d.hclust

*Methods to identify and plot groups of neurons cut from an hclust object*

---

**Description**

plot3d.hclust uses plot3d to plot neurons from each group, cut from the hclust object, by colour.



**Usage**

```
## S3 method for class 'hclust'  
plot3d(x, k = NULL, h = NULL, groups = NULL,  
       col = rainbow, ...)
```

**Arguments**

x	an <a href="#">hclust</a> object generated by <a href="#">nhclust</a> .
k	number of clusters to cut from <a href="#">hclust</a> object.
h	height to cut <a href="#">hclust</a> object.
groups	numeric vector of groups to plot.
col	colours for groups (directly specified or a function).
...	additional arguments for <a href="#">plot3d</a>

**Details**

Note that the colours are in the order of the dendrogram as assigned by [colour\\_clusters](#).

**Value**

A list of rgl IDs for plotted objects (see [plot3d](#)).

**See Also**

[nhclust](#), [plot3d](#), [slice](#), [colour\\_clusters](#)

**Examples**

```
# 20 Kenyon cells  
data(kcs20, package='nat')  
# calculate mean, normalised NBLAST scores  
x=nblast(kcs20, kcs20, normalised=TRUE)  
x=(x+t(x))/2  
# note that specifying db explicitly could be avoided by use of the  
# \code{nat.default.neuronlist} option.  
plot3d(hclust(as.dist(x)), k=3, db=kcs20)
```

---

show\_similarity

*Display two neurons with segments coloured by similarity*

---

**Description**

Display two neurons with segments coloured by similarity

**Usage**

```
show_similarity(n1, n2, smat = get(getOption("nat.nblast.defaultsmat")),
  cols = colorRampPalette(c("#0000FF", "#FF0000")), col = "black",
  AbsoluteScale = FALSE, PlotVectors = TRUE, ...)
```

**Arguments**

n1	a neuron to compare and colour.
n2	the neuron to compare against.
smat	a score matrix.
cols	the function to use to colour the segments (e.g. <a href="#">heat.colors</a> ).
col	the colour with which to draw the comparison neuron.
AbsoluteScale	logical indicating whether the colours should be calculated based on the minimum and maximum similarities for the neuron ( <code>AbsoluteScale = FALSE</code> ) or on the minimum and maximum possible for all neurons.
PlotVectors	logical indicating whether the vectors of the dotprops representation should be plotted. If <code>FALSE</code> , only the points are plotted.
...	extra arguments to pass to <a href="#">plot3d</a> .

**Value**

`show_similarity` is called for the side effect of drawing the plot; a vector of object IDs is returned.

---

smat.fcwb

*Scoring matrices for neuron similarities in FCWB template brain*

---

**Description**

Scoring matrices quantify the log<sub>2</sub> odds ratio that a segment pair with a given distance and absolute dot product come from a pair of neurons of the same type, rather than unrelated neurons.

**Details**

These scoring matrices were generated using all by all pairs from 150 DL2 antennal lobe projection neurons from the <http://flycircuit.tw> dataset and 5000 random pairs from the same dataset.

- `smat.fcwb` was trained using nearest-neighbour distance and the tangent vector defined by the first eigen vector of the k=5 nearest neighbours.
- `smat_alpha.fcwb` was defined as for `smat.fcwb` but weighted by the factor `alpha` defined as  $(I_1 - I_2) / (I_1 + I_2 + I_3)$  where  $I_1, I_2, I_3$  are the three eigen values.

Most work on the flycircuit dataset has been carried out using the `smat.fcwb` scoring matrix although the `smat_alpha.fcwb` matrix which emphasises the significance of matches between linear regions of the neuron (such as axons) may have some advantages.

---

sparse_score_mat	<i>Convert a subset of a square score matrix to a sparse representation</i>
------------------	---

---

**Description**

This can be useful for storing raw forwards and reverse NBLAST scores for a set of neurons without having to store all the uncomputed elements in the full score matrix.

**Usage**

```
sparse_score_mat(neuron_names, dense_matrix)
```

**Arguments**

neuron\_names    a character vector of neuron names to save scores for.  
dense\_matrix    the original, dense version of the full score matrix.

**Value**

A sparse matrix, in compressed, column-oriented form, as an R object inheriting from both [CsparseMatrix-class](#) and [generalMatrix-class](#).

**See Also**

`fill_in_sparse_score_mat`

**Examples**

```
data(kcs20, package = "nat")
scores=nblast_allbyall(kcs20)
scores.3.sparse=sparse_score_mat(names(kcs20)[3], scores)
scores.3.sparse
# can also add additional submatrices
fill_in_sparse_score_mat(scores.3.sparse,scores[3:6,3:4])
```

---

subset.hclust	<i>Return the labels of items in 1 or more groups cut from hclust object</i>
---------------	--

---

**Description**

Return the labels of items in 1 or more groups cut from hclust object

**Usage**

```
## S3 method for class 'hclust'
subset(x, k = NULL, h = NULL, groups = NULL, ...)
```

**Arguments**

x	tree like object
k	an integer scalar with the desired number of groups
h	numeric scalar with height where the tree should be cut
groups	a vector of which groups to inspect.
...	Additional parameters passed to methods

**Details**

Only one of h and k should be supplied.

**Value**

A character vector of labels of selected items

---

sub_dist_mat	<i>Convert (a subset of) a raw score matrix to a distance matrix</i>
--------------	--

---

**Description**

This function can convert a raw score matrix returned by nblast into a square distance matrix or dist object. It can be used with file-backed matrices as well as regular R matrices resident in memory.

**Usage**

```
sub_dist_mat(neuron_names, scoremat = NULL, form = c("matrix", "dist"),
             maxneurons = NA)
```

**Arguments**

neuron_names	character vector of neuron identifiers.
scoremat	score matrix to use (see sub_score_mat for details of default).
form	the type of object to return.
maxneurons	set this to a sensible value to avoid loading huge (order $N^2$ ) distances directly into memory.

**Details**

Note that if neuron\_names is missing then the rownames of scoremat will be used i.e. all neuron in scoremat will be used.

**Value**

return An object of class matrix or dist (as determined by the form argument), corresponding to a subset of the distance matrix

**See Also**

Other scoremats: [nhclust](#)

---

sub_score_mat	<i>Return scores (or distances) for given query and target neurons</i>
---------------	--

---

**Description**

Scores can either be returned as raw numbers, normalised such that a self-hit has score 1, or as the average of the normalised scores in both the forwards & reverse directions (i.e.  $|query \rightarrow target| + |target \rightarrow query| / 2$ ). Distances are returned as either  $1 - normscore$  in the forwards direction, or as  $1 - normscorebar$ , where  $normscorebar$  is  $normscore$  averaged across both directions.

**Usage**

```
sub_score_mat(query, target, scoremat = NULL, distance = FALSE,
              normalisation = c("raw", "normalised", "mean"))
```

**Arguments**

query, target	character vectors of neuron identifiers.
scoremat	a matrix, ff matrix, bigmatrix or a character vector specifying the name of an ff matrix containing the all by all score matrix.
distance	logical indicating whether to return distances or scores.
normalisation	the type of normalisation procedure that should be carried out, selected from 'raw', 'normalised' or 'mean' (i.e. the average of normalised scores in both directions). If distance=TRUE then this cannot be raw.

**See Also**

[sub\\_dist\\_mat](#)

---

WeightedNNBasedLinesetMatching	<i>Compute point &amp; tangent vector similarity score between two linesets</i>
--------------------------------	---

---

**Description**

WeightedNNBasedLinesetMatching will work with 2 objects of class dotprops or neuron. The code to calculate scores directly for neuron objects gives broadly comparable scores to that for dotprops objects, but has been lightly tested. Furthermore only objects in dotprops form were used in the construction of the scoring matrices distributed in this package. It is therefore recommended to convert neuron objects to dotprops objects using the [dotprops](#) function.

**Usage**

```

WeightedNNBasedLinesetMatching(target, query, ...)

## S3 method for class 'dotprops'
WeightedNNBasedLinesetMatching(target, query,
  UseAlpha = FALSE, ...)

## S3 method for class 'neuron'
WeightedNNBasedLinesetMatching(target, query,
  UseAlpha = FALSE, OnlyClosestPoints = FALSE, ...)

```

**Arguments**

target, query    dotprops or neuron objects to compare (must be of the same class)

...            extra arguments to pass to the distance function.

UseAlpha        Whether to scale dot product of tangent vectors (default=F)

OnlyClosestPoints  
                   Whether to restrict searches to the closest points in the target (default FALSE, only implemented for dotprops).

**Details**

UseAlpha determines whether the alpha values  $(\text{eig1}-\text{eig2})/\text{sum}(\text{eig1:3})$  are passed on to `WeightedNNBasedLinesetMatching`. These will be used to scale the dot products of the direction vectors for nearest neighbour pairs.

**Value**

Value of `NNDistFun` passed to `WeightedNNBasedLinesetMatching`

**See Also**

[dotprops](#)

---

[

*Extract parts of a sparse spam matrix*

---

**Description**

Extract parts of a sparse spam matrix

**Usage**

```
## S4 method for signature 'spam,character,character,logical'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'spam,character,character,missing'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'spam,character,missing,logical'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'spam,character,missing,missing'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'spam,missing,character,logical'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'spam,missing,character,missing'  
x[i, j, ..., drop = TRUE]
```

**Arguments**

x	object to extract from.
i	row identifiers.
j	column identifiers.
...	additional arguments.
drop	logical indicating that dimensions should be dropped.

# Index

## \*Topic **package**

- nat.nblast-package, 2
- [, 22
- [,spam,character,character,logical-method (L), 22
- [,spam,character,character,missing-method (L), 22
- [,spam,character,missing,logical-method (L), 22
- [,spam,character,missing,missing-method (L), 22
- [,spam,missing,character,logical-method (L), 22
- [,spam,missing,character,missing-method (L), 22
  
- calc\_dists\_dotprods, 4, 7
- calc\_prob\_mat, 4, 7
- calc\_score\_matrix, 5, 7, 15
- colour\_clusters, 17
- create\_progress\_bar, 11
- create\_scoringmatrix, 3, 6
  
- data.frame, 4
- diag, 8
- diagonal, 8
- dist, 3, 16
- dotprops, 2, 21, 22
  
- expand.grid, 15
  
- fctraces20, 8
- fill\_in\_sparse\_score\_mat, 9
- fill\_pairs\_sparse\_score\_mat, 10
  
- hclust, 3, 16, 17
- heat.colors, 18
  
- load, 3
  
- m1ply, 6
  
- na.omit, 11
- nat.nblast (nat.nblast-package), 2
- nat.nblast-package, 2
- nblast, 2, 3, 10, 13, 14
- nblast\_allbyall, 2, 12
- NeuriteBlast, 4, 6, 10, 14
- neuron\_pairs, 7, 15
- neuronlist, 2, 4, 6, 11, 14
- nhclust, 3, 13, 15, 17, 21
  
- plot3d, 17, 18
- plot3d.hclust, 16
- plyr, 11
  
- save, 3
- set.seed, 7
- show\_similarity, 17
- simplify2array, 14
- slice, 17
- smat.fcwb, 2, 3, 18
- smat\_alpha.fcwb (smat.fcwb), 18
- spam, 10
- sparse\_score\_mat, 19
- sub\_dist\_mat, 3, 16, 20, 21
- sub\_score\_mat, 3, 13, 21
- subset.hclust, 19
  
- WeightedNNBasedLinesetMatching, 14, 21