

# Package ‘tripEstimation’

July 2, 2014

**Type** Package

**Title** Metropolis sampler and supporting functions for estimating animal movement from archival tags and satellite fixes

**Version** 0.0-41

**Imports** lattice, mgcv, rgdal, sp, zoo

**Maintainer** Michael D. Sumner <mdsumner@gmail.com>

**Description** Data handling and estimation functions for animal movement estimation from archival or satellite tags. Helper functions are included for making image summaries binned by time interval from MCMC simulations of point data.

**License** GPL-3

**NeedsCompilation** no

**ByteCompile** yes

**URL** <https://github.com/mdsumner/tripEstimation>

**Author** Michael D. Sumner [aut, cre], Simon Wotherspoon [ctb]

**Repository** CRAN

**Date/Publication** 2013-07-10 06:20:02

## R topics documented:

as.image.pimg . . . . .	2
astro . . . . .	3
behav.bin . . . . .	5
bits . . . . .	6
chain.read . . . . .	7
elevation . . . . .	7
get.mask . . . . .	8
get.sst . . . . .	9

initialize.x . . . . .	11
julday . . . . .	12
metropolis . . . . .	13
mkCalibration . . . . .	14
mkLookup . . . . .	15
norm.proposal . . . . .	16
old.metropolis . . . . .	17
pick . . . . .	18
pimg.list . . . . .	19
satellite.model . . . . .	20
solar . . . . .	21
solar.model . . . . .	22

<b>Index</b>	<b>25</b>
--------------	-----------

---

as.image.pimg	<i>Convert to image list</i>
---------------	------------------------------

---

## Description

Converts Probability image (pimage) component to standard R xyz list image.

## Usage

```
as.image.pimg(pimg)
combine(pimgs, subset = 1:length(pimgs))
coords.pimg(pimg)
get.pimgs(rootdir = NULL, f2load = "p_ImageList.Rdata")
unzipper(px)
as.local.pimg(pimg)
## S3 method for class 'pimg'
as.matrix(x, ...)
```

## Arguments

pimg	Probability image component
pimgs	pimgs
subset	subset
rootdir	rootdir
f2load	f2load
px	px
x	x
...	...

## Author(s)

Michael D. Sumner



**Value**

astro returns a list object with the components of the moon or sun's position,

r	rho component
theta	theta component - elevation
phi	phi component - azimuth

**Warning**

Some of this could be faster (particularly the use of LMST in "astro" is not precalculated)

**Note**

Thanks to Nick.Ellis@csiro.au for pointing out a mistake pre-0.0-27

**Author(s)**

Michael D. Sumner

**References**

```
@BOOK{,  
  title = {Astronomy on the Personal Computer},  
  publisher = {Springer-Verlag, Berlin},  
  year = {1994},  
  author = {Oliver Montenbruck and Thomas Pflieger},  
  edition = {2 (translated from German by Storm Dunlop)},  
}
```

**See Also**

See Also [elevation](#)

**Examples**

```
## the moon  
tm <- Sys.time() + seq(by = 3600, length = 100)  
moon <- lunar(tm)  
rtp <- astro(147, -42, moon)  
op <- par(mfrow = c(2,1))  
plot(tm, rtp$theta, main = "lunar elevation, Hobart")  
plot(tm, rtp$phi, main = "lunar azimuth, Hobart")  
par(op)  
  
## the sun  
tm <- Sys.time() + seq(by = 3600, length = 100)  
sun <- mini.sun(tm)  
rtp <- astro(147, -42, sun)  
op <- par(mfrow = c(2,1))
```

```

plot(tm, rtp$theta, main = "solar elevation, Hobart")
plot(tm, rtp$phi, main = "solar azimuth, Hobart")
par(op)
## Not run:
  elev.gmt <- mkElevationSeg(1, tm)
  plot(tm, rtp$theta, main = "solar elevation mini.sun versus NOAA")
  lines(tm, elev.gmt(1, 147, -42))

## End(Not run)

```

---

behav.bin

*Bin MCMC chains.*


---

## Description

Bin MCMC chains in probability image summaries.

## Usage

```

behav.bin(z, pimgs, weights = NULL)
bin.pimg(pimg, xy, w = 1)
chunk.bin(filename, pimgs, weights = NULL, chunk = 2000, proj = NULL)

```

## Arguments

z	z
pimgs	pimgs
weights	weights
pimg	pimg
xy	xy
w	w
filename	filename
chunk	chunk
proj	proj

---

bits *Set and get bits from binary masks.*

---

### Description

Utility functions to access bits from numeric values, for the efficient storage of spatial masks.

### Usage

```
bits(object, bit)
```

```
bits(object, bit) <- value
```

### Arguments

object	a numeric value
bit	the desired bit
value	logical value to set bit to

### Details

R uses 32-bit integers, so we can (easily) access 31 binary matrices in each numeric matrix. This is very useful for storing long time-series of spatial masks, required for track-location estimation from archival tags.

### Value

A numeric object with the given bit set, or a logical value designating the status of the given bit.

### Note

The 32nd bit is harder to access, so we ignore it.

### Author(s)

Michael D. Sumner

### See Also

See Also [get.mask](#) for a higher level access of a mask object

### Examples

```
a <- 1
bits(a, 0) ## 1
bits(a, 2) <- 1
a # 5
```

---

chain.read	<i>Manage MCMC cache.</i>
------------	---------------------------

---

### Description

These functions read and write to cache files for storing long MCMC outputs from model functions, such as [solar.model](#) or [satellite.model](#).

### Usage

```
chain.read(filename)
chain.dim(filename)
chain.write(filename, A, append = FALSE)
```

### Arguments

filename	cache file for model chain
A	chain array
append	append to existing file or overwrite?

### Author(s)

Michael D. Sumner and Simon Wotherspoon

### See Also

[ping.list](#)

---

elevation	<i>Calculate elevation of astronomical objects</i>
-----------	----------------------------------------------------

---

### Description

Function to calculate elevation.

### Usage

```
elevation(lon, lat, sun)
```

### Arguments

lon	vector of longitude values
lat	vector of latitude values
sun	pre-stored values as returned by <a href="#">solar</a> or <a href="#">lunar</a>

**Author(s)**

Michael D. Sumner

**References**<http://www.srrb.noaa.gov/highlights/sunrise/azel.html>

---

`get.mask`*Create, access and manipulate spatial masks*

---

**Description**

Spatial masks are stored using the xyz-list structure used by `image` or as a series of masks stored as bits in the z-component as matrix or array object. `get.mask` is used to extract a specific mask from the binary storage, and `mkSmall` can be used to quickly down-sample an existing mask or image.

**Usage**`get.mask(masks, k)``mkSmall(lst, thin = 10)``set.mask(object, segment) <- value``mkMaskObject(xs, ys, nsegs)`**Arguments**

<code>masks</code>	A list object with components x, y, and z containing spatial masks
<code>k</code>	specifies the k-th mask
<code>lst</code>	an xyz-list structure with z containing either a matrix or array
<code>thin</code>	integer factor to down-sample grid
<code>object</code>	array Mask object
<code>segment</code>	segment number to be modified in the mask
<code>value</code>	individual mask to be set
<code>xs</code>	x coordinates of mask cells
<code>ys</code>	y coordinates of mask cells
<code>nsegs</code>	number of segments to be represented

**Author(s)**

Michael D. Sumner



**See Also**

[mkLookup](#) for the use of these masks to query individual locations and locations measured over time. See [bits](#) for the underlying mechanism to set and get mask bits.

For the use of the xyz-list structure see [image](#).

**Examples**

```

data(volcano)
d <- list(x = seq(-10, 10, length = nrow(volcano)),
         y = seq(-5, 5, length = ncol(volcano)),
         z = array(0, c(nrow(volcano), ncol(volcano), 2)) )
mv <- min(volcano)

for (i in 0:61) {
  blk <- (i %% 31) + 1
  bit <- (i - 1) %% 31
  bits(d$z[, , blk], bit) <- volcano > (mv + i*1.6 )
}
for (i in 0:61) image(get.mask(d, i))

## an object with 62 masks is only twice the size of the source data
object.size(d) / object.size(volcano)

## Not run:
## plot a smaller version
image(get.mask(d, 20), 5)

## pretend we have only one masks
lookup <- mkLookup(get.mask(d, 30), by.segment = FALSE)

## interactive to show use of lookup function
image(get.mask(d, 30), main = "Click on the red (FALSE) and cream (TRUE) areas")
for (i in 1:10) {x <- matrix(unlist(locator(1)), ncol = 2);text(x[1], x[2], lookup(x) > 0)}

## End(Not run)

```

---

get.sst

*Read SST data from online service.*


---

**Description**

Functions to read SST data from online services, by specifying spatial and temporal bounds.

**Usage**

```

get.sst(xlim = NULL, ylim = NULL, tlim = NULL,
server = "http://atlas.nmfs.hawaii.edu/cgi-bin/reynolds_extract.py")

```

### Arguments

xlim	Longitude range of SST to read.
ylim	Latitude range of SST to read.
tlim	Time range of SST to read.
server	Server to read from.

### Details

This functionality was originally taken from the kfsst package by Anders Nielsen.

Longitude xlim range may be specified in [-180, 180] or [0, 360] convention. The result is given in [-180, 180].

Time range must be given in POSIXct form.

### Value

A list object with the temperature data and coordinates.

x, y, t	Coordinates of the temperature data
z	Matrix or array of temperature data

### Author(s)

Michael D. Sumner

### References

Original concept taken from kfsst: <http://www.soest.hawaii.edu/tag-data/tracking/kfsst/>

### See Also

See Also [mkMaskObject](#) for the use of these data for masks.

### Examples

```
## Not run:  
d0 <- read.url.sst(tlim = range(ISOdatetime(2009, 1:3, 1, 0, 0, 0)))  
image(d0$x, d0$y, d0$z[,1], axes = TRUE)
```

```
## End(Not run)
```

---

initialize.x	<i>Diagnose and initialize light level estimation.</i>
--------------	--------------------------------------------------------

---

### Description

Primarily for the purposes of initializing the estimation, these functions can also be used for diagnostic purposes. `position.logp` produces grids of simplistic position likelihood for each twilight and uses those to initialize positions for running estimations.

### Usage

```
position.logp(model, x1, x2, xrest = NULL, subset = 1:model$n,
initialize.x = TRUE, start = NULL, end = NULL, prob = 0.8, winoffset = 5)
```

```
initialize.x(model, x1, x2, xrest = NULL)
```

```
light.quantile(model, chain, day, seg, prob1 = c(0.025, 0.5, 0.975))
```

```
show.segment(model, chain, segment, day, light, k, n = 50, ...)
```

### Arguments

<code>model</code>	estimation model object
<code>x1</code>	vector of x-coordinates defining the prior grid
<code>x2</code>	vector of y-coordinates defining the prior grid
<code>xrest</code>	value for remaining parameters - default is light attenuation
<code>subset</code>	evaluate subset of segments - default uses all
<code>initialize.x</code>	logical - create initial points for x?
<code>prob</code>	probability - threshold to apply to overlapping quantiles, defaults to 0.8
<code>winoffset</code>	an odd-numbered window size to use when intersecting subsequent segments - defaults to 5
<code>chain</code>	chain object from estimation
<code>day</code>	POSIXct vector of date-times
<code>seg</code>	desired segment
<code>prob1</code>	probability level for quantile
<code>start</code>	known position of release
<code>end</code>	known position of recapture
<code>segment</code>	vector of segment data
<code>light</code>	vector of light data
<code>k</code>	desired segment to show
<code>n</code>	length of vector to evaluate
<code>...</code>	additional arguments to be passed to plot

**Details**

The primary function here is `position.logp`, for initializing the estimation for `solar.model` and `metropolis0`.

**Author(s)**

Michael D. Sumner

---

julday

*Julian day and Julian century calculations from date-time values*

---

**Description**

Date values required by `solar`.

**Usage**

`julday(tm)`

`julcent(time)`

**Arguments**

`tm`            vector of date-times

`time`          vector of date-times

**Author(s)**

Michael D. Sumner

**References**

<http://www.srrb.noaa.gov/highlights/sunrise/azel.html>

---

metropolis	<i>Metropolis-Hastings sampler for location estimation for archival and satellite tag</i>
------------	-------------------------------------------------------------------------------------------

---

## Description

These functions provide a direct implementation of the Metropolis-Hastings algorithm, for calculating marginal posterior (locations and full-track estimates) properties using Markov Chain Monte Carlo. The sampler is written completely in R, vectorized to be as fast as possible. The sampler can include likelihood functions for large data records (including light and water temperature), as well as *mask* functions for simpler rejection sources. Behavioural constraints are implemented using a red/black update, so that location estimates  $X$  and  $Z$  may be estimated in an efficient manner. The parameter estimates may be cached and later queried arbitrarily.

## Usage

```
metropolis(model, iters = 1000, thin = 10, start.x = NULL, start.z = NULL)
```

```
metropolis0(model, iters = 1000, thin = 10, start.x = NULL, start.z =
NULL)
```

## Arguments

<code>model</code>	model for estimation, such as one created by <a href="#">solar.model</a>
<code>iters</code>	number of iterations to run
<code>thin</code>	number of iterations to thin by
<code>start.x</code>	starting points for the primary locations
<code>start.z</code>	starting points for the intermediate locations (midpoints between the <code>start.x</code> points is a good first guess)

## Details

[metropolis0](#) is a slightly different version of [metropolis](#) that enables an initialization step, required to find parameter estimates that are consistent with any masks used. It is difficult to make this step more elegant, and so we live with the two versions.

In terms of the estimates,  $X$ 's have  $m$  records with  $n$  parameters, where  $m$  is the number of data records in time (twilights for archival tags, Argos estimates for satellite tags) and  $n$  is at least  $x$ -coordinate,  $y$ -coordinate and maybe  $k$ -attenuation for light.  $Z$ 's have  $m-1$  records with 2 parameters for 'x' and 'y' (which are usually Longitude and Latitude). These parameters may be increased or changed, they are tied only to the likelihood functions used, not the sampler itself. Also, coordinate transformations may be used inside the model and likelihood functions, in order to use an appropriate map projection. Solar calculations rely on lon/lat and so this step does slow down light level geo-location.

**Value**

A MCM *Chain* stored as a list containing

model	The model object used by the sampler
x	The last <code>iters</code> X-samples accepted, stored as an <code>c(m, n, iters)</code> array
z	The last <code>iters</code> Z-samples accepted, stored as an <code>c(m - 1, 2, iters)</code>
last.x	The last accepted X-sample, stored as a <code>c(m, n)</code> matrix
last.z	The last accepted Z-sample, stored as a <code>c(m, 2)</code> matrix

**Author(s)**

Michael D. Sumner and Simon Wotherspoon

**References**

Sumner, Wotherspoon and Hindell (2009). Bayesian Estimation of Animal Movement from Archival and Satellite Tags, PLoS ONE. <http://dx.plos.org/10.1371/journal.pone.0007324>

**See Also**

[solar.model](#), [satellite.model](#)

---

mkCalibration

*Create calibration of solar elevation to measured light level.*

---

**Description**

Using a set of light level data from a known location create a calibration function to return the expected light level given solar elevation.

**Usage**

```
mkCalibration(x, known = NULL, elim = c(-36, 12), choose = TRUE)
```

**Arguments**

x	a data frame containing at least <code>gmt</code> and <code>light</code>
known	a known position - as a 2-element <code>c(x, y)</code> coordinate
elim	a 2-element vector of the range of solar elevation to define
choose	logical - choose segments from a plot or use all the data?

**Details**

It is assumed that the data frame `x` has columns "gmt" with POSIXct date-times and "light" with numeric light level data.

**Value**

A function, defined by `approxfun`.

**Author(s)**

Michael D. Sumner

**See Also**

[approxfun](#)

---

mkLookup

*Create a lookup function to query locations against spatial masks*

---

**Description**

Simple pixel spacing is used to overlay point locations on a spatial grid, or a series of grids.

**Usage**

```
mkLookup(x, by.segment = TRUE)
```

**Arguments**

`x` an xyz-list with matrix or array of masks  
`by.segment` logical - is the mask to be queried separately for each time step?

**Value**

A function, with one argument - a matrix of points - that returns a logical vector indicating the overlay of each point against the masks.

**Note**

Very little error checking is done.

**Author(s)**

Michael D. Sumner

**See Also**

[get.mask](#) and related examples for creating and using masks.

See [overlay](#) for more general capabilities for overlays.

---

norm.proposal	<i>Manage proposal functions tune variance for metropolis sampler</i>
---------------	-----------------------------------------------------------------------

---

**Description**

Generate new proposals for the x from the current. Generates all x at once.

**Usage**

```
norm.proposal(m, n, sigma)
```

```
mvnorm.proposal(m, n, Sigma)
```

```
bmvnorm.proposal(m, n, Sigma)
```

**Arguments**

m	number of records
n	number of parameters
sigma	variance
Sigma	variance

**Details**

norm.proposal - Independent Normal proposal - every component is independent, with variances of individual components determined by sigma. The recycling rule applies to sigma, so sigma may be a scalar, an m vector or a m by n matrix.

mvnorm.proposal - Multivariate Normal proposal - all components of all points are correlated. In this case Sigma is the joint covariance of the m\*n components of the proposal points.

bmvnorm.proposal - Block Multivariate Normal proposal - components of points are correlated, but points are independent. Here Sigma is an array of m covariance matrices that determine the covariance of the m proposal points.

**Value**

An list object with get, set and tune functions to manage the state of the proposals.

proposal	propose new set of parameters from last
get	get variance values
set	set variance values
tune	tune the variance for proposal functions

**Author(s)**

Simon Wotherspoon



---

old.metropolis      *Older versions of solar location estimation*

---

### Description

Some deprecated functions, originally used purely for light level estimation before the sampling algorithm was generalized for satellite models as well.

### Usage

```
mkElevationSeg(segments, day)

mkNLPosterior(segments, day, light, calib)

old.dist.gc(x1, x2 = NULL)

old.find.init(mask, nseg, nlpost, pars = c("Lon", "Lat", "k"))

old.metropolis(nlpost, lookup, p0, cov0, start, end, iter = 1000, step = 100)

old.mkLookup(x, binArray = TRUE)

k.prior(seg, ps)
```

### Arguments

segments	vector identifying the segment of each time and light value
day	date-time values in POSIXct
light	vector of light data
calib	calibration function for light levels
x1	matrix of track locations
x2	matrix of track locations (optional second part)
mask	image object of masked areas
nseg	number of (twilight) segments
nlpost	negative log posterior function
pars	names of parameters
lookup	lookup function for masked areas
p0	initial locations for sampler
cov0	covariance matrix for sampler
start	known start parameters
end	known end parameters
iter	number of iterations

step	number of thinning iterations per iter
x	image-like object of matrix or array of binary masks
binArray	logical: are the masks compressed into bits?
seg	segment
ps	light attenuation value

### Details

These functions are included for legacy purposes, this was the original implementation.

### Value

If it is a LIST, use

### Author(s)

Michael D. Sumner

### See Also

Please use the more up to date function [metropolis](#), with the models such as [solar.model](#) or [satellite.model](#).

---

pick *Choose twilight segments interactively from light data.*

---

### Description

pick plots up series of light data against record ID, allowing the user to click on the beginnings and ends of twilight in sequence. picksegs generates a vector of segment IDs for each record.

### Usage

```
pick(id, val, nsee = 10000)
```

```
picksegs(twind, n)
```

### Arguments

id	index vector to identify records
val	sequence of data (light levels) to choose segments from
nsee	number of points to plot per screen
twind	vector of index pairs generated by pick
n	Number of segments values required - length of record

**Value**

pick returns a vector where each value (obtained using [locator](#) is the x coordinate for the begin or end of a twilight.

picksegs uses these paired indexes to return a vector of segment IDs, with NAs for non-twilight periods.

**Warning**

Segments are expected to be chosen as non-overlapping.

**Note**

It seems best to choose more of the light data than less, using the `ekstrom` keyword to [solar.model](#) we can limit the solar elevation used.

**Author(s)**

Michael D. Sumner

**Examples**

```
## Not run:

d <- sin(seq(0, 10, by = 0.01))
id <- 1:length(d)
## choose a series of start-begin pairs
pk <- pick(id, d, 1000)
## your start/ends should be marked as blue versus red
plot(id, d, col = c("red", "blue")[is.na(picksegs(pk, 1000))+1])

## End(Not run)
```

---

pimg.list

*Create a collection of probability images, for MCMC binning.*

---

**Description**

Pimage lists.

**Usage**

```
pimg(xmin, xmax, xn, ymin, ymax, yn)
pimg.list(times, xlim, ylim, img.dim, Z = TRUE)
```

**Arguments**

xmin	xmin
xmax	xmax
xn	xn
ymin	ymin
ymax	ymax
yn	yn
times	times
xlim	xlim
ylim	ylim
img.dim	img.dim
Z	Z

---

satellite.model	<i>Function to create a satellite model object for metropolis location sampler</i>
-----------------	------------------------------------------------------------------------------------

---

**Description**

A model to manage likelihood functions, environmental masks and behavioural likelihood functions for pre-derived satellite locations. There are some options for configuration, but this may be considered a template for any given model. The model *function* exists simply to make the object construction simple.

**Arguments**

day	vector of date-times for each light level
X	matrix of pre-derived satellite locations
proposal.x	function from object managing X proposals
proposal.z	function from object managing Z proposals
mask.x	lookup function for X's against masks
mask.z	lookup function for Z's against masks
fix.release	logical - is the release point known?
fix.recapture	logical - is the recapture point known?
start.x	starting positions for the primary locations, see <a href="#">position.logp</a>
start.z	starting positions for the intermediat locations.
posn.sigma	variance for locations
behav.dist	distribution to use for behavioural constraint
behav.mean	mean to use for behavioural distribution
behav.sd	variance for behavioural distribution
proj.string	PROJ.4 string for coordinate system used

**Details**

`posn.sigma` may be a single value for all estimates, or a vector of values for each position estimate. Transformation of coordinates is supported via a simple function that only performs coordinate transforms if `proj.string` is not `longlat`. See [project](#) for the underlying functionality.

**Value**

See `solar.model` for some related detail.

**Note**

These are simple wrapper functions to create the desired model for use in [metropolis](#). These models are structurally very simple and may be easily edited as required.

**Author(s)**

Michael D. Sumner

**References**

Sumner, Wotherspoon and Hindell (2009). Bayesian Estimation of Animal Movement from Archival and Satellite Tags, PLoS ONE. <http://dx.plos.org/10.1371/journal.pone.0007324>

**See Also**

See also [solar.model](#) for the counterpart model for estimating positions for light tags.

---

solar	<i>Calculate solar position parameters</i>
-------	--------------------------------------------

---

**Description**

Pre-calculates astronomical solar position components for Earth-location sampling functions.

**Usage**

```
solar(day)
```

**Arguments**

day	vector of date-time values
-----	----------------------------

**Value**

A list of the following values for each input time:

solarTime	solar time
sinSolarDec	sine solar declination
cosSolarDec	cosine solar declination

**Note**

No account is made for horizon refraction, but this was available in the original (Javascript) code.

**Author(s)**

Michael D. Sumner

**References**

<http://www.srrb.noaa.gov/highlights/sunrise/azel.html>

---

solar.model	<i>Function to create a solar model object for metropolis location sampler</i>
-------------	--------------------------------------------------------------------------------

---

**Description**

A solar model to manage likelihood functions, environmental masks and behavioural likelihood functions. There are several options for configuring the model, and this may be considered a template for any given model. The model *function* exists simply to make the object construction simple.

**Usage**

```
solar.model(segments, day, light,
proposal.x, proposal.z, mask.x, mask.z,
fix.release = TRUE, fix.recapture = TRUE,
calibration,
light.sigma = 7, k.sigma = 10,
behav = "speed", behav.dist = "gamma",
behav.mean, behav.sd,
proj.string = "+proj=longlat",
  ekstrom = c(-5, 3, light.sigma),
  ekstrom.limit = "light")
```

**Arguments**

segments	vector identifying twilight segment
day	vector of date-times for each light level
light	vector of light levels
proposal.x	function from object managing X proposals
proposal.z	function from object managing Z proposals
mask.x	lookup function for X's against masks
mask.z	lookup function for Z's against masks
fix.release	logical - is the release point known?
fix.recapture	logical - is the recapture point known?

calibration	calibration function for predicted light level for solar elevation
light.sigma	variance for light data
k.sigma	variance for light attenuation
behav	model distributions to be used for behaviour - defaults to "speed"
behav.dist	distribution to be used for behaviour
behav.mean	mean for behavioural distribution
behav.sd	variance for behavioural distribution
proj.string	PROJ.4 string for coordinate system used
ekstrom	parameters to use for ekstrom limit - min elevation, max elevation, sigma for outside that range
ekstrom.limit	mode of ekstrom limit to impose - defaults to "light"

### Details

The vectors of `segments`, `day` and `light` are expected to be of the same length.

Fixed recapture and release points are treated specially for ease of sampling, but the sampling is written to be general for any fixed locations.

Behavioural models may be specified either as lognormal or log-gamma. By editing the function created as `logp.behavioural` this may be specified differently.

Transformation of coordinates is supported via a simple function that only performs coordinate transforms if `proj.string` is not `longlat`. See [project](#) for the underlying functionality.

### Value

`proposal.x(x)` - generates new proposals for the `x` from the current `x`. Generates all `x` at once.

`proposal.z(z)` - generates new proposals for the `x` from the current `z`. Generates all `z` at once.

`mask.x(x)` - mask function for the `x`. Simultaneously tests all `x` and returns a vector of booleans indicating which are acceptable.

`mask.z(z)` - mask function for the `z`. Simultaneously tests all `z` and returns a vector of booleans indicating which are acceptable.

`logp.position(x)` - Given the set of `x`, returns a vector that gives the contribution each `x` make to the log posterior based on position alone.

`logp.behaviourial(k,xa,z,xb)` - Computes the contribution to the log posterior from the behavioural model on a subset of segments that make up the path. Here `k` is a vector of the segment numbers, where the segments pass from `xa` to `z` to `xb`, and the function returns the contribution to the log posterior from each segment. This is the only function expected to work with only a subset of the `x` and `z`.

`start.x` - suggested starting points for the `x`

`start.z` - suggested starting points for the `z`

The only function that must operate on a subset of the `x/z` is `logp.behaviourial`. All the other functions operate on all `x` or `z` simultaneously, simplifying the implementation for the user.

Note that  $x$  can consist of several parameters, not just the locations, but we assume the first two components of each  $x$  specify the location. For example, in the light level models each  $x$  is  $(lon, lat, k)$  where  $k$  is the attenuation of the light level.

Some details of this implementation are not as nice as they could be. First, it would be better if did not calculate the contributions to the posterior for points the mask rejects. Also, it may be better to separate the specification of the functions that generate proposals from the other functions, so that we can tune the proposal distributions without re-generating the whole model specification.

**Author(s)**

Simon Wotherspoon and Michael Sumner



# Index

- \*Topic **dplot**
  - initialize.x, 11
  - mkCalibration, 14
  - pick, 18
- \*Topic **manip**
  - as.image.pimg, 2
  - astro, 3
  - behav.bin, 5
  - bits, 6
  - chain.read, 7
  - elevation, 7
  - get.mask, 8
  - get.sst, 9
  - initialize.x, 11
  - julday, 12
  - metropolis, 13
  - mkCalibration, 14
  - mkLookup, 15
  - norm.proposal, 16
  - pick, 18
  - pimg.list, 19
  - satellite.model, 20
  - solar, 21
- \*Topic **misc**
  - old.metropolis, 17
- \*Topic **models**
  - solar.model, 22
- \*Topic **spatial**
  - get.sst, 9
- approxfun, 15
- as.image.pimg, 2
- as.local.pimg (as.image.pimg), 2
- as.matrix.pimg (as.image.pimg), 2
- astro, 3
- behav.bin, 5
- bin.pimg (behav.bin), 5
- bits, 6, 9
- bits<- (bits), 6
- bmvnorm.proposal (norm.proposal), 16
- chain.dim (chain.read), 7
- chain.read, 7
- chain.write (chain.read), 7
- chunk.bin (behav.bin), 5
- combine (as.image.pimg), 2
- coords.pimg (as.image.pimg), 2
- elevation, 4, 7
- EQUHOR (astro), 3
- FRAC (astro), 3
- get.mask, 6, 8, 15
- get.pimgs (as.image.pimg), 2
- get.sst, 9
- image, 8, 9
- initialize.x, 11
- julcent (julday), 12
- julday, 12
- k.prior (old.metropolis), 17
- light.quantile (initialize.x), 11
- LMST (astro), 3
- locator, 19
- lunar, 7
- lunar (astro), 3
- metropolis, 13, 13, 18, 21
- metropolis0, 12, 13
- metropolis0 (metropolis), 13
- mini.sun (astro), 3
- MJD (astro), 3
- mkCalibration, 14
- mkElevationSeg (old.metropolis), 17
- mkLookup, 9, 15
- mkMaskObject, 10

mkMaskObject (get.mask), 8  
mkNLPosterior (old.metropolis), 17  
mkSmall (get.mask), 8  
mvnorm.proposal (norm.proposal), 16  
  
norm.proposal, 16  
  
old.dist.gc (old.metropolis), 17  
old.find.init (old.metropolis), 17  
old.metropolis, 17  
old.mkLookup (old.metropolis), 17  
overlay, 15  
  
pick, 18  
picksegs (pick), 18  
ping (ping.list), 19  
ping.list, 19  
POLAR (astro), 3  
position.logp, 20  
position.logp (initialize.x), 11  
project, 21, 23  
  
satellite.model, 7, 14, 18, 20  
set.mask<- (get.mask), 8  
show.segment (initialize.x), 11  
solar, 7, 12, 21  
solar.model, 7, 12–14, 18, 19, 21, 22  
  
unzipper (as.image.ping), 2