

Package ‘tspmeta’

July 2, 2014

Title Instance feature calculation and evolutionary instance generation for the traveling salesman problem.

Description Instance feature calculation and evolutionary instance generation for the traveling salesman problem. Also contains code to “morph” two TSP instances into each other. And the possibility to conveniently run a couple of solvers on TSP instances.

Author Bernd Bischl <bernd_bischl@gmx.net>, Jakob Bossek <jakob.bossek@tu-dortmund.de>, Olaf Mersmann <olafm@p-value.net>

Maintainer Bernd Bischl <bernd_bischl@gmx.net>

URL <https://github.com/berndbischl/tspmeta>

BugReports <https://github.com/berndbischl/tspmeta/issues>

License BSD_3_clause + file LICENSE

Depends ggplot2, TSP, MASS

Imports BBmisc, fpc, vegan, stringr, splancs

Suggests testthat

LazyData yes

ByteCompile yes

Version 1.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2014-02-25 22:33:14

R topics documented:

as_TSP	2
autoplot.tsp_instance	3
center_of_mass	4
fast_two_opt	4
features	5
feature_angle	5
feature_bounding_box	6
feature_centroid	6
feature_chull	7
feature_cluster	7
feature_distance	8
feature_modes	8
feature_mst	9
feature_nnds	9
get_solvers	10
greedy_point_matching	10
instance_dim	11
morph_instances	11
normalization_angle	12
normalize_rotation	12
number_of_cities	13
numvec_feature_statistics	13
print.tsp_instance	14
random_instance	14
read_tsplib_instance	15
read_tsplib_instances	16
read_tsplib_tour	16
remove_zero_distances	17
rescale_instance	17
rotate_coordinates	18
rotate_instance	19
run_solver	19
tsp_generation_ea	20
tsp_instance	21
Index	22

as_TSP

*Convert to TSP instance object of package TSP.***Description**

Convert to TSP instance object of package TSP.

Usage

```
as_TSP(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---------------------------------

Value

TSP .

autoplot.tsp_instance *Plot TSP instance.*

Description

Plot TSP instance.

Usage

```
## S3 method for class 'tsp_instance'  
autoplot(object, opt_tour, ...)
```

Arguments

object	[tsp_instance] TSP instance.
opt_tour	[TOUR] TOUR object from package TSP, containing order of cities, tour length and method name that generated this solution.
...	[any] Not used.

Value

ggplot .

center_of_mass *Return the center of all cities of a TSP instance.*

Description

Return the center of all cities of a TSP instance.

Usage

```
center_of_mass(instance)
```

Arguments

instance [tsp_instance]
TSP instance.

Value

numeric(2) Center of all cities of the TSP instance.

fast_two_opt *Runs 2-Opt local search on TSP instance.*

Description

Runs 2-Opt local search on TSP instance.

Usage

```
fast_two_opt(x, initial_tour)
```

Arguments

x [tsp_instance]
TSP instance.

initial_tour [numeric]
Initial tour.

Value

TOUR TOUR object from package TSP, containing order of cities, tour length and method name that generated this solution.

features	<i>Calculates list of all TSP features for an instance.</i>
----------	---

Description

Calculates list of all TSP features for an instance.

Usage

```
features(x, rescale = TRUE)
```

Arguments

x	[tsp_instance] TSP instance
rescale	[logical(1)] Rescale x to $[0, 1]^2$ before calculation of features? Default is TRUE.

Value

list .

See Also

[feature_angle](#), [feature_centroid](#), [feature_cluster](#), [feature_bounding_box](#), [feature_chull](#),
[feature_distance](#), [feature_modes](#), [feature_mst](#), [feature_nnds](#)

Examples

```
x = random_instance(10)
print(features(x))
```

feature_angle	<i>Angle features.</i>
---------------	------------------------

Description

Statistics of the distribution of the angle between a node and its 2 next neighbors.

Usage

```
feature_angle(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list .

 feature_bounding_box *Bounding box features.*

Description

Determines the ratio of cities which lie within a certain distance to the bounding box.

Usage

```
feature_bounding_box(x, distance_fraction = 0.1)
```

Arguments

x	[tsp_instance]
	TSP instance.
distance_fraction	[numeric(1)]
	Distance ratio to bounding box.

Value

list .

 feature_centroid *Centroid features.*

Description

Includes the coordinates of the mean coordinates of the the point cloud and the statistics of the distances of all cities from it.

Usage

```
feature_centroid(x)
```

Arguments

x	[tsp_instance]
	TSP instance.

Value

list .

feature_chull	<i>Convex hull features.</i>
---------------	------------------------------

Description

Determines the area of the convex hull and the ratio of the cities which lie on the convex hull in the euclidean space.

Usage

```
feature_chull(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list .

feature_cluster	<i>Cluster features.</i>
-----------------	--------------------------

Description

Determines the number of clusters and the mean distances from all cities in a cluster to its centroid.

Usage

```
feature_cluster(x, epsilon)
```

Arguments

x	[tsp_instance] TSP instance.
epsilon	[numeric(1)] Probability in [0,1]. Used to compute the reachability distance for the underlying dbscan clustering algorithm.

Value

list .

feature_distance	<i>Distance features.</i>
------------------	---------------------------

Description

Computes different statistics describing the distribution of pairwise distances between cities.

Usage

```
feature_distance(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list List of statistics describing the distribution of distances.

feature_modes	<i>Modes of edge cost distribution feature.</i>
---------------	---

Description

Includes the number of modes of the edge cost distribution.

Usage

```
feature_modes(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list List containing (estimated) number of modes.

feature_mst	<i>MST features.</i>
-------------	----------------------

Description

Construct minimum spanning tree, then calculate the statistics of a) the distances in the MST, b) the depths of all nodes in the MST.

Usage

```
feature_mst(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list .

feature_nnds	<i>Nearest neighbor features.</i>
--------------	-----------------------------------

Description

Statistics describing the distribution of distances of each city to its nearest neighbor.

Usage

```
feature_nnds(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

list .

get_solvers *Returns integrated solver names.*

Description

Returns integrated solver names.

Usage

```
get_solvers()
```

Value

character .

greedy_point_matching *Greedy point matching*

Description

Pairs of cities are matched in a greedy fashion for morphing, first the closest pair w.r.t. euclidean distance, then the closest pair of the remaining cities, and so on.

Usage

```
greedy_point_matching(x, y)
```

Arguments

x	[tsp_instance] First TSP instance
y	[tsp_instance] Second TSP instance

Value

matrix Numeric matrix of point indices with shortest distance.

instance_dim	<i>Get instance dimensionality (space where coords live).</i>
--------------	---

Description

Get instance dimensionality (space where coords live).

Usage

```
instance_dim(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

integer(1) .

morph_instances	<i>Morphing (convex-combination) of two instances with parameter alpha.</i>
-----------------	---

Description

Pairs of cities are matched in a greedy fashion, see [greedy_point_matching](#).

Usage

```
morph_instances(x, y, alpha)
```

Arguments

x	[tsp_instance]
y	[tsp_instance]
alpha	[numeric(1)] Coefficient alpha for convex combination.

Value

[tsp_instance](#) Morphed TSP instance.

Examples

```
x = random_instance(10)
y = random_instance(10)
z = morph_instances(x, y, 0.5)
autoplot(x)
autoplot(y)
autoplot(z)
```

normalization_angle	<i>Calculate rotation angle such that the main axis through the cities is aligned with the X axis.</i>
---------------------	--

Description

Calculate rotation angle such that the main axis through the cities is aligned with the X axis.

Usage

```
normalization_angle(instance)
```

Arguments

instance	[tsp_instance] TSP instance.
----------	---

Value

numeric(1)

normalize_rotation	<i>Normalize an instance w.r.t. its rotation.</i>
--------------------	---

Description

Normalization is performed by aligning the main axis of the cities with the X axis.

Usage

```
normalize_rotation(instance)
```

Arguments

instance	[tsp_instance]
----------	----------------------------------

Value

A rotated tsp_instance.

See Also

[normalization_angle](#)

number_of_cities	<i>Get number of cities in tsp instance.</i>
------------------	--

Description

Get number of cities in tsp instance.

Usage

```
number_of_cities(x)
```

Arguments

x	[tsp_instance] TSP instance.
---	---

Value

integer(1) .

numvec_feature_statistics	<i>Computes statistics from a vector of values.</i>
---------------------------	---

Description

E.g. computes features from distribution of distance. Computed statistics: min, median, mean, max, sd, span, coeff_of_var.

Usage

```
numvec_feature_statistics(x, name, na.rm = TRUE)
```

Arguments

x	[numeric] Numeric vector.
name	[numeric] Prefix name for elements in result list.
na.rm	[logical(1)] Should NAs in x be removed? Default is TRUE.

Value

list Elements are named <name_statistic>.

print.tsp_instance *Print TSP instance*

Description

Print TSP instance

Usage

```
## S3 method for class 'tsp_instance'
print(x, ...)
```

Arguments

x	[tsp_instance] TSP instance.
...	[any] Not used.

random_instance *Generates a random TSP instance by scattering random points in a hypercube.*

Description

Generates a random TSP instance by scattering random points in a hypercube.

Usage

```
random_instance(size, d = 2, lower = 0, upper = 1)
```

Arguments

size	[integer(1)] Number of cities.
d	[integer(1)] Space dimensionality, e.g. 2D. Default is 2D.
lower	[numeric(1)] Lower box constraint for hypercube. Default is 0.
upper	[numeric(1)] upper box constraint for hypercube. Default is 1.

Value

tsp_instance .

read_tsplib_instance *Read in a TSPLIB style Traveling Salesman Problem from a file.*

Description

The current state of the parser does not understand all variants of the TSPLIB format. Much effort has been spent making the parser as robust as possible. It will stop as soon as it sees input it cannot handle.

Usage

```
read_tsplib_instance(path)
```

Arguments

path	[character(1)] Character string containing path to file in TSPLIB format.
------	--

Value

tsp_instance .

read_tsplib_instances *Read in multiple TSPLIB style Traveling Salesman Problems from a directory.*

Description

Read in multiple TSPLIB style Traveling Salesman Problems from a directory.

Usage

```
read_tsplib_instances(path, pattern = "*.tsp", max_size = 1000,
  use_names = TRUE, on_no_coords = "stop")
```

Arguments

path	[character(1)] Character string containing path to file in TSPLIB format.
pattern	[character(1)] Pattern of files under path that are considered as instances.
max_size	[numeric(1)] Upper bound for instance size (i.e. number of cities). Only applicable, if instance size is contained in file name. Default value ist 1000.
use_names	[logical(1)] Use base names of files as names of instances in returned list.
on_no_coords	[character(1)] How to handle instances which do not have any coordinates. Possible values are, "stop" and "warn" which either stop or raise a warning respectively.

Value

A list List of tsp_instance objects.

read_tsplib_tour *Read in a TSPLIB style Traveling Salesman Problem tour from a file*

Description

Read in a TSPLIB style Traveling Salesman Problem tour from a file

Usage

```
read_tsplib_tour(path)
```


Arguments

path [character(1)]
Filename of file containing a TSP tour.

Value

TOUR TOUR object from package TSP, containing order of cities, tour length and method name that generated this solution.

remove_zero_distances *Remove any duplicate cities in a tsp instance.*

Description

Remove any duplicate cities in a tsp instance.

Usage

```
remove_zero_distances(instance)
```

Arguments

instance [tsp_instance]
TSP instance object.

Value

New TSP instance in which all duplicate cities have been removed.

rescale_instance *Rescale coords of TSP instance to $[0, 1]^2$.*

Description

Rescale coords of TSP instance to $[0, 1]^2$.

Usage

```
rescale_instance(x)  
  
rescale_coords(coords)
```

Arguments

x	[tsp_instance] TSP instance.
coords	[matrix] Numeric matrix of city coordinates, rows denote cities.

Value

matrix for rescale_coords and tsp_instance for rescale_instance. Numeric matrix of scaled city coordinates.

rotate_coordinates *Rotate a matrix of 2D coordinates*

Description

Rotate a matrix of 2D coordinates

Usage

```
rotate_coordinates(coords, angle, center)
```

Arguments

coords	[matrix] Numeric matrix of 2D coordinates to rotate
angle	[numeric(1)] Angle by which to rotate the coordinates. In radians.
center	[matrix] Center around which to rotate the coordinates.

Value

A matrix of rotated coordinates.

rotate_instance	<i>Rotate the cities of a TSP instance around a point.</i>
-----------------	--

Description

Rotate the cities of a TSP instance around a point.

Usage

```
rotate_instance(instance, angle, center)
```

Arguments

instance	[tsp_instance] TSP instance.
angle	[numeric] Angle by which to rotate the coordinates. In radians.
center	[numeric] Point around which to rotate the cities. If missing, defaults to the center of mass of the cities.

Value

[tsp_instance](#) New TSP instance.

run_solver	<i>Runs a solver on a TSP instance.</i>
------------	---

Description

Currently the following solvers are supported: nearest_insertion: See [solve_TSP](#). farthest_insertion : See [solve_TSP](#). cheapest_insertion : See [solve_TSP](#). arbitrary_insertion: See [solve_TSP](#). nn: See [solve_TSP](#). repetitive_nn: See [solve_TSP](#). concorde: See [solve_TSP](#).

Usage

```
run_solver(x, method, ...)
```

Arguments

x	[tsp_instance] TSP instance.
method	[character(1)] Solver to use on TSP instance. To use concorde and/or linkern it is necessary to specify the path to the concorde/linkern executable with concorde_path .
...	[any] Control parameters for solver.

Value

TOUR TOUR object from package TSP, containing order of cities, tour length and method name that generated this solution.

Examples

```
x = random_instance(10)
tours = sapply(c("nn", "cheapest_insertion", "arbitrary_insertion"), function(solver) {
  list(solver = run_solver(x, method = solver))
})
## Not run:
concorde_path(path = "/absolute/path/to/concorde/executable")
concorde_tour = run_solver(x, method = "concorde")
concorde_tour = run_solver(x, method = "linkern")

## End(Not run)
```

tsp_generation_ea	<i>TSP generating EA.</i>
-------------------	---------------------------

Description

TSP generating EA.

Usage

```
tsp_generation_ea(fitness_function, pop_size = 30L, inst_size = 50L,
  generations = 100L, time_limit = 30L, uniform_mutation_rate,
  normal_mutation_rate, normal_mutation_sd, cells_round = 100L, rnd = TRUE,
  ...)
```

Arguments

fitness_function	[function(x, ...)] Fitness function used to judge the fitness of a TSP instance. <i>x</i> is a numeric matrix with 2 columns, containing the coordinates of a TSP instance.
pop_size	[integer(1)] Number of TSP instances maintained in each population. Default is 30.
inst_size	[integer(1)] Number of cities of each TSP instance. Default is 50.
generations	[integer(1)] Number of generations. Default is 100L.
time_limit	[integer(1)] Time limit in seconds. Default is 30.

uniform_mutation_rate	[numeric(1)] Mutation probability in uniform mutation (in [0,1]).
normal_mutation_rate	[numeric(1)] Mutation probability in normal mutation (in [0,1])
normal_mutation_sd	[numeric(1)] Standard deviation of normal noise in normal mutation
cells_round	[numeric(1)] Grid resolution for rounding Default is 100.
rnd	[logical(1)] Round the coordinates before normal mutation. Default is TRUE.
...	[any] Not used.

Value

list List containing best individual form the last population, its fitness value, the generational fitness and the last population. Default is 50.

tsp_instance	<i>Generates a TSP instance S3 object either from city coordinates.</i>
--------------	---

Description

Generates a TSP instance S3 object either from city coordinates.

Usage

```
tsp_instance(coords, dists)
```

Arguments

coords	[matrix] Numeric matrix of city coordinates, rows denote cities.
dists	[dist] Optional distance matrix containing the inter-city distances. If not provided, the (euclidean) distances are computed from the coordinates.

Value

[tsp_instance](#) .

Index

as_TSP, [2](#)
autoplot.tsp_instance, [3](#)

center_of_mass, [4](#)
concorde_path, [19](#)

dbscan, [7](#)

fast_two_opt, [4](#)
feature_angle, [5, 5](#)
feature_bounding_box, [5, 6](#)
feature_centroid, [5, 6](#)
feature_chull, [5, 7](#)
feature_cluster, [5, 7](#)
feature_distance, [5, 8](#)
feature_modes, [5, 8](#)
feature_mst, [5, 9](#)
feature_nnds, [5, 9](#)
features, [5](#)

get_solvers, [10](#)
ggplot, [3](#)
greedy_point_matching, [10, 11](#)

instance_dim, [11](#)

morph_instances, [11](#)

normalization_angle, [12, 13](#)
normalize_rotation, [12](#)
number_of_cities, [13](#)
numvec_feature_statistics, [13](#)

print.tsp_instance, [14](#)

random_instance, [14](#)
read_tsplib_instance, [15](#)
read_tsplib_instances, [16](#)
read_tsplib_tour, [16](#)
remove_zero_distances, [17](#)
rescale_coords (rescale_instance), [17](#)

rescale_instance, [17](#)
rotate_coordinates, [18](#)
rotate_instance, [19](#)
run_solver, [19](#)

solve_TSP, [19](#)

TOUR, [3, 4, 17, 20](#)
TSP, [3](#)
tsp_generation_ea, [20](#)
tsp_instance, [3–9, 11–15, 18, 19, 21, 21](#)