

Package ‘RANN’

January 27, 2015

Title Fast Nearest Neighbour Search (wraps Arya and Mount's ANN library)

Version 2.4.1

Date 2014-07-21

Author Sunil Arya and David Mount (for ANN), Samuel E. Kemp, Gregory Jefferis

Copyright ANN library is copyright University of Maryland and Sunil Arya and David Mount. See file COPYRIGHT for details.

Description Finds the k nearest neighbours for every point in a given dataset in $O(N \log N)$ time using Arya and Mount's ANN library (v1.1.3). There is support for approximate as well as exact searches, fixed radius searches and bd as well as kd trees.

Maintainer Gregory Jefferis <jefferis@gmail.com>

License GPL (>= 3)

URL <https://github.com/jefferis/RANN>

Suggests testthat

NeedsCompilation yes

Repository CRAN

Date/Publication 2014-07-21 20:07:49

R topics documented:

RANN-package	2
nn2	2
RANN-defunct	3
Index	5

RANN-package	<i>Wrapper for Arya and Mount's Approximate Nearest Neighbours (ANN) C++ library</i>
--------------	--

Description

Wrapper for Arya and Mount's Approximate Nearest Neighbours (ANN) C++ library

See Also

[nn2](#)

nn2	<i>Nearest Neighbour Search</i>
-----	---------------------------------

Description

Uses a kd-tree to find the p number of near neighbours for each point in an input/output dataset. The advantage of the kd-tree is that it runs in $O(M \log M)$ time.

Usage

```
nn2(data, query = data, k = min(10, nrow(data)), treetype = c("kd", "bd"),
     searchtype = c("standard", "priority", "radius"), radius = 0, eps = 0)
```

Arguments

data	An $M \times d$ data.frame or matrix, where each of the M rows is a point or a (column) vector (where $d=1$).
query	A set of $N \times d$ points that will be queried against data. d , the number of columns, must be the same as data. If missing, defaults to data.
k	The maximum number of nearest neighbours to compute. The default value is set to the smaller of the number of columns in data
treetype	Character vector specifying the standard 'kd' tree or a 'bd' (box-decomposition, AMNSW98) tree which may perform better for larger point sets
searchtype	See details
radius	Radius of search for searchtype='radius'
eps	Error bound: default of 0.0 implies exact nearest neighbour search

Details

The RANN package utilizes the Approximate Near Neighbor (ANN) C++ library, which can give the exact near neighbours or (as the name suggests) approximate near neighbours to within a specified error bound. For more information on the ANN library please visit <http://www.cs.umd.edu/~mount/ANN/>.

Search types: `priority` visits cells in increasing order of distance from the query point, and hence, should converge more rapidly on the true nearest neighbour, but `standard` is usually faster for exact searches. `radius` only searches for neighbours within a specified radius of the point. If there are no neighbours then `nn.idx` will contain 0 and `nn.dists` will contain 1.340781e+154 for that point.

Value

A list of length 2 with elements:

<code>nn.idx</code>	A $N \times k$ integer matrix returning the near neighbour indices.
<code>nn.dists</code>	A $N \times k$ matrix returning the near neighbour Euclidean distances.

Author(s)

Gregory Jefferis based on earlier code by Samuel E. Kemp (knnFinder package)

References

Bentley J. L. (1975), Multidimensional binary search trees used for associative search. *Communication ACM*, 18:309-517.

Arya S. and Mount D. M. (1993), Approximate nearest neighbor searching, *Proc. 4th Ann. ACM-SIAM Symposium on Discrete Algorithms (SODA'93)*, 271-280.

Arya S., Mount D. M., Netanyahu N. S., Silverman R. and Wu A. Y (1998), An optimal algorithm for approximate nearest neighbor searching, *Journal of the ACM*, 45, 891-923.

Examples

```
x1 <- runif(100, 0, 2*pi)
x2 <- runif(100, 0,3)
DATA <- data.frame(x1, x2)
nearest <- nn2(DATA,DATA)
```

RANN-defunct

Defunct functions in RANN package

Description

Defunct functions in RANN package

Usage

```
nn(...)
```

Arguments

... Ignored

Details

C code underlying `nn()` contained memory leaks. [nn2](#) is a more flexible and efficient alternative.

Index

*Topic **nonparametric**

nn2, [2](#)

*Topic **package**

RANN-package, [2](#)

nn (RANN-defunct), [3](#)

nn2, [2](#), [2](#), [4](#)

RANN (RANN-package), [2](#)

RANN-defunct, [3](#)

RANN-package, [2](#)