

Package ‘dendextend’

January 31, 2015

Type Package

Title Extending R's Dendrogram Functionality

Version 0.18.3

Date 2015-01-31

Description Offers a set of functions for extending dendrogram objects in R, letting you visualize and compare trees of hierarchical clusterings. You can (1) Adjust a trees graphical parameters - the color, size, type, etc of its branches, nodes and labels. (2) Visually and statistically compare different dendrograms to one another.

Depends R (>= 3.0.0)

Imports utils, stats, magrittr (>= 1.0.1), whisker

Suggests dendextendRcpp (>= 0.5.0), knitr, testthat, colorspace, ggplot2, plyr, ape, profdpm, microbenchmark, gplots, DendSer, dynamicTreeCut, pvclust

Enhances gg dendro, labeltodendro, dendroextras, data.table

VignetteBuilder knitr

License GPL-2 | GPL-3

URL <https://github.com/talgalili/dendextend/>,
<http://cran.r-project.org/web/packages/dendextend/>,
<http://www.r-statistics.com/tag/dendextend/>

BugReports <https://github.com/talgalili/dendextend/issues>

Author Tal Galili [aut, cre, cph] (<http://www.r-statistics.com>),
Gavin Simpson [ctb],
Gregory Jefferis [ctb] (imported code from his dendroextras package),
Marco Gallotta [ctb] (a.k.a: marcog),
Johan Renaudie [ctb] (<https://github.com/plannapus>),
The R Core Team [ctb] (Thanks for the Infrastructure, and code in the examples),
Kurt Hornik [ctb],
Uwe Ligges [ctb],
Andrej-Nikolai Spiess [ctb],

Steve Horvath [ctb],
 Peter Langfelder [ctb],
 skullkey [ctb],
 Mark Van Der Loo [ctb] (<https://github.com/markvanderloo/d3dendrogram>),
 Andrie de Vries [ctb] (ggdendro author),
 Yoav Benjamini [ths]

Maintainer Tal Galili <tal.galili@gmail.com>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-01-31 21:57:37

R topics documented:

dendextend-package	4
all.equal.dendrogram	5
all_couple_rotations_at_k	6
all_unique	7
as.dendlist	8
as.phylo.dendrogram	9
assign_dendextend_options	10
assign_values_to_branches_edgePar	10
assign_values_to_leaves_edgePar	11
assign_values_to_leaves_nodePar	12
assign_values_to_nodes_nodePar	13
as_hclust_fixed	15
bakers_gamma_for_2_k_matrix	15
Bk	16
Bk_permutations	18
Bk_plot	20
branches_attr_by_clusters	23
branches_attr_by_labels	25
click_rotate	26
collapse_branch	28
colored_bars	29
color_branches	31
color_labels	34
cor.dendlist	36
cor_bakers_gamma	37
cor_cophenetic	39
count_terminal_nodes	41
cutree	42
cutree_1h.dendrogram	46
cutree_1k.dendrogram	47
cut_lower_fun	49
d3dendrogram	50
d3dendro_options	51

dendextend_options	52
dendlist	53
DendSer.dendrogram	54
dend_diff	55
dist.dendlist	56
distinct_edges	57
dist_long	58
duplicate_leaf	58
entanglement	59
fac2num	62
fix_members_attr.dendrogram	62
flatten.dendrogram	63
flip_leaves	64
FM_index	65
FM_index_permutation	67
FM_index_profdpm	69
FM_index_R	71
get_branches_heights	72
get_childrens_heights	73
get_leaves_attr	74
get_leaves_nodePar	75
get_nodes_attr	76
get_nodes_xy	78
get_root_branches_attr	79
ggdend	80
hang.dendrogram	83
heights_per_k.dendrogram	84
highlight_distinct_edges	85
identify.dendrogram	87
intersect_trees	88
is.dendlist	89
is.dendrogram	90
is.hclust	90
is.natural.number	91
is.phylo	92
is_null_list	92
labels<-	93
labels_colors	95
ladderize	97
leaf_Colors	98
lowest_common_branch	99
match_order_by_labels	99
match_order_dendrogram_by_old_order	100
na_locf	102
nleaves	103
nnodes	104
noded_with_condition	105
order.dendrogram<-	106

order.hclust	108
partition_leaves	108
plot_horiz.dendrogram	109
prune	111
prune_leaf	112
pvclust_show_signif	113
pvclust_show_signif_gradient	114
raise.dendrogram	116
rank_branches	116
rank_order.dendrogram	117
rect.dendrogram	118
remove_branches_edgePar	120
remove_leaves_nodePar	121
remove_nodes_nodePar	122
rllply	122
rotate	123
rotate_DendSer	126
sample.dendrogram	127
set	128
shuffle	132
sort_2_clusters_vectors	134
sort_dist_mat	135
sort_levels_values	136
tanglegram	137
theme_dendro	141
unbranch	142
unclass_dend	143
untangle	144
untangle_DendSer	145
untangle_random_search	146
untangle_step_rotate_1side	148
untangle_step_rotate_2side	149
which_leaf	151
which_node	152
%>%	153

Index 154

dendextend-package *Functions for extending dendrogram objects*

Description

Functions for extending dendrogram objects

See Also

[dendrogram](#), [hclust](#) in [stats](#) package.

all.equal.dendrogram *Global Comparison of two (or more) dendrograms*

Description

This function makes a global comparison of two or more dendrograms trees.

Usage

```
## S3 method for class 'equal.dendrogram'
all(target, current, use.edge.length = TRUE,
     use.tip.label.order = FALSE, use.tip.label = TRUE, use.topology = TRUE,
     tolerance = .Machine$double.eps^0.5, scale = NULL, ...)
```

Arguments

target	an object of type dendrogram or dendlist
current	an object of type dendrogram
use.edge.length	logical (TRUE). If to check branches' heights.
use.tip.label.order	logical (FALSE). If to check labels are in the same and in identical order
use.tip.label	logical (TRUE). If to check that labels are the same (regardless of order)
use.topology	logical (TRUE). If to check teh existence of distinct edges
tolerance	the numeric tolerance used to compare the branch lengths.
scale	a positive number (NULL as default), comparison of branch height is made after scaling (i.e., dividing) them by this number.
...	Ignored.

Value

Either TRUE (NULL for attr.all.equal) or a vector of mode "character" describing the differences between target and current.

See Also

[all.equal](#), [all.equal.phylo](#), [identical](#)

Examples

```
## Not run:

set.seed(23235)
ss <- sample(1:150, 10 )
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("single") %>% as.dendrogram
```

```

dend3 <- iris[ss,-5] %>% dist %>% hclust("ave") %>% as.dendrogram
dend4 <- iris[ss,-5] %>% dist %>% hclust("centroid") %>% as.dendrogram
#   cutree(dend1)

all.equal(dend1, dend1)
all.equal(dend1, dend2)
all.equal(dend1, dend2, use.edge.length = FALSE)
all.equal(dend1, dend2, use.edge.length = FALSE, use.topology = FALSE)

all.equal(dend2, dend4, use.edge.length = TRUE)
all.equal(dend2, dend4, use.edge.length = FALSE)

all.equal(dendlist(dend1, dend2, dend3, dend4))
all.equal(dendlist(dend1, dend2, dend3, dend4), use.edge.length = FALSE)
all.equal(dendlist(dend1, dend1, dend1))

## End(Not run)

```

```
all_couple_rotations_at_k
```

Rotate tree branches for k

Description

Given a tree and a k number of clusters, the tree is rotated so that the extra clusters added from k-1 to k clusters are flipped.

This is useful for finding good trees for a [tanglegram](#).

Usage

```
all_couple_rotations_at_k(dend, k, dend_heights_per_k, ...)
```

Arguments

dend	a dendrogram object
k	integer scalar with the number of clusters the tree should be cut into.
dend_heights_per_k	a named vector that resulted from running heights_per_k.dendrogram . When running the function many times, supplying this object will help improve the running time if using the cutree.dendrogram method..
...	not used

Value

A list with dendrogram objects with all the possible rotations for k clusters (beyond the k-1 clusters!).

See Also

[tanglegram](#), [match_order_by_labels](#), [entanglement](#), [flip_leaves](#).

Examples

```
## Not run:
dend1 <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram
dend2 <- all_couple_rotations_at_k(dend1, k=2)[[2]]
tanglegram(dend1,dend2)
entanglement(dend1,dend2, L = 2) # 0.5

dend2 <- all_couple_rotations_at_k(dend1, k=3)[[2]]
tanglegram(dend1,dend2)
entanglement(dend1,dend2, L = 2) # 0.4

dend2 <- all_couple_rotations_at_k(dend1, k=4)[[2]]
tanglegram(dend1,dend2)
entanglement(dend1,dend2, L = 2) # 0.05

## End(Not run)
```

all_unique

Check if all the elements in a vector are unique

Description

Check if all the elements in a vector are unique

Usage

```
all_unique(x, ...)
```

Arguments

x	a vector
...	ignored.

Value

logical (are all the elements in the vector unique)

Source

<http://r.789695.n4.nabble.com/Is-there-a-function-to-test-if-all-the-elements-in-a-vector-are-unique.html>

See Also

[unique](#)

Examples

```

all_unique(c(1:5, 1,1))
all_unique(c(1,1,2))
all_unique(c(1,1,2, 3,3,3,3))
all_unique(c(1,3,2))
all_unique(c(1:10))

```

as.dendlist

Try to coerce something into a dendlist

Description

It removes stuff that are not dendrogram/dendlist and turns what is left into a dendlist

Usage

```
as.dendlist(x, ...)
```

Arguments

x	a list with several dendrogram/hclust/phylo or dendlist objects and other junk that should be omitted.
...	NOT USED

Value

A list of class dendlist where each item is a dendrogram

Examples

```

## Not run:

dend <- iris[,-5] %>% dist %>% hclust %>% as.dendrogram
dend2 <- iris[,-5] %>% dist %>% hclust(method = "single") %>% as.dendrogram

x = list(dend, 1, dend2)
as.dendlist(x)

## End(Not run)

```

as.phylo.dendrogram *Convert a dendrogram into phylo*

Description

Based on [as.hclust.dendrogram](#) with [as.phylo.hclust](#)

In the future I hope a more direct link will be made.

Usage

```
as.phylo.dendrogram(x, ...)
```

Arguments

x	a dendrogram
...	ignored.

Value

A phylo class object

See Also

[as.dendrogram](#), [as.hclust](#), [as.phylo](#)

Examples

```
## Not run:

library(dendextend)
library(ape)
dend <- iris[1:30,-5] %>% dist %>% hclust %>% as.dendrogram
dend2 <- as.phylo(dend)
plot(dend2, type = "fan")

# Also possible to with ggplot2 :)

library(dendextend)
library(ggplot2)
library(ggdendro)
dend <- iris[1:30,-5] %>% dist %>% hclust %>% as.dendrogram
# Rectangular lines
ddata <- dend %>% dendro_data(type = "rectangle")
p <- ggplot(segment(ddata)) +
  geom_segment(aes(x = x, y = y, xend = xend, yend = yend)) +
  coord_flip() +
  scale_y_reverse(expand = c(0.2, 0)) + coord_polar(theta="x")
p
```

```
## End(Not run)
```

```
assign_dendextend_options
```

Populates dendextend functions into dendextend_options

Description

Populates dendextend functions into dendextend_options

Usage

```
assign_dendextend_options()
```

```
assign_values_to_branches_edgePar
```

Assign values to edgePar of dendrogram's branches

Description

Go through the dendrogram branches and updates the values inside its edgePar

If the value has Inf then the value in edgePar will not be changed.

Usage

```
assign_values_to_branches_edgePar(object, value, edgePar, skip_leaves = FALSE,
  warn = dendextend_options("warn"), ...)
```

Arguments

object	a dendrogram object
value	a new value scalar for the edgePar attribute.
edgePar	a character indicating the value inside edgePar to adjust. Can be either "col", "lty", or "lwd".
skip_leaves	logical (FALSE) - should the leaves be skipped/ignored?
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	not used

Value

A dendrogram, after adjusting the edgePar attribute in all of its branches,

See Also

[get_root_branches_attr](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram
plot(dend)
dend <- assign_values_to_branches_edgePar(object=dend, value = 2, edgePar = "lwd")
plot(dend)
dend <- assign_values_to_branches_edgePar(object=dend, value = 2, edgePar = "col")
plot(dend)
dend <- assign_values_to_branches_edgePar(object=dend, value = 2, edgePar = "lty")
plot(dend)

## End(Not run)
```

assign_values_to_leaves_edgePar

Assign values to edgePar of dendrogram's leaves

Description

Go through the dendrogram leaves and updates the values inside its edgePar

If the value has Inf then the value in edgePar will not be changed.

Usage

```
assign_values_to_leaves_edgePar(object, value, edgePar,
  warn = dendextend_options("warn"), ...)
```

Arguments

object	a dendrogram object
value	a new value vector for the edgePar attribute. It should be the same length as the number of leaves in the tree. If not, it will recycle the value and issue a warning.
edgePar	the value inside edgePar to adjust.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	not used

Value

A dendrogram, after adjusting the edgePar attribute in all of its leaves,

See Also

[get_leaves_attr](#), [linkassign_values_to_leaves_nodePar](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust("ave") %>% as.dendrogram

plot(dend)
dend <- assign_values_to_leaves_edgePar(object=dend, value = c(3,2), edgePar = "col")
plot(dend)
dend <- assign_values_to_leaves_edgePar(object=dend, value = c(3,2), edgePar = "lwd")
plot(dend)
dend <- assign_values_to_leaves_edgePar(object=dend, value = c(3,2), edgePar = "lty")
plot(dend)

get_leaves_attr(dend, "edgePar", simplify=FALSE)

## End(Not run)
```

`assign_values_to_leaves_nodePar`

Assign values to nodePar of dendrogram's leaves

Description

Go through the dendrogram leaves and updates the values inside its nodePar

If the value has Inf then the value in edgePar will not be changed.

Usage

```
assign_values_to_leaves_nodePar(object, value, nodePar,
  warn = dendextend_options("warn"), ...)
```

Arguments

object	a dendrogram object
value	a new value vector for the nodePar attribute. It should be the same length as the number of leaves in the tree. If not, it will recycle the value and issue a warning.
nodePar	the value inside nodePar to adjust.

warn	logical (default from dendextend_options("warn") is FALSE). Set if warnings are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	not used

Value

A dendrogram, after adjusting the nodePar attribute in all of its leaves,

See Also

[get_leaves_attr](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust("ave") %>% as.dendrogram

# reproduces "labels_colors<-"
# although it does force us to run through the tree twice,
# hence "labels_colors<-" is better...
plot(dend)
dend <- assign_values_to_leaves_nodePar(object=dend, value = c(3,2), nodePar = "lab.col")
plot(dend)

dend <- assign_values_to_leaves_nodePar(dend, 1, "pch")
plot(dend)
# fix the annoying pch=1:
dend <- assign_values_to_leaves_nodePar(dend, NA, "pch")
plot(dend)
# adjust the cex:
dend <- assign_values_to_leaves_nodePar(dend, 19, "pch")
dend <- assign_values_to_leaves_nodePar(dend, 2, "lab.cex")
plot(dend)

get_leaves_attr(dend, "nodePar", simplify=FALSE)

## End(Not run)
```

assign_values_to_nodes_nodePar

Assign values to nodePar of dendrogram's nodes

Description

Go through the dendrogram nodes and updates the values inside its nodePar
If the value has Inf then the value in edgePar will not be changed.

Usage

```
assign_values_to_nodes_nodePar(object, value, nodePar = c("pch", "cex", "col",
  "xpd", "bg"), warn = dendextend_options("warn"), ...)
```

Arguments

object	a dendrogram object
value	a new value vector for the nodePar attribute. It should be the same length as the number of nodes in the tree. If not, it will recycle the value and issue a warning.
nodePar	the value inside nodePar to adjust. This may contain components named pch, cex, col, xpd, and/or bg.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	not used

Value

A dendrogram, after adjusting the nodePar attribute in all of its nodes,

See Also

[get_leaves_attr](#), [assign_values_to_leaves_nodePar](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust("ave") %>% as.dendrogram

# reproduces "labels_colors<-"
# although it does force us to run through the tree twice,
# hence "labels_colors<-" is better...
plot(dend)
dend2 <- dend %>%
  assign_values_to_nodes_nodePar(value = 19, nodePar = "pch") %>%
  assign_values_to_nodes_nodePar(value = c(1,2), nodePar = "cex") %>%
  assign_values_to_nodes_nodePar(value = c(2,1), nodePar = "col")
plot(dend2)

## End(Not run)
```

as_hclust_fixed	<i>Convert dendrogram Objects to Class hclust</i>
-----------------	---

Description

Convert dendrogram Objects to Class hclust while preserving the call/method/dist.method values of the original hclust object (hc)

Usage

```
as_hclust_fixed(x, hc, ...)
```

Arguments

x	any object which has an as.hclust method. (mostly used for dendrogram)
hc	an old hclust object from which to re-use the call/method/dist.method values
...	passed to as.hclust

Value

An hclust object (from a dendrogram) with the original hclust call/method/dist.method values

See Also

[as.hclust](#)

Examples

```
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

as.hclust(dend)
as_hclust_fixed(dend, hc)
```

bakers_gamma_for_2_k_matrix	<i>Bakers Gamma for two k matrices</i>
-----------------------------	--

Description

Bakers Gamma for two k matrices

Usage

```
bakers_gamma_for_2_k_matrix(k_matrix_tree1, k_matrix_tree2, to_plot = FALSE)
```

Arguments

k_matrix_tree1	a matrix of k cluster groupings from a dendrogram
k_matrix_tree2	a (second) matrix of k cluster groupings from a dendrogram
to_plot	logical (FALSE). Should a scatterplot be plotted, showing the correlation between the lowest shared branch between two items in the two compared trees.
...	not used

Value

Baker's Gamma coefficient.

See Also

[cor_bakers_gamma](#)

Bk

Bk - Calculating Fowlkes-Mallows Index for two dendrogram

Description

Bk is the calculation of Fowlkes-Mallows index for a series of k cuts for two dendrograms.

Usage

```
Bk(tree1, tree2, k, include_EV = TRUE, warn = dendextend_options("warn"),
    ...)
```

Arguments

tree1	a dendrogram/hclust/phylo object.
tree2	a dendrogram/hclust/phylo object.
k	an integer scalar or vector with the desired number of cluster groups. If missing - the Bk will be calculated for a default k range of 2:(nleaves-1). No point in checking k=1/k=n, since both will give Bk=1.
include_EV	logical (TRUE). Should we calculate expectancy and variance of the FM Index under null hypothesis of no relation between the clusterings? If TRUE (Default) - then the FM_index_R function, else (FALSE) we use the (faster) FM_index_profdpm function.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	Ignored (passed to FM_index_R / FM_index_profdpm).

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

Value

A list (of k's length) of Fowlkes-Mallows index between two dendrogram for a scalar/vector of k values. The names of the lists' items is the k for which it was calculated.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[FM_index](#), [cor_bakers_gamma](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
tree1 <- as.dendrogram(hc1)
tree2 <- as.dendrogram(hc2)
#   cutree(tree1)

Bk(hc1, hc2, k = 3)
Bk(hc1, hc2, k = 2:10)
Bk(hc1, hc2)

Bk(tree1, tree2, k = 3)
Bk(tree1, tree2, k = 2:5)

system.time(Bk(hc1, hc2, k = 2:5)) # 0.01
system.time(Bk(hc1, hc2)) # 1.28
system.time(Bk(tree1, tree2, k = 2:5)) # 0.24 # after fixes.
system.time(Bk(tree1, tree2, k = 2:10)) # 0.31 # after fixes.
system.time(Bk(tree1, tree2)) # 7.85
Bk(tree1, tree2, k= 99:101)

y <- Bk(hc1, hc2, k = 2:10)
```

```

plot(unlist(y)~c(2:10), type = "b", ylim = c(0,1))

# can take a few seconds
y <- Bk(hc1, hc2)
plot(unlist(y)~as.numeric(names(y)),
     main = "Bk plot", pch = 20,
     xlab = "k", ylab = "FM Index",
     type = "b", ylim = c(0,1))
# we are still missing some hypothesis testing here.
# for this we'll have the Bk_plot function.

## End(Not run)

```

Bk_permutations	<i>Bk permutation - Calculating Fowlkes-Mallows Index for two dendrogram</i>
-----------------	--

Description

Bk is the calculation of Fowlkes-Mallows index for a series of k cuts for two dendrograms.

Bk permutation calculates the Bk under the null hypothesis of no similarity between the two trees by randomly shuffling the labels of the two trees and calculating their Bk.

Usage

```

Bk_permutations(tree1, tree2, k, R = 1000,
               warn = dendextend_options("warn"), ...)

```

Arguments

tree1	a dendrogram/hclust/phylo object.
tree2	a dendrogram/hclust/phylo object.
k	an integer scalar or vector with the desired number of cluster groups. If missing - the Bk will be calculated for a default k range of 2:(nleaves-1). No point in checking k=1/k=n, since both will give Bk=1.
R	integer (Default is 1000). The number of Bk permutation to perform for each k.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. If set to TRUE, extra checks are made to verify that the two clusters have the same size and the same labels.
...	Ignored (passed to FM_index_R/FM_index_profdpm).

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

Value

A list (of the length of k's), where each element of the list has R (number of permutations) calculations of Fowlkes-Mallows index between two dendrogram after having their labels shuffled.

The names of the lists' items is the k for which it was calculated.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[FM_index](#), [Bk](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# tree1 <- as.treerogram(hc1)
# tree2 <- as.treerogram(hc2)
#   cutree(tree1)

some_Bk <- Bk(hc1, hc2, k = 20)
some_Bk_permu <- Bk_permutations(hc1, hc2, k = 20)

# we can see that the Bk is much higher than the permutation Bks:
plot(x=rep(1,1000), y= some_Bk_permu[[1]],
     main = "Bk distribution under H0",
     ylim = c(0,1))
points(1, y= some_Bk, pch = 19, col = 2 )

## End(Not run)
```

Bk_plot	<i>Bk plot - plotting the Fowlkes-Mallows Index of two dendrogram for various k's</i>
---------	---

Description

Bk is the calculation of Fowlkes-Mallows index for a series of k cuts for two dendrograms. A Bk plot is simply a scatter plot of Bk versus k. This plot helps in identifying the similarity between two dendrograms in different levels of k (number of clusters).

Usage

```
Bk_plot(tree1, tree2, k, add_E = TRUE, rejection_line_asymptotic = TRUE,
        rejection_line_permutation = FALSE, R = 1000, k_permutation,
        conf.level = 0.95, p.adjust.methods = c("none", "bonferroni"),
        col_line_Bk = 1, col_line_asymptotic = 2, col_line_permutation = 4,
        warn = dendextend_options("warn"), main = "Bk plot",
        xlab = "k (number of clusters)", ylab = "Bk (Fowlkes-Mallows Index)",
        xlim, ylim = c(0, 1), try_cutree_hclust = TRUE, ...)
```

Arguments

tree1	a dendrogram/hclust/phylo object.
tree2	a dendrogram/hclust/phylo object.
k	an integer scalar or vector with the desired number of cluster groups. If missing - the Bk will be calculated for a default k range of 2:(nleaves-1). No point in checking k=1/k=n, since both will give Bk=1.
add_E	logical (TRUE). Should we add a line of the Expected Bk value for each k, under the null hypothesis of no relation between the clusterings?
rejection_line_asymptotic	logical (TRUE). Should we add a line of the one sided rejection region based on the asymptotic distribution of Bk values, for each k, under the null hypothesis of no relation between the clusterings?
rejection_line_permutation	logical (FALSE). Should we add a line of the one sided rejection region based on the asymptotic distribution of Bk values, for each k, under the null hypothesis of no relation between the clusterings?
R	integer (Default is 1000). The number of Bk permutation to perform for each k. Applicable only if rejection_line_permutation is TRUE.
k_permutation	the k's to be used for permutation (sometimes we might be only interested in some k's and it is not important to run the simulation for all possible ks). If missing - k itself will be used.
conf.level	the level of one sided confidence interval used for creation of the rejection lines.

<code>p.adjust.methods</code>	a character scalar of either "none" (default), or "bonferroni". This controls the multiple correction method to use for the critical rejection values. Currently only the Bonferroni method is implemented (based on the number of different k values).
<code>col_line_Bk</code>	the color of the Bk line.
<code>col_line_asymptotic</code>	the color of the rejection asymptotic Bk line.
<code>col_line_permutation</code>	the color of the rejection asymptotic Bk line.
<code>warn</code>	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. If set to TRUE, extra checks are made to varify that the two clusters have the same size and the same labels.
<code>main</code>	passed to plot .
<code>xlab</code>	passed to plot .
<code>ylab</code>	passed to plot .
<code>xlim</code>	passed to plot . If missign, xlim is from 2 to <code>nleaves-1</code>
<code>ylim</code>	passed to plot .
<code>try_cutree_hclust</code>	logical (TRUE). Since <code>cutree</code> for <code>hclust</code> is MUCH faster than for <code>dendrogram</code> - <code>Bk_plot</code> will first try to change the dendrogram into an <code>hclust</code> object. If it will fail (for example, with unbranched trees), it will continue using the <code>cutree.dendrogram</code> functions. If <code>try_cutree_hclust=FALSE</code> , it will force to use <code>cutree.dendrogram</code> and not <code>cutree.hclust</code> .
<code>...</code>	Ignored.

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

The default Bk plot comes with a line with dots (type "b") of the Bk values. Also with a fragmented (lty=2) line (of the same color) of the expected Bk line under H0, And a solid red line of the upper critical Bk values for rejection

Value

After plotting the Bk plot. Returns (invisible) the output of the elements used for constructing the plot: The Bk values, Bk permutations (if used), Bk theoretical values, etc.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[FM_index](#), [Bk](#), [Bk_permutations](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# tree1 <- as.treerogram(hc1)
# tree2 <- as.treerogram(hc2)
#   cutree(tree1)

Bk_plot(hc1, hc2, k = 2:20, xlim = c(2,149))
Bk_plot(hc1, hc2)

Bk_plot(hc1, hc2, k = 3)
Bk_plot(hc1, hc2, k = 3:10)
Bk_plot(hc1, hc2)
Bk_plot(hc1, hc2, p.adjust.methods="bonferroni") # higher rejection lines

# this one can take a bit of time:
Bk_plot(hc1, hc2, rejection_line_permutation=TRUE,
k_permutation = c(2,4,6,8,10,20,30,40,50), R= 100)
# we can see that the permutation line is VERY close to the asymptotic line.
# This is great since it means one can often use the asymptotic results
# Without having to do many simulations.

# works just as well for dendrograms:
dend1 <- as.dendrogram(hc1)
dend2 <- as.dendrogram(hc2)
Bk_plot(dend1, dend2, k = 2:3, try_cutree_hclust = FALSE) # slower than hclust, but works...
Bk_plot(hc1, dend2, k = 2:3, try_cutree_hclust = FALSE) # slower than hclust, but works...
Bk_plot(dend1, dend1, k = 2:3, try_cutree_hclust = TRUE) # slower than hclust, but works...
Bk_plot(hc1, hc1, k = 2:3) # slower than hclust, but works...
# for some reason it can't turn dend2 back to hclust :(
a= Bk_plot(hc1, hc2, k = 2:3, try_cutree_hclust = TRUE) # slower than hclust, but works...

hc1_mixed <- as.hclust(sample(as.dendrogram(hc1)))
Bk_plot(tree1=hc1, tree2=hc1_mixed,
        add_E=FALSE,
        rejection_line_permutation=TRUE, k_permutation = c(2,4,6,8,10,20,30,40,50), R= 100)
```

```
## End(Not run)
```

```
branches_attr_by_clusters
```

```
Change col/lwd/lty of branches based on clusters
```

Description

The user supplies a dend, a vector of clusters, and what to modify (and how).

And the function returns a dendrogram with branches col/lwd/lty accordingly. (the function assumes unique labels)

Usage

```
branches_attr_by_clusters(dend, clusters, values, attr = c("col", "lwd",
  "lty"), ...)
```

Arguments

dend	a dendrogram dend
clusters	an integer vector of clusters. This HAS to be of the size of the number of leaves. Items that belong to no cluster should get the value 0. The vector should be of the same order as that of the labels in the dendrogram. If you create the clusters from something like cutree you would first need to use order.dendrogram on it, before using it in the function.
values	the attributes to use for non 0 values. This should be of the same length as the number of non-0 clusters. If it is not, it is recycled.
attr	a character with one of the following values: col/lwd/lty
...	ignored.

Details

This is probably NOT a very fast implementation of the function, but it works.

This function was designed to enable the manipulation (mainly coloring) of branches, based on the results from the [cutreeDynamic](#) function.

Value

A dendrogram with modified branches (col/lwd/lty).

See Also

[branches_attr_by_labels](#), [get_leaves_attr](#), [nnodes](#), [nleaves](#) [cutreeDynamic](#), [plotDendroAndColors](#)

Examples

```

## Not run:

### Getting the hc object
iris_dist <- iris[,-5] %>% dist
hc <- iris_dist %>% hclust
# This is how it looks without any colors:
dend <- as.dendrogram(hc)
plot(dend)

# Both functions give the same outcome
# options 1:
dend %>% set("branches_k_color", k = 4) %>% plot
# options 2:
clusters <- cutree(dend, 4)[order.dendrogram(dend)]
dend %>% branches_attr_by_clusters(clusters) %>% plot

# and the second option is much slower:
system.time(set(dend, "branches_k_color", k = 4)) # 0.26 sec
system.time(branches_attr_by_clusters(dend, clusters)) # 1.61 sec
# BUT, it also allows us to do more flaxible things!

#-----
#   Plotting dynamicTreeCut
#-----

# let's get the clusters
library(dynamicTreeCut)
clusters <- cutreeDynamic(hc, distM = as.matrix(iris_dist))
# we need to sort them to the order of the dendrogram:
clusters <- clusters[order.dendrogram(dend)]

# get some functions:
library(dendextendRcpp)
library(colorspace)
no0_unique <- function(x) {
  u_x <- unique(x)
  u_x[u_x != 0]
}

clusters_numbers <- no0_unique(clusters)
n_clusters <- length(clusters_numbers)
cols <- rainbow_hcl(n_clusters)
dend2 <- branches_attr_by_clusters(dend, clusters, values = cols)
# dend2 <- branches_attr_by_clusters(dend, clusters)
plot(dend2)
# add colored bars:
ord_cols <- rainbow_hcl(n_clusters)[order(clusters_numbers)]
tmp_cols <- rep(1, length(clusters))
tmp_cols[clusters != 0] <- ord_cols[clusters != 0][clusters]
colored_bars(tmp_cols, y_shift = -1.1, rowLabels = "")
# all of the ordering is to handle the fact that the cluster numbers are not ascending...

```



```

# How is this compared with the usual cutree?
dend3 <- color_branches(dend, k = n_clusters)
labels(dend2) <- as.character(labels(dend2))
# this needs fixing, since the labels are not character!
# Well, both cluster solutions are not perfect, but at least they are interesting...
tanglegram(dend2, dend3,
            main_left = "cutreeDynamic", main_right = "cutree",
            columns_width = c(5,.5,5),
            color_lines = cols[iris[order.dendrogram(dend2),5]])
# (Notice how the color_lines is of the true Species of each Iris)
# The main difference is at the bottom,

## End(Not run)

```

branches_attr_by_labels

Change col/lwd/lty of branches matching labels condition

Description

The user supplies a dend, labels, and type of condition (all/any), and TF_values And the function returns a dendrogram with branches col/lwd/lty accordingly

Usage

```
branches_attr_by_labels(dend, labels, TF_values = c(2, Inf), attr = c("col",
  "lwd", "lty"), type = c("all", "any"), ...)
```

Arguments

dend	a dendrogram dend
labels	a character vector of labels from the tree
TF_values	a two dimensional vector with the TF_values to use in case a branch fulfills the condition (TRUE) and in the case that it does not (FALSE). Defaults are 2/Inf for col, lwd and lty. (so it will insert the first value, and will not change all the FALSE cases)
attr	a character with one of the following values: col/lwd/lty
type	a character vector of either "all" or "any", indicating which of the branches should be painted: ones that all of their labels belong to the supplied labels, or also ones that even some of their labels are included in the labels vector.
...	ignored.

Value

A dendrogram with modified branches (col/lwd/lty).

See Also

[noded_with_condition](#), [get_leaves_attr](#), [nnodes](#), [nleaves](#)

Examples

```
## Not run:

library(dendextend)

set.seed(23235)
ss <- sample(1:150, 10 )

# Getting the dend dend
dend <- iris[ss,-5] %>% dist %>% hclust %>% as.dendrogram
dend %>% plot

dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29")) %>%
  plot
dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29"), "all") %>%
  plot # the same as above
dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29"), "any") %>%
  plot

dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29"),
    "any", "col", c("blue", "red")) %>% plot
dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29"),
    "any", "lwd", c(4,1)) %>% plot
dend %>%
  branches_attr_by_labels(c("123", "126", "23", "29"),
    "any", "lty", c(2,1)) %>% plot

## End(Not run)
```

click_rotate

Interactively rotate a tree object

Description

Lets te user click a plot of dendrogram and rotates the tree based on the location of the click.

Usage

```
click_rotate(x, ...)

## S3 method for class 'dendrogram'
click_rotate(x, plot = TRUE, plot_after = plot, horiz = FALSE, continue = FALSE, ...)
```

Arguments

x	a tree object (either a dendrogram or hclust)
...	parameters passed to the plot
plot	(logical) should the dendrogram first be plotted.
plot_after	(logical) should the dendrogram be plotted after the rotation?
horiz	logical. Should the plot be normal or horizontal?
continue	logical. If TRUE, allows the user to keep clicking the plot until a click is made on the labels.

Value

A rotated tree object

Author(s)

Andrej-Nikolai Spiess, Tal Galili

See Also

[rotate.dendrogram](#)

Examples

```
# create the dend:
dend <- USArrests %>% dist %>% hclust("ave") %>%
as.dendrogram %>% color_labels

## Not run:
# play with the rotation once
dend <- click_rotate(dend)
dend <- click_rotate(dend, horiz = TRUE)
# keep playing with the rotation:
while(TRUE) dend <- click_rotate(dend)
# the same as
dend <- click_rotate(dend, continue = TRUE)

## End(Not run)
```

collapse_branch	<i>Collapse branches under a tolerance level</i>
-----------------	--

Description

Collapse branches under a tolerance level

Usage

```
collapse_branch(dend, tol = 1e-08, lower = TRUE, ...)
```

Arguments

dend	dendrogram object
tol	a numeric value giving the tolerance to consider a branch length significantly greater than zero
lower	logical (TRUE). collapse branches which are lower than tol?
...	passed on (not used)

Value

A dendrogram with both of the root's branches of the same height

See Also

[multi2di](#)

Examples

```
# # ladderize is like sort(..., type = "node")
dend <- iris[1:5,-5] %>% dist %>% hclust %>% as.dendrogram
par(mfrow = c(1,3))
dend %>% ladderize %>% plot(horiz = TRUE); abline(v = .2, col = 2, lty = 2)
dend %>% collapse_branch(tol = 0.2) %>% ladderize %>% plot(horiz = TRUE)
dend %>% collapse_branch(tol = 0.2) %>% ladderize %>%
  hang.dendrogram(hang = 0) %>% plot(horiz = TRUE)

par(mfrow = c(1,2))
dend %>% collapse_branch(tol = 0.2, lower = FALSE) %>% plot(horiz = TRUE, main = "dendrogram")
library(ape)
dend %>% as.phylo %>% di2multi(tol = 0.2) %>% plot(main = "phylo")
```

colored_bars	<i>Add colored bars to a dendrogram</i>
--------------	---

Description

Add colored bars to a dendrogram, usually corresponding to either clusters or some outside categorization.

Usage

```
colored_bars(colors, dend, rowLabels = NULL, cex.rowLabels = 0.9,
             add = TRUE, y_scale, y_shift, text_shift = 1,
             sort_by_labels_order = FALSE, ...)
```

Arguments

colors	Coloring of objects on the dendrogram. Either a vector (one color per object) or a matrix (can also be an array or a data frame) with each column giving one color per object. Each column will be plotted as a horizontal row of colors under the dendrogram.
dend	a dendrogram object. If missing, the colors are plotted without and re-ordering (this assumes that the colors are already ordered based on the dend's labels) This is also important in order to get the correct height/location of the colored bars (i.e.: adjusting the y_scale and y_shift)
rowLabels	Labels for the colorings given in colors. The labels will be printed to the left of the color rows in the plot. If the argument is given, it must be a vector of length equal to the number of columns in colors. If not given, names(colors) will be used if available. If not, sequential numbers starting from 1 will be used.
cex.rowLabels	Font size scale factor for the row labels. See par .
add	logical(TRUE), should the colored bars be added to an existing dendrogram plot?
y_scale	how much should the bars be stretched on the y axis? If no dend is supplied - the default will be 1
y_shift	where should the bars be plotted underneath the x axis? By default it will try to locate the bars underneath the labels (it may miss, in which case you would need to enter a number manually) If no dend is supplied - the default will be 0
text_shift	a dendrogram object
sort_by_labels_order	logical(FALSE) - if TRUE, then the order of the colored bars will be sorted based on the order needed to change the original order of the observations to the current order of the labels in the dendrogram. If FALSE (default) the colored bars are plotted as-is, based on the order of the colors vector.
...	ignored at this point.

Details

You will often need to adjust the `y_scale`, `y_shift` and the `text_shift` parameters, in order to get the bars in the location you would want.

(this can probably be done automatically, but will require more work. since it has to do with the current mar settings, the number of groups, and each computer's specific graphic device. patches for smarter defaults will be appreciated)

Value

An invisible vector/matrix with the ordered colors.

Author(s)

Steve Horvath <SHorvath@mednet.ucla.edu>, Peter Langfelder <Peter.Langfelder@gmail.com>, Tal Galili <Tal.Galili@gmail.com>

Source

This function is based on the `plotHclustColors` from the `moduleColor` R package. It was modified so that it would work with dendrograms (and not just `hclust` objects), as well allow to add the colored bars on top of an existing plot (and not only as a separate plot).

See: <http://cran.r-project.org/web/packages/moduleColor/> For more details.

See Also

[branches_attr_by_clusters](#), [plotDendroAndColors](#)

Examples

```
## Not run:

rows_picking <- c(1:5, 25:30)
dend <- (iris[rows_picking,-5]*10) %>% dist %>% hclust %>% as.dendrogram
odd_numbers <- rows_picking %% 2
cols <- c("gold", "grey")[odd_numbers+1]
# scale is off
plot(dend)
colored_bars(dend, cols)
# move and scale a bit
plot(dend)
colored_bars(dend, cols, y_shift = -1,
             rowLabels = "Odd\n numbers")
# Now let's cut the tree and add that info to the plot:
k2 <- cutree(dend, k = 2)
cols2 <- c("#0082CE", "#CC476B")[k2]
plot(dend)
# sadly, the shift paramteres need to be handled manually...
colored_bars(dend, cbind(cols2, cols), y_shift = -1,
             rowLabels = c("2 clusters", "Odd numbers"),
             text_shift = 1)
```

```

# let's add clusters color
# notice how we need to play with the colors a bit
# this is because color_branches places colors from
# left to right. Which means we need to give colored_bars
# the colors of the items so that after sorting they would be
# from left to right. Here is how it can be done:
the_k <- 3
library(colorspace)
cols3 <- rainbow_hcl(the_k, c=90, l=50)
dend %>% update("branches_k_color", k = the_k, with = cols3) %>% plot

kx <- cutree(dend, k = the_k)
ord <- order.dendrogram(dend)
kx <- sort_levels_values(kx[ord])
kx <- kx[match(seq_along(ord), ord)]

colored_bars(dend, cbind(cols3[kx], cols2, cols),
             y_shift = -1, y_scale = 1.4,
             rowLabels = c("3 clusters", "2 clusters", "Odd numbers"),
             text_shift = 1)

## End(Not run)

```

color_branches

Color tree's branches according to sub-clusters

Description

This function is for dendrogram and hclust objects. This function colors both the terminal leaves of a tree's cluster and the edges leading to those leaves. The edgePar attribute of nodes will be augmented by a new list item col. The groups will be defined by a call to [cutree](#) using the k or h parameters.

If col is a color vector with a different length than the number of clusters (k) - then a recycled color vector will be used.

Usage

```
color_branches(tree, k = NULL, h = NULL, col, groupLabels = NULL,
              warn = dendextend_options("warn"), ...)
```

Arguments

tree	A dendrogram or hclust tree object
k	number of groups (passed to cutree)

h	height at which to cut tree (passed to cutree)
col	Function or vector of Colors. By default it tries to use rainbow_hcl from the colorspace package. (with parameters <code>c=90</code> and <code>l=50</code>). If colorspace is not available, It will fall back on the rainbow function.
groupLabels	If TRUE add numeric group label - see Details for options
warn	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warnings are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	ignored.

Details

If `groupLabels=TRUE` then numeric group labels will be added to each cluster. If a vector is supplied then these entries will be used as the group labels. If a function is supplied then it will be passed a numeric vector of groups (e.g. `1:5`) and must return the formatted group labels.

If the [labels](#) of the dendrogram are NOT character (but, for example integers) - they are coerced into character. This step is essential for the proper operation of the function. A dendrogram labels might happen to be integers if they are based on an [hclust](#) performed on a [dist](#) of an object without [rownames](#).

Value

a tree object of class dendrogram.

Author(s)

Tal Galili, extensively based on code by Gregory Jefferis

Source

This function is a derived work from the [color_clusters](#) function, with some ideas from the [slice](#) function - both are from the [dendroextras](#) package by jefferis.

It extends it by using [cutree.dendrogram](#) - allowing the function to work for trees that [hclust](#) can not handle (unbranched and non-ultrametric trees). Also, it allows REPEATED cluster color assignments to branches on to the same tree. Something which the original function was not able to handle.

See Also

[cutree.dendrogram](#), [hclust](#), [labels_colors](#)

Examples

```
## Not run:
dend <- USArrests %>% dist %>% hclust(method = "ave") %>% as.dendrogram
d1=color_branches(dend,5, col = c(3,1,1,4,1))
plot(d1) # selective coloring of branches :)
d2=color_branches(d1,5)
```



```

plot(d2)

d1=color_branches(dend,5, col = c(3,1,1,4,1),groupLabels=TRUE)
plot(d1) # selective coloring of branches :)
d2=color_branches(d1,5,groupLabels=TRUE)
plot(d2)

d5=color_branches(dend,5)
plot(d5)
d5g=color_branches(dend,5,groupLabels=TRUE)
plot(d5g)
d5gr=color_branches(dend,5,groupLabels=as.roman)
plot(d5gr)

# messy - but interesting:
dend_override=color_branches(dend,2,groupLabels=as.roman)
dend_override=color_branches(dend_override,4,groupLabels=as.roman)
dend_override=color_branches(dend_override,7,groupLabels=as.roman)
plot(dend_override)

d5=color_branches(tree=dend[[1]],k=5)

library(dendextend)
data(iris, envir = environment())
d_iris <- dist(iris[,-5])
hc_iris <- hclust(d_iris)
dend_iris <- as.dendrogram(hc_iris)
dend_iris=color_branches(dend_iris,k=3)

library(colorspace)
labels_colors(dend_iris) <-
  rainbow_hcl(3)[sort_levels_values(
    as.numeric(iris[,5])[order.dendrogram(dend_iris)]
  )]

plot(dend_iris,
main = "Clustered Iris dataset",
  sub = "labels are colored based on the true cluster")

# cutree(dend_iris,k=3, order_clusters_as_data=FALSE,
  # sort_cluster_numbers = TRUE, try_cutree_hclust=FALSE)
# cutree(dend_iris,k=3, order_clusters_as_data=FALSE,
  # sort_cluster_numbers = TRUE, try_cutree_hclust=TRUE)

library(colorspace)

data(iris, envir = environment())
d_iris <- dist(iris[,-5])
hc_iris <- hclust(d_iris)
labels(hc_iris) # no labels, because "iris" has no row names

```

```

dend_iris <- as.dendrogram(hc_iris)
is.integer(labels(dend_iris)) # this could cause problems...

iris_species <- rev(levels(iris[,5]))
dend_iris <- color_branches(dend_iris,k=3, groupLabels=iris_species)
is.character(labels(dend_iris)) # labels are no longer "integer"

# have the labels match the real classification of the flowers:
labels_colors(dend_iris) <-
  rainbow_hcl(3)[sort_levels_values(
    as.numeric(iris[,5])[order.dendrogram(dend_iris)]
  )]

# We'll add the flower type
labels(dend_iris) <- paste(as.character(iris[,5])[order.dendrogram(dend_iris)],
  "(",labels(dend_iris),")",
  sep = "")

dend_iris <- hang.dendrogram(dend_iris,hang_height=0.1)

# reduce the size of the labels:
dend_iris <- assign_values_to_leaves_nodePar(dend_iris, 0.5, "lab.cex")

par(mar = c(3,3,3,7))
plot(dend_iris,
  main = "Clustered Iris dataset
  (the labels give the true flower species)",
  horiz = TRUE, nodePar = list(cex = .007))
legend("topleft", legend = iris_species, fill = rainbow_hcl(3))
a= dend_iris[[1]]
dend_iris1 <- color_branches(a,k = 3)
plot(dend_iris1)

# str(dendrapply(d2, unclass))
# unclass(d1)

c(1:5) %>% # take some data
  dist %>% # calculate a distance matrix,
  hclust(method = "single") %>% # on it compute hierarchical clustering using the "average" method,
  as.dendrogram %>% color_branches(k=3) %>% plot # nice, returns the tree as is...

## End(Not run)

```

color_labels

Color tree's labels according to sub-clusters

Description

This function is for dendrogram and hclust objects. This function colors tree's labels.

The groups will be defined by a call to `cutree` using the `k` or `h` parameters.

If `col` is a color vector with a different length than the number of clusters (`k`) - then a recycled color vector will be used.

Usage

```
color_labels(tree, k = NULL, h = NULL, labels, col,
             warn = dendextend_options("warn"), ...)
```

Arguments

<code>tree</code>	A dendrogram or <code>hclust</code> tree object
<code>k</code>	number of groups (passed to <code>cutree</code>)
<code>h</code>	height at which to cut tree (passed to <code>cutree</code>)
<code>labels</code>	character vector. If not missing, it overrides <code>k</code> and <code>h</code> , and simply colors these labels in the tree based on "col" parameter.
<code>col</code>	Function or vector of Colors. By default it tries to use <code>rainbow_hcl</code> from the <code>colorspace</code> package. (with parameters <code>c=90</code> and <code>l=50</code>). If <code>colorspace</code> is not available, It will fall back on the <code>rainbow</code> function.
<code>warn</code>	logical (default from <code>dendextend_options("warn")</code> is <code>FALSE</code>). Set if warnings are to be issued, it is safer to keep this at <code>TRUE</code> , but for keeping the noise down, the default is <code>FALSE</code> . (in case <code>h/k/labels</code> are not supplied, or if <code>col</code> is too short)
<code>...</code>	ignored.

Value

a tree object of class `dendrogram`.

Source

This function is in the style of `color_branches`, and based on `labels_colors`.

See Also

`cutree`, `dendrogram`, `hclust`, `labels_colors`, `color_branches`

Examples

```
## Not run:
hc <- hclust(dist(USArrests), "ave")
dend <- as.dendrogram(hc)
dend=color_labels(dend,5, col = c(3,1,1,4,1))
dend=color_branches(dend,5, col = c(3,1,1,4,1))
plot(dend) # selective coloring of branches AND labels :)

# coloring some labels, based on label names:
dend=color_labels(dend,col = "red", labels = labels(dend)[c(4,16)])
plot(dend) # selective coloring of branches AND labels :)
```

```

d5=color_branches(dend,5)
plot(d5)
d5g=color_branches(dend,5,groupLabels=TRUE)
plot(d5g)
d5gr=color_branches(dend,5,groupLabels=as.roman)
plot(d5gr)

## End(Not run)

```

cor.dendlist

Correlation matrix between a list of trees.

Description

A correlation matrix between a list of trees.

Assumes the labels in the two trees fully match. If they do not please first use [intersect_trees](#) to have them matched.

Usage

```
cor.dendlist(x, method = c("cophenetic", "baker"), ...)
```

Arguments

x	a dendlist of trees
method	a character string indicating which correlation coefficient is to be computed. One of "cophenetic" (default), or "baker", can be abbreviated.
...	Ignored.

Value

A correlation matrix between the different trees

See Also

[cophenetic](#), [cor_cophenetic](#), [cor_bakers_gamma](#)

Examples

```

## Not run:

set.seed(23235)
ss <- sample(1:150, 10 )
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("single") %>% as.dendrogram
dend3 <- iris[ss,-5] %>% dist %>% hclust("ave") %>% as.dendrogram
dend4 <- iris[ss,-5] %>% dist %>% hclust("centroid") %>% as.dendrogram

```

```
#   cutree(dend1)
cor.dendlist(dendlist(d1 = dend1, d2 = dend2, d3 = dend3, d4 = dend4))

## End(Not run)
```

cor_bakers_gamma *Baker's Gamma correlation coefficient*

Description

Calculate Baker's Gamma correlation coefficient for two trees.

Assumes the labels in the two trees fully match. If they do not please first use [intersect_trees](#) to have them matched.

WARNING: this can be quite slow for medium/large trees.

Usage

```
cor_bakers_gamma(tree1, ...)

## S3 method for class 'dendrogram'
cor_bakers_gamma(tree1, tree2, use_labels_not_values = TRUE,
to_plot = FALSE, warn = dendextend_options("warn"), ...)
## S3 method for class 'hclust'
cor_bakers_gamma(tree1, tree2, use_labels_not_values = TRUE,
to_plot = FALSE, warn = dendextend_options("warn"), ...)
## S3 method for class 'dendlist'
cor_bakers_gamma(tree1, which = c(1L, 2L), ...)
```

Arguments

tree1	a tree (dendrogram/hclust/phylo)
...	Passed to cutree .
tree2	a tree (dendrogram/hclust/phylo)
use_labels_not_values	logical (TRUE). Should labels be used in the k matrix when using cutree? Set to FALSE will make the function a bit faster BUT, it assumes the two trees have the exact same leaves order values for each labels. This can be assured by using match_order_by_labels .
to_plot	logical (FALSE). Passed to bakers_gamma_for_2_k_matrix
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. should a warning be issued when using cutree ?
which	an integer vector of length 2, indicating which of the trees in the dendlist object should be plotted (relevant for dendlist)

Details

Baker's Gamma (see reference) is a measure of association (similarity) between two trees of hierarchical clustering (dendrograms).

It is calculated by taking two items, and see what is the highest possible level of k (number of cluster groups created when cutting the tree) for which the two items still belong to the same tree. That k is returned, and the same is done for these two items for the second tree. There are n over 2 combinations of such pairs of items from the items in the tree, and all of these numbers are calculated for each of the two trees. Then, these two sets of numbers (a set for the items in each tree) are paired according to the pairs of items compared, and a Spearman correlation is calculated.

The value can range between -1 to 1. With near 0 values meaning that the two trees are not statistically similar. For exact p-value one should result to a permutation test. One such option will be to permute over the labels of one tree many times, and calculating the distribution under the null hypothesis (keeping the trees topologies constant).

Notice that this measure is not affected by the height of a branch but only of its relative position compared with other branches.

Value

Baker's Gamma association Index between two trees (a number between -1 to 1)

References

Baker, F. B., Stability of Two Hierarchical Grouping Techniques Case 1: Sensitivity to Data Errors. Journal of the American Statistical Association, 69(346), 440 (1974).

See Also

[cor_cophenetic](#)

Examples

```
## Not run:

set.seed(23235)
ss <- sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
dend1 <- as.dendrogram(hc1)
dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

cor_bakers_gamma(hc1, hc2)
cor_bakers_gamma(dend1, dend2)

dend1 <- match_order_by_labels(dend1, dend2) # if you are not sure
cor_bakers_gamma(dend1, dend2, use_labels_not_values = FALSE)

library(microbenchmark)
microbenchmark(
```

```

with_labels = cor_bakers_gamma(dend1, dend2, try_cutree_hclust=FALSE) ,
with_values = cor_bakers_gamma(dend1, dend2,
                               use_labels_not_values = FALSE, try_cutree_hclust=FALSE) ,
times=10
)

```

```

cor_bakers_gamma(dend1, dend1, use_labels_not_values = FALSE)
cor_bakers_gamma(dend1, dend1, use_labels_not_values = TRUE)

```

```
## End(Not run)
```

cor_cophenetic	<i>Cophenetic correlation between two trees</i>
----------------	---

Description

Cophenetic correlation coefficient for two trees.

Assumes the labels in the two trees fully match. If they do not please first use [intersect_trees](#) to have them matched.

Usage

```
cor_cophenetic(tree1, ...)
```

```
## Default S3 method:
```

```
cor_cophenetic(tree1, tree2, method = c("pearson", "kendall", "spearman"), ...)
```

```
## S3 method for class 'dendlist'
```

```
cor_cophenetic(tree1, which = c(1L,2L), method = c("pearson", "kendall", "spearman"), ...)
```

Arguments

tree1	a tree (dendrogram/hclust/phylo, or dendlist)
...	Ignored.
tree2	a tree (dendrogram/hclust/phylo)
which	an integer vector of length 2, indicating which of the trees in a dendlist object should have their cor_cophenetic calculated.
method	a character string indicating which correlation coefficient is to be computed. One of "pearson" (default), "kendall", or "spearman", can be abbreviated. Passed to cor .

Details

From [cophenetic](#): The cophenetic distance between two observations that have been clustered is defined to be the intergroup dissimilarity at which the two observations are first combined into a single cluster. Note that this distance has many ties and restrictions.

cor_cophenetic calculates the correlation between two cophenetic distance matrices of the two trees.

The value can range between -1 to 1. With near 0 values meaning that the two trees are not statistically similar. For exact p-value one should result to a permutation test. One such option will be to permute over the labels of one tree many times, and calculating the distribution under the null hypothesis (keeping the trees topologies constant).

Notice that this measure IS affected by the height of a branch.

Value

The correlation between cophenetic

References

Sokal, R. R. and F. J. Rohlf. 1962. The comparison of dendrograms by objective methods. *Taxon*, 11:33-40

Sneath, P.H.A. and Sokal, R.R. (1973) *Numerical Taxonomy: The Principles and Practice of Numerical Classification*, p. 278 ff; Freeman, San Francisco.

http://en.wikipedia.org/wiki/Cophenetic_correlation

See Also

[cophenetic](#), [cor_bakers_gamma](#)

Examples

```
## Not run:

set.seed(23235)
ss <- sample(1:150, 10 )
hc1 <- iris[ss,-5] %>% dist %>% hclust("com")
hc2 <- iris[ss,-5] %>% dist %>% hclust("single")
dend1 <- as.dendrogram(hc1)
dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

cophenetic(hc1)
cophenetic(hc2)
# notice how the dist matrix for the dendrograms have different orders:
cophenetic(dend1)
cophenetic(dend2)

cor(cophenetic(hc1), cophenetic(hc2)) # 0.874
cor(cophenetic(dend1), cophenetic(dend2)) # 0.16
# the difference is because the order of the distance table in the case of
# stats:::cophenetic.dendrogram will change between dendrograms!
```



```

# however, this is consistant (since I force-sort the rows/columns):
cor_cophenetic(hc1, hc2)
cor_cophenetic(dend1, dend2)

cor_cophenetic(dendlist(dend1, dend2))

# we can also use different cor methods (almost the same result though):
cor_cophenetic(hc1, hc2, method = "spearman") # 0.8456014
cor_cophenetic(dend1, dend2, method = "spearman") #

# cophenetic correlation is about 10 times (!) faster than bakers_gamma cor:
library(microbenchmark)
microbenchmark(
  cor_bakers_gamma = cor_bakers_gamma(dend1, dend2, try_cutree_hclust=FALSE),
  cor_cophenetic = cor_cophenetic(dend1, dend2) ,
  times=10
)

# but only because of the cutree for dendrogram. When allowing hclust cutree
# it is only about twice as fast:
microbenchmark(
  cor_bakers_gamma = cor_bakers_gamma(dend1, dend2, try_cutree_hclust=TRUE),
  cor_cophenetic = cor_cophenetic(dend1, dend2) ,
  times=10
)

## End(Not run)

```

count_terminal_nodes *Counts the number of terminal nodes (merging 0 nodes!)*

Description

This function counts the number of "practical" terminal nodes (nodes which are not leaves, but has 0 height to them are considered "terminal" nodes). If the tree is standard, that would simply be the number of leaves (only the leaves will have height 0). However, in cases where the tree has several nodes (before the leaves) with 0 height, the count_terminal_nodes counts such nodes as terminal nodes

The function is recursive in that it either returns 1 if it reached a terminal node (either a leaf or a 0 height node), else: it will count the number of terminal nodes in each of its sub-nodes, sum them up, and return them.

Usage

```
count_terminal_nodes(dend_node, ...)
```

Arguments

dend_node a dendrogram object for which to count its number of terminal nodes (leaves or 0 height nodes).
 ... not used

Value

The number of terminal nodes (excluding the leaves of nodes of height 0)

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

###
# Trivial case
count_terminal_nodes(dend) # 3 terminal nodes
length(labels(dend)) # 3 - the same number
plot(dend,
main = "This is considered a tree \n with THREE terminal nodes (leaves)")

###
# NON-Trivial case
str(dend)
attr(dend[[2]], "height") <- 0
count_terminal_nodes(dend) # 2 terminal nodes, why? see this plot:
plot(dend,
main = "This is considered a tree \n with TWO terminal nodes only")
# while we have 3 leaves, in practice we have only 2 terminal nodes
# (this is a feature, not a bug.)
```

cutree

Cut a Tree (Dendrogram/hclust/phylo) into Groups of Data

Description

Cuts a dendrogram tree into several groups by specifying the desired number of clusters k(s), or cut height(s).

For hclust.dendrogram - In case there exists no such k for which exists a relevant split of the dendrogram, a warning is issued to the user, and NA is returned.

Usage

```
cutree(tree, k = NULL, h = NULL, ...)
```

```
## S3 method for class 'hclust'
cutree(tree, k = NULL, h = NULL,
```

```

        use_labels_not_values = TRUE,
        order_clusters_as_data =TRUE,
        sort_cluster_numbers = TRUE,
        warn = dendextend_options("warn"),
        NA_to_0L = TRUE,
        ...)

## S3 method for class 'phylo'
cutree(tree, k = NULL, h = NULL,...)

## S3 method for class 'dendrogram'
cutree(tree, k = NULL, h = NULL,
        dend_heights_per_k = NULL,
        use_labels_not_values = TRUE,
        order_clusters_as_data =TRUE,
        sort_cluster_numbers = TRUE,
        warn = dendextend_options("warn"),
        try_cutree_hclust = TRUE,
        NA_to_0L = TRUE,
        ...)

```

Arguments

tree	a dendrogram object
k	numeric scalar (OR a vector) with the number of clusters the tree should be cut into.
h	numeric scalar (OR a vector) with a height where the tree should be cut.
...	(not currently in use)
dend_heights_per_k	a named vector that resulted from running <code>heights_per_k.dendrogram</code> . When running the function many times, supplying this object will help improve the running time if using <code>k!=NULL</code> .
use_labels_not_values	logical, defaults to TRUE. If the actual labels of the clusters do not matter - and we want to gain speed (say, 10 times faster) - then use FALSE (gives the "leaves order" instead of their labels.). This is passed to <code>cutree_1h.dendrogram</code> .
order_clusters_as_data	logical, defaults to TRUE. There are two ways by which to order the clusters: 1) By the order of the original data. 2) by the order of the labels in the dendrogram. In order to be consistent with cutree , this is set to TRUE. This is passed to <code>cutree_1h.dendrogram</code> .
sort_cluster_numbers	logical (TRUE). Should the resulting cluster id numbers be sorted? (default is TRUE in order to make the function compatible with cutree) from stats, but it allows for sensible color order when using color_branches .
warn	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the

	default is FALSE. Should the function send a warning in case the desired k is not available?
try_cutree_hclust	logical. default is TRUE. Since cutree for hclust is MUCH faster than for dendrogram - cutree.dendrogram will first try to change the dendrogram into an hclust object. If it will fail (for example, with unbranched trees), it will continue using the cutree.dendrogram function. If try_cutree_hclust=FALSE, it will force to use cutree.dendrogram and not cutree.hclust.
NA_to_0L	logical. default is TRUE. When no clusters are possible, Should the function return 0 (TRUE, default), or NA (when set to FALSE).

Details

At least one of k or h must be specified, k overrides h if both are given.

as opposed to [cutree](#) for hclust, cutree.dendrogram allows the cutting of trees at a given height also for non-ultrametric trees (ultrametric tree == a tree with monotone clustering heights). This sort_cluster_numbers parameter is based on the [sort_levels_values](#) function. Using that parameter with TRUE makes the clusters id's from cutree to be ordered from left to right. e.g: the left most cluster in the tree will be numbered "1", the one after it will be "2" etc...).

Value

If k or h are scalar - cutree.dendrogram returns an integer vector with group memberships. Otherwise a matrix with group memberships is returned where each column corresponds to the elements of k or h, respectively (which are also used as column names).

In case there exists no such k for which exists a relevant split of the dendrogram, a warning is issued to the user, and NA is returned.

Author(s)

cutree.dendrogram was written by Tal Galili. cutree.hclust is redirecting the function to [cutree](#) from base R.

See Also

[hclust](#), [cutree](#), [cutree_1h.dendrogram](#), [cutree_1k.dendrogram](#),

Examples

```
## Not run:
hc <- hclust(dist(USArrests[c(1,6,13,20, 23),]), "ave")
dend <- as.dendrogram(hc)
unbranch_dend <- unbranch(dend,2)

cutree(hc, k=2:4) # on hclust
cutree(dend, k=2:4) # on dendrogram

cutree(hc, k=2) # on hclust
cutree(dend, k=2) # on dendrogram
```

```

cutree(dend, h = c(20, 25.5, 50,170))
cutree(hc, h = c(20, 25.5, 50,170))

# the default (ordered by original data's order)
cutree(dend, k=2:3, order_clusters_as_data = FALSE)
labels(dend)

# as.hclust(unbranch_dend) # ERROR - can not do this...
cutree(unbranch_dend, k = 2) # all NA's
cutree(unbranch_dend, k = 1:4)
cutree(unbranch_dend, h = c(20, 25.5, 50,170))
cutree(dend, h = c(20, 25.5, 50,170))

library(microbenchmark)
## this shows how as.hclust is expensive - but still worth it if possible
microbenchmark(
  cutree(hc, k=2:4),
  cutree(as.hclust(dend), k=2:4),
  cutree(dend, k=2:4),
  cutree(dend, k=2:4, try_cutree_hclust=FALSE)
)
# the dendrogram is MUCH slower...

# Unit: microseconds
##          expr      min       lq   median       uq      max neval
##  cutree(hc, k = 2:4)  91.270   96.589   99.3885  107.5075  338.758   100
##  tree(as.hclust(dend),
##    k = 2:4)         1701.629 1767.700 1854.4895 2029.1875  8736.591   100
##  cutree(dend, k = 2:4) 1807.456 1869.887 1963.3960 2125.2155  5579.705   100
##  cutree(dend, k = 2:4,
##    try_cutree_hclust = FALSE) 8393.914 8570.852 8755.3490 9686.7930 14194.790   100

# and trying to "hclust" is not expensive (which is nice...)
microbenchmark(
  cutree_unbranch_dend = cutree(unbranch_dend, k=2:4),
  cutree_unbranch_dend_not_trying_to_hclust =
  cutree(unbranch_dend, k=2:4, try_cutree_hclust=FALSE)
)

## Unit: milliseconds
##          expr      min       lq   median       uq      max neval
##cutree_unbranch_dend  7.309329 7.428314 7.494107 7.752234 17.59581   100
##cutree_unbranch_dend_not
##_trying_to_hclust    6.945375 7.079198 7.148629 7.577536 16.99780   100
##There were 50 or more warnings (use warnings() to see the first 50)

# notice that if cutree can't find clusters for the desired k/h, it will produce 0's instead!
# (It will produce a warning though...)
# This is a different behaviour than stats::cutree
# For example:
cutree(as.dendrogram(hclust(dist(c(1,1,1,2,2))))),

```

```

        k=5)

## End(Not run)

```

```
cutree_1h.dendrogram  cutree for dendrogram (by 1 height only!)
```

Description

Cuts a dendrogram tree into several groups by specifying the desired cut height (only a single height!).

Usage

```
cutree_1h.dendrogram(tree, h, order_clusters_as_data = TRUE,
  use_labels_not_values = TRUE, warn = dendextend_options("warn"), ...)
```

Arguments

tree	a dendrogram object
h	numeric scalar (NOT a vector) with a height where the tree should be cut.
order_clusters_as_data	logical, defaults to TRUE. There are two ways by which to order the clusters: 1) By the order of the original data. 2) by the order of the labels in the dendrogram. In order to be consistent with cutree , this is set to TRUE.
use_labels_not_values	logical, defaults to TRUE. If the actual labels of the clusters do not matter - and we want to gain speed (say, 10 times faster) - then use FALSE (gives the "leaves order" instead of their labels.).
warn	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	(not currently in use)

Value

cutree_1h.dendrogram returns an integer vector with group memberships

Author(s)

Tal Galili

See Also

[hclust](#), [cutree](#)

Examples

```

hc <- hclust(dist(USArrests[c(1,6,13,20, 23),]), "ave")
dend <- as.dendrogram(hc)
cutree(hc, h=50) # on hclust
cutree_1h.dendrogram(dend, h=50) # on a dendrogram

labels(dend)

# the default (ordered by original data's order)
cutree_1h.dendrogram(dend, h=50, order_clusters_as_data = TRUE)

# A different order of labels - order by their order in the tree
cutree_1h.dendrogram(dend, h=50, order_clusters_as_data = FALSE)

# make it faster
## Not run:
library(microbenchmark)
microbenchmark(
  cutree_1h.dendrogram(dend, h=50),
  cutree_1h.dendrogram(dend, h=50, use_labels_not_values = FALSE)
)
# 0.8 vs 0.6 sec - for 100 runs

## End(Not run)

```

cutree_1k.dendrogram *cutree for dendrogram (by 1 k value only!)*

Description

Cuts a dendrogram tree into several groups by specifying the desired number of clusters *k* (only a single *k* value!).

In case there exists no such *k* for which exists a relevant split of the dendrogram, a warning is issued to the user, and NA is returned.

Usage

```

cutree_1k.dendrogram(tree, k, dend_heights_per_k = NULL,
  use_labels_not_values = TRUE, order_clusters_as_data = TRUE,
  warn = dendextend_options("warn"), ...)

```

Arguments

tree	a dendrogram object
k	numeric scalar (not a vector!) with the number of clusters the tree should be cut into.

dend_heights_per_k	a named vector that resulted from running <code>heights_per_k.dendrogram</code> . When running the function many times, supplying this object will help improve the running time.
use_labels_not_values	logical, defaults to TRUE. If the actual labels of the clusters do not matter - and we want to gain speed (say, 10 times faster) - then use FALSE (gives the "leaves order" instead of their labels.). This is passed to <code>cutree_1h.dendrogram</code> .
order_clusters_as_data	logical, defaults to TRUE. There are two ways by which to order the clusters: 1) By the order of the original data. 2) by the order of the labels in the dendrogram. In order to be consistent with <code>cutree</code> , this is set to TRUE. This is passed to <code>cutree_1h.dendrogram</code> .
warn	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. Should the function send a warning in case the desired k is not available?
...	(not currently in use)

Value

`cutree_1k.dendrogram` returns an integer vector with group memberships.

In case there exists no such k for which exists a relevant split of the dendrogram, a warning is issued to the user, and NA is returned.

Author(s)

Tal Galili

See Also

[hclust](#), [cutree](#), [cutree_1h.dendrogram](#)

Examples

```
hc <- hclust(dist(USArrests[c(1,6,13,20, 23),]), "ave")
dend <- as.dendrogram(hc)
cutree(hc, k=3) # on hclust
cutree_1k.dendrogram(dend, k=3) # on a dendrogram

labels(dend)

# the default (ordered by original data's order)
cutree_1k.dendrogram(dend, k=3, order_clusters_as_data = TRUE)

# A different order of labels - order by their order in the tree
cutree_1k.dendrogram(dend, k=3, order_clusters_as_data = FALSE)
```



```

# make it faster
## Not run:
library(microbenchmark)
dend_ks <- heights_per_k.dendrogram
microbenchmark(
  cutree_1k.dendrogram = cutree_1k.dendrogram(dend, k=4),
  cutree_1k.dendrogram_no_labels = cutree_1k.dendrogram(dend,
    k=4,use_labels_not_values = FALSE),
  cutree_1k.dendrogram_no_labels_per_k = cutree_1k.dendrogram(dend,
    k=4, use_labels_not_values = FALSE,
    dend_heights_per_k = dend_ks)
)
# the last one is the fastest...

## End(Not run)

```

cut_lower_fun

Cut a dendrogram - and run a function on the output

Description

Cuts the a tree at height *h* and returns a list with the FUN function implemented on all the sub trees created by cut at height *h*. This is used for creating a [cutree.dendrogram](#) function, by using the labels function as FUN.

This is the Rcpp version of the function, offering a 10-60 times improvement in speed (depending on the tree size it is used on).

Usage

```
cut_lower_fun(tree, h, FUN = labels, warn = dendextend_options("warn"), ...)
```

Arguments

tree	a dendrogram object.
h	a scalar of height to cut the tree by.
FUN	a function to run. (default is "labels")
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. Should the user be warned if reverting to default?
...	passed to FUN.

Value

A list with the output of running FUN on each of the sub trees derived from cutting "tree"

Author(s)

Tal Galili

See Also

[labels](#), [dendrogram](#), [cutree.dendrogram](#)

Examples

```
dend = as.dendrogram(hclust(dist(iris[1:4,-5])))
# this is really cool!
cut_lower_fun(dend, .4, labels)
lapply(cut(dend, h = .4)$lower, labels)
cut_lower_fun(dend, .4, order.dendrogram)

## Not run:
# library(dendextend)
library(dendextendRcpp)
dend_big = as.dendrogram(hclust(dist(iris[1:150,-5])))
library(microbenchmark)
microbenchmark(old_cut_lower_fun(dend_big, .1),
               dendextendRcpp::dendextendRcpp_cut_lower_fun(dend_big, .1),
               times = 100)
# about 7-15 times faster. It is faster the larger the tree is, and the lower h is.

## End(Not run)
```

d3dendrogram

Plot dendrogram to webpage and view.

Description

Plot dendrogram to webpage and view.

Usage

```
d3dendrogram(d, height = 500, width = 700, rightmargin = 200,
             open = TRUE, ...)
```

Arguments

d	a dendrogram object
height	pixels, height of the plot.
width	pixels, width of the plot
rightmargin	pixels to reserve on the right side for leaf labels.
open	open the graphic in a browser? (see details).
...	Graphical options, see d3dendro_options .

Details

If open=TRUE, the graphic is opened using the function defined by `getOption("viewer")`. If no viewer option is specified, `utils::browseURL` is opened. Specifically, in RStudio this means that the viewer is used.

Value

If open=TRUE, a character string containing the html is invisibly returned. If open=FALSE, a character string containing the html is returned.

Tips

Dendrogram plots with many end-nodes tend to get overlapping labels or (end)nodes. If the number of endnodes is not too large, there are several ways to overcome this.

- Decrease font size of the nodes (`node_font`, see [d3dendro_options](#) on how to specify)
- Decrease size of node radius (`node_radius`, *idem*)
- Increase the height of the plot. Use about (2 times font height) times `count_terminal_nodes(d)`.
- Plot sub-dendrograms in stead of the whole dendrogram. There's only so much detail a screen can display and your eye can observe. Consider plotting subdendrograms or other summaries when dendrograms have many, many nodes.

d3dendro_options *Get or set current defaults for d3dendrogram*

Description

Get or set current defaults for d3dendrogram

Usage

```
d3dendro_options(..., copy = FALSE)
```

Arguments

... <option>=<value> pairs (see below). If no option/value pair is given, a list with current settings is returned. If the single input "reset" is given, options are restored to factory settings.

copy only when options are set: set global options or return a modified copy of the global option environment invisibly?

Options

Option values are exported as-is to the generated javascript/webpage.

node_fill (char,"#fff")	Node color (fill)
node_stroke (char;"steelblue")	Node color (circumference)
node_stroke_width (char;"1.5px")	Width of node circumference
node_radius (num;4.5)	Size of node (pixels)
node_font (char;"14px sans-serif")	Font used to print labels. Size and type spec
link_fill (char;"none")	link fill color (you probably do not want to set this)
link_stroke (char;"#ccc")	link line color (that's the one you want)
link_stroke_width (char;"1.5px")	link line width (pixels)
axis_stroke (char;"black")	Color of axis line
axis_width (char;"2px")	Width of axis line
axis_ntick (num; 5)	Approximate nr of tick marks
axis_ticklength_in (num;5)	Length of tickmarks into the graph (pixels)
axis_ticklength_out (num;5)	Length of tickmarks out of the graph (pixels)
axis_tickmark_offset (num;8)	Distance between axis and tick labels (pixels)

dendextend_options *Access to dendextend_options*

Description

This is a function inside its own environment. This enables a bunch of functions to be manipulated outside the package, even when they are called from function within the dendextend package.

TODO: describe options.

A new "warn" dendextend_options parameter. logical (FALSE). Should warning be issued?

Usage

```
dendextend_options(option, value)
```

Arguments

option	a character scalar of the value of the options we would like to access or update.
value	any value that we would like to update into the "option" element in dendextend_options

Value

a list with functions

Author(s)

Kurt Hornik

Examples

```
dendextend_options("a")
dendextend_options("a", 1)
dendextend_options("a")
dendextend_options("a", NULL)
dendextend_options("a")
dendextend_options()
```

dendlist

Creating a dendlist object from several dendrograms

Description

It accepts several dendrograms and or dendlist objects and chain them all together. This function aim to help with the usability of comparing two or more dendrograms.

Usage

```
dendlist(...)

## S3 method for class 'dendlist'
plot(x, which = c(1L, 2L), ...)
```

Arguments

...	several dendrogram/hclust/phylo or dendlist objects If an object is hclust or phylo - it will be converted into a dendrogram.
x	a dendlist object
which	an integer vector of length 2, indicating which of the trees in the dendlist object should be plotted (relevant for dendlist)

Details

If there are list() in the ..., they are omitted. If ... is missing, it returns an empty dendlist.

Value

A list of class dendlist where each item is a dendrogram

Examples

```
## Not run:

dend <- iris[,-5] %>% dist %>% hclust %>% as.dendrogram
dend2 <- iris[,-5] %>% dist %>% hclust(method = "single") %>% as.dendrogram
dendlist(1:4, 5, a=dend) # Error
# dendlist <- function (...) list(...)
dendlist(dend)
```

```

dendlist(dend, dend)
dendlist(dend, dend, dendlist(dend))
# notice how the order of
dendlist(dend, dend2)
dendlist(dend) %>% dendlist(dend2)
dendlist(dend) %>% dendlist(dend2) %>% dendlist(dend)
dendlist(dend, dend2) %>% tanglegram
tanglegram(tree1 = dendlist(dend, dend2))

dend <- iris[1:20, -5] %>% dist %>% hclust %>% as.dendrogram
dend2 <- iris[1:20, -5] %>% dist %>% hclust(method = "single") %>% as.dendrogram

x <- dendlist(dend, dend2)
plot(x)

## End(Not run)

```

DendSer.dendrogram *Tries to run DendSer on a dendrogram*

Description

Implements dendrogram seriation. The function tries to turn the dend into hclust, on which it runs [DendSer](#).

Also, if a distance matrix is missing, it will try to use the [cophenetic](#) distance.

Usage

```
DendSer.dendrogram(dend, ser_weight, ...)
```

Arguments

dend	An object of class dendrogram
ser_weight	Used by cost function to evaluate ordering. For cost=costLS, this is a vector of object weights. Otherwise is a dist or symmetric matrix. passed to DendSer. If it is missing, the cophenetic distance is used instead.
...	parameters passed to DendSer

Value

Numeric vector giving an optimal dendrogram order

See Also

[DendSer](#), [DendSer.dendrogram](#), [untangle_DendSer](#), [rotate_DendSer](#)

Examples

```
## Not run:
library(DendSer) # already used from within the function
hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)
DendSer.dendrogram(dend)

## End(Not run)
```

dend_diff	<i>Plots two trees side by side, highlighting edges unique to each tree in red.</i>
-----------	---

Description

Plots two trees side by side, highlighting edges unique to each tree in red.

Usage

```
dend_diff(x, ...)

## S3 method for class 'dendrogram'
dend_diff(x, y, horiz = TRUE,
          ...)

## S3 method for class 'dendlist'
dend_diff(x, ..., which)
```

Arguments

x	a dendrogram or dendlist to compare with
...	passed to plot.dendrogram
y	a dendrogram to compare with
horiz	logical (TRUE) indicating if the dendrogram should be drawn horizontally or not.
which	an integer vector indicating, in the case "x" is a dendlist, on which of the trees should the modification be performed. If missing - the change will be performed on all of objects in the dendlist.

Value

Invisible [dendlist](#) of both trees.

Source

A [dendrogram](#) implementation for [phylo.diff](#) from the distory package

See Also

[distinct_edges](#), [highlight_distinct_edges](#), [dist.dendlist](#), [tanglegram](#) [assign_values_to_branches_edgePar](#), [distinct.edges](#),

Examples

```
x <- 1:5 %>% dist %>% hclust %>% as.dendrogram
y <- set(x, "labels", 5:1)

dend_diff(x, y)
dend_diff(dendlist(x, y))
dend_diff(dendlist(y, x))

dend1 <- 1:10 %>% dist %>% hclust %>% as.dendrogram
dend2 <- dend1 %>% set("labels", c(1,3,2,4, 5:10) )
dend_diff(dend1, dend2)
```

dist.dendlist

Topological Distances Between Two dendrograms

Description

This function computes the Robinson-Foulds distance (also known as symmetric difference) between two dendrograms. This is the sum of edges in both trees with labels that exist in only one of the two trees (i.e.: the length of [distinct_edges](#)).

This function might implement other topological distances in the future.

Usage

```
dist.dendlist(x, method = c("edgeset"), ...)
```

Arguments

x	a dendlist
method	currently only 'edgeset' is implemented.
...	Ignored.

Value

A [dist](#) object with topological distances between all trees

See Also

[distinct_edges](#), [dist.topo](#), [dist.multiPhylo](#), [treedist](#),

Examples

```
x <- 1:5 %>% dist %>% hclust %>% as.dendrogram
y <- set(x, "labels", 5:1)

dist.dendlist(dendlist(x1 = x,x2 = x,y1 = y))
dend_diff(x,y)
```

distinct_edges	<i>Finds the edges present in the first tree but not in the second</i>
----------------	--

Description

Finds the edges present in the first tree but not in the second

Usage

```
distinct_edges(x, y, ...)
```

Arguments

x	a dendrogram to find unique edges in
y	a dendrogram to compare with
...	Ignored.

Value

A numeric vector of edge ids for the first tree (x) that are not present in the second tree (y).

Source

A [dendrogram](#) implementation for [distinct.edges](#) from the [distory](#) package

See Also

[distinct_edges](#), [highlight_distinct_edges](#), [dist.dendlist](#), [tanglegram](#) [distinct.edges](#)

Examples

```
x <- 1:5 %>% dist %>% hclust %>% as.dendrogram
y <- set(x, "labels", 5:1)
distinct_edges(x, y)
distinct_edges(y, x)
dend_diff(x, y)
```

dist_long	<i>Turns a dist object to a "long" table</i>
-----------	--

Description

Turns a dist object to a "long" table

Usage

```
dist_long(d, ...)
```

Arguments

d	a distance object
...	not used

Value

A data.frame with two columns of rows and column names of the dist object and a third column (distance) with the distance between the two.

Examples

```
data(iris)
iris[2:6,-5] %>% dist %>% data.matrix
iris[2:6,-5] %>% dist %>% as.vector
iris[2:6,-5] %>% dist %>% dist_long
# This can later be used to making a network plot based on the distances.
```

duplicate_leaf	<i>Duplicate a leaf X times</i>
----------------	---------------------------------

Description

Duplicates a leaf in a tree. Useful for non-parametric bootstrapping trees since it emulates what would have happened if the tree was constructed based on a row-sample with replacements from the original data matrix.

Usage

```
duplicate_leaf(dend, leaf_label, times, fix_members = TRUE,
  fix_order = TRUE, fix_midpoint = TRUE, ...)
```

Arguments

dend	a dendrogram object
leaf_label	the label of the leaf to replicate.
times	the number of times we will have this leaf after replication
fix_members	logical (TRUE). Fix the number of members in attr using fix_members_attr.dendrogram
fix_order	logical (TRUE). Fix the leaves order
fix_midpoint	logical (TRUE). Fix the midpoint value. If TRUE, it overrides "fix_members" and turns it into TRUE (since it must have a correct number of members in order to work). values using rank_order.dendrogram
...	not used

Value

A dendrogram, after duplicating one of its leaves.

Examples

```
## Not run:
# define dendrogram object to play with:
dend <- USArrests[1:3,] %>% dist %>% hclust(method = "ave") %>% as.dendrogram
plot(dend)
duplicate_leaf(dend, "Alaska", 3)
duplicate_leaf(dend, "Arizona", 2, fix_members =FALSE, fix_order = FALSE)
plot(duplicate_leaf(dend, "Alaska", 2))
plot(duplicate_leaf(dend, "Alaska", 4))
plot(duplicate_leaf(dend, "Arizona", 2))
plot(duplicate_leaf(dend, "Arizona", 4))

## End(Not run)
```

entanglement

Measures entanglement between two trees

Description

Measures the entanglement between two trees. Entanglement is a measure between 1 (full entanglement) and 0 (no entanglement). The exact behavior of the number depends on the L norm which is chosen.

Usage

```
entanglement(tree1, ...)
```

```
## S3 method for class 'dendrogram'
```

```
entanglement(tree1, tree2, L = 1.5, leaves_matching_method = c("labels", "order"),...)
```

```
## S3 method for class 'dendlist'
entanglement(tree1, which = c(1L,2L), ...)

## S3 method for class 'hclust'
entanglement(tree1, tree2, ...)

## S3 method for class 'phylo'
entanglement(tree1, tree2, ...)
```

Arguments

tree1	a tree object (of class dendrogram/hclust/phylo).
...	not used
tree2	a tree object (of class dendrogram/hclust/phylo).
which	an integer vector of length 2, indicating which of the trees in a dendlist object should have their entanglement calculated
L	the distance norm to use for measuring the distance between the two trees. It can be any positive number, often one will want to use 0, 1, 1.5, 2 (see 'details' for more).
leaves_matching_method	<p>a character scalar, either "order" or "labels" (default) . If using "labels", then we use the labels for matching the leaves order value (safer).</p> <p>And if "order" then we use the old leaves order value for matching the leaves order value.</p> <p>Using "order" is faster, but "labels" is safer. "order" will assume that the original two trees had their labels and order values MATCHED.</p> <p>Hence, it is best to make sure that the trees used here have the same labels and the SAME values matched to these values - and then use "order" (for fastest results).</p>

Details

Entanglement is measured by giving the left tree's labels the values of 1 till tree size, and then match these numbers with the right tree. Now, entanglement is the L norm distance between these two vectors. That is, we take the sum of the absolute difference (each one in the power of L). e.g: $\sum(\text{abs}(x-y)**L)$. And this is divided by the "worst case" entanglement level (e.g: when the right tree is the complete reverse of the left tree).

L tells us which penalty level we are at (L0, L1, L2, partial L's etc). $L > 1$ means that we give a big penalty for sharp angles. While $L > 0$ means that any time something is not a straight horizontal line, it gets a large penalty. If $L = 0.1$ it means that we much prefer straight lines over non straight lines

Value

The number of leaves in the tree

See Also

[tanglegram](#), [match_order_by_labels](#).

Examples

```
## Not run:
dend1 <- iris[,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[,-5] %>% dist %>% hclust("sin") %>% as.dendrogram
dend12 <- dendlist(dend1, dend2)
tanglegram(dend12)

entanglement(dend12)
entanglement(dend12, L = 0)
entanglement(dend12, L = 0.25)
entanglement(dend1,dend2, L = 0) # 1
entanglement(dend1,dend2, L = 0.25) # 0.97
entanglement(dend1,dend2, L = 1) # 0.93
entanglement(dend1,dend2, L = 2) # 0.88

# a somewhat better tanglegram
tanglegram(sort(dend1),sort(dend2))
# and also a MUCH better entanglement
entanglement(sort(dend1),sort(dend2), L=1.5) # 0.0811
# but not that much, for L=0.25
entanglement(sort(dend1),sort(dend2), L=.25) # 0.579

#####
#####
#####
# messing up the order of leaves is dangerous:
entanglement(dend1 , dend2, 1.5, "order") # 0.91
order.dendrogram(dend2) <- seq_len(nleaves(dend2))
# this 0.95 number is NO LONGER correct!!
entanglement(dend1 , dend2, 1.5, "order") # 0.95
# but if we use the "labels" method - we still get the correct number:
entanglement(dend1 , dend2, 1.5, "labels") # 0.91

# however, we can fix our dend2, as follows:
dend2 <- match_order_by_labels(dend2, dend1)
# Now that labels and order are matched - entanglement is back at working fine:
entanglement(dend1 , dend2, 1.5, "order") # 0.91

## End(Not run)
```

fac2num	<i>Turns a factor into a number</i>
---------	-------------------------------------

Description

Turning a factor into a number is not trivial. Using `as.numeric` would only return to us the indicator numbers and NOT the factor levels turned into a number. `fac2num` simply turns a factor into a number, as we often need.

Usage

```
fac2num(x, force_integer = FALSE, keep_names = TRUE, ...)
```

Arguments

<code>x</code>	an object.
<code>force_integer</code>	logical (FALSE). Should the values returned be integers?
<code>keep_names</code>	logical (TRUE). Should the values returned keep the names of the original vector?
<code>...</code>	ignored.

Value

if `x` is an object - it returns logical - is the object of class `dendrogram`.

Examples

```
x <- factor(3:5)
as.numeric(x) # 1 2 3
fac2num(x) # 3 4 5
```

fix_members_attr.dendrogram	<i>Fix members attr in a dendrogram</i>
-----------------------------	---

Description

Fix members attr in a dendrogram after (for example), the tree was pruned or manipulated.

Usage

```
fix_members_attr.dendrogram(dend, ...)
```

Arguments

dend	a dendrogram object
...	not used

Value

A dendrogram, after adjusting the members attr in all of its nodes.

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)
# plot(dend)
# prune one leaf
dend[[2]] <- dend[[2]][[1]]
# plot(dend)
dend # but it is NO LONGER true that it has 3 members total!
fix_members_attr.dendrogram(dend) # it now knows it has only 2 members :)

hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

identical(prune_leaf(dend , "Alaska"), fix_members_attr.dendrogram(prune_leaf(dend , "Alaska")))
str(unclass(prune_leaf(dend , "Alaska")))
str(unclass(fix_members_attr.dendrogram(prune_leaf(dend , "Alaska"))))
```

flatten.dendrogram *Flatten the branches of a dendrogram's root*

Description

The function makes sure the two branches of the root of a dendrogram will have the same height. The user can choose how to decide which height to use.

Usage

```
flatten.dendrogram(dend, FUN = max, new_height, ...)
```

Arguments

dend	dendrogram object
FUN	how to choose the new height of both branches (defaults to taking the max between the two)
new_height	overrides FUN, and sets the new height of the two branches manually
...	passed on (not used)

Value

A dendrogram with both of the root's branches of the same height

Examples

```
hc <- hclust(dist(USArrests[2:9,]), "com")
dend <- as.dendrogram(hc)
attr(dend[[1]], "height") <- 150 # make the height un-equal

par(mfrow = c(1,2))
plot(dend, main = "original tree")
plot(flatten.dendrogram(dend), main = "Raised tree")
```

flip_leaves

Flip leaves

Description

Rotate a branch in a tree so that the locations of two bundles of leaves are flipped.

Usage

```
flip_leaves(dend, leaves1, leaves2, ...)
```

Arguments

dend	a dendrogram object
leaves1	a vector of leaves order value to flip.
leaves2	a (second) vector of leaves order value to flip.
...	not used

Details

This function is based on a bunch of string manipulation functions. There may be a smarter/better way for doing it...

Value

A dendrogram object with flipped leaves.

See Also

[tanglegram](#), [match_order_by_labels](#), [entanglement](#).

Examples

```
## Not run:
dend1 <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram
dend2 <- flip_leaves(dend1, c(3,5), c(1,2))
tanglegram(dend1,dend2)
entanglement(dend1,dend2, L = 2) # 0.4

## End(Not run)
```

FM_index

*Calculating Fowlkes-Mallows Index***Description**

Calculating Fowlkes-Mallows index.

As opposed to the [FM_index_profdpm](#) function, the `FM_index_R` function also calculates the expectancy and variance of the FM Index under the null hypothesis of no relation.

Usage

```
FM_index(A1_clusters, A2_clusters, include_EV = TRUE,
         assume_sorted_vectors = FALSE, warn = dendextend_options("warn"), ...)
```

Arguments

<code>A1_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A1. These are often obtained by using some k cut on a dendrogram.
<code>A2_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A2. These are often obtained by using some k cut on a dendrogram.
<code>include_EV</code>	logical (TRUE). Should we calculate expectancy and variance of the FM Index under null hypothesis of no relation between the clusterings? If TRUE (Default) - then the FM_index_R function, else (FALSE) we use the (faster) FM_index_profdpm function.
<code>assume_sorted_vectors</code>	logical (FALSE). Can we assume to two group vectors are sorted so that they have the same order of items? IF FALSE (default), then the vectors will be sorted based on their name attribute.
<code>warn</code>	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
<code>...</code>	Ignored (passed to <code>FM_index_R/FM_index_profdpm</code>).

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

Value

The Fowlkes-Mallows index between two vectors of clustering groups.

Includes the attributes E_FM and V_FM for the relevant expectancy and variance under the null hypothesis of no-relation.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[cor_bakers_gamma](#), [FM_index_profdp](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# dend1 <- as.dendrogram(hc1)
# dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

FM_index(cutree(hc1, k=3), cutree(hc1, k=3)) # 1 with EV
FM_index(cutree(hc1, k=3), cutree(hc1, k=3), include_EV= FALSE) # 1

# checking speed gains
library(microbenchmark)
microbenchmark(FM_index(cutree(hc1, k=3), cutree(hc1, k=3)),
               FM_index(cutree(hc1, k=3), cutree(hc1, k=3),
                         include_EV= FALSE),
               FM_index(cutree(hc1, k=3), cutree(hc1, k=3),
                         include_EV= TRUE, assume_sorted_vectors=TRUE),
               FM_index(cutree(hc1, k=3), cutree(hc1, k=3),
                         include_EV= FALSE, assume_sorted_vectors=TRUE)
               )

# C code is 1.2-1.3 times faster.
```

```

set.seed(1341)
FM_index(cutree(hc1, k=3), sample(cutree(hc1, k=3)),
  assume_sorted_vectors =TRUE) # 0.38037
FM_index(cutree(hc1, k=3), sample(cutree(hc1, k=3)),
  assume_sorted_vectors =FALSE) # 1 again :)
FM_index(cutree(hc1, k=3), cutree(hc2, k=3)) # 0.8059
FM_index(cutree(hc1, k=30), cutree(hc2, k=30)) # 0.4529

fo <- function(k) FM_index(cutree(hc1, k), cutree(hc2, k))
lapply(1:4, fo)
ks <- 1:150
plot(sapply(ks, fo)~ ks, type = "b", main = "Bk plot for the iris dataset")

## End(Not run)

```

FM_index_permutation *Calculating Fowlkes-Mallows Index under H0*

Description

Calculating Fowlkes-Mallows index under the null hypothesis of no relation between the clusterings (random order of the items labels).

Usage

```
FM_index_permutation(A1_clusters, A2_clusters,
  warn = dendextend_options("warn"), ...)
```

Arguments

A1_clusters	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A1. These are often obtained by using some k cut on a dendrogram.
A2_clusters	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A2. These are often obtained by using some k cut on a dendrogram.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	Ignored (passed to FM_index_R/FM_index_profdpn).

Value

The Fowlkes-Mallows index between two vectors of clustering groups. Under H0. (a double without attr)

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[cor_bakers_gamma](#), [FM_index_profdp](#), [FM_index_R](#), [FM_index](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# dend1 <- as.dendrogram(hc1)
# dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

# small k
A1_clusters <- cutree(hc1, k=3) # will give a right tailed distribution
# large k
A1_clusters <- cutree(hc1, k=50) # will give a discrete distribution
# "medium" k
A1_clusters <- cutree(hc1, k=25) # gives almost the normal distribution!
A2_clusters <- A1_clusters

R <- 10000
set.seed(414130)
FM_index_H0 <- replicate(R, FM_index_permutation(A1_clusters, A2_clusters)) # can take 10 sec
plot(density(FM_index_H0), main = "FM Index distribution under H0\n (10000 permutation)")
abline(v = mean(FM_index_H0), col = 1, lty = 2)
# The permutation distribution is with a heavy right tail:
library(psych)
skew(FM_index_H0) # 1.254
kurtosi(FM_index_H0) # 2.5427

mean(FM_index_H0); var(FM_index_H0)
the_FM_index <- FM_index(A1_clusters, A2_clusters)
the_FM_index
our_dnorm <- function(x) {
  dnorm(x, mean = attr(the_FM_index, "E_FM"),
        sd = sqrt(attr(the_FM_index, "V_FM")))
}
# our_dnorm(0.35)
curve(our_dnorm,
      col = 4,
      from = -1,to=1,n=R,add = TRUE)
abline(v = attr(the_FM_index, "E_FM"), col = 4, lty = 2)
```

```
legend("topright", legend = c("asymptotic", "permutation"), fill = c(4,1))

## End(Not run)
```

 FM_index_profdpm

Calculating Fowlkes-Mallows index using the profdpm R package

Description

Calculating Fowlkes-Mallows index using the `pci` function from the `profdpm` R package. This function uses C code (thanks to Matthew Shotwell's work) and is a bit faster than the R code (from my simple tests - it is about 1.2-1.3 times faster - which is not much but it might be useful).

As opposed to the `FM_index_R` function, the `FM_index_profdpm` function does NOT calculate the expectancy or the variance of the FM Index under the null hypothesis of no relation.

This function also allows us to compare our calculations with an independent writing of a function calculating the same statistic.

Usage

```
FM_index_profdpm(A1_clusters, A2_clusters, assume_sorted_vectors = FALSE,
  warn = dendextend_options("warn"), ...)
```

Arguments

<code>A1_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A1. These are often obtained by using some <code>k</code> cut on a dendrogram.
<code>A2_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A2. These are often obtained by using some <code>k</code> cut on a dendrogram.
<code>assume_sorted_vectors</code>	logical (FALSE). Can we assume to two group vectors are sorted so that they have the same order of items? IF FALSE (default), then the vectors will be sorted based on their name attribute.
<code>warn</code>	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
<code>...</code>	Ignored.

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

Value

The Fowlkes-Mallows index between two vectors of clustering groups.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

Shotwell, Matthew S. "profdpm: An R Package for MAP Estimation in a Class of Conjugate Product Partition Models." *Journal of Statistical Software* 53: 1-18.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[cor_bakers_gamma](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# dend1 <- as.dendrogram(hc1)
# dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

FM_index_profdpm(cutree(hc1, k=3), cutree(hc1, k=3)) # 1
set.seed(1341)
FM_index_profdpm(cutree(hc1, k=3), sample(cutree(hc1, k=3)),
  assume_sorted_vectors =TRUE) # 0.38037
FM_index_profdpm(cutree(hc1, k=3), sample(cutree(hc1, k=3)),
  assume_sorted_vectors =FALSE) # 1 again :)
FM_index_profdpm(cutree(hc1, k=3), cutree(hc2, k=3)) # 0.8059
FM_index_profdpm(cutree(hc1, k=30), cutree(hc2, k=30)) # 0.4529

fo <- function(k) FM_index_profdpm(cutree(hc1, k), cutree(hc2, k))
lapply(1:4, fo)
ks <- 1:150
plot(sapply(ks, fo)~ ks, type = "b", main = "Bk plot for the iris dataset")

## End(Not run)
```

 FM_index_R

Calculating Fowlkes-Mallows index in R

Description

Calculating Fowlkes-Mallows index.

As opposed to the [FM_index_profdep](#) function, the `FM_index_R` function also calculates the expectancy and variance of the FM Index under the null hypothesis of no relation.

Usage

```
FM_index_R(A1_clusters, A2_clusters, assume_sorted_vectors = FALSE,
           warn = dendextend_options("warn"), ...)
```

Arguments

<code>A1_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A1. These are often obtained by using some k cut on a dendrogram.
<code>A2_clusters</code>	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A2. These are often obtained by using some k cut on a dendrogram.
<code>assume_sorted_vectors</code>	logical (FALSE). Can we assume to two group vectors are sorter so that they have the same order of items? IF FALSE (default), then the vectors will be sorted based on their name attribute.
<code>warn</code>	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
<code>...</code>	Ignored.

Details

From Wikipedia:

Fowlkes-Mallows index (see references) is an external evaluation method that is used to determine the similarity between two clusterings (clusters obtained after a clustering algorithm). This measure of similarity could be either between two hierarchical clusterings or a clustering and a benchmark classification. A higher the value for the Fowlkes-Mallows index indicates a greater similarity between the clusters and the benchmark classifications.

Value

The Fowlkes-Mallows index between two vectors of clustering groups.

Includes the attributes `E_FM` and `V_FM` for the relevant expectancy and variance under the null hypothesis of no-relation.

References

Fowlkes, E. B.; Mallows, C. L. (1 September 1983). "A Method for Comparing Two Hierarchical Clusterings". *Journal of the American Statistical Association* 78 (383): 553.

http://en.wikipedia.org/wiki/Fowlkes-Mallows_index

See Also

[cor_bakers_gamma](#), [FM_index_profdp](#)

Examples

```
## Not run:

set.seed(23235)
ss <- TRUE # sample(1:150, 10 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# dend1 <- as.dendrogram(hc1)
# dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

FM_index_R(cutree(hc1, k=3), cutree(hc1, k=3)) # 1
set.seed(1341)
FM_index_R(cutree(hc1, k=3), sample(cutree(hc1, k=3)), assume_sorted_vectors =TRUE) # 0.38037
FM_index_R(cutree(hc1, k=3), sample(cutree(hc1, k=3)), assume_sorted_vectors =FALSE) # 1 again :)
FM_index_R(cutree(hc1, k=3), cutree(hc2, k=3)) # 0.8059
FM_index_R(cutree(hc1, k=30), cutree(hc2, k=30)) # 0.4529

fo <- function(k) FM_index_R(cutree(hc1, k), cutree(hc2, k))
lapply(1:4, fo)
ks <- 1:150
plot(sapply(ks, fo)~ ks, type = "b", main = "Bk plot for the iris dataset")

clu_1 <- cutree(hc2, k = 100) # this is a lie - since this one is NOT well defined!
clu_2 <- cutree(as.dendrogram(hc2), k = 100) # We see that we get a vector of NAs for this...

FM_index_R(clu_1, clu_2) # NA

## End(Not run)
```

get_branches_heights *Get height attributes from a dendrogram*

Description

Get height attributes from a dendrogram

Usage

```
get_branches_heights(tree, sort = TRUE, decreasing = FALSE, ...)
```

Arguments

tree	a dendrogram.
sort	logical. Should the heights be sorted?
decreasing	logical. Should the sort be increasing or decreasing? Not available for partial sorting.
...	not used.

Value

a vector of the dendrogram's nodes heights (excluding leaves).

Examples

```
hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)
get_branches_heights(dend)

## Not run:
dat1 <- iris[1:150,-5]
dat1 <- rbind(dat1,dat1,dat1,dat1,dat1,dat1,dat1)
dend = as.dendrogram(hclust(dist(dat1)))
library(microbenchmark)
library(dendextendRcpp)
microbenchmark(
  dendextendRcpp::dendextendRcpp_get_branches_heights(dend),
  old_get_branches_heights(dend,sort=F)
)

## End(Not run)
```

get_childrens_heights *Get height attributes from a dendrogram's children*

Description

Get height attributes from a dendrogram's children

Usage

```
get_childrens_heights(dend, ...)
```

Arguments

dend a dendrogram.
 ... not used.

Value

a vector of the heights of a dendrogram's current node's (first level) children.

See Also

[get_branches_heights](#)

Examples

```
hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)
get_childrens_heights(dend)
```

get_leaves_attr *Get/set attributes of dendrogram's leaves*

Description

Get/set attributes of dendrogram's leaves

Usage

```
get_leaves_attr(object, attribute, simplify = TRUE, ...)
```

Arguments

object a dendrogram object
 attribute character scalar of the attribute (attr) we wish to get/set from the leaves
 simplify logical. If TRUE (default), then the return vector is after using unlist on it.
 ... not used

Value

A vector (or a list) with the dendrogram's leaves attribute

Source

Heavily inspired by the code in the function `labels.dendrogram`, so credit should go to Martin Maechler.

See Also

[get_nodes_attr](#), [nnodes](#), [nleaves](#), [assign_values_to_leaves_nodePar](#)

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

# get_leaves_attr(dend) # error :)
get_leaves_attr(dend, "label")
labels(dend, "label")
get_leaves_attr(dend, "height") # should be 0's
get_nodes_attr(dend, "height")

get_leaves_attr(dend, "nodePar")

get_leaves_attr(dend, "leaf") # should be TRUE's
get_nodes_attr(dend, "leaf") # contains NA's

get_leaves_attr(dend, "members") # should be 1's
get_nodes_attr(dend, "members") #

get_leaves_attr(dend, "members", simplify = FALSE) # should be 1's
```

get_leaves_nodePar *Get nodePar of dendrogram's leaves*

Description

Get nodePar of dendrogram's leaves

Usage

```
get_leaves_nodePar(object, simplify = FALSE, ...)
```

Arguments

object	a dendrogram object
simplify	logical (default is FALSE). If TRUE, then the return vector is after using unlist on it.
...	not used

Value

A list (or a vector) with the dendrogram's leaves nodePar attribute

See Also

[get_nodes_attr](#), [assign_values_to_leaves_nodePar](#), [labels_colors](#)

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

# get_leaves_attr(dend) # error :)
get_leaves_nodePar(dend)
labels_colors(dend) <- 1:3
get_leaves_nodePar(dend)

dend <- assign_values_to_leaves_nodePar(dend, 2, "lab.cex")
get_leaves_nodePar(dend)

plot(dend)
```

get_nodes_attr

Get attributes of dendrogram's nodes

Description

Allows easy access to attributes of branches and/or leaves, with option of returning a vector with/without NA's (for marking the missing attr value)

Usage

```
get_nodes_attr(object, attribute, id, include_leaves = TRUE,
  include_branches = TRUE, simplify = TRUE, na.rm = FALSE, ...)
```

Arguments

object	a dendrogram object
attribute	character scalar of the attribute (attr) we wish to get from the nodes
id	integer vector. If given - only the attr of these nodes id will be returned (via depth first search)
include_leaves	logical. Should leaves attributes be included as well?
include_branches	logical. Should non-leaf (branch node) attributes be included as well?
simplify	logical (default is TRUE). should the result be simplified to a vector (using simplify2array) if possible? If it is not possible it will return a matrix. When FALSE, a list is returned.
na.rm	logical. Should NA attributes be REMOVED from the resulting vector?
...	not used

Value

A vector with the dendrogram's nodes attribute. If an attribute is missing from some nodes, it will return NA in that vector.

Source

Heavily inspired by the code in the function `labels.dendrogram`, so credit should go to Martin Maechler.

See Also

[get_leaves_attr](#), [nnodes](#), [nleaves](#)

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

# get_leaves_attr(dend) # error :)
get_leaves_attr(dend, "label")
labels(dend, "label")
get_leaves_attr(dend, "height") # should be 0's
get_nodes_attr(dend, "height")

get_leaves_attr(dend, "leaf") # should be TRUE's
get_nodes_attr(dend, "leaf") # contains NA's

get_leaves_attr(dend, "members") # should be 1's
get_nodes_attr(dend, "members", include_branches = FALSE, na.rm = TRUE) #
get_nodes_attr(dend, "members") #
get_nodes_attr(dend, "members", simplify = FALSE)
get_nodes_attr(dend, "members", include_leaves = FALSE, na.rm = TRUE) #

get_nodes_attr(dend, "members", id = c(1,3), simplify = FALSE)
get_nodes_attr(dend, "members", id = c(1,3)) #

hang_dend <- hang.dendrogram(dend)
get_leaves_attr(hang_dend, "height") # no longer 0!
get_nodes_attr(hang_dend, "height") # does not include any 0s!

# does not include leaves values:
get_nodes_attr(hang_dend, "height", include_leaves = FALSE)
# remove leaves values all together:
get_nodes_attr(hang_dend, "height", include_leaves = FALSE, na.rm = TRUE)

## Not run:
```

```

library(microbenchmark)
# get_leaves_attr is twice faster than get_nodes_attr
microbenchmark(  get_leaves_attr(dend, "members"), # should be 1's
                  get_nodes_attr(dend, "members", include_branches = FALSE, na.rm = TRUE)
                )

## End(Not run)

```

get_nodes_xy	<i>Get the x-y coordiantes of a dendrogram's nodes</i>
--------------	--

Description

Get the x-y coordiantes of a dendrogram's nodes

Usage

```
get_nodes_xy(x, type = c("rectangle", "triangle"), center = FALSE,
             horiz = FALSE, ...)
```

Arguments

x	a dendrogram object
type	type of plot.
center	logical; if TRUE, nodes are plotted centered with respect to the leaves in the branch. Otherwise (default), plot them in the middle of all direct child nodes.
horiz	logical indicating if the dendrogram should be drawn horizontally or not.
...	not used

Value

A 2-dimensional matrix, with rows as the number of nodes, and the first column is the x location, while the second is the y location.

Source

This is a striped down version of the function [plot.dendrogram](#). It performs (almost) the same task, only it does not do any plotting but it does save the x-y coordiantes of the nodes.

See Also

[get_nodes_attr](#), [nnodes](#), [nleaves](#)

Examples

```
## Not run:

# If we would like to see the numbers from plot:
# ?getOption("verbose")
# options(verbose=TRUE)
# options(verbose=FALSE)

# -----
# Draw a depth first search illustration
# -----

dend <- 1:5 %>% dist %>% hclust %>% as.dendrogram
get_nodes_xy(dend)

# polygon(get_nodes_xy(dend), col = 2)
plot(dend,
      leaflab = "none",
      main = "Depth-first search in a dendrogram")
xy <- get_nodes_xy(dend)
for(i in 1:(nrow(xy)-1)) {
  arrows(xy[i,1], xy[i,2], angle = 17,
        length = .5,
        xy[i+1,1], xy[i+1,2],
        lty = 1, col = 3, lwd = 1.5)
}
points(xy, pch = 19, cex = 4)
text(xy, labels = 1:nnodes(dend), cex = 1.2, col = "white", adj = c(0.4,0.4))

## End(Not run)
```

```
get_root_branches_attr
```

get attributes from the dendrogram's root(!) branches

Description

get attributes from the dendrogram's root(!) branches

Usage

```
get_root_branches_attr(dend, the_attr, warn = dendextend_options("warn"), ...)
```

Arguments

dend	dendrogram object
the_attr	the attribute to get from the branches (for example "height")

warn logical (default from `dendextend_options("warn")` is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. Should a warning be printed when the function is used on an object which is NOT a dendrogram.

... passed on to `attr`

Value

The attributes of the branches (often two) of the dendrogram's root

See Also

[attr](#)

Examples

```
hc <- hclust(dist(USArrests[2:9,]), "com")
dend <- as.dendrogram(hc)

get_root_branches_attr(dend, "height") # 0.00000 71.96247
# plot(dend)
str(dend, 2)
```

ggdend

Creates dendrogram plot using ggplot.

Description

Several functions for creating a dendrogram plot using `ggplot2`. The core process is to transform a dendrogram into a `ggdend` object using `as.ggdend`, and then plot it using `ggplot`. These two steps can be done in one command with either the function `ggplot` or `ggdend`.

The reason we want to have `as.ggdend` (and not only `ggplot.dendrogram`), is (1) so that you could create your own mapping of `ggdend` and, (2) since `as.ggdend` might be slow for large trees, it is probably better to be able to run it only once for such cases.

A `ggdend` class object is a list with 3 components: `segments`, `labels`, `nodes`. Each one contains the graphical parameters from the original dendrogram, but in a tabular form that can be used by `ggplot2+geom_segment+geom_text` to create a dendrogram plot.

Usage

```
as.ggdend(dend, ...)

prepare.ggdend(data, ...)

## S3 method for class 'dendrogram'
as.ggdend(dend,
          type = c("rectangle", "triangle"), edge.root = FALSE, ...)
```



```
ggplot.ggdend(data, segments = TRUE,
              labels = TRUE, horiz = FALSE, theme = theme_dendro(), ...)

ggplot.dendrogram(data, ...)
```

Arguments

...	mostly ignored.
dend	a dendrogram tree (to be turned into a ggdend object)
type	The type of plot, indicating the shape of the dendrogram. "rectangle" will draw rectangular lines, while "triangle" will draw triangular lines.
edge.root	currently ignored. One day it might do the following: logical; if true, draw an edge to the root node.
data	a ggdend class object.
segments	a logical (TRUE) if to plot the segments (branches).
labels	a logical (TRUE) if to plot the labels.
horiz	a logical (TRUE) indicating if the dendrogram should be drawn horizontally or not.
theme	the ggplot2 theme to use (default is theme_dendro , can also be NULL for the default ggplot2 theme)

Details

`prepare.ggdend` is used by `plot.ggdend` to take the ggdend object and prepare it for plotting. This is because the defaults of various parameters in `dendrogram`'s are not always stored in the object itself, but are built-in into the `plot.dendrogram` function. For example, the color of the labels is not (by default) specified in the dendrogram (only if we change it from black to something else). Hence, when taking the object into a different plotting engine (say ggplot2), we want to prepare the object by filling-in various defaults. This function is automatically invoked within the `plot.ggdend` function. You would probably use it only if you'd wish to build your own ggplot2 mapping.

Value

- `as.ggdend` - returns an object of class ggdend which is a list with 3 components: segments, labels, nodes. Each one contains the graphical parameters from the original dendrogram, but in a tabular form that can be used by `ggplot2+geom_segment+geom_text` to create a dendrogram plot.
- `prepare.ggdend` - a ggdend object (after filling it with various default values)
- `ggplot.ggdend` - a [ggplot](#) object

Author(s)

Tal Galili, using code modified from Andrie de Vries

Source

These are extended versions of the functions `ggdendrogram`, `dendro_data` (and the hidden `dendrogram_data`) from Andrie de Vries's `ggdendro` package. The motivation for this fork is the need to add more graphical parameters to the plotted tree. This required a strong mixer of functions from `ggdendro` and `dendextend` (to the point that it seemed better to just fork the code into its current form)

See Also

[dendrogram](#), [get_nodes_attr](#), [get_leaves_nodePar](#), [ggplot](#), [ggdendrogram](#), [dendro_data](#),

Examples

```
## Not run:

library(dendextend)
# library(ggdendro)
# Create a complex dend:
dend <- iris[1:30,-5] %>% dist %>% hclust %>% as.dendrogram %>%
  set("branches_k_color", k=3) %>% set("branches_lwd", c(1.5,1,1.5)) %>%
  set("branches_lty", c(1,1,3,1,1,2)) %>%
  set("labels_colors") %>% set("labels_cex", c(.9,1.2))
# plot the dend in usual "base" plotting engine:
plot(dend)
# Now let's do it in ggplot2 :)
ggd1 <- as.ggdend(dend)
library(ggplot2)
ggplot(ggd1) # reproducing the above plot in ggplot2 :)
ggplot(ggd1, horiz = TRUE) # horiz plot in ggplot2
# Adding some extra spice to it...
# creating a radial plot:
ggplot(ggd1) + scale_y_reverse(expand = c(0.2, 0)) + coord_polar(theta="x")
# The text doesn't look so great, so let's remove it:
ggplot(ggd1, labels = FALSE) + scale_y_reverse(expand = c(0.2, 0)) + coord_polar(theta="x")

# This can now be sent to plot.ly - which adds zoom-in abilities, and more.
# Here is how it might look like: https://plot.ly/~talgalili/6/y-vs-x/

## Quick guide:
# install.packages("devtools")
# library("devtools")
# devtools::install_github("ropensci/plotly")
# library(plotly)
# set_credentials_file(...)
# you'll need to get it from here: https://plot.ly/ggplot2/getting-started/

# ggplot(ggd1)
# py <- plotly()
# py$ggplotly()

# And you'll get something like this: https://plot.ly/~talgalili/6/y-vs-x/
```

```
# Another example: https://plot.ly/ggplot2/

## End(Not run)
```

hang.dendrogram	<i>Hang dendrogram leaves</i>
-----------------	-------------------------------

Description

Adjust the height attr in all of the dendrogram leaves so that the tree will hang. This is similar to `as.dendrogram(hclust, hang=0.1)` Only that it now works on other object than `hclust` turned into a dendrogram. For example, this allows us to hang non-binary trees.

Usage

```
hang.dendrogram(dend, hang = 0.1, hang_height, ...)
```

Arguments

dend	a dendrogram object
hang	The fraction of the plot height by which labels should hang below the rest of the plot. A negative value will cause the labels to hang down from 0.
hang_height	is missing, then using "hang". If a number is given, it overrides "hang" (except if "hang" is negative)
...	not used

Value

A dendrogram, after adjusting the height attr in all of its leaves, so that the tree will hang.

Source

Noticing that `as.dendrogram` has a "hang" parameter was thanks to Enrique Ramos's answer here: <http://stackoverflow.com/questions/17088136/plot-horizontal-dendrogram-with-hanging-leaves-r>

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)

par(mfrow = c(1,2))
plot(hang.dendrogram(dend))
plot(hc)
# identical(as.dendrogram(hc, hang = 0.1), hang.dendrogram(dend, hang = 0.1))
# TRUE!!
```

```

par(mfrow = c(1,4))

plot(dend)
plot(hang.dendrogram(dend, hang = 0.1))
plot(hang.dendrogram(dend, hang = 0))
plot(hang.dendrogram(dend, hang = -0.1))

par(mfrow = c(1,1))
plot(hang.dendrogram(dend), horiz = TRUE)

```

heights_per_k.dendrogram

Which height will result in which k for a dendrogram

Description

Which height will result in which k for a dendrogram

Usage

```
heights_per_k.dendrogram(tree, ...)
```

Arguments

tree	a dendrogram.
...	not used.

Value

a vector of heights, with its names being the k clusters that will result for cutting the dendrogram at each height.

Examples

```

## Not run:
hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)
heights_per_k.dendrogram(dend)
##      1      2      3      4
##86.47086 68.84745 45.98871 28.36531

cutree(hc, h = 68.8) # and indeed we get 2 clusters

unbranch_dend <- unbranch(dend,2)
plot(unbranch_dend)
heights_per_k.dendrogram(unbranch_dend)
#1      3      4
#97.90023 57.41808 16.93594

```

```

# we do NOT have a height for k=2 because of the tree's structure.

library(microbenchmark)
dend = as.dendrogram(hclust(dist(iris[1:150,-5])))
dend = as.dendrogram(hclust(dist(iris[1:30,-5])))
dend = as.dendrogram(hclust(dist(iris[1:3,-5])))
microbenchmark(
  # dendextendRcpp::heights_per_k.dendrogram(dend),
  dendextendRcpp::dendextendRcpp_heights_per_k.dendrogram(dend),
  dendextendRcpp::old_heights_per_k.dendrogram(dend)
)
# improvement is 10 times faster (in Rcpp) for a tree of size 3
# 76 times faster for a tree of size 30
# And:
# 134 times faster for a tree of size 150!!

## End(Not run)

```

highlight_distinct_edges

Highlight distinct edges in a tree (compared to another one)

Description

Highlight distinct edges in a tree (compared to another one) by changing the branches' color, line width, or line type.

This function enables this feature in [dend_diff](#) and [tanglegram](#)

Usage

```

highlight_distinct_edges(x, ...)

## S3 method for class 'dendrogram'
highlight_distinct_edges(x,
  y,
  value = 2,
  edgePar = c("col", "lty", "lwd"),
  ...)

## S3 method for class 'dendlist'
highlight_distinct_edges(x, ..., which)

```

Arguments

x	a dendrogram or dendlist to find unique edges in (to highlight)
...	Ignored.
y	a dendrogram to compare with

value	a new value scalar for the edgePar attribute.
edgePar	a character indicating the value inside edgePar to adjust. Can be either "col", "lty", or "lwd".
which	an integer vector indicating, in the case "x" is a dendlist, on which of the trees should the modification be performed. If missing - the change will be performed on all of objects in the dendlist.

Value

A dendrogram with modified edges - the distinct ones are changed (color, line width, or line type)

See Also

[distinct_edges](#), [highlight_distinct_edges](#), [dist.dendlist](#), [tanglegram](#) [assign_values_to_branches_edgePar](#), [distinct.edges](#),

Examples

```
x <- 1:5 %>% dist %>% hclust %>% as.dendrogram
y <- set(x, "labels", 5:1)
distinct_edges(x, y)
distinct_edges(y, x)

par(mfrow = c(1,2))
plot(highlight_distinct_edges(x, y))
plot(y)

# tanglegram(highlight_distinct_edges(x, y),y)
# dend_diff(x, y)

## Not run:

# using highlight_distinct_edges combined with dendlist and set
# to clearly highlight "stable" branches.
data(iris); ss <- c(1:5, 51:55, 101:105)
iris1 <- iris[ss,-5] %>% dist %>% hclust(method = "single") %>% as.dendrogram
iris2 <- iris[ss,-5] %>% dist %>% hclust(method = "complete") %>% as.dendrogram
iris12 <- dendlist(iris1, iris2) %>% set("branches_k_color",k=3) %>%
  set("branches_lwd", 3) %>% highlight_distinct_edges(value = 1, edgePar = "lwd")
iris12 %>% untangle(method = "step2side") %>%
tanglegram(sub="Iris dataset", main_left = "'single' clustering",
main_right = "'complete' clustering")

## End(Not run)
```

identify.dendrogram *Identify Clusters in a Dendrogram (not hclust)*

Description

Just like [identify.hclust](#): reads the position of the graphics pointer when the (first) mouse button is pressed. It then cuts the tree at the vertical position of the pointer and highlights the cluster containing the horizontal position of the pointer. Optionally a function is applied to the index of data points contained in the cluster.

Usage

```
## S3 method for class 'dendrogram'
identify(x, FUN = NULL, N = 20, MAXCLUSTER,
        DEV.FUN = NULL, horiz = FALSE, ...)
```

Arguments

x	a dendrogram object.
FUN	(optional) function to be applied to the index numbers of the data points in a cluster (see 'Details' below).
N	the maximum number of clusters to be identified.
MAXCLUSTER	the maximum number of clusters that can be produced by a cut (limits the effective vertical range of the pointer).
DEV.FUN	(optional) integer scalar. If specified, the corresponding graphics device is made active before FUN is applied.
horiz	logical (FALSE), indicating if the rectangles should be drawn horizontally or not (for when using <code>plot(dend, horiz = TRUE)</code>).
...	further arguments to FUN.

Details

By default clusters can be identified using the mouse and an invisible list of indices of the respective data points is returned. If FUN is not NULL, then the index vector of data points is passed to this function as first argument, see the examples below. The active graphics device for FUN can be specified using DEV.FUN. The identification process is terminated by pressing any mouse button other than the first, see also [identify](#).

Value

(Invisibly) returns a list where each element contains a vector of data points contained in the respective cluster.

Source

This function is based on [identify.hclust](#), with slight modifications to have it work with a dendrogram, as well as adding "horiz"

See Also

[identify.hclust](#), [rect.hclust](#), [order.dendrogram](#), [cutree.dendrogram](#)

Examples

```
## Not run:
set.seed(23235)
ss <- sample(1:150, 10 )
hc <- iris[ss,-5] %>% dist %>% hclust
dend <- hc %>% as.dendrogram

plot(dend)
identify.dendrogram(dend)

## End(Not run)
```

intersect_trees

Intersect trees

Description

Return two trees after pruning them so that the only leaves left are the intersection of their labels.

Usage

```
intersect_trees(x1, x2, warn = dendextend_options("warn"), ...)
```

Arguments

x1	tree object (dendrogram/hclust/phylo)
x2	tree object (dendrogram/hclust/phylo)
warn	logical (default from <code>dendextend_options("warn")</code> is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. Should a warning be issued if there was a need to perform intersaction.
...	passed on

Value

A [dendlist](#) with two pruned trees

See Also

[prune](#), [intersect](#), [labels](#)

Examples

```
hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)
labels(dend) <- 1:5
dend1 <- prune(dend, 1)
dend2 <- prune(dend, 5)
intersect_dend <- intersect_trees(dend1, dend2)

layout(matrix(c(1,1,2,3,4,5), 3,2, byrow=TRUE))
plot(dend, main = "Original tree")
plot(dend1, main = "Tree 1:\n original with label 1 pruned");
  plot(dend2, main = "Tree 2:\n original with label 2 pruned")
plot(intersect_dend[[1]],
      main = "Tree 1 pruned
with the labels that intersected with those of Tree 2")
plot(intersect_dend[[2]],
      main = "Tree 2 pruned
with the labels that intersected with those of Tree 1")
```

is.dendlist

Checks if an object is of class dendlist

Description

Checks if an object is of class dendlist

Usage

```
is.dendlist(x)
```

Arguments

x whatever object to check

Value

logical

Examples

```
# TRUE:
is.dendlist(dendlist())
# FALSE
is.dendlist(1)
```

is.dendrogram *Is the object of class dendrogram*

Description

Is the object of class dendrogram

Usage

```
is.dendrogram(x)
```

Arguments

x an object.

Value

logical - is the object of class dendrogram.

is.hclust *Is the object of class hclust*

Description

Is the object of class hclust

Usage

```
is.hclust(x)
```

Arguments

x an object.

Value

logical - is the object of class hclust.

is.natural.number *Check if numbers are natural*

Description

Vectorized function for checking if numbers are natural or not. Helps in checking if a vector is of type "order".

Usage

```
is.natural.number(x, tol = .Machine$double.eps^0.5, ...)
```

Arguments

x	a vector of numbers
tol	tolerance to floating point issues.
...	(not currently in use)

Value

logical - is the entered number natural or not.

Author(s)

Marco Gallotta (a.k.a: marcog), Tal Galili

Source

This function was written by marcog, as an answer to my question here: <http://stackoverflow.com/questions/4562257/what-is-the-fastest-way-to-check-if-a-number-is-a-positive-natural-number-in>

See Also

[is.numeric](#), [is.double](#), [is.integer](#)

Examples

```
is.natural.number(1) # is TRUE
(x <- seq(-1,5, by=0.5) )
is.natural.number( x )
# is.natural.number( "a" )
all(is.natural.number( x ))
```

is.phylo	<i>Is the object of class phylo</i>
----------	-------------------------------------

Description

Is the object of class phylo

Usage

```
is.phylo(x)
```

Arguments

x an object.

Value

logical - is the object of class phylo.

is_null_list	<i>Checks if the value is and empty list()</i>
--------------	--

Description

Checks if the value is and empty list()

Usage

```
is_null_list(x)
```

Arguments

x whatever object to check

Value

logical

Examples

```

# I can run this only if I'd make is_null_list exported
## Not run:
# TRUE:
is_null_list(list())
# FALSE
is_null_list(list(1))
is_null_list(1)

x <- list(1, list(), 123)
ss_list <- sapply(x, is_null_list)
x <- x[!ss_list]
x

x <- list(1, list(), 123)
ss_list <- sapply(x, is_null_list)
x <- list(list())
x

## End(Not run)

## Not run:
# error
is_null_list()

## End(Not run)

```

labels<-	<i>"label" assignment operator</i>
----------	------------------------------------

Description

"label" assignment operator for vectors, dendrogram, and hclust classes.
#'

Usage

```

labels(object, ...) <- value

## S3 method for class 'matrix'
labels(object, which = c("colnames", "rownames"), ...)

## S3 replacement method for class 'matrix'
labels(object, which = c("colnames", "rownames"), ...) <- value

## S3 replacement method for class 'dendrogram'
labels(object, ...) <- value

```

```
## S3 method for class 'hclust'
labels(object, order = TRUE,...)

## S3 replacement method for class 'hclust'
labels(object, ...) <- value

## S3 method for class 'phylo'
labels(object, ...)

## S3 replacement method for class 'phylo'
labels(object, ...) <- value

## S3 method for class 'hclust'
labels(object, order = TRUE, ...)

## S3 replacement method for class 'hclust'
labels(object, ...) <- value
```

Arguments

object	a variable name (possibly quoted) whose label are to be updated
...	parameters passed (not currently in use)
value	a value to be assigned to object's label
order	default is FALSE. Only relevant for extracting labels from an <code>hclust</code> object (with <code>labels.hclust</code>). Setting <code>order=TRUE</code> will return labels in their order in the dendrogram, instead of the original labels order retained from <code>object\$labels</code> - which usually corresponding to the row or column names of the <code>dist</code> object provided to the <code>hclust</code> function.
which	"colnames" or "rownames", to which of the two should labels refer to.

Details

```
#####
```

Value

The updated object

Author(s)

Gavin Simpson, Tal Galili (with some ideas from Gregory Jefferis's `dendroextras` package)

Source

The functions here are based on code by Gavin and kohske from (adopted to dendrogram by Tal Galili): <http://stackoverflow.com/questions/4614223/how-to-have-the-following-work-labelsx-some-value>. Also with some ideas from Gregory Jefferis's `dendroextras` package.

See Also[labels](#), [labels.matrix](#)**Examples**

```

x <- 1:3
labels(x)
labels(x) <- letters[1:3]
labels(x) # [1] "a" "b" "c"
x
# a b c
# 1 2 3

# get("labels<-")

#####
# Example for matrix objects

x <- matrix(1:9, 3,3)
labels(x)
x
labels(x) <- letters[1:3]
x
labels(x, which = "rownames") <- LETTERS[24:26]
x
# a b c
#X 1 4 7
#Y 2 5 8
#Z 3 6 9

#####
# Example for using the assignment with dendrogram and hclust objects:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

labels(hc) # "Arizona" "Alabama" "Alaska"
labels(hc) <- letters[1:3]
labels(hc) # "a" "b" "c"
labels(dend) # "Arizona" "Alabama" "Alaska"
labels(dend) <- letters[1:3]
labels(dend) # "a" "b" "c"
labels(dend) <- LETTERS[1:2] # will produce a warning
labels(dend) # "A" "B" "A"
labels(dend) <- LETTERS[4:6] # will replace the labels correctly
# (the fact the tree had duplicate labels will not cause a problem)
labels(dend) # "D" "E" "F"

```

Description

Retrieve/assign colors to the labels of a dendrogram

Usage

```
labels_colors(object, labels = TRUE, ...)
```

```
labels_colors(object, ...) <- value
```

Arguments

object	a dendrogram object
labels	Boolean (default is TRUE), should the returned vector of colors return with the leaves labels as names.
...	not used
value	a vector of colors to be used as new label's colors for the dendrogram

Value

A vector with the dendrogram's labels colors (or a colored dendrogram, in case assignment is used). The colors are labeled.

Source

Heavily inspired by the code in the example of [dendapply](#), so credit should go to Martin Maechler. I also implemented some ideas from Gregory Jefferis's dendroextras package (having the "names" of the returned vector be the labels).

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

# Defaults:
labels_colors(dend)
plot(dend)

# let's add some color:
labels_colors(dend) <- 2:4
labels_colors(dend)
plot(dend)

# doesn't work...
# get_nodes_attr(dend, "nodePar", include_branches = FALSE)

# changing color to black
labels_colors(dend) <- 1
labels_colors(dend)
```



```
plot(dend)

# removing color (and the nodePar completely - if it has no other attributed but lab.col)
labels_colors(dend) <- NULL
labels_colors(dend)
plot(dend)
```

ladderize*Ladderize a Tree*

Description

This function reorganizes the internal structure of the tree to get the ladderized effect when plotted.

Usage

```
ladderize(x, right = TRUE, ...)

## S3 method for class 'dendrogram'
ladderize(x, right = TRUE, ...)

## S3 method for class 'phylo'
ladderize(x, right = TRUE, phy, ...)

## S3 method for class 'dendlist'
ladderize(x, right = TRUE, ...)
```

Arguments

x	a tree object (either a dendrogram , dendlist , or phylo)
right	a logical (TRUE) specifying whether the smallest clade is on the right-hand side (when the tree is plotted upwards), or the opposite (if FALSE).
...	Currently ignored.
phy	a placeholder in case the user uses "phy ="

Value

A rotated tree object

See Also

[ladderize](#), [rev.dendrogram](#), [rotate](#) (ape)

Examples

```
dend <- USArrests[1:8,] %>% dist %>% hclust %>% as.dendrogram %>%
  set("labels_colors") %>% set("branches_k_color", k = 5)
set.seed(123)
dend <- shuffle(dend)

par(mfrow = c(1,3))
dend %>% plot(main = "Original")
dend %>% ladderize(TRUE) %>% plot(main = "Right (default)")
dend %>% ladderize(FALSE) %>% plot(main = "Left (rev of right)")
```

leaf_Colors

Return the leaf Colors of a dendrogram

Description

Return the leaf Colors of a dendrogram

Usage

```
leaf_Colors(d, col_to_return = c("edge", "node", "label"))
```

Arguments

d the dendrogram
col_to_return Character scalar - kind of Color attribute to return

Details

The returned Colors will be in dendrogram order.

Value

named character vector of Colors, NA_character_ where missing

Author(s)

jefferis

See Also

[slice](#), [color_branches](#)

Examples

```
dend <- USArrests %>% dist %>% hclust(method = "ave") %>% as.dendrogram
d5=color_branches(dend,5)
leaf_Colors(d5)
```

lowest_common_branch *Find lowest common branch were the two items are shared*

Description

Given two vectors, for two items, of cluster belonging - the function finds the lowest branch (e.g: largest number of k clusters) for which the two items are in the same cluster for the two trees.

Usage

```
lowest_common_branch(item1, item2, ...)
```

Arguments

item1	a named numeric vector (of cluster group with names of k level)
item2	a named numeric vector (of cluster group with names of k level)
...	not used

Value

The first location (from left) where the two vectors have the same A dendrogram, after adjusting the members attr in all of its nodes.

See Also

[cor_bakers_gamma](#)

Examples

```
item1 <- structure(c(1L, 1L, 1L, 1L), .Names = c("1", "2", "3", "4"))
item2 <- structure(c(1L, 1L, 2L, 2L), .Names = c("1", "2", "3", "4"))
lowest_common_branch(item1, item2)
```

match_order_by_labels *Adjust the order of one dendrogram based on another (using labels)*

Description

Takes one dendrogram and adjusts its order leaves valeus based on the order of another dendrogram. The values are matedched based on the labels of the two dendrograms.

This allows for faster [entanglement](#) running time, since we can be sure that the leaves order is just as using their labels.

Usage

```
match_order_by_labels(dend_change, dend_template,  
  check_that_labels_match = TRUE)
```

Arguments

```
dend_change      tree object (dendrogram)  
dend_template    tree object (dendrogram)  
check_that_labels_match  
                  logical (TRUE). If to check that the labels in the two dendrogram match. (if they  
                  do not, the function aborts)
```

Value

Returns dend_change after adjusting its order values to be like dend_template.

See Also

[entanglement](#) , [tanglegram](#)

Examples

```
## Not run:  
  
dend <- USArrests[1:4,] %>% dist %>% hclust %>% as.dendrogram  
order.dendrogram(dend) # c(4L, 3L, 1L, 2L)  
  
dend_changed <- dend  
order.dendrogram(dend_changed) <- 1:4  
order.dendrogram(dend_changed) # c(1:4)  
  
# now let's fix the order of the new object to be as it was:  
dend_changed <- match_order_by_labels(dend_changed, dend)  
# these two are now the same:  
order.dendrogram(dend_changed)  
order.dendrogram(dend)  
  
## End(Not run)
```

match_order_dendrogram_by_old_order

Adjust the order of one dendrogram based on another (using order)

Description

Takes one dendrogram and adjusts its order leaves values based on the order of another dendrogram. The values are matched based on the order of the two dendrograms.

This allows for faster [entanglement](#) running time, since we can be sure that the leaves order is just as using their labels.

This is a function is FASTER than [match_order_by_labels](#), but it assumes that the order and the labels of the two trees are matching!!

This will allow for a faster calculation of [entanglement](#).

Usage

```
match_order_dendrogram_by_old_order(dend_change, dend_template,
  dend_change_old_order, check_that_labels_match = FALSE,
  check_that_leaves_order_match = FALSE)
```

Arguments

`dend_change` tree object (dendrogram)

`dend_template` tree object (dendrogram)

`dend_change_old_order`
a numeric vector with the order of leaves in `dend_change` (at least before it was changes for some reason). This is the vector based on which we adjust the new values of `dend_change`.

`check_that_labels_match`
logical (FALSE). If to check that the labels in the two dendrogram match. (if they do not, the function aborts)

`check_that_leaves_order_match`
logical (FALSE). If to check that the order in the two dendrogram match. (if they do not, the function aborts)

Value

Returns `dend_change` after adjusting its order values to be like `dend_template`.

See Also

[entanglement](#) , [tanglegram](#), [match_order_by_labels](#)

Examples

```
## Not run:

dend <- USArrests[1:4,] %>% dist %>% hclust %>% as.dendrogram
order.dendrogram(dend) # c(4L, 3L, 1L, 2L)

# Watch this!
dend_changed <- dend
```

```

dend_changed <- rev(dend_changed)
expect_false(identical(order.dendrogram(dend_changed), order.dendrogram(dend)))
# we keep the order of dend_change, so that the leaves order are synced
# with their labels JUST LIKE dend:
old_dend_changed_order <- order.dendrogram(dend_changed)
# now we change dend_changed leaves order values:
order.dendrogram(dend_changed) <- 1:4
# and we can fix them again, based on their old kept leaves order:
dend_changed <- match_order_dendrogram_by_old_order(dend_changed, dend,
                                                    old_dend_changed_order)
expect_identical(order.dendrogram(dend_changed), order.dendrogram(dend))

## End(Not run)

```

na_locf

Last Observation Carried Forward

Description

A function for replacing each NA with the most recent non-NA prior to it.

Usage

```
na_locf(x, first_na_value = 0, recursive = TRUE, ...)
```

Arguments

x	some vector
first_na_value	If the first observation is NA, fill it with "first_na_value"
recursive	logical (TRUE). Should na_locf be re-run until all NA values are filled?
...	ignored.

Value

The original vector, but with all the missing values filled by the value before them.

Source

<https://stat.ethz.ch/pipermail/r-help/2003-November/042126.html> <http://stackoverflow.com/questions/5302049/last-observation-carried-forward-na-locf-on-panel-cross-section-time-series>

This could probably be solved MUCH faster using Rcpp.

See Also

[na.locf](#)

... not used

method a character scalar (default is "members"). If "order" than nleaves is based on length of [order.dendrogram](#). If "members", than length is trusting what is written in the dendrogram's root [attr](#). "members" is about 4 times faster than "order".

Details

The idea for the name is from functions like `ncol`, and `nrow`.

Also, it is worth noting that the `nleaves.dendrogram` is based on `order.dendrogram` instead of `labels.dendrogram` since the first is MUCH faster than the later.

The `phylo` method is based on turning the `phylo` to `hclust` and than to `dendrogram`. It may not work for complex `phylo` trees.

Value

The number of leaves in the tree

See Also

[nrow](#), [count_terminal_nodes](#)

Examples

```
hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)

nleaves(dend) # 5
nleaves(hc) # 5
```

nnodes

Counts the number of nodes (Vertices) in a tree

Description

Counts the number of nodes in a tree (`dendrogram`, `hclust`, `phylo`).

Usage

```
nnodes(x, ...)
```

S3 method for class 'dendrogram'

```
nnodes(x, ...)
```

S3 method for class 'hclust'

```
nnodes(x, ...)
```

S3 method for class 'phylo'

```
nnodes(x, ...)
```


Arguments

x tree object (dendrogram or hclust)
 ... not used

Details

The idea for the name is from functions like ncol, and nrow.

The phylo method is based on turning the phylo to hclust and than to dendrogram. It may not work for complex phylo trees.

Value

The number of leaves in the tree

See Also

[nrow](#), [count_terminal_nodes](#), [nleaves](#)

Examples

```
hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)
```

```
nnodes(dend) # 9
nnodes(hc) # 9
```

noded_with_condition *Find which nodes satisfies a condition*

Description

Goes through a tree's nodes in order to return a vector with whether (TRUE/FALSE) each node satisfies some condition (function)

Usage

```
noded_with_condition(dend, condition, include_leaves = TRUE,
  include_branches = TRUE, na.rm = FALSE, ...)
```

Arguments

dend a dendrogram dend
 condition a function that gets a node and return TRUE or FALSE (based on whether or not that node/tree fulfills the "condition")
 include_leaves logical. Should leaves attributes be included as well?
 include_branches logical. Should non-leaf (branch node) attributes be included as well?

`na.rm` logical. Should NA attributes be REMOVED from the resulting vector?
 ... passed to the condition function

Value

A logical vector with TRUE/FALSE, specifying for each of the dendrogram's nodes if it fulfills the condition or not.

See Also

[branches_attr_by_labels](#), [get_leaves_attr](#), [nnodes](#), [nleaves](#)

Examples

```
## Not run:

library(dendextend)

set.seed(23235)
ss <- sample(1:150, 10 )

# Getting the dend dend
dend <- iris[ss,-5] %>% dist %>% hclust %>% as.dendrogram
dend %>% plot

this is the basis for branches_attr_by_labels
has_any_labels <- function(sub_dend, the_labels) any(labels(sub_dend) %in% the_labels)
cols <- noded_with_condition(dend, has_any_labels,
  the_labels = c("126", "109", "59")) %>%
  ifelse(2,1)
set(dend, "branches_col", cols) %>% plot

# Similar to branches_attr_by_labels - but for heights!
high_enough <- function(sub_dend, height) attr(sub_dend, "height") > height
cols <- noded_with_condition(dend, high_enough, height = 1) %>% ifelse(2,1)
set(dend, "branches_col", cols) %>% plot

## End(Not run)
```

`order.dendrogram<-` *order.dendrogram<- assignment operator*

Description

`order.dendrogram<-` assignment operator. This is useful in cases where some object is turned into a dendrogram but its leaves values (the order) are all mixed up.

Usage

```
order.dendrogram(object, ...) <- value
```

Arguments

object	a variable name (possibly quoted) who's label are to be updated
...	parameters passed (not currently in use)
value	a value to be assigned to object's leaves value (their "order")

Value

dendrogram with updated order leaves values

See Also

[order.dendrogram](#), [labels<-](#)

Examples

```
#####
# Example for using the assignment with dendrogram and hclust objects:
hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)

str(dend)
order.dendrogram(dend) # 4 3 1 2
order.dendrogram(dend) <- 1:4
order.dendrogram(dend) # 1 2 3 4
str(dend) # the structure is still fine.

# This function is very useful if we try playing with subtrees
# For example:
hc <- hclust(dist(USArrests[1:6,]), "ave")
dend <- as.dendrogram(hc)
sub_dend <- dend[[1]]
order.dendrogram(sub_dend) # 4 6
# now using as.hclust(sub_dend) will cause trouble:
# labels(as.hclust(sub_dend)) # As of R 3.1.1-patched - this will produce an Error (as it should :)
# let's fix it:

order.dendrogram(sub_dend) <- rank(order.dendrogram(sub_dend), ties.method= "first")
labels(as.hclust(sub_dend)) # We now have labels :)
```

order.hclust	<i>Ordering of the Leaves in a hclust Dendrogram</i>
--------------	--

Description

Ordering of the Leaves in a hclust Dendrogram

Usage

```
order.hclust(x, ...)
```

Arguments

x	an hclust object or a distance matrix.
...	Ignored.

Value

A vector with length equal to the number of leaves in the hclust dendrogram is returned. From `r <- order.hclust()`, each element is the index into the original data (from which the hclust was computed).

See Also

[order.dendrogram](#)

Examples

```
set.seed(23235)
ss <- sample(1:150, 10)
hc <- iris[ss,-5] %>% dist %>% hclust
# dend <- hc %>% as.dendrogram
order.hclust(hc)
```

partition_leaves	<i>A list with labels for each subtree (edge)</i>
------------------	---

Description

Returns the set of all bipartitions from all edges, that is: a list with the labels for each of the nodes in the dendrogram.

Usage

```
partition_leaves(x, ...)
```

Arguments

x a dendrogram
 ... Ignored.

Value

A list with the labels for each of the nodes in the dendrogram.

Source

A [dendrogram](#) implementation for [partition.leaves](#) from the `distory` package

See Also

[distinct_edges](#), [highlight_distinct_edges](#), [dist.dendlist](#), [tanglegram](#), [partition.leaves](#)

Examples

```
x <- 1:3 %>% dist %>% hclust %>% as.dendrogram
plot(x)
partition_leaves(x)

## Not run:
set.seed(23235)
ss <- sample(1:150, 10 )
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("single") %>% as.dendrogram

partition_leaves(dend1)
partition_leaves(dend2)

## End(Not run)
```

plot_horiz.dendrogram *Plotting a left-tip-adjusted horizontal dendrogram*

Description

The default `plot(dend, horiz = TRUE)`, gives us a dendrogram tree plot with the tips turned right. The current function enables the creation of the same tree, but with the tips turned left. The main challenge in doing this is finding the distance of the labels from the leaves tips - which is solved with this function.

Usage

```
plot_horiz.dendrogram(x, type = c("rectangle", "triangle"), center = FALSE,
  edge.root = is.leaf(x) || !is.null(attr(x, "edgetext")), dLeaf = NULL,
  horiz = TRUE, xaxt = "n", yaxt = "s", xlim = NULL, ylim = NULL,
  nodePar = NULL, edgePar = list(), leaflab = c("perpendicular",
  "textlike", "none"), side = TRUE, text_pos = 2, ...)
```

Arguments

x	tree object (dendrogram)
type	a character vector with either "rectangle" or "triangle" (passed to plot.dendrogram)
center	logical; if TRUE, nodes are plotted centered with respect to the leaves in the branch. Otherwise (default), plot them in the middle of all direct child nodes.
edge.root	logical; if true, draw an edge to the root node.
dLeaf	a number specifying the distance in user coordinates between the tip of a leaf and its label. If NULL as per default, 3/4 of a letter width is used.
horiz	logical indicating if the dendrogram should be drawn horizontally or not. In this function it MUST be TRUE!
xaxt	graphical parameters, or arguments for other methods.
yaxt	graphical parameters, or arguments for other methods.
xlim	(NULL) optional x- and y-limits of the plot, passed to plot.default. The defaults for these show the full dendrogram.
ylim	(NULL) optional x- and y-limits of the plot, passed to plot.default. The defaults for these show the full dendrogram.
nodePar	NULL.
edgePar	list()
leaflab	c("perpendicular", "textlike", "none")
side	logical (TRUE). Should the tips of the drawn tree be facing the left side. This is the important feature of this function.
text_pos	integer from either 1 to 4 (2). Two relevant values are 2 and 4. 2 (default) means that the labels are alligned to the tips of the tree leaves. 4 will have the labels allign to the left, making them look like they were when the tree was on the left side (with leaves tips facing to the right).
...	passed to plot .

Value

The invisiable dLeaf value.

Source

This function is based on replicating [plot.dendrogram](#). In fact, I'd be happy if in the future, some tweaks could be make to [plot.dendrogram](#), so that it would replace the need for this function.

See Also

[plot.dendrogram](#), [tanglegram](#)

Examples

```
## Not run:
dend <- USArrests[1:10,] %>% dist %>% hclust %>% as.dendrogram

par(mfrow =c(1,2), mar = rep(6,4))
plot_horiz.dendrogram(dend, side=FALSE)
plot_horiz.dendrogram(dend, side=TRUE)
# plot_horiz.dendrogram(dend, side=TRUE, dLeaf= 0)
# plot_horiz.dendrogram(dend, side=TRUE, nodePar = list(pos = 1))
# sadly, lab.pos is not implemented yet,
## so the labels can not be right aligned...

plot_horiz.dendrogram(dend, side=F)
plot_horiz.dendrogram(dend, side=TRUE, dLeaf=0, xlim = c(100,-10)) # bad
plot_horiz.dendrogram(dend, side=TRUE, text_offset = 0)
plot_horiz.dendrogram(dend, side=TRUE, text_offset = 0, text_pos=4)

## End(Not run)
```

prune

*Prunes a tree (using leaves' labels)***Description**

Trims a tree (dendrogram, hclust) from a set of leaves based on their labels.

Usage

```
prune(x, ...)
```

```
## S3 method for class 'dendrogram'
prune(x, leaves,...)
```

```
## S3 method for class 'hclust'
prune(x, leaves,...)
```

```
## S3 method for class 'phylo'
prune(x, ...)
```

Arguments

x	tree object (dendrogram/hclust/phylo)
...	passed on
leaves	a character vector of the label(S) of the tip(s) (leaves) we wish to prune off the tree.

Details

I was not sure if to call this function `drop.tip` (from `ape`), `snip/prune` (from `rpart`) or just `remove.leaves`. I ended up deciding on `prune`.

Value

A pruned tree

See Also

[prune_leaf](#), [drop.tip](#) `ape`

Examples

```
hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)

par(mfrow = c(1,2))
plot(dend, main = "original tree")
plot(prune(dend , c("Alaska", "California")), main = "tree without Alaska and California")
```

prune_leaf

Trims one leaf from a dendrogram

Description

Trims one leaf from a dendrogram

Usage

```
prune_leaf(x, leaf_name, ...)
```

Arguments

<code>x</code>	dendrogram object
<code>leaf_name</code>	a character string as the label of the tip we wish to prune
<code>...</code>	passed on

Details

Used through [prune](#)

Value

A dendrogram with a leaf pruned

Examples

```

hc <- hclust(dist(USArrests[1:5,]), "ave")
dend <- as.dendrogram(hc)

par(mfrow = c(1,2))
plot(dend, main = "original tree")
plot(prune_leaf(dend , "Alaska"), main = "tree without Alaska")

```

pvclust_show_signif *Shows the significant branches in a dendrogram, based on a pvclust object*

Description

Shows the significant branches in a dendrogram, based on a pvclust object

Usage

```

pvclust_show_signif(dend, pvclust_obj, signif_type = c("bp", "au"),
  alpha = 0.05, signif_value = c(5, 1), show_type = c("lwd", "col"), ...)

```

Arguments

dend	a dendrogram object
pvclust_obj	a pvclust object
signif_type	a character scalar (either "bp" or "au"), indicating which of the two should be used to update the dendrogram.
alpha	a number between 0 to 1, default is .05. Indicates what is the cutoff from which branches will be updated.
signif_value	a 2d vector (default: c(5,1)), with the first element tells us what the significant branches will get, and the second element which value the non-significant branches will get.
show_type	a character scalar (either "lwd" or "col"), indicating which parameter of the branches should be updated based on significance.
...	not used

Value

A dendrogram with updated branches

See Also

[pvclust_show_signif](#), [pvclust_show_signif_gradient](#)

Examples

```

## Not run:
library(pvclust)
data(lung) # 916 genes for 73 subjects
set.seed(13134)
result <- pvclust(lung[, 1:20], method.dist="cor", method.hclust="average", nboot=100)

dend <- as.dendrogram(result)
result %>% as.dendrogram %>%
  hang.dendrogram %>%
  plot(main = "Cluster dendrogram with AU/BP values (%)")
result %>% text
result %>% pvrect(alpha=0.95)

dend %>% pvclust_show_signif(result) %>% plot
dend %>% pvclust_show_signif(result, show_type = "lwd") %>% plot
result %>% text
result %>% pvrect(alpha=0.95)

dend %>% pvclust_show_signif_gradient(result) %>% plot

dend %>%
  pvclust_show_signif_gradient(result) %>%
  pvclust_show_signif(result) %>%
  plot(main = "Cluster dendrogram with AU/BP values (%) \n bp values are highlighted by signif")
result %>% text
result %>% pvrect(alpha=0.95)

## End(Not run)

```

pvclust_show_signif_gradient

Shows the gradient of significance of branches in a dendrogram, based on a pvclust object

Description

Shows the gradient of significance of branches in a dendrogram, based on a pvclust object

Usage

```
pvclust_show_signif_gradient(dend, pvclust_obj, signif_type = c("bp", "au"),
  signif_col_fun = colorRampPalette(c("black", "darkred", "red")), ...)
```

Arguments

dend	a dendrogram object
pvclust_obj	a pvclust object

signif_type a character scalar (either "bp" or "au"), indicating which of the two should be used to update the dendrogram.

signif_col_fun a function to create colors for the significant gradient. Default is: colorRamp-Palette(c("black", "darkred", "red"))

... not used

Value

A dendrogram with updated branches

See Also

[pvclust_show_signif](#), [pvclust_show_signif_gradient](#)

Examples

```
## Not run:
library(pvclust)
data(lung) # 916 genes for 73 subjects
set.seed(13134)
result <- pvclust(lung[, 1:20], method.dist="cor", method.hclust="average", nboot=100)

dend <- as.dendrogram(result)
result %>% as.dendrogram %>%
  hang.dendrogram %>%
  plot(main = "Cluster dendrogram with AU/BP values (%)")
result %>% text
result %>% pvrect(alpha=0.95)

dend %>% pvclust_show_signif(result) %>% plot
dend %>% pvclust_show_signif(result, show_type = "lwd") %>% plot
result %>% text
result %>% pvrect(alpha=0.95)

dend %>% pvclust_show_signif_gradient(result) %>% plot

dend %>%
  pvclust_show_signif_gradient(result) %>%
  pvclust_show_signif(result) %>%
  plot(main = "Cluster dendrogram with AU/BP values (%) \n bp values are highlighted by signif")
result %>% text
result %>% pvrect(alpha=0.95)

## End(Not run)
```

raise.dendrogram	<i>Raise the height of a dendrogram tree</i>
------------------	--

Description

Raise the height of a dendrogram tree

Usage

```
raise.dendrogram(dend, heiget_to_add, ...)
```

Arguments

dend	dendrogram object
heiget_to_add	how much height to add to all the branches (not leaves) in the dendrogram
...	passed on (not used)

Value

A raised dendrogram

Examples

```
hc <- hclust(dist(USArrests[2:9,]), "com")
dend <- as.dendrogram(hc)

par(mfrow = c(1,2))
plot(dend, main = "original tree")
plot(raise.dendrogram(dend , 100), main = "Raised tree")
```

rank_branches	<i>Rank branches' heights</i>
---------------	-------------------------------

Description

Adjust the height attr in all of the dendrogram nodes so that the tree will have a distance of 1 unit between each parent/child nodes. It can be thought of as ranking the branches between themselves.

This is intended for easier comparison of the topology of two trees.

Notice that this function changes the height of all the leaves into 0, thus erasing the effect of [hang.dendrogram](#) (which should be run again, if that is the visualization you are interested in).

Usage

```
rank_branches(dend, diff_height = 1, ...)
```

Arguments

dend	a dendrogram object
diff_height	Numeric scalar (1). Affects the difference in height between two branches.
...	not used

Value

A dendrogram, after adjusting the height attr in all of its branches.

See Also

[get_branches_heights](#), [get_childrens_heights](#), [hang.dendrogram](#), [tanglegram](#)

Examples

```
# define dendrogram object to play with:
dend <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram

par(mfrow = c(1,3))

plot(dend)
plot(rank_branches(dend))
plot(hang.dendrogram(rank_branches(dend)))
```

rank_order.dendrogram *Fix rank of leaves order values in a dendrogram*

Description

Generally, leaves order value should be a sequence of integer values. From 1 to nleaves(tree). This function fixes trees by using [rank](#) on existing leaves order values.

Usage

```
rank_order.dendrogram(dend, ...)
```

Arguments

dend	a dendrogram object
...	not used

Value

A dendrogram, after fixing its leaves order values.

See Also

[prune](#)

Examples

```
# define dendrogram object to play with:
dend <- USArrests[1:4,] %>% dist %>% hclust(method = "ave") %>% as.dendrogram
# plot(dend)
order.dendrogram(dend)
dend2 <- prune(dend, "Alaska")
order.dendrogram(dend2)
order.dendrogram(rank_order.dendrogram(dend2))
```

rect.dendrogram

*Draw Rectangles Around a Dendrogram's Clusters***Description**

Draws rectangles around the branches of a dendrogram highlighting the corresponding clusters. First the dendrogram is cut at a certain level, then a rectangle is drawn around selected branches.

Usage

```
rect.dendrogram(tree, k = NULL, which = NULL, x = NULL, h = NULL,
  border = 2, cluster = NULL, horiz = FALSE, density = NULL,
  angle = 45, text = NULL, text_cex = 1, text_col = 1, xpd = TRUE,
  lower_rect, ...)
```

Arguments

tree	a dendrogram object.
k	Scalar. Cut the dendrogram such that exactly k clusters (if possible) are produced.
which	A vector selecting the clusters around which a rectangle should be drawn. which selects clusters by number (from left to right in the tree), Default is which = 1:k.
x	A vector selecting the clusters around which a rectangle should be drawn. x selects clusters containing the respective horizontal coordinates.
h	Scalar. Cut the dendrogram by cutting at height h. (k overrides h)
border	Vector with border colors for the rectangles.
cluster	Optional vector with cluster memberships as returned by cutree(dend_obj, k = k), can be specified for efficiency if already computed.
horiz	logical (FALSE), indicating if the rectangles should be drawn horizontally or not (for when using plot(dend, horiz = TRUE)).
density	Passed to rect : the density of shading lines, in lines per inch. The default value of NULL means that no shading lines are drawn. A zero value of density means no shading lines whereas negative values (and NA) suppress shading (and so allow color filling). If border is a vector of colors, the color of density will default to 1.

angle	Passed to <code>rect</code> : angle (in degrees) of the shading lines. (default is 45)
text	a character vector of labels to plot underneath the clusters. When NULL (default), no text is displayed.
text_cex	a numeric (scalar) value of the text's cex value.
text_col	a (scalar) value of the text's col(or) value.
xpd	A logical value (or NA.), passed to <code>par</code> . Default is TRUE, in order to allow the <code>rect</code> to be below the labels. If FALSE, all plotting is clipped to the plot region, if TRUE, all plotting is clipped to the figure region, and if NA, all plotting is clipped to the device region. See also <code>clip</code> .
lower_rect	a (scalar) value of how low should the lower part of the <code>rect</code> be. If missing, it will take the value of <code>par("usr")[3L]</code> (or <code>par("usr")[2L]</code> , depending if <code>horiz = TRUE</code> or not), with also the width of the labels. (notice that we would like to keep <code>xpd = TRUE</code> if we want the <code>rect</code> to be after the labels!) You can use a value such as 0, to get the <code>rect</code> above the labels. Notice that for a plot with small margins, it would be better to set this parameter manually.
...	parameters passed to <code>rect</code> (such as <code>lwd</code> , <code>lty</code> , etc.)

Value

(Invisibly) returns a list where each element contains a vector of data points contained in the respective cluster.

Source

This function is based on `rect.hclust`, with slight modifications to have it work with a dendrogram, as well as a few added features (e.g: ... to `rect`, and `horiz`)

The idea of adding text and shading lines under the clusters comes from skullkey from here: <http://stackoverflow.com/questions/4720307/change-dendrogram-leaves>

See Also

[rect.hclust](#), [order.dendrogram](#), [cutree.dendrogram](#)

Examples

```
set.seed(23235)
ss <- sample(1:150, 10 )
hc <- iris[ss,-5] %>% dist %>% hclust
dend <- hc %>% as.dendrogram

plot(dend)
rect.dendrogram(dend,2, border = 2)

plot(dend)
rect.dendrogram(dend, 3 , border = 1:3,
  density = 2, text = c("1", "b", "miao"), text_cex = 3)
```

```

plot(dend)
rect.dendrogram(dend,4, which = c(1,3), border = c(2,3))
rect.dendrogram(dend,4, x = 5, border = c(4))
rect.dendrogram(dend,3, border = 3, lwd = 2, lty = 2)
# now THIS, you can not do with the old rect.hclust
plot(dend, horiz = TRUE)
rect.dendrogram(dend,2, border = 2, horiz = TRUE)
rect.dendrogram(dend,4, border = 4, lty = 2, lwd = 3, horiz = TRUE)

```

```
remove_branches_edgePar
```

Remove all edgePar values from a dendrogram's branches

Description

Go through the dendrogram branches and remove its edgePar.

Usage

```
remove_branches_edgePar(object, ...)
```

Arguments

object	a dendrogram object
...	not used

Value

A dendrogram, after removing the edgePar attribute in all of its branches,

See Also

[get_root_branches_attr](#), [assign_values_to_branches_edgePar](#)

Examples

```

## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram
dend <- color_branches(dend, 3)
par(mfrow = c(1,2))
plot(dend)
plot(remove_branches_edgePar(dend))

## End(Not run)

```

remove_leaves_nodePar *Remove all nodePar values from a dendrogram's leaves*

Description

Go through the dendrogram leaves and remove its nodePar.

Usage

```
remove_leaves_nodePar(object, ...)
```

Arguments

object	a dendrogram object
...	not used

Value

A dendrogram, after removing the nodePar attribute in all of its leaves,

See Also

[get_leaves_attr](#), [assign_values_to_leaves_nodePar](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram

dend <- color_labels(dend, 3)
par(mfrow = c(1,2))
plot(dend)
plot(remove_leaves_nodePar(dend))

get_leaves_attr(dend, "nodePar")
get_leaves_attr(remove_leaves_nodePar(dend), "nodePar")

## End(Not run)
```

`remove_nodes_nodePar` *Remove all nodePar values from a dendrogram's nodes*

Description

Go through the dendrogram nodes and remove its nodePar

Usage

```
remove_nodes_nodePar(object, ...)
```

Arguments

<code>object</code>	a dendrogram object
<code>...</code>	not used

Value

A dendrogram, after removing the nodePar attribute in all of its nodes,

See Also

[get_root_branches_attr](#), [assign_values_to_branches_edgePar](#)

Examples

```
## Not run:

dend <- USArrests[1:5,] %>% dist %>% hclust %>% as.dendrogram
dend <- color_branches(dend, 3)
par(mfrow = c(1,2))
plot(dend)
plot(remove_branches_edgePar(dend))

## End(Not run)
```

`rllply` *recursively apply a function on a list*

Description

recursively apply a function on a list - and returns the output as a list, following the naming convention in the plyr package the big difference between this and rapply is that this will also apply the function on EACH element of the list, even if it's not a "terminal node" inside the list tree. An attribute is added to indicate if the value returned is from a branch or a leaf.

Usage

```
rllply(x, FUN, add_notation = FALSE, ...)
```

Arguments

x	a list.
FUN	a function to apply on each element of the list
add_notation	logical. Should each node be added a "position_type" attribute, stating if it is a "Branch" or a "Leaf".
...	not used.

Value

a list with ALL of the nodes (from the original "x" list), that FUN was applied on.

Examples

```
## Not run:
x <- list(1)
x
rllply(x, function(x){x}, add_notation = TRUE)

x <- list(1, 2, list(31))
x
rllply(x, function(x){x}, add_notation = TRUE)
# the first element is the entire tree
# after FUN was applied to its root element.

hc <- hclust(dist(USArrests[1:4,]), "ave")
dend <- as.dendrogram(hc)
rllply(dend, function(x){attr(x, "height")})
rllply(dend, function(x){attr(x, "members")})

## End(Not run)
```

 rotate

Rotate a tree object

Description

Rotates, rev and sort the branches of a tree object (dendrogram, hclust) based on a vector - either of labels order (numbers) or the labels in their new order (character).

Usage

```

rotate(x, ...)

## S3 method for class 'dendrogram'
rotate(x, order, ...)

## S3 method for class 'hclust'
rotate(x, order, ...)

## S3 method for class 'phylo'
rotate(x, ..., phy)

## S3 method for class 'hclust'
rev(x, ...)

## S3 method for class 'dendrogram'
sort(x, decreasing=FALSE, type = c("labels", "nodes"), ...)

## S3 method for class 'hclust'
sort(x, decreasing=FALSE, ...)

```

Arguments

x	a tree object (either a dendrogram or hclust)
...	parameters passed (for example, in case of sort)
order	Either numeric or character vector. Is numeric: it is a numeric vector with the order of the value to be assigned to object's label. The numbers say are just like when you use order : which of the items on the tree-plot should be "first" (e.g: most left), second etc. (this is relevant only to rotate) Is character: it must be a vector with the content of labels(x), in the order we'd like to have the new tree.
decreasing	logical. Should the sort be increasing or decreasing? Not available for partial sorting. (relevant only to sort)
type	a character indicating how to sort. If "labels" then by lexicographic order of the labels. If "nodes", then by using ladderize (order so that recursively, the leftmost branch will be the smallest)
phy	a placeholder in case the user uses "phy ="

Details

The motivation for this function came from the function [order.dendrogram](#) NOT being very intuitive. What rotate aims to do is give a simple tree rotation function which is based on the order which the user would like to see the tree rotated by (just as [order](#) works for numeric vectors).

[rev.dendrogram](#) is part of base R, and returns the tree object after rotating it so that the order of the labels is reversed. Here we added an S3 method for hclust objects.

The sort methods sort the labels of the tree (using order) and then attempts to rotate the tree to fit that order.

The `hclust` method of "rotate" works by first changing the object into dendrogram, performing the rotation, and then changing it back to `hclust`. Special care is taken in preserving some of the properties of the `hclust` object.

The `ape` package has its own `rotate(ape)` function (Which is sadly not S3, so cannot be easily connected with the current implementation). Still, there is an S3 plug that makes sure people loading first `ape` and then `dendextend` will still be able to use `rotate` without a problem. Notice that if you will first load `ape` and only then `dendextend`, using "rotate" will fail with the error: "Error in rotate(dend, _____) : object "phy" is not of class "phylo" - this is because rotate in ape is not S3 and will fail to find the rotate.dendrogram function. In such a case simply run `unloadNamespace(ape)`. Or, you can run: `unloadNamespace("dendextend"); attachNamespace("dendextend")` The solution for this is that if you have `ape` installed on your machine, It will be loaded when you load `dendextend` (but after it). This way, rotate will work fine for both dendrogram AND phylo objects.

Value

A rotated tree object

See Also

[order.dendrogram](#), [order](#), [rev.dendrogram](#), [rotate](#) (ape), [ladderize](#)

Examples

```
hc <- hclust(dist(USArrests[c(1,6,13,20, 23),]), "ave")
dend <- as.dendrogram(hc)

# For dendrogram objects:
labels_colors(dend) <- rainbow(nleaves(dend))
# let's color the labels to make the followup of the rotation easier
par(mfrow = c(1,2))
plot(dend, main = "Original tree")
plot(rotate(dend, c(2:5,1)), main =
"Rotates the left most leaf \n into the right side of the tree")
par(mfrow = c(1,2))
plot(dend, main = "Original tree")
plot(sort(dend), main = "Sorts the labels by alphabetical order \n
and rotates the tree to give the best fit possible")
par(mfrow = c(1,2))
plot(dend, main = "Original tree")
plot(rev(dend), main = "Reverses the order of the tree labels")

# For hclust objects:
plot(hc)
plot(rotate(hc, c(2:5,1)), main = "Rotates the left most leaf \n
into the right side of the tree")

par(mfrow = c(1,3))
dend %>% plot(main = "Original tree")
dend %>% sort %>% plot(main = "labels sort")
dend %>% sort(type = "nodes") %>% plot(main = "nodes (ladderize) sort")
```

rotate_DendSer	<i>Rotates dend based on DendSer</i>
----------------	--------------------------------------

Description

Rotates a dendrogram based on its seriation

The function tries to turn the dend into hclust using [DendSer.dendrogram](#) (based on [DendSer](#))

Also, if a distance matrix is missing, it will try to use the [cophenetic](#) distance.

Usage

```
rotate_DendSer(dend, ser_weight, ...)
```

Arguments

dend	An object of class dendrogram
ser_weight	Used by cost function to evaluate ordering. For cost=costLS, this is a vector of object weights. Otherwise is a dist or symmetric matrix. passed to DendSer.dendrogram and from there to DendSer . If it is missing, the cophenetic distance is used instead.
...	parameters passed to DendSer

Value

Numeric vector giving an optimal dendrogram order

See Also

[DendSer](#), [DendSer.dendrogram](#) , [untangle_DendSer](#), [rotate_DendSer](#)

Examples

```
## Not run:
library(DendSer) # already used from within the function
dend <- USArrests[1:4,] %>% dist %>% hclust("ave") %>% as.dendrogram
DendSer.dendrogram(dend)

tanglegram(dend, rotate_DendSer(dend))

## End(Not run)
```

sample.dendrogram	<i>Sample a tree</i>
-------------------	----------------------

Description

Samples a tree, either by permuting the labels (which is useful for a permutation test), or by repeated sampling of the same labels (essential for bootstrapping when we don't have access to the original data which produced the tree).

Duplicates a leaf in a tree. Useful for non-parametric bootstrapping trees since it emulates what would have happened if the tree was constructed based on a row-sample with replacements from the original data matrix.

Usage

```
sample.dendrogram(dend, replace = FALSE, dend_labels, sampled_labels,
  fix_members = TRUE, fix_order = TRUE, fix_midpoint = TRUE, ...)
```

Arguments

dend	a dendrogram object
replace	logical (FALSE). Should we shuffle the labels (if FALSE), or should we replicate the same leaf over and over, while omitting other leaves? (this is when set to TRUE).
dend_labels	a character vector of the tree's labels. This can save the time it takes for getting the tree labels (in case we run a simulating, computing this once might save some running time). If missing, it uses labels in order to get the labels.
sampled_labels	a character vector of the tree's sampled labels. This can help us if we wish to compare two trees. In such a case we'd like to be able to have the same sample of labels used on both trees. If missing, it uses sample in order to get the sampled labels. Only works when replace=TRUE!
fix_members	logical (TRUE). Fix the number of members in attr using fix_members_attr.dendrogram
fix_order	logical (TRUE). Fix the leaves order
fix_midpoint	logical (TRUE). Fix the midpoint value. If TRUE, it overrides "fix_members" and turns it into TRUE (since it must have a correct number of members in order to work). values using rank_order.dendrogram
...	not used

Value

A dendrogram, after "sampling" its leaves.

See Also

[sample](#), [duplicate_leaf](#)

Examples

```
## Not run:
# define dendrogram object to play with:
dend <- USArrests[1:5,] %>% dist %>% hclust(method = "ave") %>% as.dendrogram
plot(dend)

# # same tree, with different order of labels
plot(sample.dendrogram(dend, replace = FALSE))

# # A different tree (!), with some labels duplicated,
# # while others are pruned
plot(sample.dendrogram(dend, replace = TRUE))

## End(Not run)
```

set

Set (/update) features to a dendrogram

Description

a master function for updating various attributes and features of dendrogram objects.

Usage

```
set(object, ...)
```

```
## S3 method for class 'dendrogram'
set(object,
      what = c("labels",
               "labels_colors",
               "labels_cex",
               "labels_to_character",
               "leaves_pch",
               "leaves_cex",
               "leaves_col",
               "nodes_pch",
               "nodes_cex",
               "nodes_col",
               "hang_leaves",
               "branches_k_color",
               "branches_col",
               "branches_lwd",
               "branches_lty",
               "by_labels_branches_col",
               "by_labels_branches_lwd",
               "by_labels_branches_lty",
               "clear_branches",
```



```

        "clear_leaves"
    ),
    value, ...)

## S3 method for class 'dendlist'
set(object, ..., which)

## S3 method for class 'data.table'
set(...)

```

Arguments

object	a tree (dendrogram , or dendlist)
...	passed to the specific function for more options.
what	a character indicating what is the property of the tree that should be set/updated. (see the usage and the example section for the different options)
value	an object with the value to set in the tree. (the type of the value depends on the "what")
which	an integer vector indicating, in the case "object" is a dendlist, on which of the trees should the modification be performed. If missing - the change will be performed on all of objects in the dendlist.

Details

This is a wrapper function for many of the main tasks we might wish to perform on a dendrogram before plotting.

The options of `by_labels_branches_col`, `by_labels_branches_lwd`, `by_labels_branches_lty` have extra parameters: `type`, `attr`, `TF_value`. You can read more about them here: [branches_attr_by_labels](#)

The "what" parameter" can accept the following options:

- `labels` - set the labels ([labels<-dendrogram](#))
- `labels_colors` - set the labels' colors ([color_labels](#))
- `labels_cex` - set the labels' size ([assign_values_to_leaves_nodePar](#))
- `labels_to_character` - set the labels' to be characters
- `leaves_pch` - set the leaves' point type ([assign_values_to_leaves_nodePar](#))
- `leaves_cex` - set the leaves' point size ([assign_values_to_leaves_nodePar](#))
- `leaves_col` - set the leaves' point color ([assign_values_to_leaves_nodePar](#))
- `nodes_pch` - set the nodes' point type ([assign_values_to_nodes_nodePar](#))
- `nodes_cex` - set the nodes' point size ([assign_values_to_nodes_nodePar](#))
- `nodes_col` - set the nodes' point color ([assign_values_to_nodes_nodePar](#))
- `hang_leaves` - hang the leaves ([hang.dendrogram](#))
- `branches_k_color` - color the branches ([color_branches](#))
- `branches_col` - set the color of branches ([assign_values_to_branches_edgePar](#))

- `branches_lwd` - set the line width of branches ([assign_values_to_branches_edgePar](#))
- `branches_lty` - set the line type of branches ([assign_values_to_branches_edgePar](#))
- `by_labels_branches_col` - set the color of branches with specific labels ([branches_attr_by_labels](#))
- `by_labels_branches_lwd` - set the line width of branches with specific labels ([branches_attr_by_labels](#))
- `by_labels_branches_lty` - set the line type of branches with specific labels ([branches_attr_by_labels](#))
- `clear_branches` - clear branches' attributes ([remove_branches_edgePar](#))
- `clear_leaves` - clear leaves' attributes ([remove_branches_edgePar](#))

Value

An updated dendrogram (or dendlist), with some change to the parameters of it

See Also

[labels<-dendrogram](#), [labels_colors<-](#), [hang.dendrogram](#), [color_branches](#), [assign_values_to_leaves_nodePar](#), [assign_values_to_branches_edgePar](#), [remove_branches_edgePar](#), [remove_leaves_nodePar](#), [noded_with_condition](#), [branches_attr_by_labels](#), [dendrogram](#)

Examples

```
## Not run:

set.seed(23235)
ss <- sample(1:150, 10 )

# Getting the dend object
dend <- iris[ss,-5] %>% dist %>% hclust %>% as.dendrogram
dend %>% plot

dend %>% labels
dend %>% set("labels", 1:10) %>% labels
dend %>% set("labels", 1:10) %>% plot
dend %>% set("labels_color") %>% plot
dend %>% set("labels_col", c(1,2)) %>% plot # Works also with partial matching :)
dend %>% set("labels_cex", c(1, 1.2)) %>% plot
dend %>% set("leaves_pch", NA) %>% plot
dend %>% set("leaves_pch", c(1:5)) %>% plot
dend %>% set("leaves_pch", c(19,19, NA)) %>%
  set("leaves_cex", c(1,2)) %>% plot
dend %>% set("leaves_pch", c(19,19, NA)) %>%
  set("leaves_cex", c(1,2)) %>%
  set("leaves_col", c(1,1,2,2)) %>%
  plot
dend %>% set("hang") %>% plot

dend %>% set("branches_k_col") %>% plot
dend %>% set("branches_k_col", c(1,2)) %>% plot
dend %>% set("branches_k_col", c(1,2,3), k=3) %>% plot
dend %>% set("branches_k_col", k=3) %>% plot
```

```

dend %>% set("branches_col", c(1,2, 1, 2, NA)) %>% plot
dend %>% set("branches_lwd", c(2,1,2)) %>% plot
dend %>% set("branches_lty", c(1,2,1)) %>% plot

# clears all of the things added to the leaves
dend %>%
  set("labels_color", c(19,19, NA)) %>%
  set("leaves_pch", c(19,19, NA)) %>% # plot
  set("clear_leaves") %>% # remove all of what was done until this point
  plot
# Different order
dend %>%
  set("leaves_pch", c(19,19, NA)) %>%
  set("labels_color", c(19,19, NA)) %>%
  set("clear_leaves") %>% plot

# doing this without chaining (%>%) will NOT be fun:
dend %>%
  set("labels", 1:10) %>%
  set("labels_color") %>%
  set("branches_col", c(1,2, 1, 2, NA)) %>%
  set("branches_lwd", c(2,1,2)) %>%
  set("branches_lty", c(1,2,1)) %>%
  set("hang") %>%
  plot

#-----
# Examples for: by_labels_branches_col, by_labels_branches_lwd, by_labels_branches_lty

old_labels <- labels(dend)
dend %>%
  set("labels", seq_len(nleaves(dend))) %>%
  set("by_labels_branches_col", c(1:4, 7)) %>%
  set("by_labels_branches_lwd", c(1:4, 7)) %>%
  set("by_labels_branches_lty", c(1:4, 7)) %>%
  set("labels", old_labels) %>%
  plot

dend %>%
  set("labels", seq_len(nleaves(dend))) %>%
  set("by_labels_branches_col", c(1:4, 7), type = "any", TF_values = c(4,2)) %>%
  set("by_labels_branches_lwd", c(1:4, 7), type = "all", TF_values = c(4,1)) %>%
  set("by_labels_branches_lty", c(1:4, 7), TF_values = c(4,1)) %>%
  plot

#-----
# A few dendlist examples:
dendlist(dend,dend) %>% set("hang") %>% plot

```

```

dendlist(dend,dend) %>% set("branches_k_col", k=3) %>% plot
dendlist(dend,dend) %>% set("labels_col", c(1,2)) %>% plot

dendlist(dend,dend) %>%
  set("hang") %>%
  set("labels_col", c(1,2), which = 1) %>%
  set("branches_k_col", k=3, which = 2) %>%
  set("labels_cex", 1.2) %>%
  plot

#-----
# example of modifying the dendrogram in a heatmap:

library(gplots)
data(mtcars)
x <- as.matrix(mtcars)
rc <- rainbow(nrow(x), start=0, end=.3)
cc <- rainbow(ncol(x), start=0, end=.3)

##
##' demonstrate the effect of row and column dendrogram options
##
Rowv_dend <- x %>% dist %>% hclust %>%
  as.dendrogram %>%
  set("branches_k", k = 3) %>%
  set("branches_lwd", 2) %>% rotate_DendSer
Colv_dend <- t(x) %>% dist %>% hclust %>%
  as.dendrogram %>%
  set("branches_k", k = 3) %>%
  set("branches_lwd", 2) %>% rotate_DendSer
heatmap.2(x, Rowv = Rowv_dend, Colv = Colv_dend)

## End(Not run)

```

shuffle

Random rotation of trees

Description

'shuffle' randomly rotates ("shuffles") a tree, changing its presentation while preserving its topology. 'shuffle' is based on [rotate](#) and through its methods can work for any of the major tree objects in R ([dendrogram/hclust/phylo](#)).

This function is useful in combination with [tanglegram](#) and [entanglement](#).

Usage

```
shuffle(object, ...)  
  
## S3 method for class 'dendrogram'  
shuffle(object, ...)  
  
## S3 method for class 'dendlist'  
shuffle(object, which, ...)  
  
## S3 method for class 'hclust'  
shuffle(object, ...)  
  
## S3 method for class 'phylo'  
shuffle(object, ...)
```

Arguments

object	a tree object (dendrogram/hclust/phylo)
...	Ignored.
which	an integer vector for indicating which of the trees in the dendlist object should be plotted default is missing, in which case all the dendlists in dendlist will be shuffled

Details

'shuffle' is a function that randomly rotates ("shuffles") a tree. a dendrogram leaves order (by means of rotation)

Value

A randomly rotated tree object

See Also

[tanglegram](#), [entanglement](#), [rotate](#)

Examples

```
dend <- USArrests %>% dist %>% hclust %>% as.dendrogram  
set.seed(234238)  
dend2 <- shuffle(dend)  
  
tanglegram(dend, dend2, margin_inner=7)  
entanglement(dend, dend2) # 0.3983  
  
# although these ARE the SAME tree:  
tanglegram(sort(dend), sort(dend2), margin_inner=7)
```

 sort_2_clusters_vectors

Sorts two clusters vector by their names

Description

Sorts two clusters vector by their names

Usage

```
sort_2_clusters_vectors(A1_clusters, A2_clusters,
  assume_sorted_vectors = FALSE, warn = dendextend_options("warn"), ...)
```

Arguments

A1_clusters	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A1. These are often obtained by using some k cut on a dendrogram.
A2_clusters	a numeric vector of cluster grouping (numeric) of items, with a name attribute of item name for each element from group A2. These are often obtained by using some k cut on a dendrogram.
assume_sorted_vectors	logical (FALSE). Can we assume to two group vectors are sorter so that they have the same order of items? IF FALSE (default), then the vectors will be sorted based on their name attribute.
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE.
...	Ignored.

Value

A list with two elements, corresponding two the two clustering vectors.

See Also

[FM_index_profdpm](#)

Examples

```
## Not run:

set.seed(23235)
ss <- sample(1:150, 4 )
hc1 <- hclust(dist(iris[ss,-5]), "com")
hc2 <- hclust(dist(iris[ss,-5]), "single")
# dend1 <- as.dendrogram(hc1)
```

```
# dend2 <- as.dendrogram(hc2)
#   cutree(dend1)

A1_clusters <- cutree(hc1, k=3)
A2_clusters <- sample(cutree(hc1, k=3))

sort_2_clusters_vectors(A1_clusters, A2_clusters, assume_sorted_vectors =TRUE) # no sorting
sort_2_clusters_vectors(A1_clusters, A2_clusters, assume_sorted_vectors =FALSE) # Sorted

## End(Not run)
```

sort_dist_mat	<i>Sorts a distance matrix by rows and columns</i>
---------------	--

Description

Sorts a distance matrix by rows and columns

Usage

```
sort_dist_mat(dist_mat, by_rows = TRUE, by_cols = TRUE, ...)
```

Arguments

dist_mat	a distance matrix.
by_rows	logical (TRUE). Sort the distance matrix by rows?
by_cols	logical (TRUE). Sort the distance matrix by columns?
...	Ignored.

Value

A distance matrix (after sorting)

See Also

[dist](#), [cor_cophenetic](#)

sort_levels_values *Sort the values level in a vector*

Description

Takes a numeric vector and sort its values so that they would be increasing from left to right. It is different from [sort](#) in that the function will only "sort" the values levels, and not the vector itself.

This function is useful for [cutree](#) - making the sort_cluster_numbers parameter possible. Using that parameter with TRUE makes the clusters id's from cutree to be ordered from left to right. e.g: the left most cluster in the tree will be numbered "1", the one after it will be "2" etc...).

Usage

```
sort_levels_values(x, MARGIN = 2, decreasing = FALSE,
  force_integer = FALSE, warn = dendextend_options("warn"), ...)
```

Arguments

x	a numeric vector.
MARGIN	passed to apply . It is a vector giving the subscripts which the function will be applied over. E.g., for a matrix 1 indicates rows, 2 indicates columns, c(1, 2) indicates rows and columns. Where X has named dimnames, it can be a character vector selecting dimension names.
decreasing	logical (FALSE). Should the sort be increasing or decreasing?
force_integer	logical (FALSE). Should the values returned be integers?
warn	logical (default from dendextend_options("warn") is FALSE). Set if warning are to be issued, it is safer to keep this at TRUE, but for keeping the noise down, the default is FALSE. (for example when x had NA values in it)
...	ignored.

Value

if x is an object - it returns logical - is the object of class dendrogram.

See Also

[sort](#), [fac2num](#), [cutree](#)

Examples

```
x <- 1:4
sort_levels_values(x) # 1 2 3 4

x <- c(4:1)
names(x) <- letters[x]
attr(x, "keep_me") <- "a cat"
```



```

sort_levels_values(x) # 1 2 3 4

x <- c(4:1,4, 2)
sort_levels_values(x) # 1 2 3 4 1 3

x <- c(2,2,3,2,1)
sort_levels_values(x) # 1 1 2 1 3

x<- matrix(16:1, 4, 4)
rownames(x) <- letters[1:4]
x
apply(x, 2, sort_levels_values)

```

tanglegram

Tanglegram plot

Description

Plots a tanglegram plot of a side by side trees.

Usage

```

tanglegram(tree1, ...)

## S3 method for class 'dendrogram'
tanglegram(tree1, tree2 ,
  sort = FALSE,
  color_lines = "darkgrey",
  lwd = 3.5,
  edge.lwd = NULL,
  columns_width = c(5,3,5),
  margin_top = 3,
  margin_bottom = 2.5,
  margin_inner = 3,
  margin_outer = 0.5,
  left_dendo_mar = c(margin_bottom,margin_outer,margin_top,margin_inner),
  right_dendo_mar = c(margin_bottom,margin_inner,margin_top,margin_outer),
  intersecting = TRUE,
  dLeaf = NULL,
  dLeaf_left = dLeaf,
  dLeaf_right = dLeaf,
  axes = TRUE,
  type = "r", # can also be "t"
  lab.cex = NULL,
  remove_nodePar =FALSE,
  main = "",
  main_left = "",
  main_right = "",

```

```

sub = "",
k_labels = NULL,
k_branches = NULL,
rank_branches = FALSE,
hang = FALSE,
match_order_by_labels = TRUE,
cex_main = 2,
cex_main_left = cex_main,
cex_main_right = cex_main,
cex_sub = cex_main,
highlight_distinct_edges = TRUE,
...)

## S3 method for class 'dendlist'
tanglegram(tree1, which = c(1L,2L), ...)

## S3 method for class 'hclust'
tanglegram(tree1, ...)

## S3 method for class 'phylo'
tanglegram(tree1, ...)

```

Arguments

tree1	tree object (dendrogram/dendlist/hclust/phylo), plotted on the left
...	not used.
tree2	tree object (dendrogram/hclust/phylo), plotted on the right
which	an integer vector of length 2, indicating which of the trees in the dendlist object should be plotted
sort	logical (FALSE). Should the dendrogram's labels be "sorted"? (might give a better tree in some cases).
color_lines	a vector of colors for the lines connected the labels. If the colors are shorter than the number of labels, they are recycled (and a warning is issued).
lwd	width of the lines connecting the labels. (default is 3.5)
edge.lwd	width of the dendrograms lines.
columns_width	a vector with three elements, giving the relative sizes of the the three plots (left dendrogram, connecting lines, right dendrogram). This is passed to layout . The default is: c(5,3,5)
margin_top	the number of lines of margin to be specified on the top of the plots.
margin_bottom	the number of lines of margin to be specified on the bottom of the plots.
margin_inner	margin_bottom the number of lines of margin to be specified on the inner distance between the dendrograms and the connecting lines.
margin_outer	margin_bottom the number of lines of margin to be specified on the outer distance between the dendrograms and the connecting lines.
left_dendo_mar	mar parameters of the left dendrogram.

<code>right_dendo_mar</code>	mar parameters of the right dendrogram.
<code>intersecting</code>	logical (TRUE). Should the leaves of the two dendrograms be pruned so that the two trees will have the same labels?
<code>dLeaf</code>	a number specifying the distance in user coordinates between the tip of a leaf and its label. If NULL, as per default, 3/4 of a letter width or height is used. Notice that if we are comparing two dendrograms with different heights, manually changing <code>dLeaf</code> will affect both trees differently. In such a case, it is recommended to manually change <code>dLeaf_left</code> and <code>dLeaf_right</code> . This can be especially important when changing the <code>lab.cex</code> of the dendrogram's labels. Alternatively, one could manually set the <code>xlim</code> parameter for both trees, which will force the proportion of distances of the labels from the trees to remain the same.
<code>dLeaf_left</code>	<code>dLeaf</code> of the left dendrogram, by default it is equal to <code>dLeaf</code> (often negative).
<code>dLeaf_right</code>	<code>dLeaf</code> of the right dendrogram, by default it is equal to minus <code>dLeaf</code> (often positive).
<code>axes</code>	logical (TRUE). Should plot axes be plotted?
<code>type</code>	type of plot ("t"/"r" = triangle or rectangle)
<code>lab.cex</code>	numeric scalar, influencing the cex size of the labels.
<code>remove_nodePar</code>	logical (FALSE). Should the nodePar of the leaves be removed? (useful when the trees' leaves has too many parameters on them)
<code>main</code>	Character. Title above the connecting lines.
<code>main_left</code>	Character. Title of the left dendrogram.
<code>main_right</code>	Character. Title of the right dendrogram.
<code>sub</code>	Character. Title below the connecting lines.
<code>k_labels</code>	integer. Number of groups by which to color the leaves.
<code>k_branches</code>	integer. Number of groups by which to color the branches.
<code>rank_branches</code>	logical (FALSE). Should the branches heights be adjusted? (setting this to TRUE - can make it easier for comparing topological differences)
<code>hang</code>	logical (FALSE). Should we hang the leaves of the trees?
<code>match_order_by_labels</code>	logical (TRUE). Should the leaves value order be matched between the two trees based on labels? This is a MUST in order to have the lines connect the correct labels. Set this to FALSE if you want to make the plotting a bit faster, and only after you are sure the labels and orders are correctly aligned.
<code>cex_main</code>	A numerical value giving the amount by which plotting title should be magnified relative to the default.
<code>cex_main_left</code>	see <code>cex_main</code> .
<code>cex_main_right</code>	see <code>cex_main</code> .
<code>cex_sub</code>	see <code>cex_main</code> .
<code>highlight_distinct_edges</code>	logical (default is TRUE). If to highlight distinct edges in each tree (by changing their line types to 2).

Details

Notice that tanglegram does not "resize" well. In case you are resizing your window you would need to re-run the function.

Value

An invisible [dendlist](#), with two trees after being modified during the creation of the tanglegram.

Author(s)

Tal Galili, Johan Renaudie

Source

The function is based on code from Johan Renaudie (plannapus), after major revisions. See: <http://stackoverflow.com/questions/12456768/duelling-dendrograms-in-r-placing-dendrograms-back-to-back->

As far as I could tell, this code was originally inspired by Dylan Beaudette function `dueling.dendrograms` from the `sharpshootR` package: <http://cran.at.r-project.org/web/packages/sharpshootR/tanglegram>

See Also

[remove_leaves_nodePar](#), [plot_horiz.dendrogram](#), [rank_branches](#), [hang.dendrogram](#)

Examples

```
## Not run:
set.seed(23235)
ss <- sample(1:150, 10 )
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("sin") %>% as.dendrogram
dend12 <- dendlist(dend1, dend2)

dend12 %>% tanglegram

tanglegram(dend1 , dend2)
tanglegram(dend1 , dend2, sort = TRUE)
tanglegram(dend1 , dend2, remove_nodePar = TRUE)
tanglegram(dend1 , dend2, k_labels = 6, k_branches = 4)

tanglegram(dend1 , dend2, lab.cex = 2, edge.lwd = 3,
margin_inner= 5, type = "t", center = TRUE)

## works nicely:
tanglegram(dend1 , dend2, lab.cex = 2, edge.lwd = 3,
margin_inner= 3.5, type = "t", center = TRUE,
dLeaf = -0.1, xlim = c(7,0),
k_branches=3)
```

```
# using rank_branches can make the comparison even easier
tanglegram(rank_branches(dend1) , rank_branches(dend2), lab.cex = 2, edge.lwd = 3,
margin_inner= 3.5, type = "t", center = TRUE,
dLeaf = -0.1, xlim = c(5.1,0), columns_width= c(5,1,5),
k_branches=3)

## End(Not run)
```

theme_dendro

Creates completely blank theme in ggplot

Description

Sets most of the ggplot options to blank, by returning blank theme elements for the panel grid, panel background, axis title, axis text, axis line and axis ticks.

Usage

```
theme_dendro()
```

Author(s)

Andrie de Vries

Source

This function is from Andrie de Vries's `ggdendro` package.

The motivation for this fork is the need to add more graphical parameters to the plotted tree. This required a strong mixer of functions from `ggdendro` and `dendextend` (to the point that it seemed better to just fork the code into its current form)

See Also

[ggdend](#)

unbranch *unbranch trees*

Description

unbranch trees

Usage

```
unbranch(x, ...)

## S3 method for class 'dendrogram'
unbranch(x, branch_becoming_root = 1, new_root_height, ...)

## S3 method for class 'hclust'
unbranch(x, branch_becoming_root = 1, new_root_height, ...)

## S3 method for class 'phylo'
unbranch(x, ...)
```

Arguments

`x` tree (dendrogram/hclust) object
`...` passed on
`branch_becoming_root`
 a numeric choosing the branch of the root which will become the new root (from left to right)
`new_root_height`
 the new height of the branch which will become the new root. If the parameter is not given - the height of the original root is used.

Value

An unbranched dendrogram

See Also

[unroot ape](#)

Examples

```
hc <- hclust(dist(USArrests[2:9,]), "com")
dend <- as.dendrogram(hc)

par(mfrow = c(1,3))
plot(dend, main = "original tree")
plot(unbranch(dend , 1), main = "unbranched tree (left branch)")
plot(unbranch(dend , 2), main = "tree without (right branch)")
```

unclass_dend	<i>unclass an entire dendrogram tree</i>
--------------	--

Description

unclass an entire dendrogram tree

Usage

```
unclass_dend(dend, ...)
```

Arguments

dend	a dendrogram object
...	not used

Value

The list which was the dendrogram (but without a class)

See Also

[nleaves](#)

Examples

```
# define dendrogram object to play with:
hc <- hclust(dist(USArrests[1:3,]), "ave")
dend <- as.dendrogram(hc)

itself <- function(x) x
dend <- dendrapply(dend, itself)
unclass(dend) # this only returns a list with
              # two dendrogram objects inside it.
str(dend) # this is a great way to show a dendrogram,
          # but it doesn't help us understand how the R object is built.
str(unclass(dend)) # this is a great way to show a dendrogram,
                  # but it doesn't help us understand how the R object is built.
unclass_dend(dend) # this only returns a list
                  # with two dendrogram objects inside it.
str(unclass_dend(dend)) # NOW we can more easily understand
                       # how the dendrogram object is structured...
```

untangle

untangle dendrograms

Description

One untangle function to rule them all.

This function untangles dendrogram lists (dendlist), Using various heuristics.

Usage

```
untangle(dend1, ...)
```

```
## S3 method for class 'dendrogram'  
untangle(dend1, dend2 ,  
  method = c("random", "step1side", "step2side", "DendSer"),  
  ...)
```

```
## S3 method for class 'dendlist'  
untangle(dend1,  
  method = c("random", "step1side", "step2side", "DendSer"),  
  which = c(1L,2L), ...)
```

Arguments

dend1	a dendrogram or a dendlist object
...	passed to the relevant untangle function
dend2	A second dendrogram (to untangle against)
which	an integer vector of length 2, indicating which of the trees in the dendlist object should be plotted
method	a character indicating the type of untangle heuristic to use.

Details

This function wraps all of the untangle functions, in order to make it easier to find our about (and use) them.

Value

A [dendlist](#), with two trees after they have been untangled.

Author(s)

Tal Galili

See Also

[tanglegram](#), [untangle_random_search](#), [untangle_step_rotate_1side](#), [untangle_step_rotate_2side](#), [entanglement](#)

Examples

```
## Not run:
set.seed(23235)
ss <- sample(1:150, 10 )
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("sin") %>% as.dendrogram
dend12 <- dendlist(dend1, dend2)

dend12 %>% tanglegram

untangle(dend1, dend2, method="random", R = 5) %>% tanglegram

# it works, and we get something different:
set.seed(1234)
dend12 %>% untangle(method="random", R = 5) %>% tanglegram

set.seed(1234)
# fixes it completely:
dend12 %>% untangle(method="random", R = 5) %>% untangle(method="step1") %>% tanglegram
# not good enough
dend12 %>% untangle(method="step1") %>% tanglegram
# not good enough
dend12 %>% untangle(method="step2") %>% tanglegram
# How we might wish to use it:
set.seed(12777)
dend12 %>%
  untangle(method="random", R = 1) %>%
  untangle(method="step2") %>%
  tanglegram

## End(Not run)
```

untangle_DendSer

Tries to run DendSer on a dendrogram

Description

The function tries to turn the dend into hclust. It then uses the [cophenetic](#) distance matrix for optimizing the tree's rotation.

This is a good (and fast) starting point for [linkuntangle_step_rotate_2side](#)

Usage

```
untangle_DendSer(dend, ...)
```

Arguments

dend An object of class `dendlist`
 ... NOT USED

Value

A dendlist object with ordered dends

See Also

`DendSer`, `DendSer.dendrogram`, `untangle_DendSer`, `rotate_DendSer`

Examples

```
## Not run:
set.seed(232)
ss <- sample(1:150, 20)
dend1 <- iris[ss,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[ss,-5] %>% dist %>% hclust("sin") %>% as.dendrogram
dend12 <- dendlist(dend1, dend2)

# bad solutions
dend12 %>% tanglegram
dend12 %>% untangle("step2") %>% tanglegram
dend12 %>% untangle_DendSer %>% tanglegram
# but the combination is quite awesome:
dend12 %>% untangle_DendSer %>% untangle("step2") %>% tanglegram

## End(Not run)
```

untangle_random_search

Untangle - random search

Description

Searches for two untangled dendrogram by randomly shuffling them and each time checking if their entanglement was improved.

Usage

```
untangle_random_search(tree1, tree2, R = 100L, L = 1,
  leaves_matching_method = c("labels", "order"), ...)
```

Arguments

tree1	a tree object (of class dendrogram/hclust/phylo).
tree2	a tree object (of class dendrogram/hclust/phylo).
R	numeric (default is 100). The number of shuffles to perform.
L	the distance norm to use for measuring the distance between the two trees. It can be any positive number, often one will want to use 0, 1, 1.5, 2 (see 'details' for more). It is passed to entanglement .
leaves_matching_method	a character scalar passed to entanglement . It can be either "order" or "labels" (default). If using "labels", then we use the labels for matching the leaves order value. And if "order" then we use the old leaves order value for matching the leaves order value. Using "order" is faster, but "labels" is safer. "order" will assume that the original two trees had their labels and order values MATCHED. Hence, it is best to make sure that the trees used here have the same labels and the SAME values matched to these values - and then use "order" (for fastest results). If "order" is used, the function first calls match_order_by_labels in order to make sure that the two trees have their labels synced with their leaves order values.
...	not used

Details

Untangling two trees is a hard combinatorical problem without a closed form solution. One way for doing it is to run through a random spectrum of options and look for the "best" two trees. This is what this function offers.

Value

A dendlist with two trees with the best entanglement that was found.

See Also

[tanglegram](#), [match_order_by_labels](#), [entanglement](#).

Examples

```
## Not run:
dend1 <- iris[,-5] %>% dist %>% hclust("com") %>% as.dendrogram
dend2 <- iris[,-5] %>% dist %>% hclust("sin") %>% as.dendrogram
tanglegram(dend1,dend2)

set.seed(65168)
dend12 <- untangle_random_search(dend1, dend2, R = 10)
tanglegram(dend12[[1]],dend12[[2]])
tanglegram(dend12)

entanglement(dend1,dend2, L = 2) # 0.8894
```

```
entanglement(dend12[[1]],dend12[[2]], L = 2) # 0.0998
```

```
## End(Not run)
```

```
untangle_step_rotate_1side
```

Stepwise untangle one tree compared to another

Description

Given a fixed tree and a tree we wish to rotate, this function goes through all of the k number of clusters (from 2 onward), and each time rotates the branch which was introduced in the new k'th cluster. This rotated tree is compared with the fixed tree, and if it has a better entanglement, it will be used for the following iterations.

This is a greedy forward selection algorithm for rotating the tree and looking for a better match.

This is useful for finding good trees for a [tanglegram](#).

Usage

```
untangle_step_rotate_1side(dend1, dend2_fixed, L = 1.5,
  direction = c("forward", "backward"), k_seq = NULL, dend_heights_per_k,
  leaves_matching_method = c("labels", "order"), ...)
```

Arguments

dend1	a dendrogram object. The one we will rotate to best fit dend2_fixed.
dend2_fixed	a dendrogram object. This one is kept fixed.
L	the distance norm to use for measuring the distance between the two trees. It can be any positive number, often one will want to use 0, 1, 1.5, 2 (see 'details' in entanglement).
direction	a character scalar, either "forward" (default) or "backward". Impacts the direction of clustering that are tried. Either from 2 and up (in case of "forward"), or from nleaves to down (in case of "backward") If k_seq is not NULL, then it overrides "direction".
k_seq	a sequence of k clusters to go through for improving dend1. If NULL (default), then we use the "direction" parameter.
dend_heights_per_k	a numeric vector of values which indicate which height will produce which number of clusters (k)

```
leaves_matching_method
  a character scalar passed to entanglement. It can be either "order" or "labels"
  (default). If using "labels", then we use the labels for matching the leaves order
  value. And if "order" then we use the old leaves order value for matching the
  leaves order value.
  Using "order" is faster, but "labels" is safer. "order" will assume that the original
  two trees had their labels and order values MATCHED.
  Hence, it is best to make sure that the trees used here have the same labels and
  the SAME values matched to these values - and then use "order" (for fastest
  results).
  If "order" is used, the function first calls match\_order\_by\_labels in order to make
  sure that the two trees have their labels synced with their leaves order values.
...      not used
```

Value

A dendlist with 1) dend1 after it was rotated to best fit dend2_fixed. 2) dend2_fixed.

See Also

[tanglegram](#), [match_order_by_labels](#), [entanglement](#), [flip_leaves](#), [all_couple_rotations_at_k](#), [untangle_step_rotate_2side](#).

Examples

```
## Not run:
dend1 <- USArrests[1:10,] %>% dist %>% hclust %>% as.dendrogram
set.seed(3525)
dend2 <- shuffle(dend1)
tanglegram(dend1,dend2)
entanglement(dend1,dend2, L = 2) # 0.4727

dend2_corrected <- untangle_step_rotate_1side(dend2, dend1)[[1]]
tanglegram(dend1,dend2_corrected) # FIXED.
entanglement(dend1,dend2_corrected, L = 2) # 0

## End(Not run)
```

untangle_step_rotate_2side

Stepwise untangle two trees one at a time

Description

This is a greedy forward selection algorithm for rotating the tree and looking for a better match.

This is useful for finding good trees for a [tanglegram](#).

It goes through rotating dend1, then dend2, and so on - until a locally optimal solution is found.

Usage

```
untangle_step_rotate_2side(dend1, dend2, L = 1.5, direction = c("forward",
  "backward"), max_n_iterations = 10L,
  print_times = dendextend_options("warn"), k_seq = NULL, ...)
```

Arguments

dend1	a dendrogram object. The one we will rotate to best fit dend2.
dend2	a dendrogram object. The one we will rotate to best fit dend1.
L	the distance norm to use for measuring the distance between the two trees. It can be any positive number, often one will want to use 0, 1, 1.5, 2 (see 'details' in entanglement).
direction	a character scalar, either "forward" (default) or "backward". Impacts the direction of clustering that are tried. Either from 2 and up (in case of "forward"), or from nleaves to down (in case of "backward") If k_seq is not NULL, then it overrides "direction".
max_n_iterations	integer. The maximal number of times to switch between optimizing one tree with another.
print_times	logical (TRUE), should we print how many times we switched between rotating the two trees?
k_seq	a sequence of k clusters to go through for improving dend1. If NULL (default), then we use the "direction" parameter.
...	not used

Value

A list with two dendrograms (dend1/dend2), after they are rotated to best fit one another.

See Also

[tanglegram](#), [match_order_by_labels](#), [entanglement](#), [flip_leaves](#), [all_couple_rotations_at_k](#). [untangle_step_rotate_1side](#).

Examples

```
## Not run:
dend1 <- USArrests[1:20,] %>% dist %>% hclust %>% as.dendrogram
dend2 <- USArrests[1:20,] %>% dist %>% hclust(method = "single") %>% as.dendrogram
set.seed(3525)
dend2 <- shuffle(dend2)
tanglegram(dend1,dend2, margin_inner=6.5)
entanglement(dend1,dend2, L = 2) # 0.79

dend2_corrected <- untangle_step_rotate_1side(dend2, dend1)
tanglegram(dend1,dend2_corrected, margin_inner=6.5) # Good.
entanglement(dend1,dend2_corrected, L = 2) # 0.0067
# it is better, but not perfect. Can we improve it?
```

```

dend12_corrected <- untangle_step_rotate_2side(dend1, dend2)
tanglegram(dend12_corrected[[1]],dend12_corrected[[2]], margin_inner=6.5) # Better...
entanglement(dend12_corrected[[1]],dend12_corrected[[2]], L=2) # 0.0045

# best combination:
dend12_corrected_1 <- untangle_random_search(dend1, dend2)
dend12_corrected_2 <- untangle_step_rotate_2side(dend12_corrected_1[[1]],dend12_corrected_1[[2]])
tanglegram(dend12_corrected_2[[1]],dend12_corrected_2[[2]], margin_inner=6.5) # Better...
entanglement(dend12_corrected_2[[1]],dend12_corrected_2[[2]], L=2) # 0 - PERFECT.

## End(Not run)

```

which_leaf	<i>Which node is a leaf?</i>
------------	------------------------------

Description

Gives a vector as the number of nodes ([nnodes](#)), which gives a TRUE when a node is a leaf.

Usage

```
which_leaf(dend, ...)
```

Arguments

dend	a dendrogram dend
...	ignored.

Value

A logical vector with the length of [nnodes](#), which gives a TRUE when a node is a leaf.

See Also

[noded_with_condition](#), [is.leaf](#), [nnodes](#)

Examples

```

## Not run:

library(dendextend)

# Getting the dend dend
set.seed(23235)
ss <- sample(1:150, 10 )
dend <- iris[ss,-5] %>% dist %>% hclust %>% as.dendrogram

```

```
dend %>% plot
which_leaf(dend)

## End(Not run)
```

which_node	<i>Which node id is common to a group of labels</i>
------------	---

Description

This function identifies which edge(s) in a tree has group of labels ("tips") in common. By default it only returns the edge (node) with the heighest id.

Usage

```
which_node(dend, labels, max_id = TRUE, ...)
```

Arguments

dend	a dendrogram dend
labels	a character vector of labels from the tree
max_id	logical (TRUE) - if to return only the max id
...	ignored.

Value

An integer with the id(s) of the nodes which includes all of the labels.

See Also

[noded_with_condition](#), [branches_attr_by_clusters](#), [nnodes](#), [branches_attr_by_labels](#), [get_nodes_attr](#) [which.edge](#)

Examples

```
dend <- iris[1:10,-5] %>% dist %>% hclust %>% as.dendrogram %>% set("labels", 1:10)
dend %>% plot

which_node(dend, c(1,2), max_id = FALSE)
which_node(dend, c(2,3), max_id = FALSE)
which_node(dend, c(2,3))

dend %>% plot
the_h <- get_nodes_attr(dend, "height", which_node(dend, c(4,6)))
the_h
abline(h = the_h, lty = 2, col = 2)
get_nodes_attr(dend, "height", which_node(dend, c(4,6)))
get_nodes_attr(dend, "members", which_node(dend, c(4,6)))
```

`%>%`*Pipe an object forward into a function call/expression.*

Description

Pipe an object forward into a function call/expression.

Usage

```
lhs %>% rhs
```

Arguments

lhs	The value to be piped
rhs	A function or expression

Source

This is just the imported function from the magrittr package. The documentation you should read for the `%>%` function can be found here: [pipe](#)

Adding the function in the package while importing it is a trick taken from the dplyr package (in the file chain.r)

The package could have also been placed in "Depends", But I wanted to keep it robust if at some point some other package will try to take over the symbol (not likely, but still).

See Also

[pipe](#)

Index

- *Topic **dendrogram**
 - dendextend-package, 4
- *Topic **package**,
 - dendextend-package, 4
- %>%, 153

- all.equal, 5
- all.equal.dendlist
 - (all.equal.dendrogram), 5
- all.equal.dendrogram, 5
- all.equal.phylo, 5
- all_couple_rotations_at_k, 6, 149, 150
- all_unique, 7
- apply, 136
- as.dendlist, 8
- as.dendrogram, 9
- as.ggdend (ggdend), 80
- as.hclust, 9, 15
- as.hclust.dendrogram, 9
- as.phylo, 9
- as.phylo.dendrogram, 9
- as.phylo.hclust, 9
- as_hclust_fixed, 15
- assign_dendextend_options, 10
- assign_values_to_branches_edgePar, 10,
56, 86, 120, 122, 129, 130
- assign_values_to_leaves_edgePar, 11
- assign_values_to_leaves_nodePar, 12, 14,
75, 76, 121, 129, 130
- assign_values_to_nodes_nodePar, 13, 129
- attr, 80, 104

- bakers_gamma_for_2_k_matrix, 15, 37
- Bk, 16, 19, 22
- Bk_permutations, 18, 22
- Bk_plot, 20
- branches_attr_by_clusters, 23, 30, 152
- branches_attr_by_labels, 23, 25, 106, 129,
130, 152
- branches_color (color_branches), 31

- click_rotate, 26
- clip, 119
- collapse_branch, 28
- color_branches, 31, 35, 43, 98, 129, 130
- color_clusters, 32
- color_labels, 34, 129
- colored_bars, 29
- colour_branches (color_branches), 31
- colour_labels (color_labels), 34
- cophenetic, 36, 40, 54, 126, 145
- cor, 39
- cor.dendlist, 36
- cor_bakers_gamma, 16, 17, 36, 37, 40, 66, 68,
70, 72, 99
- cor_cophenetic, 36, 38, 39, 135
- count_terminal_nodes, 41, 104, 105
- cut_lower_fun, 49
- cutree, 23, 31, 32, 35, 37, 42, 43, 44, 46, 48,
136
- cutree.dendrogram, 6, 32, 49, 50, 88, 119
- cutree_1h.dendrogram, 44, 46, 48
- cutree_1k.dendrogram, 44, 47
- cutreeDynamic, 23

- d3dendro_options, 50, 51, 51
- d3dendrogram, 50
- dend_diff, 55, 85
- dendbackback (tanglegram), 137
- dendextend (dendextend-package), 4
- dendextend-package, 4
- dendextend_cut_lower_fun
 - (cut_lower_fun), 49
- dendextend_get_branches_heights
 - (get_branches_heights), 72
- dendextend_heights_per_k.dendrogram
 - (heights_per_k.dendrogram), 84
- dendextend_options, 52
- dendlist, 5, 36, 53, 55, 56, 85, 88, 97, 129,
140, 144, 146
- dendrapply, 96

- dendro_data, 82
- dendrogram, 4, 5, 32, 35, 50, 55, 57, 81, 82, 87, 97, 109, 118, 129, 130, 132, 133
- DendSer, 54, 126, 146
- DendSer.dendrogram, 54, 54, 126, 146
- dist, 32, 56, 94, 135
- dist.dendlist, 56, 56, 57, 86, 109
- dist.multiPhylo, 56
- dist.topo, 56
- dist_long, 58
- distinct.edges, 56, 57, 86
- distinct_edges, 56, 57, 57, 86, 109
- drop.tip, 112
- duplicate_leaf, 58, 127

- entanglement, 7, 59, 64, 99–101, 132, 133, 145, 147–150

- fac2num, 62, 136
- fix_members_attr.dendrogram, 59, 62, 127
- flatten.dendrogram, 63
- flip_leaves, 7, 64, 149, 150
- FM_index, 17, 19, 22, 65, 68
- FM_index_permutation, 67
- FM_index_profdep, 16, 65, 66, 68, 69, 71, 72, 134
- FM_index_R, 16, 65, 68, 69, 71

- get_branches_heights, 72, 74, 117
- get_childrens_heights, 73, 117
- get_leaves_attr, 12–14, 23, 26, 74, 77, 106, 121
- get_leaves_nodePar, 75, 82
- get_nodes_attr, 75, 76, 76, 78, 82, 152
- get_nodes_xy, 78
- get_root_branches_attr, 11, 79, 120, 122
- ggdend, 80, 141
- ggdendrogram, 82
- ggplot, 81, 82
- ggplot.dendrogram (ggdend), 80
- ggplot.ggdend (ggdend), 80

- hang.dendrogram, 83, 116, 117, 129, 130, 140
- hclust, 4, 32, 35, 44, 46, 48, 94, 132, 133
- heights_per_k.dendrogram, 6, 84
- highlight_distinct_edges, 56, 57, 85, 86, 109

- identical, 5
- identify.dendrogram, 87
- identify.hclust, 87, 88
- intersect, 88
- intersect_trees, 36, 37, 39, 88
- is.dendlist, 89
- is.dendrogram, 90
- is.double, 91
- is.hclust, 90
- is.integer, 91
- is.leaf, 151
- is.natural.number, 91
- is.numeric, 91
- is.phylo, 92
- is_null_list, 92

- labels, 32, 50, 88, 95, 127
- labels.hclust (labels<-), 93
- labels.matrix, 95
- labels.matrix (labels<-), 93
- labels.phylo (labels<-), 93
- labels<-, 93
- labels<- .dendrogram, 129, 130
- labels_colors, 32, 35, 76, 95
- labels_colors<-, 130
- labels_colors<- (labels_colors), 95
- ladderize, 97, 97, 124, 125
- layout, 138
- leaf_Colors, 98
- leaf_colors (leaf_Colors), 98
- lowest_common_branch, 99

- match_order_by_labels, 7, 37, 61, 64, 99, 101, 147, 149, 150
- match_order_dendrogram_by_old_order, 100
- multi2di, 28

- na.locf, 102
- na_locf, 102
- names, 62
- nleaves, 23, 26, 75, 77, 78, 103, 105, 106, 143
- nnodes, 23, 26, 75, 77, 78, 104, 106, 151, 152
- noded_with_condition, 26, 105, 130, 151, 152
- nrow, 104, 105

- order, 124, 125
- order.dendrogram, 23, 88, 104, 107, 108, 119, 124, 125

order.dendrogram<-, 106
 order.hclust, 108

 par, 29, 119
 partition.leaves, 109
 partition_leaves, 108
 phylo, 97, 132, 133
 phylo.diff, 55
 pipe, 153
 plot, 21, 110
 plot.dendlist (dendlist), 53
 plot.dendrogram, 55, 78, 81, 110
 plot_horiz.dendrogram, 109, 140
 plotDendroAndColors, 23, 30
 plotHclustColors, 30
 prepare.ggdend (ggdend), 80
 prune, 88, 111, 112, 117
 prune_leaf, 112, 112
 pvclust_show_signif, 113, 113, 115
 pvclust_show_signif_gradient, 113, 114, 115

 rainbow, 32, 35
 rainbow_hcl, 32, 35
 raise.dendrogram, 116
 rank, 117
 rank_branches, 116, 140
 rank_order.dendrogram, 59, 117, 127
 rect, 118, 119
 rect.dendrogram, 118
 rect.hclust, 88, 119
 remove_branches_edgePar, 120, 130
 remove_leaves_nodePar, 121, 130, 140
 remove_nodes_nodePar, 122
 rev.dendrogram, 97, 124, 125
 rev.hclust (rotate), 123
 rllply, 122
 rotate, 97, 123, 125, 132, 133
 rotate.dendrogram, 27
 rotate_DendSer, 54, 126, 126, 146
 rownames, 32

 sample, 127
 sample.dendrogram, 127
 set, 128
 shuffle, 132
 simplify2array, 76
 slice, 32, 98
 sort, 136

 sort.dendrogram (rotate), 123
 sort.hclust (rotate), 123
 sort_2_clusters_vectors, 134
 sort_dist_mat, 135
 sort_levels_values, 44, 136
 stats, 4

 tanglegram, 6, 7, 56, 57, 61, 64, 85, 86, 100, 101, 109, 110, 117, 132, 133, 137, 145, 147–150
 theme_dendro, 81, 141
 treedist, 56

 unbranch, 142
 unclass_dend, 143
 unique, 7
 unroot, 142
 untangle, 144
 untangle_DendSer, 54, 126, 145, 146
 untangle_random_search, 145, 146
 untangle_step_rotate_1side, 145, 148, 150
 untangle_step_rotate_2side, 145, 149, 149

 which.edge, 152
 which_leaf, 151
 which_node, 152