

Package ‘exactLoglinTest’

January 27, 2015

Version 1.4.2

Title Monte Carlo Exact Tests for Log-linear models

Author Brian Caffo <bcaffo@gmail.com>

Maintainer Brian Caffo <bcaffo@gmail.com>

Depends R (>= 1.5)

Suggests stats

Description Monte Carlo and MCMC goodness of fit tests for log-linear models

License GPL

URL <http://www.bcaffo.com>

Repository CRAN

Date/Publication 2013-02-05 13:40:27

NeedsCompilation yes

R topics documented:

alligator.dat	2
czech.dat	2
gof	3
hyper	4
mcexact	4
mcexact.internals	6
pathologist.dat	8
print.mcexact	8
residence.dat	9
simulateConditional	10
titanic.dat	11
update.bab	12
update.cab	13

Index	15
--------------	-----------

alligator.dat	<i>Data frame of alligator food choice by lake, gender and size.</i>
---------------	--

Description

A 5x4x2x2 table of alligators food choice, lake, gender and size stored in a data frame.

Usage

```
data(alligator.dat)
```

Format

allgiator.dat is a data frame

References

Agresti (1990). *Categorical Data Analysis*. Wiley-Interscience. Page 308.

czech.dat	<i>Czech auto workers data</i>
-----------	--------------------------------

Description

Czech auto workers data

Usage

```
data(czech.dat)
```

Format

A data frame with 64 observations on the following 7 variables.

y a numeric vector

A a factor with levels no yes

B a factor with levels no yes

C a factor with levels no yes

D a factor with levels small large

E a factor with levels small large

F a factor with levels neg pos

Source

Edwards and Havranek (1985)

Examples

```
data(czech.dat)
```

gof*Goodness-of-fit function for Poisson log-linear models*

Description

A goodness-of-fit function for Poisson log-linear models as required by `mcexact`.

Usage

```
gof(y = NULL, mu = NULL, rowlabels = FALSE)
```

Arguments

<code>y</code>	counts
<code>mu</code>	mean
<code>rowlabels</code>	labels of returned goodness-of-fit statistics

Details

This function is a useful shell for writing alternative goodness-of-fit statistics for `mcexact`.

Value

If `rowlabels = TRUE`, then `gof` returns only the labels of the goodness of fit statistics. Otherwise it returns the actual values as a vector.

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

Examples

```
#data(residence)
#get fitted values
#mu <- glm(residence$y ~ residence$x, family = poisson)$fit
#gof(residence$y, mu)
#gof(rowlabels = TRUE)
```

hyper

Generalized hypergeometric distribution on the log scale

Description

Returns the log hypergeometric conditional probability of a vector of Poisson counts up to an additive constant of proportionality.

Usage

```
hyper(y)
```

Arguments

y Counts

Value

A real-valued scalar.

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

mcexact

Computes Monte Carlo exact P-values for general log-linear models.

Description

This function computes Monte Carlo estimates of conditional P-values for goodness of fit tests for general log-linear models.

Usage

```
mcexact(formula,  
        data,  
        stat = gof,  
        dens = hyper,  
        nosim = 10 ^ 3,  
        method = "bab",  
        savechain = FALSE,  
        tdf = 3,
```

```

      maxiter = nosim,
      p = NULL,
      batchsize = NULL)

build.mcx.obj(formula,
              data,
              stat = gof,
              dens = hyper,
              nosim = 10 ^ 3,
              method = "bab",
              savechain = FALSE,
              tdf = 3,
              maxiter = nosim,
              p = NULL,
              batchsize = NULL)

```

Arguments

formula	Null model formula specified as in <code>glm</code>
data	Data frame
stat	The test statistic, a function of the form <code>function(y, mu.hat)</code> where <code>y</code> is the observed and <code>mu.hat</code> are the fitted values. Current default <code>gof</code> is a bivariate function of the deviance and the Pearson chi-squared.
dens	The target density on the log scale up to a constant of proportionality. A function of the form <code>function(y)</code> . Current default is (proportional to) the log of the generalized hypergeometric density.
nosim	Desired number of simulations.
method	Possibly two values, the importance sampling method of Booth and Butler, <code>method = "bab"</code> or the MCMC approach of Caffo and Booth <code>method = "cab"</code> .
savechain	If TRUE saves the values of the chain.
tdf	A tuning parameter
maxiter	For <code>method = "bab"</code> number of iterations is different from the number of simulations. <code>maxiter</code> is a bound on the total number of iterations.
p	A tuning parameter for <code>method = "cab"</code> .
batchsize	Required batchsizes for <code>method = "cab"</code> .

Value

Returns a list of class either "bab" or "cab" depending on `method`. The list contains all of the inputs plus all required information to resume the simulation. Generic functions `print` and `summary` format the output while `update` can be used to resume simulations. `mcexact` is the front end while `build.mcx.obj` simply builds the basic object that `mcexact` applies to. `simulate.conditional` generates a matrix of simulated tables.

Author(s)

Brian Caffo

References

Booth and Butler (1999), "An importance sampling algorithm for exact conditional tests in log-linear models", *Biometrika* 86: 321-332.

Caffo and Booth (2001). "A Markov Chain Monte Carlo Algorithm for Approximating Exact Conditional Probabilities", *The Journal of Computational and Graphical Statistics* 10: 730-45.

<http://www.biostat.jhsph.edu/~bcaffo/downloads.htm>

See Also

[fisher.test](#)

Examples

```
#library(mcexact)
set.seed(1)

#importance sampling
data(residence.dat)
mcx <- mcexact(y ~ res.1985 + res.1980 + factor(sym.pair), data = residence.dat)
summary(mcx)

#mcmc
data(pathologist.dat)
mcx <- mcexact(y ~ factor(A) + factor(B) + I(A * B),
               data = pathologist.dat,
               method = "cab",
               p = .5,
               nosim = 10 ^ 4,
               batchsize = 100)
summary(mcx)
```

mcexact.internals *Internal functions for mcexact*

Description

Internal functions used for mcexact.

Usage

```
rounded.tprob(y, m, s, df)
errorcheck(y,
           x,
           stat,
           dens,
           nosim,
           method,
           savechain,
```

```
tdf,  
maxiter,  
p,  
batchsize)
```

Arguments

y	counts
m	means
s	variances
df	degrees of freedom
x	model matrix
stat	function to be checked
dens	function to be checked
nosim	number of simulations to be checked
method	method to be checked
savechain	savechain flag to be checked
tdf	t degrees of freedom to be checked
maxiter	maximum number of iterations to be checked
p	prop of table entries left fixed to be checked
batchsize	batchsize to be checked

Value

rounded.tprob returns rounded student's t probabilities for integers y with means m and variances s. errorcheck is a function containing most of the error checking that mcexact performs.

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

pathologist.dat	<i>Cross-classification of 118 tumor grades by two pathologists</i>
-----------------	---

Description

Data frame of a 5x5 table of pathologists ratings of 118 tumors. Each pathologist, A and B, rated the tumors on a scale of 1 to 5. y represents the counts of each combination of ratings.

Usage

```
data(pathologist.dat)
```

Format

A list containing y-the counts and x-the design matrix for the uniform association model.

References

Agresti (1990). *Categorical Data Analysis*. Wiley-Interscience. Page 368.

See Also

Page 263 of *Categorical Data Analysis* for a description of the uniform association model.

print.mcexact	<i>Print utilities for mcexact</i>
---------------	------------------------------------

Description

Generic print methods for objects of class cab and bab outputted from mcexact.

Usage

```
## S3 method for class 'bab'
print(x,...)
## S3 method for class 'bab'
summary(object,...)
```

Arguments

x	An object of class bab or cab
object	An object of class bab or cab
...	Unused, retained for generic method consistency

Value

print.bab and print.cab prints the P-value estimates obtained from mcexact. summary.bab and summary.cab prints extra information and returns a matrix of the P-value estimates.

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

Examples

```
#data(residence)
#resid.mcx <- mcexact(residence$y ~ residence$x, nosim = 10 ^ 2, maxiter = 10 ^ 4)
#resid.mcx #calls print.bab
#print(resid.mcx) #calls print.bab
#summary(resid.mcx) #calls summary.bab
```

residence.dat

Residence in 1980 by residence in 1985.

Description

A data frame of a 4x4 cross-classification of residences in 1980 by residence in 1985. residence\$y gives the counts, res.1985 and res.1980 give the 1980 and 1985 residences, sym.pair is used to fit the quasi-symmetry model.

Usage

```
data(residence.dat)
```

Format

A list containing y-the counts and x-the design matrix for the quasi-symmetry model.

References

Agresti (1990). *Categorical Data Analysis*. Wiley-Interscience. Page 357.

See Also

Page 354 of *Categorical Data Analysis* for a description of the quasi-symmetry model.

simulateConditional *Simulates from the conditional distribution of a log-linear model*

Description

Simulates from the conditional distribution of log-linear models given the sufficient statistics.

Usage

```
simulateConditional(formula,
                    data,
                    dens = hyper,
                    nosim = 10^3,
                    method = "bab",
                    tdf = 3,
                    maxiter = nosim,
                    p = NULL,
                    y.start = NULL)
simtable.bab(args, nosim = NULL, maxiter = NULL)
simtable.cab(args, nosim = NULL, p = NULL, y.start = NULL)
```

Arguments

formula	A formula for the log-linear model
data	A data frame
dens	The target density on the log scale up to a constant of proportionality. A function of the form $f(y)$. Current default is (proportional to) the log of the generalized hypergeometric density.
nosim	Desired number of simulations.
method	Possibly two values, the importance sampling method of Booth and Butler, <code>method = "bab"</code> or the MCMC approach of Caffo and Booth <code>method = "cab"</code> .
tdf	A tuning parameter
maxiter	For <code>method = "bab"</code> number of iterations is different from the number of simulations. <code>maxiter</code> is a bound on the total number of iterations.
p	A tuning parameter for <code>method = "cab"</code> .
y.start	An optional starting value when <code>method = "cab"</code>
args	An object of class "bab" or "cab"

Value

A matrix where each simulated table is a row.

Author(s)

Brian Caffo

See Also[fisher.test](#)**Examples**

```
data(czech.dat)
chain2 <- simulateConditional(y ~ (A + B + C + D + E + F) ^ 2,
                             data = czech.dat,
                             method = "cab",
                             nosim = 10 ^ 3,
                             p = .4,
                             dens = function(y) 0)
```

titanic.dat

Titanic Survival Data

Description

A data frame of counts of titanic passengers classified by class, age, sex and survival

Usage

```
data(titanic.dat)
```

Format

A data frame with 32 observations on the following 5 variables.

y a numeric vector

class a numeric vector

age a numeric vector

sex a numeric vector

surv a numeric vector

Source

Cytel web site <http://www.cytel.com>

Examples

```
data(titanic.dat)
```

`update.bab`*Update method for objects of class bab*

Description

An update method for objects created by `mcexact` when `method = 'bab'`.

Usage

```
## S3 method for class 'bab'
update(object, ...)
bab(args, nosim = NULL, maxiter = NULL, savechain = FALSE)
```

Arguments

<code>object</code>	Output from <code>mcexact</code>
<code>...</code>	Alternative arguments for the update
<code>args</code>	Output from <code>mcexact</code>
<code>nosim</code>	The desired number of simulations to be performed in the update
<code>maxiter</code>	The maximum number of iterations allowed.
<code>savechain</code>	Saves the chain of goodness-of-fit statistics and their importance weights

Details

The method `update.bab` calls the function `bab`, which is the engine for `mcexact` when `method = 'bab'`.

Value

A list of the form outputted from `mcexact`

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

Examples

```
data(residence.dat)
mcx <- mcexact(y ~ res.1985 + res.1980 + factor(sym.pair), data = residence.dat)
summary(mcx)
mcx <- update(mcx, nosim = 10 ^ 4, maxiter = 10 ^ 6)
summary(mcx)
```

update.cab	<i>Update method for objects of class cab</i>
------------	---

Description

An update method for objects created by mcexact when method = 'cab'.

Usage

```
## S3 method for class 'cab'  
update(object, ...)  
cab(args,  
     nosim = NULL,  
     batchsize = NULL,  
     savechain = FALSE,  
     p = NULL,  
     flush = FALSE)
```

Arguments

object	Output from mcexact
...	Alternative arguments for the update
args	Output from mcexact
nosim	The number of simulations to be performed in the update
batchsize	A new batchsize
savechain	Saves the chain of goodness-of-fit statistics
p	An updated proportion of simulated tables left fixed.
flush	Should the previous information be discarded? flush should be set to true if the batchsize is changed.

Details

The method update.cab calls the function cab, which is the engine for mcexact when method = 'cab'.

Value

A list of the form outputted from mcexact

Author(s)

Brian S. Caffo

See Also

[mcexact](#)

Examples

```
data(residence.dat)
mcx <- mcexact(y ~ res.1985 + res.1980 + factor(sym.pair),
              data = residence.dat,
              method = "cab",
              p = .5,
              batchsize = 100)
summary(mcx)
mcx <- update(mcx, nosim = 10 ^ 4)
summary(mcx)
```

Index

*Topic **datasets**

- alligator.dat, 2
- czech.dat, 2
- pathologist.dat, 8
- residence.dat, 9
- titanic.dat, 11

*Topic **htest**

- gof, 3
- hyper, 4
- mcexact, 4
- mcexact.internals, 6
- print.mcexact, 8
- simulateConditional, 10
- update.bab, 12
- update.cab, 13

alligator.dat, 2

bab (update.bab), 12
build.mcx.obj (mcexact), 4

cab (update.cab), 13
czech.dat, 2

errorcheck (mcexact.internals), 6

fisher.test, 6, 11

gof, 3

hyper, 4

mcexact, 3, 4, 4, 7, 9, 12, 13
mcexact.internals, 6

pathologist.dat, 8
print.bab (print.mcexact), 8
print.babSummary (print.mcexact), 8
print.cab (print.mcexact), 8
print.cabSummary (print.mcexact), 8
print.mcexact, 8

residence.dat, 9

rounded.tprob (mcexact.internals), 6

simtable.bab (simulateConditional), 10
simtable.cab (simulateConditional), 10
simulateConditional, 10

summary.bab (print.mcexact), 8
summary.cab (print.mcexact), 8

titanic.dat, 11

update.bab, 12
update.cab, 13