

Package ‘myTAI’

July 31, 2015

Type Package

Title Performing Phylotranscriptomics with R

Version 0.3.0

Date 2015-07-22

Author Hajk-Georg Drost

Maintainer Hajk-Georg Drost <hajk-georg.drost@informatik.uni-halle.de>

Description A statistical framework allowing users interested in the evolution of biological processes to capture evolutionary signals in transcriptomes.

VignetteBuilder knitr

NeedsCompilation yes

License GPL-3

Depends R (>= 3.1.1)

Imports Rcpp (>= 0.11.3), nortest (>= 1.0-2), fitdistrplus (>= 1.0-2), parallel (>= 3.1.1), foreach (>= 1.4.2), doParallel (>= 1.0.8), dplyr (>= 0.3.0), RColorBrewer (>= 1.1-2), taxize (>= 0.6.0), edgeR, methods (>= 3.1.1), graphics (>= 3.1.1), stats (>= 3.1.1), grDevices (>= 3.1.1), utils (>= 3.1.1), reshape2 (>= 1.4.1), ggplot2 (>= 1.0.1)

Suggests knitr (>= 1.6), rmarkdown (>= 0.3.3), devtools (>= 1.6.1), testthat (>= 0.9.1)

LinkingTo Rcpp

URL <https://github.com/HajkD/myTAI>

BugReports <https://github.com/HajkD/myTAI/issues>

Repository CRAN

Date/Publication 2015-07-31 00:53:26

R topics documented:

age.apply	3
bar.colors	4
bootMatrix	5
CollapseReplicates	6
CombinatorialSignificance	7
DiffGenes	9
DivergenceExpressionSetExample	12
EarlyConservationTest	13
ecScore	16
EnrichmentTest	17
Expressed	18
FlatLineTest	21
geom.mean	23
harm.mean	24
is.ExpressionSet	24
MatchMap	25
omitMatrix	27
PhyloExpressionSetExample	28
PlotBarRE	29
PlotCategoryExpr	31
PlotContribution	34
PlotCorrelation	35
PlotDistribution	37
PlotEnrichment	38
PlotGeneSet	41
PlotMeans	42
PlotPattern	44
PlotRE	47
PlotReplicateQuality	50
pMatrix	51
pStrata	52
pTAI	53
pTDI	54
RE	55
ReductiveHourglassTest	56
REMatrix	59
rhScore	60
SelectGeneSet	62
TAI	63
taxonomy	65
TDI	66
tf	67

`age.apply`*Age Category Specific apply Function*

Description

This function performs the split-apply-combine methodology on Phylostrata or Divergence Strata stored within the input ExpressionSet.

This function is very useful to perform any phylostratum or divergence-stratum specific analysis.

Usage

```
age.apply(ExpressionSet, FUN, ..., as.list = FALSE)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
FUN	a function to be performed on the corresponding expression matrix of each phylostratum or divergence-stratum.
...	additional arguments of FUN.
as.list	a boolean value specifying whether the output format shall be a matrix or a list object.

Details

This function uses the [split](#) function to subset the expression matrix into phylostratum specific sub-matrices. Internally using [lapply](#), any function can be performed to the sub-matrices. The return value of this function is a numeric matrix storing the return values by FUN for each phylostratum and each developmental stage *s*. Note that the input FUN must be an function that can be applied to a matrix (e.g., [colMeans](#) or [RE](#)). In case you use an anonymous function you could use `function(x) apply(x, 2, var)` as an example to compute the variance of each phylostratum and each developmental stage *s*.

Value

Either a numeric matrix storing the return values of the applied function for each age class or a numeric list storing the return values of the applied function for each age class in a list.

Author(s)

Hajk-Georg Drost

See Also

[split](#), [tapply](#), [lapply](#), [RE](#), [REMatrix](#)

Examples

```
# source the example dataset
data(PhyloExpressionSetExample)

# Example 1
# get the relative expression profiles for each phylostratum
age.apply(PhyloExpressionSetExample, RE)

# this is analogous to
REMatrix(PhyloExpressionSetExample)
# Example 2
# compute the mean expression profiles for each phylostratum
age.apply(PhyloExpressionSetExample, colMeans)

# Example 3
# compute the variance profiles for each phylostratum
age.apply(PhyloExpressionSetExample, function(x) apply(x , 2 , var))

# Example 4
# compute the range for each phylostratum
# Note: in this case, the range() function returns 2 values for each phylostratum
# and each developmental stage, hence one should use the argument 'as.list = TRUE'
# to make sure that the results are returned properly
age.apply(PhyloExpressionSetExample, function(x) apply(x , 2 , range), as.list = TRUE)
```

bar.colors

Color palette for barplots

Description

A nice color palette for barplots with several bars.

Usage

```
bar.colors(n)
```

Arguments

n the number of colors to be in the palette.

Details

This function can be used to select colors for bar plots.

Value

a character vector containing different color names that can be used for barplots.

Author(s)

Hajk-Georg Drost

Examples

```
# get 5 different colors for 5 different bars
barplot_colors <- bar.colors(5)
```

bootMatrix

Compute a Permutation Matrix for Test Statistics

Description

This function computes the TAI for a row permuted PhyloExpressionSet or DivergenceExpressionSet.

One can specify the number of permutations which corresponds to the number of [TAI](#) or [TDI](#) profiles that are being returned as data matrix. The function then returns a TAI or TDI matrix holding the TAI or TDI profiles of the permuted PhyloExpressionSets or DivergenceExpressionSets. This procedure can be used for building test statistics based on the TAI or TDI profiles.

Usage

```
bootMatrix(ExpressionSet, permutations = 1000)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet object.
permutations a numeric value specifying the number of permutations to be performed.

Details

The sampled [TAI](#) or [TDI](#) matrix samples the phylostratum or divergence-stratum vector of a given PhyloExpressionSet or DivergenceExpressionSet and computes the corresponding TAI or TDI profiles of the randomly assigned phylostrata or divergence-strata. This sampling is then performed N times, yielding N randomly sampled TAI or TDI profiles. This random TAI or TDI profile matrix can then be used to perform statistical tests (such as the [FlatLineTest](#), [ReductiveHourglassTest](#), or [EarlyConservationTest](#)) based on the significance of TAI or TDI patterns.

Value

a numeric matrix representing N randomly permuted TAI or TDI profiles.

Author(s)

Hajk-Georg Drost

References

- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
- Drost HG et al. (2015). *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[FlatLineTest](#), [ReductiveHourglassTest](#), [EarlyConservationTest](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet using 100 permutations
randomTAI.Matrix <- bootMatrix(PhyloExpressionSetExample, permutations = 100)

# example DivergenceExpressionSet using 100 permutations
randomTDI.Matrix <- bootMatrix(DivergenceExpressionSetExample, permutations = 100)
```

CollapseReplicates *Combine Replicates in an ExpressionSet*

Description

This function takes an ExpressionSet object storing either a constant or variable number of biological or technical replicates per stage and collapses replicate expression levels using a defined FUN (window function).

Usage

```
CollapseReplicates(ExpressionSet, nrep, FUN, stage.names = NULL)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
nrep	either a numeric value specifying the constant number of replicates per stage or a numeric vector specifying the variable number of replicates for each stage position.
FUN	a window function (e.g., mean , median , max , min , etc.) specifying how replicate expression levels should be collapsed.
stage.names	a character vector specifying the new names of collapsed stages.

Author(s)

Hajk-Georg Drost

Examples

```

data(PhyloExpressionSetExample)

# combine the expression levels of the 2 replicates (const) per stage
# using mean as window function and rename new stages: "S1", "S2", "S3"
CollapseReplicates(ExpressionSet = PhyloExpressionSetExample[1:5,1:8],
                   nrep         = 2,
                   FUN           = mean,
                   stage.names   = c("S1", "S2", "S3"))

# combine the expression levels of the 2 replicates (stage one), 2 replicates (stage two),
# and 3 replicates (stage three) using mean as window function
# and rename new stages: "S1", "S2", "S3"
CollapseReplicates(ExpressionSet = PhyloExpressionSetExample[1:5,1:9],
                   nrep         = c(2,2,3),
                   FUN           = mean,
                   stage.names   = c("S1", "S2", "S3"))

```

CombinatorialSignificance

Compute the Statistical Significance of Each Replicate Combination

Description

In case a `PhyloExpressionSet` or `DivergenceExpressionSet` stores replicates for each developmental stage or experiment, this function allows to compute the p-values quantifying the statistical significance of the underlying pattern for all combinations of replicates.

Usage

```

CombinatorialSignificance(ExpressionSet, replicates,
                          TestStatistic = "FlatLineTest", permutations = 1000, parallel = FALSE)

```

Arguments

<code>ExpressionSet</code>	a standard <code>PhyloExpressionSet</code> or <code>DivergenceExpressionSet</code> object.
<code>replicates</code>	a numeric vector storing the number of replicates within each developmental stage or experiment. In case replicate stores only one value, then the function assumes that each developmental stage or experiment stores the same number of replicates.
<code>TestStatistic</code>	a string defining the type of test statistics to be used to quantify the statistical significance the present phylotranscriptomics pattern. Default is <code>TestStatistic = "FlatLineTest"</code> .
<code>permutations</code>	a numeric value specifying the number of permutations to be performed for the FlatLineTest .
<code>parallel</code>	a boolean value specifying whether parallel processing (multicore processing) shall be performed.

Details

The intention of this analysis is to validate that there exists no sequence of replicates (for all possible combination of replicates) that results in a non-significant pattern, when the initial pattern with combined replicates was shown to be significant.

A small Example:

Assume `PhyloExpressionSet` stores 3 developmental stages with 3 replicates measured for each stage. The 9 replicates in total are denoted as: 1.1, 1.2, 1.3, 2.1, 2.2, 2.3, 3.1, 3.2, 3.3. Now the function computes the statistical significance of each pattern derived by the corresponding combination of replicates, e.g.

- 1.1, 2.1, 3.1 -> p-value for combination 1
- 1.1, 2.2, 3.1 -> p-value for combination 2
- 1.1, 2.3, 3.1 -> p-value for combination 3
- 1.2, 2.1, 3.1 -> p-value for combination 4
- 1.2, 2.1, 3.1 -> p-value for combination 5
- 1.2, 2.1, 3.1 -> p-value for combination 6
- 1.3, 2.1, 3.1 -> p-value for combination 7
- 1.3, 2.2, 3.1 -> p-value for combination 8
- 1.3, 2.3, 3.1 -> p-value for combination 9
- ...

This procedure yields 27 p-values for the 3^3 ($n_s \text{ stages}_r^n \text{ replicates}$) replicate combinations.

Note, that in case you have a large amount of stages/experiments and a large amount of replicates the computation time will increase by $n_s \text{ stages}_r^n \text{ replicates}$. For 11 stages and 4 replicates, $4^{11} = 4194304$ p-values have to be computed. Each p-value computation itself is based on a permutation test running with 1000 or more permutations. Be aware that this might take some time.

The p-value vector returned by this function can then be used to plot the p-values to see whether an critical value α is exceeded or not (e.g. $\alpha = 0.05$).

The function receives a standard `PhyloExpressionSet` or `DivergenceExpressionSet` object and a vector storing the number of replicates present in each stage or experiment. Based on these arguments the function computes all possible replicate combinations using the `expand.grid` function and performs a permutation test (either a `FlatLineTest` for each replicate combination. The *permutation* parameter of this function specifies the number of permutations that shall be performed for each permutation test. When all p-values are computed, a numeric vector storing the corresponding p-values for each replicate combination is returned.

In other words, for each replicate combination present in the `PhyloExpressionSet` or `DivergenceExpressionSet` object, the TAI or TDI pattern of the corresponding replicate combination is tested for its statistical significance based on the underlying test statistic.

This function is also able to perform all computations in parallel using multicore processing. The underlying statistical tests are written in C++ and optimized for fast computations.

Value

a numeric vector storing the p-values returned by the underlying test statistic for all possible replicate combinations.

Author(s)

Hajk-Georg Drost

References

Drost HG et al. (2015). *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. *Mol Biol Evol.* 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[expand.grid](#), [FlatLineTest](#)

Examples

```
# load a standard PhyloExpressionSet
data(PhyloExpressionSetExample)

# we assume that the PhyloExpressionSetExample
# consists of 3 developmental stages
# and 2 replicates for stage 1, 3 replicates for stage 2,
# and 2 replicates for stage 3
# FOR REAL ANALYSES PLEASE USE: permutations = 1000 or 10000
# BUT NOTE THAT THIS TAKES MUCH MORE COMPUTATION TIME
p.vector <- CombinatorialSignificance(ExpressionSet = PhyloExpressionSetExample,
                                     replicates   = c(2,3,2),
                                     TestStatistic = "FlatLineTest",
                                     permutations = 10,
                                     parallel     = FALSE)
```

 DiffGenes

Differential Gene Expression Analysis

Description

Detect differentially expressed genes (DEGs) in a standard ExpressionSet object.

Usage

```
DiffGenes(ExpressionSet, nrep, method = "foldchange", lib.size = NULL,
           p.adjust.method = NULL, comparison = NULL, alpha = NULL,
           filter.method = NULL, n = NULL, stage.names = NULL)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet object.
 nrep either a numeric value specifying the constant number of replicates per stage or a numeric vector specifying the variable number of replicates for each stage position.

method	method to detect differentially expressed genes.
lib.size	the library sizes to equalize library sizes by quantile-to-quantile normalization (see equalizeLibSizes).
p.adjust.method	p value correction method.
comparison	a character string specifying whether genes having fold-change or p-values below, above, or below AND above (both) the alpha value should be excluded from the dataset. In case comparison = "both" is chosen, the cut.off argument must be a two dimensional vector defining the lower alpha value at the first position and the upper alpha value at the second position.
alpha	a numeric value specifying the cut-off value above which Genes fulfilling the corresponding fold-change, log-fold-change, or p-value should be retained and returned by DiffGenes.
filter.method	a method how to alpha values in multiple stages. Options are "const", "min-set", and "n-set".
n	a numeric value for method = "n-set".
stage.names	a character vector specifying the new names of collapsed stages.

Details

All methods to perform detection of differentially expressed genes assume that your input dataset has been normalized before passing it to *DiffGenes*. For RNA-Seq data *DiffGenes* assumes that the libraries have been normalized to have the same size, i.e., to have the same expected column sum under the null hypothesis. If this isn't the case please run [equalizeLibSizes](#) before calling *DiffGenes*.

Available methods for the detection of differentially expressed genes:

- method = "foldchange": ratio of replicate geometric means between developmental stages. Here, the *DiffGenes* functions assumes that absolute expression levels are stored in your input *ExpressionSet*.
- method = "log-foldchange": difference of replicate arithmetic means between developmental stages. Here, the *DiffGenes* functions assumes that *log2a* transformed expression levels are stored in your input *ExpressionSet*.
- method = "t.test": Welch t.test between replicate expression levels of two samples.
- method = "wilcox.test": Wilcoxon Rank Sum Test between replicate expression levels of two samples.
- method = "doubletail": Computes two-sided p-values by doubling the smaller tail probability (see [exactTestDoubleTail](#) for details).
- method = "smallp": Performs the method of small probabilities as proposed by Robinson and Smyth (2008) (see [exactTestBySmallP](#) for details).
- method = "deviance": Uses the deviance goodness of fit statistics to define the rejection region, and is therefore equivalent to a conditional likelihood ratio test (see [exactTestByDeviance](#) for details).

Exclude non differentially expressed genes from the result dataset:

When specifying the alpha argument you furthermore, need to specify the `filter.method` to decide how non differentially expressed genes should be classified in multiple sample comparisons and which genes should be retained in the final dataset returned by `DiffGenes`. In other words, all genes $< \alpha$ based on the following `filter.method` are removed from the result dataset.

Following extraction criteria are implemented in this function:

- `const`: all genes that have at least one sample comparison that undercuts or exceeds the alpha value `cut.off` will be excluded from the `ExpressionSet`. Hence, for a 7 stage `ExpressionSet` genes passing the alpha threshold in 6 stages will be retained in the `ExpressionSet`.
- `min-set`: genes passing the alpha value in `ceiling(n/2)` stages will be retained in the `ExpressionSet`, where n is the number of stages in the `ExpressionSet`.
- `n-set`: genes passing the alpha value in n stages will be retained in the `ExpressionSet`. Here, the argument n needs to be specified.

Note

In case input `ExpressionSet` objects store 0 values, internally all expression levels are shifted by +1 to allow sufficient fold-change and p-value computations. Additionally, a warning is printed to the console in case expression levels have been automatically shifted.

Author(s)

Hajk-Georg Drost

See Also

[Expressed](#)

Examples

```
data(PhyloExpressionSetExample)

# Detection of DEGs using the fold-change measure
DEGs <- DiffGenes(ExpressionSet = PhyloExpressionSetExample[,1:8],
                  nrep         = 2,
                  comparison    = "below",
                  method        = "foldchange",
                  stage.names   = c("S1", "S2", "S3"))

head(DEGs)

# Detection of DEGs using the log-fold-change measure
# when choosing method = "log-foldchange" it is assumed that
# your input expression matrix stores log2 expression levels
log.DEGs <- DiffGenes(ExpressionSet = tf(PhyloExpressionSetExample[1:5,1:8],log2),
                      nrep         = 2,
                      comparison    = "below",
```

```

method          = "log-foldchange",
stage.names     = c("S1", "S2", "S3")

head(log.DEGs)

# Remove fold-change values < 2 from the dataset:

## first have a look at the range of fold-change values of all genes
apply(DEGs[ , 3:8], 2, range)

# now remove genes undercutting the alpha = 2 threshold
# hence, remove genes having p-values <= 0.05 in at
# least one sample comparison
DEGs.alpha <- DiffGenes(ExpressionSet = PhyloExpressionSetExample[1:250 , 1:8],
                        nrep         = 2,
                        method        = "t.test",
                        alpha         = 0.05,
                        comparison     = "above",
                        filter.method = "n-set",
                        n              = 1,
                        stage.names    = c("S1", "S2", "S3"))

# now again have a look at the range and find
# that fold-change values of 2 are the min value
apply(DEGs.alpha[ , 3:5], 2, range)

# now check whether each example has at least one stage with a p-value <= 0.05
head(DEGs.alpha)

```

DivergenceExpressionSetExample

An Example DivergenceExpressionSet Data Set

Description

A standard DivergenceExpressionSet is a `data.frame` consisting of a standardized sequence of columns to store the age information for each gene and its corresponding gene expression profile.

The standard is defined as follows:

Divergencestratum | GeneID | Expression-level 1 | ... | Expression-level N

Details

This example DivergenceExpressionSet dataset covers 7 developmental stages of *Arabidopsis thaliana* embryo development. The initial gene expression dataset was published by Xiang et al., 2011 (see references section) and was then used by Quint et al., 2012 (see references section) to assign sequence divergence values (divergence strata) to each gene expression profile.

Value

a standard DivergenceExpressionSet object.

Author(s)

Hajk-Georg Drost

Source

<http://www.plantphysiol.org/content/156/1/346/suppl/DC1>

References

Quint M et al. 2012. "A transcriptomic hourglass in plant embryogenesis". Nature (490): 98-101. Supplementary Table 2 : <http://www.nature.com/nature/journal/v490/n7418/full/nature11394.html>

Xiang D et al. 2011. "Genome-Wide Analysis Reveals Gene Expression and Metabolic Network Dynamics during Embryo Development in Arabidopsis". Plant Physiology (156): 346-356. Supplemental Table 1 : <http://www.plantphysiol.org/content/156/1/346/suppl/DC1>

See Also

[PhyloExpressionSetExample](#)

EarlyConservationTest *Perform the Reductive Early Conservation Test*

Description

The *Reductive Early Conservation Test* aims to statistically evaluate the existence of a monotonically increasing phylotranscriptomic pattern based on **TAI** or **TDI** computations. The corresponding p-value quantifies the probability that a given TAI or TDI pattern (or any phylotranscriptomics pattern) does not follow an early conservation like pattern. A p-value < 0.05 indicates that the corresponding phylotranscriptomics pattern does indeed follow an early conservation (low-high-high) shape.

Usage

```
EarlyConservationTest(ExpressionSet, modules = NULL, permutations = 1000,  
  lillie.test = FALSE, plotHistogram = FALSE, runs = 10,  
  parallel = FALSE, gof.warning = FALSE, custom.perm.matrix = NULL)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
modules	a list storing three elements: early, mid, and late. Each element expects a numeric vector specifying the developmental stages or experiments that correspond to each module. For example, <code>module = list(early = 1:2, mid = 3:5, late = 6:7)</code> divides a dataset storing seven developmental stages into 3 modules.
permutations	a numeric value specifying the number of permutations to be performed for the ReductiveHourglassTest.
lillie.test	a boolean value specifying whether the Lilliefors Kolmogorov-Smirnov Test shall be performed to quantify the goodness of fit.
plotHistogram	a boolean value specifying whether a <i>Lillifor's Kolmogorov-Smirnov-Test</i> shall be performed to test the goodness of fit of the approximated distribution, as well as additional plots quantifying the significance of the observed phylotranscriptomic pattern.
runs	specify the number of runs to be performed for goodness of fit computations, in case <code>plotHistogram = TRUE</code> . In most cases <code>runs = 100</code> is a reasonable choice. Default is <code>runs = 10</code> (because it takes less computation time for demonstration purposes).
parallel	performing runs in parallel (takes all cores of your multicore machine).
gof.warning	a logical value indicating whether non significant goodness of fit results should be printed as warning. Default is <code>gof.warning = FALSE</code> .
custom.perm.matrix	a custom <code>bootMatrix</code> (permutation matrix) to perform the underlying test statistic. Default is <code>custom.perm.matrix = NULL</code> .

Details

The *reductive early conservation test* is a permutation test based on the following test statistic.

- (1) A set of developmental stages is partitioned into three modules - early, mid, and late - based on prior biological knowledge.
- (2) The mean `TAI` or `TDI` value for each of the three modules `T_early`, `T_mid`, and `T_late` are computed.
- (3) The two differences $D1 = T_{mid} - T_{early}$ and $D2 = T_{late} - T_{early}$ are calculated.
- (4) The minimum `D_min` of `D1` and `D2` is computed as final test statistic of the reductive hourglass test.

In order to determine the statistical significance of an observed minimum difference `D_min` the following permutation test was performed. Based on the `bootMatrix` `D_min` is calculated from each of the permuted `TAI` or `TDI` profiles, approximated by a Gaussian distribution with method of moments estimated parameters returned by `fitdist`, and the corresponding p-value is computed by `pnorm` given the estimated parameters of the Gaussian distribution. The *goodness of fit* for the random vector `D_min` is statistically quantified by an Lilliefors (Kolmogorov-Smirnov) test for normality.

In case the parameter `plotHistogram = TRUE`, a multi-plot is generated showing:

- (1) A Cullen and Frey skewness-kurtosis plot generated by `descdist`. This plot illustrates which distributions seem plausible to fit the resulting permutation vector `D_min`. In the case of the *reductive early conservation test* a normal distribution seemed plausible.
- (2) A histogram of `D_min` combined with the density plot is plotted. `D_min` is then fitted by a normal distribution. The corresponding parameters are estimated by *moment matching estimation* using the `fitdist` function.
- (3) A plot showing the p-values for N independent runs to verify that a specific p-value is biased by a specific permutation order.
- (4) A barplot showing the number of cases in which the underlying goodness of fit (returned by Lilliefors (Kolmogorov-Smirnov) test for normality) has shown to be significant (TRUE) or not significant (FALSE). This allows to quantify the permutation bias and their implications on the goodness of fit.

Value

a list object containing the list elements:

`p.value` : the p-value quantifying the statistical significance (low-high-high pattern) of the given phylotranscriptomics pattern.

`std.dev` : the standard deviation of the N sampled phylotranscriptomics patterns for each developmental stage S.

`lillie.test` : a boolean value specifying whether the *Lillifors KS-Test* returned a p-value > 0.05, which indicates that fitting the permuted scores with a normal distribution seems plausible.

Author(s)

Hajk-Georg Drost

References

- Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.
- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
- Piasecka B, Lichocki P, Moretti S, et al. (2013) *The hourglass and the early conservation models co-existing patterns of developmental constraints in vertebrates*. PLoS Genet. 9(4): e1003476.

See Also

[ecScore](#), [bootMatrix](#), [FlatLineTest](#), [ReductiveHourglassTest](#) , [PlotPattern](#)

Examples

```
data(PhyloExpressionSetExample)

# perform the early conservation test for a PhyloExpressionSet
# here the prior biological knowledge is that stages 1-2 correspond to module 1 = early,
# stages 3-5 to module 2 = mid (phylotypic module), and stages 6-7 correspond to
# module 3 = late
EarlyConservationTest(PhyloExpressionSetExample,
```

```

modules = list(early = 1:2, mid = 3:5, late = 6:7),
permutations = 1000)

# use your own permutation matrix based on which p-values (EarlyConservationTest)
# shall be computed
custom_perm_matrix <- bootMatrix(PhyloExpressionSetExample,100)

EarlyConservationTest(PhyloExpressionSetExample,
                      modules = list(early = 1:2, mid = 3:5, late = 6:7),
                      custom.perm.matrix = custom_perm_matrix)

```

ecScore

Compute the Hourglass Score for the EarlyConservationTest

Description

This function computes the EarlyConservationTest score for a given [TAI](#) or [TDI](#) pattern.

The reductive early conservation test is a permutation test based on the following test statistic.

- A set of developmental stages is partitioned into three modules - early, mid, and late - based on prior biological knowledge.
- The mean [TAI](#) or [TDI](#) value for each of the three modules T_{early} , T_{mid} , and T_{late} are computed.
- The two differences $D1 = T_{\text{mid}} - T_{\text{early}}$ and $D2 = T_{\text{late}} - T_{\text{early}}$ are calculated.
- The minimum D_{min} of $D1$ and $D2$ is computed as final test statistic of the reductive hourglass test.

This function *ecScore* computes the D_{min} value for a given [TAI](#) or [TDI](#) stored in the `age_vals` argument.

Usage

```
ecScore(age_vals, early, mid, late)
```

Arguments

<code>age_vals</code>	a numeric vector containing TAI or TDI values for each developmental stage s .
<code>early</code>	a numeric vector storing the numeric stage values that correspond to the early phase of development.
<code>mid</code>	a numeric vector storing the numeric stage values that correspond to the middle phase of development.
<code>late</code>	a numeric vector storing the numeric stage values that correspond to the late phase of development.

Value

a numeric value representing the early conservation score.

Author(s)

Hajk-Georg Drost

See Also[EarlyConservationTest](#), [TAI](#), [TDI](#)**Examples**

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# Example PhyloExpressionSet:

# compute the TAI profile
TAIs <- TAI(PhyloExpressionSetExample)

# compute the early conservation score for the TAI profile
ec_score <- ecScore(age_vals = TAIs,early = 1:2,mid = 3:5,late = 6:7)

# Example DivergenceExpressionSet:

# compute the TDI profile
TDIs <- TDI(DivergenceExpressionSetExample)

# compute the early conservation score for the TDI profile
ec_score <- ecScore(age_vals = TDIs,early = 1:2,mid = 3:5,late = 6:7)

# compute ecScore() vector from bootMatrix()
apply(bootMatrix(PhyloExpressionSetExample,10),1,ecScore,early = 1:2,mid = 3:5,late = 6:7)
```

EnrichmentTest	<i>Phylostratum or Divergence Stratum Enrichment of a given Gene Set based on Fisher's Test</i>
----------------	---

Description

This function computes the significance of enriched (over or underrepresented) Phylostrata or Divergence Strata within an input test.set based on the [fisher.test](#). Please consult [PlotEnrichment](#) for details.

Usage

```
EnrichmentTest(ExpressionSet, test.set, use.only.map = FALSE,
  measure = "log-foldchange", complete.bg = TRUE, epsilon = 1e-05)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
test.set	a character vector storing the gene ids for which PS/DS enrichment analyses should be performed.
use.only.map	a logical value indicating whether instead of a standard ExpressionSet only a Phylostratigraphic Map or Divergene Map is passed to this function.
measure	a character string specifying the measure that should be used to quantify over and under representation of PS/DS. Measures can either be measure = "foldchange" (odds) or measure = "log-foldchange" (log-odds).
complete.bg	a logical value indicating whether the entire background set of the input ExpressionSet should be considered when performing Fisher's exact test (complete.bg = TRUE) or whether genes that are stored in test.set should be excluded from the background set before performing Fisher's exact test (complete.bg = FALSE).
epsilon	a small value to shift values by epsilon to avoid log(0) computations.

Author(s)

Hajk-Georg Drost

See Also

[PlotEnrichment](#), [fisher.test](#)

Examples

```
data(PhyloExpressionSetExample)

set.seed(123)
test_set <- sample(PhyloExpressionSetExample[, 2], 1000)

E.Result <- EnrichmentTest(ExpressionSet = PhyloExpressionSetExample,
                           test.set     = test_set ,
                           measure      = "log-foldchange")

# get the log-fold change table
E.Result$enrichment.matrix

# get P-values for the enrichment significance for each Phylostratum
E.Result$p.values
```

Description

This function takes an ExpressionSet object and removes genes from the gene expression matrix that have an expression level below, above, or below AND above a defined cut.off value. Hence, this function allows to remove genes that have been defined as *not expressed* or *outliers* and returns an ExpressionSet retaining only expressed genes.

Usage

```
Expressed(ExpressionSet, cut.off, method = "const", comparison = "below",
          n = NULL)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
cut.off	a numeric value specifying the expression cut-off to define genes as <i>not expressed</i> (comparison = "below"), <i>outliers</i> (comparison = "above"), or both (comparison = "both"). See comparison for details. In case comparison = "both", the cut.off argument must be a two dimensional vector defining the lower cut.off value at the first position and the upper cut.off value at the second position.
method	a method defining how to treat gene expression values in multiple stages. The corresponding method that is chosen allows to control the stage-wise fulfillment of the threshold criteria. Options are "const", "min-set", and "n-set".
comparison	a character string specifying whether genes having expression levels below, above, or below AND above (both) the cut.off value should be excluded from the dataset. In case comparison = "both" is chosen, the cut.off argument must be a two dimensional vector defining the lower cut.off value at the first position and the upper cut.off value at the second position.
n	a numeric value for method = "n-set".

Details

This filter function allows users to remove genes from the ExpressionSet object that undercut or exceed a certain expression level cut.off.

Following extraction criteria are implemented in this function:

- **const**: all genes that have at least one stage that undercuts or exceeds the expression cut.off will be excluded from the ExpressionSet. Hence, for a 7 stage ExpressionSet genes passing the expression level cut.off in 6 stages will be retained in the ExpressionSet.
- **min-set**: genes passing the expression level cut.off in $\text{ceiling}(n/2)$ stages will be retained in the ExpressionSet, where n is the number of stages in the ExpressionSet.
- **n-set**: genes passing the expression level cut.off in n stages will be retained in the ExpressionSet. Here, the argument n needs to be specified.

Author(s)

Hajk-Georg Drost

Examples

```

data(PhyloExpressionSetExample)

# remove genes that have an expression level below 8000
# in at least one developmental stage
FilterConst <- Expressed(ExpressionSet = PhyloExpressionSetExample,
                        cut.off      = 8000,
                        method       = "const",
                        comparison    = "below")

dim(FilterConst) # check number of retained genes

# remove genes that have an expression level below 8000
# in at least 3 developmental stages
# (in this case: ceiling(7/2) = 4 stages fulfilling the cut-off criteria)
FilterMinSet <- Expressed(ExpressionSet = PhyloExpressionSetExample,
                        cut.off      = 8000,
                        method       = "min-set",
                        comparison    = "below")

dim(FilterMinSet) # check number of retained genes

# remove genes that have an expression level below 8000
# in at least 5 developmental stages (in this case: n = 2 stages fulfilling the criteria)
FilterNSet <- Expressed(ExpressionSet = PhyloExpressionSetExample,
                        cut.off      = 8000,
                        method       = "n-set",
                        comparison    = "below",
                        n            = 2)

dim(FilterNSet) # check number of retained genes

# remove expression levels that exceed the cut.off criteria
FilterMinSet <- Expressed(ExpressionSet = PhyloExpressionSetExample,
                        cut.off      = 12000,
                        method       = "min-set",
                        comparison    = "above")

dim(FilterMinSet) # check number of retained genes

# remove expression levels that undercut AND exceed the cut.off criteria
FilterMinSet <- Expressed(ExpressionSet = PhyloExpressionSetExample,
                        cut.off      = c(8000,12000),
                        method       = "min-set",
                        comparison    = "both")

dim(FilterMinSet) # check number of retained genes

```

FlatLineTest	<i>Perform the Flat Line Test</i>
--------------	-----------------------------------

Description

This function quantifies the statistical significance of an observed phylotranscriptomic pattern. In detail, the *Flat Line Test* quantifies any significant deviation of an observed phylotranscriptomic pattern from a flat line.

Usage

```
FlatLineTest(ExpressionSet, permutations = 1000, plotHistogram = FALSE,
             runs = 10, parallel = FALSE, custom.perm.matrix = NULL)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
permutations	a numeric value specifying the number of permutations that shall be performed for the <i>FlatLineTest</i> .
plotHistogram	a logical value indicating whether a detailed statistical analysis concerning the goodness of fit should be performed.
runs	specify the number of runs to be performed for goodness of fit computations. In most cases runs = 100 is a reasonable choice.
parallel	performing runs in parallel (takes all cores of your multicore machine).
custom.perm.matrix	a custom <code>bootMatrix</code> (permutation matrix) to perform the underlying test statistic. Default is <code>custom.perm.matrix = NULL</code> .

Details

Internally the function performs N phylotranscriptomics pattern computations (**TAI** or **TDI**) based on sampled PhyloExpressionSets or DivergenceExpressionSets (see `bootMatrix`). The test statistics is being developed as follows:

The variance $V_{pattern}$ of the S phylotranscriptomics values defines the test statistic for the `FlatLineTest`. The basic assumption is, that the variance of a flat line should be equivalent to zero for a perfect flat line. Any deviation from a flat line can be measured with a variance value > 0 .

To determine the null distribution of V_p , all PS or DS values within each developmental stage s are randomly permuted, S surrogate phylotranscriptomics values are computed from this permuted dataset, and a surrogate value of V_p is computed from these S phylotranscriptomics values. This permutation process is repeated N times, yielding a histogram of V_p .

After applying a *Lilliefors Kolmogorov-Smirnov Test for gamma distribution*, V_p is approximated by a *gamma distribution*. The two parameters of the *gamma distribution* are estimated by the function `fitdistr` from the **fitdistrplus** package by *moment matching estimation*. The fitted *gamma distribution* is considered the null distribution of $V_{pattern}$, and the p-value of the observed value of V_p is computed from this null distribution.

In case the parameter *plotHistogram* = *TRUE*, a multi-plot is generated showing:

- (1) A Cullen and Frey skewness-kurtosis plot generated by `descdist`).
- (2) A histogram of *V_p* combined with the density plot using the Method of Moments estimated parameters returned by the `fitdist` function using a gamma distribution.
- (3) A plot showing the p-values for *N* independent runs to verify that a specific p-value is biased by a specific permutation order.

The *goodness of fit* for the random vector *V_p* is quantified statistically by an adapted Lilliefors (Kolmogorov-Smirnov) test for gamma distributions.

Value

a list object containing the list elements:

- `p.value` the p-value quantifying the statistical significance (deviation from a flat line) of the given phylotranscriptomics pattern.
- `std.dev` the standard deviation of the *N* sampled phylotranscriptomics patterns for each developmental stage *S*.

Note

In case there are extreme outlier expression values stored in the dataset (`PhyloExpressionSet` or `DivergenceExpressionSet`), the internal `fitdist` function that is based on the `bootMatrix` output might return a warning: "In densfun(x, parm[1], parm[2], ...) : NaNs were produced" which indicates that permutation results caused by extreme outlier expression values that could not be fitted accordingly. This warning will not be printed out when the corresponding outlier values are extracted from the dataset.

Author(s)

Hajk-Georg Drost

References

- Drost HG et al.(2015). *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. *Mol Biol Evol.* 32 (5): 1221-1231 doi:10.1093/molbev/msv012.
- Quint M et al. (2012). A transcriptomic hourglass in plant embryogenesis. *Nature* (490): 98-101.
- M. L. Delignette-Muller, R. Pouillot, J.-B. Denis and C. Dutang (2014), `fitdistrplus`: help to fit of a parametric distribution to non-censored or censored data.
- Cullen AC and Frey HC (1999) *Probabilistic techniques in exposure assessment*. Plenum Press, USA, pp. 81-159.
- Evans M, Hastings N and Peacock B (2000) *Statistical distributions*. John Wiley and Sons Inc.
- Sokal RR and Rohlf FJ (1995) *Biometry*. W.H. Freeman and Company, USA, pp. 111-115.
- Juergen Gross and bug fixes by Uwe Ligges (2012). `nortest`: Tests for Normality. R package version 1.0-2.
- <http://CRAN.R-project.org/package=nortest>

Dallal, G.E. and Wilkinson, L. (1986): An analytic approximation to the distribution of Lilliefors test for normality. The American Statistician, 40, 294-296.

Stephens, M.A. (1974): EDF statistics for goodness of fit and some comparisons. Journal of the American Statistical Association, 69, 730-737.

<http://stackoverflow.com/questions/4290081/fitting-data-to-distributions?rq=1>

<http://stats.stackexchange.com/questions/45033/can-i-use-kolmogorov-smirnov-test-and-estimate-dist>

<http://cran.r-project.org/doc/contrib/Ricci-distributions-en.pdf>

<http://cran.r-project.org/doc/contrib/Ricci-distributions-en.pdf>

See Also

[TAI](#), [TDI](#), [PlotPattern](#), [bootMatrix](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)

# example PhyloExpressionSet using 1000 permutations
FlatLineTest(PhyloExpressionSetExample,
              permutations = 1000,
              plotHistogram = FALSE)

# use your own permutation matrix based on which p-values (FlatLineTest)
# shall be computed
custom_perm_matrix <- bootMatrix(PhyloExpressionSetExample,100)

FlatLineTest(PhyloExpressionSetExample,
              custom.perm.matrix = custom_perm_matrix)
```

geom.mean

Geometric Mean

Description

This function computes the geometric mean of a numeric input vector x .

Usage

```
geom.mean(x)
```

Arguments

x a numeric vector for which geometric mean computations shall be performed.

Author(s)

Hajk-Georg Drost

Examples

```
x <- 1:10
geom.mean(x)
```

harm.mean	<i>Harmonic Mean</i>
-----------	----------------------

Description

This function computes the harmonic mean of a numeric input vector x .

Usage

```
harm.mean(x)
```

Arguments

x a numeric vector for which harmonic mean computations shall be performed.

Author(s)

Hajk-Georg Drost

Examples

```
x <- 1:10
harm.mean(x)
```

is.ExpressionSet	<i>Test ExpressionSet Standard</i>
------------------	------------------------------------

Description

This function tests whether a given ExpressionSet follows the pre-defined PhyloExpressionSet or DivergenceExpressionSet standard.

Usage

```
is.ExpressionSet(ExpressionSet)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet that shall be tested for format validity.

Author(s)

Hajk-Georg Drost

Examples

```
# read example PhyloExpressionSet
data(PhyloExpressionSetExample)

is.ExpressionSet(PhyloExpressionSetExample)
```

MatchMap	<i>Match a Phylostratigraphic Map or Divergence Map with a ExpressionMatrix</i>
----------	---

Description

Match a Phylostratigraphic Map or Divergence Map with a ExpressionMatrix

Usage

```
MatchMap(Map, ExpressionMatrix, remove.duplicates = FALSE,
         accumulate = NULL)
```

Arguments

Map	a standard <i>Phylostratigraphic Map</i> or <i>Divergence Map</i> object.
ExpressionMatrix	a standard ExpressionMatrix object.
remove.duplicates	a logical value indicating whether duplicate gene ids should be removed from the data set.
accumulate	an accumulation function such as <code>mean()</code> , <code>median()</code> , or <code>min()</code> to accumulate multiple expression levels that map to the same unique gene id present in the ExpressionMatrix.

Details

This function matches a *Phylostratigraphic Map* or *Divergence Map* only storing unique gene ids with a ExpressionMatrix also storing only unique gene ids.

Value

a standard PhyloExpressionSet or DivergenceExpressionSet object.

Author(s)

Hajk-Georg Drost

References

Domazet-Loso T, Brajkovic J, Tautz D (2007) A phylostratigraphy approach to uncover the genomic history of major adaptations in metazoan lineages. *Trends Genet.* 23: 533-9.

Domazet-Loso T, Tautz D (2010) A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns. *Nature* 468: 815-8.

Quint M., Drost H.G., Gabel A., Ullrich K.K., Boenn M., Grosse I. (2012) A transcriptomic hourglass in plant embryogenesis. *Nature* 490: 98-101.

Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis.* *Mol Biol Evol.* 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

Examples

```
# load a standard PhyloExpressionSet
data(PhyloExpressionSetExample)

# in a standard PhyloExpressionSet,
# column one and column two denote a standard
# phylostratigraphic map
PhyloMap <- PhyloExpressionSetExample[ , 1:2]

# look at the phylostratigraphic map standard
head(PhyloMap)

# in a standard PhyloExpressionSet, column two combined
# with column 3 - N denote a standard ExpressionMatrix
ExpressionMatrixExample <- PhyloExpressionSetExample[ , c(2,3:9)]

# these two data sets shall illustrate an example
# phylostratigraphic map that is returned
# by a standard phylostratigraphy run, and a expression set
# that is the result of expression data analysis
# (background correction, normalization, ...)

# now we can use the MatchMap function to merge both data sets
# to obtain a standard PhyloExpressionSet

PES <- MatchMap(PhyloMap, ExpressionMatrixExample)

# note that the function returns a head()
# of the matched gene ids to enable
# the user to find potential mis-matches

# the entire procedure is analogous to merge()
# with two data sets sharing the same gene ids
# as column (primary key)
PES_merge <- merge(PhyloMap, ExpressionMatrixExample)
```

`omitMatrix`*Compute TAI or TDI Profiles Omitting a Given Gene*

Description

For each gene *i*, exclude the corresponding gene *i* from the global `PhyloExpressionSet` or `DivergenceExpressionSet` and compute the [TAI](#) or [TDI](#) profile for the corresponding global `PhyloExpressionSet` or `DivergenceExpressionSet` with excluded gene *i*.

This procedure results in a TAI or TDI profile Matrix storing the TAI or TDI profile for each omitted gene *i*.

Usage

```
omitMatrix(ExpressionSet)
```

Arguments

`ExpressionSet` a standard `PhyloExpressionSet` or `DivergenceExpressionSet` object.

Value

a numeric matrix storing TAI or TDI profile for each omitted gene *i*.

Author(s)

Hajk-Georg Drost

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet
omMatrix_ps <- omitMatrix(PhyloExpressionSetExample)

# example DivergenceExpressionSet
omMatrix_ds <- omitMatrix(DivergenceExpressionSetExample)
```

PhyloExpressionSetExample

An Example PhyloExpressionSet Data Set

Description

A standard PhyloExpressionSet is a `data.frame` consisting of a standardized sequence of columns to store the age information for each gene and its corresponding gene expression profile.

The standard is defined as follows:

Phylostratum | GeneID | Expression-level 1 | ... | Expression-level N

Details

This dataset covers 7 developmental stages of *Arabidopsis thaliana* embryo development. The initial gene expression dataset was published by Xiang et al., 2011 (see references section) and was then used by Quint et al., 2012 (see references section) to assign evolutionary ages to each gene expression profile.

Value

a standard PhyloExpressionSet object.

Author(s)

Hajk-Georg Drost

Source

<http://www.plantphysiol.org/content/156/1/346/suppl/DC1>

References

Quint M et al. 2012. "A transcriptomic hourglass in plant embryogenesis". *Nature* (490): 98-101. Supplementary Table 2 : <http://www.nature.com/nature/journal/v490/n7418/full/nature11394.html>

Xiang D et al. 2011. "Genome-Wide Analysis Reveals Gene Expression and Metabolic Network Dynamics during Embryo Development in *Arabidopsis*". *Plant Physiology* (156): 346-356. Supplemental Table 1 : <http://www.plantphysiol.org/content/156/1/346/suppl/DC1>

See Also

[DivergenceExpressionSetExample](#)

PlotBarRE

*Plot the Mean Relative Expression Levels as Barplot***Description**

This function takes a `PhyloExpressionSet` or `DivergenceExpressionSet` object as input and computes for two or more defined phylostratum (divergence stratum) classes the statistical significance of the differences of mean relative expression of these two (or more) corresponding phylostratum (divergence stratum) classes. As test-statistic, the function performs a nonparametric `kruskal.test` based on relative expression values stored within each defined phylostratum class.

Usage

```
PlotBarRE(ExpressionSet, Groups = NULL, wLength = 0.1, ratio = FALSE,
           p.adjust.method = NULL, ...)
```

Arguments

<code>ExpressionSet</code>	a standard <code>PhyloExpressionSet</code> or <code>DivergenceExpressionSet</code> object.
<code>Groups</code>	a list containing the phylostrata or divergence-strata that correspond to the same phylostratum class or divergence class. For ex. evolutionary old phylostrata: PS1-3 (Class 1) and evolutionary young phylostrata: PS4-12 (Class 2). In this case, the <code>Groups</code> list could be assigned as, <code>Groups = list(c(1:3), c(4:12))</code> . It is also possible to define more than 2 groups of evolutionary ages. For ex. <code>Groups = list(c(1:3),c(4:8),c(9:12))</code> would perform a <code>kruskal.test</code> to determine the statistical significance of the evolutionary classes PS1-3, PS4-6, and PS9-12 based on their corresponding mean relative expression levels.
<code>wLength</code>	a numeric value defining the whiskers length above the bars. In case there are numerous different phylostratum classes a smaller <code>wLength</code> parameter should be used for better visualizations.
<code>ratio</code>	a boolean value specifying whether the bars in the barplot represent the mean relative expression level of phylostrata belonging to the same phylostratum class. In case <code>ratio = TRUE</code> , the ratio of the mean relative expression level of the two phylostrata classes is plotted as lines within the barplot. This parameter can only be used for 2 class comparisons.
<code>p.adjust.method</code>	correction method to adjust p-values for multiple comparisons (see <code>p.adjust</code> for possible methods). E.g., <code>p.adjust.method = "BH"</code> (Benjamini & Hochberg (1995)) or <code>p.adjust.method = "bonferroni"</code> (Bonferroni correction).
<code>...</code>	default graphics parameters.

Details

In case a large number of developmental stages is included in the input `ExpressionSet`, p-values returned by `PlotBarRE` should be adjusted for multiple comparisons which can be done by specifying the `p.adjust.method` argument.

Value

A barplot comparing Phylostratum-Classes by its mean relative expression levels. Significant stages are marked by '*' referring to statistically significant differences:

- (1) '*' = P-Value \leq 0.05
- (2) '**' = P-Value \leq 0.005
- (3) '***' = P-Value \leq 0.0005

Author(s)

Hajk-Georg Drost

References

- Quint M et al. 2012. "A transcriptomic hourglass in plant embryogenesis". *Nature* (490): 98-101.
- Domazet-Lošo T. and Tautz D. 2010. "A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns". *Nature* (468): 815-818.
- Myles Hollander and Douglas A. Wolfe (1973), *Nonparametric Statistical Methods*. New York: John Wiley & Sons. Pages 115-120.

See Also

[RE](#), [REMatrix](#), [PlotRE](#), [kruskal.test](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet
PlotBarRE(ExpressionSet = PhyloExpressionSetExample,
           Groups       = list(c(1:3), c(4:12)))

# example DivergenceExpressionSet
PlotBarRE(ExpressionSet = DivergenceExpressionSetExample,
           Groups       = list(c(1:5), c(6:10)))

# Perform PlotBarRE() with p-value adjustment method Benjamini & Hochberg (1995)
PlotBarRE(ExpressionSet = PhyloExpressionSetExample,
           Groups       = list(c(1:3), c(4:12)),
           p.adjust.method = "BH")

# Example: plot ratio
# the ratio curve visualizes the ratio between bar 1 / bar 2
# the z - axis shows the corresponding ratio value of bar 1 / bar 2
PlotBarRE(ExpressionSet = PhyloExpressionSetExample,
```

```

Groups      = list(c(1:3), c(4:12)),
ratio       = TRUE)

```

PlotCategoryExpr *Plot the Expression Levels of each Age or Divergence Category as Boxplot, Violinplot, or Dotplot*

Description

This function visualizes the expression level distribution of each phylostratum during each time point or experiment as boxplot, dot plot, or violin plot enabling users to quantify the age (PS) or divergence (DS) category specific contribution to the corresponding transcriptome.

Usage

```

PlotCategoryExpr(ExpressionSet, legendName, test.stat = TRUE,
  type = "category-centered", distr.type = "boxplot", log.expr = FALSE,
  gene.set = NULL)

```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
legendName	a character string specifying whether "PS" or "DS" are used to compute relative expression profiles.
test.stat	a logical value indicating whether a Benjamini-Hochberg adjusted kruskal.test should be applied to determine significant differences in age or divergence category specific expression.
type	type of age or divergence category comparison. Specifications can be type = "category-centered" or type = "stage-centered".
distr.type	format of visualizing age or divergence category specific expression distributions. Either distr.type = "boxplot", distr.type = "dotplot", or distr.type = "violin".
log.expr	a logical value specifying whether or not expression levels should internally be log ₂ -transformed before visualization.
gene.set	a character vector storing the gene ids for which gene expression levels shall be visualized.

Details

This way of visualizing the gene expression distribution of each age (PS) or divergence (DS) category during all developmental stages or experiments allows users to detect specific age or divergence categories contributing significant levels of gene expression to the underlying biological process (transcriptome).

This quantification allows users to conclude that genes originating in specific PS or DS contribute significantly more to the overall transcriptome than other genes originating from different PS or DS

categories. More specialized analyses such as [PlotMeans](#), [PlotRE](#), [PlotBarRE](#), etc. will then allow to study the exact mean expression patterns of these age or divergence categories.

The statistical quantification of differences between expression levels of different age or divergence categories is done by performing a [kruskal.test](#) with Benjamini & Hochberg p-value adjustment for multiple comparisons.

- `type = "category-centered"` Here, the [kruskal.test](#) quantifies the differences of gene expression between all combinations of age or divergence categories for each stage or experiment separately. Here, a significant p-value quantifies that there is at least one pairwise comparison for which age or divergence categories significantly differ in their gene expression distribution. This type of analysis allows users to detect stages or experiments that show high deviation between age or divergence category contributions to the overall transcriptome or no significant deviations of age or divergence categories, suggesting equal age or divergence category contributions to the overall transcriptome.
- `type = "stage-centered"` Here, the [kruskal.test](#) quantifies the differences of gene expression between all stages or experiments for each age or divergence category separately. Hence, the test quantifies whether or not the gene expression distribution of a single age or divergence category significantly changes throughout development or experiments. This type of analysis allows users to detect specific age or divergence categories that significantly change their expression levels throughout development or experiments.

Argument Specifications:

Argument: `type`

- `type = "category-centered"` This specification allows users to compare the differences between all age or divergence categories during the same stage or experiment.
- `type = "stage-centered"` This specification allows users to compare the differences between all age or divergence categories between stages or experiments.

Argument: `distr.type`

- `distr.type = "boxplot"` This specification allows users to visualize the expression distribution of all PS or DS as boxplot.
- `distr.type = "violin"` This specification allows users to visualize the expression distribution of all PS or DS as violin plot.
- `distr.type = "dotplot"` This specification allows users to visualize the expression distribution of all PS or DS as dot plot.

Finally, users can specify a `gene.set` (a subset of genes included in the input `ExpressionSet`) for which expression levels should be visualized as boxplot, dotplot, or violinplot.

Value

A boxplot, violin plot, or dot plot visualizing the gene expression levels of different PS or DS categories.

Furthermore, the statistical test results returned from the [kruskal.test](#) are printed to the console.

(1) `'**'` = P-Value \leq 0.05

- (2) '***' = P-Value ≤ 0.005
- (3) '****' = P-Value ≤ 0.0005
- (4) 'n.s.' = not significant = P-Value > 0.05

Author(s)

Hajk-Georg Drost

See Also

[PlotMeans](#), [PlotRE](#), [PlotBarRE](#), [age.apply](#), [pTAI](#), [pTDI](#), [pStrata](#), [pMatrix](#), [TAI](#), [TDI](#)

Examples

```
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

## Not run:

# category-centered visualization of PS specific expression level distributions (log-scale)
PlotCategoryExpr(ExpressionSet = PhyloExpressionSetExample,
                 legendName   = "PS",
                 test.stat    = TRUE,
                 type         = "category-centered",
                 distr.type   = "boxplot",
                 log.expr     = TRUE)

# stage-centered visualization of PS specific expression level distributions (log-scale)
PlotCategoryExpr(ExpressionSet = PhyloExpressionSetExample,
                 legendName   = "PS",
                 test.stat    = TRUE,
                 distr.type   = "boxplot",
                 type         = "stage-centered",
                 log.expr     = TRUE)

# category-centered visualization of PS specific expression level distributions (log-scale)
# as violin plot
PlotCategoryExpr(ExpressionSet = PhyloExpressionSetExample,
                 legendName   = "PS",
                 test.stat    = TRUE,
                 distr.type   = "violin",
                 type         = "stage-centered",
                 log.expr     = TRUE)

# analogous for DivergenceExpressionSets
PlotCategoryExpr(ExpressionSet = DivergenceExpressionSetExample,
```

```

        legendName = "DS",
        test.stat   = TRUE,
        type       = "category-centered",
        distr.type  = "boxplot",
        log.expr   = TRUE)

# visualize the expression levels of 500 example genes
set.seed(234)
example.gene.set <- PhyloExpressionSetExample[sample(1:25260,500) , 2]

PlotCategoryExpr(ExpressionSet = PhyloExpressionSetExample,
                  legendName   = "PS",
                  test.stat    = TRUE,
                  type         = "category-centered",
                  distr.type    = "boxplot",
                  log.expr     = TRUE,
                  gene.set     = example.gene.set)

## End(Not run)

```

PlotContribution *Plot the Phylostratum or Divergence Stratum Contribution to the Global Pattern*

Description

This function computes the cumulative contribution of each Phylostratum or Divergence Stratum to the global [TAI](#) or [TDI](#) profile.

Usage

```
PlotContribution(ExpressionSet, colors = NULL, legendName = NULL,
                 digits.ylab = 3, y.ticks = 5, ...)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
colors	a character vector specifying the colors that should be used for each Phylostratum/Divergence Stratum. Default: colors = NULL, meaning that default colors are used.
legendName	a character string specifying whether "PS" or "DS" are used to compute relative expression profiles.
digits.ylab	a numeric value specifying the number of digits shown for the TAI or TDI values on the y-axis.
y.ticks	a numeric value specifying the number of ticks to be drawn on the y-axis.
...	additional plot parameters.

Details

Introduced by Domazet-Loaso and Tautz (2010), this function allows users to visualize the cumulative contribution of each Phylostratum or Divergence Stratum to the global Transcriptome Age Index or Transcriptome Divergence Index profile to quantify how each Phylostratum or Divergence Stratum influences the profile of the global TAI or TDI pattern.

Author(s)

Hajk-Georg Drost

References

Domazet-Loaso T. and Tautz D. (2010). A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns. *Nature* (468): 815-818.

See Also

[pTAI](#), [pTDI](#), [TAI](#), [TDI](#), [PlotPattern](#)

Examples

```
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# visualize phylostratum contribution to global TAI
PlotContribution(PhyloExpressionSetExample, legendName = "PS")

# visualize divergence stratum contribution to global TDI
PlotContribution(DivergenceExpressionSetExample, legendName = "DS")
```

PlotCorrelation

Plot the Correlation Between Phylostrata and Divergence Strata

Description

This function plots the correlation coefficient between phylostratum values and divergence-stratum values of a given PhyloExpressionSet and DivergenceExpressionSet.

This function can be used to test whether a given PS distribution and DS distribution are linear correlated so that the independence of PS and DS can be assumed for subsequent analyses (Quint et al., 2012).

Usage

```
PlotCorrelation(PhyloExpressionSet, DivergenceExpressionSet,
  method = "pearson", linearModel = FALSE, main.text = NULL, ...)
```

Arguments

PhyloExpressionSet	a standard PhyloExpressionSet object.
DivergenceExpressionSet	a standard DivergenceExpressionSet object.
method	a character string specifying the correlation method to be used, e.g. "pearson", "kendall", "spearman".
linearModel	a boolean value specifying whether a linear model should be fitted to the data and furthermore, should be visualized in the corresponding plot.
main.text	a character string specifying the text that shall be written as main. Default is main.text = NULL.
...	default plot parameters.

Value

a jitter-correlation-plot of PS and DS correlation.

Author(s)

Hajk-Georg Drost

References

Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[cor](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# plot the PS and DS correlation
PlotCorrelation(PhyloExpressionSetExample, DivergenceExpressionSetExample,
                method      = "pearson",
                linearModel = TRUE,
                main.text    = "Pearson's ")
```

PlotDistribution	<i>Plot the Frequency Distribution of Phylostrata or Divergence Strata</i>
------------------	--

Description

This function plots the frequency distribution of genes within the corresponding *phylostratigraphic map* or *divergence map* and can be used to fastly visualize the PS or DS distribution of a given phylostratum vector or divergence-stratum vector.

Usage

```
PlotDistribution(PhyloExpressionSet, plotText = TRUE, as.ratio = FALSE, ...)
```

Arguments

PhyloExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
plotText	a boolean value specifying whether the total number of genes belonging to a corresponding phylostratum or divergence-stratum class shall be plotted above each bar of the barplot.
as.ratio	a boolean value specifying whether the relative frequencies instead of absolute frequencies shall be plotted.
...	default plot parameters.

Details

The frequency distribution of all genes or a subset of genes might be of interest for subsequent analyses.

For Example:

Filtering genes using gene cluster algorithms can result in different groups (classes) of genes. For each gene group the phylostratum or divergence-stratum distribution can be visualized using this function and can be compared between different groups.

This analysis allows to compare different gene expression profiles (or gene groups in general) based on their evolutionary origins or evolutionary relationships.

Value

a barplot showing the phylostratum distribution or divergence-stratum distribution of a given numeric vector containing PS or DS values.

Author(s)

Hajk-Georg Drost

Examples

```
# load PhyloExpressionSet
data(PhyloExpressionSetExample)

# plot the phylostratum distribution of a PhyloExpressionSet
PlotDistribution(PhyloExpressionSetExample, plotText = TRUE)

# plot the relative frequency distribution of a PhyloExpressionSet
PlotDistribution(PhyloExpressionSetExample, plotText = TRUE, as.ratio = TRUE)

# a example for visualizing the PS distribution for a subset of genes
PlotDistribution(PhyloExpressionSetExample[sample(20000,5000) , ],
                plotText = TRUE, as.ratio = TRUE)
```

PlotEnrichment	<i>Plot the Phylostratum or Divergence Stratum Enrichment of a given Gene Set</i>
----------------	---

Description

This function computes and visualizes the significance of enriched (over or underrepresented) Phylostrata or Divergence Strata within an input `test.set`.

Usage

```
PlotEnrichment(ExpressionSet, test.set, use.only.map = FALSE,
               measure = "log-foldchange", complete.bg = TRUE, legendName = "",
               over.col = "steelblue", under.col = "midnightblue", epsilon = 1e-05,
               cex.legend = 1, cex.asterisk = 1, plot.bars = TRUE,
               p.adjust.method = NULL, ...)
```

Arguments

<code>ExpressionSet</code>	a standard <code>PhyloExpressionSet</code> or <code>DivergenceExpressionSet</code> object (in case <code>use.only.map = FALSE</code>).
<code>test.set</code>	a character vector storing the gene ids for which PS/DS enrichment analyses should be performed.
<code>use.only.map</code>	a logical value indicating whether instead of a standard <code>ExpressionSet</code> only a <code>Phylostratigraphic Map</code> or <code>Divergene Map</code> is passed to this function.
<code>measure</code>	a character string specifying the measure that should be used to quantify over and under representation of PS/DS. Measures can either be <code>measure = "foldchange"</code> (odds) or <code>measure = "log-foldchange"</code> (log-odds).
<code>complete.bg</code>	a logical value indicating whether the entire background set of the input <code>ExpressionSet</code> should be considered when performing Fisher's exact test (<code>complete.bg = TRUE</code>) or whether genes that are stored in <code>test.set</code> should be excluded from the background set before performing Fisher's exact test (<code>complete.bg = FALSE</code>).

legendName	a character string specifying whether "PS" or "DS" are used to compute relative expression profiles.
over.col	color of the overrepresentation bars.
under.col	color of the underrepresentation bars.
epsilon	a small value to shift values by epsilon to avoid log(0) computations.
cex.legend	the cex value for the legend.
cex.asterisk	the cex value for the asterisk.
plot.bars	a logical value specifying whether or not bars should be visualized or whether only p.values and enrichment.matrix should be returned.
p.adjust.method	correction method to adjust p-values for multiple comparisons (see p.adjust for possible methods). E.g., p.adjust.method = "BH" (Benjamini & Hochberg (1995)) or p.adjust.method = "bonferroni" (Bonferroni correction).
...	default graphics parameters.

Details

This *Phylostratum* or *Divergence Stratum* enrichment analysis is motivated by Sestak and Domazet-Loso (2015) who perform *Phylostratum* or *Divergence Stratum* enrichment analyses to correlate organ evolution with the origin of organ specific genes.

In detail this function takes the *Phylostratum* or *Divergence Stratum* distribution of all genes stored in the input ExpressionSet as background set and the *Phylostratum* or *Divergence Stratum* distribution of the test.set and performs a [fisher.test](#) for each *Phylostratum* or *Divergence Stratum* to quantify the statistical significance of over- or underrepresented *Phylostrata* or *Divergence Strata* within the set of selected test.set genes.

To visualize the odds or log-odds of over or underrepresented genes within the test.set the following procedure is performed:

- N_{ij} denotes the number of genes in group j and deriving from PS i , with $i = 1, \dots, n$ and where $j = 1$ denotes the background set and $j = 2$ denotes the test.set
- $N_{.i}$ denotes the total number of genes within PS i
- $N_{.j}$ denotes the total number of genes within group j
- $N_{..}$ is the total number of genes within all groups j and all PS i
- $f_{ij} = N_{ij} / N_{..}$ and $g_{ij} = f_{ij} / f_{.j}$ denote relative frequencies between groups
- $f_{.i}$ denotes the between group sum of f_{ij}

The result is the fold-change value (odds) denoted as $C = g_{i2} / f_{.i}$. which is visualized above and below zero.

In case a large number of *Phylostrata* or *Divergence Strata* is included in the input ExpressionSet, p-values returned by PlotEnrichment should be adjusted for multiple comparisons which can be done by specifying the p.adjust.method argument.

Author(s)

Hajk-Georg Drost

References

Sestak and Domazet-Loso (2015). Phylostratigraphic Profiles in Zebrafish Uncover Chordate Origins of the Vertebrate Brain. *Mol. Biol. Evol.* 32(2): 299-312.

See Also

[EnrichmentTest](#), [fisher.test](#)

Examples

```
data(PhyloExpressionSetExample)

set.seed(123)
test_set <- sample(PhyloExpressionSetExample[, 2], 10000)

## Examples with complete.bg = TRUE
## Hence: the entire background set of the input ExpressionSet is considered
## when performing Fisher's exact test

# measure: log-foldchange
PlotEnrichment(ExpressionSet = PhyloExpressionSetExample,
                test.set     = test_set ,
                legendName   = "PS",
                measure       = "log-foldchange")

# measure: foldchange
PlotEnrichment(ExpressionSet = PhyloExpressionSetExample,
                test.set     = test_set ,
                legendName   = "PS",
                measure       = "foldchange")

## Examples with complete.bg = FALSE
## Hence: the test.set genes are excluded from the background set before
## Fisher's exact test is performed

# measure: log-foldchange
PlotEnrichment(ExpressionSet = PhyloExpressionSetExample,
                test.set     = test_set ,
                complete.bg  = FALSE,
                legendName   = "PS",
                measure       = "log-foldchange")

# measure: foldchange
PlotEnrichment(ExpressionSet = PhyloExpressionSetExample,
                test.set     = test_set ,
                complete.bg  = FALSE,
                legendName   = "PS",
                measure       = "foldchange")
```

`PlotGeneSet`*Plot the Expression Profiles of a Gene Set*

Description

This function simply visualizes the gene expression profiles of a defined subset of genes stored in the input `ExpressionSet`.

Usage

```
PlotGeneSet(ExpressionSet, gene.set, get.subset = FALSE,
             use.only.map = FALSE, colors = NULL, plot.legend = TRUE, y.ticks = 6,
             digits.ylab = 4, ...)
```

Arguments

<code>ExpressionSet</code>	a standard <code>PhyloExpressionSet</code> or <code>DivergenceExpressionSet</code> object.
<code>gene.set</code>	a character vector storing the gene ids for which gene expression profiles shall be visualized.
<code>get.subset</code>	a logical value indicating whether or not an <code>ExpressionSet</code> subset of the selected <code>gene.set</code> should be returned.
<code>use.only.map</code>	a logical value indicating whether instead of a standard <code>ExpressionSet</code> only a <code>Phylostratigraphic Map</code> or <code>Divergene Map</code> is passed to the function.
<code>colors</code>	colors for gene expression profiles. Default: <code>colors = NULL</code> , hence default colours are used.
<code>plot.legend</code>	a logical value indicating whether gene ids should be printed as legend next to the plot.
<code>y.ticks</code>	a numeric value specifying the number of ticks to be drawn on the y-axis.
<code>digits.ylab</code>	a numeric value specifying the number of digits shown for the expression levels on the y-axis.
<code>...</code>	additional parameters passed to <code>matplot</code> .

Details

This function simply visualizes or subsets the gene expression levels of a set of genes that are stored in the input `ExpressionSet`.

Author(s)

Hajk-Georg Drost

See Also

[SelectGeneSet](#), [PlotEnrichment](#), [DiffGenes](#)

Examples

```

data(PhyloExpressionSetExample)

# the best parameter setting to visualize this plot:
# png("test_png.png",700,400)
PlotGeneSet(ExpressionSet = PhyloExpressionSetExample,
             gene.set      = PhyloExpressionSetExample[1:5, 2],
             type          = "l",
             lty           = 1,
             lwd           = 4,
             xlab          = "Ontogeny",
             ylab          = "Expression Level")

# dev.off()

# In case you would like to work with the expression levels
# of selected genes you can specify the 'get.subset' argument:

PlotGeneSet(ExpressionSet = PhyloExpressionSetExample,
             gene.set      = PhyloExpressionSetExample[1:5, 2],
             get.subset    = TRUE)

# get a gene subset using only a phylostratigraphic map
ExamplePSMap <- PhyloExpressionSetExample[, 1:2]

PlotGeneSet(ExpressionSet = ExamplePSMap,
             gene.set      = PhyloExpressionSetExample[1:5, 2],
             get.subset    = TRUE,
             use.only.map  = TRUE)

```

PlotMeans

Plot the Mean Expression Profiles of Phylostrata or Divergence Strata

Description

This function computes for each phylostratum or divergence-stratum the corresponding mean expression profile and plots the profiles in N different windows corresponding to the given Phylostratum-Classes that shall be compared.

Usage

```
PlotMeans(ExpressionSet, Groups = NULL, legendName = NULL, colors = NULL,
          ...)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet object.

Groups	a list containing the phylostrata or divergence-strata that correspond to the same phylostratum class or divergence class. For ex. evolutionary old phylostrata: PS1-3 (Class 1) and evolutionary young phylostrata: PS4-12 (Class 2). In this case, the list could be assigned as, Groups = list(c(1:3), c(4:12)). It is also possible to define more than 2 groups of evolutionary ages. For ex. Groups = list(c(1:3),c(4:8),c(9:12)).
legendName	a character string specifying whether "PS" or "DS" are used.
colors	colors for mean expression profiles. Default: colors = NULL, hence default colours are used.
...	default graphics parameters.

Details

This plot may be useful to compare the absolute mean expression levels of each phylostratum or divergence-stratum class.

In different developmental processes different phylostratum or divergence-stratum classes might be more expressed than others, hence contributing more to the overall phylotranscriptomics pattern (TAI or TDI). This plot can help to identify the phylostratum or divergence-stratum classes that contributes most to the overall transcriptome of the given developmental process.

Value

a plot showing mean expression profiles of phylostrata or divergence-strata corresponding to the same phylostratum class or divergence class.

Author(s)

Hajk-Georg Drost

See Also

[PlotBarRE](#), [RE](#), [REMatrix](#), [PlotRE](#)

Examples

```
# load PhyloExpressionSet
data(PhyloExpressionSetExample)

# load DivergenceExpressionSet
data(DivergenceExpressionSetExample)

# plot evolutionary old PS (PS1-3) vs evolutionary young PS (PS4-12)
PlotMeans(PhyloExpressionSetExample, Groups = list(c(1:3), c(4:12)),
          legendName = "PS", lty = 1, lwd = 5)

# plot conserved DS (DS1-5) vs divergent DS (DS6-10)
# NOTE: DS are always defined in the range 1, 2, ... , 10.
# Hence, make sure that your groups are within this range!
PlotMeans(DivergenceExpressionSetExample, Groups = list(c(1:5), c(6:10)),
          legendName = "DS", lty = 1, lwd = 5)
```

```
# adding custom colors for relative expression levels:
# -> colors should be ordered by PS/DS starting with PS1,2,3...
PlotMeans(PhyloExpressionSetExample,
  Groups      = list(c(1:3), c(4:12)),
  legendName  = "PS",
  colors      = c("black", "red", "green", "brown", "darkmagenta",
    "blue", "darkred", "darkblue", "darkgreen", "orange",
    "azure4", "gold4"),
  lty         = 1,
  lwd         = 5)
```

PlotPattern

Plot the Transcriptome Age Index or Transcriptome Divergence Index

Description

Function to plot the TAI or TDI of a given PhyloExpressionSet or DivergenceExpressionSet object. This function plot the [TAI](#) or [TDI](#) of a given PhyloExpressionSet or DivergenceExpressionSet object.

Usage

```
PlotPattern(ExpressionSet, TestStatistic = "FlatLineTest", modules = NULL,
  permutations = 1000, lillie.test = FALSE, digits.ylab = 4,
  p.value = TRUE, shaded.area = FALSE, y.ticks = 4,
  custom.perm.matrix = NULL, ...)
```

Arguments

- | | |
|---------------|---|
| ExpressionSet | a standard PhyloExpressionSet or DivergenceExpressionSet object. |
| TestStatistic | a string defining the type of test statistics to be used to quantify the statistical significance the present phylotranscriptomics pattern. Possible values can be: TestStatistic = "FlatLineTest" : Statistical test for the deviation from a flat line. TestStatistic = "ReductiveHourglassTest" : Statistical test for the existence of a hourglass shape (high-low-high pattern). TestStatistic = "EarlyConservationTest" : Statistical test for the existence of a earlyconser-
vation pattern (low-high-high pattern). |
| modules | a list storing three elements for the ReductiveHourglassTest or EarlyConservationTest : early, mid, and late. Each element expects a numeric vector specifying the developmental stages or experiments that correspond to each module. For example, module = list(early = 1:2, mid = 3:5, late = 6:7) devides a dataset storing seven developmental stages into 3 modules. |
| permutations | a numeric value specifying the number of permutations to be performed for the FlatLineTest , EarlyConservationTest or ReductiveHourglassTest . |
| lillie.test | a boolean value specifying whether the Lilliefors Kolmogorov-Smirnov Test shall be performed. |

<code>digits.ylab</code>	a numeric value specifying the number of digits shown for the TAI or TDI values on the y-axis.
<code>p.value</code>	a boolean value specifying whether the p-value of the test statistic shall be printed within the plot area.
<code>shaded.area</code>	a boolean value specifying whether a shaded area shall be drawn for the developmental stages defined to be the presumptive phylotypic period.
<code>y.ticks</code>	a numeric value specifying the number of ticks to be drawn on the y-axis.
<code>custom.perm.matrix</code>	a custom <code>bootMatrix</code> (permutation matrix) to perform the underlying test statistic visualized by <code>PlotPattern</code> . Default is <code>custom.perm.matrix = NULL</code> .
<code>...</code>	default plot parameters.

Details

This function computes a permutation test quantifying the statistical significance of the present phylotranscriptomics pattern. The user can choose between the `FlatLineTest`, `ReductiveHourglassTest`, or `EarlyConservationTest`. The `FlatLineTest` tests for any significant deviation from a flat line. Each period or stage that significantly deviates from a flat line, might be governed by stronger selective pressure (in terms of natural selection) compared to other stages or periods of development. The `ReductiveHourglassTest` specifically tests for the statistical significance of a molecular hourglass pattern (high-low-high pattern) with prior biological knowledge. The corresponding p-value that is printed within the plot (by default) specifies the statistical significance of the chosen test statistic.

The `EarlyConservationTest` specifically tests for the statistical significance of a low-high-high pattern (monotonically increasing function) with prior biological knowledge. The corresponding p-value that is printed within the plot (by default) specifies the statistical significance of the chosen test statistic.

The x-axis denotes the developmental series (time course / experiments / ontogeny) of the input `ExpressionSet` and the y-axis denotes the corresponding mean transcriptome age value (TAI or TDI) of the given `ExpressionSet`.

Furthermore, the grey lines above and below the actual phylotranscriptomics pattern denotes the standard deviations of TAI or TDI values that have been estimated from the `bootMatrix`. A low mean transcriptome age value denotes an evolutionary older transcriptome being active during the corresponding periods, whereas a high mean transcriptome age value denotes an evolutionary younger transcriptome being active during the corresponding periods. For mean transcriptome divergence, a low mean transcriptome divergence value denotes a more conserved transcriptome being active (between two species), whereas a high mean transcriptome divergence value denotes a more divergent transcriptome being active (between two species) - in terms of protein-sequence substitution rates.

This function is useful to fastly plot the TAI or TDI profile of a given `PhyloExpressionSet` or `DivergenceExpressionSet` object and the statistical significance of the corresponding pattern. Internally the function calls several graphics functions, such as `plot`, `axis`, and `legend`. For the ellipsis argument `...` all graphics specific arguments can be defined. Internally the function specific arguments for e.g. `plot`, `axis`, and `legend` will be detected and are passed to the corresponding function.

Hence, when calling the function `PlotPattern`, one can specify arguments for `plot` and `axis` and `legend` as `....`

In case prior biological knowledge is present for a specific period of development, the `shaded.area` argument can be set to `TRUE` and the function will use the values stored in the `mid` argument to draw a shaded area within the corresponding period of development.

Value

a plot visualizing the phylotranscriptomic pattern of a given `PhyloExpressionSet` or `DivergenceExpressionSet` object.

The corresponding *p-value* of the test statistic is named as follows:

`p_flat` = p-value of the corresponding [FlatLineTest](#)

`p_rht` = p-value of the corresponding [ReductiveHourglassTest](#)

`p_ect` = p-value of the corresponding [EarlyConservationTest](#)

Author(s)

Hajk-Georg Drost

References

Domazet-Loso T and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. *Nature* (468): 815-818.

Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. *Nature* (490): 98-101.

Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. *Mol Biol Evol.* 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[TAI](#), [TDI](#), [FlatLineTest](#), [ReductiveHourglassTest](#), [EarlyConservationTest](#)

Examples

```
# load PhyloExpressionSet
data(PhyloExpressionSetExample)

# only visualize the TAI profile without any test statistics...
# this is equivalent to performing: plot(TAI(PhyloExpressionSetExample), type = "l", lwd = 6)
PlotPattern(ExpressionSet = PhyloExpressionSetExample,
            TestStatistic = NULL,
            type          = "l",
            xlab          = "Ontogeny",
            ylab          = "TAI",
            lwd           = 9)

# the simplest example of plotting the TAI profile of a given PhyloExpressionSet:
# In this case (default) the FlatLineTest will be performed to quantify
# the statistical significance of the present TAI pattern and will be drawn as 'p = ... '
# in the plot

PlotPattern(ExpressionSet = PhyloExpressionSetExample,
```

```

    TestStatistic = "FlatLineTest",
    permutations = 100,
    type         = "1",
    xlab         = "Ontogeny",
    ylab         = "TAI",
    lwd         = 9)

# an example performing the ReductiveHourglassTest and printing the p-value
# and shaded area of the presumptive phylotypic period into the plot
# Here the 'p = ...' denotes the p-value that is returned by the ReductiveHourglassTest

PlotPattern(
  ExpressionSet = PhyloExpressionSetExample,
  TestStatistic = "ReductiveHourglassTest",
  modules      = list(early = 1:2,mid = 3:5,late = 6:7),
  permutations = 100,
  p.value      = TRUE,
  shaded.area  = TRUE,
  xlab         = "Ontogeny",
  ylab         = "TAI",
  type        = "1",
  lwd         = 9)

# testing for early conservation model
PlotPattern( ExpressionSet = PhyloExpressionSetExample,
  TestStatistic = "EarlyConservationTest",
  modules      = list(early = 1:2,mid = 3:5,late = 6:7),
  permutations = 100,
  p.value      = TRUE,
  shaded.area  = TRUE,
  xlab         = "Ontogeny",
  ylab         = "TAI",
  type        = "1",
  lwd         = 9)

# use your own permutation matrix
custom_perm_matrix <- bootMatrix(PhyloExpressionSetExample,100)

PlotPattern(ExpressionSet      = PhyloExpressionSetExample,
  TestStatistic               = "FlatLineTest",
  custom.perm.matrix          = custom_perm_matrix,
  type                        = "1",
  xlab                        = "Ontogeny",
  ylab                        = "TAI",
  lwd                         = 9)

```

Description

This function computes for each phylostratum or divergence stratum the corresponding relative expression profile and plots the profiles in N different windows corresponding to the given phylostratum classes or divergence-stratum classes that shall be compared.

For each phylostratum or divergence-stratum the corresponding relative expression profile is being computed as follows:

$$f_{js} = (e_{js} - e_{jmin}) / (e_{jmax} - e_{jmin})$$

where e_{jmin} and e_{jmax} denote the minimum/maximum **mean** expression level of phylostratum j over developmental stages s. This linear transformation corresponds to a shift by e_{jmin} and a subsequent shrinkage by $e_{jmax} - e_{jmin}$. As a result, the relative expression level f_{js} of developmental stage s with minimum e_{js} is 0, the relative expression level f_{js} of the developmental stage s with maximum e_{js} is 1, and the relative expression levels f_{js} of all other stages s range between 0 and 1, accordingly.

Usage

```
PlotRE(ExpressionSet, Groups = NULL, legendName = NULL, colors = NULL,
...)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
Groups	a list containing the phylostrata or divergence strata that correspond to the same phylostratum class or divergence class. For ex. evolutionary old phylostrata: PS1-3 (Class 1) and evolutionary young phylostrata: PS4-12 (Class 2). In this case, the list could be assigned as, Groups = list(c(1:3), c(4:12)). It is also possible to define more than 2 groups of evolutionary ages.
legendName	a character string specifying whether "PS" or "DS" are used to compute relative expression profiles.
colors	colors for relative expression profiles. Default: colors = NULL, hence default colours are used.
...	default graphics parameters.

Details

Studying the relative expression profiles of each phylostratum or divergence-stratum enables the detection of common gene expression patterns shared by several phylostrata or divergence-strata.

Finding similar relative expression profiles among phylostrata or divergence-strata suggests that phylostrata or divergence-strata sharing a similar relative expression profile are regulated by similar gene regulatory elements. Hence, these common phylostrata or divergence-strata might govern similar processes in the given developmental time course.

Value

a plot showing the relative expression profiles of phylostrata or divergence-strata belonging to the same group.

Author(s)

Hajk-Georg Drost

References

Domazet-Loso T and Tautz D. 2010. "A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns". *Nature* (468): 815-818.

Quint M et al. 2012. "A transcriptomic hourglass in plant embryogenesis". *Nature* (490): 98-101.

See Also

[PlotBarRE](#), [RE](#), [REMatrix](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet
PlotRE(PhyloExpressionSetExample, Groups = list(c(1:3), c(4:12)),
       legendName = "PS", lty = 1, lwd = 5)

# or you can choose any combination of groups
PlotRE(PhyloExpressionSetExample, Groups = list(c(1,7,9), c(2:6,8,10:12)),
       legendName = "PS", lty = 1, lwd = 5)

# or multiple groups
PlotRE(PhyloExpressionSetExample, Groups = list(c(1,7,9), c(3:6,8), c(2,10:12)),
       legendName = "PS", lty = 1, lwd = 5)

# example DivergenceExpressionSet
PlotRE(DivergenceExpressionSetExample, Groups = list(c(1:5), c(6:10)),
       legendName = "DS", lty = 1, lwd = 5)

# adding custom colors for relative expression levels:
# -> colors should be ordered by PS/DS starting with PS1,2,3...
PlotRE(PhyloExpressionSetExample,
       Groups = list(c(1:3), c(4:12)),
       legendName = "PS",
       colors = c("black", "red", "green", "brown", "darkmagenta",
                 "blue", "darkred", "darkblue", "darkgreen", "orange",
                 "azure4", "gold4"),
       lty = 1,
       lwd = 5)
```

 PlotReplicateQuality *Plot the Quality of Biological Replicates*

Description

This function performs several quality checks to validate the biological variation between replicates and stages (experiments).

Usage

```
PlotReplicateQuality(ExpressionSet, nrep, FUN = function(x)
  log(stats::var(x)), legend.pos = "topleft", stage.names = NULL, ...)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
nrep	either a numeric value specifying the constant number of replicates per stage or a numeric vector specifying the variable number of replicates for each stage position.
FUN	a function that should be applied to quantify the variability or quality of replicates. The default function is the <code>log(var(x))</code> quantifying the variance between replicates.
legend.pos	the position of the legend, e.g. 'topleft', or 'topright' (see legend).
stage.names	a character vector specifying the stage names.
...	additional graphics parameters.

Details

The following quality checks can be performed:

- Quantification of variability between replicates as density function.

Author(s)

Hajk-Georg Drost

Examples

```
data(PhyloExpressionSetExample)

# visualize log(var(x)) between replicates for each gene and developmental stage
PlotReplicateQuality(ExpressionSet = PhyloExpressionSetExample[1:5000 , 1:8],
  nrep = 2,
  legend.pos = "topright",
  ylim = c(0, 0.2),
  lwd = 6)
```

pMatrix

Compute Partial TAI or TDI Values

Description

This function computes the partial [TAI](#) or [TDI](#) values for each single gene in a `PhyloExpressionSet` or `DivergenceExpressionSet` object.

In detail, each gene gets a *TAI contribution profile* or *TDI contribution profile*.

$$TAI_{is} = f_{is} * ps_i$$

or

$$TDI_{is} = f_{is} * ps_i$$

where TAI_{is} or TDI_{is} is the partial TAI or TDI value of gene i , $f_{is} = e_{is} / \sum e_{is}$ and ps_i is the phylostratum or divergence-stratum of gene i .

Usage

```
pMatrix(ExpressionSet)
```

Arguments

`ExpressionSet` a standard `PhyloExpressionSet` or `DivergenceExpressionSet` object.

Details

The partial TAI or TDI matrix can be used to perform different cluster analyses and also gives an overall impression of the contribution of each gene to the global [TAI](#) or [TDI](#) pattern.

Value

a numeric matrix storing the partial TAI or TDI values for each gene in the corresponding `PhyloExpressionSet` or `DivergenceExpressionSet`.

Author(s)

Hajk-Georg Drost

References

Domazet-Lošo T and Tautz D. 2010. "A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns". *Nature* (468): 815-818.

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet
PTM_ps <- pMatrix(PhyloExpressionSetExample)

# example DivergenceExpressionSet
PTM_ds <- pMatrix(DivergenceExpressionSetExample)

# boxplot of the pMatrix
boxplot(pMatrix(PhyloExpressionSetExample),outline = FALSE)

# boxplot of the pMatrix using log2 transformed expression levels
boxplot(pMatrix(tf(PhyloExpressionSetExample,log2)))
```

pStrata

Compute Partial Strata Values

Description

This function computes the partial [TAI](#) or [TDI](#) values for all Phylostrata or Divergence Strata.

Usage

```
pStrata(ExpressionSet)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet object.

Author(s)

Hajk-Georg Drost

Examples

```
data(PhyloExpressionSetExample)

# compute partial TAI values for each Phylostratum
partialStrata <- pStrata(PhyloExpressionSetExample)

# show that colSums of pStrata is equivalent to the TAI values
all.equal(colSums(partialStrata),TAI(PhyloExpressionSetExample))

# show that colSums of pStrata is equivalent to colSums of pMatrix(PhyloExpressionSetExample)
all.equal(colSums(partialStrata),colSums(pMatrix(PhyloExpressionSetExample)))
```

pTAI	<i>Compute the Phylostratum Contribution to the Global Transcriptome Age Index</i>
------	--

Description

This function takes a standard *ExpressionSet* object and computes the partial contribution of the different phylostrata (ps) to the global Transcriptome Age Index profile.

Usage

```
pTAI(ExpressionSet)
```

Arguments

ExpressionSet a standard PhyloExpressionSet object.

Details

This way of computing the partial contribution of the different phylostrata (ps) to the global Transcriptome Age Index profile was introduced by Domazet-Loso and Tautz, 2010. This function (pTAI) computes the partial TAI contribution for each phylostratum and each developmental stage and returns a data matrix storing the partial TAI contribution value for each phylostratum and each developmental stage.

Author(s)

Hajk-Georg Drost

References

Domazet-Loso T. and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. Nature (468): 815-818.

See Also

[pTDI](#), [TAI](#), [TDI](#), [PlotPattern](#)

Examples

```
data(PhyloExpressionSetExample)

# get the partial contribution of phylostrata to the global
# TAI pattern
pTAI(PhyloExpressionSetExample)
```

pTDI	<i>Compute the Divergence Stratum Contribution to the Global Transcriptome Divergence Index</i>
------	---

Description

This function takes a standard *ExpressionSet* object and computes the partial contribution of the different divergence strata (ds) to the global Transcriptome Divergence Index profile.

Usage

```
pTDI(ExpressionSet)
```

Arguments

ExpressionSet a standard DivergenceExpressionSet object.

Details

This function (pTDI) computes the partial TDI contribution for each phylostratum and each developmental stage and returns a data matrix storing the partial TDI contribution value for each divergence and each developmental stage.

Author(s)

Hajk-Georg Drost

References

- Domazet-Loso T. and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. Nature (468): 815-818.
- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
- Drost HG et al. (2015). *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[pTAI](#), [TAI](#), [TDI](#), [PlotPattern](#)

Examples

```
data(DivergenceExpressionSetExample)

# get the partial contribution of divergence strata to the global
# TDI pattern
pTAI(DivergenceExpressionSetExample)
```

RE *Transform to Relative Expression Levels*

Description

This function computes the relative expression profiles of any given gene expression set. The relative expression profile is being computed as follows:

$$f_s = (e_s - e_{min}) / (e_{max} - e_{min})$$

where e_{min} and e_{max} denote the minimum/maximum mean expression level over the developmental stages s . This linear transformation corresponds to a shift by e_{min} and a subsequent shrinkage by $e_{max} - e_{min}$. As a result, the relative expression level f_s of developmental stage s with minimum e_s is 0, the relative expression level f_s of the developmental stage s with maximum e_s is 1, and the relative expression levels f_s of all other stages s range between 0 and 1, accordingly.

Usage

```
RE(ExpressionMatrix)
```

Arguments

`ExpressionMatrix`

a numeric matrix representing a gene expression matrix for which the relative expression profile shall be computed.

Value

a vector containing the relative expression profile of the corresponding data matrix.

Author(s)

Hajk-Georg Drost

References

Domazet-Lošo T and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. Nature (468): 815-818.

Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.

See Also

[REMatrix](#), [PlotRE](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)

# relative expression profile of PS1 genes
RE(PhyloExpressionSetExample[ which(PhyloExpressionSetExample[, 1] == 1), 3:9 ])
```

ReductiveHourglassTest

Perform the Reductive Hourglass Test

Description

The *Reductive Hourglass Test* aims to statistically evaluate the existence of a phylotranscriptomic hourglass pattern based on [TAI](#) or [TDI](#) computations. The corresponding p-value quantifies the probability that a given TAI or TDI pattern (or any phylotranscriptomics pattern) does not follow an hourglass like shape. A p-value < 0.05 indicates that the corresponding phylotranscriptomics pattern does indeed follow an hourglass (high-low-high) shape.

Usage

```
ReductiveHourglassTest(ExpressionSet, modules = NULL, permutations = 1000,
  lillie.test = FALSE, plotHistogram = FALSE, runs = 10,
  parallel = FALSE, gof.warning = FALSE, custom.perm.matrix = NULL)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
modules	a list storing three elements: early, mid, and late. Each element expects a numeric vector specifying the developmental stages or experiments that correspond to each module. For example, module = list(early = 1:2, mid = 3:5, late = 6:7) divides a dataset storing seven developmental stages into 3 modules.
permutations	a numeric value specifying the number of permutations to be performed for the ReductiveHourglassTest.
lillie.test	a boolean value specifying whether the Lilliefors Kolmogorov-Smirnov Test shall be performed to quantify the goodness of fit.
plotHistogram	a boolean value specifying whether a <i>Lillifor's Kolmogorov-Smirnov-Test</i> shall be performed to test the goodness of fit of the approximated distribution, as well as additional plots quantifying the significance of the observed phylotranscriptomic pattern.
runs	specify the number of runs to be performed for goodness of fit computations, in case plotHistogram = TRUE. In most cases runs = 100 is a reasonable choice. Default is runs = 10 (because it takes less computation time for demonstration purposes).
parallel	performing runs in parallel (takes all cores of your multicore machine).

- `gof.warning` a logical value indicating whether non significant goodness of fit results should be printed as warning. Default is `gof.warning = FALSE`.
- `custom.perm.matrix` a custom `bootMatrix` (permutation matrix) to perform the underlying test statistic. Default is `custom.perm.matrix = NULL`.

Details

The reductive hourglass test is a permutation test based on the following test statistic.

- (1) A set of developmental stages is partitioned into three modules - early, mid, and late - based on prior biological knowledge.
- (2) The mean `TAI` or `TDI` value for each of the three modules `T_early`, `T_mid`, and `T_late` are computed.
- (3) The two differences $D1 = T_{\text{early}} - T_{\text{mid}}$ and $D2 = T_{\text{late}} - T_{\text{mid}}$ are calculated.
- (4) The minimum `D_min` of `D1` and `D2` is computed as final test statistic of the reductive hourglass test.

In order to determine the statistical significance of an observed minimum difference `D_min` the following permutation test was performed. Based on the `bootMatrix` `D_min` is calculated from each of the permuted `TAI` or `TDI` profiles, approximated by a Gaussian distribution with method of moments estimated parameters returned by `fitdist`, and the corresponding p-value is computed by `pnorm` given the estimated parameters of the Gaussian distribution. The *goodness of fit* for the random vector `D_min` is statistically quantified by an Lilliefors (Kolmogorov-Smirnov) test for normality.

In case the parameter `plotHistogram = TRUE`, a multi-plot is generated showing:

- (1) A Cullen and Frey skewness-kurtosis plot generated by `descdist`. This plot illustrates which distributions seem plausible to fit the resulting permutation vector `D_min`. In the case of the *Reductive Hourglass Test* a normal distribution seemed plausible.
- (2) A histogram of `D_min` combined with the density plot is plotted. `D_min` is then fitted by a normal distribution. The corresponding parameters are estimated by *moment matching estimation* using the `fitdist` function.
- (3) A plot showing the p-values for `N` independent runs to verify that a specific p-value is biased by a specific permutation order.
- (4) A barplot showing the number of cases in which the underlying goodness of fit (returned by Lilliefors (Kolmogorov-Smirnov) test for normality) has shown to be significant (`TRUE`) or not significant (`FALSE`). This allows to quantify the permutation bias and their implications on the goodness of fit.

Value

a list object containing the list elements:

`p.value` : the p-value quantifying the statistical significance (high-low-high pattern) of the given phylotranscriptomics pattern.

`std.dev` : the standard deviation of the `N` sampled phylotranscriptomics patterns for each developmental stage `S`.

`lillie.test` : a boolean value specifying whether the *Lillifors KS-Test* returned a p-value > 0.05, which indicates that fitting the permuted scores with a normal distribution seems plausible.

Author(s)

Hajk-Georg Drost

References

Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. *Mol Biol Evol.* 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

Quint M et al. (2012). A transcriptomic hourglass in plant embryogenesis. *Nature* (490): 98-101.

M. L. Delignette-Muller, R. Pouillot, J.-B. Denis and C. Dutang (2014), `fitdistrplus`: help to fit of a parametric distribution to non-censored or censored data.

Cullen AC and Frey HC (1999) *Probabilistic techniques in exposure assessment*. Plenum Press, USA, pp. 81-159.

Evans M, Hastings N and Peacock B (2000) *Statistical distributions*. John Wiley and Sons Inc.

Sokal RR and Rohlf FJ (1995) *Biometry*. W.H. Freeman and Company, USA, pp. 111-115.

Juergen Gross and bug fixes by Uwe Ligges (2012). `nortest`: Tests for Normality. R package version 1.0-2.

<http://CRAN.R-project.org/package=nortest>

Dallal, G.E. and Wilkinson, L. (1986): An analytic approximation to the distribution of Lilliefors' test for normality. *The American Statistician*, 40, 294-296.

Stephens, M.A. (1974): EDF statistics for goodness of fit and some comparisons. *Journal of the American Statistical Association*, 69, 730-737.

<http://stackoverflow.com/questions/4290081/fitting-data-to-distributions?rq=1>

<http://stats.stackexchange.com/questions/45033/can-i-use-kolmogorov-smirnov-test-and-estimate-dist>

<http://cran.r-project.org/doc/contrib/Ricci-distributions-en.pdf>

<http://cran.r-project.org/doc/contrib/Ricci-distributions-en.pdf>

See Also

[rhScore](#), [bootMatrix](#), [FlatLineTest](#), [PlotPattern](#)

Examples

```
data(PhyloExpressionSetExample)

# perform the reductive hourglass test for a PhyloExpressionSet
# here the prior biological knowledge is that stages 1-2 correspond to module 1 = early,
# stages 3-5 to module 2 = mid (phylotypic module), and stages 6-7 correspond to
# module 3 = late
ReductiveHourglassTest(PhyloExpressionSetExample,
                        modules = list(early = 1:2, mid = 3:5, late = 6:7),
                        permutations = 1000)
```

```
# use your own permutation matrix based on which p-values (ReductiveHourglassTest)
# shall be computed
custom_perm_matrix <- bootMatrix(PhyloExpressionSetExample,100)

ReductiveHourglassTest(PhyloExpressionSetExample,
                       modules = list(early = 1:2, mid = 3:5, late = 6:7),
                       custom.perm.matrix = custom_perm_matrix)
```

REMatrix

*Compute a Relative Expression Matrix***Description**

This function computes the relative expression profiles of all given phylostrata or divergence-strata within a given PhyloExpressionSet or DivergenceExpressionSet.

Usage

```
REMatrix(ExpressionSet)
```

Arguments

ExpressionSet a standard PhyloExpressionSet or DivergenceExpressionSet object.

Details

For each phylostratum or divergence-stratum the corresponding relative expression profile is being computed as follows:

$$f_{js} = (e_{js} - e_{jmin}) / (e_{jmax} - e_{jmin})$$

where e_{jmin} and e_{jmax} denote the minimum/maximum mean expression level of phylostratum j over the developmental stages s . This linear transformation corresponds to a shift by e_{jmin} and a subsequent shrinkage by $e_{jmax} - e_{jmin}$. As a result, the relative expression level f_{js} of developmental stage s with minimum e_{js} is 0, the relative expression level f_{js} of the developmental stage s with maximum e_{js} is 1, and the relative expression levels f_{js} of all other stages s range between 0 and 1, accordingly.

Author(s)

Hajk-Georg Drost

References

- Domazet-Loso T and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. Nature (468): 815-818.
- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.

See Also

[RE](#), [PlotRE](#), [PlotBarRE](#)

Examples

```
# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet
REMatrix(PhyloExpressionSetExample)

# example DivergenceExpressionSet
REMatrix(DivergenceExpressionSetExample)
```

 rhScore

Compute the Hourglass Score for the Reductive Hourglass Test

Description

This function reduces the destruction of an hourglass shaped pattern to a single score value.

Based on a given **TAI** or **TDI** pattern the given vector is being divided into three developmental modules: early, mid, and late. The corresponding **TAI** or **TDI** values in each developmental module are accumulated using the *scoringMethod* argument ("max-min" or "mean-mean").

In more detail:

- (1) for a given **TAI** or **TDI** vector *tai_profile* or *tdi_profile*, we classify each value of *tai_profile* or *tdi_profile* into its corresponding developmental module early, mid, or late.
- (2) accumulate the *tai_profile* or *tdi_profile* values in each developmental module using the arithmetic mean (**mean**) in case *scoringMethod* = "mean-mean", or accumulate the *tai_profile* or *tdi_profile* values in each developmental module using **max** for the early and late module and **min** for the mid module in case *scoringMethod* = "max-min".
- (3) then reduce the three values for each developmental module by computing the difference between: early - mid, and late - mid.
- (4) the two difference values are referred to as *a_early* and *a_late*.

Each developmental module now has an accumulated representation value which is being reduced to one value using the *method* argument ("max", "min", or "mean").

Given the two accumulated values for each hourglass module: *a_early* and *a_late*, we reduce the two given values by:

"max"

$$S = \max_{a_{early}, a_{late}}$$

"min"

$$S = \min_{a_{early}, a_{late}}$$

"mean"

$$S = \text{mean}_{a_{\text{early}}, a_{\text{late}}}$$

All together this results in a global score S . This global score S is being returned by this function [rhScore](#).

Usage

```
rhScore(age_vals, early, mid, late, method, scoringMethod)
```

Arguments

age_vals	a numeric vector containing TAI or TDI values for each developmental stage s .
early	a numeric vector including the numeric stage values that correspond to the early phase of development.
mid	a numeric vector including the numeric stage values that correspond to the middle phase of development.
late	a numeric vector including the numeric stage values that correspond to the late phase of development.
method	to determine the two value reduction value, resulting in the global score S : "max", or "min", or "mean".
scoringMethod	method to determine the module accumulation value: "max-min" or "mean-mean".

Details

The gpScore is a heuristic score enabling to construct a test statistic to determine the significance of a present (phylotranscriptomic) hourglass pattern.

Value

a numeric value representing the hourglass destruction score.

Author(s)

Hajk-Georg Drost

References

Drost et al. (2014), Active maintenance of phylotranscriptomic hourglass patterns in animal and plant embryogenesis.

See Also

[ReductiveHourglassTest](#), [TAI](#), [TDI](#)

Examples

```

# read standard phylotranscriptomics data
data(PhyloExpressionSetExample)
data(DivergenceExpressionSetExample)

# example PhyloExpressionSet:

# compute the TAI profile
TAIs <- TAI(PhyloExpressionSetExample)

# compute the global hourglass destruction score
# for the TAIs profile using reduction method: mean(mean-mean)
rh_score <- rhScore(age_vals = TAIs,early = 1:2,mid = 3:5,late = 6:7,
                    method = "mean",scoringMethod = "mean-mean")

# example DivergenceExpressionSet:

# compute the TDI profile
TDIs <- TDI(DivergenceExpressionSetExample)

# compute the global hourglass destruction score for the TDIs profile
# using reduction method: mean(mean-mean)
rh_score <- rhScore(age_vals = TDIs,early = 1:2,mid = 3:5,late = 6:7,
                    method = "mean",scoringMethod = "mean-mean")

```

SelectGeneSet

Select a Subset of Genes in an ExpressionSet

Description

Select a subset of genes stored in the input ExpressionSet.

Usage

```
SelectGeneSet(ExpressionSet, gene.set, use.only.map = FALSE)
```

Arguments

ExpressionSet	a standard PhyloExpressionSet or DivergenceExpressionSet object.
gene.set	a character vector storing the gene ids for which gene expression profiles shall be visualized.
use.only.map	a logical value indicating whether instead of a standard ExpressionSet only a Phylostratigraphic Map or Divergene Map is passed to the function.

Details

This function selects a subset of genes specified in `gene.set` stored in the input `ExpressionSet` and returns a subset `ExpressionSet`.

This function is useful for studying the evolutionary *properties* of a subset of genes stored in the `ExpressionSet`.

Author(s)

Hajk-Georg Drost

See Also

[PlotGeneSet](#), [PlotEnrichment](#), [DiffGenes](#)

Examples

```
data(PhyloExpressionSetExample)

# receive a subset ExpressionSet for the first 5 genes stored in
# the PhyloExpressionSetExample
SelectGeneSet(ExpressionSet = PhyloExpressionSetExample,
              gene.set      = PhyloExpressionSetExample[1:5, 2])

# get a gene subset using only a phylostratigraphic map
ExamplePSMap <- PhyloExpressionSetExample[, 1:2]

SelectGeneSet(ExpressionSet = ExamplePSMap,
              gene.set      = PhyloExpressionSetExample[1:5, 2],
              use.only.map  = TRUE)
```

TAI

Compute the Transcriptome Age Index (TAI)

Description

This function computes the phylogenetically based transcriptome age index (TAI) introduced by Domazet-Lošo & Tautz, 2010.

Usage

```
TAI(PhyloExpressionSet)
```

Arguments

`PhyloExpressionSet`
a standard `PhyloExpressionSet` object.

Details

The TAI measure represents the weighted arithmetic mean (expression levels as weights for the phylostratum value) over all evolutionary age categories denoted as *phylostra*.

$$TAI_s = \sum (e_{is} * ps_i) / \sum e_{is}$$

where TAI_s denotes the TAI value in developmental stage s , e_{is} denotes the gene expression level of gene i in stage s , and ps_i denotes the corresponding phylostratum of gene i , $i = 1, \dots, N$ and N = total number of genes.

Internally the function calls the C++ function `cpp_TAI` to speed up TAI computations.

Value

a numeric vector containing the TAI values for all given developmental stages.

Author(s)

Hajk-Georg Drost

References

- Domazet-Loso T. and Tautz D. (2010). *A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns*. Nature (468): 815-818.
- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
- Drost HG et al. (2015) *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[TDI](#), [PlotPattern](#), [FlatLineTest](#), [ReductiveHourglassTest](#)

Examples

```
# reading a standard PhyloExpressionSet
data(PhyloExpressionSetExample)

# computing the TAI profile of a given PhyloExpressionSet object
TAIs <- TAI(PhyloExpressionSetExample)
```

taxonomy

Retrieving Taxonomic Information of a Query Organism

Description

This function takes the scientific name of a query organism and returns selected output formats of taxonomic information for the corresponding organism.

Usage

```
taxonomy(organism, db = "ncbi", output = "classification")
```

Arguments

organism	a character string specifying the scientific name of a query organism.
db	a character string specifying the database to query, e.g. db = "itiss" or "ncbi".
output	a character string specifying the taxonomic information that shall be returned. Implemented are: output = "classification", "taxid", or "children".

Details

This function is based on the powerful package **taxize** and implements the customized retrieval of taxonomic information for a query organism.

The following data bases can be selected to retrieve taxonomic information:

- db = "itiss" : Integrated Taxonomic Information Service
- db = "ncbi" : National Center for Biotechnology Information

Author(s)

Hajk-Georg Drost

References

Scott Chamberlain and Eduard Szocs (2013). taxize - taxonomic search and retrieval in R. F1000Research, 2:191. URL: <http://f1000research.com/articles/2-191/v2>.

Scott Chamberlain, Eduard Szocs, Carl Boettiger, Karthik Ram, Ignasi Bartomeus, and John Baumgartner (2014) taxize: Taxonomic information from around the web. R package version 0.3.0. <https://github.com/ropensci/taxize>

Examples

```

## Not run:
# retrieving the taxonomic hierarchy of "Arabidopsis thaliana"
# from NCBI Taxonomy
taxonomy("Arabidopsis thaliana",db = "ncbi")

# the same can be applied to database : "itis"
taxonomy("Arabidopsis thaliana",db = "itis")

# retrieving the taxonomic hierarchy of "Arabidopsis"
taxonomy("Arabidopsis",db = "ncbi") # analogous : db = "ncbi" or "itis"

# or just "Arabidopsis"
taxonomy("Arabidopsis",db = "ncbi")

# retrieving the taxonomy id of the query organism and in the corresponding database
# taxonomy("Arabidopsis thaliana",db = "ncbi", output = "taxid")

# the same can be applied to databases : "ncbi" and "itis"
taxonomy("Arabidopsis thaliana",db = "ncbi", output = "taxid")
taxonomy("Arabidopsis thaliana",db = "itis", output = "taxid")

# retrieve children taxa of the query organism stored in the corresponding database
taxonomy("Arabidopsis",db = "ncbi", output = "children")

# the same can be applied to databases : "ncbi" and "itis"
taxonomy("Arabidopsis thaliana",db = "ncbi", output = "children")
taxonomy("Arabidopsis thaliana",db = "itis", output = "children")

## End(Not run)

```

TDI

Compute the Transcriptome Divergence Index (TDI)

Description

This function computes the sequence distance based transcriptome divergence index (TDI) introduced by Quint et al., 2012.

Usage

```
TDI(DivergenceExpressionSet)
```

Arguments

DivergenceExpressionSet

a standard PhyloExpressionSet or DivergenceExpressionSet object.

Details

The TDI measure represents the weighted arithmetic mean (expression levels as weights for the divergence-stratum value) over all gene divergence categories denoted as *divergence-strata*.

$$TDI_s = \sum (e_{is} * ds_i) / \sum e_{is}$$

where TDI_s denotes the TDI value in developmental stage s, e_is denotes the gene expression level of gene i in stage s, and ds_i denotes the corresponding divergence-stratum of gene i, $i = 1, \dots, N$ and N = total number of genes.

Internally the function is written in C++ to speed up TDI computations.

Value

a numeric vector containing the TDI values for all given developmental stages.

Author(s)

Hajk-Georg Drost

References

- Quint M et al. (2012). *A transcriptomic hourglass in plant embryogenesis*. Nature (490): 98-101.
- Drost HG et al. (2015). *Evidence for Active Maintenance of Phylotranscriptomic Hourglass Patterns in Animal and Plant Embryogenesis*. Mol Biol Evol. 32 (5): 1221-1231 doi:10.1093/molbev/msv012.

See Also

[TAI](#), [PlotPattern](#), [FlatLineTest](#), [ReductiveHourglassTest](#)

Examples

```
# reading a standard DivergenceExpressionSet
data(DivergenceExpressionSetExample)

# computing the TDI profile of a given DivergenceExpressionSet object
TDIs <- TDI(DivergenceExpressionSetExample)
```

 tf

Transform Gene Expression Levels

Description

This function transforms the gene expression set stored in an input PhloExpressionSet or DivergenceExpressionSet object and returns a PhloExpressionSet or DivergenceExpressionSet object with transformed expression levels. The resulting transformed PhloExpressionSet or DivergenceExpressionSet object can then be used for subsequent analyses based on transformed expression levels.

Usage

```
tf(ExpressionSet, FUN)
```

Arguments

ExpressionSet a standard PhloExpressionSet or DivergenceExpressionSet object.

FUN any valid function that transformes gene expression levels.

Details

Motivated by the dicussion raised by Piasecka et al., 2013, the influence of gene expression transformation on the global phylotranscriptomics pattern does not seem negligible. Hence, different transformations can result in qualitatively different [TAI](#) or [TDI](#) patterns.

Initially, the [TAI](#) and [TDI](#) formulas were defined for absolute expression levels. So using the initial [TAI](#) and [TDI](#) formulas with transformed expression levels might turn out in qualitatively different patterns when compared with non-transformed expression levels, but might also belong to a different class of models, since different valid expression level transformation functions result in different patterns.

The purpose of this function is to allow the user to study the qualitative impact of different transformation functions on the global [TAI](#) and [TDI](#) pattern, or on any subsequent phylotranscriptomics analysis.

The examples using the *PhloExpressionSetExample* data set show that using common gene expression transformation functions: [log2](#) (Quackenbush, 2001 and 2002), [sqrt](#) (Yeung et al., 2001), [boxcox](#), or *inverse hyperbolic sine transformation*, each transformation results in qualitatively different patterns. Nevertheless, for each resulting pattern the statistical significance can be tested using either the [FlatLineTest](#) or [ReductiveHourglassTest](#) (Drost et al., 2014) to quantify the significance of interest.

Value

a standard PhloExpressionSet or DivergenceExpressionSet object storing transformed gene expression levels.

Author(s)

Hajk-Georg Drost

References

Piasecka B, Lichocki P, Moretti S, et al. (2013) The hourglass and the early conservation models—co-existing patterns of developmental constraints in vertebrates. *PLoS Genet.* 9(4): e1003476.

Quint M., Drost H.G., Gabel A., Ullrich K.K., Boenn M., Grosse I. (2012) A transcriptomic hourglass in plant embryogenesis. *Nature* 490: 98-101.

Domazet-Loaso T., Tautz D. (2010) A phylogenetically based transcriptome age index mirrors ontogenetic divergence patterns. *Nature* 468: 815-8.

Drost H.G., Gabel A., Grosse I., Quint M. (2015) Evidence for Active Maintenance of Phylo-transcriptomic Hourglass Patterns in Animal and Plant Embryogenesis. *Mol Biol Evol.* 32 (5): 1221-1231. doi: 10.1093/molbev/msv012

K.Y. Yeung et al.: Model-based clustering and data transformations for gene expression data. *Bioinformatics* 2001, 17:977-987

K.Y. Yeung et al.: Supplement to Model-based clustering and data transformations for gene expression data - Data Transformations and the Gaussian mixture assumption. *Bioinformatics* 2001, 17:977-987

P.A.C. Hoen et al.: Deep sequencing-based expression analysis shows major advances in robustness, resolution and inter-lab portability over five microarray platforms. *Nucleic Acids Research* 2008, Vol. 36, No. 21

H.H. Thygesen et al.: Comparing transformation methods for DNA microarray data. *BMC Bioinformatics* 2004, 5:77

John Quackenbush: Microarray data normalization and transformation. *Nature Genetics* 2002, 32:496-501

John Quackenbush: Computational Analysis of Microarray Data. *Nature Reviews* 2001, 2:418-427

R. Nadon and J. Shoemaker: Statistical issues with microarrays: processing and analysis. *TRENDS in Genetics* 2002, Vol. 18 No. 5:265-271

B.P. Durbin et al.: A variance-stabilizing transformation for gene-expression microarray data. *Bioinformatics* 2002, 18:S105-S110

J. M. Bland et al.: Transforming data. *BMJ* 1996, 312:770

<http://stats.stackexchange.com/questions/1444/how-should-i-transform-non-negative-data-including-zero>

<http://stats.stackexchange.com/questions/78929/how-can-i-estimate-theta-for-the-inverse-hyperbolic-cosine>

John B. Burbidge, Lonnie Magee and A. Leslie Robb (1988) Alternative Transformations to Handle Extreme Values of the Dependent Variable. *Journal of the American Statistical Association*, 83(401): 123-127.

G. E. P. Box and D. R. Cox (1964) An Analysis of Transformations. *Journal of the Royal Statistical Society. Series B (Methodological)*, 26(2): 211-252.

See Also

[TAI](#), [TDI](#), [FlatLineTest](#), [ReductiveHourglassTest](#)

Examples

```
data(PhyloExpressionSetExample)

# a simple example is to transform the gene expression levels
# of a given PhyloExpressionSet using a sqrt or log2 transformation

PES.sqrt <- tf(PhyloExpressionSetExample, sqrt)

PES.log2 <- tf(PhyloExpressionSetExample, log2)

# in case a given PhyloExpressionSet already stores gene expression levels
# that are log2 transformed and need to be re-transformed to absolute
```

```
# expression levels, to perform subsequent phylotranscriptomics analyses
# (that are defined for absolute expression levels), one can re-transform
# a PhyloExpressionSet like this:
```

```
PES.absolute <- tf(PES.log2 , function(x) 2^x)
```

```
# which should be the same as PhyloExpressionSetExample :
head(PhyloExpressionSetExample)
head(PES.absolute)
```

```
# plotting the TAI using log2 transformed expression levels
# and performing the Flat Line Test to obtain the p-value
PlotPattern(ExpressionSet = tf(PhyloExpressionSetExample, log2),
             type          = "l",
             lwd           = 5,
             TestStatistic = "FlatLineTest")
```

Index

..., 45

age.apply, 3, 33

axis, 45

bar.colors, 4

bootMatrix, 5, 14, 15, 21–23, 45, 57, 58

boxcox, 68

CollapseReplicates, 6

colMeans, 3

CombinatorialSignificance, 7

cor, 36

data.frame, 12, 28

descdist, 15, 22, 57

DiffGenes, 9, 41, 63

DivergenceExpressionSetExample, 12, 28

EarlyConservationTest, 5, 6, 13, 17, 44–46

ecScore, 15, 16

EnrichmentTest, 17, 40

equalizeLibSizes, 10

exactTestByDeviance, 10

exactTestBySmallP, 10

exactTestDoubleTail, 10

expand.grid, 8, 9

Expressed, 11, 18

fisher.test, 17, 18, 39, 40

fitdist, 14, 15, 21, 22, 57

FlatLineTest, 5–9, 15, 21, 21, 44–46, 58, 64, 67–69

geom.mean, 23

harm.mean, 24

is.ExpressionSet, 24

kruskal.test, 29–32

lapply, 3

legend, 45, 50

log2, 68

MatchMap, 25

matplot, 41

max, 6, 60

mean, 6, 48, 60

median, 6

min, 6, 60

omitMatrix, 27

p.adjust, 29, 39

PhyloExpressionSetExample, 13, 28

plot, 34, 45

PlotBarRE, 29, 32, 33, 43, 49, 60

PlotCategoryExpr, 31

PlotContribution, 34

PlotCorrelation, 35

PlotDistribution, 37

PlotEnrichment, 17, 18, 38, 41, 63

PlotGeneSet, 41, 63

PlotMeans, 32, 33, 42

PlotPattern, 15, 23, 35, 44, 53, 54, 58, 64, 67

PlotRE, 30, 32, 33, 43, 47, 55, 60

PlotReplicateQuality, 50

pMatrix, 33, 51

pnorm, 14, 57

pStrata, 33, 52

pTAI, 33, 35, 53, 54

pTDI, 33, 35, 53, 54

RE, 3, 30, 43, 49, 55, 60

ReductiveHourglassTest, 5, 6, 15, 44–46, 56, 61, 64, 67–69

REMatrix, 3, 30, 43, 49, 55, 59

rhScore, 58, 60, 61

SelectGeneSet, 41, 62

split, 3

sqrt, 68

TAI, 5, 13, 14, 16, 17, 21, 23, 27, 33–35,
43–46, 51–54, 56, 57, 60, 61, 63,
67–69

tapply, 3

taxonomy, 65

TDI, 5, 13, 14, 16, 17, 21, 23, 27, 33–35,
43–46, 51–54, 56, 57, 60, 61, 64, 66,
68, 69

tf, 67