

Package ‘precintcon’

February 20, 2015

Type Package

Title Precipitation Intensity, Concentration and Anomaly Analysis

Version 2.1

Date 2015-02-06

LazyData true

Author Lucas Venezian Povoá

Maintainer Lucas Venezian Povoá <lucasvenez@gmail.com>

Description It contains functions to analyze the precipitation intensity, concentration and anomaly.

URL <https://github.com/lucasvenez/precintcon>

BugReports <https://github.com/lucasvenez/precintcon/issues>

Depends R (>= 2.14), ggplot2, scales

License GPL (>= 2)

Collate 'as.precintcon.annual.r' 'as.annual.r' 'as.precintcon.daily.r'
'as.daily.r' 'as.precintcon.decade.r' 'as.decade.r'
'precintcon.deciles.analysis.r' 'deciles.r'
'as.precintcon.deciles.r' 'as.deciles.r' 'precintcon.fd.r'
'as.precintcon.fd.r' 'as.fd.r' 'as.precintcon.monthly.r'
'as.monthly.r' 'as.precintcon.seasonal.r' 'as.seasonal.r'
'precintcon.ci.per.year.analysis.r' 'ci.per.year.r'
'precintcon.ci.analysis.r' 'ci.r'
'precintcon.limits.analysis.r' 'limits.r'
'precintcon.pci.analysis.r' 'pci.r' 'precintcon.pn.analysis.r'
'pn.r' 'precintcon.plot.deciles.r' 'pplot.deciles.r'
'precintcon.plot.histogram.r' 'pplot.histogram.r'
'precintcon.plot.lorenz.r' 'pplot.lorenz.r'
'precintcon.plot.pci.r' 'pplot.pci.r' 'precintcon.plot.pn.r'
'pplot.pn.r' 'precintcon.plot.rai.r' 'pplot.rai.r'
'precintcon.plot.spi.r' 'pplot.spi.r' 'precintcon.H.r'
'precintcon.Z.r' 'precintcon.b.r' 'precintcon.classification.r'
'precintcon.gamma.r' 'precintcon.ln.a.r' 'precintcon.max.r'
'precintcon.min.r' 'precintcon.monthly.aggregation.r'

'precintcon.plot.lorenz.ungrouped.r' 'precintcon.pn.r'
 'precintcon.r' 'precintcon.r.squared.r'
 'precintcon.rai.analysis.r' 'precintcon.read.data.r'
 'precintcon.spi.analysis.r'
 'precintcon.spi.per.year.analysis.r'
 'precintcon.stat.analysis.r' 'precintcon.trend.test.r' 'rai.r'
 'read.data.r' 'spi.per.year.r' 'spi.r' 'stat.r'

NeedsCompilation no

Repository CRAN

Date/Publication 2015-02-19 12:14:45

R topics documented:

| | |
|-----------------|----|
| as.annual | 3 |
| as.daily | 4 |
| as.decade | 5 |
| as.deciles | 6 |
| as.fd | 7 |
| as.monthly | 8 |
| as.seasonal | 9 |
| ci | 10 |
| ci.per.year | 11 |
| daily | 12 |
| limits | 13 |
| monthly | 14 |
| pci | 15 |
| pn | 16 |
| pplot.deciles | 17 |
| pplot.histogram | 18 |
| pplot.lorenz | 19 |
| pplot.pci | 20 |
| pplot.pn | 22 |
| pplot.rai | 23 |
| pplot.spi | 24 |
| precintcon | 25 |
| rai | 26 |
| read.data | 27 |
| spi | 28 |
| spi.per.year | 29 |
| stat | 30 |

Index

32

| | |
|-----------|---|
| as.annual | <i>Convert a precipitation serie to an annual serie</i> |
|-----------|---|

Description

Converts a daily, monthly, or seasonal precipitation serie to an annual serie.

Usage

```
as.annual(object)
```

Arguments

| | |
|--------|---|
| object | a <code>precintcon.daily</code> , <code>precintcon.monthly</code> , or <code>precintcon.seasonal</code> object or a <code>data.frame</code> containing 33 or 3 columns. |
|--------|---|

Value

A `data.frame` (`precintcon.annual`) containing the following variables:

- `year` is the year.
- `precipitation` is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[as.daily](#) [as.monthly](#) [as.seasonal](#) [pplot.lorenz](#) [read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.annual(daily)
```

`as.daily`*Convert a data.frame to a precintcon.daily.*

Description

Converts a `data.frame` to a `precintcon.daily`.

Usage

```
as.daily(object, na.value = NA)
```

Arguments

| | |
|-----------------------|---|
| <code>object</code> | a <code>precintcon.daily</code> or a <code>data.frame</code> containing 33 columns. |
| <code>na.value</code> | the value used for representing non-existent values (Default value: NA). |

Value

A `data.frame` (`precintcon.daily`) containing the following variables:

- `year` is the year.
- `month` is the month.
- `d1` is the precipitation value in millimeters of the 1st day of the month.
- `d2` is the precipitation value in millimeters of the 2nd day of the month.
- `d3` is the precipitation value in millimeters of the 3rd day of the month.
- `d4` is the precipitation value in millimeters of the 4th day of the month.
- `d5` is the precipitation value in millimeters of the 5th day of the month.
- `d6` is the precipitation value in millimeters of the 6th day of the month.
- `d7` is the precipitation value in millimeters of the 7th day of the month.
- `d8` is the precipitation value in millimeters of the 8th day of the month.
- `d9` is the precipitation value in millimeters of the 9th day of the month.
- `d10` is the precipitation value in millimeters of the 10th day of the month.
- `d11` is the precipitation value in millimeters of the 11th day of the month.
- `d12` is the precipitation value in millimeters of the 12th day of the month.
- `d13` is the precipitation value in millimeters of the 13th day of the month.
- `d14` is the precipitation value in millimeters of the 14th day of the month.
- `d15` is the precipitation value in millimeters of the 15th day of the month.
- `d16` is the precipitation value in millimeters of the 16th day of the month.
- `d17` is the precipitation value in millimeters of the 17th day of the month.
- `d18` is the precipitation value in millimeters of the 18th day of the month.
- `d19` is the precipitation value in millimeters of the 19th day of the month.

- d20 is the precipitation value in millimeters of the 20th day of the month.
- d21 is the precipitation value in millimeters of the 21th day of the month.
- d22 is the precipitation value in millimeters of the 22th day of the month.
- d23 is the precipitation value in millimeters of the 23th day of the month.
- d24 is the precipitation value in millimeters of the 24th day of the month.
- d25 is the precipitation value in millimeters of the 25th day of the month.
- d26 is the precipitation value in millimeters of the 26th day of the month.
- d27 is the precipitation value in millimeters of the 27th day of the month.
- d28 is the precipitation value in millimeters of the 28th day of the month.
- d29 is the precipitation value in millimeters of the 29th day of the month.
- d30 is the precipitation value in millimeters of the 30th day of the month.
- d31 is the precipitation value in millimeters of the 31th day of the month.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[as.decade](#) [as.annual](#) [as.seasonal](#) [as.monthly](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.daily(daily)
```

as.decade

Convert a precipitation serie to a decade serie

Description

Converts a daily, monthly, seasonal, or annual precipitation serie to a decade serie.

Usage

```
as.decade(object)
```

Arguments

object a `precintcon.daily`, `precintcon.monthly`, `precintcon.seasonal`, `precintcon.annual` object or a `data.frame` containing 33 or 3 columns.

Value

A data.frame (precintcon.decade) containing the following variables:

- year is the year.
- precipitation is the decade's precipitation in millimeters.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[as.precintcon.annual](#) [as.precintcon.seasonal](#) [as.precintcon.monthly](#) [as.precintcon.daily](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.monthly(daily)
```

as.deciles

Deciles of a precipitation serie

Description

Groups the monthly precipitation into deciles, i.e., it splits a precipitation serie into ten equal parts in crescent order, from the lower to the highest precipitation.

Usage

```
as.precintcon.deciles(object)
```

Arguments

object a daily or monthly precipitation serie.

Value

A data.frame (precintcon.deciles) containing the following variables:

- D1 corresponds to the precipitation values not exceeding 10% of the lowest values.
- D2 corresponds to the precipitation values not exceeding 20 of the lowest values.
- D3 corresponds to the precipitation values not exceeding 30 of the lowest values.
- D4 corresponds to the precipitation values not exceeding 40% of the lowest values.

- D5 is equals to the median that corresponds to the precipitation values not exceeding 50% of the lowest values.
- D6 corresponds to the precipitation values not exceeding 60% of the lowest values.
- D7 corresponds to the precipitation values not exceeding 70 of the lowest values.
- D8 corresponds to the precipitation values not exceeding 80 of the lowest values.
- D9 corresponds to the precipitation values not exceeding 90 of the lowest values.
- D10 corresponds to the precipitation values not exceeding 100 of the lowest values.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[read.data](#)

as.fd

Frequency distribution of a precipitation serie

Description

Calculates the frequency distribution of a daily precipitation serie based on interval.

Usage

```
as.precintcon.fd(object, interval = 1)
```

Arguments

| | |
|----------|---|
| object | a daily precipitation serie. |
| interval | the interval in millimeters for calculating the frequency distribution. |

Value

A data.frame (precintcon.fd) containing the following variables:

- initial.class is the initial value of the class.
- final.class is the final value of the class.
- midpoint is the middle point of the class.
- n is the absolute frequency, i.e., the number of days in each class.
- sum.n is the cumulative frequency, obtained by adding the absolute frequencies of all the classes up to the one under consideration.
- P is the pluviometric total of each class, obtained by multiplying midpoint by n.
- sum.P is the cumulative class's pluviometric total, obtained by adding the pluviometric total of all the classes up to the one under consideration.
- p.sum.n is the cumulative percentage of rainy days.
- p.sum.P is the cumulative percentage of rainfall amounts.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[read.data.as.daily.ci](#)

Examples

```
##
# Loading the daily precipitation serie
data(daily)

##
# Performing the frequency distribution
as.precintcon.fd(daily)
```

as.monthly

Convert a daily precipitation serie to a monthly serie

Description

Converts a daily precipitation serie to a monthly serie.

Usage

```
as.monthly(object)
```

Arguments

object a precintcon.daily object or a data.frame containing 33 or 3 columns

Value

A data.frame (precintcon.monthly) containing the following variables:

- year is the year.
- month is the month.
- precipitation is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[pplot.lorenz.read.data](#)

Examples

```
## Loading the daily precipitation serie.  
#  
data(daily)  
  
## Converting precipitation  
#  
as.monthly(daily)
```

| | |
|-------------|---|
| as.seasonal | <i>Convert a precipitation serie to an seasonal serie</i> |
|-------------|---|

Description

Converts a daily or monthly precipitation serie to a seasonal serie.

Usage

```
as.seasonal(object)
```

Arguments

object a precintcon.daily, or precintcon.monthly object or a data.frame containing 33 or 3 columns.

Value

A data.frame (precintcon.seasonal) containing the following variables:

- year is the year.
- season is the season.
- precipitation is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.seasonal(daily)
```

| | |
|----|----------------------------|
| ci | <i>Concentration Index</i> |
|----|----------------------------|

Description

Calculates the Concentration Index (CI) on a daily precipitation serie.

Usage

```
ci(..., interval = 1)
```

Arguments

| | |
|----------|---|
| interval | the interval in millimeters applied for calculating the concentration index. (Default value: 1) |
| ... | a set of daily precipitation series. |

Value

A data.frame containing the following variables:

- dataset is the precipitation serie name.
- a is the constant of the exponential curve defined via the least-squares method.
- b is the constant of the exponential curve defined via the least-squares method.
- r2 is the determination of coefficient of determination (R2) of the exponential model.
- A is the area over the exponential curve.
- S is the are compressed for the exponential curve.
- ci is the concentration index.
- PP_5 is the precipitation percentage determined by 5% of the raining days.
- PP_10 is the precipitation percentage determined by 10% of the raining days.
- PP_15 is the precipitation percentage determined by 15% of the raining days.
- PP_20 is the precipitation percentage determined by 20% of the raining days.
- PP_25 is the precipitation percentage determined by 25% of the raining days.
- PP_30 is the precipitation percentage determined by 30% of the raining days.
- PP_50 is the precipitation percentage determined by 50% of the raining days.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[pplot.lorenz read.data as.daily](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the Concentration Index Analysis
ci(daily, interval = 1)
```

| | |
|-------------|-------------------------------------|
| ci.per.year | <i>Concentration Index per Year</i> |
|-------------|-------------------------------------|

Description

Calculates the Concentration Index (CI) per year on a daily precipitation serie.

Usage

```
ci.per.year(object, interval = 1)
```

Arguments

| | |
|----------|---|
| object | a daily precipitation serie. |
| interval | the interval in millimeters applied for calculating the concentration index. (Default value: 1) |

Value

A data.frame (precintcon.ci) containing the following variables:

- year is the year.
- ci is the concentration index.

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data.as.daily](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the Concentration Index Analysis
ci.per.year(daily, interval = 1)
```

daily

Daily precipitation between 1976 and 2010

Description

This data set gives the daily precipitation (in millimeters) between 1976 and 2010, as compiled by the National Water Agency (ANA), Brazil.

Usage

`data(daily)`

Format

A data frame with 420 observations on the following 33 variables:

`year` the year.

`month` the month.

`d1` the precipitation value in millimeters of the day #1 of the month.

`d2` the precipitation value in millimeters of the day #2 of the month.

`d3` the precipitation value in millimeters of the day #3 of the month.

`d4` the precipitation value in millimeters of the day #4 of the month.

`d5` the precipitation value in millimeters of the day #5 of the month.

`d6` the precipitation value in millimeters of the day #6 of the month.

`d7` the precipitation value in millimeters of the day #7 of the month.

`d8` the precipitation value in millimeters of the day #8 of the month.

`d9` the precipitation value in millimeters of the day #9 of the month.

`d10` the precipitation value in millimeters of the day #10 of the month.

`d11` the precipitation value in millimeters of the day #11 of the month.

`d12` the precipitation value in millimeters of the day #12 of the month.

`d13` the precipitation value in millimeters of the day #13 of the month.

`d14` the precipitation value in millimeters of the day #14 of the month.

`d15` the precipitation value in millimeters of the day #15 of the month.

`d16` the precipitation value in millimeters of the day #16 of the month.

`d17` the precipitation value in millimeters of the day #17 of the month.

`d18` the precipitation value in millimeters of the day #18 of the month.

`d19` the precipitation value in millimeters of the day #19 of the month.

`d20` the precipitation value in millimeters of the day #20 of the month.

`d21` the precipitation value in millimeters of the day #21 of the month.

`d22` the precipitation value in millimeters of the day #22 of the month.

d23 the precipitation value in millimeters of the day #23 of the month.
 d24 the precipitation value in millimeters of the day #24 of the month.
 d25 the precipitation value in millimeters of the day #25 of the month.
 d26 the precipitation value in millimeters of the day #26 of the month.
 d27 the precipitation value in millimeters of the day #27 of the month.
 d28 the precipitation value in millimeters of the day #28 of the month.
 d29 the precipitation value in millimeters of the day #29 of the month.
 d30 the precipitation value in millimeters of the day #30 of the month.
 d31 the precipitation value in millimeters of the day #31 of the month.

Source

National Water Agency (ANA) <http://www2.ana.gov.br/Paginas/default.aspx>

Examples

```
data(daily)
## maybe pci(daily) ; rai(daily) ...
```

limits

Limits

Description

Calculates the upper and lower limit on a set of daily or monthly precipitation series.

Usage

```
limits(...)
```

Arguments

... a set of daily or monthly precipitation series.

Value

A data.frame containing the following variables:

- dataset is the precipitation serie name.
- max is the maximum value in the precipitation serie.
- max.date is the first date of the maximum precipitation serie.
- min is the minimum value in the precipitation serie.
- min.date is the first date of the minimum precipitation serie.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[read.data.as.daily](#)

Examples

```
##
# Loading the monthly precipitation serie.
data(monthly)

##
# Performing the Concentration Index Analysis
limits(monthly)
```

monthly

Monthly precipitation between 1950 and 1992.

Description

This dataset gives the monthly precipitation (in millimeters) between 1950 and 1992, as compiled by the National Water Agency (ANA), Brazil.

Usage

```
data(monthly)
```

Format

A data frame with 516 observations on the following 3 variables:

year the year.

month the month.

precipitation the precipitation amount in millimeters.

Source

National Water Agency (ANA) <http://www2.ana.gov.br/Paginas/default.aspx>

Examples

```
data(monthly)
## maybe pci(monthly) ; rai(monthly) ...
```

| | |
|-----|--|
| pci | <i>Precipitation Concentration Index</i> |
|-----|--|

Description

Calculates the Precipitation Concentration Index (PCI) on a daily or monthly precipitation serie.

Usage

```
pci(object)
```

Arguments

object a daily or monthly precipitation serie.

Value

A data.frame containing the following variables:

- year is the year.
- pci is the precipitation concentration index.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[pplot.pci](#) [read.data.as.daily](#) [as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Precipitation Concentration Index analysis  
pci(monthly)
```

pn *Percentage of Normal*

Description

Calculates the Percentage of Normal (PN) on a daily or monthly precipitation serie.

Usage

```
pn(object, interval = 30, scale = "a")
```

Arguments

| | |
|----------|--|
| object | a daily or monthly precipitation serie. |
| interval | the number of months applied for calculating the percentage of normal. |
| scale | the scale used for calculating the percentage of normal, which should be either "w" for weak (not supported yet), "m" for month, "s" for season, or "d" for decades. |

Value

A data.frame (precintcon.pn) containing the following variables:

- year is the year.
- month is the month. It exists only whether scale = "m".
- pn is the percentage of normal.

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[pplot.pn read.data as.daily as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Percentage of Normal analysis  
pn(monthly)
```

| | |
|---------------|---------------------|
| pplot.deciles | <i>Plot deciles</i> |
|---------------|---------------------|

Description

Plots the deciles of a precipitation serie.

Usage

```
pplot.deciles(..., grouped = FALSE, ylab = "Precipitation",  
legend.title = "Legend", legend = NULL,  
fontsize = 10, axis.text.color = "black",  
export = FALSE, export.name = "deciles_plot.png",  
width = 8.6, height = 7.5, units = "cm")
```

Arguments

| | |
|-----------------|---|
| grouped | a logical value that defines whether all datasets should be plotted in the same graph or not. (Default value: FALSE) |
| ylab | the text for the y axis. (Default value: "Precipitation") |
| legend.title | the text for the legend title. (Default value: "Legend") |
| legend | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| fontsize | the font size value in pt. (Default value: 10) |
| axis.text.color | the legend colors. (Default value: "black") |
| export | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| export.name | the text for defining the exported file name. It is only used if export = TRUE. (Default value: "deciles_plot.png") |
| width | the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6) |
| height | the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5) |
| units | the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm") |
| ... | a set of daily or monthly precipitation serie. |

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[deciles.read.data](#)

Examples

```
## Loading the monthly precipitation serie.
#
data(monthly)

## Performing the a set of statistical analysis
#
pplot.deciles(monthly)
```

pplot.histogram *Plot histogram*

Description

Plots the histogram of a precipitation serie.

Usage

```
pplot.histogram(..., density = FALSE,
grouped = FALSE, xlab = "Precipitation (mm)",
ylab = "Frequency", legend.title = "Legend",
legend = NULL, fontsize = 10, axis.text.color = "black",
export = FALSE, export.name = "histogram_plot.png",
width = 10, height = 10, units = "cm")
```

Arguments

| | |
|-----------------|---|
| density | the logical value for defining whether the graph should be plotted with bars or lines. (Default value: FALSE) |
| grouped | the logical value for defining whether the series should be plotted in the same graph or not. (Default value: FALSE) |
| xlab | the text for the x axis. (Default value: "Precipitation (mm)") |
| ylab | the text for the y axis. (Default value: "Frequency") |
| legend.title | the text for the legend title. (Default value: "Legend") |
| legend | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| fontsize | the font size value in pt. (Default value: 10) |
| axis.text.color | the legend colors. (Default value: "black") |
| export | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| export.name | the text for defining the exported file name. It is only used if export = TRUE. (Default value: "histogram_plot.png") |
| width | the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 10) |

| | |
|--------|---|
| height | the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 10) |
| units | the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm") |
| ... | a set of daily or monthly precipitation series. |

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[read.data](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the a set of statistical analysis
pplot.histogram(daily)
```

| | |
|--------------|----------------------------|
| pplot.lorenz | <i>Plot Lorenz's curve</i> |
|--------------|----------------------------|

Description

Plots the Lorenz's curve of a precipitation serie.

Usage

```
pplot.lorenz(..., interval = 1, grouped = FALSE,
xlab = expression(sum(n[i]), i==1), ylab = expression(sum(P[i]), i==1),
legend.title = "Legend", legend = NULL, fontsize = 10,
axis.text.color = "black", export = FALSE, export.name = "lorenz_plot.png",
width = 8.6, height = 7.5, units = "cm")
```

Arguments

| | |
|----------|--|
| interval | the interval in millimeters applied for calculating the Lorenz's curve. (Default value: 1) |
| grouped | the logical value for defining whether all series should be plotted in the same graph or not. (Default value: FALSE) |
| xlab | the text for the x axis. (Default value: expression(sum(n[i]), i==1)) |
| ylab | the text for the y axis. (Default value: expression(sum(P[i]), i==1)) |

| | |
|------------------------------|---|
| <code>legend.title</code> | the text for the legend title. (Default value: "Legend") |
| <code>legend</code> | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| <code>fontsize</code> | the font size value in pt. (Default value: 10) |
| <code>axis.text.color</code> | the legend colors. (Default value: "black") |
| <code>export</code> | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| <code>export.name</code> | the text for defining the exported file name. It is only used if <code>export = TRUE</code> . (Default value: "histogram_plot.png") |
| <code>width</code> | the number for defining the exported graph width. It is only used if <code>export = TRUE</code> . (Default value: 10) |
| <code>height</code> | the number for defining the exported graph height. It is only used if <code>export = TRUE</code> . (Default value: 10) |
| <code>units</code> | the text for defining the units of the height and width parameters. It is only used if <code>export = TRUE</code> . (Default value: "cm") |
| <code>...</code> | a set of daily precipitation series. |

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[ci.read.data.as.daily](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the a set of statistical analysis
pplot.lorenz(daily, interval = 1)
```

pplot.pci

Plot Precipitation Concentration Index

Description

Plots the Precipitation Concentration Index of a precipitation serie.

Usage

```
pplot.pci(..., xlab = "Years", ylab = "PCI", legend = NULL,
          fontsize = 10, axis.text.color = "black", export = FALSE,
          export.name = "pci_plot.png", width = 10, height = 10, units = "cm")
```

Arguments

| | |
|-----------------|---|
| xlab | the text for the x axis. (Default value: "Years") |
| ylab | the text for the y axis. (Default value: "PCI") |
| legend | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| fontsize | the font size value in pt. (Default value: 10) |
| axis.text.color | the legend colors. (Default value: "black") |
| export | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| export.name | the text for defining the exported file name. It is only used if export = TRUE. (Default value: "pci_plot.png") |
| width | the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 10) |
| height | the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 10) |
| units | the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm") |
| ... | a set of daily precipitation series. |

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[read.data](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the a set of statistical analysis
pplot.pci(daily)
```

pplot.pn

*Plot Percent of Normal***Description**

Plots the Percent of Normal of a precipitation serie.

Usage

```
pplot.pn(..., interval = 30, scale = "a", xlab = NA, ylab = "PN",
          fontsize = 10, axis.text.color = "black", legend = NULL,
          export = FALSE, export.name = "pn_plot.png", width = 10,
          height = 10, units = "cm")
```

Arguments

| | |
|------------------------------|--|
| <code>interval</code> | the number of months applied for calculating the percentage of normal. |
| <code>scale</code> | the scale used for calculating the percentage of normal, which should be either "w" for weak (not supported yet), "m" for month, "s" for season, or "d" for decades. |
| <code>xlab</code> | the text for the x axis. (Default value: NA) |
| <code>ylab</code> | the text for the y axis. (Default value: "PN") |
| <code>fontsize</code> | the font size value in pt. (Default value: 10) |
| <code>axis.text.color</code> | the legend colors. (Default value: "black") |
| <code>legend</code> | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| <code>export</code> | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| <code>export.name</code> | the text for defining the exported file name. It is only used if <code>export = TRUE</code> . (Default value: "pci_plot.png") |
| <code>width</code> | the number for defining the exported graph width. It is only used if <code>export = TRUE</code> . (Default value: 10) |
| <code>height</code> | the number for defining the exported graph height. It is only used if <code>export = TRUE</code> . (Default value: 10) |
| <code>units</code> | the text for defining the units of the height and width parameters. It is only used if <code>export = TRUE</code> . (Default value: "cm") |
| <code>...</code> | a set of daily or monthly precipitation serie. |

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also[read.data](#)**Examples**

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the a set of statistical analysis
pplot.pn(daily)
```

pplot.rai

*Plot Rainfall Anomaly Index***Description**

Plots the Rainfall Anomaly Index of a precipitation serie.

Usage

```
pplot.rai(..., granularity = "m", xlab = "Month", ylab = "RAI",
  ylim = c(-3,3), legend = NULL, fontsize = 10,
  axis.text.color = "black", export = FALSE,
  export.name = "rai_plot.png", width = 8.6,
  height = 7.5, units = "cm")
```

Arguments

| | |
|-----------------|--|
| granularity | the granularity applied for calculating the rainfall anomaly index, which should be either "a" for annual granularity or "m" for monthly granularity ". (Default value: "m") |
| xlab | the text for the x axis. (Default value: "Month") |
| ylab | the text for the y axis. (Default value: "RAI") |
| ylim | the limits of the y axis. (Default value: c(-3, 3)) |
| legend | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| fontsize | the font size value in pt. (Default value: 10) |
| axis.text.color | the legend colors. (Default value: "black") |
| export | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| export.name | the text for defining the exported file name. It is only used if export = TRUE. (Default value: "rai_plot.png") |

| | |
|--------|---|
| width | the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6) |
| height | the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5) |
| units | the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm") |
| ... | a set of daily or monthly precipitation series. |

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[read.data](#)

Examples

```
##
# Loading the daily precipitation serie.
data(daily)

##
# Performing the a set of statistical analysis
pplot.rai(daily, granularity = "m")
```

pplot.spi

Plot Standardized Precipitation Index

Description

Plots the Standardized Precipitation Index of a precipitation serie.

Usage

```
pplot.spi(..., period = 3, distribution = "Gamma", xlab = "Months",
ylab = "SPI", ylim = c(-3,3), legend = NULL, fontsize = 10,
axis.text.color = "black", export = FALSE, export.name = "spi_plot.png",
width = 8.6, height = 7.5, units = "cm")
```

Arguments

| | |
|--------------|--|
| period | the number of months to be aggregated for calculating the standardized precipitation index. (Default value: 3) |
| distribution | it has no effect yet. (Default value: "Gamma") |
| xlab | the text for the x axis. (Default value: "Months") |
| ylab | the text for the y axis. (Default value: "SPI") |

| | |
|-----------------|---|
| ylim | the limits of the y axis. (Default value: c(-3, 3)) |
| legend | the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL) |
| fontsize | the font size value in pt. (Default value: 10) |
| axis.text.color | the legend colors. (Default value: "black") |
| export | the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE) |
| export.name | the text for defining the exported file name. It is only used if export = TRUE. (Default value: "spi_plot.png") |
| width | the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6) |
| height | the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5) |
| units | the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm") |
| ... | a set of daily or monthly precipitation series. |

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the a set of statistical analysis  
pplot.spi(daily)
```

precintcon

Precipitation Intensity, Concentration and Anomaly Analysis

Description

It contains functions to analyze the precipitation intensity, concentration and anomaly.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

References

- Michael J. Hayes (2015). *Comparison of Major Drought Indices*. National Drought Mitigation Center. <http://goo.gl/skHfs9>.
- Gibbs, W. J. (1967). *Rainfall deciles as drought indicators*. Bureau of Meteorology Bulletin, n. 48. Commonwealth of Australia.
- Luis, M. D., Gonzolez-Hidalgo, J. C., Brunetti, M., Longares, L. A. (2011). *Precipitation concentration changes in Spain 1946-2005*. Natural Hazards and Earth System Science, v. 11, n. 5, p. 1259–1265.
- Martin-Vide, J. (2004). *Spatial distribution of a daily precipitation concentration index in peninsular Spain*. International Journal of Climatology, v. 24, n. 8, p. 959–971.
- Guttman, N. B. (1999). *Accepting the standardized precipitation index: a calculation algorithm*. Journal of the American Water Resources Association, v. 35, n. 2, p. 311–322. Blackwell Publishing Ltd.
- Barring, L., Hulme, M. (1991). *Filters and approximate confidence intervals for interpreting rainfall anomaly indices*. Journal of climate, v. 4, n. 8, p. 837–847.

 rai

Rainfall Anomaly Index

Description

Calculates the Rainfall Anomaly Index (RAI) on a daily or monthly precipitation serie.

Usage

```
rai(object, granularity = "m")
```

Arguments

| | |
|-------------|--|
| object | a daily or monthly precipitation serie. |
| granularity | the granularity applied for calculating the rainfall anomaly index, which should be either "m" for monthly granularity or "a" for annual granularity. (Default value: "m") |

Value

A data.frame (precintcon.ra) containing the following variables:

- year is the year.
- month is the month. This attribute exists only when granularity = "m".
- rai is the rainfall anomaly index.

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[pplot.ra](#) [read.data](#)

Examples

```
##
# Loading the monthly precipitation serie.
data(monthly)

##
# Performing the Rainfall Anomaly Index analysis
rai(monthly, granularity = "m")
```

| | |
|-----------|------------------------------------|
| read.data | <i>Load a precipitation series</i> |
|-----------|------------------------------------|

Description

Load a file with a daily or monthly precipitation series.

Usage

```
read.data(file, sep = ",", dec = ".", header = TRUE, na.value = NA)
```

Arguments

| | |
|----------|---|
| file | a string containing the file path. |
| sep | the character applied for delimited columns. (Default value: ",") |
| dec | the character applied for defined decimal point. (Default value: ".") |
| header | a logical value defining whether the first line of the file refers to column names. (Default value: TRUE) |
| na.value | the value used for representing missing values. (Default value: NA) |

Value

A data frame containing a representation of the data in the file. The file is addressed as `precintcon.daily` or `precintcon.monthly` depending of its structure.

The file should contains three columns when loading monthly series and thirty three columns when loading daily series.

The first columns refers to years and the second one refers to months. When dealing with daily datasets, the thirty one remaining columns refers to the amount of precipitation in the days of the months. Otherwise, the remaining column refers to the amount of precipitation in each month.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

See Also

[daily](#) [monthly](#) [read.table](#) [read.csv](#) [read.csv2](#)

Examples

```
##
# Loading a serie on a Windows operating system
## Not run: d1 <- read.data("C:\PRECINTCON\203040.csv", sep = ";", dec = ".", header = TRUE)

##
# Loading a serie on an Unix-like operating system
## Not run: d1 <- read.data("/home/precintcon/203040.csv", sep = ";", dec = ".", header = TRUE)
```

spi

Standardized Precipitation Index

Description

Calculates the Standardized Precipitation Index (SPI) on a daily or monthly precipitation serie.

Usage

```
spi(object, period = 3, distribution = "Gamma")
```

Arguments

| | |
|--------------|--|
| object | a daily or monthly precipitation serie. |
| period | the number of months to be aggregated in the calculation of the standardized precipitation index. (Default value: 3) |
| distribution | it has no effect yet. (Default value: "Gamma") |

Value

A data.frame (precintcon.spi) containing the following variables:

- year is the year.
- month is the month.
- spi is the standardized precipitation index.

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[precintcon.plot.spi](#) [read.data](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Standardized Precipitation Index  
spi(monthly, period = 3)
```

| | |
|--------------|---|
| spi.per.year | <i>Standardized Precipitation Index</i> |
|--------------|---|

Description

Calculates the Standardized Precipitation Index (SPI) per year on a daily or monthly precipitation serie.

Usage

```
spi.per.year(object, period = 3, distribution = "Gamma", FUN = mean)
```

Arguments

| | |
|--------------|---|
| object | a daily or monthly precipitation serie. |
| period | the number of months to be aggregate in the calculation of the standardized precipitation index. (Default value: 3) |
| distribution | (it has no effect yet). |
| FUN | the function used to summarize the standardized precipitation index per year. (Default function: mean). |

Value

A data.frame (precintcon.spi.per.year) containing the following variables:

- year is the year.
- spi is the standardized precipitation index.

Author(s)

Lucas Venezian Povoia <lucasvenez@gmail.com>

See Also

[spi read.data](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Standardized Precipitation Index  
spi.per.year(monthly, period = 3)
```

| | |
|------|---|
| stat | <i>Basic statistics for precipitation datasets.</i> |
|------|---|

Description

Perform the calculation of basic statistics of precipitation datasets.

Usage

```
stat(...)
```

Arguments

... a set of daily or monthly precipitation serie.

Value

A data.frame (precintcon.stat) containing the following variables:

- `dataset` is the precipitation serie name.
- `mean.daily` is the daily average precipitation. It exists only for daily datasets.
- `sd.daily` is the standard deviation of a daily precipitation serie. It exists only for daily datasets.
- `var.daily` is the variance of a daily precipitation serie. It exists only for daily datasets.
- `mean.monthly` is the monthly average precipitation.
- `sd.monthly` is the standard deviation of a monthly precipitation serie.
- `var.monthly` is the variance of a monthly precipitation serie.
- `total` is the total precipitation.

Author(s)

Lucas Venezian Povoá <lucasvenez@gmail.com>

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Plotting the deciles.  
stat(monthly)
```

Index

- *Topic **annual**
 - as.annual, 3
- *Topic **anomaly**
 - pplot.rai, 23
 - precintcon, 25
 - rai, 26
 - spi, 28
 - spi.per.year, 29
- *Topic **concentration**
 - ci, 10
 - ci.per.year, 11
 - pai, 15
 - pplot.pai, 20
 - precintcon, 25
- *Topic **curve**
 - pplot.lorenz, 19
- *Topic **daily**
 - as.daily, 4
- *Topic **datasets**
 - daily, 12
 - monthly, 14
- *Topic **data**
 - read.data, 27
- *Topic **decade**
 - as.decade, 5
- *Topic **deciles**
 - as.deciles, 6
 - pplot.deciles, 17
- *Topic **distribution**
 - as.fd, 7
- *Topic **file**
 - read.data, 27
- *Topic **frequency**
 - as.fd, 7
- *Topic **histogram**
 - pplot.histogram, 18
- *Topic **import**
 - read.data, 27
- *Topic **index**
 - ci, 10
 - ci.per.year, 11
 - pai, 15
 - pplot.pai, 20
 - pplot.spi, 24
 - rai, 26
 - spi, 28
 - spi.per.year, 29
- *Topic **intensity**
 - precintcon, 25
- *Topic **limits**
 - limits, 13
- *Topic **lorenz's**
 - pplot.lorenz, 19
- *Topic **monthly**
 - as.monthly, 8
- *Topic **normal**
 - pn, 16
 - pplot.pn, 22
- *Topic **of**
 - pn, 16
 - pplot.pn, 22
- *Topic **package**
 - precintcon, 25
- *Topic **percent**
 - pn, 16
 - pplot.pn, 22
- *Topic **precintcon**
 - as.deciles, 6
- *Topic **precipitation**
 - as.annual, 3
 - as.daily, 4
 - as.decade, 5
 - as.fd, 7
 - as.monthly, 8
 - as.seasonal, 9
 - ci, 10
 - ci.per.year, 11
 - limits, 13

- pci, 15
- pn, 16
- pplot.deciles, 17
- pplot.histogram, 18
- pplot.lorenz, 19
- pplot.pci, 20
- pplot.pn, 22
- pplot.rai, 23
- pplot.spi, 24
- precintcon, 25
- rai, 26
- read.data, 27
- spi, 28
- spi.per.year, 29
- stat, 30
- *Topic **rainfall**
 - pplot.rai, 23
 - precintcon, 25
 - rai, 26
 - spi, 28
 - spi.per.year, 29
- *Topic **read**
 - read.data, 27
- *Topic **seasonal**
 - as.seasonal, 9
- *Topic **standardized**
 - pplot.spi, 24
- *Topic **summary**
 - stat, 30
- *Topic **table**
 - read.data, 27
- as.annual, 3, 5
- as.daily, 3, 4, 8, 10, 11, 14–16, 20
- as.decade, 5, 5
- as.deciles, 6
- as.fd, 7
- as.monthly, 3, 5, 8, 15, 16
- as.precintcon.annual, 6
- as.precintcon.annual (as.annual), 3
- as.precintcon.daily, 6
- as.precintcon.daily (as.daily), 4
- as.precintcon.decade (as.decade), 5
- as.precintcon.deciles (as.deciles), 6
- as.precintcon.fd (as.fd), 7
- as.precintcon.monthly, 6
- as.precintcon.monthly (as.monthly), 8
- as.precintcon.seasonal, 6
- as.precintcon.seasonal (as.seasonal), 9
- as.seasonal, 3, 5, 9
- ci, 8, 10, 20
- ci.per.year, 11
- daily, 12, 28
- deciles, 17
- deciles (as.deciles), 6
- limits, 13
- monthly, 14, 28
- pci, 15
- pn, 16
- pplot.deciles, 17
- pplot.histogram, 18
- pplot.lorenz, 3, 8–11, 19
- pplot.pci, 15, 20
- pplot.pn, 16, 22
- pplot.rai, 23, 27
- pplot.spi, 24
- precintcon, 25
- precintcon-package (precintcon), 25
- precintcon.ci.analysis (ci), 10
- precintcon.ci.per.year.analysis (ci.per.year), 11
- precintcon.deciles.analysis (as.deciles), 6
- precintcon.fd (as.fd), 7
- precintcon.limits.analysis (limits), 13
- precintcon.pci.analysis (pci), 15
- precintcon.plot.deciles (pplot.deciles), 17
- precintcon.plot.histogram (pplot.histogram), 18
- precintcon.plot.lorenz (pplot.lorenz), 19
- precintcon.plot.pci (pplot.pci), 20
- precintcon.plot.pn (pplot.pn), 22
- precintcon.plot.rai (pplot.rai), 23
- precintcon.plot.spi, 28
- precintcon.plot.spi (pplot.spi), 24
- precintcon.pn.analysis (pn), 16
- precintcon.rai.analysis (rai), 26
- precintcon.read.data (read.data), 27
- precintcon.spi.analysis (spi), 28
- precintcon.spi.per.year.analysis (spi.per.year), 29

`precintcon.stat.analysis (stat)`, 30

`rai`, 26

`read.csv`, 28

`read.csv2`, 28

`read.data`, 3, 7–11, 14–17, 19–21, 23–25, 27,
27, 28, 29

`read.table`, 28

`spi`, 28, 29

`spi.per.year`, 29

`stat`, 30