

Package ‘secrlinear’

February 20, 2015

Type Package

Title Spatially Explicit Capture-Recapture for Linear Habitats

Version 1.0.5

Depends R (>= 3.0.0), secr(>= 2.9.1), sp, igraph

Imports parallel, maptools, MASS

Suggests knitr, rgeos, secrdesign

VignetteBuilder knitr

Date 2015-01-11

Author Murray Efford

Maintainer Murray Efford <murray.efford@otago.ac.nz>

Description Tools for spatially explicit capture-recapture analysis of animal populations in linear habitats, extending package ‘secr’

License GPL (>= 2)

LazyData yes

URL <http://www.otago.ac.nz/density>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-01-12 01:09:54

R topics documented:

| | |
|------------------------------|----|
| secrlinear-package | 2 |
| Arvicola | 4 |
| checkmoves | 6 |
| clipmask | 7 |
| edges | 8 |
| glymemask | 10 |
| linearmask.object | 11 |
| linearpopn.object | 13 |
| make.line | 13 |

| | |
|-----------------------------|----|
| networkdistance | 15 |
| plotmethods | 16 |
| rbind.linearMask | 17 |
| read.linearMask | 18 |
| showpath | 20 |
| Silverstream | 21 |
| sim.linearpopn | 22 |
| subset.linearMask | 23 |
| utility | 25 |

| | |
|--------------|-----------|
| Index | 28 |
|--------------|-----------|

| | |
|-------------------|---|
| seclinear-package | <i>Spatially Explicit Capture-Recapture for Linear Habitats</i> |
|-------------------|---|

Description

An **secl** add-on package for linear habitat models.

Details

Package: secl
 Type: Package
 Version: 1.0.5
 Date: 2015-01-11
 License: GNU General Public License Version 2 or later

The important functions in **seclinear** are:

| | |
|---------------------------------|--|
| read.linearMask | import and discretize a linear habitat map (route) |
| networkdistance | compute network distances between detectors and points using a linear habitat mask |
| sim.linearpopn | simulate population along linear mask |
| make.line | place detectors along (part of) a linear route |

Other useful functions are:

| | |
|--|--|
| checkmoves | check capthist object for extreme movements |
| showpath | interactive examination of network distances |
| clipmask | drop mask points outside buffer distance |
| rbind.linearMask | combine two linear masks |
| subset.linearMask | select part of a linear mask |
| asgraph | convert linear mask to igraph |
| snapPointsToLinearMask | closest point on graph |
| make.sldf | convert coordinates to SpatialLinesDataFrame |

Documentation is provided in a vignette [../doc/seclinear-vignette.pdf](#) and in the pdf version of the help pages [../doc/seclinear-manual.pdf](#)

The package draws on the packages **sp** (Pebesma and Bivand 2005) and **igraph** (Csardi and Nepusz 2006).

In order to fit a linear-habitat model with the **secl** function `secl.fit`:

1. specify a linear mask for the ‘mask’ argument
2. specify `details = list(userdist = networkdistance)` so that `secl.fit` uses network distances rather than Euclidean distances.

An example dataset [arvicola](#) is drawn from trapping of water voles *Arvicola amphibius* in June 1984 along the River Glyme in the U.K. – the relevant linear mask is [glymemask](#).

A more complex linear network ([Silverstream](#)) is provided as an ESRI shapefile.

Author(s)

Murray Efford <murray.efford@otago.ac.nz>

References

Csardi, G. and Nepusz, T. (2006) The igraph software package for complex network research. *InterJournal, Complex Systems* **1695**. <http://igraph.org>.

Pebesma, E.J. and Bivand, R. S. (2005) Classes and methods for spatial data in R. *R News* **5(2)**, <http://cran.r-project.org/doc/Rnews/>.

See Also

[addedges](#), [asgraph](#), [checkmoves](#), [clipmask](#), [deleteedges](#), [linearmask](#), [linearpopn](#), [make.line](#), [make.sldf](#), [networkdistance](#), [plot.linearmask](#), [rbind.linearmask](#), [read.linearmask](#), [showpath](#), [showedges](#), [sim.linearpopn](#), [snapPointsToLinearMask](#), [subset.linearmask](#)

Examples

```
## Water voles in June 1984 on the R. Glyme in Oxfordshire, UK
## capture and trap location files are exactly as for a 2-D analysis

olddir <- setwd(system.file("extdata", package = "seclinear"))
on.exit(setwd(olddir))
arvicola <- read.caphist("Jun84capt.txt", "glymetrap.txt",
  detector = "multi", covname = "sex")

## Import map of linear habitat
## -- from text file of x-y coordinates
glymemask <- read.linearmask(file = "glymemap.txt", spacing = 4)
## -- from a previously constructed SpatialLinesDataFrame
library(maptools)
SLDF <- readShapeSpatial("glymemap")
glymemask <- read.linearmask(data = SLDF, spacing = 4)
```

```

## display the mask and capture data
plot (glymemask)
plot(arvicola, add = TRUE, tracks = TRUE)
plot(traps(arvicola), add = TRUE)

## fit model, estimate density
linearfit <- secr.fit(arvicola, mask = glymemask, trace = FALSE,
  details = list(userdist = networkdistance))
predict(linearfit)

## NOTE : the unit of density (D) is animals / km

```

Arvicola

Water Vole Capture Dataset

Description

Data from a trapping study of water voles (*Arvicola amphibius*) along a river in Oxfordshire, U.K.

Usage

arvicola

Format

`secr` `capthist` object

Details

Water voles were trapped monthly from May 1984 to May 1985 along 0.9 km of the River Glyme near Woodstock in Oxfordshire, U.K. (Efford 1985). Two sheet-aluminium traps were set at stations 20 m apart along one bank and checked morning and evening for 3 days. Traps were baited with slices of carrot and provisioned with bedding and additional carrot. Voles were marked with individual colour-coded ear tags. The dataset provided is from June 1984. This was early in the breeding season and most voles were overwintered adults; only 3 were young-of-the-year, and these were omitted.

Raw data files “Jun84capt.txt” and “glymetrap.txt” are provided in the ‘extdata’ folder of the **secrlinear** installation. The vignette [../doc/secrlinear-vignette.pdf](#) shows how to import the raw data.

The data comprise detections of 26 voles at 44 stations on 6 occasions. The two traps at each station were notionally labelled ‘A’ and ‘B’, but captures were recorded only by the station at which they occurred: captures were assigned label ‘A’ or ‘B’ effectively at random. Each trap could catch a single adult vole, but trap saturation was low (maximum 20.5% of traps caught a vole). No voles died in traps in June 1984.

Water voles in the U.K. restrict their activity to waterways and their immediate banks, except for some populations in more extensive (2-dimensional) wetlands. It is therefore natural to treat their

habitat as linear in a spatially explicit capture–recapture model of these data. A suitable linear habitat mask is provided in the accompanying dataset [glymemask](#).

See [../doc/secrlinear-vignette.pdf](#) for more analysis of this dataset.

Source

M. G. Efford unpublished data.

References

Efford, M. G. (1985) *The structure and dynamics of water vole populations*. D.Phil thesis, University of Oxford.

See Also

[glymemask](#)

Examples

```
summary(arvicola)
head(traps(arvicola))

## for speed, pre-compute distance matrix
userd <- networkdistance (traps(arvicola), glymemask, glymemask)
## fit model
glymefit <- secr.fit(arvicola, mask = glymemask, trace = FALSE,
                    details = list(userdist = userd))
## estimates of 'real' parameters
predict(glymefit)

## Not run:
tmp <- secr.test(glymefit, nsim = 1000)
tmp
plot(tmp)

## More voles were caught only once than is predicted by the model.
## This is probably due to within-population variation in movement or
## capture probability.

## End(Not run)
```

checkmoves

*Check Movements***Description**

This function reports problems indicated by extreme movements in a capthist object. At present it is configured for distances measured along a linearmask only.

Usage

```
checkmoves (CH, accept = c(0, 1000), userdist, mask, showall = TRUE, silent = FALSE)
```

Arguments

| | |
|----------|---|
| CH | single-session secr capthist object |
| accept | range of accepted movements in metres; may include Inf |
| userdist | matrix of distances between all traps(CH) (optional) |
| mask | linearmask object (optional) |
| showall | logical; if TRUE the output dataframe includes all detections of each individual with at least one extreme movement |
| silent | logical; if TRUE then console output is suppressed |

Details

This function works with Euclidean distances (the default if neither mask nor userdist is specified), non-Euclidean network distances implied by a linear habitat mask, or any distances presented in userdist.

Linear habitat masks are prone to breaks (missing edges in the graph representation). If an animal is ‘recaptured’ on both sides of a break then the network distance for that ‘movement’ will be infinite.

checkmoves displays the message ‘All OK’ if there are no out-of-range movements, and otherwise displays the number of individuals with out-of-range movements.

Value

Invisibly returns a list with components

| | |
|----------|---|
| badmoves | logical vector with one element for each animal (i.e. each row in CH) |
| CH | subset of the input CH containing the faulty detection histories |
| df | dataframe detailing the faulty detections |

See Also

[linearmask](#)

Examples

```
out <- checkmoves(captdata, accept = c(0,100))
out
```

clipmask

Drop Points Distant From Detectors

Description

clipmask may be used to drop superfluous points from a mask (those further than buffer from any detector).

Usage

```
clipmask(mask, traps, buffer = 100, clipvert = FALSE)
```

Arguments

| | |
|----------|--|
| traps | ‘traps’ object from secr |
| mask | ‘linearmask’ object |
| buffer | network distance for retaining mask points (m) |
| clipvert | logical; if TRUE the underlying lines are also clipped |

Details

None yet.

Value

‘linearmask’ object retaining only points within buffer m of any trap. By default, the ‘SLDF’ attribute is unchanged.

clipvert = TRUE causes the attribute “SLDF” (a SpatialLinesDataFrame) to be clipped to within spacing/2 of detectors, using functions from **rgeos** (Bivand and Rundel 2014).

References

Bivand, R. and Rundel, C. (2014) rgeos: Interface to Geometry Engine - Open Source (GEOS). R package version 0.3-4. <http://CRAN.R-project.org/package=rgeos>

See Also

[make.line](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 20)

## clipmask
trps <- make.line(mask, n = 15, startbuffer = 1000, by = 30)
newmask <- clipmask(mask, trps, buffer = 200)
plot(newmask)
plot(trps, add = TRUE)

if (require('rgeos')) {
  newmask <- clipmask(mask, trps, buffer = 200, clipvert = TRUE)
  plot(newmask)
  plot(trps, add = TRUE)
}
```

edges

Interactive Edge Edit

Description

A ‘skip’ is defined here as a graph edge between two input lines. Many skips are legitimate, but some ‘shortcut’ skips are artefacts of the simple algorithm used by [asgraph](#) to construct the graph topology. These are better removed. These functions allow skips in a [linearmask](#) to be visualised and edited.

addedges may be used to bridge artefactual gaps in a network, or to correct editing mistakes. The edge weight of a new edge is its Euclidean length.

Usage

```
showedges(mask, plt = TRUE, add = FALSE, type = c('all', 'noskips', 'skips'),
          lengths = c(0,Inf), ...)
```

```
replot(mask, xlim = NULL, ylim = NULL, ...)
```

```
addedges(mask, replot = TRUE, ...)
```

```
deleteedges(mask, replot = TRUE, ...)
```

```
cleanskips(mask)
```


Arguments

| | |
|---------|--|
| mask | linearmask object with 'graph' attribute |
| lengths | numeric vector of minimum and maximum edge length (weight) |
| plt | logical; if TRUE the edges are plotted |
| add | logical; if TRUE the edges will be added to an existing plot |
| type | character value for subset of edges to show |
| xlim | vector of min and max x-values for new plot |
| ylim | vector of min and max y-values for new plot |
| replot | logical; if TRUE the plot will be re-done using replot |
| ... | other arguments (see details) |

Details

showedges is a general-purpose function for displaying or extracting edge information from the graph attribute of a linear mask.

cleanskips removes any between-line 'skips' that are longer than the shortest 'skip'.

Other functions here are used to manually edit a mask graph.

replot is used to zoom in on part of a linear mask (often to inspect 'skips').

The dots argument ... is passed by replot to plot.linearmask and by addededges and deleteedges to showedges (if replot = TRUE).

Value

showedges returns a dataframe with one row for each edge, and columns –

| | |
|--------|---|
| start | index of start vertex |
| finish | index of finish vertex |
| line1 | line number of start |
| line2 | line number of finish |
| x1 | geographic coordinates of start |
| y1 | geographic coordinates of start |
| x2 | geographic coordinates of finish |
| y2 | geographic coordinates of finish |
| weight | "weight" attribute of edge (its length in metres) |

The dataframe is returned invisibly if plt = TRUE.

cleanskips returns a linearmask object.

replot returns NULL.

addededges and deleteedges invisibly returns a linear mask object with updated graph attribute.

See Also

[linearmask](#), [getLineID](#)

Examples

```
## Not run:

setwd(system.file("extdata", package = "secrlinear"))
tempmask <- read.linearmask(file = "silverstream.shp", spacing = 50)

## show all edges
plot(tempmask, linecol = 'white')
tmp <- showedges(tempmask, add = TRUE)

## select a rectangular area to zoom in
replot(tempmask)

## click on the vertices of one or more edges to delete or add
tempmask <- deleteedges(tempmask)
tempmask <- addedges(tempmask)

## End(Not run)
```

glymemask

Linear Mask for Water Vole Dataset

Description

Habitat geometry for a trapping study of water voles (*Arvicola amphibius*) along a river in Oxfordshire, U.K., used in conjunction with the capture dataset [arvicola](#).

Usage

```
glymemask
```

Format

A linearmask object (see [read.linearmask](#))

Details

Water voles were trapped monthly from May 1984 to May 1985 along 0.9 km of the River Glyme in Oxfordshire, U.K. (Efford 1985).

The raw data are provided both as a text file and as a shapefile in the 'extdata' folder of the **secrlinear** installation. The vignette [../doc/secrlinear-vignette.pdf](#) shows how to import the data, which are also provided here as an **secr** object.

Source

M. G. Efford unpublished data.

References

Efford, M. G. (1985) *The structure and dynamics of water vole populations*. D.Phil thesis, University of Oxford.

See Also

[arvicola](#)

Examples

```
plot(glymemask)
summary(glymemask)

## add a covariate, the distance downstream from the first mask point
downstrm <- networkdistance(glymemask, glymemask[1,], glymemask)[,1]
covariates(glymemask)<- data.frame(downstream = downstrm)
```

linearmask.object

Description of Linear Mask Objects

Description

An object of class `linearmask` maps linear habitat, such as a river, in a way that is useful for spatially explicit capture–recapture analysis. The object contains two representations of the linear habitat: as features in a `SpatialLinesDataFrame`, and discretized as a set of equally spaced points, as in a mask object from `secr`.

Usually the object was created in a call to `read.linearmask`, which performs the discretization given linear input data and a chosen spacing.

A `linearmask` object does not explicitly include topological information i.e. the branching pattern of river networks. Instead, a network is constructed on-the-fly in `asgraph` by joining adjacent mask points (those within a certain small Euclidean distance). This results in 'shortcut' edges where lines approach at an acute angle (see the Examples for a demonstration).

A more complete, but also more cumbersome, solution for river networks might be to adapt the `SpatialStreamNetwork` object class of the `SSN` package (ver Hoef et al. 2014). Data input for `SSN` requires pre-processing in the proprietary software ArcGIS.

Value

The object itself is a dataframe of coordinates for the points comprising the mask, as for a 2-dimensional habitat mask (`mask`).

Additional information is stored as attributes (these usually remain hidden, but are essential except for 'graph'):

spacingfactor The spacing factor determines which points in a linear mask are joined to form a linear network, as happens automatically when computing distances with [networkdistance](#). Points are joined when their Euclidean separation is less than spacingfactor x spacing. The default value is 1.1.

SLDF The SLDF attribute is a SpatialLinesDataFrame (defined in [sp](#)) that provides the underlying description of the linear habitat.

graph **igraph** network. Optionally computed by [read.linearmask](#) and saved as attribute, or computed on the fly by [networkdistance](#)

.

covariates A required dataframe of covariate values, including at least the column 'LineID'

Other attributes are common to masks and linearmasks:

spacing In this context, the length of habitat in metres that is associated with each mask point (segment length).

meanSD A matrix with mean and standard deviation of coordinates.

boundingbox In this context, a dataframe giving the coordinate ranges spanned by the SLDF. Differs from 2-D mask in not being 'buffered' by spacing/2.

Further attributes of 2-dimensional masks (area, polygon etc.) are not relevant but may be present. The object has class `c("linearmask", "mask", "data.frame")` or `c("list", "linearmask", "mask", "data.frame")` for a multi-session linear mask.

References

Ver Hoef, J. M., Peterson, E. E., Clifford, D. and Shah, R. (2014) **SSN** : an R package for spatial statistical modeling on stream networks. *Journal of Statistical Software* **56(3)**, 1–45.

See Also

[read.linearmask](#), [mask](#), [showpath](#), [networkdistance](#)

Examples

```
## make a complex linear mask
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
xy2 <- data.frame(x = x*100, y = cos(x)*300)
test <- read.linearmask(data = xy, spacing = 10)
test2 <- read.linearmask(data = xy2, spacing = 10)
test3 <- rbind(test, test2)

## visualize the igraph network used by networkdistance()
tmp <- asgraph(test3)
if(require('igraph')) {
  i2 <- get.edges(tmp, 1:ecount(tmp))
  plot(test3, linecol = 'white', col = 'grey')
```

```

segments(test3[i2[,1],1], test3[i2[,1],2], test3[i2[,2],1],
         test3[i2[,2],2], lwd=2, col='blue')
}

```

linearpopn.object *Description of Linear Population Objects*

Description

An object of class `linearpopn`, usually created in a call to `sim.linearpopn` and used as input to `sim.caphist`.

Value

The object itself is a dataframe of coordinates for points along the mask, as for a 2-dimensional population (`popn`).

The attribute `model2D` is always “linear”.

The object has class `c("linearpopn", "popn", "data.frame")`.

See Also

`plot.linearpopn`, `popn`.

Examples

```

glymepop <- sim.linearpopn(glymemask, 30)
plot(glymepop, jitter=1)

CH <- sim.caphist(traps(arvicola), glymepop, detectpar = list(g0 = 0.4,
  sigma = 40), noccasions = 6, userdist = networkdistance)

plot(glymemask)
plot(CH, add = TRUE, tracks = TRUE)

```

make.line *Linear Detector Array*

Description

Build `secr` ‘traps’ object, positioning detectors along a predefined set of lines. `make.line` is in the same family as `secr` functions `make.grid` etc.

Usage

```
make.line(SLDF, n = 10, startbuffer = 0, by = 20, endbuffer = 0, cluster
= NULL,
type = c("fixedstart", "randomstart", "centred"), detector = "multi")
```

Arguments

| | |
|-------------|---|
| SLDF | linearmask object or SpatialLinesDataFrame from sp |
| n | maximum number of detectors (or clusters of detectors) per line |
| startbuffer | distance of first detector from start of line(s) |
| endbuffer | minimum distance of last detector from end of line(s) |
| by | spacing between detectors (or clusters of detectors) (m) |
| cluster | numeric vector of within-cluster positions (m from start) |
| type | character |
| detector | character value for detector type - "single", "multi" etc. |

Details

Detectors are placed independently on each line.

Value

An object of class `traps` comprising a data frame of x- and y-coordinates, the detector type ("single", "multi", or "proximity" etc.), and possibly other attributes. The `SpatialLinesDataFrame` is retained as attribute 'SLDF'.

See Also

[make.traps](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 20)

trps <- make.line(mask, n = 15, startbuffer = 1000, by = 50)
plot(mask)
plot(trps, add = TRUE)
```

| | |
|-----------------|--------------------------|
| networkdistance | <i>Network Distances</i> |
|-----------------|--------------------------|

Description

Simple network computation of distance between points along linear landscape features (e.g. rivers).

Usage

```
networkdistance(xy1, xy2, geometry)
```

Arguments

| | |
|----------|------------------------------|
| xy1 | 2-column matrix or dataframe |
| xy2 | 2-column matrix or dataframe |
| geometry | 'linearmask' object |

Details

networkdistance computes the distance in metres between the points in xy1 and the points in xy2. The geometry is a linearmask; if it is missing then it takes the value of xy2, which then of course must be a full linearmask. A network is taken from the 'graph' attribute of geometry or (if necessary) constructed from the linearmask 'on the fly', joining any points closer than (spacingfactor x spacing(geometry)). Points in xy1 and xy2 are first snapped to the nearest point in geometry. The computed distance is the sum of the graph's edge weights along the shortest path joining two points.

The commonest use of networkdistance is to calculate distances between detectors (traps) and points on a linear mask. In this case it is sufficient to provide two arguments only, as xy2 serves as both destination and geometry.

networkdistance meets the requirements for a user-defined distance function (userdist) in **secr**. No parameter is estimated.

Use [showpath](#) to check network distances interactively.

Value

networkdistance –

given k detectors and m mask points, a $k \times m$ matrix of distances.

If called with no arguments networkdistance returns a zero-length character vector.

See Also

[read.linearmask](#), [showpath](#), [asgraph](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 20)
trps <- make.line(mask, n = 15, startbuffer = 1000, by = 30)

## networkdistance; geometry in 'mask'
d <- networkdistance (trps, mask, mask)
dim(d)
head(d)
```

plotmethods

Plot Methods for linearmask and linearpopn objects

Description

Custom plotting.

Usage

```
## S3 method for class 'linearpopn'
plot(x, ..., jitter = 0, plotline = TRUE)

## S3 method for class 'linearmask'
plot(x, ..., linecol = 'black', label = FALSE,
      laboffset = c(spacing(x), 0))
```

Arguments

| | |
|-----------|--|
| x | linearpopn object from sim.linearpopn , or a linearmask object from read.linearmask |
| ... | For <code>plot.linearpopn</code> : other arguments passed to <code>plot.popn</code> (may include <code>add = TRUE</code>). For <code>plot.linearmask</code> : other arguments passed to <code>plot.mask</code> (e.g., <code>col</code> , <code>cex</code> , <code>add</code>), to <code>legend</code> (<code>pt.cex</code>) or to the plot method for <code>SpatialLines</code> (<code>lwd</code> , <code>lty</code>) |
| jitter | numeric value for jittering |
| plotline | logical; if TRUE the mask line is overplotted in grey |
| linecol | line colour for linear habitat (see Color Specification in par) |
| label | logical; if TRUE each vertex is numbered |
| laboffset | offset of label from point (metres) |

Details

The linear mask used for plotting a ‘linearpopn’ is the one saved as an attribute of the object.

The main plotting in `plot.linearmask` is done by `plot.mask` with `dots = TRUE`. See the help for [plot.mask](#) for details of options such as `add`. The lines of the `SpatialLinesdataFrame` are overplotted unless `linecol = NA`.

Jittering shifts points by a random uniform distance – $(\pm 0.5 \times \text{jitter}) \times \text{mask spacing}$ – on both axes. This can give a better impression of density when points coincide.

The option `inplot.popn` for plotting rectangular ‘frame’ is suppressed: do not attempt to pass this argument in

Value

`plot.linearpopn` does not return a value.

`plot.linearmask` invisibly returns legend details as for [plot.mask](#).

See Also

[sim.linearpopn](#), [plot.mask](#), [plot.popn](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 10)
linpop <- sim.linearpopn(mask, 100)
plot(linpop, jitter = 2)

plot(mask)

## thicker band of grey points, dashed line
plot(mask, cex = 2, lty = 2)

## point colour determined by a covariate
plot(glymemask, cex = 2, covariate = 'x', pt.cex = 2)

## point size determined by a covariate
plot(glymemask, cex = covariates(glymemask)$x/50, pch = 21)
```

rbind.linearmask

Combine linearmask Objects

Description

Form a new `linearmask` object by combining the underlying vertices and drawing a new systematic sample.

Usage

```
## S3 method for class 'linear_mask'
rbind(..., cleanskips = TRUE)
```

Arguments

```
...           one or more linear_mask objects with the same spacing
cleanskips    logical; passed to internal function make.linear_mask
```

Details

The **maptools** function `spRbind` is used to combine the ‘SLDF’ attributes of the inputs. If the input objects have a ‘graph’ attribute then a new graph will be included in the output.

Value

A linear_mask object

See Also

[spRbind](#), [read.linear_mask](#), [linear_mask](#), [subset.linear_mask](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
xy2 <- data.frame(x = x*100, y = cos(x)*300)
test <- read.linear_mask(data = xy, spacing = 20)
test2 <- read.linear_mask(data = xy2, spacing = 20)

plot(rbind(test, test2))
```

read.linear_mask

Import Linear Habitat Mask

Description

Construct a linear_mask from line data in a text file, a polyline shapefile, a dataframe or a SpatialLinesDataFrame object.

Usage

```
read.linear_mask(file = NULL, data = NULL, spacing = 10, spacingfactor =
1.5, graph = TRUE, cleanskips = TRUE, ...)
```

Arguments

| | |
|---------------|--|
| file | file name |
| data | data frame or SpatialLinesDataFrame |
| spacing | length of each discretized segment |
| spacingfactor | numeric criterion for joining mask points |
| graph | logical; if TRUE the igraph representation of the mask is saved as an attribute |
| cleanskips | logical; if TRUE then cleanskips is applied to the graph |
| ... | other arguments passed to read.table for file input |

Details

Only one of ‘file’ or ‘data’ should be specified. The file name should include the extension (e.g., "silverstream.shp").

Input from a text file, polyline shapefile or dataframe is first converted to a SpatialLinesDataFrame object. Points are spaced equally along each SpatialLine, starting at $\text{spacing} / 2$.

For dataframe input via data the coordinates are expected to be in columns ‘x’ and ‘y’; if these names are missing, or input is from a file, the first two columns are used.

spacingfactor is used by [asgraph](#) to determine which points are joined when computing distances. It should be between 1 and 2.

Value

A ‘linearmask’ object, i.e. a ‘mask’ object in which each point represents a line segment of length spacing, and with additional attributes ‘SLDF’, ‘spacingfactor’ and possibly ‘graph’ (see [linear-mask](#)).

Note

A valid shapefile includes at least three files with extensions ‘.shp’, ‘.dbf’ and ‘.shx’. The full name of the .shp file is provided as the ‘file’ argument of read.linearmask. The shapefile name without any extension is used as the first argument to the **maptools** function readShapeSpatial.

Line-level covariates are copied from SpatialLinesDataFrame input. Point-specific covariates may be added later using [covariates](#) or [addCovariates](#).

See Also

[asgraph](#), [linearmask](#), [make.sldf](#), [networkdistance](#), [SpatialLinesDataFrame](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
test <- read.linearmask(data = xy, spacing = 20)
plot(test)
```

```
xy2 <- data.frame(x = x*100, y = cos(x)*300)
test2 <- read.linearmask(data = xy2, spacing = 20)

plot(test2, add = TRUE)
```

showpath *Display Shortest Path*

Description

An interactive function to examine shortest paths and the associated network distances within a linear mask.

Usage

```
showpath(mask, add = FALSE, ...)
```

Arguments

| | |
|------|---|
| mask | linearmask object |
| add | logical; if TRUE the plot is added to an existing plot |
| ... | other arguments passed to <code>lines</code> for drawing network path |

Details

The selected points are snapped to the nearest mask point before any calculations.

The path shown is a shortest path as determined by function `get.shortest.paths` of the **igraph** package. There may be others.

Value

Invisibly returns a list comprising

| | |
|---------|--|
| paths | a list of dataframes, each with the mask coordinates along a selected path |
| results | a dataframe with one row for each path giving the distances for each pair of points (columns 'from', 'to', 'Euclidean.d', 'network.d') |

References

Csardi, G. and Nepusz, T. (2006) The igraph software package for complex network research, InterJournal, Complex Systems 1695. <http://igraph.org>.

See Also

[networkdistance](#)

Examples

```
## Not run:

x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
xy2 <- data.frame(x = x*100, y = cos(x)*300)
test <- read.linearmask(data = xy, spacing = 10)
test2 <- read.linearmask(data = xy2, spacing = 10)
test3 <- rbind(test, test2)
showpath(test3, lwd = 5)

## End(Not run)
```

Silverstream

Silverstream River Centrelines

Description

Silverstream (45°48' S, 170°26' E) is a small river in a forested catchment near Dunedin, New Zealand, about 12 km from top to bottom. There are numerous side streams making this a good example of a dendritic network.

Format

An ESRI polyline shapefile (silverstream.shp, silverstream.shx, silverstream.dbf).

Source

Land Information New Zealand (LINZ) 1:50 000 topographic database <http://data.linz.govt.nz/layer/327-nz-mainland-river-centrelines-topo-150k/> licensed by LINZ for re-use under the Creative Commons Attribution 3.0 New Zealand licence. Downloaded 2014-10-26.

References

ESRI (1998) *ESRI shapefile technical description*. <http://www.esri.com/library/whitepapers/pdfs/shapefile.pdf>.

Examples

```
## Not run:

setwd(system.file("extdata", package = "seclinear"))
silverstreammask <- read.linearmask(file = "silverstream.shp", spacing = 50)
par(mar = c(1,1,1,1))
plot(silverstreammask)

## End(Not run)
```

| | |
|----------------|----------------------------------|
| sim.linearpopn | <i>Simulate Animals on Lines</i> |
|----------------|----------------------------------|

Description

This function is a simple substitute for the **secl** function `sim.popn()` for the case of a linear habitat.

Usage

```
sim.linearpopn(mask, D, N, Ndist = c('poisson', 'fixed'), ...)
```

Arguments

| | |
|-------|--|
| mask | linearmask object |
| D | numeric density animals / km |
| N | number of individuals |
| Ndist | character string for distribution of total number of individuals |
| ... | other arguments passed to sim.popn |

Details

The linearmask input represents a discretized line - essentially a chain of line segments. By default, each segment is populated with a Poisson number of individuals. The user may specify D or N.

D may be a vector with one density per mask pixel, or a single number that will be applied across all pixels.

If Ndist = 'fixed' then a constant number of individuals N are simulated in each trial; otherwise N has a Poisson distribution across trials. $N = \text{sum}(D) \times \text{mask length}$ if D is specified.

This is a simplified wrapper for [sim.popn](#) called with `model2D = "linear"`.

Value

Object of class c('linearpopn', 'popn', 'data.frame').

Note

The population output from `sim.linearpopn` may be used unchanged with **secr** functions such as `sim.caphist`. However, to be faithful to the linear network you should set the 'userdist' argument of `sim.caphist` to `networkdistance`.

See Also

[linearpopn](#), [sim.popn](#)

Examples

```
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 10)
trps <- make.line(mask, n = 15, startbuffer = 1000, by = 30)

newmask <- clipmask(mask, trps, buffer = 200)

linpop <- sim.linearpopn(newmask, 200)
CH <- sim.caphist(trps, linpop, userdist = networkdistance)
plot(newmask)
plot(CH, add = TRUE)

secr.fit(CH, mask = mask, details = list(userdist = networkdistance))
```

subset.linearmask *Select Part of linearmask Object*

Description

Methods to subset linear mask objects.

Usage

```
## S3 method for class 'linearmask'
subset(x, subset, LineID, droplinesbeyond = Inf, ...)
```

Arguments

| | |
|-----------------|--|
| x | linearmask object from read.linearmask |
| subset | numeric or logical vector to select rows of mask |
| LineID | vector of identifiers for lines to retain |
| droplinesbeyond | logical; distance criterion for dropping lines (m) |
| ... | other arguments (not used) |

Details

Specify only one of ‘subset’ and ‘LineID’.

If the input object has a ‘graph’ attribute then a new graph will be included in the output.

subset.linearmask leaves the underlying SpatialLinesDataFrame intact unless either (i) LineID is specified, or (ii) a finite value is provided for droplinesbeyond. droplinesbeyond retains lines that have at least one point within the specified distance of at least one mask point, after subsetting.

Value

A linearmask object.

See Also

[read.linearmask](#), [linearmask](#)

Examples

```
## rbind two linear masks,
x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
xy2 <- data.frame(x = x*100, y = cos(x)*300)
test <- read.linearmask(data = xy, spacing = 10)
test2 <- read.linearmask(data = xy2, spacing = 10)
test3 <- rbind(test, test2)
table(covariates(test3)$LineID)

## then retrieve one...
test4 <- subset(test3, LineID = '1.1')

## ... or the other
test5 <- subset(test3, LineID = '2.1')
```


utility

*Utility Functions***Description**

Utilities for various functions

- conversion of a flat table of coordinates for a line or set of lines to a `SpatialLinesDataFrame` object
- snapping points from objects of various types (traps, popn, matrix etc.) to a `linearmask` object.
- converting distances along a linear mask to x-y coordinates
- build igraph network from `linearmask` object

Usage

```
make.sldf(coord, f)
```

```
snapPointsToLinearMask(xy, mask)
```

```
asgraph(mask)
```

```
getLineID(mask, laboffset = rep(spacing(mask) * 3, 2), ...)
```

Arguments

| | |
|------------------------|---|
| <code>coord</code> | dataframe of coordinates - must include columns 'x','y' |
| <code>f</code> | vector of values by which to split coord rows |
| <code>xy</code> | any object that may be coerced to a 2-column matrix (columns interpreted as x- and y-coordinates) |
| <code>mask</code> | 'linearmask' object |
| <code>laboffset</code> | offset of label from point |
| <code>...</code> | other arguments passed to plot.linearmask |

Details

In `make.sldf`, if `f` is missing and there is a column 'lineID' in 'coord' then this will be used instead.

`snapPointsToLinearMask` shifts each point in the input to the nearest point on the graph stored as the 'graph' attribute of `mask`.

[make.line](#) creates a 'traps' object with equally spaced or clustered detectors.

`asgraph` is a utility function used internally for expressing the points in `mask` as an igraph network (Csardi and Nepusz 2006).

`getLineID` plots the mask and for each mouse click displays the corresponding point and LineID.

Other utilities specific to editing graphs are documented in [edges](#).

Value

For `make.sldf`, a `SpatialLinesDataFrame`.

For `snapPointsToLinearMask`, the output has the same attributes (including class) as the `xy` input: only the coordinates themselves may change.

For `alongmask`, a 2-column dataframe with the `x` and `y` coordinates of the points.

For `asgraph`, an object of class `'igraph'`

`getLineID` invisibly returns a dataframe with columns `'Point'` and `'LineID'`.

References

Csardi, G. and Nepusz, T. (2006) The `igraph` software package for complex network research, *InterJournal, Complex Systems* 1695. <http://igraph.org>.

See Also

[checkmoves](#), [make.line](#), [networkdistance](#), [SpatialLinesDataFrame](#), [showedges](#), [deleteedges](#), [addedges](#)

Examples

```
## test make.sldf()

coord <- data.frame(x = c(1,2,3,1.05,2.05,3.05),
  y = c(3,2,2,3.05,2.05,2.05))

sldf1 <- make.sldf(coord)
sldf2 <- make.sldf(coord, f = c(1,1,1,2,2,2))

if (require('sp')) {
  plot(sldf1)
  plot(sldf2)
}

## test snapPointsToLinearMask()

## Not run:

x <- seq(0, 4*pi, length = 200)
xy <- data.frame(x = x*100, y = sin(x)*300)
mask <- read.linearmask(data = xy, spacing = 20)
plot(mask)
## click several points, right-click and select 'stop'
pts <- locator()
pts <- do.call(cbind, pts)
points(pts)
pts1 <- snapPointsToLinearMask(pts, mask)
segments(pts[,1], pts[,2], pts1[,1], pts1[,2])
points(pts1, pch = 16, col = 'red')
df <- data.frame(pts, pts1)
```

```
names(df) <- c('from.x', 'from.y', 'to.x', 'to.y')
df
```

```
## End(Not run)
```

```
## asgraph (called by networkdistance)
## see 'igraph' for further manipulation
grmask <- asgraph(glymemask)
if (require('igraph')) {
  summary(grmask)
}
```

Index

- *Topic **IO**
 - read.linearMask, 18
 - *Topic **S3class**
 - linearMask.object, 11
 - linearPopn.object, 13
 - *Topic **datagen**
 - make.line, 13
 - sim.linearPopn, 22
 - *Topic **datasets**
 - Arvicola, 4
 - glymemask, 10
 - Silverstream, 21
 - *Topic **hplot**
 - plotMethods, 16
 - *Topic **manip**
 - checkMoves, 6
 - clipMask, 7
 - edges, 8
 - networkDistance, 15
 - rbind.linearMask, 17
 - showPath, 20
 - subset.linearMask, 23
 - utility, 25
 - *Topic **package**
 - seclinear-package, 2
- addCovariates, 19
- addEdges, 3, 26
- addEdges (edges), 8
- Arvicola, 4
- arvicola, 3, 10, 11
- arvicola (Arvicola), 4
- asGraph, 2, 3, 8, 11, 15, 19
- asGraph (utility), 25
- capHist, 4
- checkMoves, 2, 3, 6, 26
- cleansKips, 19
- cleansKips (edges), 8
- clipMask, 2, 3, 7
- covariates, 19
- deleteEdges, 3, 26
- deleteEdges (edges), 8
- edges, 8, 25
- get.shortest.paths, 20
- getLineID, 9
- getLineID (utility), 25
- glymemask, 3, 5, 10
- legend, 16
- linearMask, 3, 6, 8, 9, 18, 19, 24
- linearMask (linearMask.object), 11
- linearMask.object, 11
- linearPopn, 3, 13, 23
- linearPopn (linearPopn.object), 13
- linearPopn.object, 13
- lines, 20
- make.grid, 13
- make.line, 2, 3, 7, 13, 25, 26
- make.sldf, 2, 3, 19
- make.sldf (utility), 25
- make.traps, 14
- mask, 11, 12
- networkDistance, 2, 3, 12, 15, 19, 21, 26
- par, 16
- plot.linearMask, 3, 25
- plot.linearMask (plotMethods), 16
- plot.linearPopn, 13
- plot.linearPopn (plotMethods), 16
- plot.mask, 16, 17
- plot.popn, 16, 17
- plotMethods, 16
- popn, 13
- rbind.linearMask, 2, 3, 17

`read.linearMask`, 2, 3, 10–12, 15, 16, 18, 18,
24
`replot` (edges), 8

`seclinear` (`seclinear`-package), 2
`seclinear`-package, 2
`showEdges`, 3, 26
`showEdges` (edges), 8
`showPath`, 2, 3, 12, 15, 20
Silverstream, 3, 21
`sim.caphist`, 13, 23
`sim.linearPopn`, 2, 3, 13, 16, 17, 22
`sim.popn`, 22, 23
`snapPointsToLinearMask`, 2, 3
`snapPointsToLinearMask` (utility), 25
`SpatialLinesDataFrame`, 19, 26
`spRbind`, 18
`subset.linearMask`, 2, 3, 18, 23

utility, 25