

Package ‘doRNG’

February 19, 2015

Type Package

Title Generic Reproducible Parallel Backend for foreach Loops

Version 1.6

Date 2013-09-12

Author Renaud Gaujoux

Maintainer Renaud Gaujoux <renaud@tx.technion.ac.il>

Description This package provides functions to perform reproducible parallel foreach loops, using independent random streams as generated by L'Ecuyer's combined multiple-recursive generator [L'Ecuyer (1999)]. It enables to easily convert standard `%dopar%` loops into fully reproducible loops, independently of the number of workers, the task scheduling strategy, or the chosen parallel environment and associated foreach backend.

License GPL (>= 2)

LazyLoad yes

URL <https://renozao.github.io/doRNG>

BugReports <http://github.com/renozao/doRNG/issues>

SCM github:renozao, r-forge

VignetteBuilder knitr

Depends R (>= 3.0.0), foreach, rngtools (>= 1.2.4)

Imports stats, iterators, pkgmaker (>= 0.20)

Suggests doParallel, doMPI, doRedis, rbenchmark, RUnit, devtools, knitr, bibtex

Collate 'doRNG-package.R' 'doRNG.R'

NeedsCompilation no

Repository CRAN

Date/Publication 2014-03-07 10:06:10

R topics documented:

doRNG-package	2
doRNGversion	4
registerDoRNG	5
%dorng%	6

Index	8
--------------	----------

doRNG-package	<i>Generic Reproducible Parallel Backend for foreach Loops</i>
---------------	--

Description

The *doRNG* package provides functions to perform reproducible parallel foreach loops, using independent random streams as generated by L'Ecuyer's combined multiple-recursive generator [L'Ecuyer (1999)]. It enables to easily convert standard fully reproducible loops, independently of the number of workers, the task scheduling strategy, or the chosen parallel environment and associated foreach backend. It has been tested with the following foreach backend: doMC, doSNOW, doMPI.

Details

Package:	doRNG
Type:	Package
Version:	1.2.3
Date:	2012-03-30
License:	GPL (>= 2)
LazyLoad:	yes

Author(s)

Renaud Gaujoux <renaud@cbio.uct.ac.za>,

Maintainer: Renaud Gaujoux <renaud@cbio.uct.ac.za>,

References

L'Ecuyer P (1999). "Good parameters and implementations for combined multiple recursive random number generators." *_Operations Research_*, *47*(1). <URL: <http://www.jstor.org/stable/10.2307/222902>>.

See Also

[doRNG](#), [RNGseq](#)

Examples

```
# register parallel backend
library(doParallel)
cl <- makeCluster(2)
registerDoParallel(cl)

## standard %dopar% loop are not reproducible
set.seed(123)
r1 <- foreach(i=1:4) %dopar%{ runif(1) }
set.seed(123)
r2 <- foreach(i=1:4) %dopar%{ runif(1) }
identical(r1, r2)

## %dorng% loops are reproducible
set.seed(123)
r1 <- foreach(i=1:4) %dorng%{ runif(1) }
set.seed(123)
r2 <- foreach(i=1:4) %dorng%{ runif(1) }
identical(r1, r2)

# alternative way of seeding
a1 <- foreach(i=1:4, .options.RNG=123) %dorng%{ runif(1) }
a2 <- foreach(i=1:4, .options.RNG=123) %dorng%{ runif(1) }
identical(a1, a2) && identical(a1, r1)

## sequences of %dorng% loops are reproducible
set.seed(123)
s1 <- foreach(i=1:4) %dorng%{ runif(1) }
s2 <- foreach(i=1:4) %dorng%{ runif(1) }
identical(s1, r1) && !identical(s1, s2)

set.seed(123)
s1.2 <- foreach(i=1:4) %dorng%{ runif(1) }
s2.2 <- foreach(i=1:4) %dorng%{ runif(1) }
identical(s1, s1.2) && identical(s2, s2.2)

## Non-invasive way of converting %dopar% loops into reproducible loops
registerDoRNG(123)
s3 <- foreach(i=1:4) %dopar%{ runif(1) }
s4 <- foreach(i=1:4) %dopar%{ runif(1) }
identical(s3, s1) && identical(s4, s2)

stopCluster(cl)
```

doRNGversion

*Back Compatibility Option for doRNG***Description**

Sets the behaviour of `%dorng%` foreach loops from a given version number.

Usage

```
doRNGversion(x)
```

Arguments

`x` version number to switch to, or missing to get the currently active version number, or NULL to reset to the default behaviour, i.e. of the latest version.

Value

a character string If `x` is missing this function returns the version number from the current behaviour. If `x` is specified, the function returns the old value of the version number (invisible).

Behaviour changes in versions

1.4 The behaviour of `doRNGseed`, and therefore of `%dorng%` loops, changed in the case where the current RNG was L'Ecuyer-CMRG. Using `set.seed` before a non-seeded loop used not to be identical to seeding via `.options.RNG`. Another bug was that non-seeded loops would share most of their RNG seed!

Examples

```
## Seeding when current RNG is L'Ecuyer-CMRG
RNGkind("L'Ecuyer")

doRNGversion("1.4")
# in version >= 1.4 seeding behaviour changed to fix a bug
set.seed(123)
res <- foreach(i=1:3) %dorng% runif(1)
res2 <- foreach(i=1:3) %dorng% runif(1)
stopifnot( !identical(attr(res, 'rng')[2:3], attr(res2, 'rng')[1:2]) )
res3 <- foreach(i=1:3, .options.RNG=123) %dorng% runif(1)
stopifnot( identical(res, res3) )

# buggy behaviour in version < 1.4
doRNGversion("1.3")
res <- foreach(i=1:3) %dorng% runif(1)
```

```

res2 <- foreach(i=1:3) %dorng% runif(1)
stopifnot( identical(attr(res, 'rng')[2:3], attr(res2, 'rng')[1:2]) )
res3 <- foreach(i=1:3, .options.RNG=123) %dorng% runif(1)
stopifnot( !identical(res, res3) )

# restore default RNG
RNGkind("default")
# restore to current doRNG version
doRNGversion(NULL)

```

registerDoRNG	<i>Registering doRNG for Persistent Reproducible Parallel Foreach Loops</i>
---------------	---

Description

registerDoRNG registers the doRNG foreach backend. Subsequent %dopar% loops are then performed using the previously registered foreach backend, but are internally performed as %dorng% loops, making them fully reproducible.

Usage

```
registerDoRNG(seed = NULL, once = TRUE)
```

Arguments

seed	a numerical seed to use (as a single or 6-length numerical value)
once	a logical to indicate if the RNG sequence should be seeded at the beginning of each loop or only at the first loop.

Details

Briefly, the RNG is set, before each iteration, with seeds for L'Ecuyer's CMRG that overall generate a reproducible sequence of statistically independent random streams.

Note that (re-)registering a foreach backend other than doRNG, after a call to registerDoRNG disables doRNG – which then needs to be registered.

See Also

[%dorng%](#)

Examples

```

library(doParallel)
cl <- makeCluster(2)
registerDoParallel(cl)

```

```

# One can make reproducible loops using the %dorng% operator
r1 <- foreach(i=1:4, .options.RNG=1234) %dorng% { runif(1) }
# or convert %dopar% loops using registerDoRNG
registerDoRNG(1234)
r2 <- foreach(i=1:4) %dopar% { runif(1) }
identical(r1, r2)
stopCluster(c1)

# Registering another foreach backend disables doRNG
c1 <- makeCluster(2)
registerDoParallel(c1)
set.seed(1234)
s1 <- foreach(i=1:4) %dopar% { runif(1) }
set.seed(1234)
s2 <- foreach(i=1:4) %dopar% { runif(1) }
identical(s1, s2)

# doRNG is re-nabled by re-registering it
registerDoRNG()
set.seed(1234)
r3 <- foreach(i=1:4) %dopar% { runif(1) }
identical(r2, r3)
# NB: the results are identical independently of the task scheduling
# (r2 used 2 nodes, while r3 used 3 nodes)

# argument `once=FALSE` reseeds doRNG's seed at the beginning of each loop
registerDoRNG(1234, once=FALSE)
r1 <- foreach(i=1:4) %dopar% { runif(1) }
r2 <- foreach(i=1:4) %dopar% { runif(1) }
identical(r1, r2)

# Once doRNG is registered the seed can also be passed as an option to %dopar%
r1.2 <- foreach(i=1:4, .options.RNG=456) %dopar% { runif(1) }
r2.2 <- foreach(i=1:4, .options.RNG=456) %dopar% { runif(1) }
identical(r1.2, r2.2) && !identical(r1.2, r1)

stopCluster(c1)

```

%dorng%

Reproducible Parallel Foreach Backend

Description

%dorng% is a foreach operator that provides an alternative operator %dopar%, which enable reproducible foreach loops to be performed.

Usage

```
obj %dorng% ex
```

Arguments

obj a foreach object as returned by a call to [foreach](#).
ex the R expression to evaluate.

Value

%dorng% returns the result of the foreach loop. See [%dopar%](#). The whole sequence of RNG seeds is stored in the result object as an attribute. Use `attr(res, 'rng')` to retrieve it.

See Also

[foreach](#), [doParallel](#) , [registerDoParallel](#), [doMPI](#)

Examples

```
library(doParallel)
cl <- makeCluster(2)
registerDoParallel(cl)

# standard %dopar% loops are _not_ reproducible
set.seed(1234)
s1 <- foreach(i=1:4) %dopar% { runif(1) }
set.seed(1234)
s2 <- foreach(i=1:4) %dopar% { runif(1) }
identical(s1, s2)

# single %dorng% loops are reproducible
r1 <- foreach(i=1:4, .options.RNG=1234) %dorng% { runif(1) }
r2 <- foreach(i=1:4, .options.RNG=1234) %dorng% { runif(1) }
identical(r1, r2)
# the sequence of RNG seed is stored as an attribute
attr(r1, 'rng')

# stop cluster
stopCluster(cl)

# More examples can be found in demo `doRNG`
## Not run:
demo('doRNG')

## End(Not run)
```

Index

*Topic **package**

doRNG-package, 2

%dopar%, 7

%dorng%, 5, 6

doMPI, 7

doParallel, 7

doRNG, 2

doRNG-package, 2

doRNGversion, 4

foreach, 7

registerDoParallel, 7

registerDoRNG, 5

RNGseq, 2