

Package ‘EffectLiteR’

October 18, 2015

Version 0.4-1

Date 2015-10-17

Title Average and Conditional Effects

Author Axel Mayer [aut, cre],
Lisa Dietzfelbinger [ctb]

Maintainer Axel Mayer <amayer2010@gmail.com>

Description Use structural equation modeling to estimate average and conditional effects of a treatment variable on an outcome variable, taking into account multiple continuous and categorical covariates.

Depends R (>= 3.1.0), lavaan (>= 0.5-19)

Imports methods, shiny (>= 0.11), foreign, ggplot2, nnet, survey,
lavaan.survey, car

License GPL (>= 2)

URL <https://github.com/amayer2010/EffectLiteR>

LazyData yes

NeedsCompilation no

Repository CRAN

Date/Publication 2015-10-18 17:19:54

R topics documented:

conditionalEffectsPlot	2
effectLite	2
effectLiteGUI	4
EffectLiteR	5
elrReadData	5
example01	6
example02lv	6
example_multilevel	7
generateMeasurementModel	7
nonortho	8
Index	9

 conditionalEffectsPlot

Plot conditional effects

Description

Can be used to make a conditional effects plot with an effect function on the y axis and a covariate on the x axis. `ggplot2` is used to create the plot.

Usage

```
conditionalEffectsPlot(obj, zsel, gxsel = "g1", colour = "")
```

Arguments

<code>obj</code>	Object of class <code>effectlite</code> obtained from fitting an effect model using effectLite
<code>zsel</code>	Name of a covariate (character string) plotted on the x-axis.
<code>gxsel</code>	Name of an effect function (character string) plotted on the y-axis.
<code>colour</code>	Name of a covariate (character string) used as colour variable in the plot.

Value

Object of class `c("gg", "ggplot")`.

Examples

```
m1 <- effectLite(y="dv", x="x", k="k1", z="z1", control="control", data=example01)
conditionalEffectsPlot(m1, zsel="z1", gxsel="g1", colour="k1")
```

 effectLite

Estimate average and conditional effects

Description

This function is the main function of the package and can be used to estimate average and conditional effects of a treatment variable on an outcome variable, taking into account any number of continuous and categorical covariates. It automatically generates lavaan syntax for a multi-group structural equation model, runs the model using lavaan, and extracts various average and conditional effects of interest.

Usage

```
effectLite(y, x, k = NULL, z = NULL, control = "0",
  measurement = character(), data, fixed.cell = FALSE,
  missing = "listwise", se = "standard", bootstrap = 1000L,
  syntax.only = FALSE, interactions = "all", propscore = NULL, ids = ~0,
  weights = NULL, homoscedasticity = FALSE, add = character(), ...)
```

Arguments

y	Dependent variable (character string). Can be the name of a manifest variable or of a latent variable.
x	Treatment variable (character string) treated as categorical variable.
k	Vector of manifest variables treated as categorical covariates (character vector).
z	Vector of continuous covariates (character vector). Names of both manifest and latent variables are allowed.
control	Value of x that is used as control group.
measurement	Measurement model. The measurement model is lavaan syntax (character string), that will be appended before the automatically generated lavaan input. It can be used to specify a measurement for a latent outcome variable and/or latent covariates. See also the example and generateMeasurementModel .
data	A data frame.
fixed.cell	logical. If FALSE (default), the group sizes are treated as stochastic rather than fixed.
missing	Missing data handling. Will be passed on to sem .
se	Type of standard errors. Will be passed on to sem .
bootstrap	Number of bootstrap draws, if bootstrapping is used. Will be passed on to sem .
syntax.only	logical. If TRUE, only syntax is returned and the model will not be estimated.
interactions	character. Can be one of c("all", "none", "2-way", "X:K", "X:Z") and indicates the type of interaction used in the parameterization of the regression.
propscore	Vector of covariates (character vector) that will be used to compute (multiple) propensity scores based on a multinomial regression without interactions. Alternatively, the user can specify a formula with the treatment variable as dependent variable for more control over the propensity score model.
ids	Formula specifying cluster ID variables. Will be passed on to lavaan.survey . See svydesign for details.
weights	Formula to specify sampling weights. Currently only one weight variable is supported. Will be passed on to lavaan.survey . See svydesign for details.
homoscedasticity	logical. If TRUE, residual variances of the dependent variable are assumed to be homogeneous across cells.
add	Character string that will be pasted at the end of the generated lavaan syntax. Can for example be used to add additional (in-) equality constraints or to compute user-defined conditional effects.
...	Further arguments passed to sem .

Value

Object of class effectlite.

Examples

```
## Example with one categorical covariate
m1 <- effectLite(y="y", x="x", k="z", control="0", data=nonortho)
print(m1)

## Example with one categorical and one continuous covariate
m1 <- effectLite(y="dv", x="x", k=c("k1"), z=c("z1"), control="control", data=example01)
print(m1)

## Example with latent outcome and latent covariate
measurement <- '
eta2 =~ 1*CPM12 + 1*CPM22
eta1 =~ 1*CPM11 + 1*CPM21
CPM11 + CPM12 ~ 0*1
CPM21 ~ c(m,m)*1
CPM22 ~ c(p,p)*1'

m1 <- effectLite(y="eta2", x="x", z=c("eta1"), control="0",
                 measurement=measurement, data=example02lv)
print(m1)

## Not run:
## Example with cluster variable and sampling weights
m1 <- effectLite(y="y", x="x", z="z", fixed.cell=TRUE, control="0",
                 syntax.only=F, data=example_multilevel,
                 ids=~cid, weights=~weights)

print(m1)

## End(Not run)
```

effectLiteGUI

Shiny interface for effectLite

Description

This function calls a shiny interface for effectLite.

Usage

```
effectLiteGUI(launch.browser = TRUE)
```

Arguments

`launch.browser` Option will be passed on to [runApp](#)

 EffectLiteR

EffectLiteR

Description

 EffectLiteR

elrReadData

Read Data File

Description

Tries to determine the format of the data by the file ending and chooses the appropriate function to read data. Currently supports .csv, .dat, .txt, .sav, and .xpt and calls [read.csv](#), [read.table](#), [read.spss](#), [read.xport](#) accordingly. The default values for arguments depend on the function used to read data.

Usage

```
elrReadData(file, name = NULL, header = "default", sep = "default",
  dec = "default", use.value.labels = "default", na.strings = "NA")
```

Arguments

file	Name of the file to read.
name	Pure file name (without path to file) to read. If file includes a lengthy path name with many special characters, specifying this argument in addition to file may help the function to find the file ending.
header	See read.table .
sep	See read.table .
dec	See read.table .
use.value.labels	See read.spss .
na.strings	See read.spss .

Value

Object of class "data.frame".

example01

Dataset example01.

Description

A simulated dataset. The variables are:

Format

A data frame with 2000 rows and 7 variables.

Details

- x. Treatment variable with values control, treat1, and treat2.
- k1. Categorical covariate with values male and female.
- kateg2. Categorical covariate with values 1 and 2.
- z1-z3. Continuous covariates.
- dv. Continuous dependent variable.

example02lv

Dataset example02lv.

Description

A simulated dataset with latent variables. The variables are:

Format

A data frame with 300 rows and 6 variables.

Details

- CPM11. First indicator of latent covariate.
- CPM21. Second indicator of latent covariate.
- CPM12. First indicator of latent outcome.
- CPM22. Second indicator of latent outcome.
- x. Dichotomous treatment variable with values 0 (control), and 1 (treatment).
- k. Categorical covariate with values first, second, and third.

example_multilevel *Dataset example_multilevel.*

Description

A simulated dataset with a cluster ID and sampling weights to test multilevel options. The variables are:

Format

A data frame with 800 rows and 6 variables.

Details

- y. Continuous dependent variable.
- x. Treatment variable with values 0, 1.
- z. Continuous covariate.
- xz. Product of x and z.
- cid. Cluster ID.
- weights. Sampling weights.

generateMeasurementModel

Generate measurement model

Description

This function automatically generates lavaan syntax for the measurement model for a call to [effectLite](#). It is currently also used in the shiny interface.

Usage

```
generateMeasurementModel(names, indicators, ncells, model)
```

Arguments

names	A vector of character strings with names of latent variables.
indicators	A list of vectors of character strings to specify indicators of latent variables (see example).
ncells	Number of groups/cells.
model	A vector of character strings of the same length as names. It is used to specify the type of measurement model for each of the latent variables. Each element can be one of c("parallel", "tau-equi", "tau-cong") indicating whether a parallel, essentially tau-equivalent, or tau-congeneric measurement model is used.

Examples

```
names <- c("etay", "etaz1", "etaz2")
indicators <- list("etay" = c("y1", "y2", "y3"),
                  "etaz1" = c("z1", "z2"),
                  "etaz2" = c("z12", "z22", "z32", "z42"))

ncells = 6
model = c("parallel", "tau-equi", "tau-cong")

cat(generateMeasurementModel(names, indicators, ncells, model))
```

nonortho

Dataset nonortho.

Description

A simulated dataset. The variables are:

Format

A data frame with 500 rows and 3 variables

Details

- y. Continuous dependent variable depression.
- x. Treatment variable with values 0 (control), 1 (treat1), and 2 (treat2).
- z. Categorical covariate with values 0 (low neediness), 1 (medium neediness) and 2 (high neediness).

Index

*Topic **datasets**

- example01, [6](#)
- example02lv, [6](#)
- example_multilevel, [7](#)
- nonortho, [8](#)

conditionalEffectsPlot, [2](#)

effectLite, [2](#), [2](#), [7](#)

effectLiteGUI, [4](#)

EffectLiteR, [5](#)

EffectLiteR-package (EffectLiteR), [5](#)

elrReadData, [5](#)

example01, [6](#)

example02lv, [6](#)

example_multilevel, [7](#)

generateMeasurementModel, [3](#), [7](#)

lavaan.survey, [3](#)

nonortho, [8](#)

read.csv, [5](#)

read.spss, [5](#)

read.table, [5](#)

read.xport, [5](#)

runApp, [4](#)

sem, [3](#)

svydesign, [3](#)