

Package ‘meta’

December 2, 2015

Title General Package for Meta-Analysis

Version 4.3-2

Depends R (>= 2.9.1)

Imports grid

Suggests metafor

Date 2015-12-02

Description User-friendly general package providing standard methods for meta-analysis:

- fixed effect and random effects meta-analysis;
- several plots (forest, funnel, Galbraith / radial, L'Abbe, Baujat, bubble);
- statistical tests and trim-and-fill method to evaluate bias in meta-analysis;
- import data from RevMan 5;
- prediction interval, Hartung-Knapp and Paule-Mandel method for random effects model;
- cumulative meta-analysis and leave-one-out meta-analysis;
- meta-regression (if R package 'metafor' is installed).

License GPL (>= 2)

Encoding UTF-8

NeedsCompilation yes

Author Guido Schwarzer [cre, aut]

Maintainer Guido Schwarzer <sc@imbi.uni-freiburg.de>

Repository CRAN

Date/Publication 2015-12-02 14:22:28

R topics documented:

amlodipine	2
as.data.frame.meta	3
baujat	5
bubble	7
ci	9
cisapride	10
Fleiss93	12

Fleiss93cont	13
forest	14
funnel	27
labbe	31
metabias	34
metabin	38
metacont	46
metacor	53
metacr	60
metacum	62
metagen	64
metainc	71
metainf	78
metaprop	80
metareg	90
Olkin95	92
print.meta	93
print.rm5	98
read.mtv	100
read.rm5	102
settings.meta	105
smoking	107
trimfill	108
update.meta	112

Index	117
--------------	------------

amlodipine	<i>Amlodipine for Work Capacity</i>
------------	-------------------------------------

Description

Meta-analysis on the effect of amlodipine on work capacity.

This meta-analysis is used as a data example in Hartung and Knapp (2001).

Usage

```
data(amlodipine)
```

Format

A data frame with the following columns:

study Study label

n.amlo Number of observations in amlodipine group

mean.amlo Estimated mean in amlodipine group

var.amlo Variance in amlodipine group

n.plac Number of observations in placebo group

mean.plac Estimated mean in placebo group

var.plac Variance in placebo group

Source

Hartung J & Knapp G (2001), On tests of the overall treatment effect in meta-analysis with normally distributed responses. *Statistics in Medicine*, **20**, 1771–82. doi: 10.1002/sim.791 .

See Also

[metacont](#)

Examples

```
data(amlodipine)
#
m <- metacont(n.amlo, mean.amlo, sqrt(var.amlo),
              n.plac, mean.plac, sqrt(var.plac),
              data=amlodipine, studlab=study)

m.hakn <- metacont(n.amlo, mean.amlo, sqrt(var.amlo),
                  n.plac, mean.plac, sqrt(var.plac),
                  data=amlodipine, studlab=study,
                  hakn=TRUE)

# Results for mean difference - see Table III in Hartung and Knapp (2001)
#
res.md <- rbind(data.frame(summary(m)$fixed)[c("TE", "lower", "upper")],
               data.frame(summary(m)$random)[c("TE", "lower", "upper")],
               data.frame(summary(m.hakn)$random)[c("TE", "lower", "upper")])
#
res.md <- round(res.md, 5)
#
row.names(res.md) <- c("FE", "RE", "RE (HaKn)")
names(res.md) <- c("Absolute difference", "CI lower", "CI upper")
#
res.md
```

as.data.frame.meta *Additional functions for objects of class meta*

Description

The `as.data.frame` method returns a data frame containing information on individual studies, e.g., estimated treatment effect and its standard error.

Usage

```
## S3 method for class 'meta'  
as.data.frame(x, row.names=NULL, optional=FALSE, ...)
```

Arguments

x	An object of class meta.
row.names	NULL or a character vector giving the row names for the data frame.
optional	logical. If TRUE, setting row names and converting column names (to syntactic names) is optional.
...	other arguments

Value

A data frame is returned by the function `as.data.frame`.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[metabin](#), [metacont](#), [metagen](#), [forest.meta](#)

Examples

```
data(Fleiss93cont)  
#  
# Generate additional variable with grouping information  
#  
Fleiss93cont$group <- c(1,2,1,1,2)  
#  
# Do meta-analysis without grouping information  
#  
meta1 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, study,  
                 data=Fleiss93cont, sm="SMD")  
#  
# Update meta-analysis object and do subgroup analyses  
#  
summary(update(meta1, byvar=group))  
  
#  
# Same result using metacont function directly  
#  
meta2 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, study,  
                 data=Fleiss93cont, sm="SMD", byvar=group)  
summary(meta2)  
  
#
```

```
# Compare printout of the following two commands
#
as.data.frame(meta1)
meta1$data
```

baujat

Baujat plot to explore heterogeneity in meta-analysis

Description

Draw a Baujat plot to explore heterogeneity in meta-analysis.

Usage

```
baujat(x, ...)
```

```
## S3 method for class 'meta'
baujat(x,
       yscale=1, xlim, ylim,
       xlab="Contribution to overall heterogeneity",
       ylab="Influence on overall result",
       pch=21, cex=1, col="black", bg="darkgray",
       studlab=TRUE, cex.studlab=0.8,
       xmin=0, ymin=0, pos=2, offset=0.5,
       grid=TRUE, col.grid="lightgray", lty.grid="dotted", lwd.grid=par("lwd"),
       pty="s", ...)
```

Arguments

x	An object of class meta.
yscale	Scaling factor for values on y-axis.
xlim	The x limits (min,max) of the plot.
ylim	The y limits (min,max) of the plot.
xlab	A label for the x-axis.
ylab	A label for the y-axis.
pch	The plotting symbol used for individual studies.
cex	The magnification to be used for plotting symbol.
col	A vector with colour of plotting symbols.
bg	A vector with background colour of plotting symbols (only used if pch in 21:25).
studlab	A logical indicating whether study labels should be printed in the graph. A vector with study labels can also be provided (must be of same length as x\$TE then).
cex.studlab	The magnification for study labels.
xmin	A numeric specifying minimal value to print study labels (on x-axis).

<code>ymin</code>	A numeric specifying minimal value to print study labels (on y-axis).
<code>pos</code>	A position specifier for study labels (see text).
<code>offset</code>	Offset for study labels (see text).
<code>grid</code>	A logical indicating whether a grid is printed in the plot.
<code>col.grid</code>	Colour for grid lines.
<code>lty.grid</code>	The line type for grid lines.
<code>lwd.grid</code>	The line width for grid lines.
<code>pty</code>	A character specifying type of plot region (see par).
<code>...</code>	Graphical arguments as in <code>par</code> may also be passed as arguments.

Details

Baujat et al. (2002) introduced a scatter plot to explore heterogeneity in meta-analysis. On the x-axis the contribution of each study to the overall heterogeneity statistic (see list object `Q` of the meta-analysis object `x`) is plotted. On the y-axis the standardised difference of the overall treatment effect with and without each study is plotted; this quantity describes the influence of each study on the overall treatment effect.

Internally, the `metainf` function is used to calculate the values on the y-axis.

Value

A data.frame with the following variables:

<code>x</code>	Coordinate on x-axis (contribution to heterogeneity statistic).
<code>y</code>	Coordinate on y-axis (influence on overall treatment effect).

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Baujat B, Mahé C, Pignon JP, Hill C (2002), A graphical method for exploring heterogeneity in meta-analyses: Application to a meta-analysis of 65 trials. *Statistics in Medicine*, **30**, 2641–2652.

See Also

[metagen](#), [metainf](#)

Examples

```
data(Olkin95)

m1 <- metabin(event.e, n.e, event.c, n.c, data=Olkin95,
              studlab=author, sm="OR", method="I")

# Generate Baujat plot
baujat(m1)
```

```

# Do not print study labels if the x-value is smaller than 4 and the
# y-value is smaller than 1.
baujat(m1, yscale=10, xmin=4, ymin=1)

# Change position of study labels
baujat(m1, yscale=10, xmin=4, ymin=1,
       pos=1, xlim=c(0, 6.5))

# Generate Baujat plot and assign x- and y- coordinates to R object b1
b1 <- baujat(m1)

# Calculate overall heterogeneity statistic
sum(b1$x)
m1$Q

```

bubble

Bubble plot to display the result of a meta-regression

Description

Draw a bubble plot to display the result of a meta-regression.

Usage

```

bubble(x, ...)

## S3 method for class 'metareg'
bubble(x,
       xlim, ylim, xlab, ylab,
       cex, min.cex=0.5, max.cex=5,
       pch=21, col="black", bg="darkgray",
       lty=1, lwd=1, col.line="black",
       studlab=FALSE, cex.studlab=0.8,
       pos=2, offset=0.5,
       regline=TRUE,
       axes=TRUE, box=TRUE,
       ...)

```

Arguments

x	An object of class metareg.
xlim	The x limits (min,max) of the plot.
ylim	The y limits (min,max) of the plot.
xlab	A label for the x-axis.
ylab	A label for the y-axis.
cex	The magnification to be used for plotting symbols.

<code>min.cex</code>	Minimal magnification for plotting symbols.
<code>max.cex</code>	Maximal magnification for plotting symbols.
<code>pch</code>	The plotting symbol used for individual studies.
<code>col</code>	A vector with colour of plotting symbols.
<code>bg</code>	A vector with background colour of plotting symbols (only used if <code>pch</code> in 21 : 25).
<code>lty</code>	The line type for the meta-regression line.
<code>lwd</code>	The line width for the meta-regression line.
<code>col.line</code>	Colour for the meta-regression line.
<code>studlab</code>	A logical indicating whether study labels should be printed in the graph. A vector with study labels can also be provided (must be of same length as the number of studies in the meta-analysis then).
<code>cex.studlab</code>	The magnification for study labels.
<code>pos</code>	A position specifier for study labels (see text).
<code>offset</code>	Offset for study labels (see text).
<code>regline</code>	A logical indicating whether a regression line should be added to the bubble plot.
<code>axes</code>	A logical indicating whether axes should be printed.
<code>box</code>	A logical indicating whether a box should be printed.
<code>...</code>	Graphical arguments as in <code>par</code> may also be passed as arguments.

Details

A bubble plot can be used to display the result of a meta-regression. It is a scatter plot with the treatment effect for each study on the y-axis and the covariate used in the meta-regression on the x-axis. Typically, the size of the plotting symbol is inversely proportional to the variance of the estimated treatment effect (Thompson & Higgins, 2002).

Argument `cex` specifies the plotting size for each individual study. If this argument is missing the weights from the meta-regression model will be used (which typically is a random effects model). Use `weight="fixed"` in order to utilise weights from a fixed effect model to define the size of the plotted symbols (even for a random effects meta-regression). If a vector with individual study weights is provided, the length of this vector must be of the same length as the number of studies.

Arguments `min.cex` and `max.cex` can be used to define the size of the smallest and largest plotting symbol. The plotting size of the most precise study is set to `max.cex` whereas the plotting size of all studies with a plotting size smaller than `min.cex` will be set to `min.cex`.

For a meta-regression with more than one covariate. Only a scatter plot of the first covariate in the regression model is shown. In this case the effect of the first covariate adjusted for other covariates in the meta-regression model is shown.

For a factor or categorical covariate separate bubble plots for each group compared to the baseline group are plotted.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Thompson SG, Higgins JP (2002), How should meta-regression analyses be undertaken and interpreted? *Statistics in Medicine*, **21**, 1559–1573.

See Also

[metagen](#), [metainf](#)

Examples

```
data(Fleiss93cont)

# Add some (fictitious) grouping variables:
Fleiss93cont$age <- c(55, 65, 52, 65, 58)
Fleiss93cont$region <- c("Europe", "Europe", "Asia", "Asia", "Europe")

meta1 <- metacont(n.e, mean.e, sd.e,
                 n.c, mean.c, sd.c,
                 data=Fleiss93cont, sm="MD")

mr1 <- metareg(meta1, region)
mr1

bubble(mr1)
bubble(mr1, lwd=2, col.line="blue")

mr2 <- metareg(meta1, age)
mr2

bubble(mr2, lwd=2, col.line="blue", xlim=c(50, 70))
bubble(mr2, lwd=2, col.line="blue", xlim=c(50, 70), cex="fixed")

# Do not print regression line
#
bubble(mr2, lwd=2, col.line="blue", xlim=c(50, 70), regline=FALSE)
```

ci	<i>Calculation of confidence intervals (based on normal approximation or t-distribution)</i>
----	--

Description

Calculation of confidence intervals; based on normal approximation or t-distribution.

Usage

```
ci(TE, seTE, level=0.95, df=NULL)
```

Arguments

TE	Estimated treatment effect.
seTE	Standard error of treatment estimate.
level	The confidence level required.
df	Degrees of freedom (for confidence intervals based on t-distribution).

Value

List with components

TE	Estimated treatment effect.
seTE	Standard error of treatment estimate.
lower	Lower confidence limits.
upper	Upper confidence limits.
z	Test statistic (either z-score or t-score).
p	P-value of test with null hypothesis $TE=0$.
level	The confidence level required.
df	Degrees of freedom (t-distribution).

Note

This function is primarily called from other functions of the library `meta`, e.g. `forest.meta`, `summary.meta`.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

Examples

```
data.frame(ci(170, 10))
data.frame(ci(170, 10, 0.99))
data.frame(ci(1.959964, 1))
data.frame(ci(2.2621571628, 1, df=9))
```

cisapride

Cisapride in Non-Ulcer Dyspepsia

Description

Meta-analysis on cisapride in non-ulcer dyspepsia.

This meta-analysis is used as a data example in Hartung and Knapp (2001).

Usage

```
data(cisapride)
```

Format

A data frame with the following columns:

study Study label
event.cisa Number of events in cisapride group
n.cisa Number of observations in cisapride group
event.plac Number of events in placebo group
n.plac Number of observations in placebo group

Source

Hartung J & Knapp G (2001), A Refined Method for the Meta-analysis of Controlled Clinical Trials with Binary Outcome. *Statistics in Medicine*, **20**, 3875–89.

See Also

[metabin](#)

Examples

```
data(cisapride)

m.or <- metabin(event.cisa, n.cisa, event.plac, n.plac,
               data=cisapride, sm="OR", method="Inverse",
               studlab=study, addincr=TRUE)

m.rr <- metabin(event.cisa, n.cisa, event.plac, n.plac,
               data=cisapride, sm="RR", method="Inverse",
               studlab=study, addincr=TRUE)

m.or.hakn <- metabin(event.cisa, n.cisa, event.plac, n.plac,
                   data=cisapride, sm="OR", method="Inverse",
                   studlab=study, addincr=TRUE,
                   hakn=TRUE)

m.rr.hakn <- metabin(event.cisa, n.cisa, event.plac, n.plac,
                   data=cisapride, sm="RR", method="Inverse",
                   studlab=study, addincr=TRUE,
                   hakn=TRUE)

# Results for log risk ratio - see Table VII in Hartung and Knapp (2001)
#
res.rr <- rbind(data.frame(summary(m.rr)$fixed)[c("TE", "lower", "upper")],
               data.frame(summary(m.rr)$random)[c("TE", "lower", "upper")],
               data.frame(summary(m.rr.hakn)$random)[c("TE", "lower", "upper")])
#
```

```

row.names(res.rr) <- c("FE", "RE", "RE (HaKn)")
names(res.rr) <- c("Log risk ratio", "CI lower", "CI upper")
#
res.rr

# Results for log odds ratio (Table VII in Hartung and Knapp 2001)
#
res.or <- rbind(data.frame(summary(m.or)$fixed)[c("TE", "lower", "upper")],
               data.frame(summary(m.or)$random)[c("TE", "lower", "upper")],
               data.frame(summary(m.or.hakn)$random)[c("TE", "lower", "upper")])
#
row.names(res.or) <- c("FE", "RE", "RE (HaKn)")
names(res.or) <- c("Log odds ratio", "CI lower", "CI upper")
#
res.or

```

Fleiss93

Aspirin after Myocardial Infarction

Description

Meta-analysis on aspirin in preventing death after myocardial infarction.

Data example in Fleiss (1993) for meta-analysis with binary outcomes.

Usage

```
data(Fleiss93)
```

Format

A data frame with the following columns:

study Study label

year Year of publication

event.e Number of deaths in aspirin group

n.e Number of observations in aspirin group

event.c Number of deaths in placebo group

n.c Number of observations in placebo group

Source

Fleiss JL (1993), The statistical basis of meta-analysis. *Statistical Methods in Medical Research*, **2**, 121–145.

Examples

```
data(Fleiss93)
metabin(event.e, n.e, event.c, n.c,
        data=Fleiss93,
        studlab=paste(study, year),
        sm="OR", comb.random=FALSE)
```

Fleiss93cont

Mental Health Treatment

Description

Meta-analysis on the Effect of Mental Health Treatment on Medical Utilisation.

Data example in Fleiss (1993) for meta-analysis with continuous outcomes.

Usage

```
data(Fleiss93cont)
```

Format

A data frame with the following columns:

study Study label

year Year of publication

n.e Number of observations in psychotherapy group

mean.e Estimated mean in psychotherapy group

sd.e Standard deviation in psychotherapy group

n.c Number of observations in control group

mean.c Estimated mean in control group

sd.c Standard deviation in control group

Source

Fleiss JL (1993), The statistical basis of meta-analysis. *Statistical Methods in Medical Research*, **2**, 121–145.

See Also

[Fleiss93](#)

Examples

```

data(Fleiss93cont)
metacont(n.e, mean.e, sd.e,
         n.c, mean.c, sd.c,
         data=Fleiss93cont,
         studlab=paste(study, year),
         comb.random=FALSE)

```

forest

Forest plot to display the result of a meta-analysis

Description

Draws a forest plot in the active graphics window (using grid graphics system).

Usage

```

forest(x, ...)

## S3 method for class 'meta'
forest(x, sortvar, studlab=TRUE,
       comb.fixed=x$comb.fixed, comb.random=x$comb.random,
       overall=TRUE,
       text.fixed=if (x$level!=x$level.comb) paste("Fixed effect model (",
           round(x$level.comb*100), "%-CI)", sep="")
           else "Fixed effect model",
       text.random=if (x$level!=x$level.comb) paste("Random effects model (",
           round(x$level.comb*100), "%-CI)", sep="")
           else "Random effects model",
       lty.fixed=2, lty.random=3,
       prediction=x$prediction,
       text.predict=if (!(length(x$level.predict)==0) &&
           x$level!=x$level.predict)
           paste("Prediction interval (",
               round(x$level.predict*100), "%)",
               sep="") else "Prediction interval",
       bylab=x$bylab, print.byvar=x$print.byvar,
       text.fixed.w=text.fixed, text.random.w=text.random,
       bysort=FALSE,
       pooled.totals=comb.fixed|comb.random, pooled.events=FALSE,
       xlab="", xlab.pos=ref,
       smlab=NULL, smlab.pos=ref, xlim="symmetric",
       allstudies=TRUE,
       weight,
       pscale=1,
       ref=ifelse(backtransf & is.relative.effect(x$sm), 1, 0),
       layout="meta",

```

```

leftcols=NULL, rightcols=NULL,
leftlabs=NULL, rightlabs=NULL,
lab.e=x$label.e, lab.c=x$label.c,
lab.e.attach.to.col=NULL, lab.c.attach.to.col=NULL,
label.right=x$label.right, label.left=x$label.left,
lab.NA=".",
lab.NA.effect="",
lwd=1,
at=NULL, label=TRUE,
col.i="black", col.i.inside.square="white",
col.square="gray", col.square.lines=col.square,
col.diamond="gray",
col.diamond.fixed=col.diamond, col.diamond.random=col.diamond,
col.diamond.lines="black",
col.diamond.fixed.lines=col.diamond.lines,
col.diamond.random.lines=col.diamond.lines,
col.predict="red", col.predict.lines="black",
col.by="darkgray",
print.I2=comb.fixed|comb.random, print.I2.ci=FALSE,
print.tau2=comb.fixed|comb.random,
print.Q=FALSE, print.pval.Q=comb.fixed|comb.random,
hetstat=print.I2|print.tau2|print.Q|print.pval.Q,
overall.hetstat=overall&hetstat,
hetlab="Heterogeneity: ",
text.I2 = "I-squared",
text.tau2 = "tau-squared",
test.overall=.settings$test.overall,
test.overall.fixed=comb.fixed&overall&test.overall,
test.overall.random=comb.random&overall&test.overall,
label.test.overall.fixed=paste("Test for overall effect",
  if (comb.fixed & comb.random) " (fixed effect)", ": ", sep=""),
label.test.overall.random=paste("Test for overall effect",
  if (comb.fixed & comb.random) " (random effects)", ": ", sep=""),
test.subgroup=.settings$test.subgroup,
test.subgroup.fixed=if (missing(test.subgroup)) FALSE else test.subgroup,
test.subgroup.random=if (missing(test.subgroup)) !is.null(x$byvar)&
  comb.random&test.subgroup else test.subgroup,
print.Q.subgroup=print.Q,
label.test.subgroup.fixed="Test for subgroup differences (fixed effect): ",
label.test.subgroup.random=paste("Test for subgroup differences",
  if (test.subgroup.fixed | comb.fixed) " (random effects)", ": ", sep=""),
fontsize=12,
fs.heading=fontsize,
fs.fixed=fontsize, fs.random=fs.fixed, fs.predict=fs.fixed, fs.study=fontsize,
fs.fixed.labels=fs.fixed, fs.random.labels=fs.random, fs.predict.labels=fs.predict,
fs.study.labels=fs.study, fs.hetstat=fontsize-2,
fs.test.overall=fs.hetstat, fs.test.subgroup=fs.hetstat, fs.axis=fontsize,
fs.smlab=fontsize, fs.xlab=fontsize, fs.lr=fontsize,

```

```

ff.heading="bold",
ff.fixed="bold", ff.random=ff.fixed, ff.predict=ff.fixed, ff.study="plain",
ff.fixed.labels=ff.fixed, ff.random.labels=ff.random, ff.predict.labels=ff.predict,
ff.study.labels=ff.study, ff.hetstat="bold.italic",
ff.test.overall=ff.hetstat, ff.test.subgroup=ff.hetstat, ff.axis="plain",
ff.smlab="bold", ff.xlab="plain", ff.lr="plain",
#
squaresize=0.8,
#
plotwidth=grid::unit(6, "cm"),
colgap=grid::unit(2, "mm"),
colgap.left=colgap, colgap.right=colgap,
colgap.forest=colgap,
colgap.forest.left=colgap.forest, colgap.forest.right=colgap.forest,
#
just="right", just.studlab="left", just.addcols="center",
#
addspace=TRUE,
#
new=TRUE,
#
backtransf=x$backtransf,
digits=2, digits.se=4, digits.tau2=4, digits.pval=4, digits.pval.Q=digits.pval,
digits.Q=1, digits.I2=1, ...)

```

Arguments

<code>x</code>	An object of class <code>meta</code> .
<code>sortvar</code>	An optional vector used to sort the individual studies (must be of same length as <code>x\$TE</code>).
<code>studlab</code>	A logical indicating whether study labels should be printed in the graph. A vector with study labels can also be provided (must be of same length as <code>x\$TE</code> then).
<code>level</code>	The level used to calculate confidence intervals for individual studies.
<code>level.comb</code>	The level used to calculate confidence intervals for pooled estimates.
<code>comb.fixed</code>	A logical indicating whether fixed effect estimate should be plotted.
<code>comb.random</code>	A logical indicating whether random effects estimate should be plotted.
<code>overall</code>	A logical indicating whether overall summaries should be plotted. This argument is useful in combination with the argument <code>byvar</code> if summaries should only be plotted on group level.
<code>text.fixed</code>	A character string used in the plot to label the pooled fixed effect estimate.
<code>text.random</code>	A character string used in the plot to label the pooled random effects estimate.
<code>lty.fixed</code>	Line type (pooled fixed effect estimate).
<code>lty.random</code>	Line type (pooled random effects estimate).
<code>prediction</code>	A logical indicating whether a prediction interval should be printed.

<code>level.predict</code>	The level used to calculate prediction interval for a new study.
<code>text.predict</code>	A character string used in the plot to label the prediction interval.
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>text.fixed.w</code>	A character string to label the pooled fixed effect estimate within subgroups, or a character vector of same length as number of subgroups with corresponding labels.
<code>text.random.w</code>	A character string to label the pooled random effect estimate within subgroups, or a character vector of same length as number of subgroups with corresponding labels.
<code>bysort</code>	A logical indicating whether groups should be ordered alphabetically.
<code>pooled.totals</code>	A logical indicating whether total number of observations should be given in the figure.
<code>pooled.events</code>	A logical indicating whether total number of events should be given in the figure.
<code>xlab</code>	A label for the x-axis.
<code>xlab.pos</code>	A numeric specifying the center of the label on the x-axis.
<code>smlab</code>	A label for the summary measure (printed at top of figure).
<code>smlab.pos</code>	A numeric specifying the center of the label for the summary measure.
<code>xlim</code>	The x limits (min,max) of the plot, or the character "s" to produce symmetric forest plots.
<code>allstudies</code>	A logical indicating whether studies with inestimable treatment effects should be plotted.
<code>weight</code>	A character string indicating which type of plotting symbols is to be used for individual treatment estimates. One of missing (see Details), "same", "fixed", or "random", can be abbreviated. Plot symbols have the same size for all studies or represent study weights from fixed effect or random effects model.
<code>pscale</code>	A numeric giving scaling factor for probabilities for objects of class <code>metaprop</code> .
<code>ref</code>	A numerical giving the reference value to be plotted as a line in the forest plot. No reference line is plotted if argument <code>ref</code> is equal to NA.
<code>layout</code>	A character string specifying the layout of the forest plot (see Details).
<code>leftcols</code>	A character vector specifying (additional) columns to be plotted on the left side of the forest plot or a logical value (see Details).
<code>rightcols</code>	A character vector specifying (additional) columns to be plotted on the right side of the forest plot or a logical value (see Details).
<code>leftlabs</code>	A character vector specifying labels for (additional) columns on left side of the forest plot (see Details).
<code>rightlabs</code>	A character vector specifying labels for (additional) columns on right side of the forest plot (see Details).
<code>lab.e</code>	Label to be used for experimental group in table heading.
<code>lab.c</code>	Label to be used for control group in table heading.

<code>lab.e.attach.to.col</code>	A character specifying the column name where label <code>lab.e</code> should be attached to in table heading.
<code>lab.c.attach.to.col</code>	A character specifying the column name where label <code>lab.c</code> should be attached to in table heading.
<code>label.left</code>	Graph label on left side of forest plot.
<code>label.right</code>	Graph label on right side of forest plot.
<code>lab.NA</code>	A character string to label missing values.
<code>lab.NA.effect</code>	A character string to label missing values in individual treatment estimates and confidence intervals.
<code>lwd</code>	The line width, see par .
<code>at</code>	The points at which tick-marks are to be drawn, see grid.xaxis .
<code>label</code>	A logical value indicating whether to draw the labels on the tick marks, or an expression or character vector which specify the labels to use. See grid.xaxis .
<code>col.i</code>	The colour for individual study results and confidence limits.
<code>col.i.inside.square</code>	The colour for individual study results and confidence limits if confidence limits are completely within squares.
<code>col.square</code>	The colour for squares reflecting study's weight in the meta-analysis.
<code>col.square.lines</code>	The colour for the outer lines of squares reflecting study's weight in the meta-analysis.
<code>col.diamond</code>	The colour of diamonds representing the results for fixed effect and random effects models.
<code>col.diamond.fixed</code>	The colour of diamonds for fixed effect estimates.
<code>col.diamond.random</code>	The colour of diamonds for random effects estimates.
<code>col.diamond.lines</code>	The colour of the outer lines of diamonds representing the results for fixed effect and random effects models.
<code>col.diamond.fixed.lines</code>	The colour of the outer lines of diamond for fixed effect estimate.
<code>col.diamond.random.lines</code>	The colour of the outer lines of diamond for random effects estimate.
<code>col.predict</code>	Background colour of prediction interval.
<code>col.predict.lines</code>	Colour of outer lines of prediction interval.
<code>col.by</code>	The colour to print information on subgroups.
<code>print.I2</code>	A logical value indicating whether to print the value of the I-squared statistic.
<code>print.I2.ci</code>	A logical value indicating whether to print the confidence interval of the I-squared statistic.

<code>print.tau2</code>	A logical value indicating whether to print the value of the between-study variance tau-squared.
<code>print.Q</code>	A logical value indicating whether to print the value of the heterogeneity statistic Q.
<code>print.pval.Q</code>	A logical value indicating whether to print the p-value of the heterogeneity statistic Q.
<code>hetstat</code>	A logical value indicating whether to print results for heterogeneity measures at all.
<code>overall.hetstat</code>	A logical value indicating whether to print results for heterogeneity measures for overall treatment comparisons. This argument is useful in combination with subgroup analyses (list object <code>byvar</code>) if heterogeneity statistics should only be printed on group level.
<code>hetlab</code>	Label printed in front of results for heterogeneity measures.
<code>text.I2</code>	Label for I-squared statistic.
<code>text.tau2</code>	Label for between-study variance tau-squared.
<code>test.overall</code>	A logical value indicating whether to print results of test for overall effect.
<code>test.overall.fixed</code>	A logical value indicating whether to print results of test for overall effect (based on fixed effect model).
<code>test.overall.random</code>	A logical value indicating whether to print results of test for overall effect (based on random effects model).
<code>label.test.overall.fixed</code>	Label printed in front of results of test for overall effect (based on fixed effect model).
<code>label.test.overall.random</code>	Label printed in front of results of test for overall effect (based on random effects model).
<code>test.subgroup</code>	A logical value indicating whether to print results of test for subgroup differences.
<code>test.subgroup.fixed</code>	A logical value indicating whether to print results of test for subgroup differences (based on fixed effect model).
<code>test.subgroup.random</code>	A logical value indicating whether to print results of test for subgroup differences (based on random effects model).
<code>label.test.subgroup.fixed</code>	Label printed in front of results of test for subgroup differences (based on fixed effect model).
<code>label.test.subgroup.random</code>	Label printed in front of results of test for subgroup differences (based on random effects model).
<code>print.Q.subgroup</code>	A logical value indicating whether to print the value of the heterogeneity statistic Q (test for subgroup differences).

<code>fontsize</code>	The size of text (in points), see gpar .
<code>fs.heading</code>	The size of text for column headings, see gpar .
<code>fs.fixed</code>	The size of text for results of fixed effect model, see gpar .
<code>fs.random</code>	The size of text for results of random effects model, see gpar .
<code>fs.predict</code>	The size of text for results of prediction interval, see gpar .
<code>fs.study</code>	The size of text for results of individual studies, see gpar .
<code>fs.fixed.labels</code>	The size of text for label of fixed effect model, see gpar .
<code>fs.random.labels</code>	The size of text for label of random effects model, see gpar .
<code>fs.predict.labels</code>	The size of text for label of prediction interval, see gpar .
<code>fs.study.labels</code>	The size of text for labels of individual studies, see gpar .
<code>fs.hetstat</code>	The size of text for heterogeneity measures, see gpar .
<code>fs.test.overall</code>	The size of text of test for overall effect, see gpar .
<code>fs.test.subgroup</code>	The size of text of test of subgroup differences, see gpar .
<code>fs.axis</code>	The size of text on x-axis, see gpar .
<code>fs.smlab</code>	The size of text of label for summary measure, see gpar .
<code>fs.xlab</code>	The size of text of label on x-axis, see gpar .
<code>fs.lr</code>	The size of text of label on left and right side of forest plot, see gpar .
<code>ff.heading</code>	The fontface for column headings, see gpar .
<code>ff.fixed</code>	The fontface of text for results of fixed effect model, see gpar .
<code>ff.random</code>	The fontface of text for results of random effects model, see gpar .
<code>ff.predict</code>	The fontface of text for results of prediction interval, see gpar .
<code>ff.study</code>	The fontface of text for results of individual studies, see gpar .
<code>ff.fixed.labels</code>	The fontface of text for label of fixed effect model, see gpar .
<code>ff.random.labels</code>	The fontface of text for label of random effects model, see gpar .
<code>ff.predict.labels</code>	The fontface of text for label of prediction interval, see gpar .
<code>ff.study.labels</code>	The fontface of text for labels of individual studies, see gpar .
<code>ff.hetstat</code>	The fontface of text for heterogeneity measures, see gpar .
<code>ff.test.overall</code>	The fontface of text of test for overall effect, see gpar .
<code>ff.test.subgroup</code>	The fontface of text for test of subgroup differences, see gpar .

<code>ff.axis</code>	The fontface of text on x-axis, see gpar .
<code>ff.smlab</code>	The fontface of text of label for summary measure, see gpar .
<code>ff.xlab</code>	The fontface of text of label on x-axis, see gpar .
<code>ff.lr</code>	The fontface of text of label on left and right side of forest plot, see gpar .
<code>squaresize</code>	A numeric used to increase or decrease the size of squares in the forest plot.
<code>plotwidth</code>	A unit object specifying width of the forest plot.
<code>colgap</code>	A unit object specifying gap between columns printed on left and right side of forest plot.
<code>colgap.left</code>	A unit object specifying gap between columns printed on left side of forest plot.
<code>colgap.right</code>	A unit object specifying gap between columns printed on right side of forest plot.
<code>colgap.forest</code>	A unit object specifying gap between column adjacent to forest plot and the forest plot.
<code>colgap.forest.left</code>	A unit object specifying gap between column on the left side of forest plot and the forest plot.
<code>colgap.forest.right</code>	A unit object specifying gap between column on the right side of forest plot and the forest plot.
<code>just</code>	Justification of text in all columns but columns with study labels and additional variables (possible values: "left", "right", "center").
<code>just.studlab</code>	Justification of text for study labels (possible values: "left", "right", "center").
<code>just.addcols</code>	Justification of text for additional columns (possible values: "left", "right", "center").
<code>addspace</code>	A logical value indicating whether additional space (i.e. a blank row) is printed above and below study results.
<code>new</code>	A logical value indicating whether a new figure should be printed in an existing graphics window.
<code>backtransf</code>	A logical indicating whether results should be back transformed in forest plots. If <code>backtransf=TRUE</code> , results for <code>sm="OR"</code> are presented as odds ratios rather than log odds ratios and results for <code>sm="ZCOR"</code> are presented as correlations rather than Fisher's z transformed correlations, for example.
<code>digits</code>	Minimal number of significant digits for treatment effects, see <code>print.default</code> .
<code>digits.se</code>	Minimal number of significant digits for standard errors, see <code>print.default</code> .
<code>digits.tau2</code>	Minimal number of significant digits for between-study variance, see <code>print.default</code> .
<code>digits.pval</code>	Minimal number of significant digits for p-value of overall treatment effect, see <code>print.default</code> .
<code>digits.pval.Q</code>	Minimal number of significant digits for p-value of heterogeneity test, see <code>print.default</code> .
<code>digits.Q</code>	Minimal number of significant digits for heterogeneity statistic Q, see <code>print.default</code> .
<code>digits.I2</code>	Minimal number of significant digits for I-squared statistic, see <code>print.default</code> .
<code>...</code>	Additional graphical arguments (ignored at the moment).

Details

A forest plot, also called confidence interval plot, is drawn in the active graphics window. Subgroup analyses are conducted and displayed in the plot if `byvar` is not missing.

The forest function is based on the grid graphics system. In order to print the forest plot, (i) resize the graphics window, (ii) either use `dev.copy2eps` or `dev.copy2pdf`.

Result of a test for overall effect or subgroup differences are printed if argument `test.overall.fixed`, `test.overall.random`, `test.subgroup.fixed`, or `test.subgroup.random` is TRUE; by default, these arguments are FALSE. R function `settings.meta` can be used to change this default for the entire R session by setting argument `test.overall=TRUE` or `test.subgroup=TRUE`.

Information from object `x` is utilised if argument `weight` is missing. Weights from the fixed effect model are used (`weight="fixed"`) if argument `x$comb.fixed` is TRUE; weights from the random effects model are used (`weight="random"`) if argument `x$comb.random` is TRUE and `x$comb.fixed` is FALSE.

The arguments `leftcols` and `rightcols` can be used to specify columns which are plotted on the left and right side of the forest plot, respectively. If argument `rightcols` is FALSE, no columns will be plotted on the right side. By default, i.e. if arguments `leftcols` and `rightcols` are NULL and `layout="meta"`, the following default columns will be plotted.

Additional settings	Default for argument <code>rightcols</code>
—	<code>c("effect", "ci")</code>
<code>comb.fixed=TRUE & comb.random=FALSE</code>	<code>c("effect", "ci", "w.fixed")</code>
<code>comb.fixed=FALSE & comb.random=TRUE</code>	<code>c("effect", "ci", "w.random")</code>
<code>comb.fixed=TRUE & comb.random=TRUE</code>	<code>c("effect", "ci", "w.fixed", "w.random")</code>

By default, estimated treatment effect and corresponding confidence interval will be printed. Depending on arguments `comb.fixed` and `comb.random`, weights of the fixed effect and/or random effects model will be given too. For an object of class `metacum` or `metainf` only the estimated treatment effect with confidence interval are plotted.

Depending on the class of the meta-analysis object a different set of columns is printed on the left side of a forest plot.

Object type	Default for argument <code>leftcols</code>
<code>metabin</code>	<code>c("studlab", "event.e", "n.e", "event.c", "n.c")</code>
<code>metacont</code>	<code>c("studlab", "n.e", "mean.e", "sd.e", "n.c", "mean.c", "sd.c")</code>
<code>metacor</code>	<code>c("studlab", "n")</code>
<code>metagen</code>	<code>c("studlab", "TE", "seTE")</code>
<code>metainc</code>	<code>c("studlab", "event.e", "time.e", "event.c", "time.c")</code>
<code>metaprop</code>	<code>c("studlab", "event", "n")</code>
<code>metacum</code>	<code>c("studlab")</code>
<code>metainf</code>	<code>c("studlab")</code>

The arguments `leftlabs` and `rightlabs` can be used to specify column headings which are plotted on left and right side of the forest plot, respectively. For certain columns predefined labels exist. If the arguments `leftlabs` and `rightlabs` are NULL, the following default labels will be used:

Column	<code>studlab</code>	TE	seTE	n.e	n.c	n
--------	----------------------	----	------	-----	-----	---

Label	"Study"	"TE"	"seTE"	"Total"	"Total"	"Total"
Column	event.e	event.c	event	mean.e	mean.c	
Label	"Events"	"Events"	"Events"	"Mean"	"Mean"	
Column	sd.e	sd.c	time.e	time.c		
Label	"SD"	"SD"	"Time"	"Time"		
Column	effect	ci	w.fixed	w.random		
Label	x\$sm	x\$level-CI	"W(fixed)"	"W(random)"		

For additional columns the column name will be used as label. It is possible to only provide labels for new columns (see Examples). Otherwise the length of `leftlabs` and `rightlabs` must be the same as the number of printed columns. The value NA can be used to specify columns using the default labels (see Example).

If argument `layout="revman5"` (and arguments `leftcols` and `rightcols` are NULL) all columns mentioned above will be printed on the left side of the forest plot.

If arguments `lab.e` and `lab.c` are NULL, "Experimental" and "Control" are used as labels for experimental and control group, respectively.

The arguments `pscale` can be used to rescale proportions for objects of class `metaprop`, e.g. `pscale=100` means that proportions are expressed per 100 observations. This is useful in situations with (very) low proportions. For `pscale=100`, column heading and x-axis label are changed to "Prop (in %)" and "Proportion (in %)", respectively.

A prediction interval for treatment effect of a new study (Higgins et al., 2009) is given in the forest plot if arguments `prediction` and `comb.random` are TRUE. For graphical presentation of prediction intervals the approach by Guddat et al. (2012) is used.

Note, in R package `meta`, version 3.0-0 the following arguments have been removed from R function `forest.meta`: `byvar`, `level`, `level.comb`, `level.predict`. This functionality is now provided by R function `update.meta` (or directly in R functions `metabin`, `metacont`, `metagen`, `metacor`, and `metaprop`).

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Guddat C, Grouven U, Bender R, Skipka G (2012), A note on the graphical presentation of prediction intervals in random-effects meta-analyses. *Systematic Reviews*, **1**, 34.

Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137-159.

See Also

[metabin](#), [metacont](#), [metagen](#)

Examples

```
data(0lkin95)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=c(41,47,51,59),
                 sm="RR", method="I",
                 studlab=paste(author, year))

#
# Do (symmetric) forest plot
#
forest(meta1)

#
# Forest plot specifying argument xlim
#
forest(meta1, xlim=c(0.01, 10))

#
# Add prediction interval to forest plot
#
forest(meta1, prediction=TRUE)

#
# Print results of test for overall effect
#
forest(meta1, test.overall.fixed=TRUE, test.overall.random=TRUE)

#
# Forest plot with 'classic' layout used in
# R package meta, version < 1.6-0
#
forest(meta1, col.square="black", hetstat=FALSE)

#
# Layout of forest plot similar to RevMan 5
#
forest(meta1, layout="revman5", comb.random=FALSE)

#
# Change set of columns printed on left side
# of forest plot
#
forest(meta1, comb.random=FALSE,
       leftcols="studlab")
```

```
#
# Do not print columns on right side of forest plot
#
forest(meta1, rightcols=FALSE)

#
# Change study label to "Author"
#
forest(meta1, comb.random=FALSE,
        leftlabs=c("Author", NA, NA, NA, NA))

#
# Just give effect estimate and 95% confidence interval
# on right side of forest plot
#
forest(meta1, rightcols=c("effect", "ci"))

#
# 1. Change order of columns on left side
# 2. Attach labels to columns 'event.e' and 'event.c'
#    instead of columns 'n.e' and 'n.c'
#
forest(meta1,
        leftcols=c("studlab", "n.e", "event.e", "n.c", "event.c"),
        lab.e.attach.to.col="event.e",
        lab.c.attach.to.col="event.c")

#
# Specify column labels only for newly created variables
# 'year' and 'author' (which are part of dataset Olkin95)
#
forest(meta1,
        leftcols=c("studlab", "event.e", "n.e", "event.c", "n.c",
                  "author", "year"),
        leftlabs=c("Author", "Year of Publ"))

#
# Center text in all columns
#
forest(meta1,
        leftcols=c("studlab", "event.e", "n.e", "event.c", "n.c",
                  "author", "year"),
        leftlabs=c("Author", "Year of Publ"), hetstat=FALSE,
        just="center", just.addcols="center", just.studlab="center")
## Not run:
#
# Same result
```

```
#
forest(meta1,
      leftcols=c("studlab", "event.e", "n.e", "event.c", "n.c",
                "author", "year"),
      leftlabs=c("Author", "Year of Publ"), hetstat=FALSE,
      just="c", just.addcols="c", just.studlab="c")

## End(Not run)

#
# Change some fontsizes and fontfaces
#
forest(meta1,
      fs.study=10, ff.study="italic",
      fs.study.label=11, ff.study.label="bold",
      fs.axis=5, ff.axis="italic",
      ff.smlab="bold.italic",
      ff.fixed="plain", ff.hetstat="plain")

#
# Change some colours
#
forest(meta1,
      col.diamond="green", col.diamond.lines="red",
      col.i=c("green", "blue", "red", "orange"),
      col.square="pink", col.square.lines="black")

#
# Sort by weight in fixed effect model
#
forest(meta1, sortvar=1/w.fixed, comb.random=FALSE)

#
# Sort by decreasing weight in fixed effect model
#
forest(meta1, sortvar=-1/w.fixed, comb.random=FALSE)

#
# Sort by size of treatment effect
#
forest(meta1, sortvar=TE, comb.random=FALSE)

#
# Sort by size of treatment effect
#
forest(meta1, sortvar=-TE, comb.random=FALSE)
```

```

#
# Sort by decreasing year of publication
#
forest(meta1, sortvar=-year, comb.random=FALSE)

#
# Sort studies by decreasing treatment effect within year subgroups
#
meta2 <- update(meta1, byvar=ifelse(year < 1987, "Before 1987", "1987 and later"),
  print.byvar=FALSE)
forest(meta2,
  sortvar=-TE, comb.random=FALSE)

#
# Print results of test for subgroup differences (random effects model)
#
forest(meta2,
  sortvar=-TE, comb.fixed=FALSE,
  test.subgroup.random=TRUE)

```

funnel

Plot to assess funnel plot asymmetry

Description

Draw a funnel plot or radial plot (also called Galbraith plot) to assess funnel plot asymmetry in the active graphics window.

A contour-enhanced funnel plot can be produced for assessing causes of funnel plot asymmetry.

Usage

```
funnel(x, ...)
```

```
radial(x, ...)
```

```
## Default S3 method:
```

```
funnel(x, y,
  xlim=NULL, ylim=NULL, xlab=NULL, ylab=NULL,
  comb.fixed=FALSE, comb.random=FALSE,
  axes=TRUE,
  pch=21, text=NULL, cex=1,
  lty.fixed=2, lty.random=9,
  lwd=1, lwd.fixed=lwd, lwd.random=lwd,
  col="black", bg="darkgray",
  col.fixed="black", col.random="black",
  log="", yaxis="se", sm="",
  contour.levels=NULL, col.contour,
```

```

    ref=ifelse(backtransf & is.relative.effect(sm), 1, 0),
    level=NULL,
    studlab=FALSE, cex.studlab=0.8, backtransf=TRUE, ...)

## S3 method for class 'meta'
funnel(x,
       xlim=NULL, ylim=NULL, xlab=NULL, ylab=NULL,
       comb.fixed=x$comb.fixed, comb.random=x$comb.random,
       axes=TRUE,
       pch=if (!inherits(x, "trimfill")) 21 else ifelse(x$trimfill, 1, 21),
       text=NULL, cex=1,
       lty.fixed=2, lty.random=9,
       lwd=1, lwd.fixed=lwd, lwd.random=lwd,
       col="black", bg="darkgray",
       col.fixed="black", col.random="black",
       log="", yaxis="se",
       contour.levels=NULL, col.contour,
       ref=ifelse(backtransf & is.relative.effect(x$sm), 1, 0),
       level=x$level,
       studlab=FALSE, cex.studlab=0.8, backtransf=x$backtransf, ...)

## Default S3 method:
radial(x, y, xlim=NULL, ylim=NULL,
       xlab="Inverse of standard error",
       ylab="Standardised treatment effect (z-score)",
       comb.fixed=TRUE, axes=TRUE,
       pch=1, text=NULL, cex=1, col=NULL,
       level=NULL, ...)

## S3 method for class 'meta'
radial(x, xlim=NULL, ylim=NULL,
       xlab="Inverse of standard error",
       ylab="Standardised treatment effect (z-score)",
       comb.fixed=TRUE, axes=TRUE,
       pch=1, text=NULL, cex=1, col=NULL,
       level=NULL, ...)

```

Arguments

<code>x</code>	An object of class <code>meta</code> , or estimated treatment effect in individual studies.
<code>y</code>	Standard error of estimated treatment effect.
<code>xlim</code>	The x limits (min,max) of the plot.
<code>ylim</code>	The y limits (min,max) of the plot.
<code>xlab</code>	A label for the x-axis.
<code>ylab</code>	A label for the y-axis.
<code>comb.fixed</code>	A logical indicating whether the pooled fixed effect estimate should be plotted.

<code>comb.random</code>	A logical indicating whether the pooled random effects estimate should be plotted.
<code>axes</code>	A logical indicating whether axes should be drawn on the plot.
<code>pch</code>	The plotting symbol used for individual studies.
<code>text</code>	A character vector specifying the text to be used instead of plotting symbol.
<code>cex</code>	The magnification to be used for plotting symbol.
<code>lty.fixed</code>	Line type (pooled fixed effect estimate).
<code>lty.random</code>	Line type (pooled random effects estimate).
<code>col</code>	A vector with colour of plotting symbols.
<code>bg</code>	A vector with background colour of plotting symbols (only used if <code>pch</code> in 21:25).
<code>col.fixed</code>	Color of line representign fixed effect estimate.
<code>col.random</code>	Color of line representign random effects estimate.
<code>lwd</code>	The line width for confidence intervals (if <code>level</code> is not NULL).
<code>lwd.fixed</code>	The line width for fixed effect estimate (if <code>comb.fixed</code> is not NULL).
<code>lwd.random</code>	The line width for random effects estimate (if <code>comb.random</code> is not NULL).
<code>log</code>	A character string which contains "x" if the x-axis is to be logarithmic, "y" if the y-axis is to be logarithmic and "xy" or "yx" if both axes are to be logarithmic (applies only to function <code>funnel</code>).
<code>yaxis</code>	A character string indicating which type of weights are to be used. Either "se", "invvar", "invse", or "size" (applies only to function <code>funnel</code>).
<code>sm</code>	A character string indicating underlying summary measure, e.g., "RD", "RR", "OR", "ASD", "MD", "SMD" (applies only to function <code>funnel</code>).
<code>contour.levels</code>	A numeric vector specifying contour levels to produce contour-enhanced funnel plot.
<code>col.contour</code>	Colour of contours.
<code>ref</code>	Reference value (null effect) used to produce contour-enhanced funnel plot.
<code>level</code>	The confidence level utilised in the plot. For the funnel plot, confidence limits are not drawn if <code>yaxis="size"</code> .
<code>studlab</code>	A logical indicating whether study labels should be printed in the graph. A vector with study labels can also be provided (must be of same length as <code>x\$TE</code> then).
<code>cex.studlab</code>	Size of study labels.
<code>backtransf</code>	A logical indicating whether results for relative summary measures (argument <code>sm</code> equal to "OR", "RR", "HR", or "IRR") should be back transformed in funnel plots. If <code>backtransf=TRUE</code> , results for <code>sm="OR"</code> are printed as odds ratios rather than log odds ratios, for example.
<code>...</code>	Graphical arguments as in <code>par</code> may also be passed as arguments.

Details

A funnel plot or radial plot, also called Galbraith plot, is drawn in the active graphics window. If `comb.fixed` is `TRUE`, the pooled estimate of the fixed effect model is plotted. If `level` is not `NULL`, the corresponding confidence limits are drawn.

In the funnel plot, if `yaxis` is `"se"`, the standard error of the treatment estimates is plotted on the y-axis which is likely to be the best choice (Sterne & Egger, 2001). Other possible choices for `yaxis` are `"invvar"` (inverse of the variance), `"invse"` (inverse of the standard error), and `"size"` (study size).

For `yaxis!="size"`, contour-enhanced funnel plots can be produced (Peters et al., 2008) by specifying the contour levels (argument `contour.levels`). By default (argument `col.contour` missing), suitable gray levels will be used to distinguish the contours. Different colours can be chosen by argument `col.contour`.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>, Petra Graham <pgraham@efs.mq.edu.au>

References

Galbraith RF (1988a), Graphical display of estimates having differing standard errors. *Technometrics*, **30**, 271–281.

Galbraith RF (1988b), A note on graphical presentation of estimated odds ratios from several clinical trials. *Statistics in Medicine*, **7**, 889–894.

Light RJ & Pillemer DB (1984), *Summing Up. The Science of Reviewing Research*. Cambridge: Harvard University Press.

Peters JL, Sutton AJ, Jones DR, Abrams KR, Rushton L (2008), Contour-enhanced meta-analysis funnel plots help distinguish publication bias from other causes of asymmetry. *Journal of Clinical Epidemiology*, **61**, 991–996.

Sterne JAC & Egger M (2001), Funnel plots for detecting bias in meta-analysis: Guidelines on choice of axis. *Journal of Clinical Epidemiology*, **54**, 1046–1055.

See Also

[metabias](#), [metabin](#), [metagen](#)

Examples

```
data(0lkin95)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=c(41,47,51,59),
                 studlab=paste(author, year),
                 sm="RR", method="I")

#
# Radial plot
#
radial(meta1, level=0.95)
```

```

oldpar <- par(mfrow=c(2, 2))

#
# Funnel plots
#
funnel(meta1)
#
# Same result as code above:
#
funnel(meta1$TE, meta1$seTE, sm="RR",
       comb.fixed=TRUE, level=0.95)
#
# Funnel plot with confidence intervals,
# fixed effect estimate and contours
#
cc <- funnel(meta1, comb.fixed=TRUE,
            level=0.95, contour=c(0.9, 0.95, 0.99))$col.contour
legend(0.05, 0.05,
      c("0.1 > p > 0.05", "0.05 > p > 0.01", "< 0.01"), fill=cc)
#
# Contour-enhanced funnel plot with user-chosen colours
#
funnel(meta1, comb.fixed=TRUE,
      level=0.95, contour=c(0.9, 0.95, 0.99),
      col.contour=c("darkgreen", "green", "lightgreen"),
      lwd=2, cex=2, pch=16, studlab=TRUE, cex.studlab=1.25)
legend(0.05, 0.05,
      c("0.1 > p > 0.05", "0.05 > p > 0.01", "< 0.01"),
      fill=c("darkgreen", "green", "lightgreen"))

par(oldpar)

```

labbe

L'Abbe plot for meta-analysis with binary outcomes

Description

Draw a L'Abbé plot for meta-analysis with binary outcomes.

Usage

```

labbe(x, ...)

## Default S3 method:
labbe(x, y,
      xlim, ylim,
      xlab=NULL, ylab=NULL,
      TE.fixed, TE.random,

```

```

comb.fixed=FALSE, comb.random=FALSE,
axes=TRUE,
pch=21, text=NULL, cex=1,
col="black", bg="lightgray",
lwd=1, lwd.fixed=lwd, lwd.random=lwd,
lty.fixed=2, lty.random=9,
sm=NULL, weight,
studlab=FALSE, cex.studlab=0.8,
...)

## S3 method for class 'metabin'
labbe(x,
      xlim, ylim,
      xlab=NULL, ylab=NULL,
      TE.fixed=x$TE.fixed,
      TE.random=x$TE.random,
      comb.fixed=x$comb.fixed,
      comb.random=x$comb.random,
      axes=TRUE,
      pch=21, text=NULL, cex=1,
      col="black", bg="lightgray",
      lwd=1, lwd.fixed=lwd, lwd.random=lwd,
      lty.fixed=2, lty.random=9,
      sm=x$sm, weight,
      studlab=FALSE, cex.studlab=0.8, ...)

```

Arguments

x	The x coordinates of points of the L'Abbé plot. Alternatively, an object of class metabin.
y	The y coordinates of the L'Abbé plot, optional if x is an appropriate structure.
xlim	The x limits (min,max) of the plot.
ylim	The y limits (min,max) of the plot.
xlab	A label for the x-axis.
ylab	A label for the y-axis.
TE.fixed	A numeric or vector specifying combined fixed effect estimate(s).
TE.random	A numeric or vector specifying combined random effects estimate(s).
comb.fixed	A logical indicating whether the pooled fixed effect estimate should be plotted.
comb.random	A logical indicating whether the pooled random effects estimate should be plotted.
axes	A logical indicating whether axes should be drawn on the plot.
pch	The plotting symbol used for individual studies.
text	A character vector specifying the text to be used instead of plotting symbol.
cex	The magnification to be used for plotting symbol.
col	A vector with colour of plotting symbols.

<code>bg</code>	A vector with background colour of plotting symbols (only used if <code>pch</code> in 21:25).
<code>lwd</code>	The line width.
<code>lwd.fixed</code>	The line width for fixed effect estimate (if <code>comb.fixed</code> is not NULL or FALSE).
<code>lwd.random</code>	The line width for random effects estimate (if <code>comb.random</code> is not NULL or FALSE).
<code>lty.fixed</code>	Line type (pooled fixed effect estimate).
<code>lty.random</code>	Line type (pooled random effects estimate).
<code>sm</code>	A character string indicating underlying summary measure, i.e., "RD", "RR", "OR".
<code>weight</code>	Either a numeric vector specifying relative sizes of plotting symbols or a character string indicating which type of plotting symbols is to be used for individual treatment estimates. One of missing (see Details), "same", "fixed", or "random", can be abbreviated. Plot symbols have the same size for all studies or represent study weights from fixed effect or random effects model.
<code>studlab</code>	A logical indicating whether study labels should be printed in the graph. A vector with study labels can also be provided (must be of same length as <code>x\$event</code> if then).
<code>cex.studlab</code>	Size of study labels.
<code>...</code>	Graphical arguments as in <code>par</code> may also be passed as arguments.

Details

A L'Abbé plot is a scatter plot with the risk in the control group on the x-axis and the risk in the experimental group on the y-axis (L'Abbé et al., 1987). It can be used to evaluate heterogeneity in meta-analysis. Furthermore, this plot can aid to choose a summary measure (odds ratio, risk ratio, risk difference) that will result in more consistent results.

If `comb.fixed` is TRUE, the pooled estimate of the fixed effect model is plotted as a line. If `comb.random` is TRUE, the pooled estimate of the random effects model is plotted as a line.

Information from object `x` is utilised if argument `weight` is missing. Weights from the fixed effect model are used (`weight="fixed"`) if argument `x$comb.fixed` is TRUE; weights from the random effects model are used (`weight="random"`) if argument `x$comb.random` is TRUE and `x$comb.fixed` is FALSE.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

L'Abbé KA, Detsky AS, O'Rourke K (1987), Meta-analysis in clinical research. *Annals of Internal Medicine*, **107**, 224–233.

See Also

[metabin](#)

Examples

```

data(0lkin95)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95,
                 studlab=paste(author, year),
                 sm="RR", method="I")

#
# L'Abbe plot
#
labbe(meta1)

```

metabias	<i>Test for funnel plot asymmetry</i>
----------	---------------------------------------

Description

Test for funnel plot asymmetry, based on rank correlation or linear regression method.

Usage

```

metabias(x, ...)

## S3 method for class 'meta'
metabias(x, method.bias=x$method.bias,
         plotit=FALSE, correct=FALSE, k.min=10, ...)

## Default S3 method:
metabias(x, seTE, method.bias="linreg",
         plotit=FALSE, correct=FALSE, k.min=10, ...)

```

Arguments

x	An object of class meta or estimated treatment effect in individual studies.
seTE	Standard error of estimated treatment effect (mandatory if x not of class meta).
method.bias	A character string indicating which test is to be used. Either "rank", "linreg", "mm", "count", "score", or "peters", can be abbreviated.
plotit	A logical indicating whether a plot should be produced for method.bias "rank", "linreg", "mm", or "score".
correct	A logical indicating whether a continuity corrected statistic is used for rank correlation methods "rank" and "count".
k.min	Minimum number of studies to perform test for funnel plot asymmetry.
...	Additional arguments (ignored at the moment).

Details

Following recommendations by Sterne et al. (2011), by default, a test for funnel plot asymmetry is only conducted if the number of studies is ten or larger (argument `k.min=10`). This behaviour can be changed by setting a smaller value for argument `k.min`. Note, the minimum number of studies is three.

If argument `method.bias` is "rank", the test statistic is based on the rank correlation between standardised treatment estimates and variance estimates of estimated treatment effects; Kendall's tau is used as correlation measure (Begg & Mazumdar, 1994). The test statistic follows a standard normal distribution. By default (if `correct` is FALSE), no continuity correction is utilised (Kendall & Gibbons, 1990).

If argument `method.bias` is "linreg", the test statistic is based on a weighted linear regression of the treatment effect on its standard error (Egger et al., 1997). The test statistic follows a t distribution with `number of studies - 2` degrees of freedom.

If argument `method.bias` is "mm", the test statistic is based on a weighted linear regression of the treatment effect on its standard error using the method of moments estimator for the additive between-study variance component (method 3a in Thompson, Sharp, 1999). The test statistic follows a t distribution with `number of studies - 2` degrees of freedom.

If argument `method.bias` is "count", the test statistic is based on the rank correlation between a standardised cell frequency and the inverse of the variance of the cell frequency; Kendall's tau is used as correlation measure (Schwarzer et al., 2007). The test statistic follows a standard normal distribution. By default (if `correct` is FALSE), no continuity correction is utilised (Kendall & Gibbons, 1990).

If argument `method.bias` is "score", the test statistic is based on a weighted linear regression utilising efficient score and score variance (Harbord et al., 2006). The test statistic follows a t distribution with `number of studies - 2` degrees of freedom.

If argument `method.bias` is "peters", the test statistic is based on a weighted linear regression of the treatment effect on the inverse of the total sample size using the variance of the average event rate as weights (Peters et al., 2006). The test statistic follows a t distribution with `number of studies - 2` degrees of freedom.

In order to calculate an arcsine test for funnel plot asymmetry (Ruecker et al., 2008), one has to use the `metabin` function with argument `sm="ASD"` as input to the `metabias` command. The three arcsine tests described in Ruecker et al. (2008) can be calculated by setting `method.bias` to "rank", "linreg" and "mm", respectively.

If argument `method.bias` is missing, the Harbord test (`method.bias="score"`) is used for the odds ratio as effect measure and the Egger test (`method.bias="linreg"`) for other effect measures (Sterne et al., 2011).

No test for funnel plot asymmetry is conducted in meta-analyses with subgroups.

Value

A list with class "htest" containing the following components if a test for funnel plot asymmetry is conducted:

<code>estimate</code>	The estimated degree of funnel plot asymmetry, with name "ks" or "bias" corresponding to the method employed, i.e., rank correlation or regression method.
-----------------------	--

statistic	The value of the test statistic.
parameters	The degrees of freedom of the test statistic in the case that it follows a t distribution.
p.value	The p-value for the test.
alternative	A character string describing the alternative hypothesis.
method	A character string indicating what type of test was used.
data.name	A character string giving the names of the data.
title	Title of Cochrane review.
complab	Comparison label.
outclab	Outcome label.
version	Version of R package meta used to create object.

Or a list with the following elements if test is not conducted due to the number of studies:

k	Number of studies in meta-analysis.
k.min	Minimum number of studies to perform test for funnel plot asymmetry.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Begg CB & Mazumdar M (1994), Operating characteristics of a rank correlation test for publication bias. *Biometrics*, **50**, 1088–1101.
- Egger M, Smith GD, Schneider M & Minder C (1997), Bias in meta-analysis detected by a simple, graphical test. *British Medical Journal*, **315**, 629–634.
- Harbord RM, Egger M & Sterne J (2006), A modified test for small-study effects in meta-analyses of controlled trials with binary endpoints. *Statistics in Medicine*, **25**, 3443–3457.
- Kendall M & Gibbons JD (1990), *Rank Correlation Methods*. London: Edward Arnold.
- Peters JL, Sutton AJ, Jones DR, Abrams KR & Rushton L (2006), Comparison of two methods to detect publication bias in meta-analysis. *Journal of the American Medical Association*, **295**, 676–680.
- Ruecker G, Schwarzer G, Carpenter JR (2008) Arcsine test for publication bias in meta-analyses with binary outcomes. *Statistics in Medicine*, **27**, 746–763.
- Schwarzer G, Antes G & Schumacher M (2007), A test for publication bias in meta-analysis with sparse binary data. *Statistics in Medicine*, **26**, 721–733.
- Sterne, JAC et al. (2011), Recommendations for Examining and Interpreting Funnel Plot Asymmetry in Meta-Analyses of Randomised Controlled Trials. *BMJ (Clinical research ed.)*, **343**, 1, doi: 10.1136/bmj.d4002 .
- Thompson SG & Sharp, SJ (1999), Explaining heterogeneity in meta-analysis: A comparison of methods, *Statistics in Medicine*, **18**, 2693–2708.

See Also

[funnel](#), [funnel.meta](#), [metabin](#), [metacont](#), [metagen](#)

Examples

```
data(0lkin95)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=1:10,
                 sm="RR", method="I")

metabias(meta1)
metabias(meta1, plotit=TRUE)

metabias(meta1, method.bias="rank")
metabias(meta1, method.bias="rank", correct=TRUE)

metabias(meta1, method.bias="count")

metabias(meta1, method.bias="linreg")$p.value

#
# Arcsine test (based on linear regression):
#
meta1.as <- metabin(event.e, n.e, event.c, n.c,
                   data=0lkin95, subset=1:10,
                   sm="ASD", method="I")
metabias(meta1.as)
#
# Same result (using function metabias.default):
#
metabias(meta1.as$TE, meta1.as$seTE)

#
# No test for funnel plot asymmetry calculated:
#
meta2 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=1:5,
                 sm="RR", method="I")
metabias(meta2)

meta3 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=1:2,
                 sm="RR", method="I")
metabias(meta3)

# Test for funnel plot asymmetry calculated
# (use of argument k.min):
#
metabias(meta2, k.min=5)
```

metabin

*Meta-analysis of binary outcome data***Description**

Calculation of fixed and random effects estimates (risk ratio, odds ratio, risk difference or arcsine difference) for meta-analyses with binary outcome data. Mantel-Haenszel, inverse variance and Peto method are available for pooling.

Usage

```
metabin(event.e, n.e, event.c, n.c, studlab,
        data=NULL, subset=NULL,
        method=ifelse(tau.common, "Inverse", .settings$method),
        sm=
        ifelse(!is.na(charmatch(method, c("Peto", "peto"),
                                   nomatch = NA)),
              "OR", .settings$smbin),
        incr=.settings$incr, allincr=.settings$allincr,
        addincr=.settings$addincr, allstudies=.settings$allstudies,
        MH.exact=.settings$MH.exact, RR.cochrane=.settings$RR.cochrane,
        level=.settings$level, level.comb=.settings$level.comb,
        comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
        hakn=.settings$hakn,
        method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
        tau.common=.settings$tau.common,
        prediction=.settings$prediction, level.predict=.settings$level.predict,
        method.bias=ifelse(sm=="OR", "score", .settings$method.bias),
        backtransf=.settings$backtransf,
        title=.settings$title, complab=.settings$complab, outclab="",
        label.e=.settings$label.e, label.c=.settings$label.c,
        label.left=.settings$label.left, label.right=.settings$label.right,
        byvar, bylab, print.byvar=.settings$print.byvar,
        print.CMH=.settings$print.CMH,
        keepdata=.settings$keepdata,
        warn=.settings$warn)
```

Arguments

<code>event.e</code>	Number of events in experimental group.
<code>n.e</code>	Number of observations in experimental group.
<code>event.c</code>	Number of events in control group.
<code>n.c</code>	Number of observations in control group.
<code>studlab</code>	An optional vector with study labels.
<code>data</code>	An optional data frame containing the study information, i.e., <code>event.e</code> , <code>n.e</code> , <code>event.c</code> , and <code>n.c</code> .

subset	An optional vector specifying a subset of studies to be used.
method	A character string indicating which method is to be used for pooling of studies. One of "Inverse", "MH", or "Peto", can be abbreviated.
sm	A character string indicating which summary measure ("RR", "OR", "RD", or "ASD") is to be used for pooling of studies, see Details.
incr	Could be either a numerical value which is added to each cell frequency for studies with a zero cell count or the character string "TACC" which stands for treatment arm continuity correction, see Details.
allincr	A logical indicating if incr is added to each cell frequency of all studies if at least one study has a zero cell count. If FALSE (default), incr is added only to each cell frequency of studies with a zero cell count.
addincr	A logical indicating if incr is added to each cell frequency of all studies irrespective of zero cell counts.
allstudies	A logical indicating if studies with zero or all events in both groups are to be included in the meta-analysis (applies only if sm is equal to "RR" or "OR").
MH.exact	A logical indicating if incr is not to be added to all cell frequencies for studies with a zero cell count to calculate the pooled estimate based on the Mantel-Haenszel method.
RR.cochrane	A logical indicating if 2*incr instead of 1*incr is to be added to n.e and n.c in the calculation of the risk ratio (i.e., sm="RR") for studies with a zero cell. This is used in RevMan 5, the Cochrane Collaboration's program for preparing and maintaining Cochrane reviews.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .
TE.tau	Overall treatment effect used to estimate the between-study variance τ^2 .
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
method.bias	A character string indicating which test for funnel plot asymmetry is to be used. Either "rank", "linreg", "mm", "count", "score", or "peters", can be abbreviated. See function metabias
backtransf	A logical indicating whether results for odds ratio (sm="OR") and risk ratio (sm="RR") should be back transformed in printouts and plots. If TRUE (default), results will be presented as odds ratios and risk ratios; otherwise log odds ratios and log risk ratios will be shown.

<code>title</code>	Title of meta-analysis / systematic review.
<code>complab</code>	Comparison label.
<code>outclab</code>	Outcome label.
<code>label.e</code>	Label for experimental group.
<code>label.c</code>	Label for control group.
<code>label.left</code>	Graph label on left side of forest plot.
<code>label.right</code>	Graph label on right side of forest plot.
<code>byvar</code>	An optional vector containing grouping information (must be of same length as <code>event.e</code>).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>print.CMH</code>	A logical indicating whether result of the Cochran-Mantel-Haenszel test for overall effect should be printed.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.
<code>warn</code>	A logical indicating whether warnings should be printed (e.g., if <code>incr</code> is added to studies with zero cell frequencies).

Details

Treatment estimates and standard errors are calculated for each study. The following measures of treatment effect are available:

- Risk ratio (`sm="RR"`)
- Odds ratio (`sm="OR"`)
- Risk difference (`sm="RD"`)
- Arcsine difference (`sm="ASD"`)

For studies with a zero cell count, by default, 0.5 is added to all cell frequencies of these studies; if `incr` is "TACC" a treatment arm continuity correction is used instead (Sweeting et al., 2004; Diamond et al., 2007). Treatment estimates and standard errors are only calculated for studies with zero or all events in both groups if `allstudies` is TRUE.

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the `settings.meta` function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if argument `comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function `print.meta` will not print results for the random effects model if `comb.random=FALSE`.

By default, both fixed effect and random effects models are considered (see arguments `comb.fixed` and `comb.random`). If `method` is "MH" (default), the Mantel-Haenszel method is used to calculate the fixed effect estimate; if `method` is "Inverse", inverse variance weighting is used for pooling; finally, if `method` is "Peto", the Peto method is used for pooling. By default, the DerSimonian-Laird

estimate (1986) is used in the random effects model (`method.tau="DL"`). For the Peto method, Peto's log odds ratio, i.e. $(O-E)/V$ and its standard error $\sqrt{1/V}$ with $O-E$ and V denoting "Observed minus Expected" and "V", are utilised in the random effects model. Accordingly, results of a random effects model using `sm="Peto"` can be (slightly) different to results from a random effects model using `sm="MH"` or `sm="Inverse"`.

For the Mantel-Haenszel method, by default (if `MH.exact` is `FALSE`), 0.5 is added to all cell frequencies of a study with a zero cell count in the calculation of the pooled risk ratio or odds ratio as well as the estimation of the variance of the pooled risk difference, risk ratio or odds ratio. This approach is also used in other software, e.g. RevMan 5 and the Stata procedure `metan`. According to Fleiss (in Cooper & Hedges, 1994), there is no need to add 0.5 to a cell frequency of zero to calculate the Mantel-Haenszel estimate and he advocates the exact method (`MH.exact=TRUE`). Note, the estimate based on the exact method is not defined if the number of events is zero in all studies either in the experimental or control group.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are `TRUE`.

R function `update.meta` can be used to redo the meta-analysis of an existing `metabin` object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `paulemandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison at lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)
- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metabin", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`event.e`, `n.e`, `event.c`, `n.c`, `studlab`,

`sm`, `method`, `incr`, `allincr`, `addincr`,

`allstudies`, `MH.exact`, `RR.cochrane`, `warn`,

level, level.comb, comb.fixed, comb.random,
 hakn, method.tau, tau.preset, TE.tau, method.bias,
 tau.common, title, complab, outclab,
 label.e, label.c, label.left, label.right,
 byvar, bylab, print.byvar
 As defined above.
 TE, seTE Estimated treatment effect and standard error of individual studies.
 lower, upper Lower and upper confidence interval limits for individual studies.
 zval, pval z-value and p-value for test of treatment effect for individual studies.
 w.fixed, w.random
 Weight of individual studies (in fixed and random effects model).
 TE.fixed, seTE.fixed
 Estimated overall treatment effect and standard error (fixed effect model).
 lower.fixed, upper.fixed
 Lower and upper confidence interval limits (fixed effect model).
 zval.fixed, pval.fixed
 z-value and p-value for test of overall treatment effect (fixed effect model).
 TE.random, seTE.random
 Estimated overall treatment effect and standard error (random effects model).
 lower.random, upper.random
 Lower and upper confidence interval limits (random effects model).
 zval.random, pval.random
 z-value or t-value and corresponding p-value for test of overall treatment effect
 (random effects model).
 prediction, level.predict
 As defined above.
 seTE.predict Standard error utilised for prediction interval.
 lower.predict, upper.predict
 Lower and upper limits of prediction interval.
 k Number of studies combined in meta-analysis.
 Q Heterogeneity statistic Q.
 df.Q Degrees of freedom for heterogeneity statistic.
 tau Square-root of between-study variance.
 se.tau Standard error of square-root of between-study variance.
 C Scaling factor utilised internally to calculate common tau-squared across sub-
 groups.
 Q.CMH Cochran-Mantel-Haenszel test statistic for overall effect.
 incr.e, incr.c Increment added to cells in the experimental and control group, respectively.

sparse	Logical flag indicating if any study included in meta-analysis has any zero cell frequencies.
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.
lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.
w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.
df.hakn.w	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if byvar is not missing and hakn=TRUE.
n.harmonic.mean.w	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if byvar is not missing.
event.e.w	Number of events in experimental group in subgroups - if byvar is not missing.
n.e.w	Number of observations in experimental group in subgroups - if byvar is not missing.
event.c.w	Number of events in control group in subgroups - if byvar is not missing.
n.c.w	Number of observations in control group in subgroups - if byvar is not missing.
k.w	Number of studies combined within subgroups - if byvar is not missing.
k.all.w	Number of all studies in subgroups - if byvar is not missing.
Q.w	Heterogeneity statistics within subgroups - if byvar is not missing.
Q.w.fixed	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.w.random	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing (only calculated if argument tau.common is TRUE).

df.Q.w	Degrees of freedom for test of overall within subgroups heterogeneity - if byvar is not missing.
Q.b.fixed	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.b.random	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing.
df.Q.b	Degrees of freedom for test of overall between subgroups heterogeneity - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups - if byvar is not missing.
H.w	Heterogeneity statistic H within subgroups - if byvar is not missing.
lower.H.w, upper.H.w	Lower and upper confidence limti for heterogeneity statistic H within subgroups - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups - if byvar is not missing.
lower.I2.w, upper.I2.w	Lower and upper confidence limti for heterogeneity statistic I2 within subgroups - if byvar is not missing.
keepdata	As defined above.
data	Original data (set) used in function call (if keepdata=TRUE).
subset	Information on subset of original data used in meta-analysis (if keepdata=TRUE).
call	Function call.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.
- Diamond GA, Bax L, Kaul S (2007), Uncertain Effects of Rosiglitazone on the Risk for Myocardial Infarction and Cardiovascular Death. *Annals of Internal Medicine*, **147**, 578–581.
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Fleiss JL (1993), The statistical basis of meta-analysis. *Statistical Methods in Medical Research*, **2**, 121–145.
- Greenland S & Robins JM (1985), Estimation of a common effect parameter from sparse follow-up data. *Biometrics*, **41**, 55–68.
- Hartung J & Knapp G (2001), A Refined Method for the Meta-analysis of Controlled Clinical Trials with Binary Outcome. *Statistics in Medicine*, **20**, 3875–89.

Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.

Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–710, doi: 10.1002/sim.1482 .

Review Manager (RevMan) [Computer program]. Version 5.3. Copenhagen: The Nordic Cochrane Centre, The Cochrane Collaboration, 2014.

Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.

Pettigrew HM, Gart JJ, Thomas DG (1986), The bias and higher cumulants of the logarithm of a binomial variate. *Biometrika*, **73**, 425–435.

Ruecker G, Schwarzer G, Carpenter JR (2008) Arcsine test for publication bias in meta-analyses with binary outcomes. *Statistics in Medicine*, **27**, 746–763.

StataCorp. 2011. *Stata Statistical Software: Release 12*. College Station, TX: StataCorp LP.

Sweeting MJ, Sutton AJ, Lambert PC (2004), What to add to nothing? Use and avoidance of continuity corrections in meta-analysis of sparse data. *Statistics in Medicine*, **23**, 1351–1375.

Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[update.meta](#), [funnel](#), [metabias](#), [metacont](#), [metagen](#), [print.meta](#)

Examples

```
metabin(10, 20, 15, 20, sm="OR", warn=FALSE)

#
# Different results:
#
metabin(0, 10, 0, 10, sm="OR", warn=FALSE)
metabin(0, 10, 0, 10, sm="OR", allstudies=TRUE, warn=FALSE)

data(0lkin95)

meta1 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=c(41,47,51,59),
                 sm="RR", method="I")
summary(meta1)
funnel(meta1)

meta2 <- metabin(event.e, n.e, event.c, n.c,
                 data=0lkin95, subset=0lkin95$year<1970,
                 sm="RR", method="I")
summary(meta2)
forest(meta2)

meta3 <- update(meta2, sm="OR")
```

```
summary(meta3)

meta4 <- update(meta3, method="MH")
summary(meta4)

meta5 <- update(meta3, method="Peto")
summary(meta5)
```

 metacont

Meta-analysis of continuous outcome data

Description

Calculation of fixed and random effects estimates for meta-analyses with continuous outcome data; inverse variance weighting is used for pooling.

Usage

```
metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, studlab,
         data=NULL, subset=NULL,
         sm=.settings$smcont, pooledvar=.settings$pooledvar,
         method.smd=.settings$method.smd, sd.glass=.settings$sd.glass,
         exact.smd=.settings$exact.smd,
         level=.settings$level, level.comb=.settings$level.comb,
         comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
         hakn=.settings$hakn,
         method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
         tau.common=.settings$tau.common,
         prediction=.settings$prediction, level.predict=.settings$level.predict,
         method.bias=.settings$method.bias,
         title=.settings$title, complab=.settings$complab, outclab="",
         label.e=.settings$label.e, label.c=.settings$label.c,
         label.left=.settings$label.left, label.right=.settings$label.right,
         byvar, bylab, print.byvar=.settings$print.byvar,
         keepdata=.settings$keepdata,
         warn=.settings$warn)
```

Arguments

n.e	Number of observations in experimental group.
mean.e	Estimated mean in experimental group.
sd.e	Standard deviation in experimental group.
n.c	Number of observations in control group.
mean.c	Estimated mean in control group.
sd.c	Standard deviation in control group.
studlab	An optional vector with study labels.

data	An optional data frame containing the study information.
subset	An optional vector specifying a subset of studies to be used.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .
TE.tau	Overall treatment effect used to estimate the between-study variance tau-squared.
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
method.bias	A character string indicating which test is to be used. Either "rank", "linreg", or "mm", can be abbreviated. See function metabias
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
label.e	Label for experimental group.
label.c	Label for control group.
label.left	Graph label on left side of forest plot.
label.right	Graph label on right side of forest plot.
sm	A character string indicating which summary measure ("MD" or "SMD") is to be used for pooling of studies.
pooledvar	A logical indicating if a pooled variance should be used for the mean difference (sm="MD").
method.smd	A character string indicating which method is used to estimate the standardised mean difference (sm="SMD"). Either "Hedges" for Hedges' g (default), "Cohen" for Cohen's d, or "Glass" for Glass' delta, can be abbreviated.
sd.glass	A character string indicating which standard deviation is used in the denominator for Glass' method to estimate the standardised mean difference. Either "control" using the standard deviation in the control group (sd.c) or "experimental" using the standard deviation in the experimental group (sd.e), can be abbreviated.
exact.smd	A logical indicating whether exact formulae should be used in estimation of the standardised mean difference and its standard error (see Details).

<code>byvar</code>	An optional vector containing grouping information (must be of same length as <code>n.e</code>).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.
<code>warn</code>	A logical indicating whether warnings should be printed (e.g., if studies are excluded from meta-analysis due to zero standard deviations).

Details

Calculation of fixed and random effects estimates for meta-analyses with continuous outcome data; inverse variance weighting is used for pooling. By default, the DerSimonian-Laird estimate (1986) is used in the random effects model (`method.tau="DL"`).

Two different types of summary measures are available for continuous outcomes: the mean difference (`argument sm="MD"`) and the standardised mean difference (`sm="SMD"`). For the standardised mean difference three methods are implemented:

- Hedges' *g* (default, `method.smd="Hedges"`) - see Hedges (1981)
- Cohen's *d* (`method.smd="Cohen"`) - see Cohen (1988)
- Glass' delta (`method.smd="Glass"`) - see Glass (1976)

Hedges (1981) calculated the exact bias in Cohen's *d* which is a ratio of gamma distributions with the degrees of freedom, i.e. total sample size minus two, as argument. By default (`argument exact.smd=FALSE`), an accurate approximation of this bias provided in Hedges (1981) is utilised for Hedges' *g* as well as its standard error; these approximations are also used in RevMan 5. Following Borenstein et al. (2009) these approximations are not used in the estimation of Cohen's *d*. White and Thomas (2005) argued that approximations are unnecessary with modern software and accordingly promote to use the exact formulae; this is possible using `argument exact.smd=TRUE`. For Hedges' *g* the exact formulae are used to calculate the standardised mean difference as well as the standard error; for Cohen's *d* the exact formula is only used to calculate the standard error. In typical applications (with sample sizes above 10), the differences between using the exact formulae and the approximation will be minimal.

For Glass' delta, by default (`argument sd.glass="control"`), the standard deviation in the control group (`sd.c`) is used in the denominator of the standard mean difference. The standard deviation in the experimental group (`sd.e`) can be used by specifying `sd.glass="experimental"`.

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the [settings.meta](#) function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if `argument comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function [print.meta](#) will not print results for the random effects model if `comb.random=FALSE`.

The function `metagen` is called internally to calculate individual and overall treatment estimates and standard errors.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are TRUE.

R function `update.meta` can be used to redo the meta-analysis of an existing metacont object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `pau1emandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison at lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)
- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metacont", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`n.e`, `mean.e`, `sd.e`,

`n.c`, `mean.c`, `sd.c`,

`studlab`, `sm`, `level`, `level.comb`,

`comb.fixed`, `comb.random`,

`pooledvar`, `method.smd`, `sd.glass`,

`hakn`, `method.tau`, `tau.preset`, `TE.tau`, `method.bias`,

`tau.common`, `title`, `complab`, `outclab`,

`label.e`, `label.c`, `label.left`, `label.right`,

`byvar`, `bylab`, `print.byvar`, `warn`

As defined above.

`TE`, `seTE` Estimated treatment effect and standard error of individual studies.

lower, upper	Lower and upper confidence interval limits for individual studies.
zval, pval	z-value and p-value for test of treatment effect for individual studies.
w.fixed, w.random	Weight of individual studies (in fixed and random effects model).
TE.fixed, seTE.fixed	Estimated overall treatment effect and standard error (fixed effect model).
lower.fixed, upper.fixed	Lower and upper confidence interval limits (fixed effect model).
zval.fixed, pval.fixed	z-value and p-value for test of overall treatment effect (fixed effect model).
TE.random, seTE.random	Estimated overall treatment effect and standard error (random effects model).
lower.random, upper.random	Lower and upper confidence interval limits (random effects model).
zval.random, pval.random	z-value or t-value and corresponding p-value for test of overall treatment effect (random effects model).
prediction, level.predict	As defined above.
seTE.predict	Standard error utilised for prediction interval.
lower.predict, upper.predict	Lower and upper limits of prediction interval.
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
method	Pooling method: "Inverse".
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.

lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.
w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.
df.hakn.w	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if byvar is not missing and hakn=TRUE.
n.harmonic.mean.w	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if byvar is not missing.
n.e.w	Number of observations in experimental group in subgroups - if byvar is not missing.
n.c.w	Number of observations in control group in subgroups - if byvar is not missing.
k.w	Number of studies combined within subgroups - if byvar is not missing.
k.all.w	Number of all studies in subgroups - if byvar is not missing.
Q.w	Heterogeneity statistics within subgroups - if byvar is not missing.
Q.w.fixed	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.w.random	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing (only calculated if argument tau.common is TRUE).
df.Q.w	Degrees of freedom for test of overall within subgroups heterogeneity - if byvar is not missing.
Q.b.fixed	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.b.random	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing.
df.Q.b	Degrees of freedom for test of overall between subgroups heterogeneity - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups - if byvar is not missing.
H.w	Heterogeneity statistic H within subgroups - if byvar is not missing.
lower.H.w, upper.H.w	Lower and upper confidence limits for heterogeneity statistic H within subgroups - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups - if byvar is not missing.

lower.I2.w, upper.I2.w	Lower and upper confidence limti for heterogeneity statistic I2 within subgroups - if byvar is not missing.
keepdata	As defined above.
data	Original data (set) used in function call (if keepdata=TRUE).
subset	Information on subset of original data used in meta-analysis (if keepdata=TRUE).
call	Function call.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Borenstein et al. (2009), *Introduction to Meta-Analysis*, Chichester: Wiley.
- Cohen J (1988), *Statistical Power Analysis for the Behavioral Sciences* (second ed.). Lawrence Erlbaum Associates.
- Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Glass G (1976), Primary, secondary, and meta-analysis of research. *Educational Researcher*, **5**, 3–8.
- Hartung J & Knapp G (2001), On tests of the overall treatment effect in meta-analysis with normally distributed responses. *Statistics in Medicine*, **20**, 1771–82. doi: 10.1002/sim.791 .
- Hedges LV (1981), Distribution theory for Glass’s estimator of effect size and related estimators. *Journal of Educational and Behavioral Statistics*, **6**, 107–28.
- Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.
- Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–710, doi: 10.1002/sim.1482 .
- Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.
- Review Manager (RevMan)* [Computer program]. Version 5.3. Copenhagen: The Nordic Cochrane Centre, The Cochrane Collaboration, 2014.
- Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.
- White IR, Thomas J (2005), Standardized mean differences in individually-randomized and cluster-randomized trials, with applications to meta-analysis. *Clinical Trials*, **2**, 141–51.

See Also

[update.meta](#), [metabin](#), [metagen](#)

Examples

```

data(Fleiss93cont)
meta1 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, data=Fleiss93cont, sm="SMD")
meta1
forest(meta1)

meta2 <- metacont(Fleiss93cont$n.e, Fleiss93cont$mean.e,
                  Fleiss93cont$sd.e,
                  Fleiss93cont$n.c, Fleiss93cont$mean.c,
                  Fleiss93cont$sd.c,
                  sm="SMD")
meta2

data(amlodipine)
meta3 <- metacont(n.amlo, mean.amlo, sqrt(var.amlo),
                  n.plac, mean.plac, sqrt(var.plac),
                  data=amlodipine, studlab=study)
summary(meta3)

# Use pooled variance
#
meta4 <- metacont(n.amlo, mean.amlo, sqrt(var.amlo),
                  n.plac, mean.plac, sqrt(var.plac),
                  data=amlodipine, studlab=study,
                  pooledvar=TRUE)
summary(meta4)

# Use Cohen's d instead of Hedges' g as effect measure
#
meta5 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, data=Fleiss93cont,
                  sm="SMD", method.smd="Cohen")
meta5

# Use Glass' delta instead of Hedges' g as effect measure
#
meta6 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, data=Fleiss93cont,
                  sm="SMD", method.smd="Glass")
meta6

# Use Glass' delta based on the standard deviation in the experimental group
#
meta7 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c, data=Fleiss93cont,
                  sm="SMD", method.smd="Glass", sd.glass="experimental")
meta7

# Calculate Hedges' g based on exact formulae
#
update(meta1, exact.smd=TRUE)

```

Description

Calculation of fixed and random effects estimates for meta-analyses with correlations; inverse variance weighting is used for pooling.

Usage

```
metacor(cor, n, studlab,
        data=NULL, subset=NULL,
        sm=.settings$smcor,
        level=.settings$level, level.comb=.settings$level.comb,
        comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
        hakn=.settings$hakn,
        method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
        tau.common=.settings$tau.common,
        prediction=.settings$prediction, level.predict=.settings$level.predict,
        method.bias=.settings$method.bias,
        backtransf=.settings$backtransf,
        title=.settings$title, complab=.settings$complab, outclab="",
        byvar, bylab, print.byvar=.settings$print.byvar,
        keepdata=.settings$keepdata
    )
```

Arguments

cor	Correlation.
n	Number of observations.
studlab	An optional vector with study labels.
data	An optional data frame containing the study information, i.e., cor and n.
subset	An optional vector specifying a subset of studies to be used.
sm	A character string indicating which summary measure ("ZCOR" or "COR") is to be used for pooling of studies.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .

<code>TE.tau</code>	Overall treatment effect used to estimate the between-study variance tau-squared.
<code>tau.common</code>	A logical indicating whether tau-squared should be the same across subgroups.
<code>method.bias</code>	A character string indicating which test is to be used. Either "rank", "linreg", or "mm", can be abbreviated. See function metabias
<code>backtransf</code>	A logical indicating whether results for Fisher's z transformed correlations (<code>sm="ZCOR"</code>) should be back transformed in printouts and plots. If TRUE (default), results will be presented as correlations; otherwise Fisher's z transformed correlations will be shown.
<code>title</code>	Title of meta-analysis / systematic review.
<code>complab</code>	Comparison label.
<code>outclab</code>	Outcome label.
<code>byvar</code>	An optional vector containing grouping information (must be of same length as <code>event.e</code>).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.

Details

Fixed effect and random effects meta-analysis of correlations based either on Fisher's z transformation of correlations (`sm="ZCOR"`) or direct combination of correlations (`sm="COR"`) (see Cooper et al., p264-5 and p273-4). By default, the DerSimonian-Laird estimate (1986) is used in the random effects model (`method.tau="DL"`).

Only few statisticians would advocate the use of untransformed correlations unless sample sizes are very large (see Cooper et al., p265). The artificial example given below shows that the smallest study gets the largest weight if correlations are combined directly because the correlation is closest to 1.

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the [settings.meta](#) function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if argument `comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function [print.meta](#) will not print results for the random effects model if `comb.random=FALSE`.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are TRUE.

R function [update.meta](#) can be used to redo the meta-analysis of an existing `metacor` object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `pau1emandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison@lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)
- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metacor", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`cor`, `n`, `studlab`,

`sm`, `level`, `level.comb`,

`comb.fixed`, `comb.random`,

`hakn`, `method.tau`, `tau.preset`, `TE.tau`, `method.bias`,

`tau.common`, `title`, `complab`, `outclab`,

`byvar`, `bylab`, `print.byvar`

As defined above.

`TE`, `seTE` Either Fisher's z transformation of correlations (`sm="ZCOR"`) or correlations (`sm="COR"`) for individual studies.

`lower`, `upper` Lower and upper confidence interval limits for individual studies.

`zval`, `pval` z-value and p-value for test of treatment effect for individual studies.

`w.fixed`, `w.random`

Weight of individual studies (in fixed and random effects model).

`TE.fixed`, `seTE.fixed`

Estimated overall effect (Fisher's z transformation of correlation or correlation) and its standard error (fixed effect model).

`lower.fixed`, `upper.fixed`

Lower and upper confidence interval limits (fixed effect model).

`zval.fixed`, `pval.fixed`

z-value and p-value for test of overall effect (fixed effect model).

TE.random, seTE.random	Estimated overall effect (Fisher's z transformation of correlation or correlation) and its standard error (random effects model).
lower.random, upper.random	Lower and upper confidence interval limits (random effects model).
zval.random, pval.random	z-value or t-value and corresponding p-value for test of overall effect (random effects model).
prediction, level.predict	As defined above.
seTE.predict	Standard error utilised for prediction interval.
lower.predict, upper.predict	Lower and upper limits of prediction interval.
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic Q.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
method	A character string indicating method used for pooling: "Inverse"
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.
lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.
w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.

<code>df.hakn.w</code>	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if <code>byvar</code> is not missing and <code>hakn=TRUE</code> .
<code>n.harmonic.mean.w</code>	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if <code>byvar</code> is not missing.
<code>n.w</code>	Number of observations in subgroups - if <code>byvar</code> is not missing.
<code>k.w</code>	Number of studies combined within subgroups - if <code>byvar</code> is not missing.
<code>k.all.w</code>	Number of all studies in subgroups - if <code>byvar</code> is not missing.
<code>Q.w</code>	Heterogeneity statistics within subgroups - if <code>byvar</code> is not missing.
<code>Q.w.fixed</code>	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if <code>byvar</code> is not missing.
<code>Q.w.random</code>	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if <code>byvar</code> is not missing (only calculated if argument <code>tau.common</code> is <code>TRUE</code>).
<code>df.Q.w</code>	Degrees of freedom for test of overall within subgroups heterogeneity - if <code>byvar</code> is not missing.
<code>Q.b.fixed</code>	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if <code>byvar</code> is not missing.
<code>Q.b.random</code>	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if <code>byvar</code> is not missing.
<code>df.Q.b</code>	Degrees of freedom for test of overall between subgroups heterogeneity - if <code>byvar</code> is not missing.
<code>tau.w</code>	Square-root of between-study variance within subgroups - if <code>byvar</code> is not missing.
<code>C.w</code>	Scaling factor utilised internally to calculate common tau-squared across subgroups - if <code>byvar</code> is not missing.
<code>H.w</code>	Heterogeneity statistic H within subgroups - if <code>byvar</code> is not missing.
<code>lower.H.w, upper.H.w</code>	Lower and upper confidence limti for heterogeneity statistic H within subgroups - if <code>byvar</code> is not missing.
<code>I2.w</code>	Heterogeneity statistic I2 within subgroups - if <code>byvar</code> is not missing.
<code>lower.I2.w, upper.I2.w</code>	Lower and upper confidence limti for heterogeneity statistic I2 within subgroups - if <code>byvar</code> is not missing.
<code>keepdata</code>	As defined above.
<code>data</code>	Original data (set) used in function call (if <code>keepdata=TRUE</code>).
<code>subset</code>	Information on subset of original data used in meta-analysis (if <code>keepdata=TRUE</code>).
<code>call</code>	Function call.
<code>version</code>	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Cooper H, Hedges LV, Valentine JC (2009), *The Handbook of Research Synthesis and Meta-Analysis*, 2nd Edition. New York: Russell Sage Foundation.
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.
- Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–710, doi: 10.1002/sim.1482 .
- Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.
- Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[update.meta](#), [metacont](#), [metagen](#), [print.meta](#)

Examples

```
m1 <- metacor(c(0.85, 0.7, 0.95), c(20, 40, 10))

#
# Print correlations (back transformed from Fisher's z transformation)
#
m1

#
# Print Fisher's z transformed correlations
#
print(m1, backtransf=FALSE)

#
# Forest plot with back transformed correlations
#
forest(m1)

#
# Forest plot with Fisher's z transformed correlations
#
forest(m1, backtransf=FALSE)

m2 <- update(m1, sm="cor")
m2
# Identical forest plots (as back transformation is the identity transformation)
# forest(m2)
# forest(m2, backtransf=FALSE)
```

metacr

*Meta-analysis of outcome data from Cochrane review***Description**

Wrapper function to perform meta-analysis for a single outcome of a Cochrane Intervention review.

Usage

```
metacr(x, comp.no=1, outcome.no=1,
       method, sm,
       level=.settings$level, level.comb=.settings$level.comb,
       comb.fixed, comb.random,
       hakn=FALSE,
       method.tau="DL",
       tau.common=FALSE,
       prediction=.settings$prediction, level.predict=.settings$level.predict,
       swap.events, logscale,
       backtransf=.settings$backtransf,
       title, complab, outclab,
       keepdata=.settings$keepdata, warn=FALSE)
```

Arguments

x	An object of class <code>rm5</code> created by R function <code>read.rm5</code> .
comp.no	Comparison number.
outcome.no	Outcome number.
method	A character string indicating which method is to be used for pooling of studies. One of "Inverse", "MH", or "Peto", can be abbreviated.
sm	A character string indicating which summary measure ("RR", "OR", "RD", "ASD", "HR", "MD", or "SMD") is to be used for pooling of studies.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
prediction	A logical indicating whether a prediction interval should be printed.

level.predict	The level used to calculate prediction interval for a new study.
swap.events	A logical indicating whether events and non-events should be interchanged.
logscale	A logical indicating whether effect estimates are entered on log-scale.
backtransf	A logical indicating whether results should be back transformed in printouts and plots. If backtransf=TRUE (default), results for sm="OR" are printed as odds ratios rather than log odds ratios and results for sm="ZCOR" are printed as correlations rather than Fisher's z transformed correlations, for example.
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
keepdata	A logical indicating whether original data (set) should be kept in meta object.
warn	A logical indicating whether warnings should be printed (e.g., if incr is added to studies with zero cell frequencies).

Details

Cochrane Intervention reviews are based on the comparison of two interventions. Each Cochrane Intervention review can have a variable number of comparisons. For each comparison, a variable number of outcomes can be define. For each outcome, a seperate meta-analysis is conducted. Review Manager 5 (RevMan 5) is the current software used for preparing and maintaining Cochrane Reviews (<http://tech.cochrane.org/revman/>).

This wrapper function can be used to perform meta-analysis for a single outcome of a Cochrane Intervention review. Internally, R functions `metabin`, `metacont`, and `metagen` are called - depending on the definition of the outcome in RevMan 5.

Value

An object of class "meta" and "metabin", "metacont", or "metagen" depending on outcome type utilised in Cochrane Intervention review for selected outcome.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Review Manager (RevMan) [Computer program]. Version 5.3. Copenhagen: The Nordic Cochrane Centre, The Cochrane Collaboration, 2014.

See Also

[metabin](#), [metacont](#), [metagen](#), [read.rm5](#)

Examples

```

# Locate export data file "Fleiss93_CR.csv"
# in sub-directory of package "meta"
#
filename <- system.file("data/Fleiss93_CR.csv.gz", package = "meta")
#
Fleiss93_CR <- read.rm5(filename)

# Same result as R command example(Fleiss93):
#
metacr(Fleiss93_CR)

# Same result as R command example(Fleiss93cont):
#
metacr(Fleiss93_CR, 1, 2)

forest(metacr(Fleiss93_CR, 1, 2))

# Change summary measure to RR
#
m1 <- metacr(Fleiss93_CR)
update(m1, sm="RR")

```

metacum

Cumulative meta-analysis

Description

Performs a cumulative meta-analysis.

Usage

```
metacum(x, pooled, sortvar)
```

Arguments

x	An object of class meta.
pooled	A character string indicating whether a fixed effect or random effects model is used for pooling. Either missing (see Details), "fixed", or "random", can be abbreviated.
sortvar	An optional vector used to sort the individual studies (must be of same length as x\$TE).

Details

A cumulative meta-analysis is performed. Studies are included sequentially as defined by `sortvar`. Information from object `x` is utilised if argument `pooled` is missing. A fixed effect model is assumed (`pooled="fixed"`) if argument `x$comb.fixed` is TRUE; a random effects model is assumed (`pooled="random"`) if argument `x$comb.random` is TRUE and `x$comb.fixed` is FALSE.

Value

An object of class `c("metacum", "meta")` with corresponding `print`, `plot` function. The object is a list containing the following components:

<code>TE</code> , <code>seTE</code>	Estimated treatment effect and standard error of pooled estimate in cumulative meta-analyses.
<code>lower</code> , <code>upper</code>	Lower and upper confidence interval limits.
<code>studlab</code>	Study label describing addition of studies.
<code>p.value</code>	P-value for test of overall effect.
<code>w</code>	Sum of weights from fixed effect or random effects model.
<code>I2</code>	Heterogeneity statistic I ² .
<code>tau</code>	Square-root of between-study variance.
<code>df.hakn</code>	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if <code>hakn=TRUE</code>).
<code>sm</code>	Summary measure.
<code>method</code>	Method used for pooling.
<code>k</code>	Number of studies combined in meta-analysis.
<code>pooled</code>	As defined above.
<code>comb.fixed</code>	A logical indicating whether analysis is based on fixed effect model.
<code>comb.random</code>	A logical indicating whether analysis is based on random effects model.
<code>TE.fixed</code> , <code>seTE.fixed</code>	Value is NA.
<code>TE.random</code> , <code>seTE.random</code>	Value is NA.
<code>Q</code>	Value is NA.
<code>level.comb</code>	The level used to calculate confidence intervals for pooled estimates.
<code>hakn</code>	A logical indicating whether the method by Hartung and Knapp is used to adjust test statistics and confidence intervals.
<code>method.tau</code>	A character string indicating which method is used to estimate the between-study variance τ^2 .
<code>tau.preset</code>	Prespecified value for the square-root of the between-study variance τ^2 .
<code>TE.tau</code>	Overall treatment effect used to estimate the between-study variance τ^2 .
<code>n.harmonic.mean</code>	Harmonic mean of number of observations (for back transformation of Freeman-Tukey Double arcsine transformation).
<code>version</code>	Version of R package <code>meta</code> used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.

See Also

[metabin](#), [metacont](#), [print.meta](#)

Examples

```
data(Fleiss93)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                data=Fleiss93, studlab=study,
                sm="RR", method="I")

meta1

metacum(meta1)
metacum(meta1, pooled="random")

forest(metacum(meta1))
forest(metacum(meta1, pooled="random"))

metacum(meta1, sortvar=study)
metacum(meta1, sortvar=7:1)

meta2 <- update(meta1, title="Fleiss93 meta-analysis",
                backtransf=FALSE)

metacum(meta2)
```

metagen

Generic inverse variance meta-analysis

Description

Fixed and random effects meta-analysis based on estimates (e.g. log hazard ratios) and their standard errors; inverse variance weighting is used for pooling.

Usage

```
metagen(TE, seTE, studlab, data=NULL, subset=NULL, sm="",
        level=.settings$level, level.comb=.settings$level.comb,
        comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
        hakn=.settings$hakn,
        method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
```

```

tau.common=.settings$tau.common,
prediction=.settings$prediction, level.predict=.settings$level.predict,
method.bias=.settings$method.bias,
n.e=NULL, n.c=NULL,
backtransf=.settings$backtransf,
title=.settings$title, complab=.settings$complab, outclab="",
label.e=.settings$label.e, label.c=.settings$label.c,
label.left=.settings$label.left, label.right=.settings$label.right,
byvar, bylab, print.byvar=.settings$print.byvar,
keepdata=.settings$keepdata,
warn=.settings$warn)

```

Arguments

TE	Estimate of treatment effect.
seTE	Standard error of treatment estimate.
studlab	An optional vector with study labels.
data	An optional data frame containing the study information.
subset	An optional vector specifying a subset of studies to be used.
sm	A character string indicating underlying summary measure, e.g., "RD", "RR", "OR", "ASD", "MD", "SMD".
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
n.e	Number of observations in experimental group.
n.c	Number of observations in control group.
hakn	A logical indicating whether method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .
TE.tau	Overall treatment effect used to estimate the between-study variance tau-squared.
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
method.bias	A character string indicating which test is to be used. Either "rank", "linreg", or "mm", can be abbreviated. See function metabias
backtransf	A logical indicating whether results should be back transformed in printouts and plots. If backtransf=TRUE (default), results for sm="OR" are printed as odds ratios rather than log odds ratios and results for sm="ZCOR" are printed as correlations rather than Fisher's z transformed correlations, for example.

<code>title</code>	Title of meta-analysis / systematic review.
<code>complab</code>	Comparison label.
<code>outclab</code>	Outcome label.
<code>label.e</code>	Label for experimental group.
<code>label.c</code>	Label for control group.
<code>label.left</code>	Graph label on left side of forest plot.
<code>label.right</code>	Graph label on right side of forest plot.
<code>byvar</code>	An optional vector containing grouping information (must be of same length as TE).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.
<code>warn</code>	A logical indicating whether warnings should be printed (e.g., if studies are excluded from meta-analysis due to zero standard errors).

Details

Generic method for meta-analysis, only treatment estimates and their standard error are needed. The method is useful, e.g., for pooling of survival data (using log hazard ratio and standard errors as input). The inverse variance method is used for pooling. By default, the DerSimonian-Laird estimate (1986) is used in the random effects model (`method.tau="DL"`).

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the `settings.meta` function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if argument `comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function `print.meta` will not print results for the random effects model if `comb.random=FALSE`.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are TRUE.

R function `update.meta` can be used to redo the meta-analysis of an existing metagen object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `paulemandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison@lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)

- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metagen", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`TE`, `seTE`, `studlab`, `n.e`, `n.c`

`sm`, `level`, `level.comb`,

`comb.fixed`, `comb.random`,

`hakn`, `method.tau`, `tau.preset`, `TE.tau`, `method.bias`,

`tau.common`, `title`, `complab`, `outclab`,

`label.e`, `label.c`, `label.left`, `label.right`,

`byvar`, `bylab`, `print.byvar`, `warn`

As defined above.

`lower`, `upper` Lower and upper confidence interval limits for individual studies.

`zval`, `pval` z-value and p-value for test of treatment effect for individual studies.

`w.fixed`, `w.random`

Weight of individual studies (in fixed and random effects model).

`TE.fixed`, `seTE.fixed`

Estimated overall treatment effect and standard error (fixed effect model).

`lower.fixed`, `upper.fixed`

Lower and upper confidence interval limits (fixed effect model).

`zval.fixed`, `pval.fixed`

z-value and p-value for test of overall treatment effect (fixed effect model).

`TE.random`, `seTE.random`

Estimated overall treatment effect and standard error (random effects model).

`lower.random`, `upper.random`

Lower and upper confidence interval limits (random effects model).

`zval.random`, `pval.random`

z-value or t-value and corresponding p-value for test of overall treatment effect (random effects model).

prediction, level.predict	As defined above.
seTE.predict	Standard error utilised for prediction interval.
lower.predict, upper.predict	Lower and upper limits of prediction interval.
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic.
df.Q	Degrees of freedom for heterogeneity statistic.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
method	Pooling method: "Inverse".
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.
lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.
w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.
df.hakn.w	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if byvar is not missing and hakn=TRUE.
n.harmonic.mean.w	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if byvar is not missing.
n.e.w	Number of observations in experimental group in subgroups - if byvar is not missing.

n.c.w	Number of observations in control group in subgroups - if byvar is not missing.
k.w	Number of studies combined within subgroups - if byvar is not missing.
k.all.w	Number of all studies in subgroups - if byvar is not missing.
Q.w	Heterogeneity statistics within subgroups - if byvar is not missing.
Q.w.fixed	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.w.random	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing (only calculated if argument tau.common is TRUE).
df.Q.w	Degrees of freedom for test of overall within subgroups heterogeneity - if byvar is not missing.
Q.b.fixed	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.b.random	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing.
df.Q.b	Degrees of freedom for test of overall between subgroups heterogeneity - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups - if byvar is not missing.
H.w	Heterogeneity statistic H within subgroups - if byvar is not missing.
lower.H.w, upper.H.w	Lower and upper confidence limti for heterogeneity statistic H within subgroups - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups - if byvar is not missing.
lower.I2.w, upper.I2.w	Lower and upper confidence limti for heterogeneity statistic I2 within subgroups - if byvar is not missing.
keepdata	As defined above.
data	Original data (set) used in function call (if keepdata=TRUE).
subset	Information on subset of original data used in meta-analysis (if keepdata=TRUE).
call	Function call.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.
- Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–2710, doi: 10.1002/sim.1482 .
- Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.
- Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[update.meta](#), [metabin](#), [metacont](#), [print.meta](#)

Examples

```
data(Fleiss93)
meta1 <- metabin(event.e, n.e, event.c, n.c, data=Fleiss93, sm="RR", method="I")
meta1

#
# Identical results by using the following commands:
#
meta1
metagen(meta1$TE, meta1$seTE, sm="RR")

forest(metagen(meta1$TE, meta1$seTE, sm="RR"))

#
# Meta-analysis with prespecified between-study variance
#
summary(metagen(meta1$TE, meta1$seTE, sm="RR", tau.preset=sqrt(0.1)))

#
# Meta-analysis of survival data:
#
logHR <- log(c(0.95, 1.5))
selogHR <- c(0.25, 0.35)

metagen(logHR, selogHR, sm="HR")

#
```

```
# Paule-Mandel method to estimate between-study variance
# Data from Paule & Mandel (1982)
#
average <- c(27.044, 26.022, 26.340, 26.787, 26.796)
variance <- c(0.003, 0.076, 0.464, 0.003, 0.014)
#
summary(metagen(average, sqrt(variance), sm="MD", method.tau="PM"))
```

metainc

Meta-analysis of incidence rates

Description

Calculation of fixed and random effects estimates (incidence rate ratio or incidence rate difference) for meta-analyses with event counts. Mantel-Haenszel, Cochran, and inverse variance method are available for pooling.

Usage

```
metainc(event.e, time.e, event.c, time.c, studlab,
        data=NULL, subset=NULL, method="MH",
        sm=.settings$sminc,
        incr=.settings$incr, allincr=.settings$allincr,
        addincr=.settings$addincr,
        level=.settings$level, level.comb=.settings$level.comb,
        comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
        hakn=.settings$hakn,
        method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
        tau.common=.settings$tau.common,
        prediction=.settings$prediction, level.predict=.settings$level.predict,
        method.bias=.settings$method.bias,
        n.e=NULL, n.c=NULL,
        backtransf=.settings$backtransf,
        title=.settings$title, complab=.settings$complab, outclab="",
        label.e=.settings$label.e, label.c=.settings$label.c,
        label.left=.settings$label.left, label.right=.settings$label.right,
        byvar, bylab, print.byvar=.settings$print.byvar,
        keepdata=.settings$keepdata,
        warn=.settings$warn)
```

Arguments

event.e	Number of events in experimental group.
time.e	Person time at risk in experimental group.
event.c	Number of events in control group.
time.c	Person time at risk in control group.
studlab	An optional vector with study labels.

data	An optional data frame containing the study information, i.e., event.e, time.e, event.c, and time.c.
subset	An optional vector specifying a subset of studies to be used.
method	A character string indicating which method is to be used for pooling of studies. One of "MH", "Inverse", or "Cochran", can be abbreviated.
sm	A character string indicating which summary measure ("IRR" or "IRD") is to be used for pooling of studies, see Details.
incr	A numerical value which is added to each cell frequency for studies with a zero cell count, see Details.
allincr	A logical indicating if incr is added to each cell frequency of all studies if at least one study has a zero cell count. If FALSE (default), incr is added only to each cell frequency of studies with a zero cell count.
addincr	A logical indicating if incr is added to each cell frequency of all studies irrespective of zero cell counts.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .
TE.tau	Overall treatment effect used to estimate the between-study variance τ^2 .
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
method.bias	A character string indicating which test for funnel plot asymmetry is to be used. Either "linreg" or "rank", can be abbreviated. See function metabias
n.e	Number of observations in experimental group (optional).
n.c	Number of observations in control group (optional).
backtransf	A logical indicating whether results for incidence rate ratio (sm="IRR") should be back transformed in printouts and plots. If TRUE (default), results will be presented as incidence rate ratios; otherwise log incidence rate ratios will be shown.
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
label.e	Label for experimental group.

<code>label.c</code>	Label for control group.
<code>label.left</code>	Graph label on left side of forest plot.
<code>label.right</code>	Graph label on right side of forest plot.
<code>byvar</code>	An optional vector containing grouping information (must be of same length as <code>event.e</code>).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.
<code>warn</code>	A logical indicating whether warnings should be printed (e.g., if <code>incr</code> is added to studies with zero cell frequencies).

Details

Treatment estimates and standard errors are calculated for each study. The following measures of treatment effect are available:

- Incidence Rate Ratio (`sm="IRR"`)
- Incidence Rate Difference (`sm="IRD"`)

For studies with a zero cell count, by default, 0.5 is added to all cell frequencies of these studies (argument `incr`).

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the `settings.meta` function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if argument `comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function `print.meta` will not print results for the random effects model if `comb.random=FALSE`.

By default, both fixed effect and random effects models are considered (see arguments `comb.fixed` and `comb.random`). If `method` is "MH" (default), the Mantel-Haenszel method is used to calculate the fixed effect estimate (Greenland & Robbins, 1985); if `method` is "Inverse", inverse variance weighting is used for pooling; finally, if `method` is "Cochran", the Cochran method is used for pooling (Bayne-Jones, 1964, Chapter 8). By default, the DerSimonian-Laird estimate (1986) is used in the random effects model (`method.tau="DL"`).

For Mantel-Haenszel and Cochran method, nothing is added to zero cell counts. Accordingly, Mantel-Haenszel and Cochran estimate are not defined if the number of events is zero in all studies either in the experimental or control group.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are TRUE.

R function `update.meta` can be used to redo the meta-analysis of an existing `metainc` object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `pau1emandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison@lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)
- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metainc", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`event.e`, `time.e`, `event.c`, `time.c`, `studlab`,

`sm`, `method`, `incr`, `allincr`, `addincr`, `warn`,

`level`, `level.comb`, `comb.fixed`, `comb.random`,

`hakn`, `method.tau`, `tau.preset`, `TE.tau`, `method.bias`,

`tau.common`, `title`, `complab`, `outclab`,

`label.e`, `label.c`, `label.left`, `label.right`,

`byvar`, `bylab`, `print.byvar`

As defined above.

`TE`, `seTE` Estimated treatment effect and standard error of individual studies.

`lower`, `upper` Lower and upper confidence interval limits for individual studies.

`zval`, `pval` z-value and p-value for test of treatment effect for individual studies.

`w.fixed`, `w.random`

Weight of individual studies (in fixed and random effects model).

`TE.fixed`, `seTE.fixed`

Estimated overall treatment effect and standard error (fixed effect model).

`lower.fixed`, `upper.fixed`

Lower and upper confidence interval limits (fixed effect model).

`zval.fixed`, `pval.fixed`

z-value and p-value for test of overall treatment effect (fixed effect model).

TE.random, seTE.random	Estimated overall treatment effect and standard error (random effects model).
lower.random, upper.random	Lower and upper confidence interval limits (random effects model).
zval.random, pval.random	z-value or t-value and corresponding p-value for test of overall treatment effect (random effects model).
prediction, level.predict	As defined above.
seTE.predict	Standard error utilised for prediction interval.
lower.predict, upper.predict	Lower and upper limits of prediction interval.
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic Q.
df.Q	Degrees of freedom for heterogeneity statistic.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
sparse	Logical flag indicating if any study included in meta-analysis has any zero cell frequencies.
incr.event	Increment added to number of events.
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.
lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.

w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.
df.hakn.w	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if byvar is not missing and hakn=TRUE.
n.harmonic.mean.w	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if byvar is not missing.
event.e.w	Number of events in experimental group in subgroups - if byvar is not missing.
n.e.w	Number of observations in experimental group in subgroups - if byvar is not missing.
event.c.w	Number of events in control group in subgroups - if byvar is not missing.
n.c.w	Number of observations in control group in subgroups - if byvar is not missing.
k.w	Number of studies combined within subgroups - if byvar is not missing.
k.all.w	Number of all studies in subgroups - if byvar is not missing.
Q.w	Heterogeneity statistics within subgroups - if byvar is not missing.
Q.w.fixed	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.w.random	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing (only calculated if argument tau.common is TRUE).
df.Q.w	Degrees of freedom for test of overall within subgroups heterogeneity - if byvar is not missing.
Q.b.fixed	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.b.random	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing.
df.Q.b	Degrees of freedom for test of overall between subgroups heterogeneity - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups - if byvar is not missing.
H.w	Heterogeneity statistic H within subgroups - if byvar is not missing.
lower.H.w, upper.H.w	Lower and upper confidence limti for heterogeneity statistic H within subgroups - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups - if byvar is not missing.
lower.I2.w, upper.I2.w	Lower and upper confidence limti for heterogeneity statistic I2 within subgroups - if byvar is not missing.
keepdata	As defined above.

data	Original data (set) used in function call (if keepdata=TRUE).
subset	Information on subset of original data used in meta-analysis (if keepdata=TRUE).
call	Function call.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Bayne-Jones S et al. (1964), Smoking and Health: Report of the Advisory Committee to the Surgeon General of the United States. U-23 Department of Health, Education, and Welfare. Public Health Service Publication No. 1103. <http://profiles.nlm.nih.gov/ps/retrieve/ResourceMetadata/NNBBMQ>
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Greenland S & Robins JM (1985), Estimation of a common effect parameter from sparse follow-up data. *Biometrics*, **41**, 55–68.
- Hartung J & Knapp G (2001), A Refined Method for the Meta-analysis of Controlled Clinical Trials with Binary Outcome. *Statistics in Medicine*, **20**, 3875–89.
- Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.
- Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–710, doi: 10.1002/sim.1482 .
- Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.
- Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[metabin](#), [update.meta](#), [print.meta](#)

Examples

```
data(smoking)

m1 <- metainc(d.smokers, py.smokers,
             d.nonsmokers, py.nonsmokers,
             data=smoking, studlab=study)
print(m1, digits=2)

m2 <- metainc(d.smokers, py.smokers,
             d.nonsmokers, py.nonsmokers,
             data=smoking, studlab=study,
             method="Cochran")
```

```

print(m2, digits=2)

data(lungcancer)

m3 <- metainc(d.smokers, py.smokers,
             d.nonsmokers, py.nonsmokers,
             data=lungcancer, studlab=study)
print(m3, digits=2)

# Redo Cochran meta-analysis with inflated standard errors
#
# All cause mortality
#
TEa <- log( (smoking$d.smokers/smoking$py.smokers) /
           (smoking$d.nonsmokers/smoking$py.nonsmokers)
           )
seTEa <- sqrt(1/smoking$d.smokers +
             1/smoking$d.nonsmokers + 2.5/smoking$d.nonsmokers)
#
metagen(TEa, seTEa, sm="IRR", studlab=smoking$study)

# Lung cancer mortality
#
TEl <- log( (lungcancer$d.smokers/lungcancer$py.smokers) /
           (lungcancer$d.nonsmokers/lungcancer$py.nonsmokers)
           )
seTEl <- sqrt(1/lungcancer$d.smokers +
             1/lungcancer$d.nonsmokers + 2.25/lungcancer$d.nonsmokers)
#
metagen(TEl, seTEl, sm="IRR", studlab=lungcancer$study)

```

metainf

Influence analysis in meta-analysis

Description

Performs an influence analysis. Pooled estimates are calculated omitting one study at a time.

Usage

```
metainf(x, pooled, sortvar)
```

Arguments

x	An object of class meta.
pooled	A character string indicating whether a fixed effect or random effects model is used for pooling. Either missing (see Details), "fixed" or "random", can be abbreviated.

sortvar An optional vector used to sort the individual studies (must be of same length as x\$TE).

Details

Performs a influence analysis; pooled estimates are calculated omitting one study at a time. Studies are sorted according to sortvar.

Information from object x is utilised if argument pooled is missing. A fixed effect model is assumed (pooled="fixed") if argument x\$comb.fixed is TRUE; a random effects model is assumed (pooled="random") if argument x\$comb.random is TRUE and x\$comb.fixed is FALSE.

Value

An object of class c("metainf", "meta") with corresponding print, plot function. The object is a list containing the following components:

TE, seTE	Estimated treatment effect and standard error of pooled estimate in influence analysis.
lower, upper	Lower and upper confidence interval limits.
studlab	Study label describing omission of studies.
p.value	P-value for test of overall effect.
w	Sum of weights from fixed effect or random effects model.
I2	Heterogeneity statistic I2.
tau	Square-root of between-study variance.
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
sm	Summary measure.
method	Method used for pooling.
k	Number of studies combined in meta-analysis.
pooled	As defined above.
comb.fixed	A logical indicating whether analysis is based on fixed effect model.
comb.random	A logical indicating whether analysis is based on random effects model.
TE.fixed, seTE.fixed	Value is NA.
TE.random, seTE.random	Value is NA.
Q	Value is NA.
level.comb	The level used to calculate confidence intervals for pooled estimates.
hakn	A logical indicating whether the method by Hartung and Knapp is used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 .
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .

TE.tau	Overall treatment effect used to estimate the between-study variance τ^2 .
n.harmonic.mean	Harmonic mean of number of observations (for back transformation of Freeman-Tukey Double arcsine transformation).
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.

See Also

[metabin](#), [metacont](#), [print.meta](#)

Examples

```
data(Fleiss93)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                data=Fleiss93, studlab=study,
                sm="RR", method="I")
meta1

metainf(meta1)
metainf(meta1, pooled="random")

forest(metainf(meta1))
forest(metainf(meta1), layout="revman5")
forest(metainf(meta1, pooled="random"))

metainf(meta1, sortvar=study)
metainf(meta1, sortvar=7:1)

meta2 <- update(meta1, title="Fleiss93 meta-analysis",
                backtransf=FALSE)
metainf(meta2)
```

metaprop

Meta-analysis of single proportions

Description

Calculation of an overall proportion from studies reporting a single proportion.

Usage

```
metaprop(event, n, studlab,
         data=NULL, subset=NULL,
         sm=.settings$smprop,
         incr=.settings$incr, allincr=.settings$allincr,
         addincr=.settings$addincr,
         method.ci=.settings$method.ci,
         level=.settings$level, level.comb=.settings$level.comb,
         comb.fixed=.settings$comb.fixed, comb.random=.settings$comb.random,
         hakn=.settings$hakn,
         method.tau=.settings$method.tau, tau.preset=NULL, TE.tau=NULL,
         tau.common=.settings$tau.common,
         prediction=.settings$prediction, level.predict=.settings$level.predict,
         method.bias=.settings$method.bias,
         backtransf=.settings$backtransf,
         title=.settings$title, complab=.settings$complab, outclab="",
         byvar, bylab, print.byvar=.settings$print.byvar,
         keepdata=.settings$keepdata,
         warn=.settings$warn)
```

Arguments

event	Number of events.
n	Number of observations.
studlab	An optional vector with study labels.
data	An optional data frame containing the study information, i.e., event and n.
subset	An optional vector specifying a subset of studies to be used.
sm	A character string indicating which summary measure ("PFT", "PAS", "PRAW", "PLN", or "PLOGIT") is to be used for pooling of studies, see Details.
incr	A numeric which is added to each cell frequency for studies with a zero cell count.
allincr	A logical indicating if incr is added to each cell frequency of all studies if at least one study has a zero cell count. If FALSE (default), incr is added only to each cell frequency of studies with a zero cell count.
addincr	A logical indicating if incr is added to each cell frequency of all studies irrespective of zero cell counts.
method.ci	A character string indicating which method is used to calculate confidence intervals for individual studies, see Details.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.

<code>level.predict</code>	The level used to calculate prediction interval for a new study.
<code>hakn</code>	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
<code>method.tau</code>	A character string indicating which method is used to estimate the between-study variance τ^2 , see Details.
<code>tau.preset</code>	Prespecified value for the square-root of the between-study variance τ^2 .
<code>TE.tau</code>	Overall treatment effect used to estimate the between-study variance tau-squared.
<code>tau.common</code>	A logical indicating whether tau-squared should be the same across subgroups.
<code>method.bias</code>	A character string indicating which test is to be used. Either "rank", "linreg", or "mm", can be abbreviated. See function <code>metabias</code> .
<code>backtransf</code>	A logical indicating whether results for transformed proportions (argument <code>sm!="PRAW"</code>) should be back transformed in printouts and plots. If TRUE (default), results will be presented as proportions; otherwise transformed proportions will be shown. See Details for presentation of confidence intervals.
<code>title</code>	Title of meta-analysis / systematic review.
<code>complab</code>	Comparison label.
<code>outclab</code>	Outcome label.
<code>byvar</code>	An optional vector containing grouping information (must be of same length as event).
<code>bylab</code>	A character string with a label for the grouping variable.
<code>print.byvar</code>	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
<code>keepdata</code>	A logical indicating whether original data (set) should be kept in meta object.
<code>warn</code>	A logical indicating whether the addition of <code>incr</code> to studies with zero cell frequencies should result in a warning.

Details

Fixed effect and random effects meta-analysis of single proportions to calculate an overall proportion. By default, the DerSimonian-Laird estimate (1986) is used in the random effects model (`method.tau="DL"`).

The following transformations of proportions are implemented to calculate an overall proportion:

- Logit transformation (`sm="PLOGIT"`, default)
- Log transformation (`sm="PLN"`)
- Freeman-Tukey Double arcsine transformation (`sm="PFT"`)
- Arcsine transformation (`sm="PAS"`)
- Raw, i.e. untransformed, proportions (`sm="PRAW"`)

If the summary measure is equal to "PRAW", "PLN", or "PLOGIT", a continuity correction is applied if any studies has a zero cell count. By default, 0.5 is added to all cell frequencies of studies with a zero cell count (argument `incr`).

Various methods are available to calculate confidence intervals for individual study results (see Agresti & Coull 1998; Newcombe 1988):

- Clopper-Pearson interval also called 'exact' binomial interval (`method.ci="CP"`, default)
- Wilson Score interval (`method.ci="WS"`)
- Wilson Score interval with continuity correction (`method.ci="WSCC"`)
- Agresti-Coull interval (`method.ci="AC"`)
- Simple approximation interval (`method.ci="SA"`)
- Simple approximation interval with continuity correction (`method.ci="SACC"`)
- Normal approximation interval based on summary measure, i.e. defined by argument `sm` (`method.ci="NAsm"`)

Note, with exception of the normal approximation based on the summary measure, i.e. `method.ci="NAsm"`, the same confidence interval is calculated for any summary measure (argument `sm`) as only number of events and observations are used in the calculation disregarding the chosen summary measure. Results will be presented for transformed proportions if argument `backtransf=FALSE` in the `print.meta`, `print.summary.meta`, or `forest.meta` function. In this case, argument `method.ci="NAsm"` is used, i.e. confidence intervals based on the normal approximation based on the summary measure.

For several arguments defaults settings are utilised (assignments with `.settings$`). These defaults can be changed using the `settings.meta` function.

Internally, both fixed effect and random effects models are calculated regardless of values chosen for arguments `comb.fixed` and `comb.random`. Accordingly, the estimate for the random effects model can be extracted from component `TE.random` of an object of class "meta" even if argument `comb.random=FALSE`. However, all functions in R package `meta` will adequately consider the values for `comb.fixed` and `comb.random`. E.g. function `print.meta` will not print results for the random effects model if `comb.random=FALSE`.

A prediction interval for treatment effect of a new study is calculated (Higgins et al., 2009) if arguments `prediction` and `comb.random` are TRUE.

R function `update.meta` can be used to redo the meta-analysis of an existing `metaprop` object by only specifying arguments which should be changed.

For the random effects, the method by Hartung and Knapp (2003) is used to adjust test statistics and confidence intervals if argument `hakn=TRUE`.

The iterative Paule-Mandel method (1982) to estimate the between-study variance is used if argument `method.tau="PM"`. Internally, R function `paulemandel` is called which is based on R function `mpaule.default` from R package `metRology` from S.L.R. Ellison <s.ellison at lgc.co.uk>.

If R package `metafor` (Viechtbauer 2010) is installed, the following methods to estimate the between-study variance τ^2 (argument `method.tau`) are also available:

- Restricted maximum-likelihood estimator (`method.tau="REML"`)
- Maximum-likelihood estimator (`method.tau="ML"`)
- Hunter-Schmidt estimator (`method.tau="HS"`)
- Sidik-Jonkman estimator (`method.tau="SJ"`)
- Hedges estimator (`method.tau="HE"`)
- Empirical Bayes estimator (`method.tau="EB"`).

For these methods the R function `rma.uni` of R package `metafor` is called internally. See help page of R function `rma.uni` for more details on these methods to estimate between-study variance.

Value

An object of class `c("metaprop", "meta")` with corresponding `print`, `summary`, `plot` function. The object is a list containing the following components:

`event`, `n`, `studlab`,

`sm`, `incr`, `allincr`, `addincr`, `method.ci`,

`level`, `level.comb`,

As defined above.

`comb.fixed`, `comb.random`,

`hakn`, `method.tau`, `tau.preset`, `TE.tau`, `method.bias`,

`tau.common`, `title`, `complab`, `outclab`,

`byvar`, `bylab`, `print.byvar`, `warn`

`TE`, `seTE` Estimated (un)transformed proportion and its standard error for individual studies.

`lower`, `upper` Lower and upper confidence interval limits for individual studies.

`zval`, `pval` z-value and p-value for test of treatment effect for individual studies.

`w.fixed`, `w.random`

Weight of individual studies (in fixed and random effects model).

`TE.fixed`, `seTE.fixed`

Estimated overall (un)transformed proportion and standard error (fixed effect model).

`lower.fixed`, `upper.fixed`

Lower and upper confidence interval limits (fixed effect model).

`zval.fixed`, `pval.fixed`

z-value and p-value for test of overall effect (fixed effect model).

`TE.random`, `seTE.random`

Estimated overall (un)transformed proportion and standard error (random effects model).

`lower.random`, `upper.random`

Lower and upper confidence interval limits (random effects model).

`zval.random`, `pval.random`

z-value or t-value and corresponding p-value for test of overall effect (random effects model).

`prediction`, `level.predict`

As defined above.

`seTE.predict` Standard error utilised for prediction interval.

`lower.predict`, `upper.predict`

Lower and upper limits of prediction interval.

`k` Number of studies combined in meta-analysis.

Q	Heterogeneity statistic Q.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
sm	A character string: "proportion"
method	A character string indicating method used for pooling: "Inverse"
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
bylevs	Levels of grouping variable - if byvar is not missing.
TE.fixed.w, seTE.fixed.w	Estimated treatment effect and standard error in subgroups (fixed effect model) - if byvar is not missing.
lower.fixed.w, upper.fixed.w	Lower and upper confidence interval limits in subgroups (fixed effect model) - if byvar is not missing.
zval.fixed.w, pval.fixed.w	z-value and p-value for test of treatment effect in subgroups (fixed effect model) - if byvar is not missing.
TE.random.w, seTE.random.w	Estimated treatment effect and standard error in subgroups (random effects model) - if byvar is not missing.
lower.random.w, upper.random.w	Lower and upper confidence interval limits in subgroups (random effects model) - if byvar is not missing.
zval.random.w, pval.random.w	z-value or t-value and corresponding p-value for test of treatment effect in subgroups (random effects model) - if byvar is not missing.
w.fixed.w, w.random.w	Weight of subgroups (in fixed and random effects model) - if byvar is not missing.
df.hakn.w	Degrees of freedom for test of treatment effect for Hartung-Knapp method in subgroups - if byvar is not missing and hakn=TRUE.
n.harmonic.mean.w	Harmonic mean of number of observations in subgroups (for back transformation of Freeman-Tukey Double arcsine transformation) - if byvar is not missing.
event.w	Number of events in subgroups - if byvar is not missing.
n.w	Number of observations in subgroups - if byvar is not missing.
k.w	Number of studies combined within subgroups - if byvar is not missing.
k.all.w	Number of all studies in subgroups - if byvar is not missing.
Q.w	Heterogeneity statistics within subgroups - if byvar is not missing.
Q.w.fixed	Overall within subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.

Q.w.random	Overall within subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing (only calculated if argument tau.common is TRUE).
df.Q.w	Degrees of freedom for test of overall within subgroups heterogeneity - if byvar is not missing.
Q.b.fixed	Overall between subgroups heterogeneity statistic Q (based on fixed effect model) - if byvar is not missing.
Q.b.random	Overall between subgroups heterogeneity statistic Q (based on random effects model) - if byvar is not missing.
df.Q.b	Degrees of freedom for test of overall between subgroups heterogeneity - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups - if byvar is not missing.
H.w	Heterogeneity statistic H within subgroups - if byvar is not missing.
lower.H.w, upper.H.w	Lower and upper confidence limits for heterogeneity statistic H within subgroups - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups - if byvar is not missing.
lower.I2.w, upper.I2.w	Lower and upper confidence limits for heterogeneity statistic I2 within subgroups - if byvar is not missing.
incr.event	Increment added to number of events.
keepdata	As defined above.
data	Original data (set) used in function call (if keepdata=TRUE).
subset	Information on subset of original data used in meta-analysis (if keepdata=TRUE).
call	Function call.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

- Agresti A & Coull BA (1998), Approximate is better than “exact” for interval estimation of binomial proportions. *The American Statistician*, **52**, 119–126.
- DerSimonian R & Laird N (1986), Meta-analysis in clinical trials. *Controlled Clinical Trials*, **7**, 177–188.
- Edward JM et al. (2006), Adherence to antiretroviral therapy in sub-saharan Africa and North America - a meta-analysis. *Journal of the American Medical Association*, **296**, 679–690.
- Freeman MF & Tukey JW (1950), Transformations related to the angular and the square root. *Annals of Mathematical Statistics*, **21**, 607–611.

- Higgins JPT, Thompson SG, Spiegelhalter DJ (2009), A re-evaluation of random-effects meta-analysis. *Journal of the Royal Statistical Society: Series A*, **172**, 137–159.
- Knapp G & Hartung J (2003), Improved Tests for a Random Effects Meta-regression with a Single Covariate. *Statistics in Medicine*, **22**, 2693–2710, doi: 10.1002/sim.1482 .
- Miller JJ (1978), The inverse of the Freeman-Tukey double arcsine transformation. *The American Statistician*, **32**, 138.
- Newcombe RG (1998), Two-sided confidence intervals for the single proportion: Comparison of seven methods. *Statistics in Medicine*, **17**, 857–872.
- Paule RC & Mandel J (1982), Consensus values and weighting factors. *Journal of Research of the National Bureau of Standards*, **87**, 377–385.
- Pettigrew HM, Gart JJ, Thomas DG (1986), The bias and higher cumulants of the logarithm of a binomial variate. *Biometrika*, **73**, 425–435.
- Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[update.meta](#), [metacont](#), [metagen](#), [print.meta](#)

Examples

```
#
# Apply various meta-analysis methods to estimate proportions
#
m1 <- metaprop(4:1, c(10, 20, 30, 40))
m2 <- update(m1, sm="PAS")
m3 <- update(m1, sm="PRAW")
m4 <- update(m1, sm="PLN")
m5 <- update(m1, sm="PFT")
#
m1
m2
m3
m4
m5
#
forest(m1)
# forest(m2)
# forest(m3)
# forest(m3, pscale=100)
# forest(m4)
# forest(m5)

#
# Do not back transform results, e.g. print logit transformed
# proportions if sm="PLOGIT"
#
oldset <- settings.meta(backtransf=FALSE)
```

```
#
m6 <- metaprop(4:1, c(10, 20, 30, 40))
m7 <- update(m6, sm="PAS")
m8 <- update(m6, sm="PRAW")
m9 <- update(m6, sm="PLN")
m10 <- update(m6, sm="PFT")
#
forest(m6)
# forest(m7)
# forest(m8)
# forest(m8, pscale=100)
# forest(m9)
# forest(m10)
#
# Reset settings
#
settings.meta(oldset)

#
# Examples with zero events
#
m1 <- metaprop(c(0, 0, 10, 10), rep(100, 4))
m2 <- metaprop(c(0, 0, 10, 10), rep(100, 4), incr=0.1)
#
summary(m1)
summary(m2)
#
# forest(m1)
# forest(m2)

#
# Example from Miller (1978):
#
death <- c(3, 6, 10, 1)
animals <- c(11, 17, 21, 6)
#
m3 <- metaprop(death, animals, sm="PFT")
forest(m3)

#
# Data examples from Newcombe (1998)
# - apply various methods to estimate confidence intervals for
#   individual studies
#
event <- c(81, 15, 0, 1)
n <- c(263, 148, 20, 29)
#
m1 <- metaprop(event, n, sm="PLOGIT", method.ci="SA")
m2 <- update(m1, method.ci="SACC")
m3 <- update(m1, method.ci="WS")
```

```

m4 <- update(m1, method.ci="WSCC")
m5 <- update(m1, method.ci="CP")
#
lower <- round(rbind(NA, m1$lower, m2$lower, NA, m3$lower, m4$lower, NA, m5$lower), 4)
upper <- round(rbind(NA, m1$upper, m2$upper, NA, m3$upper, m4$upper, NA, m5$upper), 4)
#
tab1 <- data.frame(
  scen1=meta::p.ci(lower[,1], upper[,1]),
  scen2=meta::p.ci(lower[,2], upper[,2]),
  scen3=meta::p.ci(lower[,3], upper[,3]),
  scen4=meta::p.ci(lower[,4], upper[,4]),
  stringsAsFactors=FALSE
)
names(tab1) <- c("r=81, n=263", "r=15, n=148", "r=0, n=20", "r=1, n=29")
row.names(tab1) <- c("Simple", "- SA", "- SACC",
  "Score", "- WS", "- WSCC",
  "Binomial", "- CP")
tab1[is.na(tab1)] <- ""
#
# Newcombe (1998), Table I, methods 1-5:
#
tab1
#
# Same confidence interval, i.e. unaffected by choice of summary measure
#
print(metaprop(event, n, sm="PLOGIT", method.ci="WS"), ma=FALSE)
print(metaprop(event, n, sm="PLN", method.ci="WS"), ma=FALSE)
print(metaprop(event, n, sm="PFT", method.ci="WS"), ma=FALSE)
print(metaprop(event, n, sm="PAS", method.ci="WS"), ma=FALSE)
print(metaprop(event, n, sm="PRAW", method.ci="WS"), ma=FALSE)
#
# Different confidence intervals as argument sm="NASm"
#
print(metaprop(event, n, sm="PLOGIT", method.ci="NASm"), ma=FALSE)
print(metaprop(event, n, sm="PLN", method.ci="NASm"), ma=FALSE)
print(metaprop(event, n, sm="PFT", method.ci="NASm"), ma=FALSE)
print(metaprop(event, n, sm="PAS", method.ci="NASm"), ma=FALSE)
print(metaprop(event, n, sm="PRAW", method.ci="NASm"), ma=FALSE)
#
# Different confidence intervals as argument backtransf=FALSE.
# Accordingly, method.ci="NASm" used internally.
#
print(metaprop(event, n, sm="PLOGIT", method.ci="WS"), ma=FALSE, backtransf=FALSE)
print(metaprop(event, n, sm="PLN", method.ci="WS"), ma=FALSE, backtransf=FALSE)
print(metaprop(event, n, sm="PFT", method.ci="WS"), ma=FALSE, backtransf=FALSE)
print(metaprop(event, n, sm="PAS", method.ci="WS"), ma=FALSE, backtransf=FALSE)
print(metaprop(event, n, sm="PRAW", method.ci="WS"), ma=FALSE, backtransf=FALSE)
#
# Same results (printed on original and log scale, respectively)
#
print(metaprop(event, n, sm="PLN", method.ci="NASm"), ma=FALSE)
print(metaprop(event, n, sm="PLN"), ma=FALSE, backtransf=FALSE)
# Results for first study (on log scale)

```

```
round(log(c(0.3079848, 0.2569522, 0.3691529)), 4)
```

metareg

*Meta-regression***Description**

Meta-regression for objects of class `meta`. This is a wrapper function for the R function `rma.uni` in the R package `metafor` (Viechtbauer 2010).

Usage

```
metareg(x, formula, method.tau=x$method.tau, hakn=x$hakn,
        level.comb=x$level.comb, intercept=TRUE,...)
```

Arguments

<code>x</code>	An object of class <code>meta</code> .
<code>formula</code>	Either a character string or a formula object.
<code>method.tau</code>	A character string indicating which method is used to estimate the between-study variance tau-squared. Either "FE", "DL", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
<code>hakn</code>	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
<code>level.comb</code>	The level used to calculate confidence intervals for parameter estimates in the meta-regression model.
<code>intercept</code>	A logical indicating whether an intercept should be included in the meta-regression model.
<code>...</code>	Additional arguments passed to R function <code>rma.uni</code> .

Details

This R function is a wrapper function for R function `rma.uni` in the R package `metafor` (Viechtbauer 2010), i.e. the function `metareg` can only be used if the R package 'metafor' is installed.

Argument '`...`' can be used to pass additional arguments to R function `rma.uni`. For example, argument `control` to provide a list of control values for the iterative estimation algorithm. See help page of R function `rma.uni` for more details.

Value

An object of class `c("metareg", "rma.uni", "rma")`. Please look at the help page of R function `rma.uni` for more details on the output from this function.

In addition, a list `.meta` is added to the output containing the following components:

```
x, formula, method.tau, hakn, level.comb, intercept
  As defined above.
```

dots Information provided in argument '...'.
 call Function call.
 version Version of R package meta used to create object.
 version.metafor Version of R package metafor used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Viechtbauer W (2010), Conducting Meta-Analyses in R with the Metafor Package. *Journal of Statistical Software*, **36**, 1–48.

See Also

[bubble](#), [summary.meta](#), [metagen](#)

Examples

```
data(Fleiss93cont)

# Add some (fictitious) grouping variables:
Fleiss93cont$age <- c(55, 65, 55, 65, 55)
Fleiss93cont$region <- c("Europe", "Europe", "Asia", "Asia", "Europe")

meta1 <- metacont(n.e, mean.e, sd.e,
                 n.c, mean.c, sd.c,
                 data=Fleiss93cont, sm="MD")

mu1 <- update(meta1, byvar=region)

mu2 <- update(meta1, byvar=region,
              tau.common=TRUE, comb.fixed=FALSE)

## Not run:
# Warnings due to wrong ordering of arguments (order has changed with
# version 3.0-0 of R package meta)
#
metareg(~region, meta1)
metareg(~region, data=meta1)

# Warning as no information on covariate is available
#
metareg(meta1)

## End(Not run)

# Do meta-regression for covariate region
```

```
# (see R code to create object mu2)
#
metareg(mu2)

# Same result for
# - tau-squared
# - test of heterogeneity
# - test for subgroup differences
# (as argument 'tau.common' was used to create mu2)
#
mu2
metareg(mu2, intercept=FALSE)
metareg(meta1, region)
#
# Different result for
# - tau-squared
# - test of heterogeneity
# - test for subgroup differences
# (as argument 'tau.common' is - by default - FALSE)
#
mu1

# Generate bubble plot
#
bubble(metareg(mu2))

# Do meta-regression with two covariates
#
metareg(mu1, region + age)

# Do same meta-regressions using 'official' formula notation
#
metareg(meta1, ~region)
metareg(mu1, ~region + age)

# Do meta-regression using REML method and print intermediate results
# for iterative estimation algorithm; furthermore print results with
# three digits.
#
metareg(mu1, region, method.tau="REML",
        control=list(verbose=TRUE), digits=3)

# Use Hartung-Knapp method
#
mu3 <- update(mu2, hakn=TRUE)
mu3
metareg(mu3, intercept=FALSE)
```

Description

Meta-analysis on Thrombolytic Therapy after Acute Myocardial Infarction

Usage

```
data(0lkin95)
```

Format

A data frame with the following columns:

author First author
year Year of publication
event.e Number of events in experimental group
n.e Number of observations in experimental group
event.c Number of events in control group
n.c Number of observations in control group

Source

Olkin I (1995), Statistical and theoretical considerations in meta-analysis. *Journal of Clinical Epidemiology*, **48**, 133–146.

Examples

```
data(0lkin95)
summary(metabin(event.e, n.e, event.c, n.c, data=0lkin95))
```

```
print.meta
```

Print and summary method for objects of class meta

Description

Print and summary method for objects of class meta.

Usage

```
## S3 method for class 'meta'
print(x, sortvar,
      comb.fixed=x$comb.fixed,
      comb.random=x$comb.random,
      prediction=x$prediction,
      details=FALSE, ma=TRUE, backtransf=x$backtransf,
      digits=max(4, .Options$digits - 3), ...)

## S3 method for class 'metabias'
```

```

print(x, ...)

## S3 method for class 'meta'
summary(object,
         comb.fixed=object$comb.fixed, comb.random=object$comb.random,
         prediction=object$prediction,
         backtransf=object$backtransf,
         bylab=object$bylab, print.byvar=object$print.byvar,
         bystud=FALSE, print.CMH=object$print.CMH,
         warn=object$warn, ...)

## S3 method for class 'summary.meta'
print(x, digits = max(3, .Options$digits - 3),
      comb.fixed=x$comb.fixed, comb.random=x$comb.random,
      prediction=x$prediction,
      print.byvar=x$print.byvar, print.CMH=x$print.CMH,
      header=TRUE, backtransf=x$backtransf,
      bylab.nchar=35, ...)

cilayout(bracket="[" , separator="; ")

```

Arguments

x	An object of class meta, metabias, or summary.meta.
object	An object of class meta.
sortvar	An optional vector used to sort the individual studies (must be of same length as x\$TE).
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
prediction	A logical indicating whether a prediction interval should be printed.
bylab	A character string with a label for the grouping variable.
print.byvar	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
header	A logical indicating whether information on title of meta-analysis, comparison and outcome should be printed at the beginning of the printout.
details	A logical indicating whether further details of individual studies should be printed.
ma	A logical indicating whether the summary results of the meta-analysis should be printed.
backtransf	A logical indicating whether printed results should be back transformed. If backtransf=TRUE, results for sm="OR" are printed as odds ratios rather than log odds ratios and results for sm="ZCOR" are printed as correlations rather than Fisher's z transformed correlations, for example.
bylab.nchar	A numeric specifying the number of characters to print from label for the grouping variable.

bystud	A logical indicating whether results of individual studies should be printed by grouping variable.
print.CMH	A logical indicating whether result of the Cochran-Mantel-Haenszel test for overall effect should be printed.
digits	Minimal number of significant digits, see print.default.
warn	A logical indicating whether the use of summary.meta in connection with metacum or metainf should result in a warning.
bracket	A character with bracket symbol to print lower confidence interval: "[", "(", "{", "".
separator	A character string with information on separator between lower and upper confidence interval.
...	Additional arguments.

Details

Note, in R package meta, version 3.0-0 some arguments have been removed from R functions summary.meta (arguments: byvar, level, level.comb, level.prediction) and print.summary.meta (arguments: level, level.comb, level.prediction). This functionality is now provided by R function [update.meta](#) (or directly in R functions [metabin](#), [metacont](#), [metagen](#), [metacor](#), and [metaprop](#)).

Review Manager 5 (RevMan 5) is the current software used for preparing and maintaining Cochrane Reviews (<http://tech.cochrane.org/revman/>). In RevMan 5, subgroup analyses can be defined and data from a Cochrane review can be imported to R using the function read.rm5. If a meta-analysis is then conducted using function metacr, information on subgroups is available in R (components byvar, bylab, and print.byvar, byvar in an object of class "meta"). Accordingly, by using function metacr there is no need to define subgroups in order to redo the statistical analysis conducted in the Cochrane review.

Note, for an object of type metaprop, starting with version 3.7-0 of meta, list elements TE, lower and upper in element study correspond to transformed proportions and confidence limits (regardless whether exact confidence limits are calculated; argument ciexact=TRUE in metaprop function). Accordingly, the following results are based on the same transformation defined by argument sm: list elements TE, lower and upper in elements study, fixed, random, within.fixed and within.random.

R function cilayout can be utilised to change the layout to print confidence intervals (both in printout from print.meta and print.summary.meta function as well as in forest plots). The default layout is "[lower; upper]". Another popular layout is "(lower - upper)" which is used throughout an R session by using R command cilayout("(", " - ").

Value

A list is returned by the function summary.meta with the following elements:

study	Results for individual studies (a list with elements TE, seTE, lower, upper, z, p, level, df).
fixed	Results for fixed effect model (a list with elements TE, seTE, lower, upper, z, p, level, df).

random	Results for random effects model (a list with elements TE, seTE, lower, upper, z, p, level, df).
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic Q.
tau	Square-root of between-study variance.
se.tau	Standard error of square-root of between-study variance.
C	Scaling factor utilised internally to calculate common tau-squared across subgroups.
H	Heterogeneity statistic H (a list with elements TE, lower, upper).
I2	Heterogeneity statistic I2 (a list with elements TE, lower, upper), see Higgins & Thompson (2002).
k.all	Total number of studies.
Q.CMH	Cochran-Mantel-Haenszel test statistic for overall effect.
sm	A character string indicating underlying summary measure.
method	A character string with the pooling method.
call	Function call.
ci.lab	Label for confidence interval.
hakn	A logical indicating whether method by Hartung and Knapp was used.
method.tau	A character string indicating which method is used to estimate the between-study variance tau-squared.
tau.common	A logical indicating whether tau-squared is assumed to be the same across subgroups.
within.fixed	Result for fixed effect model within groups (a list with elements TE, seTE, lower, upper, z, p, level, df, harmonic.mean) - if byvar is not missing.
within.random	Result for random effects model within groups (a list with elements TE, seTE, lower, upper, z, p, level, df, harmonic.mean) - if byvar is not missing.
k.w	Number of studies combined within groups - if byvar is not missing.
Q.w	Heterogeneity statistic Q within groups - if byvar is not missing.
Q.b.fixed	Heterogeneity statistic Q between groups (based on fixed effect model) - if byvar is not missing.
Q.b.random	Heterogeneity statistic Q between groups (based on random effects model) - if byvar is not missing.
tau.w	Square-root of between-study variance within subgroups - if byvar is not missing.
C.w	Scaling factor utilised internally to calculate common tau-squared across subgroups.
H.w	Heterogeneity statistic H within subgroups (a list with elements TE, lower, upper) - if byvar is not missing.
I2.w	Heterogeneity statistic I2 within subgroups (a list with elements TE, lower, upper) - if byvar is not missing.

bylevs	Levels of grouping variable - if byvar is not missing.
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
data	Original data (set) used to create meta object.
subset	Information on subset of original data used in meta-analysis.
prediction, level.predict	
comb.fixed, comb.random, print.CMH	As defined above.
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Cooper H & Hedges LV (1994), *The Handbook of Research Synthesis*. Newbury Park, CA: Russell Sage Foundation.

Higgins JPT & Thompson SG (2002), Quantifying heterogeneity in a meta-analysis. *Statistics in Medicine*, **21**, 1539–1558.

See Also

[update.meta](#), [metabin](#), [metacont](#), [metagen](#)

Examples

```
data(Fleiss93cont)
meta1 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c,
                 data=Fleiss93cont, sm="SMD",
                 studlab=paste(study, year))
summary(meta1)

summary(update(meta1, byvar=c(1,2,1,1,2), bylab="group"))

forest(update(meta1, byvar=c(1,2,1,1,2), bylab="group"))
```

 print.rm5

Print and summary methods for objects of class rm5

Description

Print and summary methods for objects of class rm5.

Usage

```
## S3 method for class 'rm5'
print(x, ...)

## S3 method for class 'summary.rm5'
print(x, ...)

## S3 method for class 'rm5'
summary(object, comp.no, outcome.no, ...)

## S3 method for class 'rm5'
metabias(x, comp.no, outcome.no,
         method.bias="linreg",
         method.bias.binary=method.bias,
         method.bias.or="score",
         k.min=10, ...)
```

Arguments

x	An object of class rm5.
object	An object of class rm5.
comp.no	Comparison number.
outcome.no	Outcome number.
method.bias	A character string indicating which test for small-study effects is to be used for all outcomes. Either "rank", "linreg", or "mm", can be abbreviated. See function metabias
method.bias.binary	A character string indicating which test is to be used for binary outcomes. Either "rank", "linreg", "mm", "count", "score", or "peters", can be abbreviated. See function metabias
method.bias.or	A character string indicating which test is to be used for binary outcomes with odds ratio as summary measure. Either "rank", "linreg", "mm", "count", "score", or "peters", can be abbreviated. See function metabias
k.min	Minimum number of studies to perform test for small-study effects.
...	Additional arguments (ignored at the moment)

Details

Review Manager 5 (RevMan 5) is the current software used for preparing and maintaining Cochrane Reviews (<http://tech.cochrane.org/revman/>). In RevMan 5, subgroup analyses can be defined and data from a Cochrane review can be imported to R using the function `read.rm5`.

The R function `summary.rm5` can be used to redo all meta-analyses of the imported Cochrane Review.

The R function `metabias.rm5` can be used to conduct a test for funnel plot asymmetry for all meta-analyses of the imported Cochrane Review.

The R function `metacr` is called internally.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Higgins, J.P.T and S. Green (2011), *Cochrane Handbook for Systematic Reviews of Interventions Version 5.1.0 [Updated March 2011]*. The Cochrane Library: <http://www.cochrane-handbook.org>

See Also

[metabias.meta](#), [summary.meta](#), [read.rm5](#)

Examples

```
# Locate export data file "Fleiss93_CR.csv"
# in sub-directory of package "meta"
#
filename <- system.file("data/Fleiss93_CR.csv.gz", package = "meta")
#
Fleiss93_CR <- read.rm5(filename)

#
# Print summary results for all meta-analysis:
#
summary(Fleiss93_CR)

#
# Print results for tests of small-study effects:
#
metabias(Fleiss93_CR, k.min=5)
```

read.mtv	<i>Import RevMan 4 data files (.mtv)</i>
----------	--

Description

Reads a file created with RevMan 4 and creates a data frame from it.

Usage

```
read.mtv(file)
```

Arguments

file	The name of a file to read data values from.
------	--

Details

Reads a file created with RevMan 4 (Menu: "File" - "Export" - "Analysis data file...") and creates a data frame from it.

Value

A data frame containing the following components:

comp.no	Comparison number.
outcome.no	Outcome number.
group.no	Group number.
studlab	Study label.
year	Year of publication.
event.e	Number of events in experimental group.
n.e	Number of observations in experimental group.
event.c	Number of events in control group.
n.c	Number of observations in control group.
mean.e	Estimated mean in experimental group.
sd.e	Standard deviation in experimental group.
mean.c	Estimated mean in control group.
sd.c	Standard deviation in control group.
O.E	Observed minus expected (IPD analysis).
V	Variance of O.E (IPD analysis).
order	Ordering of studies.
conceal	Concealment of treatment allocation.
grplab	Group label.

type	Type of outcome. D = dichotomous, C = continuous, P = IPD.
outclab	Outcome label.
graph.exp	Graph label for experimental group.
graph.cont	Graph label for control group.
label.exp	Label for experimental group.
label.cont	Label for control group.
complab	Comparison label.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Review Manager (RevMan) [Computer program]. Version 4.2 for Windows. Copenhagen: The Nordic Cochrane Centre, The Cochrane Collaboration, 2003.

See Also

[metabin](#), [metacont](#), [metagen](#)

Examples

```
# Locate MTV-data file "FLEISS93.MTV" in sub-directory of package "meta"
#
filename <- system.file("extdata/Fleiss93.MTV", package = "meta")
#
fleiss93.cc <- read.mtv(filename)

# Same result as R Command example(Fleiss93):
#
metabin(event.e, n.e, event.c, n.c,
        data=fleiss93.cc, subset=type=="D",
        studlab=paste(studlab, year))

# Same result: example(Fleiss93cont)
#
metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c,
         data=fleiss93.cc, subset=type=="C",
         studlab=paste(studlab, year))
```

read.rm5

*Import RevMan 5 data files (.csv)***Description**

Reads data file from Cochrane Intervention review created with RevMan 5 and creates a data frame from it.

Usage

```
read.rm5(file, sep=",", quote = "\"", title,
         numbers.in.labels=TRUE)
```

Arguments

file	The name of a file to read data values from.
sep	The field separator character. Values on each line of the file are separated by this character. The comma is the default field separator character in RevMan 5.
quote	The set of quoting characters. In RevMan 5 a "\"" is the default quoting character.
title	Title of Cochrane review.
numbers.in.labels	A logical indicating whether comparison number and outcome number should be printed at the beginning of the comparison (argument complab) and outcome label (argument outclab); this is the default in RevMan 5.

Details

Review Manager 5 (RevMan 5) is the current software used for preparing and maintaining Cochrane Reviews (<http://tech.cochrane.org/revman/>). RevMan 5 includes the ability to write Systematic reviews of interventions, Diagnostic test accuracy reviews, Methodology reviews and Overviews of reviews.

This function provides the ability to read a data file from a Cochrane Intervention review created with RevMan 5; a data frame is created from it. Cochrane Intervention reviews are based on the comparison of two interventions.

In order to generate a data analysis file in RevMan 5 use the following Menu points: "File" - "Export" - "Data and analyses". It is mandatory to include the following fields in the exported data file by selecting them with the mouse cursor in the Export Analysis Data Wizard: (i) Comparison Number, (ii) Outcome Number, (iii) Subgroup Number. When these fields are not selected a corresponding error message will be printed in R. It is recommended to include all fields in the exported data file except for the last field "Risk of bias tables". For example, in order to redo the meta-analysis in R for the RevMan 5 data type "O-E and Variance" the fields "O-E" and "Variance" have to be selected in the Export Analysis Data Wizard. If the last field "Risk of bias tables" is selected the import in R fails with an error message "line X did not have Y elements".

By default in RevMan 5, the name of the exported data file is the title of the Cochrane Review. Accordingly, information on the title is extracted from the name of the exported data file (argument: `file`) if argument `title` is missing (default).

Each respective meta-analysis for arguments `event.e.pooled` – `df.pooled` is defined by values for `"comp.no"` and `"outcome.no"`, and `"grp.no"`.

Value

A data frame containing the following components:

<code>comp.no</code>	Comparison number.
<code>outcome.no</code>	Outcome number.
<code>group.no</code>	Group number.
<code>studlab</code>	Study label.
<code>year</code>	Year of publication.
<code>event.e</code>	Number of events in experimental group.
<code>n.e</code>	Number of observations in experimental group.
<code>event.c</code>	Number of events in control group.
<code>n.c</code>	Number of observations in control group.
<code>mean.e</code>	Estimated mean in experimental group.
<code>sd.e</code>	Standard deviation in experimental group.
<code>mean.c</code>	Estimated mean in control group.
<code>sd.c</code>	Standard deviation in control group.
<code>O.E</code>	Observed minus expected (IPD analysis).
<code>V</code>	Variance of O.E (IPD analysis).
<code>TE, seTE</code>	Estimated treatment effect and standard error of individual studies.
<code>lower, upper</code>	Lower and upper limit of 95% confidence interval for treatment effect in individual studies.
<code>weight</code>	Weight of individual studies (according to meta-analytical method used in respective meta-analysis - see below for details).
<code>order</code>	Ordering of studies.
<code>grplab</code>	Group label.
<code>type</code>	Type of outcome. D = dichotomous, C = continuous, P = IPD.
<code>method</code>	A character string indicating which method has been used for pooling of studies. One of "Inverse", "MH", or "Peto".
<code>sm</code>	A character string indicating which summary measure has been used for pooling of studies.
<code>model</code>	A character string indicating which meta-analytical model has been used (either "Fixed" or "Random").
<code>comb.fixed</code>	A logical indicating whether fixed effect meta-analysis has been used in respective meta-analysis (see below for details).

comb.random	A logical indicating whether random effects meta-analysis has been used in respective meta-analysis (see below for details).
outclab	Outcome label.
k	Total number of studies combined in respective meta-analysis).
event.e.pooled	Number of events in experimental group in respective meta-analysis (see below for details).
n.e.pooled	Number of observations in experimental group in respective meta-analysis (see below for details).
event.c.pooled	Number of events in control group in respective meta-analysis (see below for details).
n.c.pooled	Number of observations in control group in respective meta-analysis (see below for details).
TE.pooled	Estimated treatment effect in respective meta-analysis (see below for details).
lower, upper	Lower and upper limit of 95% confidence interval for treatment effect in respective meta-analysis (see below for details).
weight.pooled	Total weight in respective meta-analysis (see below for details).
Z.pooled	Z-score for test of overall treatment effect in respective meta-analysis (see below for details).
pval.pooled	P-value for test of overall treatment effect in respective meta-analysis (see below for details).
Q	Heterogeneity statistic Q in respective meta-analysis (see below for details).
pval.Q	P-value of heterogeneity statistic Q in respective meta-analysis (see below for details).
I2	Heterogeneity statistic I2 in respective meta-analysis (see below for details).
tau2	Between-study variance (moment estimator of DerSimonian-Laird) in respective meta-analysis.
Q.w	Heterogeneity statistic Q within groups in respective meta-analysis (see below for details).
pval.Q.w	P-value of heterogeneity statistic Q within groups in respective meta-analysis (see below for details).
I2.w	Heterogeneity statistic I2 within groups in respective meta-analysis (see below for details).
label.e	Label for experimental group.
label.c	Label for control group.
label.left	Graph label on left side of forest plot.
label.right	Graph label on right side of forest plot.
RR.cochrane	A logical indicating if 2*incr instead of 1*incr is to be added to n.e and n.c in the calculation of the risk ratio (i.e., sm="RR") for studies with a zero cell. This is used in RevMan 5.
complab	Comparison label.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Review Manager (RevMan) [Computer program]. Version 5.3. Copenhagen: The Nordic Cochrane Centre, The Cochrane Collaboration, 2014.

See Also

[metabin](#), [metacont](#), [metagen](#), [metacr](#)

Examples

```
# Locate export data file "Fleiss93_CR.csv"
# in sub-directory of package "meta"
#
filename <- system.file("data/Fleiss93_CR.csv.gz", package = "meta")
#
Fleiss93_CR <- read.rm5(filename)

# Same result as R command example(Fleiss93):
#
metacr(Fleiss93_CR)

# Same result as R command example(Fleiss93cont):
#
metacr(Fleiss93_CR, 1, 2)
```

settings.meta

Print and change default settings for meta-analyses in R package meta.

Description

Print and change default settings for meta-analyses in R package meta.

Usage

```
settings.meta(...)
```

Arguments

... Arguments to change default settings.

Details

This function can be used to define defaults for several arguments of the following R functions: `metabin`, `metacont`, `metacor`, `metacr`, `metagen`, `metainc`, `metaprop`.

A list of all arguments with current settings is printed using the command `settings.meta(print=TRUE)`.

In order to reset all settings to the default settings of R package meta the command `settings.meta(reset=TRUE)` can be used.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

Examples

```
#
# Get list of settings
#
settings.meta(print=TRUE)

#
# Meta-analyses using default settings of R package meta
#
metabin(10, 20, 15, 20, warn=FALSE)
metaprop(4, 20)
metabin(10, 20, 15, 20, sm="RD", warn=FALSE)
metaprop(4, 20, sm="PLN")
#
# Change default summary measure for R functions metabin and metaprop
#
oldset <- settings.meta(smbin="RD", smprop="PLN")
#
metabin(10, 20, 15, 20, warn=FALSE)
metaprop(4, 20)
#
# Reset settings
#
settings.meta(oldset)

#
# Change level for confidence intervals
#
metagen(1:3, (2:4)/10, sm="MD")
settings.meta(level=0.99, level.comb=0.999)
metagen(1:3, (2:4)/10, sm="MD")

#
# Always print a prediction interval
#
settings.meta(prediction=TRUE)
metagen(1:3, (2:4)/10, sm="MD")

#
```

```
# Try to set unknown argument
#
settings.meta(unknownarg=TRUE)

#
# Reset to default settings of R package meta
#
settings.meta(reset=TRUE)
metabin(10, 20, 15, 20, warn=FALSE)
metaprop(4, 20)
metagen(1:3, (2:4)/10, sm="MD")

#
# Never back transform results (e.g. print log odds ratios instead of
# odds ratios, print transformed correlations/proportions instead of
# correlations/proportions)
#
oldset <- settings.meta(backtransf=FALSE)
metabin(10, 20, 15, 20, warn=FALSE)
metaprop(4, 20)
metacor(c(0.85, 0.7, 0.95), c(20, 40, 10))
settings.meta(oldset)
```

smoking

Smoking example

Description

Meta-analyses on the effect of smoking on mortality risk.

Data have been reconstructed based on the famous Smoking and Health Report to the Surgeon General (Bayne-Jones S et al., 1964). Data sets can be used to evaluate the risk of smoking on overall mortality and lung-cancer deaths, respectively. The person time is attributed such that the rate ratios are equal to the reported mortality ratios implicitly assuming that the data have arisen from a homogeneous age group; more detailed information by age is not available from the report. Note, the group of "non-smokers" actually consists of all participants except those who are smokers of cigarettes only. Information on real non-smokers is not available from the published Smoking and Health Report.

Usage

```
data(smoking)
```

```
data(lungcancer)
```

Format

A data frame with the following columns:

study Study label

participants Total number of participants
d.smokers Number of deaths in smokers' group
py.smokers Person years at risk in smokers' group
d.nonsmokers Number of deaths in non-smokers' group
py.nonsmokers Person years at risk in non-smokers' group

Source

Bayne-Jones S et al. (1964), Smoking and Health: Report of the Advisory Committee to the Surgeon General of the United States. U-23 Department of Health, Education, and Welfare. Public Health Service Publication No. 1103. <http://profiles.nlm.nih.gov/ps/retrieve/ResourceMetadata/NNBBMQ>

See Also

[metainc](#)

Examples

```
data(smoking)

m1 <- metainc(d.smokers, py.smokers,
             d.nonsmokers, py.nonsmokers,
             data=smoking, studlab=study)
print(m1, digits=2)

data(lungcancer)

m2 <- metainc(d.smokers, py.smokers,
             d.nonsmokers, py.nonsmokers,
             data=lungcancer, studlab=study)
print(m2, digits=2)
```

trimfill

Trim-and-fill method to adjust for bias in meta-analysis

Description

Trim-and-fill method for estimating and adjusting for the number and outcomes of missing studies in a meta-analysis.

Usage

```
trimfill(x, ...)

## Default S3 method:
trimfill(x, seTE, left=NULL, ma.fixed=TRUE, type="L", n.iter.max=50,
```

```

sm=NULL, studlab=NULL, level=0.95, level.comb=level,
comb.fixed=FALSE, comb.random=TRUE,
hakn=FALSE, method.tau="DL",
prediction=FALSE, level.predict=level,
backtransf=TRUE,
silent=TRUE, ...)

## S3 method for class 'meta'
trimfill(x, left=NULL, ma.fixed=TRUE, type="L", n.iter.max=50,
         level=x$level, level.comb=x$level.comb,
         comb.fixed=FALSE, comb.random=TRUE,
         hakn=x$hakn, method.tau=x$method.tau,
         prediction=x$prediction, level.predict=x$level.predict,
         backtransf=x$backtransf,
         silent=TRUE, ...)

```

Arguments

x	An object of class meta, or estimated treatment effect in individual studies.
seTE	Standard error of estimated treatment effect.
left	A logical indicating whether studies are supposed to be missing on the left or right side of the funnel plot. If NULL, the linear regression test for funnel plot symmetry (i.e., function metabias(..., method="linreg")) is used to determine whether studies are missing on the left or right side.
ma.fixed	A logical indicating whether a fixed effect or random effects model is used to estimate the number of missing studies.
type	A character indicating which method is used to estimate the number of missing studies. Either "L" or "R".
n.iter.max	Maximum number of iterations to estimate number of missing studies.
sm	An optional character string indicating underlying summary measure, e.g., "RD", "RR", "OR", "ASD", "MD", "SMD"; ignored if x is of class meta.
studlab	An optional vector with study labels; ignored if x is of class meta.
level	The level used to calculate confidence intervals for individual studies. If existing, x\$level is used as value for level; otherwise 0.95 is used.
level.comb	The level used to calculate confidence interval for the pooled estimate. If existing, x\$level.comb is used as value for level.comb; otherwise 0.95 is used.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated.
prediction	A logical indicating whether a prediction interval should be printed.

<code>level.predict</code>	The level used to calculate prediction interval for a new study.
<code>backtransf</code>	A logical indicating whether results should be back transformed in printouts and plots. If <code>backtransf=TRUE</code> , results for <code>sm="OR"</code> are printed as odds ratios rather than log odds ratios and results for <code>sm="ZCOR"</code> are printed as correlations rather than Fisher's z transformed correlations, for example.
<code>silent</code>	A logical indicating whether basic information on iterations shown.
<code>...</code>	other arguments

Details

The trim-and-fill method (Duval, Tweedie 2000a, 2000b) can be used for estimating and adjusting for the number and outcomes of missing studies in a meta-analysis. The method relies on scrutiny of one side of a funnel plot for asymmetry assumed due to publication bias.

Three different methods have been proposed originally to estimate the number of missing studies. Two of these methods (L- and R-estimator) have been shown to perform better in simulations, and are available in this R function (argument `type`).

A fixed effect or random effects model can be used to estimate the number of missing studies (argument `ma.fixed`). Furthermore, a fixed effect and/or random effects model can be used to summaries study results (arguments `comb.fixed` and `comb.random`). Simulation results (Peters et al. 2007) indicate that the fixed-random model, i.e. using a fixed effect model to estimate the number of missing studies and a random effects model to summaries results, (i) performs better than the fixed-fixed model, and (ii) performs no worse than and marginally better in certain situations than the random-random model. Accordingly, the fixed-random model is the default.

An empirical comparison of the trim-and-fill method and the Copas selection model (Schwarzer et al. 2010) indicates that the trim-and-fill method leads to excessively conservative inference in practice. The Copas selection model is available in R package `copas`.

The function `metagen` is called internally.

Value

An object of class `c("metagen", "meta", "trimfill")`. The object is a list containing the following components:

`studlab`, `sm`, `left`, `ma.fixed`, `type`,

`n.iter.max`, `level`, `level.comb`, `level.predict`,

As defined above.

`comb.fixed`, `comb.random`, `prediction`, `hakn`, `method.tau`

`TE`, `seTE` Estimated treatment effect and standard error of individual studies.

`lower`, `upper` Lower and upper confidence interval limits for individual studies.

`zval`, `pval` z-value and p-value for test of treatment effect for individual studies.

`w.fixed`, `w.random`

Weight of individual studies (in fixed and random effects model).

`TE.fixed`, `seTE.fixed`

Estimated overall treatment effect and standard error (fixed effect model).

TE.random, seTE.random	Estimated overall treatment effect and standard error (random effects model).
seTE.predict	Standard error utilised for prediction interval.
lower.predict, upper.predict	Lower and upper limits of prediction interval.
k	Number of studies combined in meta-analysis.
Q	Heterogeneity statistic Q.
tau	Square-root of between-study variance.
method	Pooling method: "Inverse".
call	Function call.
n.iter	Actual number of iterations to estimate number of missing studies.
trimfill	A logical vector indicating studies that have been added by trim-and-fill method.
df.hakn	Degrees of freedom for test of treatment effect for Hartung-Knapp method (only if hakn=TRUE).
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
label.e	Label for experimental group.
label.c	Label for control group.
label.left	Graph label on left side of forest plot.
label.right	Graph label on right side of forest plot.
k0	Number of studies added by trim-and-fill.
n.e	Number of observations in experimental group (only for object x of class metabin or metacont).
n.c	Number of observations in control group (only for object x of class metabin or metacont).
event.e	Number of events in experimental group (only for object x of class metabin).
event.c	Number of events in control group (only for object x of class metabin).
mean.e	Estimated mean in experimental group (only for object x of class metacont).
sd.e	Standard deviation in experimental group (only for object x of class metacont).
mean.c	Estimated mean in control group (only for object x of class metacont).
sd.c	Standard deviation in control group (only for object x of class metacont).
n	Number of observations (only for object x of class metaprop).
event	Number of events (only for object x of class metaprop).
cor	Correlation (only for object x of class metacor).
class.x	Main class of object x (e.g. 'metabin' or 'metacont').
version	Version of R package meta used to create object.

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

References

Duval S & Tweedie R (2000a), A nonparametric "Trim and Fill" method of accounting for publication bias in meta-analysis. *Journal of the American Statistical Association*, **95**, 89–98.

Duval S & Tweedie R (2000b), Trim and Fill: A simple funnel-plot-based method of testing and adjusting for publication bias in meta-analysis. *Biometrics*, **56**, 455–463.

Peters JL, Sutton AJ, Jones DR, Abrams KR, Rushton L (2007), Performance of the trim and fill method in the presence of publication bias and between-study heterogeneity. *Statistics in Medicine*, **10**, 4544–62.

Schwarzer G, Carpenter J, Rücker G (2010), Empirical evaluation suggests Copas selection model preferable to trim-and-fill method for selection bias in meta-analysis. *Journal of Clinical Epidemiology*, **63**, 282–8.

See Also

[metagen](#), [metabias](#), [funnel](#)

Examples

```
data(Fleiss93)
meta1 <- metabin(event.e, n.e, event.c, n.c,
                data=Fleiss93, sm="OR")
tf1 <- trimfill(meta1)
summary(tf1)
funnel(tf1)
funnel(tf1, pch=ifelse(tf1$trimfill, 1, 16),
       level=0.9, comb.random=FALSE)
#
# Use log odds ratios on x-axis
#
funnel(tf1, backtransf=FALSE)
funnel(tf1, pch=ifelse(tf1$trimfill, 1, 16),
       level=0.9, comb.random=FALSE, backtransf=FALSE)

trimfill(meta1$TE, meta1$seTE, sm=meta1$sm)
```

update.meta

Update a meta-analysis object

Description

Update an existing meta-analysis object.

Usage

```
## S3 method for class 'meta'
update(object,
       data=object$data, subset=object$subset,
       studlab=object$data$.studlab,
       method=object$method, sm=object$sm,
       incr=object$incr, allincr=object$allincr,
       addincr=object$addincr, allstudies=object$allstudies,
       MH.exact=object$MH.exact, RR.cochrane=object$RR.cochrane,
       level=object$level, level.comb=object$level.comb,
       comb.fixed=object$comb.fixed, comb.random=object$comb.random,
       hakn=object$hakn, method.tau=object$method.tau,
       tau.preset=object$tau.preset,
       TE.tau=object$TE.tau, tau.common=object$tau.common,
       prediction=object$prediction, level.predict=object$level.predict,
       method.bias=object$method.bias, backtransf = object$backtransf,
       title=object$title, complab=object$complab, outclab=object$outclab,
       label.e=object$label.e, label.c=object$label.c,
       label.left=object$label.left, label.right=object$label.right,
       n.e=object$n.e, n.c=object$n.c,
       pooledvar=object$pooledvar, method.smd=object$method.smd,
       sd.glass=object$sd.glass, exact.smd=object$exact.smd, method.ci=object$method.ci,
       byvar=object$byvar, bylab=object$bylab, print.byvar=object$print.byvar,
       print.CMH=object$print.CMH, keepdata=TRUE,
       left=object$left, ma.fixed=object$ma.fixed,
       type=object$type, n.iter.max=object$n.iter.max,
       warn=object$warn, ...)
```

Arguments

object	An object of class meta.
data	Dataset.
subset	Subset.
studlab	Study label.
method	A character string indicating which method is to be used for pooling of studies. One of "Inverse", "MH", or "Peto", can be abbreviated. (only for metabin object)
sm	A character string indicating which summary measure is used for pooling.
incr	Could be either a numerical value which is added to each cell frequency for studies with a zero cell count or the character string "TA" which stands for treatment arm continuity correction.
allincr	A logical indicating if incr is added to each cell frequency of all studies if at least one study has a zero cell count. If FALSE (default), incr is added only to each cell frequency of studies with a zero cell count.
addincr	A logical indicating if incr is added to each cell frequency of all studies irrespective of zero cell counts.

allstudies	A logical indicating if studies with zero or all events in both groups are to be included in the meta-analysis (applies only if sm is equal to "RR" or "OR").
MH.exact	A logical indicating if incr is not to be added to all cell frequencies for studies with a zero cell count to calculate the pooled estimate based on the Mantel-Haenszel method.
RR.cochrane	A logical indicating if 2*incr instead of 1*incr is to be added to n.e and n.c in the calculation of the risk ratio (i.e., sm="RR") for studies with a zero cell. This is used in RevMan 5, the Cochrane Collaboration's program for preparing and maintaining Cochrane reviews.
level	The level used to calculate confidence intervals for individual studies.
level.comb	The level used to calculate confidence intervals for pooled estimates.
comb.fixed	A logical indicating whether a fixed effect meta-analysis should be conducted.
comb.random	A logical indicating whether a random effects meta-analysis should be conducted.
hakn	A logical indicating whether the method by Hartung and Knapp should be used to adjust test statistics and confidence intervals.
method.tau	A character string indicating which method is used to estimate the between-study variance τ^2 . Either "DL", "PM", "REML", "ML", "HS", "SJ", "HE", or "EB", can be abbreviated. See function metagen .
tau.preset	Prespecified value for the square-root of the between-study variance τ^2 .
TE.tau	Overall treatment effect used to estimate the between-study variance τ^2 .
tau.common	A logical indicating whether tau-squared should be the same across subgroups.
prediction	A logical indicating whether a prediction interval should be printed.
level.predict	The level used to calculate prediction interval for a new study.
method.bias	A character string indicating which test for funnel plot asymmetry is to be used. Either "rank", "linreg", "mm", "count", "score", or "peters", can be abbreviated. See function metabias
backtransf	A logical indicating whether results should be back transformed in printouts and plots. If backtransf=TRUE, results for sm="OR" are printed as odds ratios rather than log odds ratios and results for sm="ZCOR" are printed as correlations rather than Fisher's z transformed correlations, for example.
title	Title of meta-analysis / systematic review.
complab	Comparison label.
outclab	Outcome label.
label.e	Label for experimental group.
label.c	Label for control group.
label.left	Graph label on left side of forest plot.
label.right	Graph label on right side of forest plot.
n.e	Number of observations in experimental group. (only for metagen object)
n.c	Number of observations in control group. (only for metagen object)

pooledvar	A logical indicating if a pooled variance should be used for the mean difference (only for metacont object with sm="MD").
method.smd	A character string indicating which method is used to estimate the standardised mean difference (only for metacont object with sm="SMD"). Either "Hedges" for Hedges' g (default), "Cohen" for Cohen's d, or "Glass" for Glass' delta, can be abbreviated.
sd.glass	A character string indicating which standard deviation is used in the denominator for Glass' method to estimate the standardised mean difference (only for metacont object with sm="SMD"). Either "control" using the standard deviation in the control group (sd.c) or "experimental" using the standard deviation in the experimental group (sd.e), can be abbreviated.
exact.smd	A logical indicating whether exact formulae should be used in estimation of the standardised mean difference and its standard error.
method.ci	A character string indicating which method is used to calculate confidence intervals for individual studies. Either "CP", "WS", "WSCC", "AC", "SA", "SACC", or "NASm", can be abbreviated. See function metaprop .
byvar	An optional vector containing grouping information (must be of same length as event.e).
bylab	A character string with a label for the grouping variable.
print.byvar	A logical indicating whether the name of the grouping variable should be printed in front of the group labels.
print.CMH	A logical indicating whether result of the Cochran-Mantel-Haenszel test for overall effect should be printed.
keepdata	A logical indicating whether original data (set) should be kept in meta object.
left	A logical indicating whether studies are supposed to be missing on the left or right side of the funnel plot. If NULL, the linear regression test for funnel plot symmetry (i.e., function metabias(..., method="linreg")) is used to determine whether studies are missing on the left or right side.
ma.fixed	A logical indicating whether a fixed effect or random effects model is used to estimate the number of missing studies.
type	A character indicating which method is used to estimate the number of missing studies. Either "L" or "R".
n.iter.max	Maximum number of iterations to estimate number of missing studies.
warn	A logical indicating whether warnings should be printed (e.g., if incr is added to studies with zero cell frequencies).
...	Additional arguments (ignored at the moment).

Details

Wrapper function to update an existing meta-analysis object which was created with R function [metabin](#), [metacont](#), [metagen](#), [metacor](#), [metainc](#), or [metaprop](#).

This function can also be used for objects of class 'trimfill', 'metacum', and 'metainf'.

More details on function arguments are available in help files of respective R functions, i.e. [metabin](#), [metacont](#), ...

Value

An object of class "meta" and "metabin", "metacont", "metagen", "metaprop", or "metacor".

Author(s)

Guido Schwarzer <sc@imbi.uni-freiburg.de>

See Also

[metabin](#), [metacont](#), [metagen](#), [metaprop](#), [metacor](#)

Examples

```
data(Fleiss93cont)
meta1 <- metacont(n.e, mean.e, sd.e, n.c, mean.c, sd.c,
                 data=Fleiss93cont, sm="SMD", studlab=study)
meta1

# Change summary measure (from 'SMD' to 'MD')
#
update(meta1, sm="MD")

# Restrict analysis to subset of studies
#
update(meta1, subset=1:2)

# Use different levels for confidence intervals
#
meta2 <- update(meta1, level=0.66, level.comb=0.99)
print(meta2, digits=2)
forest(meta2)
```

Index

- *Topic **datagen**
 - read.mtv, 100
 - read.rm5, 102
- *Topic **datasets**
 - amlodipine, 2
 - cisapride, 10
 - Fleiss93, 12
 - Fleiss93cont, 13
 - Olkin95, 92
 - smoking, 107
- *Topic **hplot**
 - baujat, 5
 - bubble, 7
 - forest, 14
 - funnel, 27
 - labbe, 31
- *Topic **htest**
 - ci, 9
 - metabias, 34
 - metabin, 38
 - metacont, 46
 - metacor, 53
 - metacr, 60
 - metacum, 62
 - metagen, 64
 - metainc, 71
 - metainf, 78
 - metaprop, 80
 - trimfill, 108
 - update.meta, 112
- *Topic **print**
 - as.data.frame.meta, 3
 - metareg, 90
 - print.meta, 93
 - print.rm5, 98
- amlodipine, 2
- as.data.frame.meta, 3
- baujat, 5
- bubble, 7, 91
- ci, 9
- cilayout (print.meta), 93
- cisapride, 10
- dev.copy2eps, 22
- dev.copy2pdf, 22
- Fleiss93, 12, 13
- Fleiss93_CR (read.rm5), 102
- Fleiss93cont, 13
- forest, 14
- forest.meta, 4, 83
- funnel, 27, 37, 45, 112
- funnel.meta, 37
- galbraith (funnel), 27
- gpar, 20, 21
- grid.xaxis, 18
- labbe, 31
- lungcancer (smoking), 107
- metabias, 30, 34, 39, 45, 47, 55, 65, 72, 82, 98, 112, 114
- metabias.meta, 99
- metabias.rm5 (print.rm5), 98
- metabin, 4, 11, 23, 30, 33, 37, 38, 52, 61, 64, 70, 77, 80, 95, 97, 101, 105, 106, 116
- metacont, 3, 4, 23, 37, 45, 46, 59, 61, 64, 70, 80, 87, 95, 97, 101, 105, 106, 116
- metacor, 23, 53, 95, 106, 116
- metacr, 60, 105, 106
- metacum, 62
- metagen, 4, 6, 9, 23, 30, 37, 45, 52, 59, 61, 64, 87, 91, 95, 97, 101, 105, 106, 112, 114, 116
- metainc, 71, 106, 108
- metainf, 6, 9, 78
- metaprop, 23, 80, 95, 106, 115, 116

metareg, 90

Olkin95, 92

par, 6, 18

print.meta, 40, 45, 48, 55, 59, 64, 66, 70, 73,
77, 80, 83, 87, 93

print.metabias (print.meta), 93

print.rm5, 98

print.summary.meta, 83

print.summary.meta (print.meta), 93

print.summary.rm5 (print.rm5), 98

radial (funnel), 27

read.mtv, 100

read.rm5, 61, 99, 102

rma.uni, 90

settings.meta, 22, 40, 48, 55, 66, 73, 83, 105

smoking, 107

summary.meta, 91, 99

summary.meta (print.meta), 93

summary.rm5 (print.rm5), 98

text, 6, 8

trimfill, 108

update.meta, 23, 41, 45, 49, 52, 55, 59, 66,
70, 73, 77, 83, 87, 95, 97, 112