

Package ‘ECctmc’

August 12, 2016

Type Package

Title Simulation from Endpoint-Conditioned Continuous Time Markov Chains

Version 0.2.2

Date 2016-08-12

URL <https://github.com/fintzij/ECctmc>

BugReports <https://github.com/fintzij/ECctmc/issues>

Description Draw sample paths for endpoint-conditioned continuous time Markov chains via modified rejection sampling or uniformization.

License GPL-3

LazyData TRUE

Imports Rcpp (>= 0.12.3)

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 5.0.1

Suggests knitr, rmarkdown, testthat

VignetteBuilder knitr

NeedsCompilation yes

Author Jon Fintzi [aut, cre]

Maintainer Jon Fintzi <fintzij@uw.edu>

Repository CRAN

Date/Publication 2016-08-12 23:49:38

R topics documented:

sample_path	2
sample_path_mr	2
sample_path_unif	3
sample_path_unif2	4

Index	5
--------------	----------

sample_path	<i>Sample path from the distribution of an endpoint-conditioned CTMC.</i>
-------------	---

Description

Sample path from the distribution of an endpoint-conditioned CTMC.

Usage

```
sample_path(a, b, t0, t1, Q, method = "mr", npaths = 1, eigen_vals = NULL,
            eigen_vecs = NULL, inverse_vecs = NULL)
```

Arguments

a, b	States at the left and right endpoints of the interval, given as row numbers of the CTMC rate matrix
t0, t1	Times for the left and right endpoints of the interval.
Q	CTMC rate matrix.
method	Either "mr" corresponding to modified rejection sampling, or "unif" for uniformization.
npaths	optional argument for the number of sample paths to simulate.
eigen_vals	optional vector of eigen values of Q.
eigen_vecs	optional matrix of eigen vectors of Q.
inverse_vecs	optional inverse of the eigen vector matrix.

Value

sample_path returns either a matrix with a sample path or a list of matrices of sample paths.

Examples

```
sample_path(1, 2, 0, 5, matrix(c(-0.49, 0.49, 0.51, -0.51), nrow = 2, byrow = TRUE))
```

sample_path_mr	<i>Simulate a sample path from an endpoint conditioned CTMC by modified rejection sampling.</i>
----------------	---

Description

Simulate a sample path from an endpoint conditioned CTMC by modified rejection sampling.

Usage

```
sample_path_mr(a, b, t0, t1, Q)
```

Arguments

a, b	States at the interval endpoints, provided as integers corresponding to rows of the CTMC rate matrix.
t0, t1	times of the interval endpoints
Q	CTMC rate matrix

Value

matrix whose first column is the sequence of transition times bookended by interval endpoints, and whose second column is the sequence of states

sample_path_unif	<i>Simulate a sample path from an endpoint conditioned CTMC by uniformization.</i>
------------------	--

Description

Simulate a sample path from an endpoint conditioned CTMC by uniformization.

Usage

```
sample_path_unif(a, b, t0, t1, Q)
```

Arguments

a, b	States at the interval endpoints, provided as integers corresponding to rows of the CTMC rate matrix.
t0, t1	times of the interval endpoints
Q	CTMC rate matrix

Value

matrix whose first column is the sequence of transition times bookended by interval endpoints, and whose second column is the sequence of states

sample_path_unif2 *Simulate a sample path from an endpoint conditioned CTMC by uniformization using pre-computed eigen-values.*

Description

Simulate a sample path from an endpoint conditioned CTMC by uniformization using pre-computed eigen-values.

Usage

```
sample_path_unif2(a, b, t0, t1, Q, eigen_vals, eigen_vecs, inverse_vecs)
```

Arguments

a, b	States at the interval endpoints, provided as integers corresponding to rows of the CTMC rate matrix.
t0, t1	times of the interval endpoints
Q	CTMC rate matrix
eigen_vals	vector of eigen values of Q.
eigen_vecs	matrix of eigen vectors of Q.
inverse_vecs	inverse of the eigen vector matrix.

Value

matrix whose first column is the sequence of transition times bookended by interval endpoints, and whose second column is the sequence of states

Index

sample_path, 2
sample_path_mr, 2
sample_path_unif, 3
sample_path_unif2, 4