

Package ‘fuzzr’

August 29, 2016

Type Package

Title Fuzz-Test R Functions

Version 0.1.0

Description Test function arguments with a wide array of inputs, and produce reports summarizing messages, warnings, errors, and returned values.

License MIT + file LICENSE

LazyData TRUE

RoxygenNote 5.0.1

Imports assertthat, progress, purrr, tidyr

Suggests testthat, knitr, rmarkdown

VignetteBuilder knitr

URL <https://github.com/mdlincoln/fuzzr>

BugReports <https://github.com/mdlincoln/fuzzr/issues>

NeedsCompilation no

Author Matthew Lincoln [aut, cre]

Maintainer Matthew Lincoln <matthew.d.lincoln@gmail.com>

Repository CRAN

Date/Publication 2016-06-27 07:00:02

R topics documented:

as.data.frame.fuzz_results	2
fuzzr	2
fuzz_function	3
fuzz_results	4
test_all	5

Index	7
--------------	----------

```
as.data.frame.fuzz_results
```

Summarize fuzz test results as a data frame

Description

Summarize fuzz test results as a data frame

Usage

```
## S3 method for class 'fuzz_results'
as.data.frame(x, ..., delim = "; ")
```

Arguments

x	Object returned by fuzz_function .
...	Additional arguments to be passed to or from methods.
delim	The delimiter to use for fields like messages or warnings in which there may be multiple results.

Value

A data frame with the following columns:

fuzz_input	The name of the fuzz test performed.
output	Delimited outputs to the command line from the process, if applicable.
messages	Delimited messages, if applicable.
warnings	Delimited warnings, if applicable.
errors	Error returned, if applicable.
value_classes	Delimited classes of the object returned by the function, if applicable
results_index	Index of x from which the summary was produced.

```
fuzzr
```

Fuzz-Test R Functions

Description

Test function arguments with a wide array of inputs, and produce reports summarizing messages, warnings, errors, and returned values.

fuzz_function	<i>Fuzz-test a function</i>
---------------	-----------------------------

Description

Evaluate how a function responds to unexpected or non-standard inputs.

Usage

```
fuzz_function(fun, arg_name, ..., tests = test_all(), check_args = TRUE,
  test_delim = ";", progress = interactive())
```

```
p_fuzz_function(fun, .l, check_args = TRUE, test_delim = ";",
  progress = interactive())
```

Arguments

fun	A function.
arg_name	Quoted name of the argument to fuzz test.
...	Other non-dynamic arguments to pass to fun. These will be repeated for every one of the tests.
tests	Which fuzz tests to run. Accepts a named list of inputs, defaulting to test_all .
check_args	Check if arg_name and any arguments passed as ... are accepted by fun. Set to FALSE if you need to pass arguments to a function that itself accepts arguments via ...
test_delim	The delimiter to use in separating argument names in the named list of fuzz test combinations. Note that this value will be passed to separate when <code>link{as.data.frame.fuzz_results}</code> is called, which will treat it as a regex pattern. Therefore, using reserved regex characters may result in unexpected behavior.
progress	Show a progress bar while running tests?
.l	A named list of tests.

Details

fuzz_function provides a simple interface to fuzz test a single argument of a function by passing the function, name of the argument, static values of other required arguments, and a named list of test values.

p_fuzz_function takes a nested list of arguments paired with lists of tests to run on each argument, and will evaluate every combination of argument and provided test.

Value

A fuzz_results object.

Note

The user will be asked to confirm executing the function if the combinations of potential tests exceeds 500,000.

See Also

[as.data.frame.fuzz_results](#) and [fuzz_value](#) to access fuzz test results.

Examples

```
# Evaluate the 'formula' argument of lm, passing additional required variables
fr <- fuzz_function(lm, "formula", data = iris)

# When evaluating a function that takes ..., set check_args to FALSE
fr <- fuzz_function(paste, "x", check_args = FALSE)

# Pass tests to multiple arguments via a named list
test_args <- list(
  data = test_df(),
  subset = test_all(),
  # Specify custom tests with a new named list
  formula = list(all_vars = Sepal.Length ~ ., one_var = mpg ~ .))
fr <- p_fuzz_function(lm, test_args)
```

fuzz_results

Access individual fuzz test results

Description

Access individual fuzz test results

Usage

```
fuzz_value(fr, index)
```

```
fuzz_call(fr, index)
```

Arguments

fr	fuzz_results object
index	The test index (by position) to access. Same as the results_index in the data frame returned by as.data.frame.fuzz_results .

Functions

- `fuzz_value`: Access the object returned by the fuzz test
- `fuzz_call`: Access the call used for the fuzz test

test_all	<i>Fuzz test inputs</i>
----------	-------------------------

Description

test_all returns a named list concatenating all the available tests specified below.

Usage

```
test_all()
test_char()
test_int()
test_dbl()
test_lgl()
test_fctr()
test_date()
test_raw()
test_df()
```

Functions

- test_char: Character vectors
 - char_empty: character(0)
 - char_single: "a"
 - char_single_blank: ""
 - char_multiple: c("a", "b", "c")
 - char_multiple_blank: c("a", "b", "c", "")
 - char_with_na: c("a", "b", NA)
- test_int: Integer vectors
 - int_empty: integer(0)
 - int_single: 1L
 - int_multiple: 1:3
 - int_with_na: c(1L, 2L, NA)
- test_dbl: Double vectors
 - dbl_empty: numeric(0)
 - dbl_single: 1.5

- dbl_mutliple: c(1.5, 2.5, 3.5)
- dbl_with_na: c(1.5, 2.5, NA)
- test_lgl: Logical vectors
 - lgl_empty: logical(0)
 - lgl_single: TRUE
 - lgl_mutliple: c(TRUE, FALSE, FALSE)
 - lgl_with_na: c(TRUE, NA, FALSE)
- test_fctr: Factor vectors
 - fctr_empty: structure(integer(0), .Label = character(0), class = "factor")
 - fctr_single: structure(1L, .Label = "a", class = "factor")
 - fctr_multiple: structure(1:3, .Label = c("a", "b", "c"), class = "factor")
 - fctr_with_na: structure(c(1L, 2L, NA), .Label = c("a", "b"), class = "factor")
 - fctr_missing_levels: structure(1:3, .Label = c("a", "b", "c", "d"), class = "factor")
- test_date: Date vectors
 - date_single: as.Date("2001-01-01")
 - date_multiple: as.Date(c("2001-01-01", "1950-05-05"))
 - date_with_na: as.Date(c("2001-01-01", NA, "1950-05-05"))
- test_raw: Raw vectors
 - raw_empty: raw(0)
 - raw_char: as.raw(0x62)
- test_df: Data frames
 - df_complete: datasets::iris
 - df_empty: data.frame(NULL)
 - df_one_row: datasets::iris[1,]
 - df_one_col: datasets::iris[, 1]
 - df_with_na: iris with several NAs added to each column.

Index

`as.data.frame.fuzz_results`, [2](#), [4](#)

`fuzz_call (fuzz_results)`, [4](#)

`fuzz_function`, [2](#), [3](#)

`fuzz_results`, [4](#)

`fuzz_value`, [4](#)

`fuzz_value (fuzz_results)`, [4](#)

`fuzzr`, [2](#)

`fuzzr-package (fuzzr)`, [2](#)

`p_fuzz_function (fuzz_function)`, [3](#)

`regex`, [3](#)

`separate`, [3](#)

`test_all`, [3](#), [5](#)

`test_char (test_all)`, [5](#)

`test_date (test_all)`, [5](#)

`test_dbl (test_all)`, [5](#)

`test_df (test_all)`, [5](#)

`test_fctr (test_all)`, [5](#)

`test_int (test_all)`, [5](#)

`test_lgl (test_all)`, [5](#)

`test_raw (test_all)`, [5](#)