

Package ‘gamlss.dist’

October 18, 2016

Title Distributions to be Used for GAMLSS Modelling

Version 5.0-0

Date 2016-10-11

Author Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby with contributions from Calliope Akantziliotou, Gillian Heller, Raydonal Ospina <rospina@ime.usp.br>, Nicoletta Motpan, Fiona McElduff, Vlasios Voudouris, Majid Djennad, Marco Enea and Alexios Ghalanos.

Maintainer Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

Depends R (>= 2.15.0), MASS, graphics, stats, methods

Description The different distributions used for the response variables in GAMLSS modelling.

License GPL-2 | GPL-3

URL <http://www.gamlss.org/>

NeedsCompilation yes

Repository CRAN

Date/Publication 2016-10-18 23:49:24

R topics documented:

gamlss.dist-package	3
BB	4
BCCG	7
BCPE	9
BCT	12
BE	14
BEINF	16
BEOI	20
BEZI	23
BI	25
checklink	27

DEL	28
DPO	30
EGB2	32
exGAUS	34
EXP	36
flexDist	38
GA	39
gamlss.family	41
GB1	44
GB2	46
GE	48
gen.Family	50
GEOM	52
GG	54
GIG	56
GT	58
GU	59
hazardFun	61
IG	62
IGAMMA	64
JSU	66
JSUo	68
LG	70
LNO	72
LO	75
LOGITNO	77
make.link.gamlss	78
MN3	82
NBF	84
NBI	86
NBII	88
NET	90
NO	91
NO2	93
NOF	95
PARETO2	97
PE	99
PIG	101
PO	103
RG	105
RGE	107
SEP	109
SEP1	111
SHASH	113
SI	117
SICHEL	119
SN1	121
SN2	123

ST1	124
TF	128
WARING	130
WEI	131
WEI2	133
WEI3	135
YULE	137
ZABB	139
ZABI	141
ZAGA	143
ZAIG	145
ZANBI	147
ZAP	149
ZIP	150
ZIP2	152
ZIPIG	154

Index	156
--------------	------------

gamlss.dist-package *The GAMLSS distributions*

Description

This package contains all distributions to be used for GAMLSS models. Each distributions has its probability function, d , its commutative probability function, p , the inverse of the commutative probability function, q , its random generation function, r , and also the `gamlss.family` generating function

Details

Package: `gamlss.dist`
Type: Package
Version: 1.5.0
Date: 2006-12-13
License: GPL (version 2 or later)

This package is design to be used with the package **gamlss** but the d , p , q and r functions can be used separately.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby <r.rigby@londonmet.ac.uk> with contributions from Calliope Akantziliotou and Raydonal Ospina <rospina@ime.usp.br>.

Maintainer: Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2003) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>)
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
plot(function(y) dSICHEL(y, mu=10, sigma = 0.1 , nu=1 ), from=0, to=30, n=30+1, type="h") # pdf
# cdf plot
PPP <- par(mfrow=c(2,1))
plot(function(y) pSICHEL(y, mu=10, sigma =0.1, nu=1 ), from=0, to=30, n=30+1, type="h") # cdf
cdf<-pSICHEL(0:30, mu=10, sigma=0.1, nu=1)
sfun1 <- stepfun(1:30, cdf, f = 0)
plot(sfun1, xlim=c(0,30), main="cdf(x)")
par(PPP)
```

BB

Beta Binomial Distribution For Fitting a GAMLSS Model

Description

This function defines the beta binomial distribution, a two parameter distribution, for a `gamlss.family` object to be used in a GAMLSS fitting using the function `gamlss()`

Usage

```
BB(mu.link = "logit", sigma.link = "log")
dBB(x, mu = 0.5, sigma = 1, bd = 10, log = FALSE)
pBB(q, mu = 0.5, sigma = 1, bd = 10, lower.tail = TRUE,
    log.p = FALSE)
qBB(p, mu = 0.5, sigma = 1, bd = 10, lower.tail = TRUE,
    log.p = FALSE, fast = FALSE)
rBB(n, mu = 0.5, sigma = 1, bd = 10, fast = FALSE)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the <code>mu</code> parameter. Other links are "probit" and "cloglog" (complementary log-log)
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse", "identity" and "sqrt"
<code>mu</code>	vector of positive probabilities
<code>sigma</code>	the dispersion parameter
<code>bd</code>	vector of binomial denominators
<code>p</code>	vector of probabilities
<code>x,q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>fast</code>	a logical variable if <code>fast=TRUE</code> the <code>dB</code> function is used in the calculation of the inverse c.d.f function. This is faster to the default <code>fast=FALSE</code> , where the <code>pBB{}</code> is used, but not always consistent with the results obtained from <code>pBB()</code> , for example if <code>p <- pBB(c(0,1,2,3,4,5), mu=.5, sigma=1, bd=5)</code> do not ensure that <code>qBB(p, mu=.5, sigma=1, bd=5)</code> will be <code>c(0,1,2,3,4,5)</code>

Details

Definition file for beta binomial distribution.

$$f(y|\mu, \sigma) = \frac{\Gamma(n+1)}{\Gamma(y+1)\Gamma(n-y+1)} \frac{\Gamma(\frac{1}{\sigma})\Gamma(y + \frac{\mu}{\sigma})\Gamma[n + \frac{(1-\mu)}{\sigma} - y]}{\Gamma(n + \frac{1}{\sigma})\Gamma(\frac{\mu}{\sigma})\Gamma(\frac{1-\mu}{\sigma})}$$

for $y = 0, 1, 2, \dots, n$, $0 < \mu < 1$ and $\sigma > 0$. For $\mu = 0.5$ and $\sigma = 0.5$ the distribution is uniform.

Value

Returns a `gamlss.family` object which can be used to fit a Beta Binomial distribution in the `gamlss()` function.

Warning

The functions `pBB` and `qBB` are calculated using a laborious procedure so they are relatively slow.

Note

The response variable should be a matrix containing two columns, the first with the count of successes and the second with the count of failures. The parameter `mu` represents a probability parameter with limits $0 < \mu < 1$. $n\mu$ is the mean of the distribution where `n` is the binomial denominator. $\{n\mu(1-\mu)[1 + (n-1)\sigma/(\sigma+1)]\}^{0.5}$ is the standard deviation of the Beta Binomial distribution. Hence `sigma` is a dispersion type parameter

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Kalliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BI](#),

Examples

```
# BB()# gives information about the default links for the Beta Binomial distribution
#plot the pdf
plot(function(y) dBB(y, mu = .5, sigma = 1, bd =40), from=0, to=40, n=40+1, type="h")
#calculate the cdf and plotting it
ppBB <- pBB(seq(from=0, to=40), mu=.2 , sigma=3, bd=40)
plot(0:40,ppBB, type="h")
#calculating quantiles and plotting them
qqBB <- qBB(ppBB, mu=.2 , sigma=3, bd=40)
plot(qqBB~ ppBB)
# when the argument fast is useful
p <- pBB(c(0,1,2,3,4,5), mu=.01 , sigma=1, bd=5)
qBB(p, mu=.01 , sigma=1, bd=5, fast=TRUE)
# 0 1 1 2 3 5
qBB(p, mu=.01 , sigma=1, bd=5, fast=FALSE)
# 0 1 2 3 4 5
# generate random sample
tN <- table(Ni <- rBB(1000, mu=.2, sigma=1, bd=20))
r <- barplot(tN, col='lightblue')
# fitting a model
# library(gamlss)
#data(aep)
# fits a Beta-Binomial model
#h<-gamlss(y~ward+loglos+year, sigma.formula=~year+ward, family=BB, data=aep)
```

BCCG	<i>Box-Cox Cole and Green distribution (or Box-Cox normal) for fitting a GAMLSS</i>
------	---

Description

The function BCCG defines the Box-Cox Cole and Green distribution (Box-Cox normal), a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dBCCG`, `pBCCG`, `qBCCG` and `rBCCG` define the density, distribution function, quantile function and random generation for the specific parameterization of the Box-Cox Cole and Green distribution. [The function `BCCGuntr()` is the original version of the function suitable only for the untruncated Box-Cox Cole and Green distribution See Cole and Green (1992) and Rigby and Stasinopoulos (2003a,2003b) for details. The function `BCCGo` is identical to `BCCG` but with `log link` for `mu`.

Usage

```
BCCG(mu.link = "identity", sigma.link = "log", nu.link = "identity")
BCCGo(mu.link = "log", sigma.link = "log", nu.link = "identity")
BCCGuntr(mu.link = "identity", sigma.link = "log", nu.link = "identity")
dBCCG(x, mu = 1, sigma = 0.1, nu = 1, log = FALSE)
pBCCG(q, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
qBCCG(p, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
rBCCG(n, mu = 1, sigma = 0.1, nu = 1)
dBCCGo(x, mu = 1, sigma = 0.1, nu = 1, log = FALSE)
pBCCGo(q, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
qBCCGo(p, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
rBCCGo(n, mu = 1, sigma = 0.1, nu = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter, other links are "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other links are "inverse", "identity" and "own"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter, other links are "inverse", "log" and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The probability distribution function of the untruncated Box-Cox Cole and Green distribution, `BCCGuntr`, is defined as

$$f(y|\mu, \sigma, \nu) = \frac{1}{\sqrt{2\pi}\sigma} \frac{y^{\nu-1}}{\mu^\nu} \exp\left(-\frac{z^2}{2}\right)$$

where if $\nu \neq 0$ then $z = [(y/\mu)^\nu - 1]/(\nu\sigma)$ else $z = \log(y/\mu)/\sigma$, for $y > 0$, $\mu > 0$, $\sigma > 0$ and $\nu = (-\infty, +\infty)$.

The Box-Cox Cole and Green distribution, BCCG, adjusts the above density $f(y|\mu, \sigma, \nu)$ for the truncation resulting from the condition $y > 0$. See Rigby and Stasinopoulos (2003a,2003b) for details.

Value

`BCCG()` returns a `gamlss.family` object which can be used to fit a Cole and Green distribution in the `gamlss()` function. `dBCCG()` gives the density, `pBCCG()` gives the distribution function, `qBCCG()` gives the quantile function, and `rBCCG()` generates random deviates.

Warning

The `BCCGuntr` distribution may be unsuitable for some combinations of the parameters (mainly for large σ) where the integrating constant is less than 0.99. A warning will be given if this is the case. The BCCG distribution is suitable for all combinations of the distributional parameters within their range [i.e. $\mu > 0$, $\sigma > 0$, $\nu = (-\infty, +\infty)$]

Note

μ is the median of the distribution σ is approximately the coefficient of variation (for small values of σ), and ν controls the skewness.

The BCCG distribution is suitable for all combinations of the parameters within their ranges [i.e. $\mu > 0$, $\sigma > 0$, and $\nu = (-\infty, \infty)$]

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Kalliope Akantziliotou

References

- Cole, T. J. and Green, P. J. (1992) Smoothing reference centile curves: the LMS method and penalized likelihood, *Statist. Med.* **11**, 1305–1319
- Rigby, R. A. and Stasinopoulos, D. M. (2004). Smooth centile curves for skew and kurtotic data modelled using the Box-Cox Power Exponential distribution. *Statistics in Medicine*, **23**: 3053-3076.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Rigby, R.A. Stasinopoulos, D.M. (2006). Using the Box-Cox t distribution in GAMLSS to model skewness and kurtosis. to appear in *Statistical Modelling*.

Stasinopoulos D. M., Rigby R.A. and Akantziotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCPE](#), [BCT](#)

Examples

```
BCCG() # gives information about the default links for the Cole and Green distribution
# library(gamlss)
#data(abdom)
#h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=BCCG, data=abdom)
#plot(h)
plot(function(x) dBCCG(x, mu=5,sigma=.5,nu=-1), 0.0, 20,
      main = "The BCCG density mu=5,sigma=.5,nu=-1")
plot(function(x) pBCCG(x, mu=5,sigma=.5,nu=-1), 0.0, 20,
      main = "The BCCG cdf mu=5, sigma=.5, nu=-1")
```

BCPE

Box-Cox Power Exponential distribution for fitting a GAMLSS

Description

This function defines the Box-Cox Power Exponential distribution, a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dBCE`, `pBCE`, `qBCE` and `rBCE` define the density, distribution function, quantile function and random generation for the Box-Cox Power Exponential distribution. The function `checkBCE` can be used, typically when a BCE model is fitted, to check whether there exit a turning point of the distribution close to zero. It give the number of values of the response below their minimum turning point and also the maximum probability of the lower tail below minimum turning point. [The function `Biventer()` is the original version of the function suitable only for the untruncated BCE distribution.] See Rigby and Stasinopoulos (2003) for details. The function `BCEo` is identical to BCE but with log link for mu.

Usage

```
BCPE(mu.link = "identity", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
BCEo(mu.link = "log", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
BCEuntr(mu.link = "identity", sigma.link = "log", nu.link = "identity",
         tau.link = "log")
dBCE(x, mu = 5, sigma = 0.1, nu = 1, tau = 2, log = FALSE)
```

```

pBCPE(q, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
qBCPE(p, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
rBCPE(n, mu = 5, sigma = 0.1, nu = 1, tau = 2)
dBCPEo(x, mu = 5, sigma = 0.1, nu = 1, tau = 2, log = FALSE)
pBCPEo(q, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
qBCPEo(p, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
rBCPEo(n, mu = 5, sigma = 0.1, nu = 1, tau = 2)
checkBCPE(obj = NULL, mu = 10, sigma = 0.1, nu = 0.5, tau = 2,...)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. Other links are "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse", "identity" and "own"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter. Other links are "inverse", "log" and "own"
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter. Other links are "logshifted", "identity" and "own"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of <code>nu</code> parameter values
<code>tau</code>	vector of <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required
<code>obj</code>	a <code>gamlss BCPE</code> family object
<code>...</code>	for extra arguments

Details

The probability density function of the untruncated Box Cox Power Exponential distribution, (`BCPE.untr`), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = \frac{y^{\nu-1} \tau \exp[-\frac{1}{2}|\frac{z}{c}|^{\tau}]}{\mu^{\nu} \sigma c 2^{(1+1/\tau)} \Gamma(\frac{1}{\tau})}$$

where $c = [2^{(-2/\tau)} \Gamma(1/\tau) / \Gamma(3/\tau)]^{0.5}$, where if $\nu \neq 0$ then $z = [(y/\mu)^{\nu} - 1] / (\nu\sigma)$ else $z = \log(y/\mu) / \sigma$, for $y > 0$, $\mu > 0$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$.

The Box-Cox Power Exponential, BCPE, adjusts the above density $f(y|\mu, \sigma, \nu, \tau)$ for the truncation resulting from the condition $y > 0$. See Rigby and Stasinopoulos (2003) for details.

Value

BCPE() returns a `gamlss.family` object which can be used to fit a Box Cox Power Exponential distribution in the `gamlss()` function. `dBCPE()` gives the density, `pBCPE()` gives the distribution function, `qBCPE()` gives the quantile function, and `rBCPE()` generates random deviates.

Warning

The `BCPE.untr` distribution may be unsuitable for some combinations of the parameters (mainly for large σ) where the integrating constant is less than 0.99. A warning will be given if this is the case.

The BCPE distribution is suitable for all combinations of the parameters within their ranges [i.e. $\mu > 0, \sigma > 0, \nu = (-\infty, \infty)$ and $\tau > 0$]

Note

μ , is the median of the distribution, σ is approximately the coefficient of variation (for small σ and moderate $\nu > 0$), ν controls the skewness and τ the kurtosis of the distribution

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Rigby, R. A. and Stasinopoulos, D. M. (2004). Smooth centile curves for skew and kurtotic data modelled using the Box-Cox Power Exponential distribution. *Statistics in Medicine*, **23**: 3053-3076.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCT](#)

Examples

```
# BCPE() #
# library(gamlss)
# data(abdom)
#h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=BCPE, data=abdom)
#plot(h)
plot(function(x)dBCPE(x, mu=5,sigma=.5,nu=1, tau=3), 0.0, 15,
      main = "The BCPE density mu=5,sigma=.5,nu=1, tau=3")
plot(function(x) pBCPE(x, mu=5,sigma=.5,nu=1, tau=3), 0.0, 15,
```

```
main = "The BCPE cdf mu=5, sigma=.5, nu=1, tau=3")
```

BCT

Box-Cox t distribution for fitting a GAMLSS

Description

The function `BCT()` defines the Box-Cox t distribution, a four parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dBCT`, `pBCT`, `qBCT` and `rBCT` define the density, distribution function, quantile function and random generation for the Box-Cox t distribution. [The function `BCTuntr()` is the original version of the function suitable only for the untruncated BCT distribution]. See Rigby and Stasinopoulos (2003) for details. The function `BCT` is identical to `BCT` but with log link for μ .

Usage

```
BCT(mu.link = "identity", sigma.link = "log", nu.link = "identity",
    tau.link = "log")
BCTo(mu.link = "log", sigma.link = "log", nu.link = "identity",
    tau.link = "log")
BCTuntr(mu.link = "identity", sigma.link = "log", nu.link = "identity",
    tau.link = "log")
dBCT(x, mu = 5, sigma = 0.1, nu = 1, tau = 2, log = FALSE)
pBCT(q, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
qBCT(p, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
rBCT(n, mu = 5, sigma = 0.1, nu = 1, tau = 2)
dBCTo(x, mu = 5, sigma = 0.1, nu = 1, tau = 2, log = FALSE)
pBCTo(q, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
qBCTo(p, mu = 5, sigma = 0.1, nu = 1, tau = 2, lower.tail = TRUE, log.p = FALSE)
rBCTo(n, mu = 5, sigma = 0.1, nu = 1, tau = 2)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the μ parameter. Other links are "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the σ parameter. Other links are "inverse", "identity", "own"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the ν parameter. Other links are "inverse", "log", "own"
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the τ parameter. Other links are "inverse", "identity" and "own"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of ν parameter values

<code>tau</code>	vector of tau parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function of the untruncated Box-Cox t distribution, `BCTuntr`, is given by

$$f(y|\mu, \sigma, \nu, \tau) = \frac{y^{\nu-1}}{\mu^\nu \sigma} \frac{\Gamma[(\tau+1)/2]}{\Gamma(1/2)\Gamma(\tau/2)\tau^{0.5}} [1 + (1/\tau)z^2]^{-(\tau+1)/2}$$

where if $\nu \neq 0$ then $z = [(y/\mu)^\nu - 1]/(\nu\sigma)$ else $z = \log(y/\mu)/\sigma$, for $y > 0$, $\mu > 0$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$.

The Box-Cox *t* distribution, `BCT`, adjusts the above density $f(y|\mu, \sigma, \nu, \tau)$ for the truncation resulting from the condition $y > 0$. See Rigby and Stasinopoulos (2003) for details.

Value

`BCT()` returns a `gamlss.family` object which can be used to fit a Box-Cox-t distribution in the `gamlss()` function. `dBCT()` gives the density, `pBCT()` gives the distribution function, `qBCT()` gives the quantile function, and `rBCT()` generates random deviates.

Warning

The use `BCTuntr` distribution may be unsuitable for some combinations of the parameters (mainly for large σ) where the integrating constant is less than 0.99. A warning will be given if this is the case.

The `BCT` distribution is suitable for all combinations of the parameters within their ranges [i.e. $\mu > 0$, $\sigma > 0$, $\nu = (-\infty, \infty)$ and $\tau > 0$]

Note

μ is the median of the distribution, $\sigma(\frac{\tau}{\tau-2})^{0.5}$ is approximate the coefficient of variation (for small σ and moderate $\nu > 0$ and moderate or large τ), ν controls the skewness and τ the kurtosis of the distribution

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Rigby, R.A. Stasinopoulos, D.M. (2006). Using the Box-Cox t distribution in GAMLSS to model skewness and kurtosis. to appear in *Statistical Modelling*.
- Stasinopoulos, D. M. Rigby, R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCPE](#), [BCCG](#)

Examples

```
BCT() # gives information about the default links for the Box Cox t distribution
# library(gamlss)
#data(abdom)
#h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=BCT, data=abdom) #
#plot(h)
plot(function(x)dBCT(x, mu=5,sigma=.5,nu=1, tau=2), 0.0, 20,
      main = "The BCT density mu=5,sigma=.5,nu=1, tau=2")
plot(function(x) pBCT(x, mu=5,sigma=.5,nu=1, tau=2), 0.0, 20,
      main = "The BCT cdf mu=5, sigma=.5, nu=1, tau=2")
```

BE

The beta distribution for fitting a GAMLSS

Description

The functions `BE()` and `BEo()` define the beta distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. `BE()` has mean equal to the parameter `mu` and `sigma` as scale parameter, see below. `BE()` is the original parameterizations of the beta distribution as in `dbeta()` with `shape1=mu` and `shape2=sigma`. The functions `dBE` and `dBEo`, `pBE` and `pBEo`, `qBE` and `qBEo` and finally `rBE` and `rBEo` define the density, distribution function, quantile function and random generation for the `BE` and `BEo` parameterizations respectively of the beta distribution.

Usage

```
BE(mu.link = "logit", sigma.link = "logit")
dBE(x, mu = 0.5, sigma = 0.2, log = FALSE)
pBE(q, mu = 0.5, sigma = 0.2, lower.tail = TRUE, log.p = FALSE)
qBE(p, mu = 0.5, sigma = 0.2, lower.tail = TRUE, log.p = FALSE)
```

```

rBE(n, mu = 0.5, sigma = 0.2)
BEO(mu.link = "log", sigma.link = "log")
dBEO(x, mu = 0.5, sigma = 0.2, log = FALSE)
pBEO(q, mu = 0.5, sigma = 0.2, lower.tail = TRUE, log.p = FALSE)
qBEO(p, mu = 0.5, sigma = 0.2, lower.tail = TRUE, log.p = FALSE)

```

Arguments

<code>mu.link</code>	the mu link function with default <code>logit</code>
<code>sigma.link</code>	the sigma link function with default <code>logit</code>
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The original beta distributions distribution is given as

$$f(y|\alpha, \beta) = \frac{1}{B(\alpha, \beta)} y^{\alpha-1} (1-y)^{\beta-1}$$

for $y \in (0, 1)$, $\alpha > 0$ and $\beta > 0$. In the `gamlss` implementation of `BEO` $\alpha = \mu$ and $\beta > \sigma$. The reparametrization in the function `BE()` is $\mu = \frac{\alpha}{\alpha+\beta}$ and $\sigma = \frac{1}{\alpha+\beta+1}$ for $\mu \in (0, 1)$ and $\sigma \in (0, 1)$. The expected value of y is μ and the variance is $\sigma^2 \mu * (1 - \mu)$.

Value

returns a `gamlss.family` object which can be used to fit a normal distribution in the `gamlss()` function.

Note

Note that for `BE`, `mu` is the mean and `sigma` a scale parameter contributing to the variance of y

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BEINF](#)

Examples

```
BE()# gives information about the default links for the normal distribution
dat1<-rBE(100, mu=.3, sigma=.5)
hist(dat1)
#library(gamlss)
# mod1<-gamlss(dat1~1,family=BE) # fits a constant for mu and sigma
#fitted(mod1)[1]
#fitted(mod1,"sigma")[1]
plot(function(y) dBE(y, mu=.1 ,sigma=.5), 0.001, .999)
plot(function(y) pBE(y, mu=.1 ,sigma=.5), 0.001, 0.999)
plot(function(y) qBE(y, mu=.1 ,sigma=.5), 0.001, 0.999)
plot(function(y) qBE(y, mu=.1 ,sigma=.5, lower.tail=FALSE), 0.001, .999)
dat2<-rBEo(100, mu=1, sigma=2)
#mod2<-gamlss(dat2~1,family=BEo) # fits a constant for mu and sigma
#fitted(mod2)[1]
#fitted(mod2,"sigma")[1]
```

BEINF

The beta inflated distribution for fitting a GAMLSS

Description

The function `BEINF()` defines the beta inflated distribution, a four parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The beta inflated is similar to the beta but allows zeros and ones as values for the response variable. The two extra parameters model the probabilities at zero and one.

The functions `BEINF0()` and `BEINF1()` are three parameter beta inflated distributions allowing zeros or ones only at the response respectively. `BEINF0()` and `BEINF1()` are re-parameterize versions of the distributions `BEZI` and `BEOI` contributed to `gamlss` by Raydonal Ospina (see Ospina and Ferrari (2010)).

The functions `dBEINF`, `pBEINF`, `qBEINF` and `rBEINF` define the density, distribution function, quantile function and random generation for the `BEINF` parametrization of the beta inflated distribution.

The functions `dBEINF0`, `pBEINF0`, `qBEINF0` and `rBEINF0` define the density, distribution function, quantile function and random generation for the BEINF0 parametrization of the beta inflated at zero distribution.

The functions `dBEINF1`, `pBEINF1`, `qBEINF1` and `rBEINF1` define the density, distribution function, quantile function and random generation for the BEINF1 parametrization of the beta inflated at one distribution.

`plotBEINF`, `plotBEINF0` and `plotBEINF1` can be used to plot the distributions. `meanBEINF`, `meanBEINF0` and `meanBEINF1` calculates the expected value of the response for a fitted model.

Usage

```
BEINF(mu.link = "logit", sigma.link = "logit", nu.link = "log",
      tau.link = "log")
BEINF0(mu.link = "logit", sigma.link = "logit", nu.link = "log")
BEINF1(mu.link = "logit", sigma.link = "logit", nu.link = "log")

dBEINF(x, mu = 0.5, sigma = 0.1, nu = 0.1, tau = 0.1,
       log = FALSE)
dBEINF0(x, mu = 0.5, sigma = 0.1, nu = 0.1, log = FALSE)
dBEINF1(x, mu = 0.5, sigma = 0.1, nu = 0.1, log = FALSE)

pBEINF(q, mu = 0.5, sigma = 0.1, nu = 0.1, tau = 0.1,
       lower.tail = TRUE, log.p = FALSE)
pBEINF0(q, mu = 0.5, sigma = 0.1, nu = 0.1,
       lower.tail = TRUE, log.p = FALSE)
pBEINF1(q, mu = 0.5, sigma = 0.1, nu = 0.1,
       lower.tail = TRUE, log.p = FALSE)

qBEINF(p, mu = 0.5, sigma = 0.1, nu = 0.1, tau = 0.1,
       lower.tail = TRUE, log.p = FALSE)
qBEINF0(p, mu = 0.5, sigma = 0.1, nu = 0.1, tau = 0.1,
       lower.tail = TRUE, log.p = FALSE)
qBEINF1(p, mu = 0.5, sigma = 0.1, nu = 0.1,
       lower.tail = TRUE, log.p = FALSE)

rBEINF(n, mu = 0.5, sigma = 0.1, nu = 0.1, tau = 0.1)
rBEINF0(n, mu = 0.5, sigma = 0.1, nu = 0.1)
rBEINF1(n, mu = 0.5, sigma = 0.1, nu = 0.1)

plotBEINF(mu = 0.5, sigma = 0.5, nu = 0.5, tau = 0.5,
         from = 0.001, to = 0.999, n = 101, ...)
plotBEINF0(mu = 0.5, sigma = 0.5, nu = 0.5,
         from = 1e-04, to = 0.9999, n = 101, ...)
plotBEINF1(mu = 0.5, sigma = 0.5, nu = 0.5,
         from = 1e-04, to = 0.9999, n = 101, ...)

meanBEINF(obj)
meanBEINF0(obj)
```

meanBEINF1(obj)

Arguments

mu.link	the mu link function with default logit
sigma.link	the sigma link function with default logit
nu.link	the nu link function with default log
tau.link	the tau link function with default log
x,q	vector of quantiles
mu	vector of location parameter values
sigma	vector of scale parameter values
nu	vector of parameter values modelling the probability at zero
tau	vector of parameter values modelling the probability at one
log, log.p	logical; if TRUE, probabilities p are given as log(p).
lower.tail	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required
from	where to start plotting the distribution from
to	up to where to plot the distribution
obj	a fitted BEINF object
...	other graphical parameters for plotting

Details

The beta inflated distribution is given as

$$f(y) = p_0$$

if (y=0)

$$f(y) = p_1$$

if (y=1)

$$f(y|\alpha, \beta) = \frac{1}{B(\alpha, \beta)} y^{\alpha-1} (1-y)^{\beta-1}$$

otherwise

for $y = (0, 1)$, $\alpha > 0$ and $\beta > 0$. The parametrization in the function BEINF() is $\mu = \frac{\alpha}{\alpha+\beta}$ and $\sigma = \frac{1}{\alpha+\beta+1}$ for $\mu = (0, 1)$ and $\sigma = (0, 1)$ and $\nu = \frac{p_0}{p_2}$, $\tau = \frac{p_1}{p_2}$ where $p_2 = 1 - p_0 - p_1$.

Value

returns a `gamlss.family` object which can be used to fit a beta inflated distribution in the `gamlss()` function. ...

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Ospina R. and Ferrari S. L. P. (2010) Inflated beta distributions, *Statistical Papers*, **23**, 111-126.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BE](#), [BEo](#), [BEZI](#), [BEOI](#)

Examples

```
BEINF()# gives information about the default links for the beta inflated distribution
BEINF0()
BEINF1()
# plotting the distributions
op<-par(mfrow=c(2,2))
plotBEINF( mu =.5 , sigma=.5, nu = 0.5, tau = 0.5, from = 0, to=1, n = 101)
plotBEINF0( mu =.5 , sigma=.5, nu = 0.5, from = 0, to=1, n = 101)
plotBEINF1( mu =.5 , sigma=.5, nu = 0.5, from = 0.001, to=1, n = 101)
curve(dBE(x, mu =.5, sigma=.5), 0.01, 0.999)
par(op)
# plotting the cdf
op<-par(mfrow=c(2,2))
plotBEINF( mu =.5 , sigma=.5, nu = 0.5, tau = 0.5, from = 0, to=1, n = 101, main="BEINF")
plotBEINF0( mu =.5 , sigma=.5, nu = 0.5, from = 0, to=1, n = 101, main="BEINF0")
plotBEINF1( mu =.5 , sigma=.5, nu = 0.5, from = 0.001, to=1, n = 101, main="BEINF1")
curve(dBE(x, mu =.5, sigma=.5), 0.01, 0.999, main="BE")
par(op)
#-----
op<-par(mfrow=c(2,2))
plotBEINF( mu =.5 , sigma=.5, nu = 0.5, tau = 0.5, from = 0, to=1, n = 101, main="BEINF")
plotBEINF0( mu =.5 , sigma=.5, nu = 0.5, from = 0, to=1, n = 101, main="BEINF0")
plotBEINF1( mu =.5 , sigma=.5, nu = 0.5, from = 0.001, to=1, n = 101, main="BEINF1")
curve(dBE(x, mu =.5, sigma=.5), 0.01, 0.999, main="BE")
par(op)
#-----
op<-par(mfrow=c(2,2))
curve(pBEINF(x, mu=.5 ,sigma=.5, nu = 0.5, tau = 0.5, ), 0, 1, ylim=c(0,1), main="BEINF" )
curve(pBEINF0(x, mu=.5 ,sigma=.5, nu = 0.5), 0, 1, ylim=c(0,1), main="BEINF0")
curve(pBEINF1(x, mu=.5 ,sigma=.5, nu = 0.5), 0, 1, ylim=c(0,1), main="BEINF1")
```

```

curve(  pBE(x, mu=.5 ,sigma=.5), .001, .99, ylim=c(0,1), main="BE")
par(op)
#-----
op<-par(mfrow=c(2,2))
curve(qBEINF(x, mu=.5 ,sigma=.5, nu = 0.5, tau = 0.5), .01, .99, main="BEINF" )
curve(qBEINF0(x, mu=.5 ,sigma=.5, nu = 0.5), .01, .99, main="BEINF0" )
curve(qBEINF1(x, mu=.5 ,sigma=.5, nu = 0.5), .01, .99, main="BEINF1" )
curve(qBE(x, mu=.5 ,sigma=.5), .01, .99 , main="BE")
par(op)

#-----
op<-par(mfrow=c(2,2))
hist(rBEINF(200, mu=.5 ,sigma=.5, nu = 0.5, tau = 0.5))
hist(rBEINF0(200, mu=.5 ,sigma=.5, nu = 0.5))
hist(rBEINF1(200, mu=.5 ,sigma=.5, nu = 0.5))
hist(rBE(200, mu=.5 ,sigma=.5))
par(op)
# fit a model to the data
# library(gamlss)
#m1<-gamlss(dat~1,family=BEINF)
#meanBEINF(m1)[1]

```

BEOI

The one-inflated beta distribution for fitting a GAMLSS

Description

The function `BEOI()` defines the one-inflated beta distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The one-inflated beta is similar to the beta distribution but allows ones as y values. This distribution is an extension of the beta distribution using a parameterization of the beta law that is indexed by mean and precision parameters (Ferrari and Cribari-Neto, 2004). The extra parameter models the probability at one. The functions `dBEOI`, `pBEOI`, `qBEOI` and `rBEOI` define the density, distribution function, quantile function and random generation for the BEOI parameterization of the one-inflated beta distribution. `plotBEOI` can be used to plot the distribution. `meanBEOI` calculates the expected value of the response for a fitted model.

Usage

```

BEOI(mu.link = "logit", sigma.link = "log", nu.link = "logit")

dBEOI(x, mu = 0.5, sigma = 1, nu = 0.1, log = FALSE)

pBEOI(q, mu = 0.5, sigma = 1, nu = 0.1, lower.tail = TRUE, log.p = FALSE)

qBEOI(p, mu = 0.5, sigma = 1, nu = 0.1, lower.tail = TRUE,
      log.p = FALSE)

rBEOI(n, mu = 0.5, sigma = 1, nu = 0.1)

```

```
plotBEOI(mu = .5, sigma = 1, nu = 0.1, from = 0.001, to = 1, n = 101,
  ...)
```

```
meanBEOI(obj)
```

Arguments

<code>mu.link</code>	the mu link function with default <code>logit</code>
<code>sigma.link</code>	the sigma link function with default <code>log</code>
<code>nu.link</code>	the nu link function with default <code>logit</code>
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of precision parameter values
<code>nu</code>	vector of parameter values modelling the probability at one
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required
<code>from</code>	where to start plotting the distribution from
<code>to</code>	up to where to plot the distribution
<code>obj</code>	a fitted BEOI object
<code>...</code>	other graphical parameters for plotting

Details

The one-inflated beta distribution is given as

$$f(y) = \nu$$

if $(y = 1)$

$$f(y|\mu, \sigma) = (1 - \nu) \frac{\Gamma(\sigma)}{\Gamma(\mu\sigma)\Gamma((1-\mu)\sigma)} y^{\mu\sigma} (1-y)^{((1-\mu)\sigma)-1}$$

if $y = (0, 1)$. The parameters satisfy $0 < \mu < 1$, $\sigma > 0$ and $0 < \nu < 1$.

Here $E(y) = \nu + (1 - \nu)\mu$ and $Var(y) = (1 - \nu) \frac{\mu(1-\mu)}{\sigma+1} + \nu(1 - \nu)(1 - \mu)^2$.

Value

returns a `gamlss.family` object which can be used to fit a one-inflated beta distribution in the `gamlss()` function.

Note

This work is part of my PhD project at the University of Sao Paulo under the supervision of Professor Silvia Ferrari. My thesis is concerned with regression modelling of rates and proportions with excess of zeros and/or ones

Author(s)

Raydonal Ospina, Department of Statistics, University of Sao Paulo, Brazil.
<rospina@ime.usp.br>

References

- Ferrari, S.L.P., Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31** (1), 799-815.
- Ospina R. and Ferrari S. L. P. (2010) Inflated beta distributions, *Statistical Papers*, **23**, 111-126.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape (with discussion). *Applied Statistics*, **54** (3), 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006). Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BEOI](#)

Examples

```
BEOI()# gives information about the default links for the BEOI distribution
# plotting the distribution
plotBEOI( mu =0.5 , sigma=5, nu = 0.1, from = 0.001, to=1, n = 101)
# plotting the cdf
plot(function(y) pBEOI(y, mu=.5 ,sigma=5, nu=0.1), 0.001, 0.999)
# plotting the inverse cdf
plot(function(y) qBEOI(y, mu=.5 ,sigma=5, nu=0.1), 0.001, 0.999)
# generate random numbers
dat<-rBEOI(100, mu=.5, sigma=5, nu=0.1)
# fit a model to the data.
# library(gamlss)
#mod1<-gamlss(dat~1,sigma.formula=~1, nu.formula=~1, family=BEOI)
#fitted(mod1)[1]
#summary(mod1)
#fitted(mod1,"mu")[1]      #fitted mu
#fitted(mod1,"sigma")[1]  #fitted sigma
#fitted(mod1,"nu")[1]    #fitted nu
#meanBEOI(mod1)[1] # expected value of the response
```

Description

The function `BEZI()` defines the zero-inflated beta distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The zero-inflated beta is similar to the beta distribution but allows zeros as `y` values. This distribution is an extension of the beta distribution using a parameterization of the beta law that is indexed by mean and precision parameters (Ferrari and Cribari-Neto, 2004). The extra parameter models the probability at zero. The functions `dBEZI`, `pBEZI`, `qBEZI` and `rBEZI` define the density, distribution function, quantile function and random generation for the BEZI parameterization of the zero-inflated beta distribution. `plotBEZI` can be used to plot the distribution. `meanBEZI` calculates the expected value of the response for a fitted model.

Usage

```
BEZI(mu.link = "logit", sigma.link = "log", nu.link = "logit")

dBEZI(x, mu = 0.5, sigma = 1, nu = 0.1, log = FALSE)

pBEZI(q, mu = 0.5, sigma = 1, nu = 0.1, lower.tail = TRUE, log.p = FALSE)

qBEZI(p, mu = 0.5, sigma = 1, nu = 0.1, lower.tail = TRUE,
      log.p = FALSE)

rBEZI(n, mu = 0.5, sigma = 1, nu = 0.1)

plotBEZI(mu = .5, sigma = 1, nu = 0.1, from = 0, to = 0.999, n = 101,
         ...)

meanBEZI(obj)
```

Arguments

<code>mu.link</code>	the mu link function with default <code>logit</code>
<code>sigma.link</code>	the sigma link function with default <code>log</code>
<code>nu.link</code>	the nu link function with default <code>logit</code>
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of precision parameter values
<code>nu</code>	vector of parameter values modelling the probability at zero
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
from	where to start plotting the distribution from
to	up to where to plot the distribution
obj	a fitted BEZI object
...	other graphical parameters for plotting

Details

The zero-inflated beta distribution is given as

$$f(y) = \nu$$

if $(y = 0)$

$$f(y|\mu, \sigma) = (1 - \nu) \frac{\Gamma(\sigma)}{\Gamma(\mu\sigma)\Gamma((1-\mu)\sigma)} y^{\mu\sigma} (1-y)^{((1-\mu)\sigma)-1}$$

if $y = (0, 1)$. The parameters satisfy $0 < \mu < 1$, $\sigma > 0$ and $0 < \nu < 1$.

Here $E(y) = (1 - \nu)\mu$ and $Var(y) = (1 - \nu)\frac{\mu(1-\mu)}{\sigma+1} + \nu(1 - \nu)\mu^2$.

Value

returns a `gamlss.family` object which can be used to fit a zero-inflated beta distribution in the `gamlss()` function.

Note

This work is part of my PhD project at the University of Sao Paulo under the supervision of Professor Silvia Ferrari. My thesis is concerned with regression modelling of rates and proportions with excess of zeros and/or ones

Author(s)

Raydonal Ospina, Department of Statistics, University of Sao Paulo, Brazil.
<rospina@ime.usp.br>

References

- Ferrari, S.L.P., Cribari-Neto, F. (2004). Beta regression for modelling rates and proportions. *Journal of Applied Statistics*, **31** (1), 799-815.
- Ospina R. and Ferrari S. L. P. (2010) Inflated beta distributions, *Statistical Papers*, **23**, 111-126.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape (with discussion). *Applied Statistics*, **54** (3), 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006). Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BEZI](#)

Examples

```
BEZI()# gives information about the default links for the BEZI distribution
# plotting the distribution
plotBEZI( mu =0.5 , sigma=5, nu = 0.1, from = 0, to=0.99, n = 101)
# plotting the cdf
plot(function(y) pBEZI(y, mu=.5 ,sigma=5, nu=0.1), 0, 0.999)
# plotting the inverse cdf
plot(function(y) qBEZI(y, mu=.5 ,sigma=5, nu=0.1), 0, 0.999)
# generate random numbers
dat<-rBEZI(100, mu=.5, sigma=5, nu=0.1)
# fit a model to the data. Tits a constant for mu, sigma and nu
# library(gamlss)
#mod1<-gamlss(dat~1,sigma.formula=~1, nu.formula=~1, family=BEZI)
#fitted(mod1)[1]
#summary(mod1)
#fitted(mod1,"mu")[1]          #fitted mu
#fitted(mod1,"sigma")[1]      #fitted sigma
#fitted(mod1,"nu")[1]         #fitted nu
#meanBEZI(mod1)[1] # expected value of the response
```

 BI

Binomial distribution for fitting a GAMLSS

Description

The `BI()` function defines the binomial distribution, a one parameter family distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dBI`, `pBI`, `qBI` and `rBI` define the density, distribution function, quantile function and random generation for the binomial, `BI()`, distribution.

Usage

```
BI(mu.link = "logit")
dBI(x, bd = 1, mu = 0.5, log = FALSE)
pBI(q, bd = 1, mu = 0.5, lower.tail = TRUE, log.p = FALSE)
qBI(p, bd = 1, mu = 0.5, lower.tail = TRUE, log.p = FALSE)
rBI(n, bd = 1, mu = 0.5)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the <code>mu</code> parameter. Other links are "probit" and "cloglog" (complementary log-log)
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive probabilities
<code>bd</code>	vector of binomial denominators
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Definition file for binomial distribution.

$$f(y|\mu) = \frac{\Gamma(n+1)}{\Gamma(y+1)\Gamma(n-y+1)} \mu^y (1-\mu)^{(n-y)}$$

for $y = 0, 1, 2, \dots, n$ and $0 < \mu < 1$.

Value

returns a `gamlss.family` object which can be used to fit a binomial distribution in the `gamlss()` function.

Note

The response variable should be a matrix containing two columns, the first with the count of successes and the second with the count of failures. The parameter `mu` represents a probability parameter with limits $0 < \mu < 1$. $n\mu$ is the mean of the distribution where `n` is the binomial denominator.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [ZABI](#), [ZIBI](#)

Examples

```
BI()# gives information about the default links for the Binomial distribution
# data(aep)
# library(gamlss)
# h<-gamlss(y~ward+loglos+year, family=BI, data=aep)
# plot of the binomial distribution
curve(dBI(x, mu = .5, bd=10), from=0, to=10, n=10+1, type="h")
tN <- table(Ni <- rBI(1000, mu=.2, bd=10))
r <- barplot(tN, col='lightblue')
```

checklink

Set the Right Link Function for Specified Parameter and Distribution

Description

This function is used within the distribution family specification of a GAMLSS model to define the right link for each of the parameters of the distribution. This function should not be called by the user unless he/she specify a new distribution family or wishes to change existing link functions in the parameters.

Usage

```
checklink(which.link = NULL, which.dist = NULL, link = NULL, link.List = NULL)
```

Arguments

which.link	which parameter link e.g. which.link="mu.link"
which.dist	which distribution family e.g. which.dist="Cole.Green"
link	a repetition of which.link e.g. link=substitute(mu.link)
link.List	what link function are required e.g. link.List=c("inverse", "log", "identity")

Value

Defines the right link for each parameter

Author(s)

Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

DEL

The Delaporte distribution for fitting a GAMLSS model

Description

The DEL() function defines the Delaporte distribution, a three parameter discrete distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dDEL`, `pDEL`, `qDEL` and `rDEL` define the density, distribution function, quantile function and random generation for the Delaporte DEL(), distribution.

Usage

```
DEL(mu.link = "log", sigma.link = "log", nu.link = "logit")
dDEL(x, mu=1, sigma=1, nu=0.5, log=FALSE)
pDEL(q, mu=1, sigma=1, nu=0.5, lower.tail = TRUE,
      log.p = FALSE)
qDEL(p, mu=1, sigma=1, nu=0.5, lower.tail = TRUE,
      log.p = FALSE, max.value = 10000)
rDEL(n, mu=1, sigma=1, nu=0.5, max.value = 10000)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "logit" link as the default for the nu parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive mu
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of nu
<code>p</code>	vector of probabilities

q	vector of quantiles
n	number of random values to return
log, log.p	logical; if TRUE, probabilities p are given as log(p)
lower.tail	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
max.value	a constant, set to the default value of 10000 for how far the algorithm should look for q

Details

The probability function of the Delaporte distribution is given by

$$f(y|\mu, \sigma, \nu) = \frac{e^{-\mu\nu}}{\Gamma(1/\sigma)} [1 + \mu\sigma(1 - \nu)]^{-1/\sigma} S$$

where

$$S = \sum_{j=0}^y \binom{y}{j} \frac{\mu^y \nu^{y-j}}{y!} \left[\mu + \frac{1}{\sigma(1-\nu)} \right]^{-j} \Gamma\left(\frac{1}{\sigma} + j\right)$$

for $y = 0, 1, 2, \dots, \infty$ where $\mu > 0$, $\sigma > 0$ and $0 < \nu < 1$. This distribution is a parametrization of the distribution given by Wimmer and Altmann (1999) p 515-516 where $\alpha = \mu\nu$, $k = 1/\sigma$ and $\rho = [1 + \mu\sigma(1 - \nu)]^{-1}$

Value

Returns a `gamlss.family` object which can be used to fit a Delaporte distribution in the `gamlss()` function.

Note

The mean of Y is given by $E(Y) = \mu$ and the variance by $V(Y) = \mu + \mu^2\sigma(1 - \nu)^2$.

Author(s)

Rigby, R. A., Stasinopoulos D. M. and Marco Enea

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Rigby, R. A., Stasinopoulos D. M. and Akantziliotou, C. (2006) Modelling the parameters of a family of mixed Poisson distributions including the Sichel and Delaportte. Submitted for publication.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2003) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Wimmer, G. and Altmann, G (1999). *Thesaurus of univariate discrete probability distributions*. Stamm Verlag, Essen, Germany

See Also

[gamlss.family](#), [SI](#), [SICHEL](#)

Examples

```
DEL()# gives information about the default links for the Delaporte distribution
#plot the pdf using plot
plot(function(y) dDEL(y, mu=10, sigma=1, nu=.5), from=0, to=100, n=100+1, type="h") # pdf
# plot the cdf
plot(seq(from=0,to=100),pDEL(seq(from=0,to=100), mu=10, sigma=1, nu=0.5), type="h") # cdf
# generate random sample
tN <- table(Ni <- rDEL(100, mu=10, sigma=1, nu=0.5))
r <- barplot(tN, col='lightblue')
# fit a model to the data
# library(gamlss)
# gamlss(Ni~1,family=DEL, control=gamlss.control(n.cyc=50))
```

DPO

The Double Poisson distribution

Description

The function `DPO()` defines the double Poisson distribution, a two parameters distribution, for a `gamlss.family` object to be used in `GAMLSS` fitting using the function `gamlss()`. The functions `dDPO`, `pDPO`, `qDPO` and `rDPO` define the density, distribution function, quantile function and random generation for the double Poisson, `DPO()`, distribution. The function `get_C()` calculates numerically the constant of proportionality needed for the pdf to sum up to 1.

Usage

```
DPO(mu.link = "log", sigma.link = "log")
dDPO(x, mu = 1, sigma = 1, log = FALSE)
pDPO(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qDPO(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE,
     max.value = 10000)
rDPO(n, mu = 1, sigma = 1, max.value = 10000)
get_C(x, mu, sigma)
```

Arguments

<code>mu.link</code>	the link function for <code>mu</code> with default <code>log</code>
<code>sigma.link</code>	the link function for <code>sigma</code> with default <code>log</code>
<code>x, q</code>	vector of (non-negative integer) quantiles
<code>p</code>	vector of probabilities
<code>mu</code>	the <code>mu</code> parameter
<code>sigma</code>	the <code>sigma</code> parameter

<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as $\log(p)$
<code>max.value</code>	a constant, set to the default value of 10000 for how far the algorithm should look for q
<code>n</code>	how many random values to generate

Details

The definition for the Double Poisson distribution first introduced by Efron (1986) is:

$$f(y|\mu, \sigma) = \left(\frac{1}{\sigma}\right)^{1/2} e^{-\mu/\sigma} \left(\frac{e^{-y} y^y}{y!}\right) \left(\frac{e\mu}{y}\right)^{y/\sigma} C$$

for $y = 0, 1, 2, \dots, \infty$, $\mu > 0$ and $\sigma > 0$ where C is the constant of proportionality which is calculated numerically using the function `get_C`.

Value

The function `DPO` returns a `gamlss.family` object which can be used to fit a double Poisson distribution in the `gamlss()` function.

Note

The distribution calculates the constant of proportionality numerically therefore it can be slow for large data

Author(s)

Mikis Stasinopoulos, Bob Rigby and Marco Enea

References

- Efron, B., 1986. Double exponential families and their use in generalized linear Regression. *Journal of the American Statistical Association* 81 (395), 709-721.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[PO](#)

Examples

```
DPO()
# overdispersed DPO
x <- 0:20
plot(x, dDPO(x, mu=5, sigma=3), type="h", col="red")
# underdispersed DPO
plot(x, dDPO(x, mu=5, sigma=.3), type="h", col="red")
# generate random sample
Y <- rDPO(100,5,.5)
plot(table(Y))
points(0:20, 100*dDPO(0:20, mu=5, sigma=.5)+0.2, col="red")
# fit a model to the data
# library(gamlss)
# gamlss(Y~1,family=DPO)
```

EGB2

The exponential generalized Beta type 2 distribution for fitting a GAMLSS

Description

This function defines the generalized t distribution, a four parameter distribution. The response variable is in the range from minus infinity to plus infinity. The functions `dEGB2`, `pEGB2`, `qEGB2` and `rEGB2` define the density, distribution function, quantile function and random generation for the generalized beta type 2 distribution.

Usage

```
EGB2(mu.link = "identity", sigma.link = "log", nu.link = "log",
      tau.link = "log")
dEGB2(x, mu = 0, sigma = 1, nu = 1, tau = 0.5, log = FALSE)
pEGB2(q, mu = 0, sigma = 1, nu = 1, tau = 0.5, lower.tail = TRUE,
      log.p = FALSE)
qEGB2(p, mu = 0, sigma = 1, nu = 1, tau = 0.5, lower.tail = TRUE,
      log.p = FALSE)
rEGB2(n, mu = 0, sigma = 1, nu = 1, tau = 0.5)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter.
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter.
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values

<code>nu</code>	vector of skewness nu parameter values
<code>tau</code>	vector of kurtosis tau parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function of the Generalized Beta type 2, (GB2), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = e^{\nu z} \{ |\sigma| B(\nu, \tau) [1 + e^z]^{\nu+\tau} \}^{-1}$$

for $-\infty < y < \infty$, where $z = (y - \mu)/\sigma$ and $-\infty < \mu < \infty$, $-\infty < \sigma < \infty$, $\nu > 0$ and $\tau > 0$, McDonald and Xu (1995).

Value

`EGB2()` returns a `gamlss.family` object which can be used to fit the EGB2 distribution in the `gamlss()` function. `dEGB2()` gives the density, `pEGB2()` gives the distribution function, `qEGB2()` gives the quantile function, and `rEGB2()` generates random deviates.

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```

EGB2() #
y<- rEGB2(200, mu=5, sigma=2, nu=1, tau=4)
library(MASS)
truehist(y)
fx<-dEGB2(seq(min(y), 20, length=200), mu=5 ,sigma=2, nu=1, tau=4)
lines(seq(min(y),20,length=200),fx)
# something funny here
# library(gamlss)
# histDist(y, family=EGB2, n.cyc=60)
integrate(function(x) x*dEGB2(x=x, mu=5, sigma=2, nu=1, tau=4), -Inf, Inf)
curve(dEGB2(x, mu=5 ,sigma=2, nu=1, tau=4), -10, 10, main = "The EGB2 density
      mu=5, sigma=2, nu=1, tau=4")

```

exGAUS

The ex-Gaussian distribution

Description

The ex-Gaussian distribution is often used by psychologists to model response time (RT). It is defined by adding two random variables, one from a normal distribution and the other from an exponential. The parameters μ and σ are the mean and standard deviation from the normal distribution variable while the parameter ν is the mean of the exponential variable. The functions `dexGAUS`, `pexGAUS`, `qexGAUS` and `rexGAUS` define the density, distribution function, quantile function and random generation for the ex-Gaussian distribution.

Usage

```

exGAUS(mu.link = "identity", sigma.link = "log", nu.link = "log")
dexGAUS(x, mu = 5, sigma = 1, nu = 1, log = FALSE)
pexGAUS(q, mu = 5, sigma = 1, nu = 1, lower.tail = TRUE, log.p = FALSE)
qexGAUS(p, mu = 5, sigma = 1, nu = 1, lower.tail = TRUE, log.p = FALSE)
rexGAUS(n, mu = 5, sigma = 1, nu = 1, ...)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter. Other links are "inverse", "identity", "logshifted" (shifted from one) and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of <code>mu</code> parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of <code>nu</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .

lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
p	vector of probabilities.
n	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
...	for extra arguments

Details

The probability density function of the ex-Gaussian distribution, (exGAUS), is defined as

$$f(y|\mu, \sigma, \nu) = \frac{1}{\nu} e^{\frac{\mu-y}{\nu} + \frac{\sigma^2}{2\nu^2}} \Phi\left(\frac{y-\mu}{\sigma} - \frac{\sigma}{\nu}\right)$$

where Φ is the cdf of the standard normal distribution, for $-\infty < y < \infty$, $-\infty < \mu < \infty$, $\sigma > 0$ and $\nu > 0$.

Value

exGAUS() returns a `gamlss.family` object which can be used to fit ex-Gaussian distribution in the `gamlss()` function. `dexGAUS()` gives the density, `pexGAUS()` gives the distribution function, `qexGAUS()` gives the quantile function, and `rexGAUS()` generates random deviates.

Note

The mean of the ex-Gaussian is $\mu + \nu$ and the variance is $\sigma^2 + \nu^2$.

Author(s)

Mikis Stasinopoulos and Bob Rigby

References

- Cousineau, D. Brown, S. and Heathcote A. (2004) Fitting distributions using maximum likelihood: Methods and packages, *Behavior Research Methods, Instruments and Computers*, **46**, 742-756.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCCG](#), [GA](#), [IG LNO](#)

Examples

```

exGAUS() #
y<- rexGAUS(100, mu=300, nu=100, sigma=35)
hist(y)
# library(gamlss)
# m1<-gamlss(y~1, family=exGAUS)
# plot(m1)
curve(dexGAUS(x, mu=300 ,sigma=35,nu=100), 100, 600,
      main = "The ex-GAUS density mu=300 ,sigma=35,nu=100")
plot(function(x) pexGAUS(x, mu=300,sigma=35,nu=100), 100, 600,
      main = "The ex-GAUS cdf mu=300, sigma=35, nu=100")

```

EXP

*Exponential distribution for fitting a GAMLSS***Description**

The function EXP defines the exponential distribution, a one parameter distribution for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The `mu` parameter represents the mean of the distribution. The functions `dEXP`, `pEXP`, `qEXP` and `rEXP` define the density, distribution function, quantile function and random generation for the specific parameterization of the exponential distribution defined by function EXP.

Usage

```

EXP(mu.link = "log")
dEXP(x, mu = 1, log = FALSE)
pEXP(q, mu = 1, lower.tail = TRUE, log.p = FALSE)
qEXP(p, mu = 1, lower.tail = TRUE, log.p = FALSE)
rEXP(n, mu = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse" and "identity"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The specific parameterization of the exponential distribution used in EXP is

$$f(y|\mu) = \frac{1}{\mu} \exp \left\{ -\frac{y}{\mu} \right\}$$

, for $y > 0, \mu > 0$.

Value

EXP() returns a `gamlss.family` object which can be used to fit an exponential distribution in the `gamlss()` function. `dEXP()` gives the density, `pEXP()` gives the distribution function, `qEXP()` gives the quantile function, and `rEXP()` generates random deviates.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Nicoleta Motpan

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
y<-rEXP(1000,mu=1) # generates 1000 random observations
hist(y)
# library(gamlss)
# histDist(y, family=EXP)
```

flexDist

*Non-parametric pdf from limited information data***Description**

This is an attempt to create a distribution function if the only existing information is the quantiles or expectiles of the distribution.

Usage

```
flexDist(quantiles = list(values=c(-1.96,0,1.96), prob=c(0.05, .50, 0.95)),
         expectiles = list(), lambda = 10,
         kappa = 10, delta = 1e-07, order = 3, n.iter = 200,
         plot = TRUE, no.inter = 100, lower = NULL,
         upper = NULL, perc.quant = 0.3, ...)
```

Arguments

quantiles	a list with components values and prob
expectiles	a list with components values and prob
lambda	smoothing parameter for the log-pdf
kappa	smoothing parameter for log concavity
delta	smoothing parameter for ridge penalty
order	the order of the penalty for log-pdf
n.iter	maximum number of iterations
plot	whether to plot the result
no.inter	How many discrete probabilities to evaluate
lower	the lower value of the x
upper	the upper value of the x
perc.quant	how far from the quantile should go out to define the limit of x if not set by lower or upper
...	additional arguments

Value

Returns a list with components

pdf	the heights of the fitted pdf, the sum of it multiplied by the Dx should add up to 1 i.e. $\text{sum}(\text{object}\$pdf * \text{diff}(\text{object}\$x)[1])$
cdf	the fitted cdf
x	the values of x where the discretise distribution is defined
pFun	the cdf of the fitted non-parametric distribution
qFun	the inverse cdf function of the fitted non-parametric distribution
rFun	a function to generate a random sample from the fitted non-parametric distribution

Author(s)

Mikis Stasinopoulos, Paul Eilers, Bob Rigby and Vlasios Voudouris

References

Eilers, P. H. C., Voudouris, V., Rigby R. A., Stasinopoulos D. M. (2012) Estimation of nonparametric density from sparse summary information, under review.

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), Appl. Statist., 54, part 3, pp 507-554.

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. Journal of Statistical Software, Vol. 23, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[histSmo](#)

Examples

```
# Normal
r1<-flexDist(quantiles=list(values=qNO(c(0.05, 0.25, 0.5,0.75, 0.95), mu=0,
      sigma=1), prob=c( 0.05, 0.25, 0.5,0.75,0.95 )),
      no.inter=200, lambda=10, kappa=10, perc.quant=0.3)

# GAMMA
r1<-flexDist(quantiles=list(values=qGA(c(0.05,0.25, 0.5,0.75,0.95), mu=1,
      sigma=.8), prob=c(0.05,0.25, 0.5,0.75,0.95)),
      expectiles=list(values=1, prob=0.5), lambda=10,
      kappa=10, lower=0, upper=5)#
```

GA

Gamma distribution for fitting a GAMLSS

Description

The function GA defines the gamma distribution, a two parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The parameterization used has the mean of the distribution equal to μ and the variance equal to $\sigma^2\mu^2$. The functions `dGA`, `pGA`, `qGA` and `rGA` define the density, distribution function, quantile function and random generation for the specific parameterization of the gamma distribution defined by function GA.

Usage

```
GA(mu.link = "log", sigma.link = "log")
dGA(x, mu = 1, sigma = 1, log = FALSE)
pGA(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qGA(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rGA(n, mu = 1, sigma = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse", "identity" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other link is the "inverse", "identity" and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The specific parameterization of the gamma distribution used in GA is

$$f(y|\mu, \sigma) = \frac{y^{(1/\sigma^2)-1} \exp[-y/(\sigma^2\mu)]}{(\sigma^2\mu)^{(1/\sigma^2)}\Gamma(1/\sigma^2)}$$

for $y > 0$, $\mu > 0$ and $\sigma > 0$.

Value

`GA()` returns a `gamlss.family` object which can be used to fit a gamma distribution in the `gamlss()` function. `dGA()` gives the density, `pGA()` gives the distribution function, `qGA()` gives the quantile function, and `rGA()` generates random deviates. The latest functions are based on the equivalent R functions for gamma distribution.

Note

μ is the mean of the distribution in GA. In the function GA, σ is the square root of the usual dispersion parameter for a GLM gamma model. Hence $\sigma\mu$ is the standard deviation of the distribution defined in GA.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
GA()# gives information about the default links for the gamma distribution
# dat<-rgamma(100, shape=1, scale=10) # generates 100 random observations
# fit a gamlss model
# gamlss(dat~1,family=GA)
# fits a constant for each parameter mu and sigma of the gamma distribution
newdata<-rGA(1000,mu=1,sigma=1) # generates 1000 random observations
hist(newdata)
rm(dat,newdata)
```

gamlss.family

Family Objects for fitting a GAMLSS model

Description

GAMLSS families are the current available distributions that can be fitted using the `gamlss()` function.

Usage

```
gamlss.family(object,...)
as.gamlss.family(object)
as.family(object)
## S3 method for class 'gamlss.family'
print(x,...)
```

Arguments

object	a gamlss family object e.g. BCT
x	a gamlss family object e.g. BCT
...	further arguments passed to or from other methods.

Details

There are several distributions available for the response variable in the `gamlss` function. The following table display their names and their abbreviations in R. Note that the different distributions can be fitted using their R abbreviations (and optionally excluding the brackets) i.e. `family=BI()`, `family=BI` are equivalent.

Distributions	R names	No of parameters
Beta	<code>BE()</code>	2
Beta Binomial	<code>BB()</code>	2
Beta one inflated	<code>BEOI()</code>	3
Beta zero inflated	<code>BEZI()</code>	3
Beta inflated	<code>BEINF()</code>	4
Binomial	<code>BI()</code>	1
Box-Cox Cole and Green	<code>BCCG()</code>	3
Box-Cox Power Exponential	<code>BCPE()</code>	4
Box-Cox-t	<code>BCT()</code>	4
Delaport	<code>DEL()</code>	3
Exponential	<code>EXP()</code>	1
Exponential Gaussian	<code>exGAUS()</code>	3
Exponential generalized Beta type 2	<code>EGB2()</code>	4
Gamma	<code>GA()</code>	2
Generalized Beta type 1	<code>GB1()</code>	4
Generalized Beta type 2	<code>GB2()</code>	4
Generalized Gamma	<code>GG()</code>	3
Generalized Inverse Gaussian	<code>GIG()</code>	3
Generalized t	<code>GT()</code>	4
Geometric	<code>GEOM()</code>	1
Gumbel	<code>GU()</code>	2
Inverse Gamma	<code>IGAMMA()</code>	2
Inverse Gaussian	<code>IG()</code>	2
Johnson's SU	<code>JSU()</code>	4
Logarithmic	<code>LG()</code>	1
Logistic	<code>LO()</code>	2
log-Normal	<code>LOGNO()</code>	2
log-Normal (Box-Cox)	<code>LNO()</code>	3 (1 fixed)
Negative Binomial type I	<code>NBI()</code>	2
Negative Binomial type II	<code>NBII()</code>	2
Normal Exponential t	<code>NET()</code>	4 (2 fixed)
Normal	<code>NO()</code>	2
Normal Family	<code>NOF()</code>	3 (1 fixed)
Pareto type 2	<code>PARET02()</code>	2
Pareto type 2 original	<code>PARET02o()</code>	2
Power Exponential	<code>PE()</code>	3
Power Exponential type 2	<code>PE2()</code>	3
Poisson	<code>PO()</code>	1
Poisson inverse Gaussian	<code>PIG()</code>	2
Reverse generalized extreme	<code>RGE()</code>	3
Reverse Gumbel	<code>RG()</code>	2

Skew Power Exponential type 1	SEP1()	4
Skew Power Exponential type 2	SEP2()	4
Skew Power Exponential type 3	SEP3()	4
Skew Power Exponential type 4	SEP4()	4
Shash	SHASH()	4
Shash original	SHASHo()	4
Shash original 2	SHASH()	4
Sichel (original)	SI()	3
Sichel (mu as the maen)	SICHEL()	3
Skew t type 1	ST1()	3
Skew t type 2	ST2()	3
Skew t type 3	ST3()	3
Skew t type 4	ST4()	3
Skew t type 5	ST5()	3
t-distribution	TF()	3
Waring	WARING()	1
Weibull	WEI()	2
Weibull(PH parameterization)	WEI2()	2
Weibull (mu as mean)	WEI3()	2
Yule	YULE()	1
Zero adjusted binomial	ZABI()	2
Zero inflated binomial	ZIBI()	2
Zero adjusted logarithmic	ZALG()	2
Zero inflated poisson	ZIP()	2
Zero inf. poiss.(mu as mean)	ZIP2()	2
Zero adjusted poisson	ZAP()	2
Zero adjusted IG	ZAIG()	2

Note that some of the distributions are in the package `gamlss.dist`. The parameters of the distributions are in order, `mu` for location, `sigma` for scale (or dispersion), and `nu` and `tau` for shape. More specifically for the BCCG family `mu` is the median, `sigma` approximately the coefficient of variation, and `nu` the skewness parameter. The parameters for BCPE distribution have the same interpretation with the extra fourth parameter `tau` modelling the kurtosis of the distribution. The parameters for BCT have the same interpretation except that $\sigma[(\tau/(\tau - 2))^{0.5}]$ is approximately the coefficient of variation.

All of the distribution in the above list are also provided with the corresponding `d`, `p`, `q` and `r` functions for density (pdf), distribution function (cdf), quantile function and random generation function respectively, (see individual distribution for details).

Value

The above GAMLSS families return an object which is of type `gamlss.family`. This object is used to define the family in the `gamlss()` fit.

Note

More distributions will be documented in later GAMLSS releases. Further user defined distributions can be incorporate relatively easy, see, for example, the help documentation accompanying the

gamlss library.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[BE, BB, BEINF, BI, LNO, BCT, BCPE, BCCG, GA, GU, JSU, IG, LO, NBI, NBII, NO, PE, PO, RG, PIG, TF, WEI, WEI2, ZIP](#)

Examples

```
normal<-N0(mu.link="log", sigma.link="log")
normal
```

GB1

The generalized Beta type 1 distribution for fitting a GAMLSS

Description

This function defines the generalized beta type 1 distribution, a four parameter distribution. The function GB1 creates a `gamlss.family` object which can be used to fit the distribution using the function `gamlss()`. Note the range of the response variable is from zero to one. The functions `dGB1`, `GB1`, `qGB1` and `rGB1` define the density, distribution function, quantile function and random generation for the generalized beta type 1 distribution.

Usage

```
GB1(mu.link = "logit", sigma.link = "logit", nu.link = "log",
    tau.link = "log")
dGB1(x, mu = 0.5, sigma = 0.4, nu = 1, tau = 1, log = FALSE)
pGB1(q, mu = 0.5, sigma = 0.4, nu = 1, tau = 1, lower.tail = TRUE,
    log.p = FALSE)
qGB1(p, mu = 0.5, sigma = 0.4, nu = 1, tau = 1, lower.tail = TRUE,
    log.p = FALSE)
rGB1(n, mu = 0.5, sigma = 0.4, nu = 1, tau = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter.
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter.
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness <code>nu</code> parameter values
<code>tau</code>	vector of kurtosis <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The probability density function of the Generalized Beta type 1, (GB1), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = \frac{\tau \nu^\beta y^{\tau \alpha - 1} (1 - y^\tau)^{\beta - 1}}{B(\alpha, \beta) [\nu + (1 - \nu) y^\tau]^{\alpha + \beta}}$$

where $0 < y < 1$, $\alpha = \mu(1 - \sigma^2)/\sigma^2$ and $\beta = (1 - \mu)(1 - \sigma^2)/\sigma^2$, and $\alpha > 0$, $\beta > 0$. Note the $\mu = \alpha/(\alpha + \beta)$, $\sigma = (\alpha + \beta + 1)^{-1/2}$.

Value

`GB1()` returns a `gamlss.family` object which can be used to fit the GB1 distribution in the `gamlss()` function. `dGB1()` gives the density, `pGB1()` gives the distribution function, `qGB1()` gives the quantile function, and `rGB1()` generates random deviates.

Warning

The `qSHASH` and `rSHASH` are slow since they are relying on golden section for finding the quantiles

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```
GB1() #
y<- rGB1(200, mu=.1, sigma=.6, nu=1, tau=4)
hist(y)
# library(gamlss)
# histDist(y, family=GB1, n.cyc=60)
curve(dGB1(x, mu=.1 ,sigma=.6, nu=1, tau=4), 0.01, 0.99, main = "The GB1
      density mu=0.1, sigma=.6, nu=1, tau=4")
```

GB2

The generalized Beta type 2 and generalized Pareto distributions for fitting a GAMLSS

Description

This function defines the generalized beta type 2 distribution, a four parameter distribution. The function GB2 creates a `gamlss.family` object which can be used to fit the distribution using the function `gamlss()`. The response variable is in the range from zero to infinity. The functions `dGB2`, `GB2`, `qGB2` and `rGB2` define the density, distribution function, quantile function and random generation for the generalized beta type 2 distribution. The generalised Pareto GP distribution is defined by setting the parameters `sigma` and `nu` of the GB2 distribution to 1.

Usage

```
GB2(mu.link = "log", sigma.link = "log", nu.link = "log",
    tau.link = "log")
dGB2(x, mu = 1, sigma = 1, nu = 1, tau = 0.5, log = FALSE)
pGB2(q, mu = 1, sigma = 1, nu = 1, tau = 0.5, lower.tail = TRUE,
    log.p = FALSE)
qGB2(p, mu = 1, sigma = 1, nu = 1, tau = 0.5, lower.tail = TRUE,
    log.p = FALSE)
```

```

rGB2(n, mu = 1, sigma = 1, nu = 1, tau = 0.5)

GP(mu.link = "log", sigma.link = "log")
dGP(x, mu = 1, sigma = 1, log = FALSE)
pGP(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qGP(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rGP(n, mu = 1, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter.
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter.
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness <code>nu</code> parameter values
<code>tau</code>	vector of kurtosis <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The probability density function of the Generalized Beta type 2, (GB2), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = |\sigma| y^{\sigma\nu-1} \{ \mu^{\sigma\nu} B(\nu, \tau) [1 + (y/\mu)^\sigma]^{\nu+\tau} \}^{-1}$$

where $y > 0$, $\mu > 0$, $-\infty < \sigma < \infty$, $\nu > 0$ and $\tau > 0$.

Value

`GB2()` returns a `gamlss.family` object which can be used to fit the GB2 distribution in the `gamlss()` function. `dGB2()` gives the density, `pGB2()` gives the distribution function, `qGB2()` gives the quantile function, and `rGB2()` generates random deviates.

Warning

The `qSHASH` and `rSHASH` are slow since they are relying on golden section for finding the quantiles

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```
GB2() #
y<- rGB2(200, mu=5, sigma=2, nu=1, tau=1)
library(MASS)
truehist(y)
fx<-dGB2(seq(0.01, 20, length=200), mu=5 ,sigma=2, nu=1, tau=1)
lines(seq(0.01,20,length=200),fx)
integrate(function(x) x*dGB2(x=x, mu=5, sigma=2, nu=1, tau=1), 0, Inf)
mean(y)
curve(dGB2(x, mu=5 ,sigma=2, nu=1, tau=1), 0.01, 20,
      main = "The GB2 density mu=5, sigma=2, nu=1, tau=4")
```

 GE

Geometric distribution for fitting a GAMLSS

Description

The function `GE()` defines the Yule distribution, a one parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with mean equal to the parameter `mu`. The functions `dGE`, `pGE`, `qGE` and `rGE` define the density, distribution function, quantile function and random generation for the GE parameterization of the Geometric distribution.

Usage

```
GE(mu.link = "log")
dGE(x, mu = 2, log = FALSE)
pGE(q, mu = 2, lower.tail = TRUE, log.p = FALSE)
qGE(p, mu = 2, lower.tail = TRUE, log.p = FALSE, max.value=10000)
rGE(n, mu = 2)
```


Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
<code>max.value</code>	constant; generates a sequence of values for the cdf function

Details

The parameterization of the Geometric distribution in the function `GE` is

$$f(y|mu) = (1 - p)^y p$$

where $p = 1/(mu + 1)$ for $y \geq 0$ and $mu > 0$.

Value

returns a `gamlss.family` object which can be used to fit a Geometric distribution in the `gamlss()` function.

Author(s)

Bob Rigby, Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Fiona McElduff and Kalliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, 54, part 3, pp 507–554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. 23, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```

par(mfrow=c(2,2))
y<-seq(0,20,1)
plot(y, dGE(y), type="h")
q <- seq(0, 20, 1)
plot(q, pGE(q), type="h")
p<-seq(0.0001,0.999,0.05)
plot(p , qGE(p), type="s")
dat <- rGE(100)
hist(dat)
#summary(gamlss(dat~1, family="GE"))

```

gen.Family

Functions to generate log and logit distributions from existing continuous gamlss.family distributions

Description

There are five functions here. Only the functions Family and gen.Family should be used (see details).

Usage

```

Family.d(family = "NO", type = c("log", "logit"), ...)
Family.p(family = "NO", type = c("log", "logit"), ...)
Family.q(family = "NO", type = c("log", "logit"), ...)
Family.r(family = "NO", type = c("log", "logit"), ...)
Family(family = "NO", type = c("log", "logit"), local = TRUE, ...)
gen.Family(family = "NO", type = c("log", "logit"), ...)

```

Arguments

family	a continuous gamlss.family distribution
type	the type of transformation only "log" and "logit" are allowed
local	It is TRUE if is called within gamlss() otherwise is FALSE
...	for passing extra arguments

Details

The function gen.Family creates the standard d,p,q,r functions for the distribution plus the fitting gamlss.family. For example gen.Family("NO", "logit") will generate the functions dlogitNO(), plogitNO(), qlongitNO(), rlogitNO() and dlogitNO(). The latest function can be used in family argument of gamlss() to fit a logic-Normal distribution i.e. family=logitNO. The same fitting can be achieved by using family=Family("NO", "logit"). Here the required dlogitNO(), plogitNO() and logitNO() functions are generated locally within the gamlss() environment.

Value

The function `gen.Family` returns the `d`, `p`, `q` `r` functions plus the fitting function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org> and Bob Rigby

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

Examples

```
# generating a log t distribution
gen.Family("TF")
# plotting the d, p, q, and r functions
op<-par(mfrow=c(2,2))
curve(dlogTF(x, mu=0), 0, 10)
curve(plogTF(x, mu=0), 0, 10)
curve(qlogTF(x, mu=0), 0, 1)
Y<- rlogTF(200)
hist(Y)
par(op)

# different mu
curve(dlogTF(x, mu=-1, sigma=1, nu=10), 0, 5, ylim=c(0,1))
curve(dlogTF(x, mu=0, sigma=1, nu=10), 0, 5, add=TRUE, col="red", lty=2)
curve(dlogTF(x, mu=1, sigma=1, nu=10), 0, 5, add=TRUE, col="blue", lty=3)

# different sigma
curve(dlogTF(x, mu=0, sigma=.5, nu=10), 0, 5, ylim=c(0,1))
curve(dlogTF(x, mu=0, sigma=1, nu=10), 0, 5, add=TRUE, col="red", lty=2)
curve(dlogTF(x, mu=0, sigma=2, nu=10), 0, 5, add=TRUE, col="blue", lty=3)

# different degrees of freedom nu
curve(dlogTF(x, mu=0, sigma=1, nu=1), 0, 5, ylim=c(0,.8), n = 1001)
curve(dlogTF(x, mu=0, sigma=1, nu=2), 0, 5, add=TRUE, col="red", lty=2)
curve(dlogTF(x, mu=0, sigma=1, nu=5), 0, 5, add=TRUE, col="blue", lty=3)

# generating a logit t distribution
gen.Family("TF", "logit")
```

```

# plotting the d, p, q, and r functions
op<-par(mfrow=c(2,2))
curve(dlogitTF(x, mu=0), 0, 1)
curve(plogitTF(x, mu=0), 0, 1)
curve(qlogitTF(x, mu=0), 0, 1)
abline(v=1)
Y<- rlogitTF(200)
hist(Y)
par(op)

# different mu
curve(dlogitTF(x, mu=-2, sigma=1, nu=10), 0, 1, ylim=c(0,5))
curve(dlogitTF(x, mu=0, sigma=1, nu=10), 0, 1, add=TRUE, col="red", lty=2)
curve(dlogitTF(x, mu=2, sigma=1, nu=10), 0, 1, add=TRUE, col="blue", lty=3)

# different sigma
curve(dlogitTF(x, mu=0, sigma=1, nu=10), 0, 1, ylim=c(0,2.5))
curve(dlogitTF(x, mu=0, sigma=2, nu=10), 0, 1, add=TRUE, col="red", lty=2)
curve(dlogitTF(x, mu=0, sigma=.7, nu=10), 0, 1, add=TRUE, col="blue", lty=3)

# different degrees of freedom nu
curve(dlogitTF(x, mu=0, sigma=1, nu=1), 0, 1, ylim=c(0,1.6))
curve(dlogitTF(x, mu=0, sigma=1, nu=2), 0, 1, add=TRUE, col="red", lty=2)
curve(dlogitTF(x, mu=0, sigma=1, nu=5), 0, 1, add=TRUE, col="blue", lty=3)

```

 GEOM

Geometric distribution for fitting a GAMLSS model

Description

The function `GEOM()` defines the Geometric distribution, a one parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with mean equal to the parameter `mu`. The functions `dGEOM`, `pGEOM`, `qGEOM` and `rGEOM` define the density, distribution function, quantile function and random generation for the GEOM parameterization of the Geometric distribution.

Usage

```

GEOM(mu.link = "log")
dGEOM(x, mu = 2, log = FALSE)
pGEOM(q, mu = 2, lower.tail = TRUE, log.p = FALSE)
qGEOM(p, mu = 2, lower.tail = TRUE, log.p = FALSE, max.value=10000)
rGEOM(n, mu = 2)

```

Arguments

`mu.link` Defines the `mu.link`, with log link as the default for the `mu` parameter

<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
<code>max.value</code>	constant; generates a sequence of values for the cdf function.

Details

The parameterization of the Geometric distribution in the function `GEOM` is

$$f(y|\mu) = (1 - p)^y p$$

where $p = 1/(mu + 1)$ for $y \geq 0$ and $mu > 0$.

Value

returns a `gamlss.family` object which can be used to fit a Geometric distribution in the `gamlss()` function.

Author(s)

Fiona McElduff, Bob Rigby and Mikis Stasinopoulos.

References

- Johnson, N. L., Kemp, A. W., and Kotz, S. (2005). *Univariate discrete distributions*. Wiley.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, 54, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. 23, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```

par(mfrow=c(2,2))
y<-seq(0,20,1)
plot(y, dGEOM(y), type="h")
q <- seq(0, 20, 1)
plot(q, pGEOM(q), type="h")
p<-seq(0.0001,0.999,0.05)
plot(p , qGEOM(p), type="s")
dat <- rGEOM(100)
hist(dat)
#summary(gamlss(dat~1, family=GEOM))

```

GG

*Generalized Gamma distribution for fitting a GAMLSS***Description**

The function GG defines the generalized gamma distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The parameterization used has the mean of the distribution equal to μ and the variance equal to $(\sigma^2)(\mu^2)$. The functions `dGG`, `pGG`, `qGG` and `rGG` define the density, distribution function, quantile function and random generation for the specific parameterization of the generalized gamma distribution defined by function GG.

Usage

```

GG(mu.link = "log", sigma.link = "log",
   nu.link = "identity")
dGG(x, mu=1, sigma=0.5, nu=1,
    log = FALSE)
pGG(q, mu=1, sigma=0.5, nu=1, lower.tail = TRUE,
    log.p = FALSE)
qGG(p, mu=1, sigma=0.5, nu=1, lower.tail = TRUE,
    log.p = FALSE )
rGG(n, mu=1, sigma=0.5, nu=1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse" and "identity"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other links are "inverse" and "identity"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>sigma</code> parameter, other links are $1/nu^2$ and "log"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values

<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of shape parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The specific parameterization of the generalized gamma distribution used in GG is

$$f(y|\mu, \sigma, \nu) = \frac{\theta^\theta z^\theta \nu e^{(-\theta z)}}{(\Gamma(\theta) y)}$$

where $z = (y/\mu)^\nu$, $\theta = 1/(\sigma^2|\nu|^2)$ for $y > 0$, $\mu > 0$, $\sigma > 0$ and $-\infty < \nu < +\infty$. Note that for $\nu = 0$ the distribution is log normal.

Value

GG() returns a `gamlss.family` object which can be used to fit a generalized gamma distribution in the `gamlss()` function. `dGG()` gives the density, `pGG()` gives the distribution function, `qGG()` gives the quantile function, and `rGG()` generates random deviates.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Nicoleta Motpan

References

- Lopatzidis, A. and Green, P. J. (2000), Nonparametric quantile regression using the gamma distribution, unpublished.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [GA](#)

Examples

```

y<-rGG(100,mu=1,sigma=0.1, nu=-.5) # generates 100 random observations
hist(y)
# library(gamlss)
#histDist(y, family=GG)
#m1 <-gamlss(y~1,family=GG)
#prof.dev(m1, "nu", min=-2, max=2, step=0.2)

```

GIG

*Generalized Inverse Gaussian distribution for fitting a GAMLSS***Description**

The function GIG defines the generalized inverse gaussian distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions DIG, pGIG, GIG and rGIG define the density, distribution function, quantile function and random generation for the specific parameterization of the generalized inverse gaussian distribution defined by function GIG.

Usage

```

GIG(mu.link = "log", sigma.link = "log",
     nu.link = "identity")
dGIG(x, mu=1, sigma=1, nu=1,
     log = FALSE)
pGIG(q, mu=1, sigma=1, nu=1, lower.tail = TRUE,
     log.p = FALSE)
qGIG(p, mu=1, sigma=1, nu=1, lower.tail = TRUE,
     log.p = FALSE)
rGIG(n, mu=1, sigma=1, nu=1, ...)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse" and "identity"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other links are "inverse" and "identity"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter, other links are "inverse" and "log"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of shape parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

p	vector of probabilities
n	number of observations. If length(n) > 1, the length is taken to be the number required
...	for extra arguments

Details

The specific parameterization of the generalized inverse gaussian distribution used in GIG is $f(y|\mu, \sigma, \nu) = \left(\frac{c}{\mu}\right)^\nu \left(\frac{y^{\nu-1}}{2K(\frac{1}{\sigma}, \nu)}\right) \left(\exp\left(\left(\frac{-1}{2\sigma}\right)\left(\frac{cy}{\mu} + \frac{\mu}{cy}\right)\right)\right)$ where $c = \frac{K(\frac{1}{\sigma}, \nu+1)}{K(\frac{1}{\sigma}, \nu)}$, for $y > 0$, $\mu > 0$, $\sigma > 0$ and $-\infty < \nu < +\infty$.

Value

GIG() returns a `gamlss.family` object which can be used to fit a generalized inverse gaussian distribution in the `gamlss()` function. `DIG()` gives the density, `pGIG()` gives the distribution function, `GIG()` gives the quantile function, and `rGIG()` generates random deviates.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Nicoleta Motpan

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Jorgensen B. (1982) Statistical properties of the generalized inverse Gaussian distribution, Series: Lecture notes in statistics; 9, New York : Springer-Verlag.

See Also

[gamlss.family, IG](#)

Examples

```
y<-rGIG(100,mu=1,sigma=1, nu=-0.5) # generates 1000 random observations
hist(y)
# library(gamlss)
# histDist(y, family=GIG)
```

GT

*The generalized t distribution for fitting a GAMLSS***Description**

This function defines the generalized t distribution, a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dGT`, `pGT`, `qGT` and `rGT` define the density, distribution function, quantile function and random generation for the generalized t distribution.

Usage

```
GT(mu.link = "identity", sigma.link = "log", nu.link = "log",
   tau.link = "log")
dGT(x, mu = 0, sigma = 1, nu = 3, tau = 1.5, log = FALSE)
pGT(q, mu = 0, sigma = 1, nu = 3, tau = 1.5, lower.tail = TRUE,
    log.p = FALSE)
qGT(p, mu = 0, sigma = 1, nu = 3, tau = 1.5, lower.tail = TRUE,
    log.p = FALSE)
rGT(n, mu = 0, sigma = 1, nu = 3, tau = 1.5)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter.
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter.
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness <code>nu</code> parameter values
<code>tau</code>	vector of kurtosis <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function of the generalized t distribution, (GT), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = \tau \left\{ 2\sigma\nu^{1/\tau} B\left(\frac{1}{\tau}, \nu\right) [1 + |z|^\tau/\nu]^{\nu+1/\tau} \right\}^{-1}$$

where $-\infty < y < \infty$, $z = (y - \mu)/\sigma$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu > 0$ and $\tau > 0$.

Value

GT() returns a `gamlss.family` object which can be used to fit the GT distribution in the `gamlss()` function. `dGT()` gives the density, `pGT()` gives the distribution function, `qGT()` gives the quantile function, and `rGT()` generates random deviates.

Warning

The `qGT` and `rGT` are slow since they are relying on optimization for finding the quantiles

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```
GT() #
y<- rGT(200, mu=5, sigma=1, nu=1, tau=4)
hist(y)
curve(dGT(x, mu=5 ,sigma=2,nu=1, tau=4), -2, 11,
      main = "The GT density mu=5 ,sigma=1, nu=1, tau=4")
# library(gamlss)
# m1<-gamlss(y~1, family=GT)
```

Description

The function `GU` defines the Gumbel distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dGU`, `pGU`, `qGU` and `rGU` define the density, distribution function, quantile function and random generation for the specific parameterization of the Gumbel distribution.

Usage

```

GU(mu.link = "identity", sigma.link = "log")
dGU(x, mu = 0, sigma = 1, log = FALSE)
pGU(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qGU(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rGU(n, mu = 0, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. other available link is "inverse", "log" and "own")
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other links are the "inverse", "identity" and "own"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The specific parameterization of the Gumbel distribution used in GU is

$$f(y|\mu, \sigma) = \frac{1}{\sigma} \exp \left\{ \left(\frac{y - \mu}{\sigma} \right) - \exp \left(\frac{y - \mu}{\sigma} \right) \right\}$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, +\infty)$ and $\sigma > 0$.

Value

`GU()` returns a `gamlss.family` object which can be used to fit a Gumbel distribution in the `gamlss()` function. `dGU()` gives the density, `pGU()` gives the distribution function, `qGU()` gives the quantile function, and `rGU()` generates random deviates.

Note

The mean of the distribution is $\mu - 0.57722\sigma$ and the variance is $\pi^2\sigma^2/6$.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantzi-Iotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [RG](#)

Examples

```
plot(function(x) dGU(x, mu=0,sigma=1), -6, 3,
      main = "{Gumbel density mu=0,sigma=1}")
GU()# gives information about the default links for the Gumbel distribution
dat<-rGU(100, mu=10, sigma=2) # generates 100 random observations
hist(dat)
# library(gamlss)
# gamlss(dat~1,family=GU) # fits a constant for each parameter mu and sigma
```

hazardFun

Hazard functions for gamlss.family distributions

Description

The function `hazardFun()` takes as an argument a `gamlss.family` object and creates the hazard function for it. The function `gen.hazard()` generates a hazard function called `hNAME` where `NAME` is a `gamlss.family` i.e. `hGA()`.

Usage

```
hazardFun(family = "NO", ...)
gen.hazard(family = "NO", ...)
```

Arguments

```
family      a gamlss.family object
...         for passing extra arguments
```

Value

A hazard function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Vlasios Voudouris

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
gen.hazard("WEI2")
y<-seq(0,10,by=0.01)
plot(hWEI2(y, mu=1, sigma=1)~y, type="l", col="black", ylab="h(y)", ylim=c(0,2.5))
lines(hWEI2(y, mu=1, sigma=1.2)~y, col="red",lt=2,lw=2)
lines(hWEI2(y, mu=1, sigma=.5)~y, col="blue",lt=3,lw=2)
```

 IG

Inverse Gaussian distribution for fitting a GAMLSS

Description

The function `IG()`, or equivalently `Inverse.Gaussian()`, defines the inverse Gaussian distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dIG`, `pIG`, `qIG` and `rIG` define the density, distribution function, quantile function and random generation for the specific parameterization of the Inverse Gaussian distribution defined by function `IG`.

Usage

```
IG(mu.link = "log", sigma.link = "log")
dIG(x, mu = 1, sigma = 1, log = FALSE)
pIG(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qIG(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rIG(n, mu = 1, sigma = 1, ...)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
<code>...</code>	<code>...</code> can be used to pass the <code>uppr.limit</code> argument to <code>qIG</code>

Details

Definition file for inverse Gaussian distribution.

$$f(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi\sigma^2 y^3}} \exp\left\{-\frac{1}{2\mu^2\sigma^2 y} (y - \mu)^2\right\}$$

for $y > 0$, $\mu > 0$ and $\sigma > 0$.

Value

returns a `gamlss.family` object which can be used to fit a inverse Gaussian distribution in the `gamlss()` function.

Note

μ is the mean and $\sigma^2\mu^3$ is the variance of the inverse Gaussian

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>)

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [GA](#), [GIG](#)

Examples

```
IG()# gives information about the default links for the normal distribution
# library(gamlss)
# data(rent)
# gamlss(R~cs(F1),family=IG, data=rent) #
plot(function(x)dIG(x, mu=1,sigma=.5), 0.01, 6,
      main = "{Inverse Gaussian density mu=1,sigma=0.5}")
plot(function(x)pIG(x, mu=1,sigma=.5), 0.01, 6,
      main = "{Inverse Gaussian cdf mu=1,sigma=0.5}")
```

 IGAMMA

Inverse Gamma distribution for fitting a GAMLSS

Description

The function `IGAMMA()` defines the Inverse Gamma distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with parameters `mu` (the mode) and `sigma`. The functions `dIGAMMA`, `pIGAMMA`, `qIGAMMA` and `rIGAMMA` define the density, distribution function, quantile function and random generation for the IGAMMA parameterization of the Inverse Gamma distribution.

Usage

```
IGAMMA(mu.link = "log", sigma.link="log")
dIGAMMA(x, mu = 1, sigma = .5, log = FALSE)
pIGAMMA(q, mu = 1, sigma = .5, lower.tail = TRUE, log.p = FALSE)
qIGAMMA(p, mu = 1, sigma = .5, lower.tail = TRUE, log.p = FALSE)
rIGAMMA(n, mu = 1, sigma = .5)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with <code>log</code> link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with <code>log</code> as the default for the <code>sigma</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if <code>TRUE</code> , probabilities <code>p</code> are given as <code>log(p)</code>
<code>lower.tail</code>	logical; if <code>TRUE</code> (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The parameterization of the Inverse Gamma distribution in the function IGAMMA is

$$f(y|\mu, \sigma) = \frac{[\mu(\alpha + 1)]^\alpha}{\Gamma(\alpha)} y^{-(\alpha+1)} \exp\left[-\frac{\mu(\alpha + 1)}{y}\right]$$

where $\alpha = 1/(\sigma^2)$ for $y > 0$, $\mu > 0$ and $\sigma > 0$.

Value

returns a `gamlss.family` object which can be used to fit an Inverse Gamma distribution in the `gamlss()` function.

Note

For the function IGAMMA(), *mu* is the mode of the Inverse Gamma distribution.

Author(s)

Fiona McElduff, Bob Rigby and Mikis Stasinopoulos.

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, 54, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. 23, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [GA](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(0.2,20,0.2)
plot(y, dIGAMMA(y), type="l")
q <- seq(0.2, 20, 0.2)
plot(q, pIGAMMA(q), type="l")
p<-seq(0.0001,0.999,0.05)
plot(p , qIGAMMA(p), type="l")
dat <- rIGAMMA(50)
hist(dat)
#summary(gamlss(dat~1, family="IGAMMA"))
```

Description

This function defines the , a four parameter distribution, for a `gamlss` family object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dJSU`, `pJSU`, `qJSU` and `rJSU` define the density, distribution function, quantile function and random generation for the the Johnson's Su distribution.

Usage

```
JSU(mu.link = "identity", sigma.link = "log", nu.link = "identity", tau.link = "log")
dJSU(x, mu = 0, sigma = 1, nu = 1, tau = 0.5, log = FALSE)
pJSU(q, mu = 0, sigma = 1, nu = 1, tau = 0.5, lower.tail = TRUE, log.p = FALSE)
qJSU(p, mu = 0, sigma = 1, nu = 0, tau = 0.5, lower.tail = TRUE, log.p = FALSE)
rJSU(n, mu = 0, sigma = 1, nu = 0, tau = 0.5)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the mu parameter. Other links are "inverse" "log" ans "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter. Other links are "inverse", "identity" ans "own"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the nu parameter. Other links are "onverse", "log" and "own"
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the tau parameter. Other links are "onverse", "identity" ans "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness nu parameter values
<code>tau</code>	vector of kurtosis tau parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function of the Johnson's SU distribution, (JSU), is defined as

$$f(y|n, \mu, \sigma, \nu, \tau) = \frac{1}{c\sigma} \frac{1}{\tau(z^2 + 1)^{\frac{1}{2}}} \frac{1}{\sqrt{2\pi}} \exp\left[-\frac{1}{2}r^2\right]$$

for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$. where $r = -\nu + \frac{1}{\tau} \sinh^{-1}(z)$, $z = \frac{y - (\mu + c\sigma w^{\frac{1}{2}} \sinh \Omega)}{c\sigma}$, $c = [\frac{1}{2}(w - 1)(w \cosh 2\Omega + 1)]^{\frac{1}{2}}$, $w = e^{\tau^2}$ and $\Omega = -\nu\tau$.

This is a reparameterization of the original Johnson Su distribution, Johnson (1954), so the parameters μ and σ are the mean and the standard deviation of the distribution. The parameter ν determines the skewness of the distribution with $\nu > 0$ indicating positive skewness and $\nu < 0$ negative. The parameter τ determines the kurtosis of the distribution. τ should be positive and most likely in the region from zero to 1. As τ goes to 0 (and for $\nu = 0$) the distribution approaches the the Normal density function. The distribution is appropriate for leptokurtic data that is data with kurtosis larger than the Normal distribution one.

Value

JSU() returns a `gamlss.family` object which can be used to fit a Johnson's Su distribution in the `gamlss()` function. `dJSU()` gives the density, `pJSU()` gives the distribution function, `qJSU()` gives the quantile function, and `rJSU()` generates random deviates.

Warning

The function JSU uses first derivatives square in the fitting procedure so standard errors should be interpreted with caution

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Johnson, N. L. (1954). Systems of frequency curves derived from the first law of Laplace., *Trabajos de Estadística*, **5**, 283-291.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSUo](#), [BCT](#)

Examples

```
JSUo()
plot(function(x)dJSU(x, mu=0,sigma=1,nu=-1, tau=.5), -4, 4,
      main = "The JSU density mu=0,sigma=1,nu=-1, tau=.5")
plot(function(x) pJSU(x, mu=0,sigma=1,nu=-1, tau=.5), -4, 4,
      main = "The JSU cdf mu=0, sigma=1, nu=-1, tau=.5")
# library(gamlss)
# data(abdom)
# h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=JSU, data=abdom)
```

 JSUo

The original Johnson's Su distribution for fitting a GAMLSS

Description

This function defines the , a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dJSUo`, `pJSUo`, `qJSUo` and `rJSUo` define the density, distribution function, quantile function and random generation for the the Johnson's Su distribution.

Usage

```
JSUo(mu.link = "identity", sigma.link = "log", nu.link = "identity", tau.link = "log")
dJSUo(x, mu = 0, sigma = 1, nu = 0, tau = 1, log = FALSE)
pJSUo(q, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE, log.p = FALSE)
qJSUo(p, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE, log.p = FALSE)
rJSUo(n, mu = 0, sigma = 1, nu = 0, tau = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. Other links are "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse", "identity" and "own"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter. Other links are "inverse", "log" and "own"
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter. Other links are "inverse", "identity" and "own"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness <code>nu</code> parameter values
<code>tau</code>	vector of kurtosis <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .

<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The probability density function of the ordinal Johnson's SU distribution, (JSU), is defined as

$$f(y|n, \mu, \sigma, \nu, \tau) = \frac{\tau}{\sigma} \frac{1}{(z^2 + 1)^{\frac{1}{2}}} \frac{1}{\sqrt{2\pi}} \exp\left[-\frac{1}{2}r^2\right]$$

for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$. where $z = \frac{(y-\mu)}{\sigma}$, $r = \nu + \tau \sinh^{-1}(z)$.

Value

`JSUo()` returns a `gamlss.family` object which can be used to fit a Johnson's Su distribution in the `gamlss()` function. `dJSUo()` gives the density, `pJSUo()` gives the distribution function, `qJSUo()` gives the quantile function, and `rJSUo()` generates random deviates.

Warning

The function JSU uses first derivatives square in the fitting procedure so standard errors should be interpreted with caution. It is recommended to be used only with `method=mixed(2, 20)`

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org> and Bob Rigby

References

- Johnson, N. L. (1954). Systems of frequency curves derived from the first law of Laplace., *Trabajos de Estadística*, **5**, 283-291.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```

JSUo()
plot(function(x)dJSUo(x, mu=0,sigma=1,nu=-1, tau=.5), -4, 15,
      main = "The JSUo density mu=0,sigma=1,nu=-1, tau=.5")
plot(function(x) pJSUo(x, mu=0,sigma=1,nu=-1, tau=.5), -4, 15,
      main = "The JSUo cdf mu=0, sigma=1, nu=-1, tau=.5")
# library(gamlss)
# data(abdom)
# h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=JSUo,
#           data=abdom, method=mixed(2,20))
# plot(h)

```

 LG

Logarithmic and zero adjusted logarithmic distributions for fitting a GAMLSS model

Description

The function LG defines the logarithmic distribution, a one parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dLG`, `pLG`, `qLG` and `rLG` define the density, distribution function, quantile function and random generation for the logarithmic, `LG()`, distribution.

The function ZALG defines the zero adjusted logarithmic distribution, a two parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZALG`, `pZALG`, `qZALG` and `rZALG` define the density, distribution function, quantile function and random generation for the inflated logarithmic, `ZALG()`, distribution.

Usage

```

LG(mu.link = "logit")
dLG(x, mu = 0.5, log = FALSE)
pLG(q, mu = 0.5, lower.tail = TRUE, log.p = FALSE)
qLG(p, mu = 0.5, lower.tail = TRUE, log.p = FALSE, max.value = 10000)
rLG(n, mu = 0.5)
ZALG(mu.link = "logit", sigma.link = "logit")
dZALG(x, mu = 0.5, sigma = 0.1, log = FALSE)
pZALG(q, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZALG(p, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZALG(n, mu = 0.5, sigma = 0.1)

```

Arguments

<code>mu.link</code>	defines the <code>mu.link</code> , with <code>logit</code> link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	defines the <code>sigma.link</code> , with <code>logit</code> link as the default for the <code>sigma</code> parameter which in this case is the probability at zero.
<code>x</code>	vector of (non-negative integer)

<code>mu</code>	vector of positive means
<code>sigma</code>	vector of probabilities at zero
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>max.value</code>	valued needed for the numerical calculation of the q-function

Details

For the definition of the distributions see Rigby and Stasinopoulos (2010) below.

Value

The function `LG` and `ZALG` return a `gamlss.family` object which can be used to fit a logarithmic and a zero inflated logarithmic distributions respectively in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Johnson, Norman Lloyd; Kemp, Adrienne W; Kotz, Samuel (2005). "Chapter 7: Logarithmic and Lagrangian distributions". *Univariate discrete distributions* (3 ed.). John Wiley & Sons. ISBN 9780471272465.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.com/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.org/>)

See Also

[gamlss.family](#), [P0](#), [ZAP](#)

Examples

```

LG()
ZAP()
# creating data and plotting them
dat <- rLG(1000, mu=.3)
r <- barplot(table(dat), col='lightblue')
dat1 <- rZALG(1000, mu=.3, sigma=.1)
r1 <- barplot(table(dat1), col='lightblue')

```

LNO

Log Normal distribution for fitting in GAMLSS

Description

The functions LOGNO and LOGNO2 define a `gamlss.family` distribution to fits the log-Normal distribution. The difference between them is that while LOGNO retains the original parametrization for μ , (identical to the normal distribution NO) and therefore $\mu = (-\infty, +\infty)$, the function LOGNO2 use μ as the median, so $\mu = (0, +\infty)$.

The function LNO is more general and can fit a Box-Cox transformation to data using the `gamlss()` function. In the LOGNO (and LOGNO2) there are two parameters involved μ σ , while in the LNO there are three parameters μ σ , and the transformation parameter ν . The transformation parameter ν in LNO is a 'fixed' parameter (not estimated) and it has its default value equal to zero allowing the fitting of the log-normal distribution as in LOGNO. See the example below on how to fix ν to be a particular value. In order to estimate (or model) the parameter ν , use the [gamlss.family BCCG](#) distribution which uses a reparameterized version of the the Box-Cox transformation. The functions `dLOGNO`, `pLOGNO`, `qLOGNO` and `rLOGNO` define the density, distribution function, quantile function and random generation for the specific parameterization of the log-normal distribution.

The functions `dLOGNO2`, `pLOGNO2`, `qLOGNO2` and `rLOGNO2` define the density, distribution function, quantile function and random generation when μ is the median of the log-normal distribution.

The functions `dLNO`, `pLNO`, `qLNO` and `rLNO` define the density, distribution function, quantile function and random generation for the specific parameterization of the log-normal distribution and more generally a Box-Cox transformation.

Usage

```

LNO(mu.link = "identity", sigma.link = "log")
LOGNO(mu.link = "identity", sigma.link = "log")
LOGNO2(mu.link = "log", sigma.link = "log")
dLNO(x, mu = 1, sigma = 0.1, nu = 0, log = FALSE)
dLOGNO(x, mu = 0, sigma = 1, log = FALSE)
dLOGNO2(x, mu = 1, sigma = 1, log = FALSE)
pLNO(q, mu = 1, sigma = 0.1, nu = 0, lower.tail = TRUE, log.p = FALSE)
pLOGNO(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
pLOGNO2(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)

```



```

qLNO(p, mu = 1, sigma = 0.1, nu = 0, lower.tail = TRUE, log.p = FALSE)
qLOGNO(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qLOGNO2(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rLNO(n, mu = 1, sigma = 0.1, nu = 0)
rLOGNO(n, mu = 0, sigma = 1)
rLOGNO2(n, mu = 1, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" or "log" link depending on the parametrization
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter. Other links are "inverse", "identity" and "own"
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of shape parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function in LOGNO is defined as

$$f(y|\mu, \sigma) = \frac{1}{y\sqrt{2\pi}\sigma} \exp\left[-\frac{1}{2\sigma^2}(\log(y) - \mu)^2\right]$$

for $y > 0$, $\mu = (-\infty, +\infty)$ and $\sigma > 0$.

The probability density function in LNO is defined as

$$f(y|\mu, \sigma, \nu) = \frac{1}{\sqrt{2\pi}\sigma} y^{\nu-1} \exp\left[-\frac{1}{2\sigma^2}(z - \mu)^2\right]$$

where if $\nu \neq 0$ $z = (y^\nu - 1)/\nu$ else $z = \log(y)$ and $z \sim N(0, \sigma^2)$, for $y > 0$, $\mu > 0$, $\sigma > 0$ and $\nu = (-\infty, +\infty)$.

Value

LNO() returns a `gamlss.family` object which can be used to fit a log-normal distribution in the `gamlss()` function. `dLNO()` gives the density, `pLNO()` gives the distribution function, `qLNO()` gives the quantile function, and `rLNO()` generates random deviates.

Warning

This is a two parameter fit for μ and σ while ν is fixed. If you wish to model ν use the `gamlss` family `BCCG`.

Note

μ is the mean of z (and also the median of y), the Box-Cox transformed variable and σ is the standard deviation of z and approximate the coefficient of variation of y

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Box, G. E. P. and Cox, D. R. (1964) An analysis of transformations (with discussion), *J. R. Statist. Soc. B.*, **26**, 211–252
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), `BCCG`

Examples

```
LOGNO()# gives information about the default links for the log normal distribution
LOGNO2()
LNO()# gives information about the default links for the Box Cox distribution

# plotting the d, p, q, and r functions
op<-par(mfrow=c(2,2))
curve(dLOGNO(x, mu=0), 0, 10)
curve(pLOGNO(x, mu=0), 0, 10)
curve(qLOGNO(x, mu=0), 0, 1)
Y<- rLOGNO(200)
hist(Y)
par(op)

# plotting the d, p, q, and r functions
op<-par(mfrow=c(2,2))
curve(dLOGNO2(x, mu=1), 0, 10)
curve(pLOGNO2(x, mu=1), 0, 10)
curve(qLOGNO2(x, mu=1), 0, 1)
```

```

Y<- rLOGNO(200)
hist(Y)
par(op)

# library(gamlss)
# data(abdom)
# h1<-gamlss(y~cs(x), family=LOGNO, data=abdom)#fits the log-Normal distribution
# h2<-gamlss(y~cs(x), family=LNO, data=abdom) #should be identical to the one above
# to change to square root transformation, i.e. fix nu=0.5
# h3<-gamlss(y~cs(x), family=LNO, data=abdom, nu.fix=TRUE, nu.start=0.5)

```

LO

*Logistic distribution for fitting a GAMLSS***Description**

The function `LO()`, or equivalently `Logistic()`, defines the logistic distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`

Usage

```

LO(mu.link = "identity", sigma.link = "log")
dLO(x, mu = 0, sigma = 1, log = FALSE)
pLO(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qLO(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rLO(n, mu = 0, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

Definition file for Logistic distribution.

$$f(y|\mu, \sigma) = \frac{1}{\sigma} e^{-\frac{y-\mu}{\sigma}} [1 + e^{-\frac{y-\mu}{\sigma}}]^{-2}$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, \infty)$ and $\sigma > 0$.

Value

L0() returns a `gamlss.family` object which can be used to fit a logistic distribution in the `gamlss()` function. `dL0()` gives the density, `pL0()` gives the distribution function, `qL0()` gives the quantile function, and `rL0()` generates random deviates for the logistic distribution. The latest functions are based on the equivalent R functions for logistic distribution.

Note

μ is the mean and $\sigma\pi/\sqrt{3}$ is the standard deviation for the logistic distribution

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [N0](#), [TF](#)

Examples

```
L0()# gives information about the default links for the Logistic distribution
plot(function(y) dL0(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) pL0(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) qL0(y, mu=10 ,sigma=2), 0, 1)
# library(gamlss)
# data(abdom)
# h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=L0, data=abdom) # fits
# plot(h)
```

LOGITNO

*Logit Normal distribution for fitting in GAMLSS***Description**

The functions `dLOGITNO`, `pLOGITNO`, `qLOGITNO` and `rLOGITNO` define the density, distribution function, quantile function and random generation for the logit-normal distribution. The function `LOGITNO` can be used for fitting the distribution in `gamlss()`.

Usage

```
LOGITNO(mu.link = "logit", sigma.link = "log")
dLOGITNO(x, mu = 0.5, sigma = 1, log = FALSE)
pLOGITNO(q, mu = 0.5, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qLOGITNO(p, mu = 0.5, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rLOGITNO(n, mu = 0.5, sigma = 1)
```

Arguments

<code>mu.link</code>	the link function for mu
<code>sigma.link</code>	the link function for sigma
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The probability density function in `LOGITNO` is defined as

$$f(y|\mu, \sigma) = \frac{1}{y(1-y)\sqrt{2\pi\sigma}} \exp\left[-\frac{1}{2\sigma^2}(\log(y/(1-y)) - \log(\mu/(1-\mu)))^2\right]$$

for $0 < y < 1$, $\mu \in (0, 1)$ and $\sigma > 0$.

Value

`LOGITNO()` returns a `gamlss.family` object which can be used to fit a logit-normal distribution in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos, Bob Rigby

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [LOGNO](#)

Examples

```
# plotting the d, p, q, and r functions
op<-par(mfrow=c(2,2))
curve(dLOGITNO(x), 0, 1)
curve(pLOGITNO(x), 0, 1)
curve(qLOGITNO(x), 0, 1)
Y<- rLOGITNO(200)
hist(Y)
par(op)
```

```
# plotting the d, p, q, and r functions
# sigma 3
op<-par(mfrow=c(2,2))
curve(dLOGITNO(x, sigma=3), 0, 1)
curve(pLOGITNO(x, sigma=3), 0, 1)
curve(qLOGITNO(x, sigma=3), 0, 1)
Y<- rLOGITNO(200, sigma=3)
hist(Y)
par(op)
```

make.link.gamlss

Create a Link for GAMLSS families

Description

The function `make.link.gamlss()` is used with `gamlss.family` distributions in package `gamlss()`. Given a link, it returns a link function, an inverse link function, the derivative $d\text{par}/d\text{eta}$ where 'par' is the appropriate distribution parameter and a function for checking the domain. It differs from the usual `make.link` of `glm()` by having extra links as the `logshift1`, and the `own`. For the use of the

own link see the example bellow. show.link provides a way in which the user can identify the link functions available for each gamlss distribution. If your required link function is not available for any of the gamlss distributions you can add it in.

Usage

```
make.link.gamlss(link)
show.link(family = "NO")
```

Arguments

link	character or numeric; one of "logit", "probit", "cloglog", "identity", "log", "sqrt", "1/mu^2", "inverse", "logshifted", "logitshifted", or number, say lambda resulting in power link μ^λ .
family	a gamlss distribution family

Details

The own link function is added to allow the user greater flexibility. In order to used the own link function for any of the parameters of the distribution the own link should appear in the available links for this parameter. You can check this using the function show.link. If the own do not appear in the list you can create a new function for the distribution in which own is added in the list. For example the first line of the code of the binomial distribution, BI, has change from

```
"mstats <- checklink("mu.link", "Binomial", substitute(mu.link), c("logit", "probit", "cloglog", "log")),
in version 1.0-0 of gamlss, to
```

```
"mstats <- checklink("mu.link", "Binomial", substitute(mu.link), c("logit", "probit", "cloglog", "log",
"own"))
```

in version 1.0-1. Given that the parameter has own as an option the user needs also to define the following four new functions in order to used an own link.

i) own.linkfun

ii) own.linkinv

iii) own.mu.eta and

iv) own.valideta.

An example is given below.

Only one parameter of the distribution at a time is allowed to have its own link, (unless the same four own functions above are suitable for more that one parameter of the distribution).

Note that from **gamlss** version 1.9-0 the user can introduce its own link function by define an appropriate function, (see the example below).

Value

For the make.link.gamlss a list with components

linkfun: Link function function(parameter)

linkinv: Inverse link function function(eta)

mu.eta: Derivative function(eta) dparameter/deta

valideta: function(eta) TRUE if all of eta is in the domain of linkinv.

For the show.link a list with components the available links for the distribution parameters

Note

For the links involving parameters as in logshifted and logitshifted the parameters can be passed in the definition of the distribution by calling the checklink function, for example in the definition of the tau parameter in BCPE distribution the following call is made: `tstats <- checklink("tau.link", "Bo`

Author(s)

Mikis Stasinopoulos and Bob Rigby

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
str(make.link.gamlss("logshiftt1"))
l2<-make.link.gamlss("logshiftt1")
l2$linkfun(2) # should close to zero (Note that 0.00001 is added)
l2$linkfun(1-0.00001) # should be -Inf but it is large negative
#-----
# now use the own link function
# first if the distribution allows you
show.link(BI)
# seems OK now define the four own functions
# First try the probit link using the own link function
# 1: the linkfun function
own.linkfun <- function(mu) { qNO(p=mu)}
# 2: the inverse link function
own.linkinv <- function(eta) {
  thresh <- -qNO(.Machine$double.eps)
  eta <- pmin(thresh, pmax(eta, -thresh))
  pNO(eta)}
# 3: the dmua/deta function
own.mu.eta <- function(eta) pmax(dNO(eta), .Machine$double.eps)
# 4: the valideta function
```



```

own.valideta <- function(eta) TRUE

## bring the data
# library(gamlss)
#data(aep)
# fitting the model using "own"
# h1<-gamlss(y~ward+loglos+year, family=BI(mu.link="own"), data=aep)
# model h1 should be identical to the probit
# h2<-gamlss(y~ward+loglos+year, family=BI(mu.link="probit"), data=aep)
# now using a function instead of "own"
probittest <- function()
{
linkfun <- function(mu) { qNO(p=mu)}
linkinv <- function(eta)
  {
    thresh <- -qNO(.Machine$double.eps)
    eta <- pmin(thresh, pmax(eta, -thresh))
    pNO(eta)
  }
mu.eta <- function(eta) pmax(dNO(eta), .Machine$double.eps)
valideta <- function(eta) TRUE
link <- "probitTest"
structure(list(linkfun = linkfun, linkinv = linkinv, mu.eta = mu.eta,
  valideta = valideta, name = link), class = "link-gamlss")
}
# h3<-gamlss(y~ward+loglos+year, family=BI(mu.link=probittest()), data=aep)
# Second try the complementary log-log
# using the Gumbel distribution
own.linkfun <- function(mu) { qGU(p=mu)}
own.linkinv <- function(eta) {
  thresh <- -qGU(.Machine$double.eps)
  eta <- pmin(thresh, pmax(eta, -thresh))
  pGU(eta)}
own.mu.eta <- function(eta) pmax(dGU(eta), .Machine$double.eps)
own.valideta <- function(eta) TRUE
# h1 and h2 should be identical to cloglog
# h1<-gamlss(y~ward+loglos+year, family=BI(mu.link="own"), data=aep)
# h2<-gamlss(y~ward+loglos+year, family=BI(mu.link="cloglog"), data=aep)
# note that the Gumbel distribution is negatively skew
# for a positively skew link function we can used the Reverse Gumbel
revloglog <- function()
{
linkfun <- function(mu) { qRG(p=mu)}
linkinv <- function(eta) {
  thresh <- -qRG(.Machine$double.eps)
  eta <- pmin(thresh, pmax(eta, -thresh))
  pRG(eta)}
mu.eta <- function(eta) pmax(dRG(eta), .Machine$double.eps)
valideta <- function(eta) TRUE
link <- "revloglog"
structure(list(linkfun = linkfun, linkinv = linkinv, mu.eta = mu.eta,
  valideta = valideta, name = link), class = "link-gamlss")
}

```

```

# h1<-gamlss(y~ward+loglos+year, family=BI(mu.link=revloglog()), data=aep)
# a considerable improvement in the deviance
# try a shifted logit link function from -1, 1
own.linkfun <- function(mu)
  { shift = c(-1,1)
    log((mu-shift[1])/(shift[2]-mu))
  }
own.linkinv <- function(eta)
  {
  shift = c(-1,1)
  thresh <- -log(.Machine$double.eps)
  eta <- pmin(thresh, pmax(eta, -thresh))
  shift[2]-(shift[2]-shift[1])/(1 + exp(eta))
  }
own.mu.eta <- function(eta)
  {
  shift = c(-1,1)
  thresh <- -log(.Machine$double.eps)
  res <- rep(.Machine$double.eps, length(eta))
  res[abs(eta) < thresh] <- ((shift[2]-shift[1])*exp(eta)/(1 +
  exp(eta))^2)[abs(eta) < thresh]
  res
  }
own.valideta <- function(eta) TRUE
#-----
str(make.link.gamlss("own"))
l2<-make.link.gamlss("own")
l2$linkfun(0) # should be zero
l2$linkfun(1) # should be Inf
l2$linkinv(-5:5)

```

Description

The set of function presented here is useful for fitting multinomial regression within gamlss.

Usage

```

MN3(mu.link = "log", sigma.link = "log")
MN4(mu.link = "log", sigma.link = "log", nu.link = "log")
MN5(mu.link = "log", sigma.link = "log", nu.link = "log", tau.link = "log")
MULTIN(type = "3")
fittedMN(model)

dMN3(x, mu = 1, sigma = 1, log = FALSE)
dMN4(x, mu = 1, sigma = 1, nu = 1, log = FALSE)
dMN5(x, mu = 1, sigma = 1, nu = 1, tau = 1, log = FALSE)

```

```

pMN3(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
pMN4(q, mu = 1, sigma = 1, nu = 1, lower.tail = TRUE, log.p = FALSE)
pMN5(q, mu = 1, sigma = 1, nu = 1, tau = 1, lower.tail = TRUE, log.p = FALSE)

qMN3(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qMN4(p, mu = 1, sigma = 1, nu = 1, lower.tail = TRUE, log.p = FALSE)
qMN5(p, mu = 1, sigma = 1, nu = 1, tau = 1, lower.tail = TRUE, log.p = FALSE)

rMN3(n, mu = 1, sigma = 1)
rMN4(n, mu = 1, sigma = 1, nu = 1)
rMN5(n, mu = 1, sigma = 1, nu = 1, tau = 1)

```

Arguments

<code>mu.link</code>	the link function for mu
<code>sigma.link</code>	the link function for sigma
<code>nu.link</code>	the link function for nu
<code>tau.link</code>	the link function for tau
<code>x</code>	the x variable
<code>q</code>	vector of quantiles
<code>p</code>	vector of probabilities
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$ otherwise, $P[X > x]$.
<code>log.p</code>	logical; if TRUE, probabilities p are given as $\log(p)$.
<code>log</code>	logical; if TRUE, probabilities p are given as $\log(p)$.
<code>n</code>	the number of observations
<code>mu</code>	the mu parameter
<code>sigma</code>	the sigma parameter
<code>nu</code>	the nu parameter
<code>tau</code>	the tau parameter
<code>type</code>	permitted values are 2 (Binomial), 3, 4, and 5
<code>model</code>	a <code>gamlss</code> multinomial fitted model

Details

GAMLSS is in general not suitable for multinomial regression. Nevertheless multinomial regression can be fitted within GAMLSS if the response variable y has less than five categories. The function here provide the facilities to do so. The functions `MN3()`, `MN4()` and `MN5()` fit multinomial responses with 3, 4 and 5 categories respectively. The function `MULTIN()` can be used instead of `codeMN3()`, `MN4()` and `MN5()` by specifying the number of levels of the response. Note that `MULTIN(2)` will produce a binomial fit.

Value

returns a `gamlss.family` object which can be used to fit a binomial distribution in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Vlasios Voudouris

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BI](#)

Examples

```
dMN3(3)
pMN3(2)
qMN3(.6)
rMN3(10)
```

NBF

Negative Binomial Family distribution for fitting a GAMLSS

Description

The `NBF()` function defines the Negative Binomial family distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dNBF`, `pNBF`, `qNBF` and `rNBF` define the density, distribution function, quantile function and random generation for the Negative Binomial family, `NBF()`, distribution

Usage

```
NBF(mu.link = "log", sigma.link = "log", nu.link = "identity")

dNBF(x, mu = 0, sigma = 1, nu = 2, log = FALSE)

pNBF(q, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)

qNBF(p, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)

rNBF(n, mu = 0, sigma = 1, nu = 2)
```

Arguments

<code>mu.link</code>	The link function for <code>mu</code>
<code>sigma.link</code>	The link function for <code>sigma</code>
<code>nu.link</code>	The link function for <code>nu</code>
<code>x</code>	vector of (non-negative integer)
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of power parameter
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return

Details

The definition for Negative Binomial Family distribution, NBF, is similar to the Negative Binomial type I. The probability function of the NBF can be obtained by replacing σ with $\sigma\mu^{\nu-2}$ where ν is a power parameter. The distribution has mean μ and variance $\mu + \sigma\mu^{\nu}$.

Value

returns a `gamlss.family` object which can be used to fit a Negative Binomial Family distribution in the `gamlss()` function.

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Anscombe, F. J. (1950) Sampling theory of the negative binomial and logarithmic distributiona, *Biometrika*, **37**, 358-382.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[NBI](#), [NBII](#)

Examples

```

NBF() # gives information about the default links for the Negative Binomial Family
# plotting the distribution
plot(function(y) dNBF(y, mu = 10, sigma = 0.5, nu=2 ), from=0, to=40, n=40+1, type="h")
# creating random variables and plot them
tN <- table(Ni <- rNBF(1000, mu=5, sigma=0.5, nu=2))
r <- barplot(tN, col='lightblue')
## Not run:
library(gamlss)
data(species)
species <- transform(species, x=log(lake))
m6 <- gamlss(fish~poly(x,2), sigma.fo=~1, data=species, family=NBF, n.cyc=200)
fitted(m6, "nu")[1]

## End(Not run)

```

NBI

Negative Binomial type I distribution for fitting a GAMLSS

Description

The `NBI()` function defines the Negative Binomial type I distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dNBI`, `pNBI`, `qNBI` and `rNBI` define the density, distribution function, quantile function and random generation for the Negative Binomial type I, `NBI()`, distribution.

Usage

```

NBI(mu.link = "log", sigma.link = "log")
dNBI(x, mu = 1, sigma = 1, log = FALSE)
pNBI(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qNBI(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rNBI(n, mu = 1, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Definition file for Negative Binomial type I distribution.

$$f(y|\mu, \sigma) = \frac{\Gamma(y + 1/\sigma)}{\Gamma(y + 1)\Gamma(1/\sigma)} \left[\frac{(\mu\sigma)^y}{(\mu\sigma + 1)} \right]^{y+(1/\sigma)}$$

for $y = 0, 1, 2, \dots, \infty$, $\mu > 0$ and $\sigma > 0$. This parameterization is equivalent to that used by Anscombe (1950) except he used $\alpha = 1/\sigma$ instead of σ .

Value

returns a `gamlss.family` object which can be used to fit a Negative Binomial type I distribution in the `gamlss()` function.

Warning

For values of $\sigma < 0.0001$ the `d,p,q,r` functions switch to the Poisson distribution

Note

μ is the mean and $(\mu + \sigma\mu^2)^{0.5}$ is the standard deviation of the Negative Binomial type I distribution (so σ is the dispersion parameter in the usual GLM for the negative binomial type I distribution)

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

Anscombe, F. J. (1950) Sampling theory of the negative binomial and logarithmic distributions, *Biometrika*, **37**, 358-382.

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NBII](#), [PIG](#), [SI](#)

Examples

```

NBII() # gives information about the default links for the Negative Binomial type I distribution
# plotting the distribution
plot(function(y) dNBII(y, mu = 10, sigma = 0.5 ), from=0, to=40, n=40+1, type="h")
# creating random variables and plot them
tN <- table(Ni <- rNBII(1000, mu=5, sigma=0.5))
r <- barplot(tN, col='lightblue')
# library(gamlss)
# data(aids)
# h<-gamlss(y~cs(x,df=7)+qrt, family=NBII, data=aids) # fits the model
# plot(h)
# pdf.plot(family=NBII, mu=10, sigma=0.5, min=0, max=40, step=1)

```

 NBII

Negative Binomial type II distribution for fitting a GAMLSS

Description

The NBII() function defines the Negative Binomial type II distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dNBII`, `pNBII`, `qNBII` and `rNBII` define the density, distribution function, quantile function and random generation for the Negative Binomial type II, NBII(), distribution.

Usage

```

NBII(mu.link = "log", sigma.link = "log")
dNBII(x, mu = 1, sigma = 1, log = FALSE)
pNBII(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qNBII(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rNBII(n, mu = 1, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Definition file for Negative Binomial type II distribution.

$$f(y|\mu, \sigma) = \frac{\Gamma(y + (\mu/\sigma))\sigma^y}{\Gamma(\mu/\sigma)\Gamma(y + 1)(1 + \sigma)^{y+(\mu/\sigma)}}$$

for $y = 0, 1, 2, \dots, \infty$, $\mu > 0$ and $\sigma > 0$. This parameterization was used by Evans (1953) and also by Johnson *et al.* (1993) p 200.

Value

returns a `gamlss.family` object which can be used to fit a Negative Binomial type II distribution in the `gamlss()` function.

Note

μ is the mean and $[(1 + \sigma)\mu]^{0.5}$ is the standard deviation of the Negative Binomial type II distribution, so σ is a dispersion parameter

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

Evans, D. A. (1953). Experimental evidence concerning contagious distributions in ecology. *Biometrika*, **40**: 186-211.

Johnson, N. L., Kotz, S. and Kemp, A. W. (1993). *Univariate Discrete Distributions*, 2nd edn. Wiley, New York.

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NBI](#), [PIG](#), [SI](#)

Examples

```
NBII() # gives information about the default links for the Negative Binomial type II distribution
# plotting the distribution
plot(function(y) dNBII(y, mu = 10, sigma = 0.5 ), from=0, to=40, n=40+1, type="h")
# creating random variables and plot them
```

```
tN <- table(Ni <- rNBII(1000, mu=5, sigma=0.5))
r <- barplot(tN, col='lightblue')
# library(gamlss)
# data(aids)
# h<-gamlss(y~cs(x,df=7)+qrt, family=NBII, data=aids) # fits a model
# plot(h)
# pdf.plot(family=NBII, mu=10, sigma=0.5, min=0, max=40, step=1)
```

NET

*Normal Exponential t distribution (NET) for fitting a GAMLSS***Description**

This function defines the Power Exponential t distribution (NET), a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dNET`, `pNET` define the density and distribution function the NET distribution.

Usage

```
NET(mu.link = "identity", sigma.link = "log")
pNET(q, mu = 5, sigma = 0.1, nu = 1, tau = 2)
dNET(x, mu = 0, sigma = 1, nu = 1.5, tau = 2, log = FALSE)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. Other links are "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse", "identity" and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of <code>nu</code> parameter values
<code>tau</code>	vector of <code>tau</code> parameter values
<code>log</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .

Details

The NET distribution was introduced by Rigby and Stasinopoulos (1994) as a robust distribution for a response variable with heavier tails than the normal. The NET distribution is the abbreviation of the Normal Exponential Student t distribution. The NET distribution is a four parameter continuous distribution, although in the GAMLSS implementation only the two parameters, `mu` and `sigma`, of the distribution are modelled with `nu` and `tau` fixed. The distribution takes its names because it is normal up to `nu`, Exponential from `nu` to `tau` (hence $\text{abs}(\text{nu}) \leq \text{abs}(\text{tau})$) and Student-t with $\text{nu} * \text{tau} - 1$ degrees of freedom after `tau`. Maximum likelihood estimator of the third and fourth parameter can be obtained, using the GAMLSS functions, `find.hyper` or `prof.dev`.

Value

NET() returns a `gamlss.family` object which can be used to fit a Box Cox Power Exponential distribution in the `gamlss()` function. `dNET()` gives the density, `pNET()` gives the distribution function.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos, D. M. (1994), Robust fitting of an additive model for variance heterogeneity, *COMPSTAT : Proceedings in Computational Statistics*, editors:R. Dutter and W. Grossmann, pp 263-268, Physica, Heidelberg.

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCPE](#)

Examples

```
NET() #
data(abdom)
plot(function(x)dNET(x, mu=0,sigma=1,nu=2, tau=3), -5, 5)
plot(function(x)pNET(x, mu=0,sigma=1,nu=2, tau=3), -5, 5)
# fit NET with nu=1 and tau=3
# library(gamlss)
#h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=NET,
#         data=abdom, nu.start=2, tau.start=3)
#plot(h)
```

Description

The function `NO()` defines the normal distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with mean equal to the parameter `mu` and `sigma` equal the standard deviation. The functions `dNO`, `pNO`, `qNO` and `rNO` define the density, distribution function, quantile function and random generation for the NO parameterization of the normal distribution. [A alternative parameterization with `sigma` equal to the variance is given in the function `NO2()`]

Usage

```
NO(mu.link = "identity", sigma.link = "log")
dNO(x, mu = 0, sigma = 1, log = FALSE)
pNO(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qNO(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rNO(n, mu = 0, sigma = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parametrization of the normal distribution given in the function `NO()` is

$$f(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi}\sigma} \exp \left[-\frac{1}{2} \left(\frac{y - \mu}{\sigma} \right)^2 \right]$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, +\infty)$ and $\sigma > 0$.

Value

returns a `gamlss.family` object which can be used to fit a normal distribution in the `gamlss()` function.

Note

For the function `NO()`, μ is the mean and σ is the standard deviation (not the variance) of the normal distribution.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NO2](#)

Examples

```
NO()# gives information about the default links for the normal distribution
plot(function(y) dNO(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) pNO(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) qNO(y, mu=10 ,sigma=2), 0, 1)
dat<-rNO(100)
hist(dat)
# library(gamlss)
# gamlss(dat~1,family=NO) # fits a constant for mu and sigma
```

NO2

Normal distribution (with variance as sigma parameter) for fitting a GAMLSS

Description

The function NO2() defines the normal distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()` with mean equal to `mu` and variance equal to `sigma`. The functions `dNO2`, `pNO2`, `qNO2` and `rNO2` define the density, distribution function, quantile function and random generation for this specific parameterization of the normal distribution.

[A alternative parameterization with `sigma` as the standard deviation is given in the function `NO()`]

Usage

```

NO2(mu.link = "identity", sigma.link = "log")
dNO2(x, mu = 0, sigma = 1, log = FALSE)
pNO2(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qNO2(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rNO2(n, mu = 0, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parametrization of the normal distribution given in the function `NO2()` is

$$f(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi\sigma}} \exp\left[-\frac{1}{2} \frac{(y - \mu)^2}{\sigma}\right]$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, +\infty)$ and $\sigma > 0$.

Value

returns a `gamlss.family` object which can be used to fit a normal distribution in the `gamlss()` function.

Note

For the function `NO()`, μ is the mean and σ is the standard deviation (not the variance) of the normal distribution. [The function `NO2()` defines the normal distribution with σ as the variance.]

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NO](#)

Examples

```
NO()# gives information about the default links for the normal distribution
dat<-rNO(100)
hist(dat)
plot(function(y) dNO(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) pNO(y, mu=10 ,sigma=2), 0, 20)
plot(function(y) qNO(y, mu=10 ,sigma=2), 0, 1)
# library(gamlss)
# gamlss(dat~1,family=NO) # fits a constant for mu and sigma
```

NOF

Normal distribution family for fitting a GAMLSS

Description

The function `NOF()` defines a normal distribution family, which has three parameters. The distribution can be used in a GAMLSS fitting using the function `gamlss()`. The mean of NOF is equal to μ . The variance is equal to $\sigma^2 \mu^\nu$ so the standard deviation is $\sigma \mu^{\nu/2}$. The function is design for cases where the variance is proportional to a power of the mean. The functions `dNOF`, `pNOF`, `qNOF` and `rNOF` define the density, distribution function, quantile function and random generation for the NOF parametrization of the normal distribution family.

Usage

```
NOF(mu.link = "identity", sigma.link = "log", nu.link = "identity")
dNOF(x, mu = 0, sigma = 1, nu = 0, log = FALSE)
pNOF(q, mu = 0, sigma = 1, nu = 0, lower.tail = TRUE, log.p = FALSE)
qNOF(p, mu = 0, sigma = 1, nu = 0, lower.tail = TRUE, log.p = FALSE)
rNOF(n, mu = 0, sigma = 1, nu = 0)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> with "identity" link as the default for the <code>nu</code> parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of power parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parametrization of the normal distribution given in the function `NOF()` is

$$f(y|\mu, \sigma, \nu) = \frac{1}{\sqrt{2\pi}\sigma\mu^{\nu/2}} \exp\left[-\frac{1}{2} \frac{(y - \mu)^2}{\sigma^2\mu^\nu}\right]$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, \infty)$, $\sigma > 0$ and $\nu = (-\infty, +\infty)$.

Value

returns a `gamlss.family` object which can be used to fit a normal distribution family in the `gamlss()` function.

Note

For the function `NOF()`, μ is the mean and $\sigma\mu^{\nu/2}$ is the standard deviation of the normal distribution family. The NOF is design for fitting regression type models where the variance is proportional to a power of the mean. Models of this type are related to the "pseudo likelihood" models of Carroll and Rubert (1987) but here a proper likelihood is maximised.

Note that because the high correlation between the `sigma` and the `nu` parameter the `mixed()` method should be used in the fitting.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Calliope Akantziliotou

References

- Davidian, M. and Carroll, R. J. (1987), Variance Function Estimation, *Journal of the American Statistical Association*, Vol. **82**, pp. 1079-1091
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NO](#), [NO2](#)

Examples

```
NOF()# gives information about the default links for the normal distribution family
# library(gamlss)
#data(abdom)
## the normal distribution fit with constant sigma
#m1<-gamlss(y~poly(x,2), sigma.fo=~1, family=NO, data=abdom)
## the normal family fit with variance proportional to mu
#m2<-gamlss(y~poly(x,2), sigma.fo=~1, family=NOF, data=abdom, method=mixed(1,20))
## a normal distribution fit with variance as a function of x
#m3 <-gamlss(y~poly(x,2), sigma.fo=~x, family=NO, data=abdom, method=mixed(1,20))
#GAIC(m1,m2,m3)
```

PARETO2

Pareto Type 2 distribution for fitting a GAMLSS

Description

The functions `PARETO2()` and `PARETO2o()` define the Pareto Type 2 distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The parameters are `mu` and `sigma` in both functions but the parameterisation different. The `mu` is identical for both `PARETO2()` and `PARETO2o()`. The `sigma` in `PARETO2o()` is the inverse of the `sigma` in `codePARETO2()` and corresponds to the usual parameter `alpha` of the Pareto distribution. The functions `dPARETO2`, `pPARETO2`, `qPARETO2` and `rPARETO2` define the density, distribution function, quantile function and random generation for the `PARETO2` parameterization of the Pareto type 2 distribution while the functions `dPARETO2o`, `pPARETO2o`, `qPARETO2o` and `rPARETO2o` define the density, distribution function, quantile function and random generation for the original `PARETO2o` parameterization of the Pareto type 2 distribution

Usage

```

PARETO2(mu.link = "log", sigma.link = "log")
dPARETO2(x, mu = 1, sigma = 0.5, log = FALSE)
pPARETO2(q, mu = 1, sigma = 0.5, lower.tail = TRUE, log.p = FALSE)
qPARETO2(p, mu = 1, sigma = 0.5, lower.tail = TRUE, log.p = FALSE)
rPARETO2(n, mu = 1, sigma = 0.5)
PARETO2o(mu.link = "log", sigma.link = "log")
dPARETO2o(x, mu = 1, sigma = 0.5, log = FALSE)
pPARETO2o(q, mu = 1, sigma = 0.5, lower.tail = TRUE, log.p = FALSE)
qPARETO2o(p, mu = 1, sigma = 0.5, lower.tail = TRUE, log.p = FALSE)
rPARETO2o(n, mu = 1, sigma = 0.5)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" as the default for the <code>sigma</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parameterization of the Pareto Type 2 distribution in the function PA2 is:

$$f(y|\mu, \sigma) = \frac{1}{\sigma} \mu^{\frac{1}{\sigma}} (y + \mu)^{-\frac{1}{\sigma} - 1}$$

for $y \geq 0$, $\mu > 0$ and $\sigma > 0$.

Value

returns a `gamlss.family` object which can be used to fit a Pareto type 2 distribution in the `gamlss()` function.

Author(s)

Fiona McElduff, Bob Rigby and Mikis Stasinopoulos

References

- Johnson, N., Kotz, S., and Balakrishnan, N. (1997). *Discrete Multivariate Distributions*. Wiley-Interscience, NY, USA.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(0.2,20,0.2)
plot(y, dPARETO2(y), type="l" , lwd=2)
q<-seq(0,20,0.2)
plot(q, pPARETO2(q), ylim=c(0,1), type="l", lwd=2)
p<-seq(0.0001,0.999,0.05)
plot(p, qPARETO2(p), type="l", lwd=2)
dat <- rPARETO2(100)
hist(rPARETO2(100), nclass=30)
#summary(gamlss(a~1, family="PARETO2"))
```

Description

The functions define the Power Exponential distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dPE`, `pPE`, `qPE` and `rPE` define the density, distribution function, quantile function and random generation for the specific parameterization of the power exponential distribution showing below. The functions `dPE2`, `pPE2`, `qPE2` and `rPE2` define the density, distribution function, quantile function and random generation of a standard parameterization of the power exponential distribution.

Usage

```
PE(mu.link = "identity", sigma.link = "log", nu.link = "log")
dPE(x, mu = 0, sigma = 1, nu = 2, log = FALSE)
pPE(q, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
qPE(p, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
```

```

rPE(n, mu = 0, sigma = 1, nu = 2)
PE2(mu.link = "identity", sigma.link = "log", nu.link = "log")
dPE2(x, mu = 0, sigma = 1, nu = 2, log = FALSE)
pPE2(q, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
qPE2(p, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
rPE2(n, mu = 0, sigma = 1, nu = 2)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of kurtosis parameter
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

Power Exponential distribution (PE) is defined as

$$f(y|\mu, \sigma, \nu) = \frac{\nu \exp[-(\frac{1}{2})|\frac{y}{c}|^\nu]}{\sigma c 2^{(1+1/\nu)} \Gamma(\frac{1}{\nu})}$$

where $c = [2^{-2/\nu} \Gamma(1/\nu) / \Gamma(3/\nu)]^{0.5}$, for $y = (-\infty, +\infty)$, $\mu = (-\infty, +\infty)$, $\sigma > 0$ and $\nu > 0$. This parametrization was used by Nelson (1991) and ensures μ is the mean and σ is the standard deviation of y (for all parameter values of μ , σ and ν within the ranges above)

The Power Exponential distribution (PE2) is defined as

$$f(y|\mu, \sigma, \nu) = \frac{\nu \exp[-|z|^\nu]}{2\sigma \Gamma(\frac{1}{\nu})}$$

Value

returns a `gamlss.family` object which can be used to fit a Power Exponential distribution in the `gamlss()` function.

Note

μ is the mean and σ is the standard deviation of the Power Exponential distribution

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Nelson, D.B. (1991) Conditional heteroskedasticity in asset returns: a new approach. *Econometrica*, **57**, 347-370.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [BCPE](#)

Examples

```
PE()# gives information about the default links for the Power Exponential distribution
# library(gamlss)
# data(abdom)
# h1<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=PE, data=abdom) # fit
# h2<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=PE2, data=abdom) # fit
# plot(h1)
# plot(h2)
# leptokurtotic
plot(function(x) dPE(x, mu=10,sigma=2,nu=1), 0.0, 20,
      main = "The PE density mu=10,sigma=2,nu=1")
# platykurtotic
plot(function(x) dPE(x, mu=10,sigma=2,nu=4), 0.0, 20,
      main = "The PE density mu=10,sigma=2,nu=4")
```

Description

The PIG() function defines the Poisson-inverse Gaussian distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dPIG`, `pPIG`, `qPIG` and `rPIG` define the density, distribution function, quantile function and random generation for the Poisson-inverse Gaussian PIG(), distribution.

Usage

```

PIG(mu.link = "log", sigma.link = "log")
dPIG(x, mu = 0.5, sigma = 0.02, log = FALSE)
pPIG(q, mu = 0.5, sigma = 0.02, lower.tail = TRUE, log.p = FALSE)
qPIG(p, mu = 0.5, sigma = 0.02, lower.tail = TRUE, log.p = FALSE,
     max.value = 10000)
rPIG(n, mu = 0.5, sigma = 0.02)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>max.value</code>	a constant, set to the default value of 10000 for how far the algorithm should look for q

Details

The probability function of the Poisson-inverse Gaussian distribution, is given by

$$f(y|\mu, \sigma) = \left(\frac{2\alpha^{1/2}}{\pi} \right) \frac{\mu^y e^{\frac{1}{\sigma}} K_{y-\frac{1}{2}}(\alpha)}{(\alpha\sigma)^y y!}$$

where $\alpha^2 = \frac{1}{\sigma^2} + \frac{2\mu}{\sigma}$, for $y = 0, 1, 2, \dots, \infty$ where $\mu > 0$ and $\sigma > 0$ and $K_\lambda(t) = \frac{1}{2} \int_0^\infty x^{\lambda-1} \exp\{-\frac{1}{2}t(x+x^{-1})\} dx$ is the modified Bessel function of the third kind. [Note that the above parameterization was used by Dean, Lawless and Willmot(1989). It is also a special case of the Sichel distribution SI() when $\nu = -\frac{1}{2}$.]

Value

Returns a `gamlss.family` object which can be used to fit a Poisson-inverse Gaussian distribution in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Marco Enea

References

- Dean, C., Lawless, J. F. and Willmot, G. E., A mixed poisson-inverse-Gaussian regression model, *Canadian J. Statist.*, **17**, 2, pp 171-181
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NBI](#), [NBII](#), [SI](#), [SICHEL](#)

Examples

```
PIG()# gives information about the default links for the Poisson-inverse Gaussian distribution
#plot the pdf using plot
plot(function(y) dPIG(y, mu=10, sigma = 1 ), from=0, to=50, n=50+1, type="h") # pdf
# plot the cdf
plot(seq(from=0,to=50),pPIG(seq(from=0,to=50), mu=10, sigma=1), type="h") # cdf
# generate random sample
tN <- table(Ni <- rPIG(100, mu=5, sigma=1))
r <- barplot(tN, col='lightblue')
# fit a model to the data
# library(gamlss)
# gamlss(Ni~1,family=PIG)
```

PO

Poisson distribution for fitting a GAMLSS model

Description

This function PO defines the Poisson distribution, an one parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dPO`, `pPO`, `qPO` and `rPO` define the density, distribution function, quantile function and random generation for the Poisson, `PO()`, distribution.

Usage

```
PO(mu.link = "log")
dPO(x, mu = 1, log = FALSE)
pPO(q, mu = 1, lower.tail = TRUE, log.p = FALSE)
qPO(p, mu = 1, lower.tail = TRUE, log.p = FALSE)
rPO(n, mu = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Definition file for Poisson distribution.

$$f(y|\mu) = \frac{e^{-\mu} \mu^y}{\Gamma(y+1)}$$

for $y = 0, 1, 2, \dots$ and $\mu > 0$.

Value

returns a `gamlss.family` object which can be used to fit a Poisson distribution in the `gamlss()` function.

Note

μ is the mean of the Poisson distribution

Author(s)

Bob Rigby, Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, and Kalliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [NBI](#), [NBII](#), [SI](#), [SICHEL](#)

Examples

```

PO()# gives information about the default links for the Poisson distribution
# fitting data using PO()

# plotting the distribution
plot(function(y) dPO(y, mu=10 ), from=0, to=20, n=20+1, type="h")
# creating random variables and plot them
tN <- table(Ni <- rPO(1000, mu=5))
r <- barplot(tN, col='lightblue')
# library(gamlss)
# data(aids)
# h<-gamlss(y~cs(x,df=7)+qrt, family=PO, data=aids) # fits the constant+x+qrt model
# plot(h)
# pdf.plot(family=PO, mu=10, min=0, max=20, step=1)

```

RG

*The Reverse Gumbel distribution for fitting a GAMLSS***Description**

The function RG defines the reverse Gumbel distribution, a two parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dRG`, `pRG`, `qRG` and `rRG` define the density, distribution function, quantile function and random generation for the specific parameterization of the reverse Gumbel distribution.

Usage

```

RG(mu.link = "identity", sigma.link = "log")
dRG(x, mu = 0, sigma = 1, log = FALSE)
pRG(q, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qRG(p, mu = 0, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rRG(n, mu = 0, sigma = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. other available link is "inverse", "log" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other links are the "inverse", "identity" and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The specific parameterization of the reverse Gumbel distribution used in RG is

$$f(y|\mu, \sigma) = \frac{1}{\sigma} \exp \left\{ - \left(\frac{y - \mu}{\sigma} \right) - \exp \left[- \frac{(y - \mu)}{\sigma} \right] \right\}$$

for $y = (-\infty, \infty)$, $\mu = (-\infty, +\infty)$ and $\sigma > 0$.

Value

RG() returns a `gamlss.family` object which can be used to fit a Gumbel distribution in the `gamlss()` function. `dRG()` gives the density, `pGU()` gives the distribution function, `qRG()` gives the quantile function, and `rRG()` generates random deviates.

Note

The mean of the distribution is $\mu + 0.57722\sigma$ and the variance is $\pi^2\sigma^2/6$.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantziliotou

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
plot(function(x) dRG(x, mu=0, sigma=1), -3, 6,
     main = "{Reverse Gumbel density mu=0, sigma=1}")
RG()# gives information about the default links for the Gumbel distribution
dat<-rRG(100, mu=10, sigma=2) # generates 100 random observations
# library(gamlss)
# gamlss(dat~1, family=RG) # fits a constant for each parameter mu and sigma
```

RGE

*Reverse generalized extreme family distribution for fitting a GAMLSS***Description**

The function RGE defines the reverse generalized extreme family distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dRGE`, `pRGE`, `qRGE` and `rRGE` define the density, distribution function, quantile function and random generation for the specific parameterization of the reverse generalized extreme distribution given in details below.

Usage

```
RGE(mu.link = "identity", sigma.link = "log", nu.link = "log")
dRGE(x, mu = 1, sigma = 0.1, nu = 1, log = FALSE)
pRGE(q, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
qRGE(p, mu = 1, sigma = 0.1, nu = 1, lower.tail = TRUE, log.p = FALSE)
rRGE(n, mu = 1, sigma = 0.1, nu = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of the shape parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

Definition file for reverse generalized extreme family distribution.

The probability density function of the generalized extreme value distribution is obtained from Johnson *et al.* (1995), Volume 2, p76, equation (22.184) [where $(\xi, \theta, \gamma) \rightarrow (\mu, \sigma, \nu)$].

The probability density function of the reverse generalized extreme value distribution is then obtained by replacing `y` by `-y` and `μ` by `$-\mu$` .

Hence the probability density function of the reverse generalized extreme value distribution with $\nu > 0$ is given by

$$f(y|\mu, \sigma, \nu) = \frac{1}{\sigma} \left[1 + \frac{\nu(y - \mu)}{\sigma} \right]^{\frac{1}{\nu} - 1} S_1(y|\mu, \sigma, \nu)$$

for

$$\mu - \frac{\sigma}{\nu} < y < \infty$$

where

$$S_1(y|\mu, \sigma, \nu) = \exp \left\{ - \left[1 + \frac{\nu(y - \mu)}{\sigma} \right]^{\frac{1}{\nu}} \right\}$$

and where $-\infty < \mu < y + \frac{\sigma}{\nu}$, $\sigma > 0$ and $\nu > 0$. Note that only the case $\nu > 0$ is allowed here. The reverse generalized extreme value distribution is denoted as $RGE(\mu, \sigma, \nu)$ or as `ReverseGeneralizedExtremeFamily`(μ, σ, ν).

Note that the above distribution is a reparameterization of the three parameter Weibull distribution given by

$$f(y|\alpha_1, \alpha_2, \alpha_3) = \frac{\alpha_3}{\alpha_2} \left[\frac{y - \alpha_1}{\alpha_2} \right]^{\alpha_3 - 1} \exp \left[- \left(\frac{y - \alpha_1}{\alpha_2} \right)^{\alpha_3} \right]$$

given by setting $\alpha_1 = \mu - \sigma/\nu$, $\alpha_2 = \sigma/\nu$, $\alpha_3 = 1/\nu$.

Value

`RGE()` returns a `gamlss.family` object which can be used to fit a reverse generalized extreme distribution in the `gamlss()` function. `drGE()` gives the density, `prGE()` gives the distribution function, `qrGE()` gives the quantile function, and `rRGE()` generates random deviates.

Note

This distribution is very difficult to fit because the y values depends on the parameter values. The `RS()` and `CG()` algorithms are not appropriate for this type of problem.

Author(s)

Bob Rigby, Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org> and Kalliope Akantziliotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
RGE()# default links for the reverse generalized extreme family distribution
newdata<-rRGE(100,mu=0,sigma=1,nu=5) # generates 100 random observations
# library(gamlss)
# gamlss(newdata~1, family=RGE, method=mixed(5,50)) # difficult to converse
```

 SEP

The Skew Power exponential (SEP) distribution for fitting a GAMLSS

Description

This function defines the Skew Power exponential (SEP) distribution, a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dSEP`, `pSEP`, `qSEP` and `rSEP` define the density, distribution function, quantile function and random generation for the Skew Power exponential (SEP) distribution.

Usage

```
SEP(mu.link = "identity", sigma.link = "log", nu.link = "identity",
    tau.link = "log")
dSEP(x, mu = 0, sigma = 1, nu = 0, tau = 2, log = FALSE)
pSEP(q, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
     log.p = FALSE)
qSEP(p, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
     log.p = FALSE, lower.limit = mu - 5 * sigma,
     upper.limit = mu + 5 * sigma)
rSEP(n, mu = 0, sigma = 1, nu = 0, tau = 2)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. Other links are "1/mu ² " and "log"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse" and "identity"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter. Other links are "1/nu ² " and "log"
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter. Other links are "1/tau ² ", and "identity"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values

<code>nu</code>	vector of skewness <code>nu</code> parameter values
<code>tau</code>	vector of kurtosis <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
<code>lower.limit</code>	lower limit for the golden search to find quantiles from probabilities
<code>upper.limit</code>	upper limit for the golden search to find quantiles from probabilities

Details

The probability density function of the Skew Power exponential distribution, (SEP), is defined as

$$f(y|n, \mu, \sigma, \nu, \tau) = \frac{z}{\sigma} \Phi(\omega) f_{EP}(z, 0, 1, \tau)$$

for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$. where $z = \frac{y-\mu}{\sigma}$, $\omega = \text{sign}(z)|z|^{\tau/2}\nu\sqrt{2/\tau}$ and $f_{EP}(z, 0, 1, \tau)$ is the pdf of an Exponential Power distribution.

Value

`SEP()` returns a `gamlss.family` object which can be used to fit the SEP distribution in the `gamlss()` function. `dSEP()` gives the density, `pSEP()` gives the distribution function, `qSEP()` gives the quantile function, and `rSEP()` generates random deviates.

Warning

The `qSEP` and `rSEP` are slow since they are relying on golden section for finding the quantiles

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

- Diciccio, T. J. and Monti A. C. (2004). Inferential Aspects of the Skew Exponential Power distribution., *JASA*, **99**, 439-450.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```
SEP() #
plot(function(x)dSEP(x, mu=0,sigma=1, nu=1, tau=2), -5, 5,
      main = "The SEP density mu=0,sigma=1,nu=1, tau=2")
plot(function(x) pSEP(x, mu=0,sigma=1,nu=1, tau=2), -5, 5,
      main = "The BCPE cdf mu=0, sigma=1, nu=1, tau=2")
dat <- rSEP(100,mu=10,sigma=1,nu=-1,tau=1.5)
# library(gamlss)
# gamlss(dat~1,family=SEP, control=gamlss.control(n.cyc=30))
```

SEP1	<i>The Skew Power exponential type 1-4 distribution for fitting a GAMLSS</i>
------	--

Description

These functions define the Skew Power exponential type 1 to 4 distributions. All of them are four parameter distributions and can be used to fit a GAMLSS model. The functions dSEP1, dSEP2, dSEP3 and dSEP4 define the probability distribution functions, the functions pSEP1, pSEP2, pSEP3 and pSEP4 define the cumulative distribution functions the functions qSEP1, qSEP2, qSEP3 and qSEP4 define the inverse cumulative distribution functions and the functions rSEP1, rSEP2, rSEP3 and rSEP4 define the random generation for the Skew exponential power distributions.

Usage

```
SEP1(mu.link = "identity", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
dSEP1(x, mu = 0, sigma = 1, nu = 0, tau = 2, log = FALSE)
pSEP1(q, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
qSEP1(p, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
rSEP1(n, mu = 0, sigma = 1, nu = 0, tau = 2)

SEP2(mu.link = "identity", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
dSEP2(x, mu = 0, sigma = 1, nu = 0, tau = 2, log = FALSE)
pSEP2(q, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
qSEP2(p, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
rSEP2(n, mu = 0, sigma = 1, nu = 0, tau = 2)
```

```

SEP3(mu.link = "identity", sigma.link = "log", nu.link = "log",
      tau.link = "log")
dSEP3(x, mu = 0, sigma = 1, nu = 2, tau = 2, log = FALSE)
pSEP3(q, mu = 0, sigma = 1, nu = 2, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
qSEP3(p, mu = 0, sigma = 1, nu = 2, tau = 2, lower.tail = TRUE,
      log.p = FALSE)

SEP4(mu.link = "identity", sigma.link = "log", nu.link = "log",
      tau.link = "log")
dSEP4(x, mu = 0, sigma = 1, nu = 2, tau = 2, log = FALSE)
pSEP4(q, mu = 0, sigma = 1, nu = 2, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
qSEP4(p, mu = 0, sigma = 1, nu = 2, tau = 2, lower.tail = TRUE,
      log.p = FALSE)
rSEP4(n, mu = 0, sigma = 1, nu = 2, tau = 2)

```

Arguments

mu.link	Defines the mu.link, with "identity" link as the default for the mu parameter. Other links are "inverse" and "log"
sigma.link	Defines the sigma.link, with "log" link as the default for the sigma parameter. Other links are "inverse" and "identity"
nu.link	Defines the nu.link, with "log" link as the default for the nu parameter. Other links are "identity" and "inverse"
tau.link	Defines the tau.link, with "log" link as the default for the tau parameter. Other links are "inverse", and "identity"
x,q	vector of quantiles
mu	vector of location parameter values
sigma	vector of scale parameter values
nu	vector of skewness nu parameter values
tau	vector of kurtosis tau parameter values
log, log.p	logical; if TRUE, probabilities p are given as log(p).
lower.tail	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required

Details

The probability density function of the Skew Power exponential distribution type 2, (SEP2), is defined as

$$f_Y(y|\mu, \sigma, \nu, \tau) = \frac{\nu}{\sigma(1+\nu^2)2^{1/\tau}\Gamma(1+1/\tau)} \left\{ \exp\left(-\frac{1}{2}\left|\frac{\nu(y-\mu)}{\sigma}\right|^\tau\right) I(y < \mu) + \exp\left(-\frac{1}{2}\left|\frac{(y-\mu)}{\sigma\nu}\right|^\tau\right) I(y \geq \mu) \right\}$$

for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu > 0$ and $\tau > 0$.

Value

SEP2() returns a `gamlss.family` object which can be used to fit the SEP2 distribution in the `gamlss()` function. `dSEP2()` gives the density, `pSEP2()` gives the distribution function, `qSEP2()` gives the quantile function, and `rSEP2()` generates random deviates.

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

Fernandez C., Osiewalski J. and Steel M.F.J.(1995) Modelling and inference with v-spherical distributions. *JASA*, **90**, pp 1331-1340.

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [SEP](#)

Examples

```
SEP1()
curve(dSEP4(x, mu=5 ,sigma=1, nu=2, tau=1.5), -2, 10,
      main = "The SEP4 density mu=5 ,sigma=1, nu=1, tau=1.5")
# library(gamlss)
#y<- rSEP4(100, mu=5, sigma=1, nu=2, tau=1.5);hist(y)
#m1<-gamlss(y~1, family=SEP1, n.cyc=50)
#m2<-gamlss(y~1, family=SEP2, n.cyc=50)
#m3<-gamlss(y~1, family=SEP3, n.cyc=50)
#m4<-gamlss(y~1, family=SEP4, n.cyc=50)
#GAIC(m1,m2,m3,m4)
```

Description

The Sinh-Arcsinh (SHASH) distribution is a four parameter distribution, for a `gamlss.family` object to be used for a GAMLSS fitting using the function `gamlss()`. The functions `dSHASH`, `pSHASH`, `qSHASH` and `rSHASH` define the density, distribution function, quantile function and random generation for the Sinh-Arcsinh (SHASH) distribution.

There are 3 different SHASH distributions implemented in GAMLSS.

Usage

```
SHASH(mu.link = "identity", sigma.link = "log", nu.link = "log",
      tau.link = "log")
dSHASH(x, mu = 0, sigma = 1, nu = 0.5, tau = 0.5, log = FALSE)
pSHASH(q, mu = 0, sigma = 1, nu = 0.5, tau = 0.5, lower.tail = TRUE,
      log.p = FALSE)
qSHASH(p, mu = 0, sigma = 1, nu = 0.5, tau = 0.5, lower.tail = TRUE,
      log.p = FALSE)
rSHASH(n, mu = 0, sigma = 1, nu = 0.5, tau = 0.5)

SHASHo(mu.link = "identity", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
dSHASHo(x, mu = 0, sigma = 1, nu = 0, tau = 1, log = FALSE)
pSHASHo(q, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE,
      log.p = FALSE)
qSHASHo(p, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE,
      log.p = FALSE)
rSHASHo(n, mu = 0, sigma = 1, nu = 0, tau = 1)

SHASHo2(mu.link = "identity", sigma.link = "log", nu.link = "identity",
      tau.link = "log")
dSHASHo2(x, mu = 0, sigma = 1, nu = 0, tau = 1, log = FALSE)
pSHASHo2(q, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE,
      log.p = FALSE)
qSHASHo2(p, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE,
      log.p = FALSE)
rSHASHo2(n, mu = 0, sigma = 1, nu = 0, tau = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter.
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter.
<code>tau.link</code>	Defines the <code>tau.link</code> , with "log" link as the default for the <code>tau</code> parameter.
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of skewness <code>nu</code> parameter values

tau	vector of kurtosis tau parameter values
log, log.p	logical; if TRUE, probabilities p are given as log(p).
lower.tail	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
p	vector of probabilities.
n	number of observations. If length(n) > 1, the length is taken to be the number required

Details

The probability density function of the Sinh-Arcsinh distribution, (SHASH), Jones(2005), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = \frac{c}{\sqrt{2\pi}\sigma(1+z^2)^{1/2}} e^{-r^2/2}$$

where

$$r = \frac{1}{2} \{ \exp [\tau \sinh^{-1}(z)] - \exp [-\nu \sinh^{-1}(z)] \}$$

and

$$c = \frac{1}{2} \{ \tau \exp [\tau \sinh^{-1}(z)] + \nu \exp [-\nu \sinh^{-1}(z)] \}$$

and $z = (y - \mu)/\sigma$ for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu > 0$ and $\tau > 0$.

The parameters μ and σ are the location and scale of the distribution. The parameter ν determines the left hand tail of the distribution with $\nu > 1$ indicating a lighter tail than the normal and $\nu < 1$ heavier tail than the normal. The parameter τ determines the right hand tail of the distribution in the same way.

The second form of the Sinh-Arcsinh distribution can be found in Jones and Pewsey (2009, p.2) denoted by SHASHo and the probability density function is defined as,

$$f(y|\mu, \sigma, \nu, \tau) = \frac{\tau}{\sigma} \frac{c}{\sqrt{2\pi}} \frac{1}{2\sqrt{1+z^2}} \exp\left(-\frac{r^2}{2}\right)$$

where

$$r = \sinh(\tau \arcsin(z) - \nu)$$

and

$$c = \cosh(\tau \arcsin(z) - \nu)$$

and $z = (y - \mu)/\sigma$ for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$.

The third form of the Sinh-Arcsinh distribution (Jones and Pewsey, 2009, p.8) divides the distribution by sigma for the density of the unstandardized variable. This distribution is denoted by SHASHo2 and has pdf

$$f(y|\mu, \sigma, \nu, \tau) = \frac{c}{\sigma} \frac{\tau}{\sqrt{2\pi}} \frac{1}{\sqrt{1+z^2}} - \exp -\frac{r^2}{2}$$

where $z = (y - \mu)/(\sigma\tau)$, with r and c as for the pdf of the SHASHo distribution, for $-\infty < y < \infty$, $\mu = (-\infty, +\infty)$, $\sigma > 0$, $\nu = (-\infty, +\infty)$ and $\tau > 0$.

Value

SHASH() returns a `gamlss.family` object which can be used to fit the SHASH distribution in the `gamlss()` function. `dSHASH()` gives the density, `pSHASH()` gives the distribution function, `qSHASH()` gives the quantile function, and `rSHASH()` generates random deviates.

Warning

The `qSHASH` and `rSHASH` are slow since they are relying on golden section for finding the quantiles

Author(s)

Bob Rigby, Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org> and Fiona McElduff

References

- Jones, M. C. (2006) p 546-547 in the discussion of Rigby, R. A. and Stasinopoulos D. M. (2005) *Appl. Statist.*, **54**, part 3.
- Jones and Pewsey (2009) Sinh-arcsinh distributions. *Biometrika*. **96**(4), pp. 761-780.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [JSU](#), [BCT](#)

Examples

```
SHASH() #
plot(function(x)dSHASH(x, mu=0,sigma=1, nu=1, tau=2), -5, 5,
      main = "The SHASH density mu=0,sigma=1,nu=1, tau=2")
plot(function(x) pSHASH(x, mu=0,sigma=1,nu=1, tau=2), -5, 5,
      main = "The BCPE cdf mu=0, sigma=1, nu=1, tau=2")
dat<-rSHASH(100,mu=10,sigma=1,nu=1,tau=1.5)
```

```

hist(dat)
# library(gamlss)
# gamlss(dat~1,family=SHASH, control=gamlss.control(n.cyc=30))

```

Description

The SI() function defines the Sichel distribution, a three parameter discrete distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dSI`, `pSI`, `qSI` and `rSI` define the density, distribution function, quantile function and random generation for the Sichel SI(), distribution.

Usage

```

SI(mu.link = "log", sigma.link = "log", nu.link = "identity")
dSI(x, mu = 0.5, sigma = 0.02, nu = -0.5, log = FALSE)
pSI(q, mu = 0.5, sigma = 0.02, nu = -0.5, lower.tail = TRUE,
    log.p = FALSE)
qSI(p, mu = 0.5, sigma = 0.02, nu = -0.5, lower.tail = TRUE,
    log.p = FALSE, max.value = 10000)
rSI(n, mu = 0.5, sigma = 0.02, nu = -0.5)
tofyS(y, mu, sigma, nu, what = 1)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the nu parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive mu
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of nu
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>max.value</code>	a constant, set to the default value of 10000 for how far the algorithm should look for q
<code>y</code>	the y variable. The function <code>tofyS()</code> should be not used on its own.
<code>what</code>	take values 1 or 2, for function <code>tofyS()</code> .

Details

The probability function of the Sichel distribution is given by

$$f(y|\mu, \sigma, \nu) = \frac{\mu^y K_{y+\nu}(\alpha)}{(\alpha\sigma)^{y+\nu} y! K_\nu(\frac{1}{\sigma})}$$

where $\alpha^2 = \frac{1}{\sigma^2} + \frac{2\mu}{\sigma}$, for $y = 0, 1, 2, \dots, \infty$ where $\mu > 0$, $\sigma > 0$ and $-\infty < \nu < \infty$ and $K_\lambda(t) = \frac{1}{2} \int_0^\infty x^{\lambda-1} \exp\{-\frac{1}{2}t(x + x^{-1})\} dx$ is the modified Bessel function of the third kind. Note that the above parameterization is different from Stein, Zucchini and Juritz (1988) who use the above probability function but treat μ , α and ν as the parameters. Note that $\sigma = [(\mu^2 + \alpha^2)^{\frac{1}{2}} - \mu]^{-1}$.

Value

Returns a `gamlss.family` object which can be used to fit a Sichel distribution in the `gamlss()` function.

Author(s)

Akantziliotou C., Rigby, R. A., Stasinopoulos D. M. and Marco Enea

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2003) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Stein, G. Z., Zucchini, W. and Juritz, J. M. (1987). Parameter Estimation of the Sichel Distribution and its Multivariate Extension. *Journal of American Statistical Association*, **82**, 938-944.

See Also

[gamlss.family](#), [PIG](#), [NBI](#), [NBII](#)

Examples

```
SI()# gives information about the default links for the Sichel distribution
#plot the pdf using plot
plot(function(y) dSI(y, mu=10, sigma=1, nu=1), from=0, to=100, n=100+1, type="h") # pdf
# plot the cdf
plot(seq(from=0,to=100),pSI(seq(from=0,to=100), mu=10, sigma=1, nu=1), type="h") # cdf
# generate random sample
tN <- table(Ni <- rSI(100, mu=5, sigma=1, nu=1))
r <- barplot(tN, col='lightblue')
# fit a model to the data
# library(gamlss)
# gamlss(Ni~1,family=SI, control=gamlss.control(n.cyc=50))
```

Description

The `SICHEL()` function defines the Sichel distribution, a three parameter discrete distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dSICHEL`, `pSICHEL`, `qSICHEL` and `rSICHEL` define the density, distribution function, quantile function and random generation for the Sichel `SICHEL()`, distribution. The function `VSICHEL` gives the variance of a fitted Sichel model.

Usage

```
SICHEL(mu.link = "log", sigma.link = "log", nu.link = "identity")
dSICHEL(x, mu=1, sigma=1, nu=-0.5, log=FALSE)
pSICHEL(q, mu=1, sigma=1, nu=-0.5, lower.tail = TRUE,
        log.p = FALSE)
qSICHEL(p, mu=1, sigma=1, nu=-0.5, lower.tail = TRUE,
        log.p = FALSE, max.value = 10000)
rSICHEL(n, mu=1, sigma=1, nu=-0.5, max.value = 10000)
VSICHEL(obj)
tofySICHEL(y, mu, sigma, nu)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the nu parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive mu
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of nu
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log</code> , <code>log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>max.value</code>	a constant, set to the default value of 10000 for how far the algorithm should look for q
<code>obj</code>	a fitted Sichel <code>gamlss</code> model
<code>y</code>	the y variable, the <code>tofySICHEL()</code> should not be used on its own.

Details

The probability function of the Sichel distribution is given by

$$f(y|\mu, \sigma, \nu) = \frac{\mu^y K_{y+\nu}(\alpha)}{c^y (\alpha\sigma)^{y+\nu} y! K_\nu(\frac{1}{\sigma})}$$

where $\alpha^2 = \frac{1}{\sigma^2} + \frac{2\mu}{c\sigma}$, and $c = R_\nu(1/\sigma) = K_{\nu+1}(1/\sigma) [K_\nu(1/\sigma)]^{-1}$ for $y = 0, 1, 2, \dots, \infty$ where $\mu > 0$, $\sigma > 0$ and $-\infty < \nu < \infty$ and $K_\lambda(t) = \frac{1}{2} \int_0^\infty x^{\lambda-1} \exp\{-\frac{1}{2}t(x + x^{-1})\} dx$ is the modified Bessel function of the third kind. Note that the above parameterization is different from Stein, Zucchini and Juritz (1988) who use the above probability function but treat μ , α and ν as the parameters.

Value

Returns a `gamlss.family` object which can be used to fit a Sichel distribution in the `gamlss()` function.

Note

The mean of the above Sichel distribution is μ and the variance is $\mu^2 \left[\frac{2\sigma(\nu+1)}{c} + \frac{1}{c^2} - 1 \right]$

Author(s)

Rigby, R. A., Stasinopoulos D. M., Akantziliotou C and Marco Enea.

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Rigby, R. A., Stasinopoulos D. M. and Akantziliotou, C. (2006) Modelling the parameters of a family of mixed Poisson distributions including the Sichel and Delaportte. Submitted for publication.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2003) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stein, G. Z., Zucchini, W. and Juritz, J. M. (1987). Parameter Estimation of the Sichel Distribution and its Multivariate Extension. *Journal of American Statistical Association*, **82**, 938-944.
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [PIG](#), [SI](#)

Examples

```

SICHEL()# gives information about the default links for the Sichel distribution
#plot the pdf using plot
plot(function(y) dSICHEL(y, mu=10, sigma=1, nu=1), from=0, to=100, n=100+1, type="h") # pdf
# plot the cdf
plot(seq(from=0,to=100),pSICHEL(seq(from=0,to=100), mu=10, sigma=1, nu=1), type="h") # cdf
# generate random sample
tN <- table(Ni <- rSICHEL(100, mu=5, sigma=1, nu=1))
r <- barplot(tN, col='lightblue')
# fit a model to the data
# library(gamlss)
# gamlss(Ni~1,family=SICHEL, control=gamlss.control(n.cyc=50))

```

SN1

*Skew Normal Type 1 distribution for fitting a GAMLSS***Description**

The function `SN1()` defines the Skew Normal Type 1 distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with parameters `mu`, `sigma` and `nu`. The functions `dSN1`, `pSN1`, `qSN1` and `rSN1` define the density, distribution function, quantile function and random generation for the SN1 parameterization of the Skew Normal Type 1 distribution.

Usage

```

SN1(mu.link = "identity", sigma.link = "log", nu.link="identity")
dSN1(x, mu = 0, sigma = 1, nu = 0, log = FALSE)
pSN1(q, mu = 0, sigma = 1, nu = 0, lower.tail = TRUE, log.p = FALSE)
qSN1(p, mu = 0, sigma = 1, nu = 0, lower.tail = TRUE, log.p = FALSE)
rSN1(n, mu = 0, sigma = 1, nu = 0)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" links the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" as the default for the <code>nu</code> parameter
<code>x, q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of scale parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parameterization of the Skew Normal Type 1 distribution in the function SN1 is ...

Value

returns a `gamlss.family` object which can be used to fit a Skew Normal Type 1 distribution in the `gamlss()` function.

Note

This is a special case of the Skew Exponential Power type 1 distribution (SEP1) where $\tau=2$.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Fiona McElduff

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(-3,3,0.2)
plot(y, dSN1(y), type="l" , lwd=2)
q<-seq(-3,3,0.2)
plot(q, pSN1(q), ylim=c(0,1), type="l", lwd=2)
p<-seq(0.0001,0.999,0.05)
plot(p, qSN1(p), type="l", lwd=2)
dat <- rSN1(100)
hist(rSN1(100), nclass=30)
```

Description

The function `SN2()` defines the Skew Normal Type 2 distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with parameters `mu`, `sigma` and `nu`. The functions `dSN2`, `pSN2`, `qSN2` and `rSN2` define the density, distribution function, quantile function and random generation for the SN2 parameterization of the Skew Normal Type 2 distribution.

Usage

```
SN2(mu.link = "identity", sigma.link = "log", nu.link = "log")
dSN2(x, mu = 0, sigma = 1, nu = 2, log = FALSE)
pSN2(q, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
qSN2(p, mu = 0, sigma = 1, nu = 2, lower.tail = TRUE, log.p = FALSE)
rSN2(n, mu = 0, sigma = 1, nu = 2)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" links the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" as the default for the <code>sigma</code> parameter
<code>x</code> , <code>q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of scale parameter values
<code>log</code> , <code>log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise $P[X > x]$
<code>p</code>	vector of probabilities
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parameterization of the Skew Normal Type 2 distribution in the function `SN2` is ...

Value

returns a `gamlss.family` object which can be used to fit a Skew Normal Type 2 distribution in the `gamlss()` function.

Note

This is a special case of the Skew Exponential Power type 3 distribution (SEP3) where $\tau=2$.

Author(s)

Mikis Stasinopoulos, Bob Rigby and Fiona McElduff.

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(-3,3,0.2)
plot(y, dSN2(y), type="l" , lwd=2)
q<-seq(-3,3,0.2)
plot(q, pSN2(q), ylim=c(0,1), type="l", lwd=2)
p<-seq(0.0001,0.999,0.05)
plot(p, qSN2(p), type="l", lwd=2)
dat <- rSN2(100)
hist(rSN2(100), nclass=30)
```

 ST1

The skew t distributions, type 1 to 5

Description

There are 5 different skew t distributions implemented in GAMLSS.

The Skew t type 1 distribution, ST1, is based on Azzalini (1986).

The skew t type 2 distribution, ST2, is based on Azzalini and Capitanio (2003).

The skew t type 3 , ST3 and ST3C, distribution is based Fernande and Steel (1998). The difference between the ST3 and ST3C is that the first is written entirely in R while the second is in C.

The skew t type 4 distribution , ST4, is a spliced-shape distribution.

The skew t type 5 distribution, ST5, is Jones and Faddy (2003).

The SST is a reparametrised version of dST3 where sigma is the standard deviation of the distribution.

Usage

```
ST1(mu.link = "identity", sigma.link = "log", nu.link = "identity", tau.link="log")
dST1(x, mu = 0, sigma = 1, nu = 0, tau = 2, log = FALSE)
pST1(q, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE, log.p = FALSE)
qST1(p, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE, log.p = FALSE)
rST1(n, mu = 0, sigma = 1, nu = 0, tau = 2)
```

```
ST2(mu.link = "identity", sigma.link = "log", nu.link = "identity", tau.link = "log")
dST2(x, mu = 0, sigma = 1, nu = 0, tau = 2, log = FALSE)
pST2(q, mu = 0, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE, log.p = FALSE)
qST2(p, mu = 1, sigma = 1, nu = 0, tau = 2, lower.tail = TRUE, log.p = FALSE)
rST2(n, mu = 0, sigma = 1, nu = 0, tau = 2)
```

```
ST3(mu.link = "identity", sigma.link = "log", nu.link = "log", tau.link = "log")
dST3(x, mu = 0, sigma = 1, nu = 1, tau = 10, log = FALSE)
pST3(q, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
qST3(p, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
rST3(n, mu = 0, sigma = 1, nu = 1, tau = 10)
```

```
ST3C(mu.link = "identity", sigma.link = "log", nu.link = "log", tau.link = "log")
dST3C(x, mu = 0, sigma = 1, nu = 1, tau = 10, log = FALSE)
pST3C(q, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
qST3C(p, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
rST3C(n, mu = 0, sigma = 1, nu = 1, tau = 10)
```

```
SST(mu.link = "identity", sigma.link = "log", nu.link = "log",
     tau.link = "logshiftto2")
dSST(x, mu = 0, sigma = 1, nu = 0.8, tau = 7, log = FALSE)
pSST(q, mu = 0, sigma = 1, nu = 0.8, tau = 7, lower.tail = TRUE, log.p = FALSE)
qSST(p, mu = 0, sigma = 1, nu = 0.8, tau = 7, lower.tail = TRUE, log.p = FALSE)
rSST(n, mu = 0, sigma = 1, nu = 0.8, tau = 7)
```

```
ST4(mu.link = "identity", sigma.link = "log", nu.link = "log", tau.link = "log")
dST4(x, mu = 0, sigma = 1, nu = 1, tau = 10, log = FALSE)
pST4(q, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
qST4(p, mu = 0, sigma = 1, nu = 1, tau = 10, lower.tail = TRUE, log.p = FALSE)
rST4(n, mu = 0, sigma = 1, nu = 1, tau = 10)
```

```
ST5(mu.link = "identity", sigma.link = "log", nu.link = "identity", tau.link = "log")
dST5(x, mu = 0, sigma = 1, nu = 0, tau = 1, log = FALSE)
pST5(q, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE, log.p = FALSE)
qST5(p, mu = 0, sigma = 1, nu = 0, tau = 1, lower.tail = TRUE, log.p = FALSE)
rST5(n, mu = 0, sigma = 1, nu = 0, tau = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter. Other links are "1/mu ² " and "log"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter. Other links are "inverse" and "identity"
<code>nu.link</code>	Defines the <code>nu.link</code> , with "identity" link as the default for the <code>nu</code> parameter. Other links are "1/mu ² " and "log"
<code>tau.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter. Other links are "inverse", "identity"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of <code>mu</code> parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of <code>nu</code> parameter values
<code>tau</code>	vector of <code>tau</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are <code>P[X <= x]</code> , otherwise, <code>P[X > x]</code>
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required
<code>...</code>	for extra arguments

Details

$$f(y|\mu, \sigma, \nu, \frac{z}{\sigma} f_{z_1}(z) F_{z_2}(w)\tau) =$$

for $-\infty < y < \infty$, where $z = (y - \mu)/\sigma$, $w = \nu\lambda^{1/2}z$, $\lambda = (\tau + 1)/(\tau + z^2)$ and $z_1 \sim TF(0, 1, \tau)$ and $z_2 \sim TF(0, 1, \tau + 1)$.

The probability density function of the skew t distribution type q, (ST3), is defined in Chapter 10 of the GAMLSS manual.

The probability density function of the skew t distribution type q, (ST4), is defined in Chapter of the GAMLSS manual.

The probability density function of the skew t distribution type 5, (ST5), is defined as

$$f(y|\mu, \sigma, \nu, \tau) = \frac{1}{c} \left[1 + \frac{z}{(a+b+z^2)^{1/2}} \right]^{a+1/2} \left[1 - \frac{z}{(a+b+z^2)^{1/2}} \right]^{b+1/2}$$

where $c = 2^{a+b-1}(a+b)^{1/2}B(a,b)$, and $B(a,b) = \Gamma(a)\Gamma(b)/\Gamma(a+b)$ and $z = (y - \mu)/\sigma$ and $\nu = (a - b)/[ab(a+b)]^{1/2}$ and $\tau = 2/(a+b)$ for $-\infty < y < \infty$, $-\infty < \mu < \infty$, $\sigma > 0$, $-\infty < \nu < \infty$ and $\tau > 0$.

Value

ST1(), ST2(), ST3(), ST4() and ST5() return a `gamlss.family` object which can be used to fit the skew t type 1-5 distribution in the `gamlss()` function. `dST1()`, `dST2()`, `dST3()`, `dST4()` and `dST5()` give the density functions, `pST1()`, `pST2()`, `pST3()`, `pST4()` and `pST5()` give the cumulative distribution functions, `qST1()`, `qST2()`, `qST3()`, `qST4()` and `qST5()` give the quantile function, and `rST1()`, `rST2()`, `rST3()`, `rST4()` and `rST3()` generates random deviates.

Note

The mean of the ex-Gaussian is $\mu + \nu$ and the variance is $\sigma^2 + \nu^2$.

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Azzalini A. (1986) Further results on a class of distributions which includes the normal ones, *Statistica*, **46**, pp. 199-208.
- Azzalini A. and Capitanio, A. Distributions generated by perturbation of symmetry with emphasis on a multivariate skew t-distribution, *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, **65**, pp. 367-389.
- Jones, M.C. and Faddy, M. J. (2003) A skew extension of the t distribution, with applications. *Journal of the Royal Statistical Society, Series B*, **65**, pp 159-174.
- Fernandez, C. and Steel, M. F. (1998) On Bayesian modeling of fat tails and skewness. *Journal of the American Statistical Association*, **93**, pp. 359-371.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M. Rigby R. A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [SEP1](#), [SHASH](#)

Examples

```
y<- rST5(200, mu=5, sigma=1, nu=.1)
hist(y)
curve(dST5(x, mu=30 ,sigma=5,nu=-1), -50, 50, main = "The ST5 density mu=30 ,sigma=5,nu=1")
# library(gamlss)
# m1<-gamlss(y~1, family=ST1)
# m2<-gamlss(y~1, family=ST2)
```

```
# m3<-gamlss(y~1, family=ST3)
# m4<-gamlss(y~1, family=ST4)
# m5<-gamlss(y~1, family=ST5)
# GAIC(m1,m2,m3,m4,m5)
```

TF

t family distribution for fitting a GAMLSS

Description

The function TF defines the t-family distribution, a three parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dTF`, `pTF`, `qTF` and `rTF` define the density, distribution function, quantile function and random generation for the specific parameterization of the t distribution given in details below, with mean equal to μ and standard deviation equal to $\sigma(\frac{\nu}{\nu-2})^{0.5}$ with the degrees of freedom ν . The function TF2 is a different parametrization where `sigma` is the standard deviation.

Usage

```
TF(mu.link = "identity", sigma.link = "log", nu.link = "log")
dTF(x, mu = 0, sigma = 1, nu = 10, log = FALSE)
pTF(q, mu = 0, sigma = 1, nu = 10, lower.tail = TRUE, log.p = FALSE)
qTF(p, mu = 0, sigma = 1, nu = 10, lower.tail = TRUE, log.p = FALSE)
rTF(n, mu = 0, sigma = 1, nu = 10)

TF2(mu.link = "identity", sigma.link = "log", nu.link = "logshiftto2")
dTF2(x, mu = 0, sigma = 1, nu = 10, log = FALSE)
pTF2(q, mu = 0, sigma = 1, nu = 10, lower.tail = TRUE, log.p = FALSE)
qTF2(p, mu = 0, sigma = 1, nu = 10, lower.tail = TRUE, log.p = FALSE)
rTF2(n, mu = 0, sigma = 1, nu = 10)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "identity" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "log" link as the default for the <code>nu</code> parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of the degrees of freedom parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as <code>log(p)</code> .
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

Definition file for t family distribution.

$$f(y|\mu, \sigma, \nu) = \frac{\Gamma((\nu + 1)/2)}{\sigma\Gamma(1/2)\Gamma(\nu/2)\nu^{0.5}} \left[1 + \frac{(y - \mu)^2}{\nu\sigma^2} \right]^{-(\nu+1)/2}$$

$y = (-\infty, +\infty)$, $\mu = (-\infty, +\infty)$, $\sigma > 0$ and $\nu > 0$. Note that $z = (y - \mu)/\sigma$ has a standard t distribution with degrees of freedom ν .

Value

TF() returns a `gamlss.family` object which can be used to fit a t distribution in the `gamlss()` function. `dTF()` gives the density, `pTF()` gives the distribution function, `qTF()` gives the quantile function, and `rTF()` generates random deviates. The latest functions are based on the equivalent R functions for gamma distribution.

Note

μ is the mean and $\sigma[\nu/(\nu - 2)]^{0.5}$ is the standard deviation of the t family distribution. $\nu > 0$ is a positive real valued parameter.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Kalliope Akantzi-Iotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantzi-Iotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#)

Examples

```
TF()# gives information about the default links for the t-family distribution
# library(gamlss)
#data(abdom)
#h<-gamlss(y~cs(x,df=3), sigma.formula=~cs(x,1), family=TF, data=abdom) # fits
#plot(h)
newdata<-rTF(1000,mu=0,sigma=1,nu=5) # generates 1000 random observations
hist(newdata)
```

 WARING

Waring distribution for fitting a GAMLSS model

Description

The function `WARING()` defines the Waring distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with mean equal to the parameter `mu` and scale parameter `sigma`. The functions `dWARING`, `pWARING`, `qWARING` and `rWARING` define the density, distribution function, quantile function and random generation for the `WARING` parameterization of the Waring distribution.

Usage

```
WARING(mu.link = "log", sigma.link = "log")
dWARING(x, mu = 2, sigma = 2, log = FALSE)
pWARING(q, mu = 2, sigma = 2, lower.tail = TRUE, log.p = FALSE)
qWARING(p, mu = 2, sigma = 2, lower.tail = TRUE, log.p = FALSE,
        max.value = 10000)
rWARING(n, mu = 2, sigma = 2)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter
<code>x</code>	vector of (non-negative integer) quantiles.
<code>q</code>	vector of quantiles.
<code>p</code>	vector of probabilities.
<code>n</code>	number of random values to return.
<code>mu</code>	vector of positive <code>mu</code> values.
<code>sigma</code>	vector of positive <code>sigma</code> values.
<code>lower.tail</code>	logical; if TRUE (default) probabilities are $P[Y \leq y]$, otherwise, $P[Y > y]$.
<code>log, log.p</code>	logical; if TRUE probabilities <code>p</code> are given as $\log(p)$.
<code>max.value</code>	constant; generates a sequence of values for the cdf function.

Details

The Waring distribution has density,

$$f(y|\mu, \sigma) = \frac{(1 + \sigma) \Gamma(y + \frac{\mu}{\sigma}) \Gamma(\frac{\mu + \sigma + 1}{\sigma})}{\sigma \Gamma(y + \frac{\mu + 1}{\sigma} + 2) \Gamma(\frac{\mu}{\sigma})}$$

for $y = 0, 1, 2, \dots$, $\mu > 0$ and $\sigma > 0$.

Value

Returns a `gamlss.family` object which can be used to fit a Waring distribution in the `gamlss()` function.

Author(s)

Fiona McElduff, Bob Rigby and Mikis Stasinopoulos. <f.mcelduff@ich.ucl.ac.uk>

References

Wimmer, G. and Altmann, G. (1999) *Thesaurus of univariate discrete probability distributions*. Stamm.

See Also

[gamlss.family](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(0,20,1)
plot(y, dWARING(y), type="h")
q <- seq(0, 20, 1)
plot(q, pWARING(q), type="h")
p<-seq(0.0001,0.999,0.05)
plot(p , qWARING(p), type="s")
dat <- rWARING(100)
hist(dat)
#summary(gamlss(dat~1, family=WARING))
```

 WEI

Weibull distribution for fitting a GAMLSS

Description

The function WEI can be used to define the Weibull distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. [Note that the GAMLSS function WEI2 uses a different parameterization for fitting the Weibull distribution.] The functions `dWEI`, `pWEI`, `qWEI` and `rWEI` define the density, distribution function, quantile function and random generation for the specific parameterization of the Weibull distribution.

Usage

```
WEI(mu.link = "log", sigma.link = "log")
dWEI(x, mu = 1, sigma = 1, log = FALSE)
pWEI(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qWEI(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rWEI(n, mu = 1, sigma = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse", "identity" and "own"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other link is the "inverse", "identity" and "own"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of the <code>mu</code> parameter
<code>sigma</code>	vector of <code>sigma</code> parameter
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parameterization of the function WEI is given by

$$f(y|\mu, \sigma) = \frac{\sigma y^{\sigma-1}}{\mu^\sigma} \exp \left[- \left(\frac{y}{\mu} \right)^\sigma \right]$$

for $y > 0$, $\mu > 0$ and $\sigma > 0$. The GAMLSS functions `dWEI`, `pWEI`, `qWEI`, and `rWEI` can be used to provide the pdf, the cdf, the quantiles and random generated numbers for the Weibull distribution with argument `mu`, and `sigma`. [See the GAMLSS function `WEI2` for a different parameterization of the Weibull.]

Value

`WEI()` returns a `gamlss.family` object which can be used to fit a Weibull distribution in the `gamlss()` function. `dWEI()` gives the density, `pWEI()` gives the distribution function, `qWEI()` gives the quantile function, and `rWEI()` generates random deviates. The latest functions are based on the equivalent R functions for Weibull distribution.

Note

The mean in WEI is given by $\mu\Gamma(\frac{1}{\sigma} + 1)$ and the variance $\mu^2 [\Gamma(\frac{2}{\sigma} + 1) - (\Gamma(\frac{1}{\sigma} + 1))^2]$

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantzi-Iotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [WEI2](#), [WEI3](#)

Examples

```
WEI()
dat<-rWEI(100, mu=10, sigma=2)
# library(gamlss)
# gamlss(dat~1, family=WEI)
```

WEI2	<i>A specific parameterization of the Weibull distribution for fitting a GAMLSS</i>
------	---

Description

The function WEI2 can be used to define the Weibull distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. This is the parameterization of the Weibull distribution usually used in proportional hazard models and is defined in details below. [Note that the GAMLSS function WEI uses a different parameterization for fitting the Weibull distribution.] The functions `dWEI2`, `pWEI2`, `qWEI2` and `rWEI2` define the density, distribution function, quantile function and random generation for the specific parameterization of the Weibull distribution.

Usage

```
WEI2(mu.link = "log", sigma.link = "log")
dWEI2(x, mu = 1, sigma = 1, log = FALSE)
pWEI2(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qWEI2(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rWEI2(n, mu = 1, sigma = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter, other links are "inverse" and "identity"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter, other link is the "inverse" and "identity"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of the <code>mu</code> parameter values
<code>sigma</code>	vector of <code>sigma</code> parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required

Details

The parameterization of the function WEI2 is given by

$$f(y|\mu, \sigma) = \sigma \mu y^{\sigma-1} e^{-\mu y^\sigma}$$

for $y > 0$, $\mu > 0$ and $\sigma > 0$. The GAMLSS functions `dWEI2`, `pWEI2`, `qWEI2`, and `rWEI2` can be used to provide the pdf, the cdf, the quantiles and random generated numbers for the Weibull distribution with argument `mu`, and `sigma`. [See the GAMLSS function `WEI` for a different parameterization of the Weibull.]

Value

`WEI2()` returns a `gamlss.family` object which can be used to fit a Weibull distribution in the `gamlss()` function. `dWEI2()` gives the density, `pWEI2()` gives the distribution function, `qWEI2()` gives the quantile function, and `rWEI2()` generates random deviates. The latest functions are based on the equivalent R functions for Weibull distribution.

Warning

In `WEI2` the estimated parameters `mu` and `sigma` can be highly correlated so it is advisable to use the `CG()` method for fitting [as the `RS()` method can be veru slow in this situation.]

Note

The mean in `WEI2` is given by $\mu^{-1/\sigma} \Gamma(\frac{1}{\sigma} + 1)$ and the variance $\mu^{-2/\sigma} (\Gamma(\frac{2}{\sigma} + 1) - [\Gamma(\frac{1}{\sigma} + 1)]^2)$

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby and Calliope Akantzi-Iotou

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [WEI](#), [WEI3](#),

Examples

```
WEI2()
dat<-rWEI(100, mu=.1, sigma=2)
hist(dat)
# library(gamlss)
# gamlss(dat~1, family=WEI2, method=CG())
```

WEI3

A specific parameterization of the Weibull distribution for fitting a GAMLSS

Description

The function WEI3 can be used to define the Weibull distribution, a two parameter distribution, for a [gamlss.family](#) object to be used in GAMLSS fitting using the function `gamlss()`. This is a parameterization of the Weibull distribution where μ is the mean of the distribution. [Note that the GAMLSS functions [WEI](#) and [WEI2](#) use different parameterizations for fitting the Weibull distribution.] The functions `dWEI3`, `pWEI3`, `qWEI3` and `rWEI3` define the density, distribution function, quantile function and random generation for the specific parameterization of the Weibull distribution.

Usage

```
WEI3(mu.link = "log", sigma.link = "log")
dWEI3(x, mu = 1, sigma = 1, log = FALSE)
pWEI3(q, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
qWEI3(p, mu = 1, sigma = 1, lower.tail = TRUE, log.p = FALSE)
rWEI3(n, mu = 1, sigma = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter, other links are "inverse" and "identity"
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter, other link is the "inverse" and "identity"
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of the mu parameter values
<code>sigma</code>	vector of sigma parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

Details

The parameterization of the function WEI3 is given by

$$f(y|\mu, \sigma) = \frac{\sigma}{\beta} \left(\frac{y}{\beta}\right)^{\sigma-1} e^{-\left(\frac{y}{\beta}\right)^\sigma}$$

where $\beta = \frac{\mu}{\Gamma((1/\sigma)+1)}$ for $y > 0$, $\mu > 0$ and $\sigma > 0$. The GAMLSS functions `dWEI3`, `pWEI3`, `qWEI3`, and `rWEI3` can be used to provide the pdf, the cdf, the quantiles and random generated numbers for the Weibull distribution with argument `mu`, and `sigma`. [See the GAMLSS function `WEI` for a different parameterization of the Weibull.]

Value

`WEI3()` returns a `gamlss.family` object which can be used to fit a Weibull distribution in the `gamlss()` function. `dWEI3()` gives the density, `pWEI3()` gives the distribution function, `qWEI3()` gives the quantile function, and `rWEI3()` generates random deviates. The latest functions are based on the equivalent R functions for Weibull distribution.

Warning

In `WEI3` the estimated parameters `mu` and `sigma` can be highly correlated so it is advisable to use the `CG()` method for fitting [as the `RS()` method can be very slow in this situation.]

Note

The mean in `WEI3` is given by μ and the variance $\mu^2 \left\{ \Gamma(2/\sigma + 1) / [\Gamma(1/\sigma + 1)]^2 - 1 \right\}$

Author(s)

Bob Rigby and Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [WEI](#), [WEI2](#)

Examples

```
WEI3()
dat<-rWEI(100, mu=.1, sigma=2)
# library(gamlss)
# gamlss(dat~1, family=WEI3, method=CG())
```

YULE

Yule distribution for fitting a GAMLSS model

Description

The function YULE defines the Yule distribution, a one parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`, with mean equal to the parameter `mu`. The functions `dYULE`, `pYULE`, `qYULE` and `rYULE` define the density, distribution function, quantile function and random generation for the YULE parameterization of the Yule distribution.

Usage

```
YULE(mu.link = "log")
dYULE(x, mu = 2, log = FALSE)
pYULE(q, mu = 2, lower.tail = TRUE, log.p = FALSE)
qYULE(p, mu = 2, lower.tail = TRUE, log.p = FALSE,
      max.value = 10000)
rYULE(n, mu = 2)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>x</code>	vector of (non-negative integer) quantiles.
<code>q</code>	vector of quantiles.

<code>p</code>	vector of probabilities.
<code>n</code>	number of random values to return.
<code>mu</code>	vector of positive mu values.
<code>lower.tail</code>	logical; if TRUE (default) probabilities are $P[Y \leq y]$, otherwise, $P[Y > y]$.
<code>log, log.p</code>	logical; if TRUE probabilities p are given as $\log(p)$.
<code>max.value</code>	constant; generates a sequence of values for the cdf function.

Details

The Yule distribution has density

$$p(y) = \text{beta}(\text{lambda} + 1, x + 1) / \text{beta}(\text{lambda}, 1)$$

where

$$\text{lambda} = (\text{mu} + 1) / \text{mu}$$

for $y = 0, 1, 2, \dots$ and $\text{mu} > 0$.

Value

Returns a `gamlss.family` object which can be used to fit a Yule distribution in the `gamlss()` function.

Author(s)

Fiona McElduff, Bob Rigby and Mikis Stasinopoulos.

References

Wimmer, G. and Altmann, G. (1999) *Thesaurus of univariate discrete probability distributions*. Stamm.

See Also

[gamlss.family](#)

Examples

```
par(mfrow=c(2,2))
y<-seq(0,20,1)
plot(y, dYULE(y), type="h")
q <- seq(0, 20, 1)
plot(q, pYULE(q), type="h")
p<-seq(0.0001,0.999,0.05)
plot(p , qYULE(p), type="s")
dat <- rYULE(100)
hist(dat)
#summary(gamlss(dat~1, family=YULE))
```

ZABB	<i>Zero inflated and zero adjusted Binomial distribution for fitting in GAMLSS</i>
------	--

Description

The function ZIBB defines the zero inflated beta binomial distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZIBB`, `pZIBB`, `qZIBB` and `rZINN` define the density, distribution function, quantile function and random generation for the zero inflated beta binomial, ZIBB, distribution.

The function ZABB defines the zero adjusted beta binomial distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZABB`, `pZABB`, `qZABB` and `rZABB` define the density, distribution function, quantile function and random generation for the zero inflated beta binomial, ZABB(), distribution.

Usage

```
ZABB(mu.link = "logit", sigma.link = "log", nu.link = "logit")
ZIBB(mu.link = "logit", sigma.link = "log", nu.link = "logit")

dZIBB(x, mu = 0.5, sigma = 0.5, nu = 0.1, bd = 1, log = FALSE)
dZABB(x, mu = 0.5, sigma = 0.1, nu = 0.1, bd = 1, log = FALSE)

pZIBB(q, mu = 0.5, sigma = 0.5, nu = 0.1, bd = 1, lower.tail = TRUE, log.p = FALSE)
pZABB(q, mu = 0.5, sigma = 0.1, nu = 0.1, bd = 1, lower.tail = TRUE, log.p = FALSE)

qZIBB(p, mu = 0.5, sigma = 0.5, nu = 0.1, bd = 1, lower.tail = TRUE, log.p = FALSE)
qZABB(p, mu = 0.5, sigma = 0.1, nu = 0.1, bd = 1, lower.tail = TRUE, log.p = FALSE)

rZIBB(n, mu = 0.5, sigma = 0.5, nu = 0.1, bd = 1)
rZABB(n, mu = 0.5, sigma = 0.1, nu = 0.1, bd = 1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the <code>mu</code> parameter. Other links are "probit" and "cloglog" (complementary log-log)
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the <code>sigma</code> parameter.
<code>nu.link</code>	Defines the <code>sigma.link</code> , with "logit" link as the default for the <code>mu</code> parameter. Other links are "probit" and "cloglog" (complementary log-log)
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive probabilities
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of positive probabilities
<code>bd</code>	vector of binomial denominators

p	vector of probabilities
q	vector of quantiles
n	number of random values to return
log, log.p	logical; if TRUE, probabilities p are given as log(p)
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

For the definition of the distributions see Rigby and Stasinopoulos (2010) below.

Value

The functions ZIBB and ZABB return a `gamlss.family` object which can be used to fit a zero inflated or zero adjusted beta binomial distribution respectively in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.com/>)

See Also

[gamlss.family](#), [NBI](#), [NBII](#)

Examples

```
ZIBB()
ZABB()
# creating data and plotting them
dat <- rZIBB(1000, mu=.5, sigma=.5, nu=0.1, bd=10)
r <- barplot(table(dat), col='lightblue')
dat1 <- rZABB(1000, mu=.5, sigma=.2, nu=0.1, bd=10)
r1 <- barplot(table(dat1), col='lightblue')
```

ZABI	<i>Zero inflated and zero adjusted Binomial distribution for fitting in GAMLSS</i>
------	--

Description

The ZABI() function defines the zero adjusted binomial distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZABI`, `pZABI`, `qZABI` and `rZABI` define the density, distribution function, quantile function and random generation for the zero adjusted binomial, ZABI(), distribution.

The ZIBI() function defines the zero inflated binomial distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZIBI`, `pZIBI`, `qZIBI` and `rZIBI` define the density, distribution function, quantile function and random generation for the zero inflated binomial, ZIBI(), distribution.

Usage

```
ZABI(mu.link = "logit", sigma.link = "logit")
dZABI(x, bd = 1, mu = 0.5, sigma = 0.1, log = FALSE)
pZABI(q, bd = 1, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZABI(p, bd = 1, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZABI(n, bd = 1, mu = 0.5, sigma = 0.1)

ZIBI(mu.link = "logit", sigma.link = "logit")
dZIBI(x, bd = 1, mu = 0.5, sigma = 0.1, log = FALSE)
pZIBI(q, bd = 1, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZIBI(p, bd = 1, mu = 0.5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZIBI(n, bd = 1, mu = 0.5, sigma = 0.1)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the mu parameter. Other links are "probit" and "cloglog"(complementary log-log)
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "logit" link as the default for the mu parameter. Other links are "probit" and "cloglog"(complementary log-log)
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive probabilities
<code>sigma</code>	vector of positive probabilities
<code>bd</code>	vector of binomial denominators
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x]

Details

For the definition of the distributions see Rigby and Stasinopoulos (2010) below.

Value

The functions ZABI and ZIBI return a `gamlss.family` object which can be used to fit a binomial distribution in the `gamlss()` function.

Note

The response variable should be a matrix containing two columns, the first with the count of successes and the second with the count of failures.

Author(s)

Mikis Stasinopoulos, Bob Rigby

References

Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.

Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).

Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.org/>)

See Also

[gamlss.family](#), [BI](#)

Examples

```
ZABI()
curve(dZABI(x, mu = .5, bd=10), from=0, to=10, n=10+1, type="h")
tN <- table(Ni <- rZABI(1000, mu=.2, sigma=.3, bd=10))
r <- barplot(tN, col='lightblue')
```

```
ZIBI()
curve(dZIBI(x, mu = .5, bd=10), from=0, to=10, n=10+1, type="h")
tN <- table(Ni <- rZIBI(1000, mu=.2, sigma=.3, bd=10))
r <- barplot(tN, col='lightblue')
```

Description

The function `ZAGA()` defines the zero adjusted Gamma distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The zero adjusted Gamma distribution is similar to the Gamma distribution but allows zeros as y values. The extra parameter `nu` models the probabilities at zero. The functions `dZAGA`, `pZAGA`, `qZAGA` and `rZAGA` define the density, distribution function, quartile function and random generation for the ZAGA parameterization of the zero adjusted Gamma distribution. `plotZAGA` can be used to plot the distribution. `meanZAGA` calculates the expected value of the response for a fitted model.

Usage

```
ZAGA(mu.link = "log", sigma.link = "log", nu.link = "logit")
dZAGA(x, mu = 1, sigma = 1, nu = 0.1, log = FALSE)
pZAGA(q, mu = 1, sigma = 1, nu = 0.1, lower.tail = TRUE,
      log.p = FALSE)
qZAGA(p, mu = 1, sigma = 1, nu = 0.1, lower.tail = TRUE,
      log.p = FALSE,
      upper.limit = mu + 10 * sqrt(sigma^2 * mu^2))
rZAGA(n, mu = 1, sigma = 1, nu = 0.1, ...)
plotZAGA(mu = 5, sigma = 1, nu = 0.1, from = 0, to = 10,
         n = 101, main=NULL, ...)
meanZAGA(obj)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "logit" link as the default for the sigma parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values
<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of probability at zero parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p).
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>upper.limit</code>	the argument <code>upper.limit</code> sets the upper limit in the golden section search for q, the default is 10 time its standard deviation
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If <code>length(n) > 1</code> , the length is taken to be the number required

from	where to start plotting the distribution from
to	up to where to plot the distribution
obj	a fitted <code>gamlss</code> object
main	for title in the plot
...	... can be used to pass the <code>uppr.limit</code> argument to <code>qIG</code>

Details

The Zero adjusted GA distribution is given as

$$f(y|\mu, \sigma, \nu) = \nu$$

if $(y=0)$

$$f(y|\mu, \sigma, \nu) = (1 - \nu) \left[\frac{1}{(\sigma^2 \mu)^{1/\sigma^2}} \frac{y^{\frac{1}{\sigma^2}-1} e^{-y/(\sigma^2 \mu)}}{\Gamma(1/\sigma^2)} \right]$$

otherwise

for $y = (0, \infty)$, $\mu > 0$, $\sigma > 0$ and $0 < \nu < 1$. $E(y) = (1 - \nu)\mu$ and $Var(y) = (1 - \nu)\mu^2(\nu + \sigma^2)$.

Value

The function `ZAGA` returns a `gamlss.family` object which can be used to fit a zero adjusted Gamma distribution in the `gamlss()` function.

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [GA](#), [ZAIG](#)

Examples

```
ZAGA()# gives information about the default links for the ZAGA distribution
# plotting the function
PPP <- par(mfrow=c(2,2))
plotZAGA(mu=1, sigma=.5, nu=.2, from=0,to=3)
#curve(dZAGA(x,mu=1, sigma=.5, nu=.2), 0,3) # pdf
curve(pZAGA(x,mu=1, sigma=.5, nu=.2), 0,3, ylim=c(0,1)) # cdf
curve(qZAGA(x,mu=1, sigma=.5, nu=.2), 0,.99) # inverse cdf
y<-rZAGA(100, mu=1, sigma=.5, nu=.2) # randomly generated values
hist(y)
par(PPP)
# check that the positive part sums up to .8 (since nu=0.2)
integrate(function(x) dZAGA(x,mu=1, sigma=.5, nu=.2), 0,Inf)
```

ZAIG

The zero adjusted Inverse Gaussian distribution for fitting a GAMLSS model

Description

The function ZAIG() defines the zero adjusted Inverse Gaussian distribution, a three parameter distribution, for a `gamlss` family object to be used in GAMLSS fitting using the function `gamlss()`. The zero adjusted Inverse Gaussian distribution is similar to the Inverse Gaussian distribution but allows zeros as y values. The extra parameter models the probabilities at zero. The functions `dZAIG`, `pZAIG`, `qZAIG` and `rZAIG` define the density, distribution function, quantile function and random generation for the ZAIG parameterization of the zero adjusted Inverse Gaussian distribution. `plotZAIG` can be used to plot the distribution. `meanZAIG` calculates the expected value of the response for a fitted model.

Usage

```
ZAIG(mu.link = "log", sigma.link = "log", nu.link = "logit")
dZAIG(x, mu = 1, sigma = 1, nu = 0.1, log = FALSE)
pZAIG(q, mu = 1, sigma = 1, nu = 0.1, lower.tail = TRUE, log.p = FALSE)
qZAIG(p, mu = 1, sigma = 1, nu = 0.1, lower.tail = TRUE, log.p = FALSE,
      upper.limit = mu + 10 * sqrt(sigma^2 * mu^3))
rZAIG(n, mu = 1, sigma = 1, nu = 0.1, ...)
plotZAIG(mu = 5, sigma = 1, nu = 0.1, from = 0, to = 10, n = 101, ...)
meanZAIG(obj)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>nu.link</code> , with "logit" link as the default for the sigma parameter
<code>x,q</code>	vector of quantiles
<code>mu</code>	vector of location parameter values

<code>sigma</code>	vector of scale parameter values
<code>nu</code>	vector of probability at zero parameter values
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$.
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$
<code>upper.limit</code>	the argument <code>upper.limit</code> sets the upper limit in the golden section search for <code>q</code> , the default is 10 time its standard deviation
<code>p</code>	vector of probabilities.
<code>n</code>	number of observations. If $\text{length}(n) > 1$, the length is taken to be the number required
<code>from</code>	where to start plotting the distribution from
<code>to</code>	up to where to plot the distribution
<code>obj</code>	a fitted BEINF object
<code>...</code>	<code>...</code> can be used to pass the <code>upper.limit</code> argument to <code>qIG</code>

Details

The Zero adjusted IG distribution is given as

$$f(y|\mu, \sigma, \nu) = \nu$$

if $y=0$

$$f(y|\mu, \sigma, \nu) = (1 - \nu) \frac{1}{\sqrt{2\pi\sigma^2 y^3}} \exp\left(-\frac{(y - \mu)^2}{2\mu^2\sigma^2 y}\right)$$

otherwise

for $y \in (0, \infty)$, $\mu > 0$, $\sigma > 0$ and $0 < \nu < 1$. $E(y) = (1 - \nu)\mu$ and $Var(y) = (1 - \nu)\mu^2(\nu + \mu\sigma^2)$.

Value

returns a `gamlss.family` object which can be used to fit a zero adjusted inverse Gaussian distribution in the `gamlss()` function.

Author(s)

Bob Rigby and Mikis Stasinopoulos

References

- Heller, G. Stasinopoulos M and Rigby R.A. (2006) The zero-adjusted Inverse Gaussian distribution as a model for insurance claims. in *Proceedings of the 21th International Workshop on Statistical Modelling*, eds J. Hinde, J. Einbeck and J. Newell, pp 226-233, Galway, Ireland.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family, IG](#)

Examples

```

ZAIG()# gives information about the default links for the ZAIG distribution
# plotting the distribution
plotZAIG( mu =10 , sigma=.5, nu = 0.1, from = 0, to=10, n = 101)
# plotting the cdf
plot(function(y) pZAIG(y, mu=10 ,sigma=.5, nu = 0.1 ), 0, 1)
# plotting the inverse cdf
plot(function(y) qZAIG(y, mu=10 ,sigma=.5, nu = 0.1 ), 0.001, .99)
# generate random numbers
dat <- rZAIG(100,mu=10,sigma=.5, nu=.1)
# fit a model to the data
# library(gamlss)
# m1<-gamlss(dat~1,family=ZAIG)
# meanZAIG(m1)[1]

```

ZANBI

Zero inflated and zero adjusted negative binomial distributions for fitting a GAMLSS model

Description

The function ZINBI defines the zero inflated negative binomial distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZINBI`, `pZINBI`, `qZINBI` and `rZINBI` define the density, distribution function, quantile function and random generation for the zero inflated negative binomial, `ZINBI()`, distribution.

The function ZANBI defines the zero adjusted negative binomial distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZANBI`, `pZANBI`, `qZANBI` and `rZANBI` define the density, distribution function, quantile function and random generation for the zero inflated negative binomial, `ZANBI()`, distribution.

Usage

```

ZINBI(mu.link = "log", sigma.link = "log", nu.link = "logit")
dZINBI(x, mu = 1, sigma = 1, nu = 0.3, log = FALSE)
pZINBI(q, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
qZINBI(p, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
rZINBI(n, mu = 1, sigma = 1, nu = 0.3)
ZANBI(mu.link = "log", sigma.link = "log", nu.link = "logit")
dZANBI(x, mu = 1, sigma = 1, nu = 0.3, log = FALSE)
pZANBI(q, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
qZANBI(p, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
rZANBI(n, mu = 1, sigma = 1, nu = 0.3)

```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the nu parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of zero probability parameter
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities p are given as log(p)
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

The definition for the zero inflated Negative Binomial type I distribution and for the zero adjusted Negative Binomial type I distribution is given in Rigby and Stasinopoulos (2010) below

Value

The functions ZINBI and ZANBI return a `gamlss.family` object which can be used to fit a zero inflated or zero adjusted Negative Binomial type I distribution respectively in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.org/>)

See Also

[gamlss.family](#), [NBI](#), [NBII](#)

Examples

```
ZINBI()
ZANBI()
# creating data and plotting them
dat <- rZINBI(1000, mu=5, sigma=.5, nu=0.1)
r <- barplot(table(dat), col='lightblue')
dat1 <- rZANBI(1000, mu=5, sigma=.5, nu=0.1)
r1 <- barplot(table(dat1), col='lightblue')
```

ZAP

*Zero adjusted poisson distribution for fitting a GAMLSS model***Description**

The function ZAP defines the zero adjusted Poisson distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZAP`, `pZAP`, `qZAP` and `rZAP` define the density, distribution function, quantile function and random generation for the inflated poisson, ZAP(), distribution.

Usage

```
ZAP(mu.link = "log", sigma.link = "logit")
dZAP(x, mu = 5, sigma = 0.1, log = FALSE)
pZAP(q, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZAP(p, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZAP(n, mu = 5, sigma = 0.1)
```

Arguments

<code>mu.link</code>	defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	defines the <code>sigma.link</code> , with "logit" link as the default for the <code>sigma</code> parameter which in this case is the probability at zero. Other links are "probit" and "cloglog"(complementary log-log)
<code>x</code>	vector of (non-negative integer)
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of probabilities at zero
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log</code> , <code>log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

For the definition of the distribution see Rigby and Stasinopoulos (2010) below.

Value

The function ZAP returns a `gamlss.family` object which can be used to fit a zero inflated poisson distribution in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.org/>)

See Also

[gamlss.family](#), [P0](#), [ZIP](#), [ZIP2](#), [ZALG](#)

Examples

```
ZAP()
# creating data and plotting them
dat<-rZAP(1000, mu=5, sigma=.1)
r <- barplot(table(dat), col='lightblue')
```

ZIP

Zero inflated poisson distribution for fitting a GAMLSS model

Description

The function ZIP defines the zero inflated Poisson distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZIP`, `pZIP`, `qZIP` and `rZIP` define the density, distribution function, quantile function and random generation for the inflated poisson, `ZIP()`, distribution.

Usage

```

ZIP(mu.link = "log", sigma.link = "logit")
dZIP(x, mu = 5, sigma = 0.1, log = FALSE)
pZIP(q, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZIP(p, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZIP(n, mu = 5, sigma = 0.1)

```

Arguments

<code>mu.link</code>	defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	defines the <code>sigma.link</code> , with "logit" link as the default for the <code>sigma</code> parameter which in this case is the probability at zero. Other links are "probit" and "cloglog"(complementary log-log)
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of probabilities at zero
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Let $Y = 0$ with probability σ and $Y \sim Po(\mu)$ with probability $(1 - \sigma)$ the Y has a Zero inflated Poisson Distribution given by

$$f(y) = \sigma + (1 - \sigma)e^{-\mu}$$

if ($y=0$)

$$f(y) = (1 - \sigma) \frac{e^{-\mu} \mu^y}{y!}$$

if ($y>0$) for $y = 0, 1, \dots$.

Value

returns a `gamlss.family` object which can be used to fit a zero inflated poisson distribution in the `gamlss()` function.

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Lambert, D. (1992), Zero-inflated Poisson Regression with an application to defects in Manufacturing, *Technometrics*, **34**, pp 1-14.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [P0](#), [ZIP2](#)

Examples

```
ZIP()# gives information about the default links for the normal distribution
# creating data and plotting them
dat<-rZIP(1000, mu=5, sigma=.1)
r <- barplot(table(dat), col='lightblue')
# library(gamlss)
# fit the distribution
# mod1<-gamlss(dat~1, family=ZIP)# fits a constant for mu and sigma
# fitted(mod1)[1]
# fitted(mod1,"sigma")[1]
```

ZIP2

Zero inflated poisson distribution for fitting a GAMLSS model

Description

The function ZIP2 defines the zero inflated Poisson type 2 distribution, a two parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZIP2`, `pZIP2`, `qZIP2` and `rZIP2` define the density, distribution function, quantile function and random generation for the inflated poisson, `ZIP2()`, distribution. The ZIP2 is a different parameterization of the ZIP distribution. In the ZIP2 the μ is the mean of the distribution.

Usage

```
ZIP2(mu.link = "log", sigma.link = "logit")
dZIP2(x, mu = 5, sigma = 0.1, log = FALSE)
pZIP2(q, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
qZIP2(p, mu = 5, sigma = 0.1, lower.tail = TRUE, log.p = FALSE)
rZIP2(n, mu = 5, sigma = 0.1)
```


Arguments

<code>mu.link</code>	defines the <code>mu.link</code> , with "log" link as the default for the <code>mu</code> parameter
<code>sigma.link</code>	defines the <code>sigma.link</code> , with "logit" link as the default for the <code>sigma</code> parameter which in this case is the probability at zero. Other links are "probit" and "cloglog" (complementary log-log)
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of probabilities at zero
<code>p</code>	vector of probabilities
<code>q</code>	vector of quantiles
<code>n</code>	number of random values to return
<code>log, log.p</code>	logical; if TRUE, probabilities <code>p</code> are given as $\log(p)$
<code>lower.tail</code>	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

Let $Y = 0$ with probability σ and $Y \sim Po(\mu / [1 - \sigma])$ with probability $(1 - \sigma)$ then Y has a Zero inflated Poisson type 2 distribution given by

$$f(y|\mu, \sigma) = \sigma + (1 - \sigma)e^{-\mu/(1-\sigma)} \quad \text{if } y = 0$$

$$f(y|\mu, \sigma) = (1 - \sigma) \frac{e^{-\mu/(1-\sigma)} [\mu/(1 - \sigma)]^y}{y!} \quad \text{if } y = 1, 2, 3, \dots$$

The mean of the distribution in this parameterization is `mu`.

Value

returns a `gamlss.family` object which can be used to fit a zero inflated poisson distribution in the `gamlss()` function.

Author(s)

Bob Rigby, Gillian Heller and Mikis Stasinopoulos

References

- Lambert, D. (1992), Zero-inflated Poisson Regression with an application to defects in Manufacturing, *Technometrics*, **34**, pp 1-14.
- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape, (with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.

See Also

[gamlss.family](#), [ZIP](#)

Examples

```
ZIP2())# gives information about the default links for the normal distribution
# creating data and plotting them
dat<-rZIP2(1000, mu=5, sigma=.1)
r <- barplot(table(dat), col='lightblue')
# fit the distribution
# library(gamlss)
# mod1<-gamlss(dat~1, family=ZIP2)# fits a constant for mu and sigma
# fitted(mod1)[1]
# fitted(mod1,"sigma")[1]
```

 ZIPIG

Zero inflated Poisson inverse Gaussian distributions for fitting a GAMLSS model

Description

The function ZIPIG defines the zero inflated Poisson inverse Gaussian distribution, a three parameter distribution, for a `gamlss.family` object to be used in GAMLSS fitting using the function `gamlss()`. The functions `dZIPIG`, `pZIPIG`, `qZIPIG` and `rZIPIG` define the density, distribution function, quantile function and random generation for the zero inflated negative binomial, `ZIPIG()`, distribution.

Usage

```
ZIPIG(mu.link = "log", sigma.link = "log", nu.link = "logit")
dZIPIG(x, mu = 1, sigma = 1, nu = 0.3, log = FALSE)
pZIPIG(q, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
qZIPIG(p, mu = 1, sigma = 1, nu = 0.3, lower.tail = TRUE, log.p = FALSE)
rZIPIG(n, mu = 1, sigma = 1, nu = 0.3)
```

Arguments

<code>mu.link</code>	Defines the <code>mu.link</code> , with "log" link as the default for the mu parameter
<code>sigma.link</code>	Defines the <code>sigma.link</code> , with "log" link as the default for the sigma parameter
<code>nu.link</code>	Defines the <code>mu.link</code> , with "logit" link as the default for the nu parameter
<code>x</code>	vector of (non-negative integer) quantiles
<code>mu</code>	vector of positive means
<code>sigma</code>	vector of positive dispersion parameter
<code>nu</code>	vector of zero probability parameter
<code>p</code>	vector of probabilities

q	vector of quantiles
n	number of random values to return
log, log.p	logical; if TRUE, probabilities p are given as log(p)
lower.tail	logical; if TRUE (default), probabilities are $P[X \leq x]$, otherwise, $P[X > x]$

Details

For the definition of the distribution see Rigby and Stasinopoulos (2010) below.

Value

The function ZIPIG return a `gamlss.family` object which can be used to fit a zero inflated Poisson inverse Gaussian in the `gamlss()` function

Author(s)

Mikis Stasinopoulos <mikis.stasinopoulos@gamlss.org>, Bob Rigby

References

- Rigby, R. A. and Stasinopoulos D. M. (2005). Generalized additive models for location, scale and shape,(with discussion), *Appl. Statist.*, **54**, part 3, pp 507-554.
- Stasinopoulos D. M., Rigby R.A. and Akantziliotou C. (2006) Instructions on how to use the GAMLSS package in R. Accompanying documentation in the current GAMLSS help files, (see also <http://www.gamlss.org/>).
- Stasinopoulos D. M. Rigby R.A. (2007) Generalized additive models for location scale and shape (GAMLSS) in R. *Journal of Statistical Software*, Vol. **23**, Issue 7, Dec 2007, <http://www.jstatsoft.org/v23/i07>.
- Rigby, R. A. and Stasinopoulos D. M. (2010) The `gamlss.family` distributions, (distributed with this package or see <http://www.gamlss.org/>)

See Also

[gamlss.family](#), [PIG](#)

Examples

```
ZIPIG()
# creating data and plotting them
dat <- rZIPIG(1000, mu=5, sigma=.5, nu=0.1)
r <- barplot(table(dat), col='lightblue')
```

Index

- *Topic **\textasciitildekwd1**
 - GE, [48](#)
- *Topic **\textasciitildekwd2**
 - GE, [48](#)
- *Topic **distribution**
 - BB, [4](#)
 - BCCG, [7](#)
 - BCPE, [9](#)
 - BCT, [12](#)
 - BE, [14](#)
 - BEINF, [16](#)
 - BEOI, [20](#)
 - BEZI, [23](#)
 - BI, [25](#)
 - DEL, [28](#)
 - DPO, [30](#)
 - EGB2, [32](#)
 - exGAUS, [34](#)
 - EXP, [36](#)
 - flexDist, [38](#)
 - GA, [39](#)
 - gamlss.dist-package, [3](#)
 - GB1, [44](#)
 - GB2, [46](#)
 - gen.Family, [50](#)
 - GEOM, [52](#)
 - GG, [54](#)
 - GIG, [56](#)
 - GT, [58](#)
 - GU, [59](#)
 - hazardFun, [61](#)
 - IG, [62](#)
 - IGAMMA, [64](#)
 - JSU, [66](#)
 - JSUo, [68](#)
 - LG, [70](#)
 - LNO, [72](#)
 - LO, [75](#)
 - LOGITNO, [77](#)
 - MN3, [82](#)
 - NBF, [84](#)
 - NBI, [86](#)
 - NBII, [88](#)
 - NET, [90](#)
 - NO, [91](#)
 - NO2, [93](#)
 - NOF, [95](#)
 - PARETO2, [97](#)
 - PE, [99](#)
 - PIG, [101](#)
 - PO, [103](#)
 - RG, [105](#)
 - RGE, [107](#)
 - SEP, [109](#)
 - SEP1, [111](#)
 - SHASH, [113](#)
 - SI, [117](#)
 - SICHEL, [119](#)
 - SN1, [121](#)
 - SN2, [123](#)
 - ST1, [124](#)
 - TF, [128](#)
 - WARNING, [130](#)
 - WEI, [131](#)
 - WEI2, [133](#)
 - WEI3, [135](#)
 - YULE, [137](#)
 - ZABB, [139](#)
 - ZABI, [141](#)
 - ZAGA, [143](#)
 - ZAIG, [145](#)
 - ZANBI, [147](#)
 - ZAP, [149](#)
 - ZIP, [150](#)
 - ZIP2, [152](#)
 - ZIPIG, [154](#)
- *Topic **package**
 - gamlss.dist-package, [3](#)

*Topic **regression**

BB, 4
 BCCG, 7
 BCPE, 9
 BCT, 12
 BE, 14
 BEINF, 16
 BEOI, 20
 BEZI, 23
 BI, 25
 checklink, 27
 DEL, 28
 DPO, 30
 EGB2, 32
 exGAUS, 34
 EXP, 36
 flexDist, 38
 GA, 39
 gamlss.family, 41
 GB1, 44
 GB2, 46
 gen.Family, 50
 GEOM, 52
 GG, 54
 GIG, 56
 GT, 58
 GU, 59
 hazardFun, 61
 IG, 62
 IGAMMA, 64
 JSU, 66
 JSUo, 68
 LG, 70
 LNO, 72
 LO, 75
 LOGITNO, 77
 make.link.gamlss, 78
 MN3, 82
 NBF, 84
 NBI, 86
 NBII, 88
 NET, 90
 NO, 91
 NO2, 93
 NOF, 95
 PARETO2, 97
 PE, 99
 PIG, 101
 PO, 103
 RG, 105
 RGE, 107
 SEP, 109
 SEP1, 111
 SHASH, 113
 SI, 117
 SICHEL, 119
 SN1, 121
 SN2, 123
 ST1, 124
 TF, 128
 WARING, 130
 WEI, 131
 WEI2, 133
 WEI3, 135
 YULE, 137
 ZABB, 139
 ZABI, 141
 ZAGA, 143
 ZAIG, 145
 ZANBI, 147
 ZAP, 149
 ZIP, 150
 ZIP2, 152
 ZIPIG, 154
 as.family (gamlss.family), 41
 as.gamlss.family (gamlss.family), 41
 BB, 4, 42, 44
 BCCG, 7, 14, 35, 42, 44, 72, 74
 BCCGo (BCCG), 7
 BCCGuntr (BCCG), 7
 BCPE, 9, 9, 14, 42, 44, 91, 101
 BCPEo (BCPE), 9
 BCPEuntr (BCPE), 9
 BCT, 9, 11, 12, 33, 42, 44, 46, 48, 59, 67, 69,
 111, 116
 BCTo (BCT), 12
 BCTuntr (BCT), 12
 BE, 14, 19, 42, 44
 BEINF, 16, 16, 42, 44
 BEINF0 (BEINF), 16
 BEINF1 (BEINF), 16
 BEo, 19
 BEo (BE), 14
 BEOI, 16, 19, 20, 22, 42
 BEZI, 16, 19, 23, 25, 42

BI, [6](#), [25](#), [42](#), [44](#), [84](#), [142](#)

checkBCPE (BCPE), [9](#)
checklink, [27](#)

dBB (BB), [4](#)
dBCCG (BCCG), [7](#)
dBCCGo (BCCG), [7](#)
dBCPE (BCPE), [9](#)
dBCPEo (BCPE), [9](#)
dBCT (BCT), [12](#)
dBCTo (BCT), [12](#)
dBE (BE), [14](#)
dBEINF (BEINF), [16](#)
dBEINF0 (BEINF), [16](#)
dBEINF1 (BEINF), [16](#)
dBEo (BE), [14](#)
dBEOI (BEOI), [20](#)
dBEZI (BEZI), [23](#)
dBI (BI), [25](#)
dDEL (DEL), [28](#)
dDPO (DPO), [30](#)
dEGB2 (EGB2), [32](#)
DEL, [28](#), [42](#)
dexGAUS (exGAUS), [34](#)
dEXP (EXP), [36](#)
dGA (GA), [39](#)
dGB1 (GB1), [44](#)
dGB2 (GB2), [46](#)
dGE (GE), [48](#)
dGEOM (GEOM), [52](#)
dGG (GG), [54](#)
dGIG (GIG), [56](#)
dGP (GB2), [46](#)
dGT (GT), [58](#)
dGU (GU), [59](#)
dIG (IG), [62](#)
dIGAMMA (IGAMMA), [64](#)
dJSU (JSU), [66](#)
dJSUo (JSUo), [68](#)
dLG (LG), [70](#)
dLNO (LNO), [72](#)
dLO (LO), [75](#)
dLOGITNO (LOGITNO), [77](#)
dLOGNO (LNO), [72](#)
dLOGNO2 (LNO), [72](#)
dMN3 (MN3), [82](#)
dMN4 (MN3), [82](#)
dMN5 (MN3), [82](#)

dNBF (NBF), [84](#)
dNBI (NBI), [86](#)
dNBII (NBII), [88](#)
dNET (NET), [90](#)
dNO (NO), [91](#)
dNO2 (NO2), [93](#)
dNOF (NOF), [95](#)
dPARETO2 (PARETO2), [97](#)
dPARETO2o (PARETO2), [97](#)
dPE (PE), [99](#)
dPE2 (PE), [99](#)
dPIG (PIG), [101](#)
DPO, [30](#)
dPO (PO), [103](#)
dRG (RG), [105](#)
dRGE (RGE), [107](#)
dSEP (SEP), [109](#)
dSEP1 (SEP1), [111](#)
dSEP2 (SEP1), [111](#)
dSEP3 (SEP1), [111](#)
dSEP4 (SEP1), [111](#)
dSHASH (SHASH), [113](#)
dSHASHo (SHASH), [113](#)
dSHASHo2 (SHASH), [113](#)
dSI (SI), [117](#)
dSICHEL (SICHEL), [119](#)
dSN1 (SN1), [121](#)
dSN2 (SN2), [123](#)
dSST (ST1), [124](#)
dST1 (ST1), [124](#)
dST2 (ST1), [124](#)
dST3 (ST1), [124](#)
dST3C (ST1), [124](#)
dST4 (ST1), [124](#)
dST5 (ST1), [124](#)
dTF (TF), [128](#)
dTF2 (TF), [128](#)
dWARING (WARING), [130](#)
dWEI (WEI), [131](#)
dWEI2 (WEI2), [133](#)
dWEI3 (WEI3), [135](#)
dYULE (YULE), [137](#)
dZABB (ZABB), [139](#)
dZABI (ZABI), [141](#)
dZAGA (ZAGA), [143](#)
dZAIG (ZAIG), [145](#)
dZALG (LG), [70](#)
dZANBI (ZANBI), [147](#)

- dZAP (ZAP), 149
 dZIBB (ZABB), 139
 dZIBI (ZABI), 141
 dZINBI (ZANBI), 147
 dZIP (ZIP), 150
 dZIP2 (ZIP2), 152
 dZIPIG (ZIPIG), 154
- EGB2, 32, 42
 exGAUS, 34, 42
 EXP, 36, 42
- Family (gen.Family), 50
 fittedMN (MN3), 82
 flexDist, 38
- GA, 35, 39, 42, 44, 55, 64, 65, 144
 gamlss.dist (gamlss.dist-package), 3
 gamlss.dist-package, 3
 gamlss.family, 4, 6, 9, 11, 14, 16, 19, 22, 25, 27, 28, 30, 33, 35, 37, 41, 41, 46, 48, 49, 53, 55, 57, 59, 61, 62, 64, 65, 67, 69, 71, 72, 74, 76, 78, 80, 84, 87, 89, 91, 93, 95, 97, 99, 101, 103, 104, 106, 109, 111, 113, 116, 118, 120, 122, 124, 127, 129, 131, 133, 135–138, 140, 142, 144, 147, 148, 150, 152, 154, 155
- GB1, 42, 44
 GB2, 42, 46
 GE, 48
 gen.Family, 50
 gen.hazard (hazardFun), 61
 GEOM, 42, 52
 get_C (DPO), 30
 GG, 42, 54
 GIG, 42, 56, 64
 GP (GB2), 46
 GT, 42, 58
 GU, 42, 44, 59
- hazardFun, 61
 histSmo, 39
- IG, 35, 42, 44, 57, 62, 147
 IGAMMA, 42, 64
- JSU, 33, 42, 44, 46, 48, 59, 66, 69, 111, 116
 JSUo, 67, 68
- LG, 42, 70
 LNO, 35, 42, 44, 72
 LO, 42, 44, 75
 LOGITNO, 77
 LOGNO, 42, 78
 LOGNO (LNO), 72
 LOGNO2 (LNO), 72
- make.link.gamlss, 78
 meanBEINF (BEINF), 16
 meanBEINF0 (BEINF), 16
 meanBEINF1 (BEINF), 16
 meanBEOI (BEOI), 20
 meanBEZI (BEZI), 23
 meanZAGA (ZAGA), 143
 meanZAIG (ZAIG), 145
 MN3, 82
 MN4 (MN3), 82
 MN5 (MN3), 82
 MULTIN (MN3), 82
- NBF, 84
 NBI, 42, 44, 85, 86, 89, 103, 104, 118, 140, 148
 NBII, 42, 44, 85, 87, 88, 103, 104, 118, 140, 148
- NET, 42, 90
 NO, 42, 44, 76, 91, 95, 97
 NO2, 93, 93, 97
 NOF, 42, 95
- own.linkfun (make.link.gamlss), 78
 own.linkinv (make.link.gamlss), 78
 own.mu.eta (make.link.gamlss), 78
 own.valideta (make.link.gamlss), 78
- PARETO2, 42, 97
 PARETO2o, 42
 PARETO2o (PARETO2), 97
 pBB (BB), 4
 pBCCG (BCCG), 7
 pBCCGo (BCCG), 7
 pBCPE (BCPE), 9
 pBCPEo (BCPE), 9
 pBCT (BCT), 12
 pBCTo (BCT), 12
 pBE (BE), 14
 pBEINF (BEINF), 16
 pBEINF0 (BEINF), 16
 pBEINF1 (BEINF), 16

- pBEo (BE), 14
 pBEOI (BEOI), 20
 pBEZI (BEZI), 23
 pBI (BI), 25
 pDEL (DEL), 28
 pDPO (DPO), 30
 PE, 42, 44, 99
 PE2, 42
 PE2 (PE), 99
 pEGB2 (EGB2), 32
 pexGAUS (exGAUS), 34
 pEXP (EXP), 36
 pGA (GA), 39
 pGB1 (GB1), 44
 pGB2 (GB2), 46
 pGE (GE), 48
 pGEOM (GEOM), 52
 pGG (GG), 54
 pGIG (GIG), 56
 pGP (GB2), 46
 pGT (GT), 58
 pGU (GU), 59
 FIG, 42, 44, 87, 89, 101, 118, 120, 155
 pIG (IG), 62
 pIGAMMA (IGAMMA), 64
 pJSU (JSU), 66
 pJSUo (JSUo), 68
 pLG (LG), 70
 pLNO (LNO), 72
 pLO (LO), 75
 pLOGITNO (LOGITNO), 77
 pLOGNO (LNO), 72
 pLOGNO2 (LNO), 72
 plotBEINF (BEINF), 16
 plotBEINF0 (BEINF), 16
 plotBEINF1 (BEINF), 16
 plotBEOI (BEOI), 20
 plotBEZI (BEZI), 23
 plotZAGA (ZAGA), 143
 plotZAIG (ZAIG), 145
 pMN3 (MN3), 82
 pMN4 (MN3), 82
 pMN5 (MN3), 82
 pNBF (NBF), 84
 pNBI (NBI), 86
 pNBII (NBII), 88
 pNET (NET), 90
 pNO (NO), 91
 pNO2 (NO2), 93
 pNOF (NOF), 95
 PO, 31, 42, 44, 71, 103, 150, 152
 pPARETO2 (PARETO2), 97
 pPARETO2o (PARETO2), 97
 pPE (PE), 99
 pPE2 (PE), 99
 pPIG (PIG), 101
 pPO (PO), 103
 pRG (RG), 105
 pRGE (RGE), 107
 print.gamlss.family (gamlss.family), 41
 pSEP (SEP), 109
 pSEP1 (SEP1), 111
 pSEP2 (SEP1), 111
 pSEP3 (SEP1), 111
 pSEP4 (SEP1), 111
 pSHASH (SHASH), 113
 pSHASHo (SHASH), 113
 pSHASHo2 (SHASH), 113
 pSI (SI), 117
 pSICHEL (SICHEL), 119
 pSN1 (SN1), 121
 pSN2 (SN2), 123
 pSST (ST1), 124
 pST1 (ST1), 124
 pST2 (ST1), 124
 pST3 (ST1), 124
 pST3C (ST1), 124
 pST4 (ST1), 124
 pST5 (ST1), 124
 pTF (TF), 128
 pTF2 (TF), 128
 pWARING (WARING), 130
 pWEI (WEI), 131
 pWEI2 (WEI2), 133
 pWEI3 (WEI3), 135
 pYULE (YULE), 137
 pZABB (ZABB), 139
 pZABI (ZABI), 141
 pZAGA (ZAGA), 143
 pZAIG (ZAIG), 145
 pZALG (LG), 70
 pZANBI (ZANBI), 147
 pZAP (ZAP), 149
 pZIBB (ZABB), 139
 pZIBI (ZABI), 141
 pZINBI (ZANBI), 147

- pZIP (ZIP), 150
 pZIP2 (ZIP2), 152
 pZIPIG (ZIPIG), 154
- qBB (BB), 4
 qBCCG (BCCG), 7
 qBCCGo (BCCG), 7
 qBCPE (BCPE), 9
 qBCPEo (BCPE), 9
 qBCT (BCT), 12
 qBCTo (BCT), 12
 qBE (BE), 14
 qBEINF (BEINF), 16
 qBEINF0 (BEINF), 16
 qBEINF1 (BEINF), 16
 qBEo (BE), 14
 qBEOI (BEOI), 20
 qBEZI (BEZI), 23
 qBI (BI), 25
 qDEL (DEL), 28
 qDPO (DPO), 30
 qEGB2 (EGB2), 32
 qexGAUS (exGAUS), 34
 qEXP (EXP), 36
 qGA (GA), 39
 qGB1 (GB1), 44
 qGB2 (GB2), 46
 qGE (GE), 48
 qGEOM (GEOM), 52
 qGG (GG), 54
 qGIG (GIG), 56
 qGP (GB2), 46
 qGT (GT), 58
 qGU (GU), 59
 qIG (IG), 62
 qIGAMMA (IGAMMA), 64
 qJSU (JSU), 66
 qJSUo (JSUo), 68
 qLG (LG), 70
 qLNO (LNO), 72
 qLO (LO), 75
 qLOGITNO (LOGITNO), 77
 qLOGNO (LNO), 72
 qLOGNO2 (LNO), 72
 qMN3 (MN3), 82
 qMN4 (MN3), 82
 qMN5 (MN3), 82
 qNBF (NBF), 84
 qNBI (NBI), 86
- qNBII (NBII), 88
 qNO (NO), 91
 qNO2 (NO2), 93
 qNOF (NOF), 95
 qPARETO2 (PARETO2), 97
 qPARETO2o (PARETO2), 97
 qPE (PE), 99
 qPE2 (PE), 99
 qPIG (PIG), 101
 qPO (PO), 103
 qRG (RG), 105
 qRGE (RGE), 107
 qSEP (SEP), 109
 qSEP1 (SEP1), 111
 qSEP2 (SEP1), 111
 qSEP3 (SEP1), 111
 qSEP4 (SEP1), 111
 qSHASH (SHASH), 113
 qSHASHo (SHASH), 113
 qSHASHo2 (SHASH), 113
 qSI (SI), 117
 qSICHEL (SICHEL), 119
 qSN1 (SN1), 121
 qSN2 (SN2), 123
 qSST (ST1), 124
 qST1 (ST1), 124
 qST2 (ST1), 124
 qST3 (ST1), 124
 qST3C (ST1), 124
 qST4 (ST1), 124
 qST5 (ST1), 124
 qTF (TF), 128
 qTF2 (TF), 128
 qWARING (WARING), 130
 qWEI (WEI), 131
 qWEI2 (WEI2), 133
 qWEI3 (WEI3), 135
 qYULE (YULE), 137
 qZABB (ZABB), 139
 qZABI (ZABI), 141
 qZAGA (ZAGA), 143
 qZAIG (ZAIG), 145
 qZALG (LG), 70
 qZANBI (ZANBI), 147
 qZAP (ZAP), 149
 qZIBB (ZABB), 139
 qZIBI (ZABI), 141
 qZINBI (ZANBI), 147

- qZIP (ZIP), [150](#)
- qZIP2 (ZIP2), [152](#)
- qZIPIG (ZIPIG), [154](#)

- rBB (BB), [4](#)
- rBCCG (BCCG), [7](#)
- rBCCGo (BCCG), [7](#)
- rBCPE (BCPE), [9](#)
- rBCPEo (BCPE), [9](#)
- rBCT (BCT), [12](#)
- rBCTo (BCT), [12](#)
- rBE (BE), [14](#)
- rBEINF (BEINF), [16](#)
- rBEINF0 (BEINF), [16](#)
- rBEINF1 (BEINF), [16](#)
- rBEo (BE), [14](#)
- rBEOI (BEOI), [20](#)
- rBEZI (BEZI), [23](#)
- rBI (BI), [25](#)
- rDEL (DEL), [28](#)
- rDPO (DPO), [30](#)
- rEGB2 (EGB2), [32](#)
- rexGAUS (exGAUS), [34](#)
- rEXP (EXP), [36](#)
- RG, [42](#), [44](#), [61](#), [105](#)
- rGA (GA), [39](#)
- rGB1 (GB1), [44](#)
- rGB2 (GB2), [46](#)
- RGE, [42](#), [107](#)
- rGE (GE), [48](#)
- rGEOM (GEOM), [52](#)
- rGG (GG), [54](#)
- rGIG (GIG), [56](#)
- rGP (GB2), [46](#)
- rGT (GT), [58](#)
- rGU (GU), [59](#)
- rIG (IG), [62](#)
- rIGAMMA (IGAMMA), [64](#)
- rJSU (JSU), [66](#)
- rJSUo (JSUo), [68](#)
- rLG (LG), [70](#)
- rLNO (LNO), [72](#)
- rLO (LO), [75](#)
- rLOGITNO (LOGITNO), [77](#)
- rLOGNO (LNO), [72](#)
- rLOGNO2 (LNO), [72](#)
- rMN3 (MN3), [82](#)
- rMN4 (MN3), [82](#)
- rMN5 (MN3), [82](#)

- rNBF (NBF), [84](#)
- rNBI (NBI), [86](#)
- rNBII (NBII), [88](#)
- rNO (NO), [91](#)
- rNO2 (NO2), [93](#)
- rNOF (NOF), [95](#)
- rPARETO2 (PARETO2), [97](#)
- rPARETO2o (PARETO2), [97](#)
- rPE (PE), [99](#)
- rPE2 (PE), [99](#)
- rPIG (PIG), [101](#)
- rPO (PO), [103](#)
- rRG (RG), [105](#)
- rRGE (RGE), [107](#)
- rSEP (SEP), [109](#)
- rSEP1 (SEP1), [111](#)
- rSEP2 (SEP1), [111](#)
- rSEP3 (SEP1), [111](#)
- rSEP4 (SEP1), [111](#)
- rSHASH (SHASH), [113](#)
- rSHASHo (SHASH), [113](#)
- rSHASHo2 (SHASH), [113](#)
- rSI (SI), [117](#)
- rSICHEL (SICHEL), [119](#)
- rSN1 (SN1), [121](#)
- rSN2 (SN2), [123](#)
- rSST (ST1), [124](#)
- rST1 (ST1), [124](#)
- rST2 (ST1), [124](#)
- rST3 (ST1), [124](#)
- rST3C (ST1), [124](#)
- rST4 (ST1), [124](#)
- rST5 (ST1), [124](#)
- rTF (TF), [128](#)
- rTF2 (TF), [128](#)
- rWARING (WARING), [130](#)
- rWEI (WEI), [131](#)
- rWEI2 (WEI2), [133](#)
- rWEI3 (WEI3), [135](#)
- rYULE (YULE), [137](#)
- rZABB (ZABB), [139](#)
- rZABI (ZABI), [141](#)
- rZAGA (ZAGA), [143](#)
- rZAIG (ZAIG), [145](#)
- rZALG (LG), [70](#)
- rZANBI (ZANBI), [147](#)
- rZAP (ZAP), [149](#)
- rZIBB (ZABB), [139](#)

- rZIBI (ZABI), 141
rZINBI (ZANBI), 147
rZIP (ZIP), 150
rZIP2 (ZIP2), 152
rZIPIG (ZIPIG), 154
- SEP, 109, 113
SEP1, 43, 111, 127
SEP2, 43
SEP2 (SEP1), 111
SEP3, 43
SEP3 (SEP1), 111
SEP4, 43
SEP4 (SEP1), 111
SHASH, 43, 113, 127
SHASHo, 43
SHASHo (SHASH), 113
SHASHo2 (SHASH), 113
show.link (make.link.gamlss), 78
SI, 30, 43, 87, 89, 103, 104, 117, 120
SICHEL, 30, 43, 103, 104, 119
SN1, 121
SN2, 123
SST (ST1), 124
ST1, 43, 124
ST2, 43
ST2 (ST1), 124
ST3, 43
ST3 (ST1), 124
ST3C (ST1), 124
ST4, 43
ST4 (ST1), 124
ST5, 43
ST5 (ST1), 124
- TF, 43, 44, 76, 128
TF2 (TF), 128
tofyS (SI), 117
tofySICHEL (SICHEL), 119
- VSICHEL (SICHEL), 119
- WARING, 43, 130
WEI, 43, 44, 131, 135, 137
WEI2, 43, 44, 133, 133, 135, 137
WEI3, 43, 133, 135, 135
- YULE, 43, 137
- ZABB, 139
ZABI, 27, 43, 141
ZAGA, 143
ZAIG, 43, 144, 145
ZALG, 43, 150
ZALG (LG), 70
ZANBI, 147
ZAP, 43, 71, 149
ZIBB (ZABB), 139
ZIBI, 27, 43
ZIBI (ZABI), 141
ZINBI (ZANBI), 147
ZIP, 43, 44, 150, 150, 154
ZIP2, 43, 150, 152, 152
ZIPIG, 154