

Package ‘EMSC’

April 24, 2016

Type Package

Title Extended Multiplicative Signal Correction

Version 0.8

Date 2016-04-24

Author Kristian Hovde Liland

Maintainer Kristian Hovde Liland <kristian.liland@nofima.no>

Description Background correction of spectral like data. Handles variations in scaling, polynomial baselines, interferences, constituents and replicate variation. Parameters for corrections are stored for further analysis, and spectra are corrected accordingly.

License GPL-2

LazyData TRUE

Depends R (>= 2.10)

Imports pracma

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2016-04-24 23:26:16

R topics documented:

EMSC	2
EMSC_model	3
milk	4
orthogonalVectors	5
plot.EMSC	5
predict.EMSC	7

Index	9
--------------	----------

EMSC

Extended multiplicative signal correction (EMSC)

Description

Performs model-based background correction and normalisation of spectra. EMSC handles variations in scaling, polynomial baselines and interferences. Parameters for corrections are stored for further analysis, and spectra are corrected accordingly.

Usage

```
EMSC(X, model = NULL, ...)
```

Arguments

X	matrix containing spectra as rows.
model	an EMSC model to use instead of the other parameters.
...	named model parameters for EMSC_model.

Details

This is the main EMSC function performing all calculations. It can be run with no parameters (defaults are used), with a predefined EMSC model object or with parameters that are passed on to the EMSC model building function [EMSC_model](#).

Value

An object of class EMSC is returned. This contains:

- corrected: matrix of corrected spectra.
- parameters: matrix of fitted parameter values.
- model: object containing input all input parameters.
- X: original data.

References

H. Martens, E. Stark, Extended multiplicative signal correction and spectral interference subtraction: new preprocessing methods for near infrared spectroscopy. *J Pharm Biomed Anal.* 1991; 9(8):625-35.

See Also

[EMSC_model](#) [predict](#).[EMSC](#) [plot](#).[EMSC](#)

Examples

```

data(milk)
Raman      <- milk$Raman[, 850:3300]
EMSC.basic <- EMSC(Raman)
EMSC.poly6 <- EMSC(Raman, degree = 6)
EMSC.rep   <- EMSC(Raman, degree = 6, reference = Raman[30, ],
                  replicates = milk$replicates)

## Not run:
old.par    <- par(mfrow = c(2,2), mar = c(4,4,1,1))
xlim       <- rev(as.numeric(range(colnames(Raman))))
matplot(colnames(Raman), t(Raman), type = 'l', xlim = xlim,
        ylab = 'Relative intensity', xlab = 'Raw spectra')
matplot(colnames(Raman), t(EMSC.basic$corrected), type = 'l', xlim = xlim,
        ylab = 'Relative intensity', xlab = 'Corrected (basic)')
matplot(colnames(Raman), t(EMSC.poly6$corrected), type = 'l', xlim = xlim,
        ylab = 'Relative intensity', xlab = 'Corrected (6th degree polynomial)')
matplot(colnames(Raman), t(EMSC.rep$corrected), type = 'l', xlim = xlim,
        ylab = 'Relative intensity',
        xlab = 'Corrected (reference = spec. #30, replicate correction (90%))')
par(old.par)

## End(Not run)

```

EMSC_model

*Model object for extended multiplicative signal correction (EMSC)***Description**

Sets up an EMSC model to be applied to one or more set of spectra.

Usage

```
EMSC_model(x, reference = NA, degree = 2, interferent = NULL,
           constituent = NULL, weights = NULL, replicates = NULL, rep_corr = 0.9)
```

Arguments

x	numeric vector containing abscissas of spectra to be corrected or matrix to be corrected with/without names colnames.
reference	numeric vector containing the reference spectrum.
degree	integer giving the polynomial degree of the baseline; 0 or higher, default = 2.
interferent	numeric vector containing a spectral component to remove.
constituent	numeric vector containing a spectral component to include.
weights	numeric vector of abscissas weights.

replicates	optional vector which identifies replicates. Default = NULL, meaning no replicate correction will be performed.
rep_corr	proportion of variance or number of subspace components in replicate space (default = 0.9).

Value

An EMSC model is returned containing all parameters.

See Also

[EMSC predict](#). [EMSC plot](#). [EMSC](#)

milk

Raman spectra of milk

Description

42 milk samples with 3 replicates each constitute a Raman data set of 126 samples over 3471 Raman shifts. There is a large fluorescence signal in the spectra that needs to be removed before any data analysis can be performed.

Usage

```
data(milk)
```

Format

A data frame consisting of three parts. The estimated Iodine concentrations of the milk samples, Raman spectra (`matrix`) and a replicate vector.

References

K.H. Liland, A. Kohler, N.K. Afseth. Model-based pre-processing in Raman spectroscopy of biological samples. *Journal of Raman Spectroscopy* (2016).

orthogonalVectors	<i>Orthogonal vectors</i>
-------------------	---------------------------

Description

Create orthogonal set of vectors that resemble the original input vectors.

Usage

```
orthogonalVectors(X, dim = 1, re = TRUE)
```

Arguments

X	a matrix with vectors as rows (default) or columns (see below).
dim	an integer specifying which dimension is the object dimension.
re	a logical indicating if vectors should be norm-scaled before orthogonalization and rescaled afterwards (default = TRUE).

Details

The input vectors are orthogonalized using singular value decomposition. To make the resulting vectors similar to the input vectors (not just any base for the same space) they are re-oriented towards the original vectors using Procrustes rotations.

To force the procedure to handle vectors of unequal magnitudes similarly they are by default rescaled to norm vectors before orthogonalization and rescaled afterwards. This can be overridden using the re parameter.

See Also

[EMSC](#) [EMSC_model](#) [plot.EMSC](#)

plot.EMSC	<i>Plot, print and summary methods for EMSC</i>
-----------	---

Description

Plotting routine for EMSC objects. The default behaviour is to plot raw spectra, reference spectrum, polynomials, interferences, constituents, replicate model and corrected spectra. This can be tweaked by changing the parameters.

Usage

```
## S3 method for class 'EMSC'
plot(x, y, spec = "all", what = c("raw", "reference",
  "polynomials", "interferents", "constituents", "replicates", "corrected"),
  where = c(1, 1, 2, 3, 3, 4, 5), revX = FALSE, labels, type, lty,
  lwd = NULL, pch, cex = NULL, col, xlab, ylab, pretty.xlabels = TRUE,
  xlim, ...)
```

```
## S3 method for class 'EMSC'
print(x, ...)
```

```
## S3 method for class 'EMSC'
summary(object, ...)
```

Arguments

x	An object fitted by the EMSC function.
y	Unused parameter to conform to generic plot.
spec	Parameter specifying if all spectra should be plotted (default) or a subset (numeric vector).
what	character vector defining what to plot.
where	integer vector defining which elements should be plotted in which subplot.
revX	Reverse x axis (default = FALSE).
labels	"names" or "numbers" uses column names for x axis labelling.
type	plotting type (line, points, ...).
lty	line type.
lwd	line width.
pch	plot character.
cex	symbol/line scaling.
col	symbol/line colour.
xlab	x label.
ylab	y label.
pretty.xlabels	Use pretty x labels (default = TRUE).
xlim	x limits.
...	Additional arguments to matplot.
object	An object fitted by the EMSC function.

Details

The parameters `what` and `where` must match so that the parts of the EMSC model end up in the correct subplot. There are limits to the freedom of this function.

`print` and `summary` return minimal information on the EMSC object.

Value

No return.

Author(s)

Kristian Hovde Liland

See Also

[EMSC](#) [EMSC_model](#) [plot.EMSC](#)

Examples

```
data(milk, package = "EMSC")
Raman      <- milk$Raman[, 850:3300]
EMSC.rep   <- EMSC(Raman, degree = 6, reference = Raman[30, ],
                  replicates = milk$replicates)
plot(EMSC.rep)
```

predict.EMSC

Predict Method for EMSC

Description

Prediction for EMSC objects. Corrections are calculated for the new matrix based on the EMSC model used in the input object.

Usage

```
## S3 method for class 'EMSC'
predict(object, newdata = NULL, ...)
```

Arguments

object	An object fitted by the EMSC function.
newdata	A matrix or object convertible to a matrix containing observations as rows.
...	unused.

See Also

[EMSC](#) [EMSC_model](#)

Examples

```
data(milk)
Raman.cal <- milk$Raman[ 1:90, 850:3300]
Raman.val <- milk$Raman[-(1:90), 850:3300]
EMSC.cal <- EMSC(Raman.cal)
EMSC.val <- predict(EMSC.cal, Raman.val)
identical(EMSC.cal$model, EMSC.val$model) # Same model, reference spectrum, etc.

matplot(t(EMSC.cal$corrected), type = 'l', col = 'black', lty = 1, ylab = 'Intensity')
matplot(t(EMSC.val$corrected), type = 'l', col = 'red', lty = 2, add = TRUE)
legend('topleft', legend = c('Calibration','Validation'), lty = 1:2, col = 1:2)
```

Index

EMSC, [2](#), [4](#), [5](#), [7](#)

EMSC_model, [2](#), [3](#), [5](#), [7](#)

milk, [4](#)

orthogonalVectors, [5](#)

plot.EMSC, [2](#), [4](#), [5](#), [5](#), [7](#)

predict.EMSC, [2](#), [4](#), [7](#)

print.EMSC (plot.EMSC), [5](#)

summary.EMSC (plot.EMSC), [5](#)