

Package ‘climwin’

August 29, 2016

Type Package

Title Climate Window Analysis

Version 1.0.0

Author Liam D. Bailey and Martijn van de Pol

Maintainer Liam D. Bailey <liam.bailey@anu.edu.au>

URL <https://github.com/LiamDBailey/climwin>

BugReports <https://github.com/LiamDBailey/climwin/issues>

Description Contains functions to detect and visualise periods of climate sensitivity (climate windows) for a given biological response.

Depends R (>= 2.10), ggplot2, gridExtra, Matrix

Imports evd, lubridate, lme4, MuMIn, reshape, plyr

Suggests testthat, knitr, rmarkdown

License GPL-2

Repository CRAN

LazyData True

VignetteBuilder knitr

RoxygenNote 5.0.1

NeedsCompilation no

Date/Publication 2016-06-01 07:40:05

R topics documented:

autowin	2
Chaff	5
ChaffClim	5
crosswin	6
explore	8
Mass	9
MassClimate	9

MassOutput	9
MassRand	10
medwin	11
Offspring	12
OffspringClimate	12
plotall	13
plotbest	14
plotbetas	15
plotcor	16
plotdelta	17
plothist	18
plotweights	19
plotwin	20
pvalue	21
randwin	22
singlewin	25
Size	28
SizeClimate	28
slidingwin	29
weightwin	32

Index	36
--------------	-----------

autowin	<i>Test for auto-correlation in climate.</i>
---------	--

Description

Tests the correlation between the climate in a specified climate window and other fitted climate windows.

Usage

```
autowin(reference, xvar, cdate, bdate, baseline, range, stat, func, type,
         refday, cmissing = FALSE, cinterval = "day", upper = NA, lower = NA,
         binary = FALSE, centre = list(NULL, "both"), cohort = NULL,
         spatial = NULL, cutoff.day = NULL, cutoff.month = NULL,
         furthest = NULL, closest = NULL, thresh = NULL)
```

Arguments

reference	Reference climate data to be compared. Generated by functions singlewin or slidingwin .
xvar	The climate variable of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
cdate	The climate date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Climate\$Date).

bdate	The biological date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Biol\$Date).
baseline	The baseline model used to fit climate windows. These will be correlated with the reference climate window.
range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the cutoff date or biological record to include in the climate window search.
stat	The aggregate statistic used to analyse the climate data. Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See parameter FUN in apply for more detail.
func	The function used to fit the climate variable. Can be linear ("lin"), quadratic ("quad"), cubic ("cub"), inverse ("inv") or log ("log"). Not required when a variable is provided for parameter 'centre'.
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is "absolute", the day and month respectively of the year from which the absolute window analysis will start.
cmissing	TRUE or FALSE, determines what should be done if there are missing climate data. If FALSE, the function will not run if missing climate data is encountered. If TRUE, any records affected by missing climate data will be removed from climate window analysis.
cinterval	The resolution at which climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ with the choice of cinterval.
upper	Cut-off value used to determine growing degree days or positive climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, autowin will instead calculate an optimal climate zone.
lower	Cut-off value used to determine chill days or negative climate thresholds (determined by parameter thresh). Note that when values of lower and upper are both provided, autowin will instead calculate an optimal climate zone.
binary	TRUE or FALSE. Determines whether to use values of upper and lower to calculate binary climate data (binary = TRUE), or to use for growing degree days (binary = FALSE).
centre	A list item containing: 1. The variable used for mean centring (e.g. Year, Site, Individual). Please specify the parent environment and variable name (e.g. Biol\$Year). 2. Whether the model should include both within-group means and variance ("both"), only within-group means ("mean"), or only within-group variance ("var").
cohort	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). By default, autowin will use year (extracted from parameter bdate) as the cohort variable. The cohort variable should be in the same dataset as the variable bdate.

`spatial` A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. The length of this factor should correspond to the length of the climate dataset.

`cutoff.day, cutoff.month` Redundant parameters. Now replaced by `refday`.

`furthest, closest` Redundant parameters. Now replaced by `range`.

`thresh` Redundant parameter. Now replaced by `binary`.

Value

Will return a data frame showing the correlation between the climate in each fitted window and the chosen reference window.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:

# Test for auto-correlation using 'Mass' and 'MassClimate' data frames

data(Mass)
data(MassClimate)

# Fit a single climate window using the datasets Mass and MassClimate.

single <- singlewin(xvar = list(Temp = MassClimate$Temp),
                   cdate = MassClimate$Date, bdate = Mass$Date,
                   baseline = lm(Mass ~ 1, data = Mass),
                   range = c(72, 15),
                   stat = "mean", func = "lin", type = "absolute",
                   refday = c(20, 5),
                   cmissing = FALSE, cinterval = "day")

# Test the autocorrelation between the climate in this single window and other climate windows.

auto <- autowin(reference = single,
               xvar = list(Temp = MassClimate$Temp), cdate = MassClimate$Date, bdate = Mass$Date,
               baseline = lm(Mass ~ 1, data = Mass), range = c(365, 0),
               stat = "mean", func = "lin",
               type = "absolute", refday = c(20, 5),
               cmissing = FALSE, cinterval = "day")

# View the output
head(auto)
```

```
# Plot the output
plotcor(auto, type = "A")

## End(Not run)
```

Chaff	<i>Annual laying date of breeding common chaffinch (Fringilla coelebs).</i>
-------	---

Description

Average annual laying date of common chaffinch (*Fringilla coelebs*) measured over 47 years.

Format

A data frame with 47 rows and 3 variables.

Year Year of laying date measurement.

Date Average date of measurement.

Laydate Average annual laying date in days after January 1st.

ChaffClim	<i>Daily climate data from 1965 to 2012.</i>
-----------	--

Description

Maximum daily temperature and average rainfall data from 1965 to 2012. Coincides with biological data from [Chaff](#).

Format

A data frame with 17,520 rows and 3 variables.

Date Date when climate was recorded (dd/mm/yyyy).

Rain Average daily rainfall data in mm.

Temp Maximum daily temperature in degrees centigrade.

crosswin

*Test the correlation between two climate variables.***Description**

Test the correlation between two climate variables.

Usage

```
crosswin(xvar, xvar2, cdate, bdate, range, stat, stat2, type, refday,
  cinterval = "day", cmissing = FALSE, spatial = NULL, cohort = NULL,
  cutoff.day = NULL, cutoff.month = NULL, furthest = NULL,
  closest = NULL)
```

Arguments

xvar	The first climate variable of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
xvar2	The second climate variable of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
cdate	The climate date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Climate\$Date).
bdate	The biological date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Biol\$Date).
range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the cutoff date or biological record to include in the climate window search.
stat	The aggregate statistic used to analyse the climate data. Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See FUN in apply for more detail.
stat2	Second aggregate statistic used to analyse climate data (xvar2). Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See FUN in apply for more detail.
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is absolute, the day and month respectively of the year from which the absolute window analysis will start.
cinterval	The resolution at which climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ depending on the choice of cinterval

<code>cmissing</code>	TRUE or FALSE, determines what should be done if there are missing climate data. If FALSE, the function will not run if missing climate data is encountered. If TRUE, any records affected by missing climate data will be removed from climate window analysis.
<code>spatial</code>	A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. This length of this factor should correspond to the length of the climate dataset.
<code>cohort</code>	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). By default, autowin will use year (extracted from parameter <code>bdate</code>) as the cohort variable. The cohort variable should be in the same dataset as the variable <code>bdate</code> .
<code>cutoff.day</code> , <code>cutoff.month</code>	Redundant parameters. Now replaced by <code>refday</code> .
<code>furthest</code> , <code>closest</code>	Redundant parameters. Now replaced by <code>range</code> .

Value

Will return a dataframe containing the correlation between the two climate variables.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:
# Test correlation between temperature and rainfall in the MassClimate dataset.

data(Mass)
data(MassClimate)

cross <- crosswin(xvar = list(Temp = MassClimate$Temp),
                 xvar2 = list(Rain = MassClimate$Rain),
                 cdate = MassClimate$Date, bdate = Mass$Date,
                 range = c(365, 0),
                 stat = "mean", stat2 = "mean", type = "relative",
                 cmissing = FALSE, cinterval = "day")

# View the output
head(cross)

# Plot the output
plotcor(cross, type = "C")

## End(Not run)
```

explore

Visualise the weight distribution for given parameter values

Description

Create a plot of the Weibull or Generalised Extreme Values (GEV) distribution for given values of shape, scale and location parameters. Used to determine initial parameter values for [weightwin](#).

Usage

```
explore(shape = 1, scale = 1, loc = 0, weightfunc = "W")
```

Arguments

shape	A parameter that determines the shape of the distribution. Should be greater than 0.
scale	A parameter that determines the scale of the distribution. Should be greater than 0.
loc	A parameter that determines the location of the distribution. Should be less than or equal to 0.
weightfunc	Choose whether to use a weibull ("W") or GEV ("G") distribution.

Value

explore will return an example plot of the distribution using given parameter values. This can be used to select the initial parameter values for [weightwin](#)

Author(s)

Martijn van de Pol and Liam D. Bailey

Examples

```
# Test a weibull distribution
explore(shape = 3, scale = 0.2, loc = 0, weightfunc = "W")

# Test a GEV distribution
explore(shape = 3, scale = 5, loc = -5, weightfunc = "G")
```

Mass	<i>Body mass data since 1979.</i>
------	-----------------------------------

Description

Artificially generated data representing average body mass since 1979.

Format

A data frame with 47 rows and 2 variables

Date Date of mass measurements (dd/mm/yyyy).

Mass Annual average body mass in grams.

MassClimate	<i>Daily climate data since 1979.</i>
-------------	---------------------------------------

Description

Daily temperature and rainfall data since 1979.

Format

A data frame with 17,532 rows and 3 variables.

Date Date when climate data was recorded (dd/mm/yyyy).

Rain Daily rainfall data in mm.

Temp Daily temperature data in degrees centigrade.

MassOutput	<i>Example output dataframe from function slidingwin.</i>
------------	---

Description

Output file from [slidingwin](#) using temperature and body mass data. Generated with [Mass](#) and [MassClimate](#) dataframes.

Format

A data frame with 5,151 rows and 19 variables.

deltaAICc Difference between model AICc of fitted climate window and a null model containing no climate.

WindowOpen The start day of each tested climate window. Furthest from the biological record.

WindowClose The end day of each tested climate window. Closest to the biological record.

ModelBeta Beta estimate of the relationship between temperature and mass.

Std.Error Standard error term for linear model betas.

ModelBetaQ Quadratic beta estimate of the relationship between temperature and mass.

ModelBetaC Cubic beta estimate of the relationship between temperature and mass.

ModelInt Model intercept.

Function The function used to fit climate (e.g. linear ("lin"), quadratic ("quad"))

Furthest Furthest day back considered in slidingwin.

Closest Closest day back considered in slidingwin.

Statistics The aggregate statistic used to analyse climate (e.g. mean, max, slope).

Type Whether "absolute" or "relative" climate windows were tested.

K Number of folds used for k-fold cross validation.

ModWeight Model weight of each fitted climate window.

sample.size Sample size (i.e. number of years or sites) used for climate window analysis.

Reference.day,Reference.month If type is "absolute", the date from which the climate window was tested.

Randomised Whether the data was generated using [slidingwin](#) or [randwin](#).

MassRand

Example output dataframe from function randwin.

Description

Output file from function [randwin](#) using temperature and mass data. Generated with [Mass](#) and [MassClimate](#) dataframes.

Format

A data frame with 5 rows and 21 variables.

deltaAICc Difference between model AICc of fitted climate window and a null model containing no climate.

WindowOpen The start day of each tested climate window. Furthest from the biological record.

WindowClose The end day of each tested climate window. Closest to the biological record.

ModelBeta Beta estimate of the relationship between temperature and mass.

- Std.Error** Standard error term for linear model betas.
- ModelBetaQ** Quadratic beta estimate of the relationship between temperature and mass.
- ModelBetaC** Cubic beta estimate of the relationship between temperature and mass.
- ModelInt** Model intercept.
- Function** The function used to fit climate (e.g. linear ("lin"), quadratic ("quad"))
- Furthest** Furthest day back considered in slidingwin.
- Closest** Closest day back considered in slidingwin.
- Statistics** The aggregate statistic used to analyse climate (e.g. mean, max, slope).
- Type** Whether "fixed" or "variable" climate windows were tested.
- K** Number of folds used for k-fold cross validation.
- ModWeight** Model weight of each fitted climate window.
- sample.size** Sample size (i.e. number of years or sites) used for climate window analysis.
- Reference.day,Reference.month** If type is "absolute", the date from which the climate window was tested.
- Randomised** Whether the data was generated using [slidingwin](#) or [randwin](#).
- Repeat** The number of randomisations carried out.
- WeightDist** Model spread of 95 percent confidence set of models.

 medwin

Determine the median start and end time for climate windows

Description

Determine the median start and end time for climate windows within a chosen confidence set.

Usage

```
medwin(dataset, cw = 0.95)
```

Arguments

dataset	Output dataframe of function slidingwin .
cw	Cut-off for confidence set (0.95 by default)

Value

Returns two values representing the median start and end time of climate windows within the confidence set.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:
# Determine median start and end time of MassOutput from the 95% confidence set

medwin(MassOutput, cw = 0.95)

## End(Not run)
```

Offspring	<i>Reproductive success of birds since 2009.</i>
-----------	--

Description

Artificially generated data representing reproductive success of birds since 2009.

Format

A data frame with 1,619 rows and 5 variables.

Offspring Total number of offspring produced.

Date Date of hatching (dd/mm/yyyy).

Order Order of nest within each season.

BirdID Individual ID of female.

Cohort Grouping factor designating the breeding season of each record.

OffspringClimate	<i>Daily climate data since 2009.</i>
------------------	---------------------------------------

Description

Daily temperature and rainfall data since 2009. Coincides with biological data from [Offspring](#).

Format

A data frame with 2,588 rows and 3 variables.

Date Date when climate was recorded (dd/mm/yyyy).

Rain Daily rainfall data in mm.

Temperature Daily temperature data in degrees centigrade.

plotall	<i>Visualise climate window data</i>
---------	--------------------------------------

Description

Creates a panel of plots to help visualise climate window data.

Usage

```
plotall(dataset, datasetrand = NULL, bestmodel = NULL,
        bestmodeldata = NULL, cw1 = 0.95, cw2 = 0.5, cw3 = 0.25,
        title = NULL, arrow = FALSE)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
datasetrand	A dataframe containing information on all fitted climate windows using randomised data. Output from randwin .
bestmodel	A model object. The strongest climate window model. Returned from singlewin or slidingwin .
bestmodeldata	A dataframe containing the biological and climate data used to fit the strongest climate window model. Output from singlewin or slidingwin .
cw1, cw2, cw3	Cumulative weight levels used to visualise model weight distribution. See plotweights for more detail.
title	Title of the plot panel.
arrow	TRUE or FALSE. Add arrows to plots to pinpoint best window.

Value

Will return a panel of 6-8 plots:

- DeltaAICc: A colour plot of model deltaAICc values (larger negative values indicate stronger models). DeltaAICc is the difference between AICc of each climate window model and the baseline model containing no climate data.
- Model weight: A plot showing the distribution of cumulative model weights. Gradient levels determined by parameters cw1, cw2 and cw3. Darker areas have a higher chance of containing the best climate window. Also returns the percentage of models within the 95
- Model betas: A colour plot of model beta estimates. Where applicable, 2nd order coefficients (quadratic) and 3rd order coefficients (cubic) will be plotted separately.
- Histogram(s): If datasetrand is provided, plotall will return a histogram showing the deltaAICc of randomised data. This can help determine the likelihood of obtaining a deltaAICc value for a fitted climate window model at random. plotall will also use [pvalue](#) to return values of Pc and PdeltaAICc.

- **Boxplots:** Two boxplots showing the start and end time for a subset of best climate windows. Best climate windows make up the cumulative model weight equivalent to the largest value of `cw1`, `cw2` and `cw3`. Values above boxplots represent the median values.
- **Best Model:** If `bestmodel` and `bestmodeldata` are provided, `plotall` will create a scatterplot to show the fit of the best model through the data.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Visualise a fixed climate window generated for dataframes Mass and MassClimate

data(MassOutput)
data(Mass)
data(MassClimate)

single <- singlewin(xvar = list(Temp = MassClimate$Temp),
                   cdate = MassClimate$Date, bdate = Mass$Date,
                   baseline = lm(Mass ~ 1, data = Mass),
                   range = c(72, 15),
                   stat = "mean", func = "lin",
                   type = "absolute", relday = c(20, 5),
                   cmissing = FALSE, cinterval = "day")

plotall(dataset = MassOutput, bestmodel = single$bestmodel,
        bestmodeldata = single$bestmodeldata,
        cw1 = 0.95, cw2 = 0.5, cw3 = 0.25, title = "Mass")
```

plotbest

Visualise the best climate window

Description

Create a scatterplot showing the fit of the best climate window model through the biological data.

Usage

```
plotbest(dataset, bestmodel, bestmodeldata)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
bestmodel	A model object. The strongest climate window model. Output from singlewin or slidingwin .
bestmodeldata	A dataframe with the data used to fit the strongest climate window model. Output from singlewin or slidingwin .

Value

Returns a scatterplot with a fitted line to show the fit of the best model through the data.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Visualise the best climate window from the datasets Mass and MassClimate

data(MassOutput)
data(Mass)
data(MassClimate)

single <- singlewin(xvar = list(Temp = MassClimate$Temp),
                   cdate = MassClimate$Date, bdate = Mass$Date,
                   baseline = lm(Mass ~ 1, data = Mass),
                   range = c(72, 15),
                   stat = "mean", func = "lin",
                   type = "absolute", refday = c(20, 5),
                   cmissing = FALSE, cinterval = "day")

plotbest(dataset = MassOutput, bestmodel = single$BestModel,
         bestmodeldata = single$BestModelData)
```

plotbetas

Plot model beta estimates

Description

Create colour plots of model beta estimates. Will include quadratic and cubic beta estimates where appropriate.

Usage

```
plotbetas(dataset, arrow = FALSE, plotallenv, plotall = FALSE)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
arrow	TRUE or FALSE. Add arrows to plots to pinpoint best window.
plotallenv	Used in conjunction with function plotall . Should not be changed manually.
plotall	Used in conjunction with function plotall . Should not be changed manually.

Value

Returns colour plots of model beta estimates. Where applicable, 2nd order coefficients (quadratic) and 3rd order coefficients (cubic) will be plotted seperately.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Plot model beta estimates for linear models in the Mass dataset

data(MassOutput)

plotbetas(dataset = MassOutput)
```

plotcor

Visualise climate cross correlation or autocorrelation.

Description

Create a colour plot to visualise the results of [autowin](#) or [crosswin](#). Displays correlation across all desired climate windows.

Usage

```
plotcor(cor.output, type, arrow = FALSE)
```

Arguments

cor.output	Output of autowin or crosswin
type	Should be either "A" for data generated by autowin or "C" for data generated by crosswin .
arrow	TRUE or FALSE. Add arrows to plots to pinpoint best window.

Value

Will generate a colour plot to visualise the correlation data.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:
# Visualise climate autocorrelation

data(Mass)
data(MassClimate)

# Fit a single climate window using the datasets Mass and MassClimate.

single <- singlewin(xvar = list(Temp = MassClimate$Temp),
                   cdate = MassClimate$Date, bdate = Mass$Date,
                   baseline = lm(Mass ~ 1, data = Mass),
                   range = c(72, 15),
                   stat = "mean", func = "lin",
                   type = "absolute", refday = c(20, 5),
                   cmissing = FALSE, cinterval = "day")

# Test the autocorrelation between the climate in this single window and other climate windows.

auto <- autowin(reference = single,
               xvar = list(Temp = MassClimate$Temp),
               cdate = MassClimate$Date, bdate = Mass$Date,
               baseline = lm(Mass ~ 1, data = Mass),
               range = c(365, 0),
               stat = "mean", func = "lin",
               type = "absolute", refday = c(20, 5),
               cmissing = FALSE, cinterval = "day")

# Plot the auto-correlation data

plotcor(auto, type = "A")

## End(Not run)
```

plotdelta

Plot deltaAICc of models

Description

Create a colour plot of model deltaAICc values.

Usage

```
plotdelta(dataset, arrow = FALSE, plotall = FALSE, plotallenv)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
arrow	TRUE or FALSE. Add arrows to plots to pinpoint best window.
plotall	Used in conjunction with function plotall . Should not be changed manually.
plotallenv	Used in conjunction with function plotall . Should not be changed manually.

Value

Returns a colour plot of model deltaAICc values (larger negative values indicate stronger models). DeltaAICc is the difference between AICc of each climate window and a null model.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Plot deltaAICc estimates for climate windows in the Mass dataset
data(MassOutput)

plotdelta(dataset = MassOutput)
```

plothist

Create a histogram of randomised deltaAICc values

Description

Create a histogram of deltaAICc values from randomised data.

Usage

```
plothist(dataset, datasetrand)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows from observed data. Output from slidingwin .
datasetrand	A dataframe containing information on all fitted climate windows using randomised data. Output from randwin .

Value

plothist will return a histograms of deltaAICc values from randomised data. Values of PdeltaAICc and Pc will be provided to help determine the likelihood that an observed deltaAICc value would occur by chance.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Plot randomised data for the Mass dataset

data(MassOutput)
data(MassRand)

plothist(datasetrand = MassRand, dataset = MassOutput)
```

plotweights *Plot distribution of model weights*

Description

Create a plot showing the distribution of cumulative model weights for all fitted climate windows.

Usage

```
plotweights(dataset, cw1 = 0.95, cw2 = 0.5, cw3 = 0.25, arrow = FALSE,
            plotall = FALSE, plotallenv)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
cw1, cw2, cw3	Cumulative weight levels used to visualise model weight distribution. Cumulative weights represent the chance that the best model is contained within a set. For example, there is a 95 percent chance that the best climate window model is contained within the cumulative weight level of 0.95. Parameter values must ≤ 1 .
arrow	TRUE or FALSE. Add arrows to plots to pinpoint best window.
plotall	Used in conjunction with function plotall . Should not be changed manually.
plotallenv	Used in conjunction with function plotall . Should not be changed manually.

Value

Returns a plot showing the distribution of cumulative model weights. Levels determined by parameters cw1,cw2 and cw3.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Plot distribution of model weights for Mass dataset

data(MassOutput)

plotweights(dataset = MassOutput, cw1 = 0.95, cw2 = 0.75, cw3 = 0.25)
```

plotwin

Plot the start and end time of best climate windows

Description

Visualise the start and end time for a subset of best climate windows.

Usage

```
plotwin(dataset, cw = 0.95)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
cw	Cumulative model weight used to subset the group of best models.

Value

Creates two boxplots showing the start and end time for a subset of best climate windows. Best climate windows make up the cumulative model weight equivalent to the value of cw.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# View window limits for climate windows in the top 95% of model weights.

data(MassOutput)

plotwin(dataset = MassOutput, cw = 0.95)
```

pvalue	<i>Determine the probability that a given climate signal is 'true'.</i>
--------	---

Description

Calculate probability that a given climate signal is 'true' using either PDAICc or Pc.

Usage

```
pvalue(dataset, datasetrand, metric, sample.size)
```

Arguments

dataset	A dataframe containing information on all fitted climate windows. Output from slidingwin .
datasetrand	A dataframe containing information on all fitted climate windows using randomised data. Output from randwin .
metric	"AIC" or "C". Determine whether a value of PDAICc or Pc will be returned.
sample.size	Sample size of analysis.

Value

Returns a value representing the probability that a given climate window result is a false positive.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
# Calculate PDAICc for the Mass dataset
pvalue(datasetrand = MassRand, dataset = MassOutput,
        metric = "AIC", sample.size = 47)

# Calculate Pc for the Mass dataset
pvalue(datasetrand = MassRand, dataset = MassOutput,
        metric = "C", sample.size = 47)
```

 randwin

Climate window analysis for randomised data

Description

Randomises biological data and carries out a climate window analysis. Used to help determine the chance of obtaining an observed result at random.

Usage

```
randwin(exclude = NA, repeats = 5, window = "sliding", xvar, cdate, bdate,
        baseline, stat, range, func, type, refday, cmissing = FALSE,
        cinterval = "day", spatial = NULL, cohort = NULL, upper = NA,
        lower = NA, binary = FALSE, centre = list(NULL, "both"), k = 0,
        weightfunc = "W", par = c(3, 0.2, 0), control = list(ndeps = c(0.01,
        0.01, 0.01)), method = "L-BFGS-B", cutoff.day = NULL,
        cutoff.month = NULL, furthest = NULL, closest = NULL, thresh = NULL,
        cvk = NULL)
```

Arguments

exclude	Two values (distance and duration) which allow users to exclude short-duration long-lag climate windows from analysis (e.g., windows with a duration of 10 days which occur over a month ago). These windows are often considered to be biologically implausible.
repeats	The number of times that data will be randomised and analysed for climate windows.
window	Whether randomisations are carried out for a sliding window ("sliding") or weighted window ("weighted") approach.
xvar	A list object containing all climate variables of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
cdat	The climate date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Climate\$Date).
bdate	The biological date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Biol\$Date).
baseline	The baseline model structure used for testing correlation. Currently known to support lm, glm, lmer and glmer objects.
stat	If window = "sliding"; The aggregate statistic used to analyse the climate data. Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See FUN in apply for more detail.
range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the cutoff date or biological record to include in the climate window search.

func	The functions used to fit the climate variable. Can be linear ("lin"), quadratic ("quad"), cubic ("cub"), inverse ("inv") or log ("log").
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is absolute, the day and month respectively of the year from which the absolute window analysis will start.
cmissing	TRUE or FALSE, determines what should be done if there are missing climate data. If FALSE, the function will not run if missing climate data is encountered. If TRUE, any records affected by missing climate data will be removed from climate window analysis.
cinterval	The resolution at which climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ depending on the choice of cinterval.
spatial	A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. This length of this factor should correspond to the length of the climate dataset.
cohort	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). Only required when type is "absolute". The cohort variable should be in the same dataset as the variable bdate.
upper	Cut-off values used to determine growing degree days or positive climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, climatewin will instead calculate an optimal climate zone.
lower	Cut-off values used to determine chill days or negative climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, climatewin will instead calculate an optimal climate zone.
binary	TRUE or FALSE. Determines whether to use values of upper and lower to calculate binary climate data (thresh = TRUE), or to use for growing degree days (thresh = FALSE).
centre	A list item containing: 1. The variable used for mean centring (e.g. Year, Site, Individual). Please specify the parent environment and variable name (e.g. Biol\$Year). 2. Whether the model should include both within-group means and variance ("both"), only within-group means ("mean"), or only within-group variance ("var").
k	If window = "sliding"; the number of folds used for k-fold cross validation. By default this value is set to 0, so no cross validation occurs. Value should be a minimum of 2 for cross validation to occur.
weightfunc	If window = "weighted"; the distribution to be used for optimisation. Can be either a Weibull ("W") or Generalised Extreme Value distribution ("G").
par	If window = "weighted"; the shape, scale and location parameters of the Weibull or GEV weight function used as start weight function. For Weibull : Shape and scale parameters must be greater than 0, while location parameter must be less than or equal to 0. For GEV : Scale parameter must be greater than 0.

control	If window = "weighted"; parameters used to determine step size for the optimisation function. Please see optim for more detail.
method	If window = "weighted"; the method used for the optimisation function. Please see optim for more detail.
cutoff.day, cutoff.month	Redundant parameters. Now replaced by refday.
furthest, closest	Redundant parameters. Now replaced by range.
thresh	Redundant parameter. Now replaced by binary.
cvk	Redundant parameter. Now replaced by k.

Value

Returns a dataframe containing information on the best climate window from each randomisation. See [MassRand](#) as an example.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:

## EXAMPLE 1 ##

# Test climate windows in randomised data using a sliding window approach.

data(Mass)
data(MassClimate)

# Randomise data twice
# Note all other parameters are fitted in the same way as the climatewin function.

rand <- randwin(repeats = 2, window = "sliding",
               xvar = list(Temp = MassClimate$Temp),
               cdate = MassClimate$Date, bdate = Mass$Date,
               baseline = lm(Mass ~ 1, data = Mass),
               range = c(100, 0),
               stat = "mean", func = "lin", type = "absolute",
               refday = c(20, 5),
               cmissing = FALSE, cinterval = "day")

# View output #

head(rand)

## EXAMPLE 2 ##

# Test climate windows in randomised data using a weighted window approach.
```



```

data(Offspring)
data(OffspringClimate)

# Randomise data twice
# Note all other parameters are fitted in the same way as the weightwin function.

weightrand <- randwin(repeats = 2, window = "weighted",
  xvar = list(Temp = OffspringClimate$Temperature),
  cdate = OffspringClimate$Date,
  bdate = Offspring$Date,
  baseline = glm(Offspring ~ 1, family = poisson, data = Offspring),
  range = c(365, 0), func = "quad",
  type = "relative", weightfunc = "W", cinterval = "day",
  par = c(3, 0.2, 0), control = list(ndeps = c(0.01, 0.01, 0.01)),
  method = "L-BFGS-B")

# View output

head(weightrand)

## End(Not run)

```

singlewin

Fit a single climate window

Description

Fit a single climate window with a known start and end time.

Usage

```

singlewin(xvar, cdate, bdate, baseline, range, stat, func, type, refday,
  cmissing = FALSE, cinterval = "day", cohort = NULL, spatial = NULL,
  upper = NA, lower = NA, binary = FALSE, centre = list(NULL, "both"),
  cutoff.day = NULL, cutoff.month = NULL, furthest = NULL,
  closest = NULL, thresh = NULL)

```

Arguments

xvar	A list object containing all climate variables of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
cdate	The climate date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Climate\$Date).
bdate	The biological date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Biol\$Date).

baseline	The baseline model structure used for testing correlation. Currently known to support lm, glm, lmer and glmer objects.
range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the cutoff date or biological record to include in the climate window search.
stat	The aggregate statistic used to analyse the climate data. Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See FUN in apply for more detail.
func	The functions used to fit the climate variable. Can be linear ("lin"), quadratic ("quad"), cubic ("cub"), inverse ("inv") or log ("log").
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is absolute, the day and month respectively of the year from which the absolute window analysis will start.
cmissing	TRUE or FALSE, determines what should be done if there are missing climate data. If FALSE, the function will not run if missing climate data is encountered. If TRUE, any records affected by missing climate data will be removed from climate window analysis.
cinterval	The resolution at which climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ depending on the choice of cinterval.
cohort	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). Only required when type is "absolute". The cohort variable should be in the same dataset as the variable bdate.
spatial	A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. This length of this factor should correspond to the length of the climate dataset.
upper	Cut-off values used to determine growing degree days or positive climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, climatewin will instead calculate an optimal climate zone.
lower	Cut-off values used to determine chill days or negative climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, climatewin will instead calculate an optimal climate zone.
binary	TRUE or FALSE. Determines whether to use values of upper and lower to calculate binary climate data (thresh = TRUE), or to use for growing degree days (thresh = FALSE).
centre	A list item containing: 1. The variable used for mean centring (e.g. Year, Site, Individual). Please specify the parent environment and variable name (e.g. Biol\$Year). 2. Whether the model should include both within-group means and variance ("both"), only within-group means ("mean"), or only within-group variance ("var").

cutoff.day, cutoff.month
 Redundant parameters. Now replaced by refday.

furthest, closest
 Redundant parameters. Now replaced by range.

thresh
 Redundant parameter. Now replaced by binary.

Value

Will return a list containing two objects:

- BestModel, a model object of the fitted climate window model.
- BestModelData, a dataframe with the biological and climate data used to fit the climate window model.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:
# Fit a known climate window to the datasets Mass and MassClimate

data(Mass)
data(MassClimate)

# Test for a fixed climate window, starting from 20th May
# Fit a climate window starting 72 days ago and ending 15 days ago
# Fit a linear term for the mean climate
# Fit climate windows at the resolution of days

single <- singlewin(xvar = list(Temp = MassClimate$Temp),
                   cdate = MassClimate$Date, bdate = Mass$Date,
                   baseline = lm(Mass ~ 1, data = Mass),
                   range = c(72, 15),
                   stat = "mean", func = "lin",
                   type = "absolute", refday = c(20, 5),
                   cmissing = FALSE, cinterval = "day")

##View data##
single$BestModel
head(single$BestModelData)

## End(Not run)
```

Size	<i>Average size of red winged fairy wren (Malurus elegans) chicks.</i>
------	--

Description

Average size (using standardised measures of tarsus length, head-bill length and wing length) in red winged fairy wren (*Malurus elegans*) chicks. Measured over 7 years.

Format

A data frame with 1,003 rows and 5 variables.

NestID Unique nest identifier.

Cohort Year of breeding season.

Helpers Total number of non-breeding helpers at the nest.

Size Average offspring size.

Date Date when offspring size was recorded (dd/mm/yyyy).

SizeClimate	<i>Daily climate data from 2006 to 2015.</i>
-------------	--

Description

Average, maximum and minimum daily temperature data, average rainfall data from 2006 to 2015. Coincides with biological data from [Size](#).

Format

A data frame with 3,411 rows and 5 variables.

Date Date when climate was recorded (dd/mm/yyyy).

Rain Average daily rainfall data in mm.

Temperature Average daily temperature data in degrees centigrade.

MaxTemp Maximum daily temperature in degrees centigrade.

MinTemp Minimum daily temperature in degrees centigrade.

slidingwin

Test for a climate windows in data.

Description

Finds the time period when a biological variable is most strongly affected by climate. Note that climate data and biological data should be loaded as two separate objects. Both objects should contain a date column to designate when the data were recorded (dd/mm/yyyy).

Usage

```
slidingwin(exclude = NA, xvar, cdate, bdate, baseline, type, refday,
  stat = "mean", func = "lin", range, cmissing = FALSE,
  cinterval = "day", k = 0, upper = NA, lower = NA, binary = FALSE,
  centre = list(NULL, "both"), spatial = NULL, cohort = NULL,
  cutoff.day = NULL, cutoff.month = NULL, furthest = NULL,
  closest = NULL, thresh = NULL, cvk = NULL)
```

Arguments

exclude	Two values (distance and duration) which allow users to exclude short-duration long-lag climate windows from analysis (e.g., windows with a duration of 10 days which occur over a month ago). These windows are often considered to be biologically implausible.
xvar	A list object containing all climate variables of interest. Please specify the parent environment and variable name (e.g. climate\$Temp).
cdater	The climate date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. climate\$Date).
bdate	The biological date variable (dd/mm/yyyy). Please specify the parent environment and variable name (e.g. Biol\$Date).
baseline	The baseline model structure used for model testing. Currently known to support lm, glm, lmer, glmer and coxph objects.
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is "absolute", the day and month respectively of the year from which the absolute window analysis will start.
stat	The aggregate statistics used to analyse the climate data. Can currently use basic R statistics (e.g. mean, min), as well as slope. Additional aggregate statistics can be created using the format function(x) (...). See FUN in apply for more detail.
func	The functions used to fit the climate variable. Can be linear ("lin"), quadratic ("quad"), cubic ("cub"), inverse ("inv") or log ("log").

range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the refdays or biological record to include in the climate window search.
cmissing	TRUE or FALSE, determines what should be done if there are missing climate data. If FALSE, the function will not run if missing climate data is encountered. If TRUE, any records affected by missing climate data will be removed from climate window analysis.
cinterval	The resolution at which climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ depending on the choice of cinterval.
k	The number of folds used for k-fold cross validation. By default this value is set to 0, so no cross validation occurs. Value should be a minimum of 2 for cross validation to occur.
upper	Cut-off values used to determine growing degree days or positive climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, slidingwin will instead calculate an optimal climate zone.
lower	Cut-off values used to determine chill days or negative climate thresholds (depending on parameter thresh). Note that when values of lower and upper are both provided, slidingwin will instead calculate an optimal climate zone.
binary	TRUE or FALSE. Determines whether to use values of upper and lower to calculate binary climate data (binary = TRUE), or to use for growing degree days (binary = FALSE).
centre	A list item containing: 1. The variable used for mean centring (e.g. Year, Site, Individual). Please specify the parent environment and variable name (e.g. Biol\$Year). 2. Whether the model should include both within-group means and variance ("both"), only within-group means ("mean"), or only within-group variance ("var").
spatial	A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. This length of this factor should correspond to the length of the climate dataset.
cohort	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). Only required when type is "absolute". The cohort variable should be in the same dataset as the variable bdate.
cutoff.day, cutoff.month	Redundant parameters. Now replaced by refdays.
furthest, closest	Redundant parameters. Now replaced by range.
thresh	Redundant parameter. Now replaced by binary.
cvk	Redundant parameter. Now replaced by k.

Details

Note that slidingwin allows you to test multiple possible parameters with the same code (e.g. func, stat, xvar). See examples for more detail.

Value

Will return a list with an output for each tested set of climate window parameters. Each list item contains three objects:

- BestModel, a model object. The strongest climate window model based on AICc.
- BestModelData, a dataframe used to fit the strongest climate window model.
- Dataset, a dataframe with information on all fitted climate windows. Ordered using deltaAICc, with most negative deltaAICc values first. See [MassOutput](#) as an example.

In addition, the returned list includes an object 'combos', a summary of all tested sets of climate window parameters.

Author(s)

Liam D. Bailey and Martijn van de Pol

Examples

```
## Not run:
##EXAMPLE 1##

# Test both a linear and quadratic variable climate window using datasets "Offspring"
# and "OffspringClimate".

# Load data.

data(Offspring)
data(OffspringClimate)

# Test both linear and quadratic functions with climate variable temperature

OffspringWin <- slidingwin(xvar = list(Temp = OffspringClimate$Temperature),
                          cdate = OffspringClimate$Date,
                          bdate = Offspring$Date,
                          baseline = glm(Offspring ~ 1, data = Offspring, family = poisson),
                          range = c(150, 0),
                          type = "relative", stat = "mean",
                          func = c("lin", "quad"), cmissing = FALSE, cinterval = "day")

# Examine tested combinations

OffspringWin$combos

# View output for func = "lin"

head(OffspringWin[[1]]$Dataset)
summary(OffspringWin[[1]]$BestModel)

# View output for func = "quad"

head(OffspringWin[[2]]$Dataset)
```

```

summary(OffspringWin[[2]]$BestModel)

##EXAMPLE 2##

# Test for an absolute climate window with both 'mean' and 'max' aggregate statistics
# using datasets 'Mass' and 'MassClimate'.

# Load data.

data(Mass)
data(MassClimate)

# Test an absolute window, starting 20 May (refday = c(20, 5))
# Test for climate windows between 100 and 0 days ago (range = c(100, 0))
# Test both mean and max aggregate statistics (stat = c("mean", "max"))
# Fit a linear term (func = "lin")
# Test at the resolution of days (cinterval = "day")

MassWin <- slidingwin(xvar = list(Temp = MassClimate$Temp), cdate = MassClimate$Date,
                      bdate = Mass$Date, baseline = lm(Mass ~ 1, data = Mass),
                      range = c(100, 0),
                      stat = c("mean", "max"), func = "lin",
                      type = "absolute", refday = c(20, 5),
                      cmissing = FALSE, cinterval = "day")

# Examine tested combinations

MassWin$combos

# View output for mean temperature

head(MassWin[[1]]$Dataset)
summary(MassWin[[1]]$BestModel)

# View output for max temperature

head(MassWin[[2]]$Dataset)
summary(MassWin[[2]]$BestModel)

## End(Not run)

```

weightwin

Find a weighted climate window

Description

Finds the best weighted average of a weather variable over a period that correlates most strongly with a biological variable. Uses weibull or Generalised Extreme Value (GEV) distribution. See references for a full description.

Usage

```
weightwin(xvar, cdate, bdate, baseline, range, func = "lin", type, refday,
  nrandom = 0, centre = NULL, weightfunc = "W", cinterval = "day",
  cohort = NULL, spatial = NULL, par = c(3, 0.2, 0),
  control = list(ndepts = c(0.001, 0.001, 0.001)), method = "L-BFGS-B",
  cutoff.day = NULL, cutoff.month = NULL, furthest = NULL,
  closest = NULL)
```

Arguments

xvar	A list object containing all climate variables of interest. Please specify the parent environment and variable name (e.g. Climate\$Temp).
cdater	The climate date variable. Please specify the parent environment and variable name (e.g. Climate\$Date).
bdate	The biological date variable. Please specify the parent environment and variable name (e.g. Biol\$Date).
baseline	The baseline model structure used for testing correlation. Currently known to support lm, lme, glm and glmer objects.
range	Two values signifying respectively the furthest and closest number of time intervals (set by cinterval) back from the cutoff date or biological record to include in the climate window search.
func	The function used to fit the climate variable in the model. Can be linear ("lin"), quadratic ("quad"), cubic ("cub"), inverse ("inv") or log ("log").
type	"absolute" or "relative", whether you wish the climate window to be relative (e.g. the number of days before each biological record is measured) or absolute (e.g. number of days before a set point in time).
refday	If type is absolute, the day and month respectively of the year from which the absolute window analysis will start.
nrandom	Used when conducting data randomisation, should not be changed manually.
centre	A list item containing: 1. The variable used for mean centring (e.g. Year, Site, Individual). Please specify the parent environment and variable name (e.g. Biol\$Year). 2. Whether the model should include both within-group means and variance ("both"), only within-group means ("mean"), or only within-group variance ("var").
weightfunc	The distribution to be used for optimisation. Can be either a Weibull ("W") or Generalised Extreme Value distribution ("G").
cinterval	The resolution at which the climate window analysis will be conducted. May be days ("day"), weeks ("week"), or months ("month"). Note the units of parameter 'range' will differ depending on the choice of cinterval.
cohort	A variable used to group biological records that occur in the same biological season but cover multiple years (e.g. southern hemisphere breeding season). Only required when type is "absolute". The cohort variable should be in the same dataset as the variable bdate.

spatial	A list item containing: 1. A factor that defines which spatial group (i.e. population) each biological record is taken from. The length of this factor should correspond to the length of the biological dataset. 2. A factor that defines which spatial group (i.e. population) climate data corresponds to. This length of this factor should correspond to the length of the climate dataset.
par	Shape, scale and location parameters of the Weibull or GEV weight function used as start weight function. For Weibull : Shape and scale parameters must be greater than 0, while location parameter must be less than or equal to 0. For GEV : Scale parameter must be greater than 0.
control	Parameters used to determine step size for the optimisation function. Please see optim for more detail.
method	The method used for the optimisation function. Please see optim for more detail.
cutoff.day, cutoff.month	Redundant parameters. Now replaced by refday.
furthest, closest	Redundant parameters. Now replaced by range.

Value

Produces a constantly updating grid of plots as the optimisation function is running.

- Right panel from top to bottom: The three parameters (shape, scale and location) determining the weight function.
- Left top panel: The resulting weight function.
- Right middle panel: The delta AICc compared to the baseline model.
- Right bottom panel: The weighted mean of climate for the current weight function.

Also returns a list containing three objects:

- BestModel, a model object. The best weighted window model determined by deltaAICc.
- BestModelData, a dataframe. Biological and climate data used to fit the best weighted window model.
- WeightedOutput. Parameter values for the best weighted window.

Author(s)

Martijn van de Pol and Liam D. Bailey

References

van de Pol & Cockburn 2011 Am Nat 177(5):698-707 (doi: 10.1086/659101) "Identifying the critical climatic time window that affects trait expression"

Examples

```
## Not run:

# Test for a weighted average over a fixed climate window
# using datasets 'Offspring' and 'OffspringClimate'

# N.B. THIS EXAMPLE MAY TAKE A MOMENT TO CONVERGE ON THE BEST MODEL.

# Load data

data(Offspring)
data(OffspringClimate)

# Test for climate windows between 365 and 0 days ago (range = c(365, 0))
# Fit a quadratic term for the mean weighted climate (func="quad")
# in a Poisson regression (offspring number ranges 0-3)
# Test a variable window (type = "absolute")
# Test at the resolution of days (cinterval="day")
# Uses a Weibull weight function (weightfunc="week")

weight <- weightwin(xvar = list(Temp = OffspringClimate$Temperature),
                    cdate = OffspringClimate$Date,
                    bdate = Offspring$Date,
                    baseline = glm(Offspring ~ 1, family = poisson, data = Offspring),
                    range = c(365, 0), func = "quad",
                    type = "relative", weightfunc = "W", cinterval = "day",
                    par = c(3, 0.2, 0), control = list(ndepts = c(0.01, 0.01, 0.01)),
                    method = "L-BFGS-B")

# View output

head(weight[[3]])
summary(weight[[1]])
head(weight[[2]])

## End(Not run)
```

Index

apply, [3](#), [6](#), [22](#), [26](#), [29](#)
autowin, [2](#), [16](#)

Chaff, [5](#), [5](#)
ChaffClim, [5](#)
crosswin, [6](#), [16](#)

explore, [8](#)

Mass, [9](#), [9](#), [10](#)
MassClimate, [9](#), [9](#), [10](#)
MassOutput, [9](#), [31](#)
MassRand, [10](#), [24](#)
medwin, [11](#)

Offspring, [12](#), [12](#)
OffspringClimate, [12](#)
optim, [24](#), [34](#)

plotall, [13](#), [16](#), [18](#), [19](#)
plotbest, [14](#)
plotbetas, [15](#)
plotcor, [16](#)
plotdelta, [17](#)
plothist, [18](#)
plotweights, [13](#), [19](#)
plotwin, [20](#)
pvalue, [13](#), [21](#)

randwin, [10](#), [11](#), [13](#), [18](#), [21](#), [22](#)

singlewin, [2](#), [13](#), [15](#), [25](#)
Size, [28](#), [28](#)
SizeClimate, [28](#)
slidingwin, [2](#), [9–11](#), [13](#), [15](#), [16](#), [18–21](#), [29](#)

weightwin, [8](#), [32](#)