

Package ‘groc’

May 7, 2015

Version 1.0.5

Date 2015-05-07

Title Generalized Regression on Orthogonal Components

Author M. Bilodeau and P. Lafaye de Micheaux

Maintainer P. Lafaye de Micheaux <lafaye@dms.umontreal.ca>

Imports pls, mgcv, robust, robustbase, MASS

Depends rrcov

Suggests pppls

Description Robust multiple or multivariate linear regression, nonparametric regression on orthogonal components, classical or robust partial least squares models.

License GPL (>= 2)

LazyLoad yes

NeedsCompilation yes

Repository CRAN

Date/Publication 2015-05-07 22:26:57

R topics documented:

corrob	2
covrob	3
dcov	4
groc	5
groc.fit	11
grocCrossval	12
model.frame.groc	14
plot.groc	15
predict.groc	16
prim7	17
summary.groc	18

Index	20
--------------	-----------

`corrob`*Robust correlation measure*

Description

Compute robust estimates of the correlation between two variables using the Orthogonalized Gnanadesikan-Kettenring pairwise estimator.

Usage

```
corrob(t, u)
```

Arguments

`t` a numeric vector containing the data for the first variable.
`u` a numeric vector containing the data for the second variable.

Details

This function uses the `covRob` function from the **robust** package.

Value

Value of the robust correlation.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Jiahui Wang, Ruben Zamar, Alfio Marazzi, Victor Yohai, Matias Salibian-Barrera, Ricardo Maronna, Eric Zivot, David Rocke, Doug Martin, Martin Maechler and Kjell Konis. (2013). `robust`: Robust Library. R package version 0.4-11. <http://CRAN.R-project.org/package=robust>

See Also

[covrob](#), [dcov](#)

Examples

```
data(stackloss)
corrob(stackloss$Air.Flow, stackloss$Water.Temp)
```

covrob	<i>Robust covariance measure</i>
--------	----------------------------------

Description

Compute robust estimates of the covariance between two variables using the robust tau estimate of univariate scale, as proposed by Maronna and Zamar (2002).

Usage

```
covrob(t, u)
```

Arguments

t a numeric vector containing the data for the first variable.
u a numeric vector containing the data for the second variable.

Details

This function uses the [scaleTau2](#) function from the **robustbase** package.

Value

Value of the robust covariance.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Maronna, R.A. and Zamar, R.H. (2002) Robust estimates of location and dispersion of high-dimensional datasets; *Technometrics* **44**(4), 307–317.

See Also

[corrob](#), [dcov](#)

Examples

```
data(stackloss)  
covrob(stackloss$Air.Flow, stackloss$Water.Temp)
```

dcov *Distance covariance matrix.*

Description

Compute the distance covariance measure of Szekely, Rizzo, and Bakirov (2007) between two samples. Warning: Only valid to compute the distance covariance for two random variables X and Y. This means that X and Y cannot be random Vectors. If this is the case, consider the package **energy**.

Usage

```
dcov(x, y, Cpp = TRUE)
```

Arguments

x	data of first sample
y	data of second sample
Cpp	logical. If TRUE (the default), computations are performed using a C version of the code.

Details

See **energy**.

Value

returns the sample distance covariance.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Szekely, G.J., Rizzo, M.L., and Bakirov, N.K. (2007), Measuring and Testing Dependence by Correlation of Distances, *Annals of Statistics*, Vol. 35 No. 6, pp. 2769-2794.
<http://dx.doi.org/10.1214/009053607000000505>

See Also

[covrob](#), [corrob](#)

Examples

```
data(stackloss)
dcov(stackloss$Air.Flow, stackloss$Water.Temp)
```

groc *groc method*

Description

Generalized regression on orthogonal components.

Usage

```
## Default S3 method:
groc(formula, ncomp, data, subset, na.action, plsrob =
      FALSE, method = c("lm", "lo", "s", "lts"), D = NULL,
      gamma = 0.75, Nc = 10, Ng = 20, scale = FALSE, Cpp =
      TRUE, model = TRUE, x = FALSE, y = FALSE, sp = NULL, ...)

groc(...)
```

Arguments

formula	a model formula. Most of the <code>lm</code> formula constructs are supported. See below.
ncomp	the number of components (orthogonal components) to include in the model.
data	an optional data frame with the data to fit the model from.
subset	an optional vector specifying a subset of observations to be used in the fitting process.
na.action	a function which indicates what should happen when the data contain missing values.
plsrob	logical. If TRUE, we use the <code>D=covrob</code> measure of dependence with the least trimmed squares <code>method="lts"</code> .
method	character giving the name of the method to use. The user can supply his own function. The methods available are linear models, "lm", local polynomials, "lo", smoothing splines, "s", and least trimmed squares, "lts".
D	function with two arguments, each one being a vector, which measures the dependence between two variables using <code>n</code> observations from them. If NULL, the covariance measure will be used. The user can supply his own function.
gamma	parameter used with the option <code>plsrob=TRUE</code> . It defines the quantile used to compute the "lts" regression. The default <code>gamma=0.75</code> gives a breakdown of 25% for a good compromise between robustness and efficiency. The value <code>gamma=0.5</code> gives the maximal breakdown of 50%.
Nc	Integer, Number of cycles in the grid algorithm.
Ng	Integer, Number of points for the grid in the grid algorithm.
scale	Logical, Should we scale the data.
Cpp	Logical, if TRUE this function will use a C++ implementation of the grid algorithm. The FALSE value should not be used, unless to get a better understanding of the grid algorithm or to compare the speed of computation between R and C++ versions of this algorithm

<code>model</code>	a logical. If TRUE, the model frame is returned.
<code>x</code>	a logical. If TRUE, the model matrix is returned.
<code>y</code>	a logical. If TRUE, the response is returned.
<code>sp</code>	A vector of smoothing parameters can be provided here. Smoothing parameters must be supplied in the order that the smooth terms appear in the model formula. Negative elements indicate that the parameter should be estimated, and hence a mixture of fixed and estimated parameters is possible. <code>'length(sp)'</code> should be equal to <code>'ncomp'</code> and corresponds to the number of underlying smoothing parameters.
<code>...</code>	further arguments to be passed to or from methods.

Value

<code>Y</code>	vector or matrix of responses.
<code>fitted.values</code>	an array of fitted values.
<code>residuals</code>	residuals
<code>T</code>	a matrix of orthogonal components (scores). Each column corresponds to a component.
<code>R</code>	a matrix of directions (loadings). Each column is a direction used to obtain the corresponding component (scores).
<code>Gobjects</code>	contain the objects produced by the fit of the responses on the orthogonal components.
<code>Hobjects</code>	contain the objects produced by the "lts" fit of each deflated predictors on the orthogonal components. <code>Hobjects</code> are produced when <code>plsrob=TRUE</code> .
<code>B</code>	matrix of coefficients produced by the "lm" fit of each deflated predictors on the last component. <code>B</code> is produced when <code>plsrob=FALSE</code> .
<code>Xmeans</code>	a vector of means of the X variables.
<code>Ymeans</code>	a vector of means of the Y variables.
<code>D</code>	Dependence measure used.
<code>V</code>	a matrix whose columns contain the right singular vectors of the data. Computed in the preprocessing to principal component scores when the number of observations is less than the number of predictors.
<code>dimnames</code>	<code>dimnames</code> of <code>'fitted.values'</code>
<code>ncomp</code>	the number of components used in the modelling.
<code>method</code>	the method used.
<code>scale</code>	Logical. TRUE if the responses have been scaled.
<code>call</code>	the function call.
<code>terms</code>	the model terms.
<code>plsrob</code>	Logical. If <code>plsrob=TRUE</code> , a robust partial least squares fit.
<code>model</code>	if <code>model=TRUE</code> , the model frame.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>) and Smail Mahdi (<smail.mahdi@cavehill.uwi.edu>)

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

Examples

```
## Not run:
#####
# Codes for Example 1 #
#####
require("groc")
data("wood")
out <- groc(y ~ x1 + x2 + x3 + x4 + x5, ncomp = 1, data = wood,
           D = corrob, method = "lts")
corrob(wood$y, fitted(out)) ^ 2
plot(out)

#####
# Codes for Example 2 #
#####
data("trees")
out <- groc(Volume ~ Height + Girth, ncomp = 1, D = spearman,
           method = "s", data = trees)
cor(trees$Volume, fitted(out)) ^ 2
plot(out$T, trees$Volume, xlab = "First latent variable",
     ylab = "Volume", pch = 20)
lines(sort(out$T), fitted(out)[order(out$T)])
out <- boxcox(Volume ~ Height + Girth, data = trees,
             lambda = seq(-0.5, 0.5, length = 100), plotit = FALSE)
lambda <- out$x[which.max(out$y)]
out <- lm(Volume ^ lambda ~ Height + Girth, data = trees)
cor(trees$Volume, fitted(out)^(1/lambda)) ^ 2

#####
# Codes for Example 3 #
#####
data("wood")
plsr.out <- plsr(y ~ x1 + x2 + x3 + x4 + x5, data = wood)
groc.out <- groc(y ~ x1 + x2 + x3 + x4 + x5, data = wood)
apply(abs((fitted(plsr.out) - fitted(groc.out)) /
         fitted(plsr.out)), 3, max) * 100

#####
# Codes for Example 4 #
#####
```

```

set.seed(1)
n <- 200
x1 <- runif(n, -1, 1)
x2 <- runif(n, -1, 1)
y <- x1 * x2 + rnorm(n, 0, sqrt(.04))
data <- data.frame(x1 = x1, x2 = x2, y = y)
plsr.out <- plsr(y ~ x1 + x2, data = data)
groc.out <- groc(y ~ x1 + x2, D = dcov, method = "s", data = data)
plsr.v <- crossval(plsr.out, segment.type = "consecutive")
groc.v <- grocCrossval(groc.out, segment.type = "consecutive")
groc.v$validation$PRESS
plsr.v$validation$PRESS
gam.data <- data.frame(y = y, t1 = groc.out$T[, 1], t2 = groc.out$T[, 2])
gam.out <- gam(y ~ s(t1) + s(t2), data = gam.data)
par(mfrow = c(1, 2))
plot(gam.out)
par(mfrow = c(1, 1))
PRESS <- 0
for(i in 1 : 10){
  data.in <- data[-(((i - 1) * 20 + 1) : (i * 20)), ]
  data.out <- data[(((i - 1) * 20 + 1) : (i * 20)), ]
  ppr.out <- ppr(y ~ x1 + x2, nterms = 2, optlevel = 3, data = data.in)
  PRESS <- PRESS + sum((predict(ppr.out, newdata = data.out)-data.out$y) ^ 2)
}
PRESS

#####
# Codes for Example 5 #
#####
data("yarn")
dim(yarn$NIR)
n <- nrow(yarn)
system.time(plsr.out <- plsr(density ~ NIR, ncomp = n - 2, data = yarn))
system.time(groc.out <- groc(density ~ NIR, Nc = 20, ncomp = n - 2, data = yarn))
max(abs((fitted(plsr.out) - fitted(groc.out)) / fitted(plsr.out))) * 100
plsr.v <- crossval(plsr.out, segments = n, trace = FALSE)
plsr.v$validation$PRESS
groc.v <- grocCrossval(groc.out, segments = n, trace = FALSE)
groc.v$validation$PRESS
groc.v$validation$PREMAD

#####
# Codes for Example 6 #
#####
data("prim7")
prim7.out <- groc(X1 ~ ., ncomp = 3, D = dcov, method = "s", data = prim7)
prim7.out$R
pca <- princomp(~ ., data = as.data.frame(prim7[, -1]))
prim7.pca <- data.frame(X1 = prim7$X1, scores = pca$scores)
prim7.pca.out <- groc(X1 ~ ., ncomp = 3, D = dcov, method = "s",
  data = prim7.pca)

pca$loadings
groc.v <- grocCrossval(prim7.out, segment.type = "consecutive")

```



```

groc.v$validation$PRESS
plsr.out <- plsr(X1 ~ ., ncomp = 3, data = prim7)
plsr.v <- crossval(plsr.out, segment.type = "consecutive")
plsr.v$validation$PRESS
PRESS <- 0
for(i in 1 : 10){
  data.in <- prim7[-(((i - 1) * 50 + 1) : (i * 50)), ]
  data.out <- prim7[(((i - 1) * 50 + 1) : (i * 50)), ]
  ppr.out <- ppr(X1 ~ ., nterms = 3, optlevel = 3, data = data.in)
  PRESS <- PRESS + sum((predict(ppr.out, newdata = data.out) - data.out$X1) ^ 2)
}
PRESS

#####
# Codes for Example 7 #
#####
n <- 50 ; B <- 30
mat.cor <- matrix(0, nrow = B, ncol = 3) ; mat.time <- matrix(0, nrow = B, ncol = 3)
for (i in 1:B) {
  X <- matrix(runif(n * 5, -1, 1), ncol = 5)
  A <- matrix(runif(n * 50, -1, 1), nrow = 5)
  y <- (X[,1] + X[,2])^2 + (X[,1] + 5 * X[,2])^2 + rnorm(n)
  X <- cbind(X, X)
  D <- data.frame(X = X, y = y)
  mat.time[i,1] <- system.time(out1 <- plsr(y ~ X, , ncomp = 2, data = D))[1]
  mat.time[i,2] <- system.time(out2 <- ppr(y ~ X, , nterms = 2, data = D))[1]
  mat.time[i,3] <- system.time(out3 <- groc(y ~ X, D = dcov, method = "s", ncomp = 2, data = D))[1]
  mat.cor[i,] <- cor(y, cbind(fitted(out1)[,2], fitted(out2), fitted(out3)[,2]))
}
colMeans(mat.cor)
colMeans(mat.time)

#####
# Codes for Example 8 #
#####
data("oliveoil")
n <- nrow(oliveoil)
plsr.out <- plsr(sensory ~ chemical, data = oliveoil, method = "simpls")
groc.out <- groc(sensory ~ chemical, data = oliveoil)
max(abs((fitted(plsr.out) - fitted(groc.out)) / fitted(plsr.out))) * 100
groc.v <- grocCrossval(groc.out, segments = n)
groc.v$validation$PRESS
colMeans(groc.v$validation$PRESS)
Y <- oliveoil$sensory
for (j in 1 : ncol(Y)) print(cor(Y[, j], fitted(groc.out)[, j, 2]))

#####
# Codes for Example 9 #
#####
require("ppls")
data("cookie")
X <- as.matrix(log(cookie[1 : 40, 51 : 65]))
Y <- as.matrix(cookie[1 : 40, 701 : 704])

```

```

X <- X[, 2 : 601] - X[, 1 : 600]
data <- data.frame(Y = I(Y), X = I(X))
n <- nrow(data)
q <- ncol(Y)
x1 <- "Wavelength index"
y1 <- "First differences of log(1/reflectance)"
matplot(1:ncol(X), t(X), lty = 1, xlab = x1, ylab = y1, type = "l")
out1 <- plsr(Y ~ X, ncomp = n - 2, data = data)
cv <- crossval(out1, segments = n)
cv.mean <- colMeans(cv$validation$PRESS)
plot(cv.mean, xlab = "h", ylab = "Average PRESS", pch = 20)
h <- 3
for (j in 1 : q) print(cor(Y[, j], fitted(out1)[, j, h]))
set.seed(1)
out2 <- groc(Y ~ X, ncomp = h, data = data, plsrob = TRUE)
for (j in 1 : q) print(corrob(Y[, j], fitted(out2)[, j, h]))
plot(out2)

#####
# Codes for Example 10 #
#####
set.seed(2)
n <- 30
t1 <- sort(runif(n, -1, 1))
y <- t1 + rnorm(n, mean = 0, sd = .05)
y[c(14, 15, 16)] <- y[c(14, 15, 16)] + .5
data <- data.frame(x1 = t1, x2 = 2 * t1, x3 = -1.5 * t1, y = y)
out <- groc(y ~ x1 + x2 + x3, ncomp = 1, data = data, plsrob = TRUE)
tau <- scaleTau2(residuals(out), mu.too = TRUE)
std.res <- scale(residuals(out), center = tau[1], scale = tau[2])
index <- which(abs(std.res)>3)
prm.res <- read.table("prmresid.txt")
plot(t1, y, pch = 20)
matlines(t1, cbind(t1, fitted(out), y - prm.res), lty = 1 : 3)
legend(.4, -.5, legend = c("true model", "groc", "prm"), lty = 1 : 3)
text(t1[index], y[index], index, cex = .8, pos = 3)

#####
# Codes for Example 11 #
#####
data("pulpfiber")
X <- as.matrix(pulpfiber[, 1:4])
Y <- as.matrix(pulpfiber[, 5:8])
data <- data.frame(X = I(X), Y = I(Y))
set.seed(55481)
out.rob <- groc(Y ~ X, data = data, plsrob = TRUE)
plot(out.rob, cex = .6)
out.simpls <- groc(Y ~ X, data = data)
cv.rob <- grocCrossval(out.rob, segment.type = "consecutive")
PREMAD.rob <- cv.rob$validation$PREMAD[,4]
PREMAD.rob
cv.simpls <- grocCrossval(out.simpls, segment.type = "consecutive")
PREMAD.simpls <- cv.simpls$validation$PREMAD[,4]

```

```

PREMAD.simpls
(PREMAD.rob - PREMAD.simpls) / PREMAD.simpls * 100

## End(Not run)

```

groc.fit

*Fitting a groc model***Description**

Fits a groc model with the grid algorithm.

Usage

```

groc.fit(X, Y, ncomp = min(nrow(X) - 1, ncol(X)), D = NULL, gamma =
  0.75, method = NULL, plsrob = FALSE, Nc = 10, Ng = 20,
  scale = FALSE, Cpp = TRUE, stripped = FALSE, maxiter =
  100, sp = NULL, ...)

```

Arguments

X	a matrix of predictors. NAs and Infs are not allowed.
Y	a vector or matrix of responses. NAs and Infs are not allowed.
ncomp	the number of components to be used in the modelling.
D	Dependence measure.
gamma	Used to set the breakdown value when method="lts".
method	the method to be used. Currently only 'lm', 'lo', 's', and 'lts'.
plsrob	Logical. If TRUE, the function sets D=covrov and method="lts" for a robust partial least squares fit.
Nc	Integer. Number of cycles in the grid algorithm
Ng	Integer. Number of points for the grid in the grid algorithm.
scale	Logical. If TRUE the responses are scaled.
Cpp	Logical. If TRUE, computations are performed in a faster way using a C code.
stripped	logical. If TRUE the calculations are stripped as much as possible for speed; this is meant for use with cross-validation or simulations when only the coefficients are needed. Defaults to FALSE.
maxiter	Integer. Maximal number of iterations in the grid algorithm. Used only when there are more than one response.
sp	A vector of smoothing parameters can be provided here. Smoothing parameters must be supplied in the order that the smooth terms appear in the model formula. Negative elements indicate that the parameter should be estimated, and hence a mixture of fixed and estimated parameters is possible. 'length(sp)' should be equal to 'ncomp' and corresponds to the number of underlying smoothing parameters.
...	other arguments. Currently ignored.

Value

Y	data used as response.
fitted.values	an array of fitted values. Its element [i,j,k] is the fitted value for observation i, response j, and when k components are used.
residuals	an array of regression residuals. It has the same dimensions as fitted.values.
T	a matrix of orthogonal components (scores). Each column corresponds to a component.
R	a matrix of directions (loadings). Each column is a direction used to obtain the corresponding component (scores).
Gobjects	contain the objects produced by the fit of the responses on the orthogonal components.
Hobjects	contain the objects produced by the "lts" fit of each deflated predictors on the orthogonal components. Hobjects are produced when plsrob=TRUE.
B	matrix of coefficients produced by the "lm" fit of each deflated predictors on the last component. B is produced when plsrob=FALSE.
Xmeans	a vector of means of the X variables.
Ymeans	a vector of means of the Y variables.
D	Dependence measure used.
V	a matrix whose columns contain the right singular vectors of the data. Computed in the preprocessing to principal component scores when the number of observations is less than the number of predictors.
dimnames	dimnames of 'fitted.values'

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

grocCrossval

Cross-validation of groc models

Description

A “stand alone” cross-validation function for groc objects.

Usage

```
grocCrossval(object, segments = 10, segment.type = c("random",
"consecutive","interleaved"), length.seg, trace = 15, ...)
```

Arguments

object	a groc object; the regression to cross-validate.
segments	the number of segments to use, or a list with segments (see below).
segment.type	the type of segments to use.
length.seg	Positive integer. The length of the segments to use.
trace	if TRUE, tracing is turned on. If numeric, it denotes a time limit (in seconds). If the estimated total time of the cross-validation exceeds this limit, tracing is turned on.
...	additional arguments, sent to the underlying fit function.

Details

This function performs cross-validation on a model fit by `groc`. It can handle models such as `groc(Y ~ X, ...)`.

Note that to use `grocCrossval`, the data *must* be specified with a `data` argument when fitting object.

If `segments` is a list, the arguments `segment.type` and `length.seg` are ignored. The elements of the list should be integer vectors specifying the indices of the segments.

Otherwise, segments of type `segment.type` are generated. How many segments to generate is selected by specifying the number of segments in `segments`, or giving the segment length in `length.seg`. If both are specified, `segments` is ignored.

When tracing is turned on, the segment number is printed for each segment.

Value

The supplied object is returned, with an additional component `validation`, which is a list with components

method	equals "CV" for cross-validation.
pred	an array with the cross-validated predictions.
PRESS	a matrix of PRESS values for models with 1, ..., <code>ncomp</code> components. Each row corresponds to one response variable.
PREMAD	a matrix of PREMAD values for models with 1, ..., <code>ncomp</code> components. Each row corresponds to one response variable.
RMSEP	a matrix of $\sqrt{\text{PRESS}/\text{nobj}}$ values for models with 1, ..., <code>ncomp</code> components. Each row corresponds to one response variable.
segments	the list of segments used in the cross-validation.
ncomp	the number of components.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

Examples

```
data(yarn,package="pls")
yarn.groc <- groc(density ~ NIR, 6, data = yarn)
yarn.cv <- grocCrossval(yarn.groc, segments = 10)

yarn.cv$validation$PRESS
yarn.cv$validation$PREMAD
```

model.frame.groc

Extract Information From a Fitted groc Model

Description

Functions to extract information from groc objects: the model frame, the model matrix.

Usage

```
## S3 method for class 'groc'
model.matrix(object, ...)
## S3 method for class 'groc'
model.frame(formula, ...)
```

Arguments

object, formula a groc object. The fitted model.

... other arguments sent to underlying functions.

Details

model.frame.groc returns the model frame; i.e. a data frame with all variables necessary to generate the model matrix. See [model.frame](#) for details.

model.matrix.groc returns the (possibly coded) matrix used as X in the fitting. See [model.matrix](#) for details.

Value

model.frame.groc returns a data frame with all variables necessary to generate the model matrix.

model.matrix.groc returns the X matrix.

Author(s)

Ron Wehrens and Bjørn-Helge Mevik

See Also

[coef](#), [fitted](#), [residuals](#), [model.frame](#)

plot.groc

Plot groc objects.

Description

A function to plot groc objects.

Usage

```
## S3 method for class 'groc'  
plot(x, h=x$ncomp, cex=0.8, ...)
```

Arguments

x	A groc object.
h	Number of components in the model.
cex	Character expansion factor for point labels.
...	Further arguments passed to internal plot function.

Details

If `plsrrob=FALSE`, a plot of robust Mahalanobis distances for residuals versus robust Mahalanobis distances for components. Useful for identification of good points, vertical outliers, good and bad leverage points.

If `plsrrob=TRUE`, the previous plot is done with another similar plot of classical Mahalanobis distances to compare the identification of the various type of points obtained by classical or robust partial least squares.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

Examples

```
## This example takes some time:
## Not run:
data("pulpfiber",package="robustbase")
X <- as.matrix(pulpfiber[, 1:4])
Y <- as.matrix(pulpfiber[, 5:8])
data <- data.frame(X=I(X), Y=I(Y))
set.seed(55481)
out.rob <- groc(Y ~ X, data=data, plsrob=TRUE)
plot(out.rob, cex=.6)

## End(Not run)
```

predict.groc

Predict Method for groc

Description

Prediction for groc models. New responses or scores are predicted using a fitted model and a new matrix of observations.

Usage

```
## S3 method for class 'groc'
predict(object, newdata, ncomp = object$ncomp, na.action = na.pass, ...)
```

Arguments

object	a groc object. The fitted model
newdata	a data frame. The new data. If missing, the training data is used.
ncomp	vector of positive integers. The components to use in the prediction.
na.action	function determining what should be done with missing values in newdata. By default, nothing is done.
...	further arguments. Currently not used

Value

A three dimensional array of predicted response values is returned. The dimensions correspond to the observations, the response variables and the model sizes, respectively.

Author(s)

Martin Bilodeau (<bilodeau@dms.umontreal.ca>) and Pierre Lafaye de Micheaux (<lafaye@dms.umontreal.ca>)

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

See Also

[plot.groc](#)

Examples

```
data("wood", package="robustbase")
out <- groc(y ~ x1+x2+x3+x4+x5, ncomp=1, data=wood, D=corrob, method="lts")
predict(out)

newdata<- data.frame(x1= 0.5, x2=0.1, x3=0.4, x4=0.5, x5=0.8)
predict(out, newdata)
```

prim7

prim7 Dataset

Description

The data prim7 is a particle physics experiment analyzed by projection pursuit regression in Friedman and Stuetzle (1981). It has 7 variables on 500 observations. The data set is described in Friedman and Tukey (1974).

Format

This data frame contains the following columns:

- X1** First variable.
- X2** Second variable.
- X3** Third variable.
- X4** Fourth variable.
- X5** Fifth variable.
- X6** Sixth variable.
- X7** Seventh variable.

References

Friedman and Tukey (1974), A Projection Pursuit Algorithm for Exploratory Data Analysis, *IEEE Transactions on Computers* (Volume:C-23, Issue: 9)

Friedman, Jerome H.; Stuetzle, Werner (1981), Projection pursuit regression. *J. Amer. Statist. Assoc.* 76, no. 376, 817–823.

Examples

```
data(prim7)
```

summary.groc

Summary and Print Methods for groc objects

Description

Summary and print methods for groc objects.

Usage

```
## S3 method for class 'groc'  
summary(object, what = "validation",  
         digits = 4, print.gap = 2, ...)  
## S3 method for class 'groc'  
print(x, ...)
```

Arguments

x, object	a groc object
what	character, only "validation" for the moment
digits	integer. Minimum number of significant digits in the output. Default is 4.
print.gap	Integer. Gap between coloumns of the printed tables.
...	Other arguments sent to underlying methods.

Details

If what is "validation", the cross-validated PRESS, RPEMAD and RMSEPs (if available) are given.

Value

print.groc return the object invisibly.

Author(s)

P. Lafaye de Micheaux

References

Martin Bilodeau, Pierre Lafaye de Micheaux, Smail Mahdi (2015), The R Package groc for Generalized Regression on Orthogonal Components, *Journal of Statistical Software*, 65(1), 1-29, <http://www.jstatsoft.org/v65/i01/>

See Also

[groc](#), [grocCrossval](#)

Examples

```
data("yarn",package="pls")
yarn.groc <- groc(density ~ NIR, 6, data = yarn)
yarn.cv <- grocCrossval(yarn.groc, segments = 10)
print(yarn.groc)
summary(yarn.cv)
```

Index

- *Topic **datasets**
 - prim7, 17
- *Topic **distribution**
 - groc, 5
- *Topic **htest**
 - groc, 5
- *Topic **multivariate**
 - dcov, 4
 - groc.fit, 11
 - grocCrossval, 12
 - model.frame.groc, 14
 - plot.groc, 15
 - predict.groc, 16
 - summary.groc, 18
- *Topic **regresion**
 - plot.groc, 15
- *Topic **regression**
 - groc.fit, 11
 - grocCrossval, 12
 - model.frame.groc, 14
 - predict.groc, 16
 - summary.groc, 18
- *Topic **robust**
 - corrob, 2
 - covrob, 3

coef, 15

corrob, 2, 3, 4

covRob, 2

covrob, 2, 3, 4

dcov, 2, 3, 4

fitted, 15

groc, 5, 19

groc.fit, 11

grocCrossval, 12, 19

model.frame, 14, 15

model.frame.groc, 14

model.matrix, 14

model.matrix.groc (model.frame.groc), 14

plot.groc, 15, 17

predict.groc, 16

prim7, 17

print.groc (summary.groc), 18

residuals, 15

scaleTau2, 3

summary.groc, 18