

Package ‘smoof’

August 3, 2016

Type Package

Title Single and Multi-Objective Optimization Test Functions

Description Provides generators for a high number of both single- and multi-objective test functions which are frequently used for the benchmarking of (numerical) optimization algorithms. Moreover, it offers a set of convenient functions to generate, plot and work with objective functions.

Version 1.4

Date 2016-08-03

URL <https://github.com/jakobbossek/smoof>

BugReports <https://github.com/jakobbossek/smoof/issues>

License BSD_2_clause + file LICENSE

Depends ParamHelpers (>= 1.8), BBmisc (>= 1.6), checkmate (>= 1.1)

Imports ggplot2, RColorBrewer, plot3D, plotly, mco, Rcpp (>= 0.11.0)

Suggests testthat, rPython (>= 0.0-5)

LazyData yes

ByteCompile yes

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 5.0.1

NeedsCompilation yes

Author Jakob Bossek [aut, cre],
Pascal Kerschke [ctb]

Maintainer Jakob Bossek <j.bossek@gmail.com>

Repository CRAN

Date/Publication 2016-08-03 16:47:12

R topics documented:

smoof-package	5
addCountingWrapper	6
addLoggingWrapper	7
autoplot.smoof_function	8
computeExpectedRunningTime	9
conversion	11
doesCountEvaluations	12
filterFunctionsByTags	12
getAvailableTags	13
getDescription	13
getGlobalOptimum	14
getID	14
getLocalOptimum	15
getLoggedValues	15
getLowerBoxConstraints	16
getMeanFunction	16
getName	17
getNumberOfEvaluations	17
getNumberOfObjectives	18
getNumberOfParameters	18
getParamSet	19
getRefPoint	19
getTags	20
getUpperBoxConstraints	20
getWrappedFunction	21
hasBoxConstraints	21
hasConstraints	22
hasGlobalOptimum	22
hasLocalOptimum	23
hasOtherConstraints	23
hasTags	24
isMultiobjective	24
isNoisy	25
isSingleobjective	25
isSmoofFunction	26
isVectorized	26
isWrappedSmoofFunction	27
makeAckleyFunction	27
makeAdjimanFunction	28
makeAlpine01Function	28
makeAlpine02Function	29
makeAluffiPentiniFunction	30
makeBartelsConnFunction	30
makeBBOBFunction	31
makeBealeFunction	32
makeBentCigarFunction	32

makeBirdFunction	33
makeBiSphereFunction	33
makeBK1Function	34
makeBohachevskyN1Function	34
makeBoothFunction	35
makeBraninFunction	35
makeBrentFunction	36
makeBrownFunction	37
makeBukinN2Function	37
makeBukinN4Function	38
makeBukinN6Function	39
makeCarronTableFunction	39
makeChichinadzeFunction	40
makeChungReynoldsFunction	40
makeComplexFunction	41
makeCosineMixtureFunction	41
makeCrossInTrayFunction	42
makeCubeFunction	43
makeDeckkersAartsFunction	43
makeDeflectedCorrugatedSpringFunction	44
makeDentFunction	44
makeDixonPriceFunction	45
makeDoubleSumFunction	46
makeDTLZ1Function	46
makeDTLZ2Function	47
makeDTLZ3Function	48
makeDTLZ4Function	49
makeDTLZ5Function	50
makeDTLZ6Function	51
makeDTLZ7Function	52
makeEasomFunction	53
makeEggCrateFunction	54
makeEggholderFunction	54
makeElAttarVidyasagarDuttaFunction	55
makeEngvallFunction	55
makeExponentialFunction	56
makeFreudensteinRothFunction	56
makeFunctionsByName	57
makeGeneralizedDropWaveFunction	58
makeGiuntaFunction	58
makeGoldsteinPriceFunction	59
makeGOMOPFunction	59
makeGriewankFunction	60
makeHansenFunction	61
makeHimmelblauFunction	61
makeHolderTableN1Function	62
makeHolderTableN2Function	62
makeHosakiFunction	63

makeHyperEllipsoidFunction	64
makeJennrichSampsonFunction	64
makeJudgeFunction	65
makeKeaneFunction	65
makeKearfottFunction	66
makeLeonFunction	66
makeMatyasFunction	67
makeMcCormickFunction	67
makeMichalewiczFunction	68
makeMOP1Function	69
makeMOP2Function	69
makeMOP3Function	70
makeMOP4Function	70
makeMOP5Function	71
makeMOP6Function	71
makeMOP7Function	72
makeMPM2Function	72
makeMultiObjectiveFunction	73
makePeriodicFunction	75
makePowellSumFunction	76
makePriceN1Function	76
makePriceN2Function	77
makePriceN4Function	78
makeRastriginFunction	78
makeRosenbrockFunction	79
makeSchafferN2Function	80
makeSchafferN4Function	80
makeSchwefelFunction	81
makeShubertFunction	81
makeSingleObjectiveFunction	82
makeSixHumpCamelFunction	84
makeSphereFunction	85
makeStyblinskiTangFunction	86
makeSumOfDifferentSquaresFunction	86
makeSwiler2014Function	87
makeThreeHumpCamelFunction	87
makeTrecanniFunction	88
makeUFFunction	88
makeViennetFunction	89
makeZDT1Function	90
makeZDT2Function	91
makeZDT3Function	92
makeZDT4Function	93
makeZDT6Function	94
makeZettlFunction	95
plot.smoof_function	95
plot1DNumeric	96
plot2DNumeric	96

plot3D	97
resetEvaluationCounter	98
shouldBeMinimized	99
violatesConstraints	99
visualizeParetoOptimalFront	100

Index**101**

smoof-package

*smoof: Single and Multi-Objective Optimization test functions.***Description**

The **smoof** R package provides generators for huge set of single- and multi-objective test functions, which are frequently used in the literature to benchmark optimization algorithms. Moreover the package provides methods to create arbitrary objective functions in an object-orientated manner, extract their parameters sets and visualize them graphically.

Some more details

Given a set of criteria $\mathcal{F} = \{f_1, \dots, f_m\}$ with each $f_i : S \subseteq \mathbf{R}^d \rightarrow \mathbf{R}, i = 1, \dots, m$ being an objective-function, the goal in *Global Optimization (GO)* is to find the best solution $\mathbf{x}^* \in S$. The set S is termed the *set of feasible solutions*. In the case of only a single objective function f , - which we want to restrict ourself in this brief description - the goal is to minimize the objective, i. e.,

$$\min_{\mathbf{x}} f(\mathbf{x}).$$

Sometimes we may be interested in maximizing the objective function value, but since $\min(f(\mathbf{x})) = -\min(-f(\mathbf{x}))$, we do not have to tackle this separately. To compare the robustness of optimization algorithms and to investigate their behaviour in different contexts, a common approach in the literature is to use *artificial benchmarking functions*, which are mostly deterministic, easy to evaluate and given by a closed mathematical formula. A recent survey by Jamil and Yang lists 175 single-objective benchmarking functions in total for global optimization [1]. The **smoof** package offers implementations of a subset of these functions beside some other functions as well as generators for large benchmarking sets like the noiseless BBOB2009 function set [2] or functions based on the multiple peaks model 2 [3].

References

- [1] Momin Jamil and Xin-She Yang, A literature survey of benchmark functions for global optimization problems, Int. Journal of Mathematical Modelling and Numerical Optimisation, Vol. 4, No. 2, pp. 150-194 (2013). [2] Hansen, N., Finck, S., Ros, R. and Auger, A. Real-Parameter Black-Box Optimization Benchmarking 2009: Noiseless Functions Definitions. Technical report RR-6829. INRIA, 2009. [3] Simon Wessing, The Multiple Peaks Model 2, Algorithm Engineering Report TR15-2-001, TU Dortmund University, 2015.

addCountingWrapper *Return a function which counts its evaluations.*

Description

This is a counting wrapper for a `smoof_function`, i.e., the returned function first checks whether the given argument is a vector or matrix, saves the number of function evaluations of the wrapped function to compute the function values and finally passes down the argument to the wrapped `smoof_function`.

Usage

```
addCountingWrapper(fn)
```

Arguments

`fn` `[smoof_function]`
SmooF function which should be wrapped.

Value

`smoof_counting_function`

See Also

[getNumberOfEvaluations](#), [resetEvaluationCounter](#)

Examples

```
fn = makeBB0BFunction(dimension = 2L, fid = 1L, iid = 1L)
fn = addCountingWrapper(fn)

# we get a value of 0 since the function has not been called yet
print(getNumberOfEvaluations(fn))

# now call the function 10 times consecutively
for (i in seq(10L)) {
  fn(runif(2))
}
print(getNumberOfEvaluations(fn))

# Here we pass a (2x5) matrix to the function with each column representing
# one input vector
x = matrix(runif(10), ncol = 5L)
fn(x)
print(getNumberOfEvaluations(fn))
```

addLoggingWrapper *Return a function which internally stores x or y values.*

Description

Return a function which internally stores x or y values.

Usage

```
addLoggingWrapper(fn, logg.x = FALSE, logg.y = TRUE)
```

Arguments

fn	[smoof_function] Smoof function.
logg.x	[logical(1)] Should x-values be logged? Default is FALSE.
logg.y	[logical(1)] Should objective values be logged? Default is TRUE.

Value

smoof_logging_function

Note

Logging values, in particular logging x-values, will substantially slow down the evaluation of the function.

Examples

```
# We first build the smoof function and apply the logging wrapper to it
fn = makeSphereFunction(dimension = 2L)
fn = addLoggingWrapper(fn, logg.x = TRUE)

# We now apply an optimization algorithm to it and the logging wrapper keeps
# track of the evaluated points.
res = optim(fn, par = c(1, 1), method = "Nelder-Mead")

# Extract the logged values
log.res = getLoggedValues(fn)
print(log.res$params)
print(log.res$obj.vals)
log.res = getLoggedValues(fn, compact = TRUE)
print(log.res)
```

 autoplot.smooof_function

Generate [ggplot](#) object.

Description

This function expects a smooof function and returns a ggplot object depicting the function landscape. The output depends highly on the decision space of the smooof function or more technically on the [ParamSet](#) of the function. The following distinctions regarding the parameter types are made. In case of a single numeric parameter a simple line plot is drawn. For two numeric parameters or a single numeric vector parameter of length 2 either a contour plot or a heatmap (or a combination of both depending on the choice of additional parameters) is depicted. If there are both up to two numeric and at least one discrete vector parameter, ggplot faceting is used to generate subplots of the above-mentioned types for all combinations of discrete parameters.

Usage

```
## S3 method for class 'smooof_function'
autoplot(x, show.optimum = FALSE,
         main = getName(x), render.levels = FALSE, render.contours = TRUE,
         length.out = 50L, ...)
```

Arguments

x	[smooof_function] Objective function.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smooof function.
render.levels	[logical(1)] For 2D numeric functions only: Should an image map be plotted? Default is FALSE.
render.contours	[logical(1)] For 2D numeric functions only: Should contour lines be plotted? Default is TRUE.
length.out	[integer(1)] Desired length of the sequence of equidistant values generated for numeric parameters. Higher values lead to more smooth resolution in particular if render.levels is TRUE. Avoid using a very high value here especially if the function at hand has many parameters. Default is 50.
...	[any] Not used.

Value

ggplot

Note

Keep in mind, that the plots for mixed parameter spaces may be very large and computationally expensive if the number of possible discrete parameter values is large. I.e., if we have d discrete parameter with each n_1, n_2, \dots, n_d possible values we end up with $n_1 \times n_2 \times \dots \times n_d$ subplots.

Examples

```
library(ggplot2)

# Simple 2D contour plot with activated heatmap for the Himmelblau function
fn = makeHimmelblauFunction()
print(autoplot(fn))
print(autoplot(fn, render.levels = TRUE, render.contours = FALSE))
print(autoplot(fn, show.optimum = TRUE))

# Now we create 4D function with a mixed decision space (two numeric, one discrete,
# and one logical parameter)
fn.mixed = makeSingleObjectiveFunction(
  name = "4d S00 function",
  fn = function(x) {
    if (x$disc1 == "a") {
      (x$x1^2 + x$x2^2) + 10 * as.numeric(x$logic)
    } else {
      x$x1 + x$x2 - 10 * as.numeric(x$logic)
    }
  },
  has.simple.signature = FALSE,
  par.set = makeParamSet(
    makeNumericParam("x1", lower = -5, upper = 5),
    makeNumericParam("x2", lower = -3, upper = 3),
    makeDiscreteParam("disc1", values = c("a", "b")),
    makeLogicalParam("logic")
  )
)
p1 = autoplot(fn.mixed)
print(p1)

# Since autoplot returns a ggplot object we can modify it, e.g., add a title
# or hide the legend
p1 + ggtitle("My fancy function") + theme(legend.position = "none")
```

computeExpectedRunningTime

Compute the Expected Running Time (ERT) performance measure.

Description

The functions can be called in two different ways

- 1. Pass a vector of function evaluations and a logical vector which indicates which runs were successful (see details).
- 2. Pass a vector of function evaluation, a vector of reached target values and a single target value. In this case the logical vector of option 1. is computed internally.

Usage

```
computeExpectedRunningTime(fun.ivals, fun.success.runs = NULL,
  fun.reached.target.values = NULL, fun.target.value = NULL,
  penalty.value = Inf)
```

Arguments

<code>fun.ivals</code>	[numeric] Vector containing the number of function evaluations.
<code>fun.success.runs</code>	[logical] Boolean vector indicating which algorithm runs were successful, i. e., which runs reached the desired target value. Default is NULL.
<code>fun.reached.target.values</code>	[numeric NULL] Numeric vector with the objective values reached in the runs. Default is NULL.
<code>fun.target.value</code>	[numeric(1) NULL] Target value which shall be reached. Default is NULL.
<code>penalty.value</code>	[numeric(1)] Penalty value which should be returned if none of the algorithm runs was successful. Default is Inf.

Details

The Expected Running Time (ERT) is one of the most popular performance measures in optimization. It is defined as the expected number of function evaluations needed to reach a given precision level, i. e., to reach a certain objective value for the first time.

Value

numeric(1) Estimated Expected Running Time.

References

A. Auger and N. Hansen. Performance evaluation of an advanced local search evolutionary algorithm. In Proceedings of the IEEE Congress on Evolutionary Computation (CEC 2005), pages 1777-1784, 2005.

conversion

Conversion between minimization and maximization problems.

Description

We can minimize f by maximizing $-f$. The majority of predefined objective functions in **smoof** should be minimized by default. However, there is a handful of functions, e.g., Keane or Alpine02, which shall be maximized by default. For benchmarking studies it might be beneficial to inverse the direction. The functions `convertToMaximization` and `convertToMinimization` do exactly that keeping the attributes.

Usage

```
convertToMaximization(fn)
```

```
convertToMinimization(fn)
```

Arguments

<code>fn</code>	<code>[smoof_function]</code> Smoof function.
-----------------	--

Value

`smoof_function`

Note

Internally no wrapper is put around the original function. Instead the function is copied and the body of the function is manipulated via the body function. Both functions will quit with an error if multi-objective functions are passed.

Examples

```
# create a function which should be minimized by default
fn = makeSphereFunction(1L)
print(shouldBeMinimized(fn))
# Now invert the objective direction ...
fn2 = convertToMaximization(fn)
# and invert it again
fn3 = convertToMinimization(fn2)
# Now to convince ourselves we render some plots
opar = par(mfrow = c(1, 3))
plot(fn)
plot(fn2)
plot(fn3)
par(opar)
```

doesCountEvaluations *Check whether the function is counting its function evaluations.*

Description

In this case the function is of type `smoof_counting_function` or it is further wrapped by another wrapper. This function then checks recursively, if there is a counting wrapper.

Usage

```
doesCountEvaluations(object)
```

Arguments

object	[any] Arbitrary R object.
--------	------------------------------

Value

```
logical(1)
```

See Also

[addCountingWrapper](#)

filterFunctionsByTags *Get a list of implemented test functions with specific tags.*

Description

Get a list of implemented test functions with specific tags.

Usage

```
filterFunctionsByTags(tags, or = FALSE)
```

Arguments

tags	[character] Character vector of tags. All available tags can be determined with a call to getAvailableTags .
or	[logical(1)] Should all tags be assigned to the function or are single tags allowed as well? Default is FALSE.

Value

character Named vector of function names with the given tags.

Examples

```
# list all functions which are unimodal
filterFunctionsByTags("unimodal")
# list all functions which are both unimodal and separable
filterFunctionsByTags(c("unimodal", "separable"))
# list all functions which are unimodal or separable
filterFunctionsByTags(c("multimodal", "separable"), or = TRUE)
```

getAvailableTags	<i>Returns a character vector of possible function tags.</i>
------------------	--

Description

Test function are frequently distinguished by characteristic high-level properties, e.g., unimodal or multimodal, continuous or discontinuous, separable or non-separable. The **smoof** package offers the possibility to associate a set of properties, termed “tags” to a `smoof_function`. This helper function returns a character vector of all possible tags.

Usage

```
getAvailableTags()
```

Value

character

getDescription	<i>Return the description of the function.</i>
----------------	--

Description

Return the description of the function.

Usage

```
getDescription(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

character(1)

getGlobalOptimum *Returns the global optimum and its value.*

Description

Returns the global optimum and its value.

Usage

```
getGlobalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

list List containing the following entries:

- param [list]Named list of parameter value(s).
- value [numeric(1)]Optimal value.
- is.minimum [logical(1)]Is the global optimum a minimum or maximum?

Note

Keep in mind, that this method makes sense only for single-objective target function.

getID *Return the ID / short name of the function.*

Description

Return the ID / short name of the function.

Usage

```
getID(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

character(1)

getLocalOptimum	<i>Returns the local optima.</i>
-----------------	----------------------------------

Description

This function returns the parameters and objective values of all local optima (including the global one).

Usage

```
getLocalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

list List containing the following entries:

- param [list] List of parameter values per local optima.
- value [list] List of objective values per local optima.
- is.minimum [logical(1)] Are the local optima minima or maxima?

Note

Keep in mind, that this method makes sense only for single-objective target functions.

getLoggedValues	<i>Extract logged values of a function wrapped by a logging wrapper.</i>
-----------------	--

Description

Extract logged values of a function wrapped by a logging wrapper.

Usage

```
getLoggedValues(fn, compact = FALSE)
```

Arguments

fn	[wrapped_smoof_function] Wrapped smoof function.
compact	[logical(1)] Wrap all logged values in a single data frame? Default is FALSE.

Value

list | data.frame If compact is TRUE, a single data frame. Otherwise the function returns a list containing the following values:

pars Data frame of parameter values, i.e., x-values or the empty data frame if x-values were not logged.

obj.vals Numeric vector of objective vals in the single-objective case respectively a matrix of objective vals for multi-objective functions.

See Also

[addLoggingWrapper](#)

getLowerBoxConstraints

Return lower box constraints.

Description

Return lower box constraints.

Usage

```
getLowerBoxConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

numeric

getMeanFunction

Return the true mean function in the noisy case.

Description

Return the true mean function in the noisy case.

Usage

```
getMeanFunction(fn)
```


Arguments

fn [smoof_function]
Objective function.

Value

function

getName *Return the name of the function.*

Description

Return the name of the function.

Usage

getName(fn)

Arguments

fn [smoof_function]
Objective function.

Value

character(1)

getNumberOfEvaluations
*Return the number of function evaluations performed by the wrapped
smoof_function.*

Description

Return the number of function evaluations performed by the wrapped smoof_function.

Usage

getNumberOfEvaluations(fn)

Arguments

fn [smoof_counting_function]
Wrapped smoof_function.

Value

integer(1)

getNumberOfObjectives *Determine the number of objectives.*

Description

Determine the number of objectives.

Usage

```
getNumberOfObjectives(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

integer(1)

getNumberOfParameters *Determine the number of parameters.*

Description

Determine the number of parameters.

Usage

```
getNumberOfParameters(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

integer(1)

getParamSet	<i>Get parameter set.</i>
-------------	---------------------------

Description

Each smooof function contains a parameter set of type [ParamSet](#) assigned to it, which describes types and bounds of the function parameters. This function returns the parameter set.

Arguments

fn	[smooof_function] Objective function.
----	--

Value

[ParamSet](#)

Examples

```
fn = makeSphereFunction(3L)
ps = getParamSet(fn)
print(ps)
```

getRefPoint	<i>Returns the reference point of a multi-objective function.</i>
-------------	---

Description

Returns the reference point of a multi-objective function.

Usage

```
getRefPoint(fn)
```

Arguments

fn	[smooof_function] Objective function.
----	--

Value

numeric

Note

Keep in mind, that this method makes sense only for multi-objective target functions.

getTags *Returns vector of associated tags.*

Description

Returns vector of associated tags.

Usage

```
getTags(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

character

getUpperBoxConstraints
Return upper box constraints.

Description

Return upper box constraints.

Usage

```
getUpperBoxConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

numeric

getWrappedFunction *Extract wrapped function.*

Description

The **smoof** package offers means to let a function log its evaluations or even store to points and function values it has been evaluated on. This is done by wrapping the function with other functions. This helper function extract the wrapped function.

Usage

```
getWrappedFunction(fn, deepest = FALSE)
```

Arguments

fn	[smoof_wrapped_function] Wrapping function.
deepest	[logical(1)] Function may be wrapped with multiple wrappers. If deepest is set to TRUE the function unwraps recursively until the “deepest” wrapped smoof_function is reached. Default is FALSE.

Value

function

Note

If this function is applied to a simple smoof_function, the smoof_function itself is returned.

See Also

[addCountingWrapper](#), [addLoggingWrapper](#)

hasBoxConstraints *Checks whether the objective function has box constraints.*

Description

Checks whether the objective function has box constraints.

Usage

```
hasBoxConstraints(fn)
```

Arguments

fn [smoof_function]
Objective function.

Value

logical(1)

hasConstraints	<i>Checks whether the objective function has constraints.</i>
----------------	---

Description

Checks whether the objective function has constraints.

Usage

hasConstraints(fn)

Arguments

fn [smoof_function]
Objective function.

Value

logical(1)

hasGlobalOptimum	<i>Checks whether global optimum is known.</i>
------------------	--

Description

Checks whether global optimum is known.

Usage

hasGlobalOptimum(fn)

Arguments

fn [smoof_function]
Objective function.

Value

logical(1)

hasLocalOptimum	<i>Checks whether local optima are known.</i>
-----------------	---

Description

Checks whether local optima are known.

Usage

```
hasLocalOptimum(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

logical(1)

hasOtherConstraints	<i>Checks whether the objective function has other constraints.</i>
---------------------	---

Description

Checks whether the objective function has other constraints.

Usage

```
hasOtherConstraints(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

logical(1)

hasTags*Check if function has assigned special tags.*

Description

Each single-objective smooof function has tags assigned to it (see [getAvailableTags](#)). This little helper returns a vector of assigned tags from a smooof function.

Usage

```
hasTags(fn, tags)
```

Arguments

fn	[smooof_function] Function of smooof_function, a smooof_generator or a string.
tags	[character] Vector of tags/properties to check fn for.

Value

```
logical(1)
```

isMultiobjective*Checks whether the given function is multi-objective.*

Description

Checks whether the given function is multi-objective.

Usage

```
isMultiobjective(fn)
```

Arguments

fn	[smooof_function] Objective function.
----	--

Value

```
logical(1) TRUE if function is multi-objective.
```

isNoisy	<i>Checks whether the given function is noisy.</i>
---------	--

Description

Checks whether the given function is noisy.

Usage

```
isNoisy(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

logical(1)

isSingleobjective	<i>Checks whether the given function is single-objective.</i>
-------------------	---

Description

Checks whether the given function is single-objective.

Usage

```
isSingleobjective(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

logical(1) TRUE if function is single-objective.

isSmoofFunction	<i>Checks whether the given object is a smooof_function or a smooof_wrapped_function.</i>
-----------------	---

Description

Checks whether the given object is a smooof_function or a smooof_wrapped_function.

Usage

```
isSmoofFunction(object)
```

Arguments

object	[any] Arbitrary R object.
--------	------------------------------

Value

logical(1)

See Also

[addCountingWrapper](#), [addLoggingWrapper](#)

isVectorized	<i>Checks whether the given function accept “vectorized” input.</i>
--------------	---

Description

Checks whether the given function accept “vectorized” input.

Usage

```
isVectorized(fn)
```

Arguments

fn	[smooof_function] Objective function.
----	--

Value

logical(1)

Value

smoof_single_objective_function

References

Ackley, D. H.: A connectionist machine for genetic hillclimbing. Boston: Kluwer Academic Publishers, 1987.

makeAdjimanFunction *Adjiman function*

Description

This two-dimensional multimodal test function follows the formula

$$f(\mathbf{x}) = \cos(\mathbf{x}_1) \sin(\mathbf{x}_2) - \frac{\mathbf{x}_1}{(\mathbf{x}_2^2 + 1)}$$

with $\mathbf{x}_1 \in [-1, 2]$, $\mathbf{x}_2 \in [2, 1]$.

Usage

makeAdjimanFunction()

Value

smoof_single_objective_function

References

C. S. Adjiman, S. Sallwig, C. A. Flouda, A. Neumaier, A Global Optimization Method, aBB for General Twice-Differentiable NLPs-1, Theoretical Advances, Computers Chemical Engineering, vol. 22, no. 9, pp. 1137-1158, 1998.

makeAlpine01Function *Alpine01 function*

Description

Highly multimodal single-objective optimization test function. It is defined as

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i \sin(\mathbf{x}_i) + 0.1\mathbf{x}_i|$$

with box constraints $\mathbf{x}_i \in [-10, 10]$ for $i = 1, \dots, n$.

Usage

```
makeAlpine01Function(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, A Novel Population Initialization Method for Accelerating Evolutionary Algorithms, Computers and Mathematics with Applications, vol. 53, no. 10, pp. 1605-1614, 2007.

makeAlpine02Function *Alpine02 function*

Description

Another multimodal optimization test function. The implementation is based on the formula

$$f(\mathbf{x}) = \prod_{i=1}^n \sqrt{x_i} \sin(x_i)$$

with $x_i \in [0, 10]$ for $i = 1, \dots, n$.

Usage

```
makeAlpine02Function(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

M. Clerc, The Swarm and the Queen, Towards a Deterministic and Adaptive Particle Swarm Optimization, IEEE Congress on Evolutionary Computation, Washington DC, USA, pp. 1951-1957, 1999.

makeAluffiPentiniFunction

Aluffi-Pentini function.

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = 0.25x_1^4 - 0.5x_1^2 + 0.1x_1 + 0.5x_2^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-10, 10]$.

Usage

makeAluffiPentiniFunction()

Value

smoof_single_objective_function

Note

This functions is also know as the Zirilli function.

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/26-aluffi-pentini-s-or-zirilli-s-func>

makeBartelsConnFunction

Bartels Conn Function

Description

The Bartels Conn Function is defined as

$$f(\mathbf{x}) = |\mathbf{x}_1^2 + \mathbf{x}_2^2 + \mathbf{x}_1\mathbf{x}_2| + |\sin(\mathbf{x}_1)| + |\cos(\mathbf{x})|$$

subject to $\mathbf{x}_i \in [-500, 500]$ for $i = 1, 2$.

Usage

makeBartelsConnFunction()

Value

smoof_single_objective_function

makeBBOBFunction	<i>Generator for the noiseless function set of the real-parameter Black-Box Optimization Benchmarking (BBOB).</i>
------------------	---

Description

Generator for the noiseless function set of the real-parameter Black-Box Optimization Benchmarking (BBOB).

Usage

```
makeBBOBFunction(dimension, fid, iid)
```

Arguments

dimension	[integer(1)] Problem dimension. Integer value between 2 and 40.
fid	[integer(1)] Function identifier. Integer value between 1 and 24.
iid	[integer(1)] Instance identifier. Integer value greater than or equal 1.

Value

smoof_single_objective_function

Note

It is possible to pass a matrix of parameters to the functions, where each column consists of one parameter setting.

References

See the [BBOB website](#) for a detailed description of the BBOB functions.

Examples

```
# get the first instance of the 2D Sphere function
fn = makeBBOBFunction(dimension = 2L, fid = 1L, iid = 1L)
if (require(plot3D)) {
  plot3D(fn, contour = TRUE)
}
```

makeBealeFunction *Beale Function*

Description

Multimodal single-objective test function for optimization. It is based on the mathematic formula

$$f(\mathbf{x}) = (1.5 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2)^2 + (2.25 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2^2)^2 + (2.625 - \mathbf{x}_1 + \mathbf{x}_1\mathbf{x}_2^3)^2$$

usually evaluated within the bounds $\mathbf{x}_i \in [-4.5, 4.5], i = 1, 2$. The function has a flat but multimodal region around the single global optimum and large peaks in the edges of its definition space.

Usage

makeBealeFunction()

Value

smoof_single_objective_function

makeBentCigarFunction *Bent-Cigar Function*

Description

Scalable test function f with

$$f(\mathbf{x}) = x_1^2 + 10^6 \sum_{i=2}^n x_i^2$$

subject to $-100 \leq \mathbf{x}_i \leq 100$ for $i = 1, \dots, n$.

Usage

makeBentCigarFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/n-dimensions/164-bent-cigar-function>.

makeBirdFunction *Bird Function*

Description

Multimodal single-objective test function. The implementation is based on the mathematical formulation

$$f(\mathbf{x}) = (\mathbf{x}_1 - \mathbf{x}_2)^2 + \exp((1 - \sin(\mathbf{x}_1))^2) \cos(\mathbf{x}_2) + \exp((1 - \cos(\mathbf{x}_2))^2) \sin(\mathbf{x}_1).$$

The function is restricted to two dimensions with $\mathbf{x}_i \in [-2\pi, 2\pi]$, $i = 1, 2$.

Usage

```
makeBirdFunction()
```

Value

smoof_single_objective_function

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeBiSphereFunction *Bi-objective Sphere function*

Description

Builds and returns the bi-objective Sphere test problem:

$$f(\mathbf{x}) = \left(\sum_{i=1}^n \mathbf{x}_i^2, \sum_{i=1}^n (\mathbf{x}_i - \mathbf{a})^2 \right)$$

where

$$\mathbf{a} \in R^n$$

Usage

```
makeBiSphereFunction(dimensions, a = rep(0, dimensions))
```

Arguments

dimensions	[integer(1)] Number of decision variables.
a	[numeric(1)] Shift parameter for the second objective. Default is (0,...,0).

Value

smoof_multi_objective_function

makeBK1Function	<i>BK1 function generator</i>
-----------------	-------------------------------

Description

...

Usage

makeBK1Function()

Value

smoof_multi_objective_function

References

...

makeBohachevskyN1Function	<i>Bohachevsky function N. 1</i>
---------------------------	----------------------------------

Description

Highly multimodal single-objective test function. The mathematical formula is given by

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} (\mathbf{x}_i^2 + 2\mathbf{x}_{i+1}^2 - 0.3 \cos(3\pi\mathbf{x}_i) - 0.4 \cos(4\pi\mathbf{x}_{i+1}) + 0.7)$$

with box-constraints $\mathbf{x}_i \in [-100, 100]$ for $i = 1, \dots, n$. The multimodality will be visible by “zooming in” in the plot.

Usage

makeBohachevskyN1Function(dimensions)

Arguments

dimensions [integer(1)]
 Size of corresponding parameter space.

Value

smoof_single_objective_function

References

I. O. Bohachevsky, M. E. Johnson, M. L. Stein, General Simulated Annealing for Function Optimization, *Technometrics*, vol. 28, no. 3, pp. 209-217, 1986.

makeBoothFunction *Booth Function*

Description

This function is based on the formula

$$f(\mathbf{x}) = (\mathbf{x}_1 + 2\mathbf{x}_2 - 7)^2 + (2\mathbf{x}_1 + \mathbf{x}_2 - 5)^2$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeBoothFunction()

Value

smoof_single_objective_function

makeBraninFunction *Branin RCOS function*

Description

Popular 2-dimensional single-objective test function based on the formula:

$$f(\mathbf{x}) = a (\mathbf{x}_2 - b\mathbf{x}_1^2 + c\mathbf{x}_1 - d)^2 + e (1 - f) \cos(\mathbf{x}_1) + e,$$

where $a = 1, b = \frac{5.1}{4\pi^2}, c = \frac{5}{\pi}, d = 6, e = 10$ and $f = \frac{1}{8\pi}$. The box constraints are given by $\mathbf{x}_1 \in [-5, 10]$ and $\mathbf{x}_2 \in [0, 15]$. The function has three global minima.

Usage

makeBraninFunction()

Value

smoof_single_objective_function

References

F. H. Branin. Widely convergent method for finding multiple solutions of simultaneous nonlinear equations. IBM J. Res. Dev. 16, 504-522, 1972.

Examples

```
library(ggplot2)
fn = makeBraninFunction()
print(fn)
print(autoplot(fn, show.optimum = TRUE))
```

makeBrentFunction *Brent Function*

Description

Single-objective two-dimensional test function. The formula is given as

$$f(\mathbf{x}) = (\mathbf{x}_1 + 10)^2 + (\mathbf{x}_2 + 10)^2 + \exp(-\mathbf{x}_1^2 - \mathbf{x}_2^2)$$

subject to the constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makeBrentFunction()
```

Value

smoof_single_objective_function

References

F. H. Branin Jr., Widely Convergent Method of Finding Multiple Solutions of Simultaneous Nonlinear Equations, IBM Journal of Research and Development, vol. 16, no. 5, pp. 504-522, 1972.

makeBrownFunction *Brown Function*

Description

This function belongs to the unimodal single-objective test functions. The function is formulated as

$$f(\mathbf{x}) = \sum_{i=1}^n (\mathbf{x}_i^2)^{(\mathbf{x}_{i+1}+1)} + (\mathbf{x}_{i+1})^{(\mathbf{x}_i+1)}$$

subject to $\mathbf{x}_i \in [-1, 4]$ for $i = 1, \dots, n$.

Usage

makeBrownFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

O. Begambre, J. E. Laier, A hybrid Particle Swarm Optimization - Simplex Algorithm (PSOS) for Structural Damage Identification, Journal of Advances in Engineering Software, vol. 40, no. 9, pp. 883-891, 2009.

makeBukinN2Function *Bukin function N. 2*

Description

Multimodal, non-scalable, continuous optimization test function given by:

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - 0.01 * \mathbf{x}_1^2 + 1) + 0.01(\mathbf{x}_1 + 10)^2$$

subject to $\mathbf{x}_1 \in [-15, -5]$ and $\mathbf{x}_2 \in [-3, 3]$.

Usage

makeBukinN2Function()

Value

smoof_single_objective_function

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN4Function](#), [makeBukinN6Function](#)

makeBukinN4Function *Bukin function N. 4*

Description

Second continous Bukin function test function. The formula is given by

$$f(\mathbf{x}) = 100\mathbf{x}_2^2 + 0.01 * ||\mathbf{x}_1 + 10||$$

and the box constraints $\mathbf{x}_1 \in [-15, 5]$, $\mathbf{x}_2 \in [-3, 3]$.

Usage

makeBukinN4Function()

Value

smoof_single_objective_function

References

Z. K. Silagadze, Finding Two-Dimesnional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN2Function](#), [makeBukinN6Function](#)

makeBukinN6Function *Bukin function N. 6*

Description

Beside Bukin N. 2 and N. 4 this is the last “Bukin family” function. It is given by the formula

$$f(\mathbf{x}) = 100\sqrt{|\mathbf{x}_2 - 0.01\mathbf{x}_1^2|} + 0.01|\mathbf{x}_1 + 10|$$

and the box constraints $\mathbf{x}_1 \in [-15, 5], \mathbf{x}_2 \in [-3, 3]$.

Usage

makeBukinN6Function()

Value

smoof_single_objective_function

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

See Also

[makeBukinN2Function](#), [makeBukinN4Function](#)

makeCarromTableFunction
Carrom Table Function

Description

This function is defined as follows:

$$f(\mathbf{x}) = -\frac{1}{30} \left((\cos(\mathbf{x}_1) \exp(|1 - ((\mathbf{x}_1^2 + \mathbf{x}_2^2)^{0.5}/\pi)^2|)) \right).$$

The box-constraints are given by $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeCarromTableFunction()

Value

smoof_single_objective_function

Value

smoof_single_objective_function

References

C. J. Chung, R. G. Reynolds, CAEP: An Evolution-Based Tool for Real-Valued Function Optimization Using Cultural Algorithms, International Journal on Artificial Intelligence Tool, vol. 7, no. 3, pp. 239-291, 1998.

makeComplexFunction *Complex function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = (x_1^3 - 3x_1x_2^2 - 1)^2 + (3x_2x_1^2 - x_2^3)^2$$

with $x_1, x_2 \in [-2, 2]$.

Usage

makeComplexFunction()

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/43-complex-function>.

makeCosineMixtureFunction
Cosine Mixture Function

Description

Single-objective test function based on the formula

$$f(\mathbf{x}) = -0.1 \sum_{i=1}^n \cos(5\pi \mathbf{x}_i) - \sum_{i=1}^n \mathbf{x}_i^2$$

subject to $\mathbf{x}_i \in [-1, 1]$ for $i = 1, \dots, n$.

Usage

```
makeCosineMixtureFunction(dimensions)
```

Arguments

```
dimensions    [integer(1)]
              Size of corresponding parameter space.
```

Value

smoof_single_objective_function

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

```
makeCrossInTrayFunction
              Cross-In-Tray Function
```

Description

Non-scalable, two-dimensional test function for numerical optimization with

$$f(\mathbf{x}) = -0.0001 \left(|\sin(\mathbf{x}_1 \mathbf{x}_2 \exp(|100 - [(\mathbf{x}_1^2 + \mathbf{x}_2^2)]^{0.5} / \pi|))| + 1 \right)^{0.1}$$

subject to $\mathbf{x}_i \in [-15, 15]$ for $i = 1, 2$.

Usage

```
makeCrossInTrayFunction()
```

Value

smoof_single_objective_function

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeCubeFunction	<i>Cube Function</i>
------------------	----------------------

Description

The Cube Function is defined as follows:

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - \mathbf{x}_1^3)^2 + (1 - \mathbf{x}_1)^2.$$

The box-constraints are given by $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeCubeFunction()

Value

smoof_single_objective_function

References

A. Lavi, T. P. Vogel (eds), Recent Advances in Optimization Techniques, John Wiley & Sons, 1966.

makeDeckkersAartsFunction	<i>Deckkers-Aarts Function</i>
---------------------------	--------------------------------

Description

This continuous single-objective test function is defined by the formula

$$f(\mathbf{x}) = 10^5 \mathbf{x}_1^2 + \mathbf{x}_2^2 - (\mathbf{x}_1^2 + \mathbf{x}_2^2)^2 + 10^{-5} (\mathbf{x}_1^2 + \mathbf{x}_2^2)^4$$

with the bounding box $-20 \leq \mathbf{x}_i \leq 20$ for $i = 1, 2$.

Usage

makeDeckkersAartsFunction()

Value

smoof_single_objective_function

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

makeDeflectedCorrugatedSpringFunction
Deflected Corrugated Spring function

Description

Scalable single-objective test function based on the formula

$$f(\mathbf{x}) = 0.1 \sum_{i=1}^n (x_i - \alpha)^2 - \cos \left(K \sqrt{\sum_{i=1}^n (x_i - \alpha)^2} \right)$$

with $\mathbf{x}_i \in [0, 2\alpha]$, $i = 1, \dots, n$ and $\alpha = K = 5$ by default.

Usage

makeDeflectedCorrugatedSpringFunction(dimensions, K = 5, alpha = 5)

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
K	[numeric(1)] Parameter. Default is 5.
alpha	[numeric(1)] Parameter. Default is 5.

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/n-dimensions/238-deflected-corrugated-spring-funct>

makeDentFunction *Dent Function*

Description

Builds and returns the bi-objective Dent test problem, which is defined as follows:

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = 0.5 \left(\sqrt{1 + (x_1 + x_2)^2} + \sqrt{1 + (x_1 - x_2)^2} + x_1 - x_2 \right) + d$$

and

$$f_2(\mathbf{x}_1) = 0.5 \left(\sqrt{1 + (x_1 + x_2)^2} + \sqrt{1 + (x_1 - x_2)^2} - x_1 + x_2 \right) + d$$

where $d = \lambda * \exp(-(x_1 - x_2)^2)$ and $\mathbf{x}_i \in [-1.5, 1.5]$, $i = 1, 2$.

Usage

```
makeDentFunction()
```

Value

smoof_multi_objective_function

```
makeDixonPriceFunction
```

Dixon-Price Function

Description

Dixon and Price defined the function

$$f(\mathbf{x}) = (\mathbf{x}_1 - 1)^2 + \sum_{i=1}^n i(2\mathbf{x}_i^2 - \mathbf{x}_{i-1})$$

subject to $\mathbf{x}_i \in [-10, 10]$ for $i = 1, \dots, n$.

Usage

```
makeDixonPriceFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

L. C. W. Dixon, R. C. Price, The Truncated Newton Method for Sparse Unconstrained Optimisation Using Automatic Differentiation, Journal of Optimization Theory and Applications, vol. 60, no. 2, pp. 261-275, 1989.

makeDoubleSumFunction *Double-Sum Function*

Description

Also known as the rotated hyper-ellipsoid function. The formula is given by

$$f(\mathbf{x}) = \sum_{i=1}^n \left(\sum_{j=1}^i \mathbf{x}_j \right)^2$$

with $\mathbf{x}_i \in [-65.536, 65.536], i = 1, \dots, n$.

Usage

makeDoubleSumFunction(dimensions)

Arguments

dimensions [integer(1)]
 Size of corresponding parameter space.

Value

smoof_single_objective_function

References

H.-P. Schwefel. Evolution and Optimum Seeking. John Wiley & Sons, New York, 1995.

makeDTLZ1Function *DTLZ1 Function (family)*

Description

Builds and returns the multi-objective DTLZ1 test problem.

The DTLZ1 test problem is defined as follows:

Minimize $f_1(\mathbf{x}) = \frac{1}{2}x_1x_2 \cdots x_{M-1}(1 + g(\mathbf{x}_M))$,

Minimize $f_2(\mathbf{x}) = \frac{1}{2}x_1x_2 \cdots (1 - x_{M-1})(1 + g(\mathbf{x}_M))$,

⋮

Minimize $f_{M-1}(\mathbf{x}) = \frac{1}{2}x_1(1 - x_2)(1 + g(\mathbf{x}_M))$,

Minimize $f_M(\mathbf{x}) = \frac{1}{2}(1 - x_1)(1 + g(\mathbf{x}_M))$,

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $g(\mathbf{x}_M) = 100 \left[|\mathbf{x}_M| + \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2 - \cos(20\pi(x_i - 0.5)) \right]$

Usage

```
makeDTLZ1Function(dimensions, n.objectives)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ2Function	<i>DTLZ2 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ2 test problem.

The DTLZ2 test problem is defined as follows:

Minimize $f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \cos(x_{M-1}\pi/2)$,

Minimize $f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \sin(x_{M-1}\pi/2)$,

Minimize $f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \sin(x_{M-2}\pi/2)$,

⋮

Minimize $f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \sin(x_2\pi/2)$,

Minimize $f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1\pi/2)$,

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$

Usage

```
makeDTLZ2Function(dimensions, n.objectives)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ3Function	<i>DTLZ3 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ3 test problem. The formula is very similar to the formula of DTLZ2, but it uses the g function of DTLZ1, which introduces a lot of local Pareto-optimal fronts. Thus, this problems is well suited to check the ability of an optimizer to converge to the global Pareto-optimal front.

The DTLZ3 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \cos(x_{M-1}\pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \cos(x_{M-2}\pi/2) \sin(x_{M-1}\pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \cos(x_2\pi/2) \cdots \sin(x_{M-2}\pi/2),$$

⋮

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1\pi/2) \sin(x_2\pi/2),$$

$$\text{Minimize } f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1\pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

$$\text{where } g(\mathbf{x}_M) = 100 \left[|\mathbf{x}_M| + \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2 - \cos(20\pi(x_i - 0.5)) \right]$$

Usage

makeDTLZ3Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ4Function	<i>DTLZ4 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ4 test problem. It is a slight modification of the DTLZ2 problems by introducing the parameter α . The parameter is used to map $\mathbf{x}_i \rightarrow \mathbf{x}_i^\alpha$.

The DTLZ4 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \cos(x_{M-2}^\alpha \pi/2) \cos(x_{M-1}^\alpha \pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \cos(x_{M-2}^\alpha \pi/2) \sin(x_{M-1}^\alpha \pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \cos(x_2^\alpha \pi/2) \cdots \sin(x_{M-2}^\alpha \pi/2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(x_1^\alpha \pi/2) \sin(x_2^\alpha \pi/2),$$

$$\text{Minimize } f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \sin(x_1^\alpha \pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

$$\text{where } g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$$

Usage

```
makeDTLZ4Function(dimensions, n.objectives, alpha = 100)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.
alpha	[numeric(1)] Optional parameter. Default is 100, which is recommended by Deb et al.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ5Function	<i>DTLZ5 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ5 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ5 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1\pi/2) \cos(\theta_2\pi/2) \cdots \cos(\theta_{M-2}\pi/2) \cos(\theta_{M-1}\pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1\pi/2) \cos(\theta_2\pi/2) \cdots \cos(\theta_{M-2}\pi/2) \sin(\theta_{M-1}\pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1\pi/2) \cos(\theta_2\pi/2) \cdots \sin(\theta_{M-2}\pi/2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1\pi/2) \sin(\theta_2\pi/2),$$

$$\text{Minimize } f_M((1 + g(\mathbf{x}_M)) \sin(\theta_1\pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $\theta_i = \frac{\pi}{4(1+g(\mathbf{x}_M))} (1 + 2g(\mathbf{x}_M)x_i)$, for $i = 2, 3, \dots, (M - 1)$

$$\text{and } g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} (x_i - 0.5)^2$$

Usage

makeDTLZ5Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ6Function	<i>DTLZ6 Function (family)</i>
-------------------	--------------------------------

Description

Builds and returns the multi-objective DTLZ6 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ6 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \cos(\theta_{M-2} \pi/2) \cos(\theta_{M-1} \pi/2),$$

$$\text{Minimize } f_2(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \cos(\theta_{M-2} \pi/2) \sin(\theta_{M-1} \pi/2),$$

$$\text{Minimize } f_3(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \cos(\theta_2 \pi/2) \cdots \sin(\theta_{M-2} \pi/2),$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = (1 + g(\mathbf{x}_M)) \cos(\theta_1 \pi/2) \sin(\theta_2 \pi/2),$$

$$\text{Minimize } f_M((1 + g(\mathbf{x}_M)) \sin(\theta_1 \pi/2),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

where $\theta_i = \frac{\pi}{4(1+g(\mathbf{x}_M))} (1 + 2g(\mathbf{x}_M)x_i)$, for $i = 2, 3, \dots, (M - 1)$

and $g(\mathbf{x}_M) = \sum_{x_i \in \mathbf{x}_M} x_i^{0.1}$

Usage

makeDTLZ6Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeDTLZ7Function *DTLZ7 Function (family)*

Description

Builds and returns the multi-objective DTLZ7 test problem. This problem can be characterized by a disconnected Pareto-optimal front in the search space. This introduces a new challenge to evolutionary multi-objective optimizers, i.e., to maintain different subpopulations within the search space to cover the entire Pareto-optimal front.

The DTLZ7 test problem is defined as follows:

$$\text{Minimize } f_1(\mathbf{x}) = x_1,$$

$$\text{Minimize } f_2(\mathbf{x}) = x_2,$$

$$\vdots$$

$$\text{Minimize } f_{M-1}(\mathbf{x}) = x_{M-1},$$

$$\text{Minimize } f_M(\mathbf{x}) = (1 + g(\mathbf{x}_M))h(f_1, f_2, \dots, f_{M-1}, g),$$

with $0 \leq x_i \leq 1$, for $i = 1, 2, \dots, n$,

$$\text{where } g(\mathbf{x}_M) = 1 + \frac{9}{|\mathbf{x}_M|} \sum_{x_i \in \mathbf{x}_M} x_i$$

$$\text{and } h(f_1, f_2, \dots, f_{M-1}, g) = M - \sum_{i=1}^{M-1} \left[\frac{f_i}{1+g} (1 + \sin(3\pi f_i)) \right]$$

Usage

makeDTLZ7Function(dimensions, n.objectives)

Arguments

dimensions	[integer(1)] Number of decision variables.
n.objectives	[integer(1)] Number of objectives.

Value

smoof_multi_objective_function

References

K. Deb and L. Thiele and M. Laumanns and E. Zitzler. Scalable Multi-Objective Optimization Test Problems. Computer Engineering and Networks Laboratory (TIK), Swiss Federal Institute of Technology (ETH) Zurich, 112, 2001

makeEasomFunction	<i>Easom Function</i>
-------------------	-----------------------

Description

Unimodal function with its global optimum in the center of the search space. The attraction area of the global optimum is very small in relation to the search space:

$$f(\mathbf{x}) = -\cos(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp(-((\mathbf{x}_1 - \pi)^2 + (\mathbf{x}_2 - \pi)^2))$$

with $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

```
makeEasomFunction()
```

Value

smoof_single_objective_function

References

Easom, E. E.: A survey of global optimization techniques. M. Eng. thesis, University of Louisville, Louisville, KY, 1990.

makeEggCrateFunction *Egg Crate Function*

Description

This single-objective function follows the definition

$$f(\mathbf{x}) = \mathbf{x}_1^2 + \mathbf{x}_2^2 + 25(\sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2))$$

with $\mathbf{x}_i \in [-5, 5]$ for $i = 1, 2$.

Usage

makeEggCrateFunction()

Value

smoof_single_objective_function

makeEggholderFunction *Egg Holder function*

Description

The Egg Holder function is a difficult to optimize function based on the definition

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} \left[-(\mathbf{x}_{i+1} + 47) \sin \sqrt{|\mathbf{x}_{i+1} + 0.5\mathbf{x}_i + 47|} - \mathbf{x}_i \sin(\sqrt{|\mathbf{x}_i - (\mathbf{x}_{i+1} - 47)|}) \right]$$

subject to $-512 \leq \mathbf{x}_i \leq 512$ for $i = 1, \dots, n$.

Usage

makeEggholderFunction()

Value

smoof_single_objective_function

makeElAttarVidyasagarDuttaFunction
El-Attar-Vidyasagar-Dutta Function

Description

This function is based on the formula

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2 - 10)^2 + (\mathbf{x}_1 + \mathbf{x}_2^2 - 7)^2 + (\mathbf{x}_1^2 + \mathbf{x}_2^3 - 1)^2$$

subject to $\mathbf{x}_i \in [-500, 500], i = 1, 2$.

Usage

makeElAttarVidyasagarDuttaFunction()

Value

smoof_single_objective_function

References

R. A. El-Attar, M. Vidyasagar, S. R. K. Dutta, An Algorithm for II-norm Minimization With Application to Nonlinear II-approximation, SIAM Journal on Numerical Analysis, vol. 16, no. 1, pp. 70-86, 1979.

makeEngvallFunction *Complex function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = (x_1^4 + x_2^4 + 2x_1^2x_2^2 - 4x_1 + 3$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-2000, 2000]$.

Usage

makeEngvallFunction()

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/116-engvall-s-function>.

 makeExponentialFunction

Exponential Function

Description

This scalable test function is based on the definition

$$f(\mathbf{x}) = -\exp\left(-0.5 \sum_{i=1}^n x_i^2\right)$$

with the box-constraints $x_i \in [-1, 1], i = 1, \dots, n$.

Usage

makeExponentialFunction(dimensions)

Arguments

dimensions [integer(1)]
 Size of corresponding parameter space.

Value

smoof_single_objective_function

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, Opposition-Based Differential Evolution (ODE) with Variable Jumping Rate, IEEE Symposium Foundations Com- putation Intelligence, Honolulu, HI, pp. 81-88, 2007.

 makeFreudensteinRothFunction

Freudenstein Roth Function

Description

This test function is based on the formula

$$f(\mathbf{x}) = (x_1 - 13 + ((5 - x_2)x_2 - 2)x_2)^2 + (x_1 - 29 + ((x_2 + 1)x_2 - 14)x_2)^2$$

subject to $x_i \in [-10, 10], i = 1, 2$.

Usage

makeFreudensteinRothFunction()

Value

smoof_single_objective_function

References

S. S. Rao, Engineering Optimization: Theory and Practice, John Wiley & Sons, 2009.

makeFunctionsByName	<i>Generate smoof function by passing a character vector of generator names.</i>
---------------------	--

Description

This function is especially useful in combination with [filterFunctionsByTags](#) to generate a test set of functions with certain properties, e.g., multimodality.

Usage

```
makeFunctionsByName(fun.names, ...)
```

Arguments

fun.names	[character] Non empty character vector of generator function names.
...	[any] Further arguments passed to generator.

Value

smoof_function

See Also

[filterFunctionsByTags](#)

Examples

```
# generate a testset of multimodal 2D functions  
test.set = makeFunctionsByName(filterFunctionsByTags("multimodal"), dimensions = 2L)
```

makeGeneralizedDropWaveFunction
Generalized Drop-Wave Function

Description

Multimodal single-objective function following the formula:

$$\mathbf{x} = -\frac{1 + \cos(\sqrt{\sum_{i=1}^n \mathbf{x}_i^2})}{2 + 0.5 \sum_{i=1}^n \mathbf{x}_i^2}$$

with $\mathbf{x}_i \in [-5.12, 5.12], i = 1, \dots, n$.

Usage

makeGeneralizedDropWaveFunction(dimensions = 2L)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

makeGiuntaFunction *Giunta Function*

Description

Multimodal test function based on the definition

$$f(\mathbf{x}) = 0.6 + \sum_{i=1}^n \left[\sin\left(\frac{16}{15}\mathbf{x}_i - 1\right) + \sin^2\left(\frac{16}{15}\mathbf{x}_i - 1\right) + \frac{1}{50} \sin\left(4\left(\frac{16}{15}\mathbf{x}_i - 1\right)\right) \right]$$

with box-constraints $\mathbf{x}_i \in [-1, 1]$ for $i = 1, \dots, n$.

Usage

makeGiuntaFunction()

Value

smoof_single_objective_function

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

makeGoldsteinPriceFunction
Goldstein-Price Function

Description

Two-dimensional test function for global optimization. The implementation follows the formula:

$$f(\mathbf{x}) = (1 + (\mathbf{x}_1 + \mathbf{x}_2 + 1))^2 \cdot (19 - 14\mathbf{x}_1 + 3\mathbf{x}_1^2 - 14\mathbf{x}_2 + 6\mathbf{x}_1\mathbf{x}_2 + 3\mathbf{x}_2^2) \cdot (30 + (2\mathbf{x}_1 - 3\mathbf{x}_2)^2) \cdot (18 - 32\mathbf{x}_1 + 12\mathbf{x}_2)$$

with $\mathbf{x}_i \in [-2, 2], i = 1, 2$.

Usage

```
makeGoldsteinPriceFunction()
```

Value

smoof_single_objective_function

References

Goldstein, A. A. and Price, I. F.: On descent from local minima. Math. Comput., Vol. 25, No. 115, 1971.

makeGOMOPFunction *GOMOP function generator.*

Description

Construct a multi-objective function by putting together multiple single-objective smoof functions.

Usage

```
makeGOMOPFunction(dimensions = 2L, funs = list())
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
funs	[list] List of single-objective smoof functions.

Details

The decision space of the resulting function is restricted to $[0, 1]^d$. Each parameter x is stretched for each objective function. I.e., if f_1, \dots, f_n are the single objective smooth functions with box constraints $[l_i, u_i], i = 1, \dots, n$, then

$$f(x) = (f_1(l_1 + x * (u_1 - l_1)), \dots, f_n(l_1 + x * (u_1 - l_1)))$$

for $x \in [0, 1]^d$ where the additions and multiplication are performed component-wise.

Value

smoof_multi_objective_function

makeGriewankFunction *Griewank Function*

Description

Highly multimodal function with a lot of regularly distributed local minima. The corresponding formula is:

$$f(\mathbf{x}) = \sum_{i=1}^n \frac{\mathbf{x}_i^2}{4000} - \prod_{i=1}^n \cos\left(\frac{\mathbf{x}_i}{\sqrt{i}}\right) + 1$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, \dots, n$.

Usage

makeGriewankFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

A. O. Griewank, Generalized Descent for Global Optimization, Journal of Optimization Theory and Applications, vol. 34, no. 1, pp. 11-39, 1981.

makeHansenFunction *Hansen Function*

Description

Test function with multiple global optima based on the definition

$$f(\mathbf{x}) = \sum_{i=1}^4 (i+1) \cos(i\mathbf{x}_1 + i - 1) \sum_{j=1}^4 (j+1) \cos((j+2)\mathbf{x}_2 + j + 1)$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeHansenFunction()

Value

smoof_single_objective_function

References

C. Fraley, Software Performances on Nonlinear lems, Technical Report no. STAN-CS-89-1244, Computer Science, Stanford University, 1989.

makeHimmelblauFunction
Himmelblau Function

Description

Two-dimensional test function based on the function definition

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2 - 11)^2 + (\mathbf{x}_1 + \mathbf{x}_2^2 - 7)^2$$

with box-constraints $\mathbf{x}_i \in [-5, 5], i = 1, 2$.

Usage

makeHimmelblauFunction()

Value

smoof_single_objective_function

References

D. M. Himmelblau, Applied Nonlinear Programming, McGraw-Hill, 1972.

 makeHolderTableN1Function

Holder Table function N. 1

Description

This multimodal function is defined as

$$f(\mathbf{x}) = - \left| \cos(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp(|1 - \sqrt{\mathbf{x}_1 + \mathbf{x}_2}/\pi|) \right|$$

with box-constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeHolderTableN1Function()

Value

smoof_single_objective_function

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

See Also

[makeHolderTableN2Function](#)

 makeHolderTableN2Function

Holder Table function N. 2

Description

This multimodal function is defined as

$$f(\mathbf{x}) = - \left| \sin(\mathbf{x}_1) \cos(\mathbf{x}_2) \exp(|1 - \sqrt{\mathbf{x}_1 + \mathbf{x}_2}/\pi|) \right|$$

with box-constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeHolderTableN2Function()

Value

smoof_single_objective_function

References

S. K. Mishra, Global Optimization By Differential Evolution and Particle Swarm Methods: Evaluation On Some Benchmark Functions, Munich Research Papers in Economics.

See Also[makeHolderTableN1Function](#)

makeHosakiFunction	<i>Hosaki Function</i>
--------------------	------------------------

Description

Two-dimensional test function f with

$$f(\mathbf{x}) = (1 - 8\mathbf{x}_1 + 7\mathbf{x}_1^2 - 7/3\mathbf{x}_1^3 + 1/4\mathbf{x}_1^4)\mathbf{x}_2^2 e^{-\mathbf{x}_2}$$

subject to $0 \leq \mathbf{x}_1 \leq 5$ and $0 \leq \mathbf{x}_2 \leq 6$.

Usage

makeHosakiFunction()

Value

smoof_single_objective_function

References

G. A. Bekey, M. T. Ung, A Comparative Evaluation of Two Global Search Algorithms, IEEE Transaction on Systems, Man and Cybernetics, vol. 4, no. 1, pp. 112- 116, 1974.

makeHyperEllipsoidFunction

Hyper-Ellipsoid function

Description

Unimodal, convex test function similar to the Sphere function (see [makeSphereFunction](#)). Calculated via the formula:

$$f(\mathbf{x}) = \sum_{i=1}^n i \cdot \mathbf{x}_i.$$

Usage

makeHyperEllipsoidFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

makeJennrichSampsonFunction

Jennrich-Sampson function.

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = \sum_{i=1}^{10} [2 + 2i - (e^{ix_1} + e^{ix_2})]^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-1, 1]$.

Usage

makeJennrichSampsonFunction()

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/134-jennrich-sampson-s-function>.

makeJudgeFunction *Judge function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = \sum_{i=1}^{20} [(x_1 + B_i x_2 + C_i x_2^2) - A_i]^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-10, 10]$. For details on A, B, C see the referenced website.

Usage

makeJudgeFunction()

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/133-judge-s-function>.

makeKeaneFunction *Keane Function*

Description

Two-dimensional test function based on the definition

$$f(\mathbf{x}) = \frac{\sin^2(\mathbf{x}_1 - \mathbf{x}_2) \sin^2(\mathbf{x}_1 + \mathbf{x}_2)}{\sqrt{\mathbf{x}_1^2 + \mathbf{x}_2^2}}.$$

The domain of definition is bounded by the box constraints $\mathbf{x}_i \in [0, 10], i = 1, 2$.

Usage

makeKeaneFunction()

Value

smoof_single_objective_function

makeKearfottFunction *Kearfott function.*

Description

Two-dimensional test function based on the formula

$$f(\mathbf{x}) = (x_1^2 + x_2^2 - 2)^2 + (x_1^2 - x_2^2 - 1)^2$$

with $\mathbf{x}_1, \mathbf{x}_2 \in [-3, 4]$.

Usage

makeKearfottFunction()

Value

smoof_single_objective_function

References

See <http://al-roomi.org/benchmarks/unconstrained/2-dimensions/59-kearfott-s-function>.

makeLeonFunction *Leon Function*

Description

The function is based on the definition

$$f(\mathbf{x}) = 100(\mathbf{x}_2 - \mathbf{x}_1^2)^2 + (1 - \mathbf{x}_1)^2$$

. Box-constraints: $\mathbf{x}_i \in [-1.2, 1.2]$ for $i = 1, 2$.

Usage

makeLeonFunction()

Value

smoof_single_objective_function

References

A. Lavi, T. P. Vogel (eds), Recent Advances in Optimization Techniques, John Wiley & Sons, 1966.

makeMatyasFunction *Matyas Function*

Description

Two-dimensional, unimodal test function

$$f(\mathbf{x}) = 0.26(\mathbf{x}_1^2 + \mathbf{x}_2^2) - 0.48\mathbf{x}_1\mathbf{x}_2$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makeMatyasFunction()

Value

smoof_single_objective_function

References

A.-R. Hedar, Global Optimization Test Problems.

makeMcCormickFunction *McCormick Function*

Description

Two-dimensional, multimodal test function. The definition is given by

$$f(\mathbf{x}) = \sin(\mathbf{x}_1 + \mathbf{x}_2) + (\mathbf{x}_1 - \mathbf{x}_2)^2 - 1.5\mathbf{x}_1 + 2.5\mathbf{x}_2 + 1$$

subject to $\mathbf{x}_1 \in [-1.5, 4], \mathbf{x}_2 \in [-3, 3]$.

Usage

makeMcCormickFunction()

Value

smoof_single_objective_function

References

F. A. Lootsma (ed.), Numerical Methods for Non-Linear Optimization, Academic Press, 1972.

`makeMichalewiczFunction`*Michalewicz Function*

Description

Highly multimodal single-objective test function with $n!$ local minima with the formula:

$$f(\mathbf{x}) = - \sum_{i=1}^n \sin(\mathbf{x}_i) \cdot \left(\sin \left(\frac{i \cdot \mathbf{x}_i}{\pi} \right) \right)^{2m} .$$

The recommended value $m = 10$, which is used as a default in the implementation.

Usage

```
makeMichalewiczFunction(dimensions, m = 10)
```

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
m	[integer(1)] “Steepness” parameter.

Value

smoof_single_objective_function

Note

The location of the global optimum s varying based on both the dimension and m parameter and is thus not provided in the implementation.

References

Michalewicz, Z.: Genetic Algorithms + Data Structures = Evolution Programs. Berlin, Heidelberg, New York: Springer-Verlag, 1992.

makeMOP1Function *MOP1 function generator.*

Description

MOP1 function from Van Valedhuizen's test suite.

Usage

```
makeMOP1Function()
```

Value

smoof_multi_objective_function

References

J. D. Schaffer, "Multiple objective optimization with vector evaluated genetic algorithms," in Proc. 1st Int. Conf. Genetic Algorithms and Their Applications, J. J. Grenfenstett, Ed., 1985, pp. 93-100.

makeMOP2Function *MOP2 function generator.*

Description

MOP2 function from Van Valedhuizen's test suite due to Fonseca and Fleming.

Usage

```
makeMOP2Function(dimensions = 2L)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_multi_objective_function

References

C. M. Fonseca and P. J. Fleming, "Multiobjective genetic algorithms made easy: Selection, sharing and mating restriction," Genetic Algorithms in Engineering Systems: Innovations and Applications, pp. 45-52, Sep. 1995. IEE.

makeMOP3Function *MOP3 function generator.*

Description

MOP3 function from Van Valedhuizen's test suite.

Usage

```
makeMOP3Function(dimensions = 2L)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_multi_objective_function

References

C. Poloni, G. Mosetti, and S. Contessi, "Multi objective optimization by GAs: Application to system and component design," in Proc. Comput. Methods in Applied Sciences'96: Invited Lectures and Special Technological Sessions of the 3rd ECCOMAS Comput. Fluid Dynamics Conf. and the 2nd ECCOMAS Conf. Numerical Methods in Engineering, Sep. 1996, pp. 258-264

makeMOP4Function *MOP4 function generator.*

Description

MOP4 function from Van Valedhuizen's test suite based on Kursawe.

Usage

```
makeMOP4Function()
```

Value

smoof_multi_objective_function

References

F. Kursawe, "A variant of evolution strategies for vector optimization," in Lecture Notes in Computer Science, H.-P. Schwefel and R. Maenner, Eds. Berlin, Germany: Springer-Verlag, 1991, vol. 496, Proc. Parallel Problem Solving From Nature. 1st Workshop, PPSN I, pp. 193-197.

makeMOP5Function *MOP5 function generator.*

Description

MOP5 function from Van Valedhuizen's test suite.

Usage

makeMOP5Function()

Value

smoof_multi_objective_function

Note

Original box constraints where $[-3, 3]$.

References

R. Viennet, C. Fonteix, and I. Marc, "Multicriteria optimization using a genetic algorithm for determining a Pareto set," *Int. J. Syst. Sci.*, vol. 27, no. 2, pp. 255-260, 1996

makeMOP6Function *MOP6 function generator.*

Description

MOP6 function from Van Valedhuizen's test suite.

Usage

makeMOP6Function()

Value

smoof_multi_objective_function

makeMOP7Function	<i>MOP7 function generator.</i>
------------------	---------------------------------

Description

MOP7 function from Van Valedhuizen's test suite.

Usage

```
makeMOP7Function()
```

Value

smoof_multi_objective_function

References

R. Viennet, C. Fonteix, and I. Marc, "Multicriteria optimization using a genetic algorithm for determining a Pareto set," *Int. J. Syst. Sci.*, vol. 27, no. 2, pp. 255-260, 1996

makeMPM2Function	<i>Generator for function with multiple peaks following the multiple peaks model 2.</i>
------------------	---

Description

Generator for function with multiple peaks following the multiple peaks model 2.

Usage

```
makeMPM2Function(n.peaks, dimensions, topology, seed, rotated = TRUE,  
  peak.shape = "ellipse")
```

Arguments

n.peaks	[integer(1)] Desired number of peaks, i. e., number of (local) optima.
dimensions	[integer(1)] Size of corresponding parameter space.
topology	[character(1)] Type of topology. Possible values are "random" and "funnel".
seed	[integer(1)] Seed for the random numbers generator.

rotated	[logical(1)] Should the peak shapes be rotated? This parameter is only relevant in case of elliptically shaped peaks.
peak.shape	[character(1)] Shape of peak(s). Possible values are “ellipse” and “sphere”.

Value

smoof_single_objective_function

Author(s)

R interface by Jakob Bossek. Original python code provided by the Simon Wessing.

References

See the [technical report](#) of multiple peaks model 2 for an in-depth description of the underlying algorithm.

Examples

```
## Not run:
fn = makeMPM2Function(n.peaks = 10L, dimensions = 2L,
  topology = "funnel", seed = 123, rotated = TRUE, peak.shape = "ellipse")
if (require(plot3D)) {
  plot3D(fn)
}

## End(Not run)
## Not run:
fn = makeMPM2Function(n.peaks = 5L, dimensions = 2L,
  topology = "random", seed = 134, rotated = FALSE)
plot(fn, render.levels = TRUE)

## End(Not run)
```

makeMultiObjectiveFunction

Generator for multi-objective target functions.

Description

Generator for multi-objective target functions.

Usage

```
makeMultiObjectiveFunction(name = NULL, id = NULL, description = NULL, fn,
  has.simple.signature = TRUE, par.set, n.objectives, noisy = FALSE,
  fn.mean = NULL, minimize = rep(TRUE, n.objectives), vectorized = FALSE,
  constraint.fn = NULL, ref.point = NULL)
```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
has.simple.signature	[logical(1)] Set this to TRUE if the objective function expects a vector as input and FALSE if it expects a named list of values. The latter is needed if the function depends on mixed parameters. Default is TRUE.
par.set	[ParamSet] Parameter set describing different aspects of the objective function parameters, i.e., names, lower and/or upper bounds, types and so on. See makeParamSet for further information.
n.objectives	[integer(1)] Number of objectives of the multi-objective function.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical] Logical vector of length n.objectives indicating if the corresponding objectives shall be minimized or maximized. Default is the vector with all components set to TRUE.
vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.

ref.point [numeric]
 Optional reference point in the objective space, e.g., for hypervolume computation.

Value

function Target function with additional stuff attached as attributes.

Examples

```
fn = makeMultiObjectiveFunction(
  name = "My test function",
  fn = function(x) c(sum(x^2), exp(x)),
  n.objectives = 2L,
  par.set = makeNumericParamSet("x", len = 1L, lower = -5L, upper = 5L)
)
print(fn)
```

makePeriodicFunction *Periodic Function*

Description

Single-objective two-dimensional test function. The formula is given as

$$f(\mathbf{x}) = 1 + \sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2) - 0.1e^{-(\mathbf{x}_1^2 + \mathbf{x}_2^2)}$$

subject to the constraints $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

```
makePeriodicFunction()
```

Value

smoof_single_objective_function

References

M. M. Ali, C. Khompatraporn, Z. B. Zabinsky, A Numerical Evaluation of Several Stochastic Algorithms on Selected Continuous Global Optimization Test Problems, Journal of Global Optimization, vol. 31, pp. 635-672, 2005.

makePowellSumFunction *Powell-Sum Function*

Description

The formula that underlies the implementation is given by

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i|^{i+1}$$

with $\mathbf{x}_i \in [-1, 1], i = 1, \dots, n$.

Usage

makePowellSumFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

S. Rahnamyan, H. R. Tizhoosh, N. M. M. Salama, A Novel Population Initialization Method for Accelerating Evolutionary Algorithms, *Computers and Mathematics with Applications*, vol. 53, no. 10, pp. 1605-1614, 2007.

makePriceN1Function *Price Function N. 1*

Description

Second function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = (|\mathbf{x}_1| - 5)^2 + (|\mathbf{x}_2 - 5|)^2$$

subject to $\mathbf{x}_i \in [-500, 500], i = 1, 2$.

Usage

makePriceN1Function()

Value

smoof_single_objective_function

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN2Function](#), [makePriceN4Function](#)

makePriceN2Function *Price Function N. 2*

Description

Second function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = 1 + \sin^2(\mathbf{x}_1) + \sin^2(\mathbf{x}_2) - 0.1 \exp(-\mathbf{x}^2 - \mathbf{x}_2^2)$$

subject to $\mathbf{x}_i \in [-10, 10], i = 1, 2$.

Usage

makePriceN2Function()

Value

smoof_single_objective_function

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN1Function](#), [makePriceN4Function](#)

makePriceN4Function *Price Function N. 4*

Description

Fourth function by Price. The implementation is based on the definition

$$f(\mathbf{x}) = (2\mathbf{x}_1^3\mathbf{x}_2 - \mathbf{x}_2^3)^2 + (6\mathbf{x}_1 - \mathbf{x}_2^2 + \mathbf{x}_2)^2$$

subject to $\mathbf{x}_i \in [-500, 500]$.

Usage

makePriceN4Function()

Value

smoof_single_objective_function

References

W. L. Price, A Controlled Random Search Procedure for Global Optimisation, Computer journal, vol. 20, no. 4, pp. 367-370, 1977.

See Also

[makePriceN1Function](#), [makePriceN2Function](#)

makeRastriginFunction *Rastrigin Function*

Description

One of the most popular single-objective test functions consists of many local optima and is thus highly multimodal with a global structure. The implementation follows the formula

$$f(\mathbf{x}) = 10n + \sum_{i=1}^n (\mathbf{x}_i^2 - 10 \cos(2\pi\mathbf{x}_i)).$$

The box-constraints are given by $\mathbf{x}_i \in [-5.12, 5.12]$ for $i = 1, \dots, n$.

Usage

makeRastriginFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

L. A. Rastrigin. Extremal control systems. Theoretical Foundations of Engineering Cybernetics Series. Nauka, Moscow, 1974.

makeRosenbrockFunction

Rosenbrock Function

Description

Also known as the “De Jong’s function 2” or the “(Rosenbrock) banana/valley function” due to its shape. The global optimum is located within a large flat valley and thus it is hard for optimization algorithms to find it. The following formula underlies the implementation:

$$f(\mathbf{x}) = \sum_{i=1}^{n-1} 100 \cdot (\mathbf{x}_{i+1} - \mathbf{x}_i^2)^2 + (1 - \mathbf{x}_i)^2.$$

The domain is given by the constraints $\mathbf{x}_i \in [-30, 30], i = 1, \dots, n$.

Usage

makeRosenbrockFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

H. H. Rosenbrock, An Automatic Method for Finding the Greatest or least Value of a Function, Computer Journal, vol. 3, no. 3, pp. 175-184, 1960.

 makeSchafferN2Function

Modified Schaffer Function N. 2

Description

Second function by Schaffer. The definition is given by the formula

$$f(\mathbf{x}) = 0.5 + \frac{\sin^2(\mathbf{x}_1^2 - \mathbf{x}_2^2) - 0.5}{(1 + 0.001(\mathbf{x}_1^2 + \mathbf{x}_2^2))^2}$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

makeSchafferN2Function()

Value

smoof_single_objective_function

References

S. K. Mishra, Some New Test Functions For Global Optimization And Performance of Repulsive Particle Swarm Method.

 makeSchafferN4Function

Schaffer Function N. 4

Description

Second function by Schaffer. The definition is given by the formula

$$f(\mathbf{x}) = 0.5 + \frac{\cos^2(\sin(|\mathbf{x}_1^2 - \mathbf{x}_2^2|)) - 0.5}{(1 + 0.001(\mathbf{x}_1^2 + \mathbf{x}_2^2))^2}$$

subject to $\mathbf{x}_i \in [-100, 100], i = 1, 2$.

Usage

makeSchafferN4Function()

Value

smoof_single_objective_function

References

S. K. Mishra, Some New Test Functions For Global Optimization And Performance of Repulsive Particle Swarm Method.

makeSchwefelFunction *Schwefel function*

Description

Highly multimodal test function. The cursial thing about this function is, that the global optimum is far away from the next best local optimum. The function is computed via:

$$f(\mathbf{x}) = \sum_{i=1}^n -x_i \sin\left(\sqrt{|x_i|}\right)$$

with $x_i \in [-500, 500], i = 1, \dots, n$.

Usage

makeSchwefelFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

Schwefel, H.-P.: Numerical optimization of computer models. Chichester: Wiley & Sons, 1981.

makeShubertFunction *Shubert Function*

Description

The defintion of this two-dimensional function is given by

$$f(\mathbf{x}) = \prod_{i=1}^2 \left(\sum_{j=1}^5 \cos((j+1)x_i + j) \right)$$

subject to $x_i \in [-10, 10], i = 1, 2$.

Usage

```
makeShubertFunction()
```

Value

smoof_single_objective_function

References

J. P. Hennart (ed.), Numerical Analysis, Proc. 3rd AS Workshop, Lecture Notes in Mathematics, vol. 90, Springer, 1982.

```
makeSingleObjectiveFunction
```

Generator for single-objective target functions.

Description

Generator for single-objective target functions.

Usage

```
makeSingleObjectiveFunction(name = NULL, id = NULL, description = NULL,
  fn, has.simple.signature = TRUE, vectorized = FALSE, par.set,
  noisy = FALSE, fn.mean = NULL, minimize = TRUE, constraint.fn = NULL,
  tags = character(0), global.opt.params = NULL, global.opt.value = NULL,
  local.opt.params = NULL, local.opt.values = NULL)
```

Arguments

name	[character(1)] Function name. Used for the title of plots for example.
id	[character(1) NULL] Optional short function identifier. If provided, this should be a short name without whitespaces and now special characters beside the underscore. Default is NULL, which means no ID at all.
description	[character(1) NULL] Optional function description.
fn	[function] Objective function.
has.simple.signature	[logical(1)] Set this to TRUE if the objective function expects a vector as input and FALSE if it expects a named list of values. The latter is needed if the function depends on mixed parameters. Default is TRUE.

vectorized	[logical(1)] Can the objective function handle “vector” input, i.e., does it accept matrix of parameters? Default is FALSE.
par.set	[ParamSet] Parameter set describing different aspects of the objective function parameters, i.e., names, lower and/or upper bounds, types and so on. See makeParamSet for further information.
noisy	[logical(1)] Is the function noisy? Defaults to FALSE.
fn.mean	[function] Optional true mean function in case of a noisy objective function. This functions should have the same mean as fn.
minimize	[logical(1)] Set this to TRUE if the function should be minimized and to FALSE otherwise. The default is TRUE.
constraint.fn	[function NULL] Function which returns a logical vector indicating whether certain conditions are met or not. Default is NULL, which means, that there are no constraints beside possible box constraints defined via the par.set argument.
tags	[character] Optional character vector of tags or keywords which characterize the function, e.g. “unimodal”, “separable”. See getAvailableTags for a character vector of allowed tags.
global.opt.params	[list numeric data.frame matrix NULL] Default is NULL which means unknown. Passing a numeric vector will be the most frequent case (numeric only functions). In this case there is only a single global optimum. If there are multiple global optima, passing a numeric matrix is the best choice. Passing a list or a data.frame is necessary if your function is mixed, e.g., it expects both numeric and discrete parameters. Internally, however, each representation is casted to a data.frame for reasons of consistency.
global.opt.value	[numeric(1) NULL] Global optimum value if known. Default is NULL, which means unknown. If only the global.opt.params are passed, the value is computed automatically.
local.opt.params	[list numeric data.frame matrix NULL] Default is NULL, which means the function has no local optima or they are unknown. For details see the description of global.opt.params.
local.opt.values	[numeric NULL] Value(s) of local optima. Default is NULL, which means unknown. If only the local.opt.params are passed, the values are computed automatically.

Value

function Objective function with additional stuff attached as attributes.

Examples

```

library(ggplot2)

fn = makeSingleObjectiveFunction(
  name = "Sphere Function",
  fn = function(x) sum(x^2),
  par.set = makeNumericParamSet("x", len = 1L, lower = -5L, upper = 5L),
  global.opt.params = list(x = 0)
)
print(fn)
print(autoplot(fn))

fn.num2 = makeSingleObjectiveFunction(
  name = "Numeric 2D",
  fn = function(x) sum(x^2),
  par.set = makeParamSet(
    makeNumericParam("x1", lower = -5, upper = 5),
    makeNumericParam("x2", lower = -10, upper = 20)
  )
)
print(fn)
print(autoplot(fn))

fn.mixed = makeSingleObjectiveFunction(
  name = "Mixed 2D",
  fn = function(x) x$num1^2 + as.integer(as.character(x$disc1) == "a"),
  has.simple.signature = FALSE,
  par.set = makeParamSet(
    makeNumericParam("num1", lower = -5, upper = 5),
    makeDiscreteParam("disc1", values = c("a", "b"))
  ),
  global.opt.params = list(num1 = 0, disc1 = "b")
)
print(fn)
print(autoplot(fn))

```

makeSixHumpCamelFunction

Three-Hump Camel Function

Description

Two dimensional single-objective test function with six local minima oh which two are global. The surface is similar to the back of a camel. That is why it is called Camel function. The implementation is based on the formula:

$$f(\mathbf{x}) = (4 - 2.1\mathbf{x}_1^2 + \mathbf{x}_1^{0.75}) \mathbf{x}_1^2 + \mathbf{x}_1\mathbf{x}_2 + (-4 + 4\mathbf{x}_2^2) \mathbf{x}_2^2$$

with box constraints $\mathbf{x}_1 \in [-3, 3]$ and $\mathbf{x}_2 \in [-2, 2]$.

Usage

```
makeSixHumpCamelFunction()
```

Value

smoof_single_objective_function

References

Dixon, L. C. W. and Szego, G. P.: The optimization problem: An introduction. In: Towards Global Optimization II, New York: North Holland, 1978.

makeSphereFunction *Sphere Function*

Description

Also known as the the “De Jong function 1”. Convex, continuous function calculated via the formula

$$f(\mathbf{x}) = \sum_{i=1}^n \mathbf{x}_i^2$$

with box-constraints $\mathbf{x}_i \in [-5.12, 5.12], i = 1, \dots, n$.

Usage

```
makeSphereFunction(dimensions)
```

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

References

M. A. Schumer, K. Steiglitz, Adaptive Step Size Random Search, IEEE Transactions on Automatic Control. vol. 13, no. 3, pp. 270-276, 1968.

makeStyblinskiTangFunction
Styblinski-Tang function

Description

This function is based on the definition

$$f(\mathbf{x}) = \frac{1}{2} \sum_{i=1}^2 (\mathbf{x}_i^4 - 16\mathbf{x}_i^2 + 5\mathbf{x}_i)$$

with box-constraints given by $\mathbf{x}_i \in [-5, 5], i = 1, 2$.

Usage

makeStyblinskiTangFunction()

Value

smoof_single_objective_function

References

Z. K. Silagadze, Finding Two-Dimensional Peaks, Physics of Particles and Nuclei Letters, vol. 4, no. 1, pp. 73-80, 2007.

makeSumOfDifferentSquaresFunction
Sum of Different Squares Function

Description

Simple unimodal test function similar to the Sphere and Hyper-Ellipsoidal functions. Formula:

$$f(\mathbf{x}) = \sum_{i=1}^n |\mathbf{x}_i|^{i+1}.$$

Usage

makeSumOfDifferentSquaresFunction(dimensions)

Arguments

dimensions [integer(1)]
Size of corresponding parameter space.

Value

smoof_single_objective_function

 makeSwiler2014Function

Swiler2014 function.

Description

Mixed parameter space with one discrete parameter $x_1 \in \{1, 2, 3, 4, 5\}$ and two numerical parameters $x_2, x_3 \in [0, 1]$. The function is defined as follows:

$$f(\mathbf{x}) = \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) \text{ if } x_1 = 1 \quad \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) + 12 \sin(2\pi x_3 - \pi) \text{ if } x_1 = 2 \quad \sin(2\pi x_3 - \pi) + 7 \sin^2(2\pi x_2 - \pi) + 12 \sin(2\pi x_3 - \pi) + 12 \sin(2\pi x_2 - \pi) \text{ if } x_1 = 3$$

Usage

```
makeSwiler2014Function()
```

Value

smoof_single_objective_function

makeThreeHumpCamelFunction

Three-Hump Camel Function

Description

This two-dimensional function is based on the definition

$$f(\mathbf{x}) = 2\mathbf{x}_1^2 - 1.05\mathbf{x}_1^4 + \frac{\mathbf{x}_1^6}{6} + \mathbf{x}_1\mathbf{x}_2 + \mathbf{x}_2^2$$

subject to $-5 \leq \mathbf{x}_i \leq 5$.

Usage

```
makeThreeHumpCamelFunction()
```

Value

smoof_single_objective_function

References

F. H. Branin Jr., Widely Convergent Method of Finding Multiple Solutions of Simultaneous Non-linear Equations, IBM Journal of Research and Development, vol. 16, no. 5, pp. 504-522, 1972.

makeTrecanniFunction *Trecanni Function*

Description

The Trecanni function belongs to the unimodal test functions. It is based on the formula

$$f((x)) = (x)_1^4 - 4(x)_1^3 + 4(x)_1 + (x)_2^2.$$

The box-constraints $\mathbf{x}_i \in [-5, 5], i = 1, 2$ define the domain of definition.

Usage

makeTrecanniFunction()

Value

smoof_single_objective_function

References

L. C. W. Dixon, G. P. Szego (eds.), Towards Global Optimization 2, Elsevier, 1978.

makeUFFunction *Generator for the functions UF1, ..., UF10 of the CEC 2009.*

Description

Generator for the functions UF1, ..., UF10 of the CEC 2009.

Usage

makeUFFunction(dimensions, id)

Arguments

dimensions	[integer(1)] Size of corresponding parameter space.
id	[integer(1)] Instance identifier. Integer value between 1 and 10.

Value

smoof_single_objective_function

Note

The implementation is based on the original CPP implemenation by Qingfu Zhang, Aimin Zhou, Shizheng Zhaoy, Ponnuthurai Nagaratnam Suganthany, Wudong Liu and Santosh Tiwar.

Author(s)

Jakob Bossek <j.bossek@gmail.com>

makeViennetFunction *Viennet function generator*

Description

The Viennet test problem VNT is designed for three objectives only. It has a discrete set of Pareto fronts. It is defined by the following formulae.

$$f(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}), f_3(\mathbf{x}))$$

with

$$f_1(\mathbf{x}) = 0.5(\mathbf{x}_1^2 + \mathbf{x}_2^2) + \sin(\mathbf{x}_1^2 + \mathbf{x}_2^2)$$

$$f_2(\mathbf{x}) = \frac{(3\mathbf{x}_1 + 2\mathbf{x}_2 + 4)^2}{8} + \frac{(\mathbf{x}_1 - \mathbf{x}_2 + 1)^2}{27} + 15$$

$$f_3(\mathbf{x}) = \frac{1}{\mathbf{x}_1^2 + \mathbf{x}_2^2 + 1} - 1.1 \exp(-(\mathbf{x}_1^1 + \mathbf{x}_2^2))$$

with box constraints $-3 \leq \mathbf{x}_1, \mathbf{x}_2 \leq 3$.

Usage

makeViennetFunction()

Value

smoof_multi_objective_function

References

Viennet, R. (1996). Multicriteria optimization using a genetic algorithm for determining the Pareto set. *International Journal of Systems Science* 27 (2), 255-260.

makeZDT1Function	ZDT1 Function
------------------	---------------

Description

Builds and returns the two-objective ZDT1 test problem. For m objective it is defined as follows:

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \sqrt{\frac{f_1}{g}}$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$

Usage

makeZDT1Function(dimensions)

Arguments

dimensions [integer(1)]
 Number of decision variables.

Value

smoof_multi_objective_function

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT2Function	<i>ZDT2 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT2 test problem. The function is nonconvex and resembles the ZDT1 function. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \left(\frac{f_1}{g}\right)^2$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$

Usage

```
makeZDT2Function(dimensions)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
------------	---

Value

```
smoof_multi_objective_function
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT3Function	ZDT3 Function
------------------	---------------

Description

Builds and returns the two-objective ZDT3 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + \frac{9}{m-1} \sum_{i=2}^m \mathbf{x}_i, h(f_1, g) = 1 - \sqrt{\frac{f_1(\mathbf{x})}{g(\mathbf{x})} - \left(\frac{f_1(\mathbf{x})}{g(\mathbf{x})}\right) \sin(10\pi f_1(\mathbf{x}))}$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function has some discontinuities in the Pareto-optimal front introduced by the sine term in the h function (see above). The front consists of multiple convex parts.

Usage

```
makeZDT3Function(dimensions)
```

Arguments

```
dimensions    [integer(1)]
              Number of decision variables.
```

Value

```
smoof_multi_objective_function
```

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT4Function	<i>ZDT4 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT4 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}_1), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}_1) = \mathbf{x}_1, f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + 10(m - 1) + \sum_{i=2}^m (\mathbf{x}_i^2 - 10 \cos(4\pi\mathbf{x}_i)), h(f_1, g) = 1 - \sqrt{\frac{f_1(\mathbf{x})}{g(\mathbf{x})}}$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function has many Pareto-optimal fronts and is thus suited to test the algorithms ability to tackle multimodal problems.

Usage

```
makeZDT4Function(dimensions)
```

Arguments

dimensions	[integer(1)]	Number of decision variables.
------------	--------------	-------------------------------

Value

smoof_multi_objective_function

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZDT6Function	<i>ZDT6 Function</i>
------------------	----------------------

Description

Builds and returns the two-objective ZDT6 test problem. For m objective it is defined as follows

$$f(\mathbf{x}) = (f_1(\mathbf{x}), f_2(\mathbf{x}))$$

with

$$f_1(\mathbf{x}) = 1 - \exp(-4\mathbf{x}_1) \sin^6(6\pi\mathbf{x}_1), f_2(\mathbf{x}) = g(\mathbf{x})h(f_1(\mathbf{x}_1), g(\mathbf{x}))$$

where

$$g(\mathbf{x}) = 1 + 9 \left(\frac{\sum_{i=2}^m \mathbf{x}_i}{m-1} \right)^{0.25}, h(f_1, g) = 1 - \left(\frac{f_1(\mathbf{x})}{g(\mathbf{x})} \right)^2$$

and $\mathbf{x}_i \in [0, 1], i = 1, \dots, m$. This function introduced two difficulties (see reference): 1. the density of solutions decreases with the closeness to the Pareto-optimal front and 2. the Pareto-optimal solutions are nonuniformly distributed along the front.

Usage

```
makeZDT6Function(dimensions)
```

Arguments

dimensions	[integer(1)] Number of decision variables.
------------	---

Value

smoof_multi_objective_function

References

E. Zitzler, K. Deb, and L. Thiele. Comparison of Multiobjective Evolutionary Algorithms: Empirical Results. *Evolutionary Computation*, 8(2):173-195, 2000

makeZettlFunction	<i>Zettl Function</i>
-------------------	-----------------------

Description

The unimodal Zettl Function is based on the definition

$$f(\mathbf{x}) = (\mathbf{x}_1^2 + \mathbf{x}_2^2 - 2\mathbf{x}_1)^2 + 0.25\mathbf{x}_1$$

with box-constraints $\mathbf{x}_i \in [-5, 10], i = 1, 2$.

Usage

```
makeZettlFunction()
```

Value

smoof_single_objective_function

References

H. P. Schwefel, Evolution and Optimum Seeking, John Wiley Sons, 1995.

plot.smoof_function	Generate ggplot object.
---------------------	---

Description

Generate [ggplot](#) object.

Usage

```
## S3 method for class 'smoof_function'
plot(x, ...)
```

Arguments

x	[smoof_function] Function.
...	[any] Further parameters passed to the corresponding plot functions.

Value

Nothing

plot1DNumeric *Plot an one-dimensional function.*

Description

Plot an one-dimensional function.

Usage

```
plot1DNumeric(x, show.optimum = FALSE, main = getName(x),
  n.samples = 500L, ...)
```

Arguments

x	[smoof_function] Function.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smoof function.
n.samples	[integer(1)] Number of locations to be sampled. Default is 500.
...	[any] Further paramerters passed to plot function.

Value

Nothing

plot2DNumeric *Plot a two-dimensional numeric function.*

Description

Either a contour-plot or a level-plot.

Usage

```
plot2DNumeric(x, show.optimum = FALSE, main = getName(x),
  render.levels = FALSE, render.contours = TRUE, n.samples = 100L, ...)
```


Arguments

x	[smoof_function] Function.
show.optimum	[logical(1)] If the function has a known global optimum, should its location be plotted by a point or multiple points in case of multiple global optima? Default is FALSE.
main	[character(1L)] Plot title. Default is the name of the smoof function.
render.levels	[logical(1)] Show a level-plot? Default is FALSE.
render.contours	[logical(1)] Render contours? Default is TRUE.
n.samples	[integer(1)] Number of locations per dimension to be sampled. Default is 100.
...	[any] Further paramerters passed to image respectively contour function.

Value

Nothing

plot3D *Surface plot of two-dimensional test function.*

Description

Surface plot of two-dimensional test function.

Usage

```
plot3D(x, length.out = 100L, package = "plot3D", ...)
```

Arguments

x	[smoof_function] Two-dimensional snoof function.
length.out	[integer(1)] Determines the “smoothness” of the grid. The higher the value, the smoother the function landscape looks like. However, you should avoid setting this parameter to high, since with the contour option set to TRUE the drawing can take quite a lot of time. Default is 100.

package	[character(1)] String describing the package to use for 3D visualization. At the moment “plot3D” (package plot3D) and “plotly” (package plotly) are supported. The latter opens a highly interactive plot in a web browser and is thus suited well to explore a function by hand. Default is “plot3D”.
...	[any] Further parameters passed to method used for visualization (which is determined by the package argument).

Examples

```
library(plot3D)
fn = makeRastriginFunction(dimensions = 2L)
## Not run:
# use the plot3D::persp3D method (default behaviour)
plot3D(fn)
plot3D(fn, contour = TRUE)
plot3D(fn, image = TRUE, phi = 30)

# use plotly::plot_ly for interactive plot
plot3D(fn, method = "plotly")

## End(Not run)
```

resetEvaluationCounter

Reset evaluation counter.

Description

Reset evaluation counter.

Usage

```
resetEvaluationCounter(fn)
```

Arguments

fn	[smoof_counting_function] Wrapped smoof_function.
----	--

shouldBeMinimized	<i>Check if function should be minimized.</i>
-------------------	---

Description

Functions can have an associated global optimum. In this case one needs to know whether the optimum is a minimum or a maximum.

Usage

```
shouldBeMinimized(fn)
```

Arguments

fn	[smoof_function] Objective function.
----	---

Value

logical Each component indicates whether the corresponding objective should be minimized.

violatesConstraints	<i>Checks whether constraints are violated.</i>
---------------------	---

Description

Checks whether constraints are violated.

Usage

```
violatesConstraints(fn, values)
```

Arguments

fn	[smoof_function] Objective function.
values	[numeric] List of values.

Value

logical(1)

`visualizeParetoOptimalFront`*Pareto-optimal front visualization.*

Description

Quickly visualize the Pareto-optimal front of a bi-criteria objective function by calling the EMOA [nsga2](#) and extracting the approximated Pareto-optimal front.

Usage

```
visualizeParetoOptimalFront(fn, ...)
```

Arguments

<code>fn</code>	[<code>smoof_multi_objective_function</code>] Multi-objective smooof function.
<code>...</code>	[any] Arguments passed to nsga2 .

Value

[ggplot](#)

Examples

```
# Here we visualize the Pareto-optimal front of the bi-objective ZDT3 function
fn = makeZDT3Function(dimensions = 3L)
vis = visualizeParetoOptimalFront(fn)
```

```
# Alternatively we can pass some more algorithm parameters to the NSGA2 algorithm
vis = visualizeParetoOptimalFront(fn, popsize = 1000L)
```

Index

addCountingWrapper, [6](#), [12](#), [21](#), [26](#)
addLoggingWrapper, [7](#), [16](#), [21](#), [26](#)
autoplot.smooof_function, [8](#)

computeExpectedRunningTime, [9](#)
conversion, [11](#)
convertToMaximization (conversion), [11](#)
convertToMinimization (conversion), [11](#)

doesCountEvaluations, [12](#)

filterFunctionsByTags, [12](#), [57](#)

getAvailableTags, [12](#), [13](#), [24](#), [83](#)
getDescription, [13](#)
getGlobalOptimum, [14](#)
getID, [14](#)
getLocalOptimum, [15](#)
getLoggedValues, [15](#)
getLowerBoxConstraints, [16](#)
getMeanFunction, [16](#)
getName, [17](#)
getNumberOfEvaluations, [6](#), [17](#)
getNumberOfObjectives, [18](#)
getNumberOfParameters, [18](#)
getParamSet, [19](#)
getRefPoint, [19](#)
getTags, [20](#)
getUpperBoxConstraints, [20](#)
getWrappedFunction, [21](#)
ggplot, [8](#), [9](#), [95](#), [100](#)

hasBoxConstraints, [21](#)
hasConstraints, [22](#)
hasGlobalOptimum, [22](#)
hasLocalOptimum, [23](#)
hasOtherConstraints, [23](#)
hasTags, [24](#)

isMultiobjective, [24](#)
isNoisy, [25](#)
isSingleobjective, [25](#)
isSmooofFunction, [26](#)
isVectorized, [26](#)
isWrappedSmooofFunction, [27](#)

makeAckleyFunction, [27](#)
makeAdjimanFunction, [28](#)
makeAlpine01Function, [28](#)
makeAlpine02Function, [29](#)
makeAluffiPentiniFunction, [30](#)
makeBartelsConnFunction, [30](#)
makeBB0BFunction, [31](#)
makeBealeFunction, [32](#)
makeBentCigarFunction, [32](#)
makeBirdFunction, [33](#)
makeBiSphereFunction, [33](#)
makeBK1Function, [34](#)
makeBohachevskyN1Function, [34](#)
makeBoothFunction, [35](#)
makeBraninFunction, [35](#)
makeBrentFunction, [36](#)
makeBrownFunction, [37](#)
makeBukinN2Function, [37](#), [38](#), [39](#)
makeBukinN4Function, [38](#), [38](#), [39](#)
makeBukinN6Function, [38](#), [39](#)
makeCarromTableFunction, [39](#)
makeChichinadzeFunction, [40](#)
makeChungReynoldsFunction, [40](#)
makeComplexFunction, [41](#)
makeCosineMixtureFunction, [41](#)
makeCrossInTrayFunction, [42](#)
makeCubeFunction, [43](#)
makeDeckkersAartsFunction, [43](#)
makeDeflectedCorrugatedSpringFunction, [44](#)
makeDentFunction, [44](#)
makeDixonPriceFunction, [45](#)
makeDoubleSumFunction, [46](#)
makeDTLZ1Function, [46](#)
makeDTLZ2Function, [47](#)

makeDTLZ3Function, 48
makeDTLZ4Function, 49
makeDTLZ5Function, 50
makeDTLZ6Function, 51
makeDTLZ7Function, 52
makeEasomFunction, 53
makeEggCrateFunction, 54
makeEggholderFunction, 54
makeElAttarVidyasagarDuttaFunction, 55
makeEngvallFunction, 55
makeExponentialFunction, 56
makeFreudensteinRothFunction, 56
makeFunctionsByName, 57
makeGeneralizedDropWaveFunction, 58
makeGiuntaFunction, 58
makeGoldsteinPriceFunction, 59
makeGOMOPFunction, 59
makeGriewankFunction, 60
makeHansenFunction, 61
makeHimmelblauFunction, 61
makeHolderTableN1Function, 62, 63
makeHolderTableN2Function, 62, 62
makeHosakiFunction, 63
makeHyperEllipsoidFunction, 64
makeJennrichSampsonFunction, 64
makeJudgeFunction, 65
makeKeaneFunction, 65
makeKearfottFunction, 66
makeLeonFunction, 66
makeMatyasFunction, 67
makeMcCormickFunction, 67
makeMichalewiczFunction, 68
makeMOP1Function, 69
makeMOP2Function, 69
makeMOP3Function, 70
makeMOP4Function, 70
makeMOP5Function, 71
makeMOP6Function, 71
makeMOP7Function, 72
makeMPM2Function, 72
makeMultiObjectiveFunction, 73
makeParamSet, 74, 83
makePeriodicFunction, 75
makePowellSumFunction, 76
makePriceN1Function, 76, 77, 78
makePriceN2Function, 77, 77, 78
makePriceN4Function, 77, 78
makeRastriginFunction, 78
makeRosenbrockFunction, 79
makeSchafferN2Function, 80
makeSchafferN4Function, 80
makeSchwefelFunction, 81
makeShubertFunction, 81
makeSingleObjectiveFunction, 82
makeSixHumpCamelFunction, 84
makeSphereFunction, 64, 85
makeStyblinskiTangFunction, 86
makeSumOfDifferentSquaresFunction, 86
makeSwiler2014Function, 87
makeThreeHumpCamelFunction, 87
makeTrecanniFunction, 88
makeUFFFunction, 88
makeViennetFunction, 89
makeZDT1Function, 90
makeZDT2Function, 91
makeZDT3Function, 92
makeZDT4Function, 93
makeZDT6Function, 94
makeZettlFunction, 95

nsga2, 100

ParamSet, 8, 19, 74, 83
plot.smooF_function, 95
plot1DNumeric, 96
plot2DNumeric, 96
plot3D, 97

resetEvaluationCounter, 6, 98

shouldBeMinimized, 99
smooF-package, 5

violatesConstraints, 99
visualizeParetoOptimalFront, 100