

# Package ‘PopGenReport’

May 11, 2016

**Type** Package

**Title** A Simple Framework to Analyse Population Genetic Data

**Version** 2.2.2

**Date** 2016-05-9

**Description** Provides beginner friendly framework to analyse population genetic data. It uses 'knitr' to create comprehensive reports on spatial genetic data. For detailed information how to use the package refer to the comprehensive tutorials or visit [www.popgenreport.org](http://www.popgenreport.org).

**License** GPL

**LazyData** true

**Depends** R (>= 3.0.0), knitr, adegenet (>= 2.0.0), raster

**Imports** lattice, RgoogleMaps, gap, calibrate, xtable, plyr, dismo, reshape, ggplot2, R.utils, ade4, pegas, genetics, rgdal, gdistance, vegan, sp, mmod, GGally, data.table, graphics, grDevices, methods, stats, utils

**VignetteBuilder** knitr

**URL** <https://github.com/green-striped-gecko/PopGenReport>

**Suggests**

**RoxygenNote** 5.0.1

**NeedsCompilation** no

**Author** Bernd Gruber [aut, cre],  
Aaron Adamack [aut]

**Maintainer** Bernd Gruber <[bernd.gruber@canberra.edu.au](mailto:bernd.gruber@canberra.edu.au)>

**Repository** CRAN

**Date/Publication** 2016-05-11 12:06:20

**R topics documented:**

PopGen-package	2
addline	3
addpoly	4
allel.rich	5
allele.dist	6
bilby	7
costdistances	7
emigration	8
fric.raster	8
gd.kosman	9
gd.smouse	10
genleastcost	11
init.poggensim	13
landgen	13
landgenreport	14
lgrMMRR	16
mutation	17
null.all	18
opt.landgen	19
p2p	20
pairwise.fstb	21
popgenreport	21
pops2genind	25
read.genetable	25
reproduction	27
run.poggensim	28
spautocor	29
wassermann	30
<b>Index</b>	<b>32</b>

---

 PopGen-package

*Analysing population genetic data within a simple framework*


---

**Description**

Provides a simple framework for analysing population genetic data (microsatellite data and snp data). The framework is open and meant to be user friendly, so R and its capabilities can be used by non-programmers. We encourage contributions and extensions of the package to allow for more sophisticated analyses of spatial populaiton genetic data. This packages draws heavily on already existing packages such as adegenet, mmod, pegas and others and we would like to thank the creators of those packages for their work in developing those packages.

**Details**

Package: PopGenReport  
Type: Package  
Version: 2.2.2  
Date: 2016-05-09  
License: GPL

The package provides a framework to analyse population genetic data. The main intention is to make the capabilities, which are already there, available to a wider community. Several standard routines are already implemented. We invite other developers and researchers to either recommend new extensions or analyses and to provide additional code that could be included within the existing framework which has a very modular format. The long term aim is to have a widely used standard package that serves as a first step in analyzing population genetic data and to facilitate comparability between studies.

**Author(s)**

Aaraon T. Adamack & Bernd Gruber (2012)

Maintainer: Bernd Gruber, Bernd.Gruber@canberra.edu.au

**References**

Adamack & Gruber (2014). PopGenReport - simplifying basic population genetic analyses in R, *Methods in Ecology and Evolution*, 5, 384 - 387. doi: 10.1111/2041-210X.12158.

Gruber & Adamack (2015). landgenreport: a new R function to simplify landscape genetic analysis using resistance surface layers. *Molecular Ecology Resources*, doi: 10.1111/1755-0998.12381.

**See Also**

[adegenet](#) [mmod](#) [pegas](#)

---

addline

*Function to add lines to landscape*

---

**Description**

adds a line from x1 to x2 to a raster layer

**Usage**

```
addline(r, x1, x2, val, plot = FALSE)
```

**Arguments**

r	raster that represents the landscape
x1	from coordinates
x2	to coordinates
val	resistance value 1 is no resistance
plot	switch if landscape should be plotted

**Value**

returns modified raster layer

---

addpoly                      *Function to add a polygon to a landscape*

---

**Description**

adds a polygon to a raster layer

**Usage**

```
addpoly(r, pol, val, plot = T)
```

**Arguments**

r	raster that represents the landscape
pol	coordinates of the polygon
val	resistance value, One equals no resistance
plot	switch if landscape should be plotted

**Value**

returns modified raster layer

---

`allele.rich`*Calculates the allelic richness for a genind object*

---

### Description

The function calculates the allelic richness for each combination of population and locus for a `genind` object. To account for differences in sample sizes and genotyping success, rarefaction is used in the calculation. The sample size for each combination of population and locus was set equal to the smallest number of alleles seen in a sample across all combinations of population and locus. Allelic richness was calculated using the methods of Mousadik and Petit (1996) which are in turn based upon the work of Hurlbert (1971).

This function is similar to the `allelic.richness` function in `hiefstat`. The main differences between the two packages are that `allele.rich` works on a `genind` object while `allelic.richness` works on a data frame and `allele.rich` is capable of determining allelic richness for species with most ploidies while `allelic.richness` only works for haploid and diploid species.

### Usage

```
allele.rich(population, min.alleles = NULL)
```

### Arguments

<code>population</code>	a <code>genind</code> object (from package <code>adegenet</code> )
<code>min.alleles</code>	the minimum number of alleles that will be sampled for calculating allelic richness. If <code>min.alleles</code> is set to <code>NULL</code> the <code>min.alleles</code> sampled will be determined automatically (see description)

### Value

Returns a list with the following entries:

`all.richness` is the allelic richness for each combination of population and locus `sum.richness` is the sum of the allelic richnesses for each population `mean.richness` is the mean allelic richness across all loci `alleles.sampled` is the smallest number of individuals sampled across all combinations of population and locus multiplied by the ploidy of the species. `pop.sizes` is a matrix with the total number of alleles counted for each combination of population and locus.

### Author(s)

Aaron Adamack, [aaron.adamack@canberra.edu.au](mailto:aaron.adamack@canberra.edu.au)

### References

El Mousadik A, Petit RJ. (1996) High level of genetic differentiation for allelic richness among populations of the argan tree [*Argania spinosa* (L.) Skeels] endemic to Morocco

**See Also**

[popgenreport](#)

**Examples**

```
#not run:
#data(bilby)
#here we use only the first 50 individuals to speed up the example
#popgenreport(bilby, mk.allel.rich=TRUE, mk.pdf=FALSE)

#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby, mk.allel.rich=TRUE, mk.pdf=TRUE)

#data(bilby)
#allel.rich(bilby)
```

---

allele.dist	<i>Counts and visualises allele frequencies across loci and subpopulations</i>
-------------	--

---

**Description**

Counts the number of observations for each combination of allele variant and subpopulation for each locus. Calculates relative allele proportions for each subpopulations and then produces a heatmap using that data.

**Usage**

```
allele.dist(population, mk.figures = TRUE)
```

**Arguments**

population	this is the <a href="#">genind</a> object the analysis will be based on
mk.figures	if set to FALSE no figures are plotted. Default is TRUE.

**Value**

Produces heatmaps of the relative allele frequencies for each subpopulation at each locus and returns a list containing the counts (count) for each combination of allele and subpopulation and the relative frequencies of alleles by subpopulation (frequency) for each locus. The color bars on the heatmaps shows the relative frequency of an allele within a subpopulation for a locus while the histogram gives an overall count for the number of combinations of allele and subpopulation with a relative frequency.

**Author(s)**

Aaron Adamack, aaron.adamack@canberra.edu.au

**See Also**[popgenreport](#)**Examples**

```
# data(bilby)
#here we use only the first 50 individuals to speed up the example
# popgenreport(bilby, mk.allele.dist=TRUE, mk.pdf=FALSE)

#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby, mk.allele.dist=TRUE, mk.pdf=TRUE)
```

---

**bilby***Bilby data set*

---

**Description**

This is a synthetic sample data set (in [genind](#) format) of microsatellite data.

**Usage**

```
data(bilby)
```

**Examples**

```
data(bilby)
bilby
```

---

**costdistances***Calculates cost distances for a given landscape (resistance matrix)*

---

**Description**

calculates a cost distance matrix, to be used with `run.poppensim`

**Usage**

```
costdistances(landscape, locs, method, NN)
```

**Arguments**

landscape	a raster object coding the resistance of the landscape
locs	coordinates of the subpopulations
method	defines the type of cost distance, types are "least-cost", "rSPDistance" or "commute (Circuitscape type)"
NN	number of next neighbours recommendation is 8

**Value**

a costdistance matrix between all pairs of locs

---

emigration	<i>Function to execute emigration on a pops object</i>
------------	--

---

**Description**

emigration process on all population in one go

**Usage**

```
emigration(xp, perc.mig, emi.m, emi.table = NULL)
```

**Arguments**

xp	all pops combined in a list
perc.mig	percentage if migrating individuals
emi.m	emigration probability (normally based on cost dispersal distance)
emi.table	a fixed number of migrating individuals can be specified (overrides emi.m)

**Value**

a list, first entry are updated pops, second entry the number of disperser in a matrix

---

fric.raster	<i>a simulated friction map</i>
-------------	---------------------------------

---

**Description**

This data set is used to demonstrate the use of the [landgenreport](#) and [genleastcost](#) functions. It is a simple raster file, with dimensions of 50 x 50 and now coordinate system.

**Usage**

```
data(fric.raster)
```

**See Also**

[landgenreport](#), [genleastcost](#)

**Examples**

```
require(raster)
data(fric.raster)
plot(fric.raster)
```



---

`gd.kosman`*Individual genetic distance calculation based on Kosman & Leonhard 2005*

---

### Description

Calculates pairwise genetic distances between all individuals using the individual genetic distance measure of Kosman and Leonard (2005). This function is similar to the `dist.codom` in the package `mmod`. The two functions differ in their treatment of individuals with missing data. `dist.codom` omits individuals from the calculation of pairwise individual genetic distances while this function includes individuals with missing data. This is done by simply calculating the mean individual pairwise genetic distance over all loci for which there are values. Note that depending on your computer's capabilities, you may run into memory errors when this function is used on datasets with large numbers of individuals (>1000). Additionally, the time for this function to run can be lengthy. Using a PC with a 3.5 GHz processor to calculate pairwise genetic distances between individuals with 36 diploid loci it took 0.3 seconds for 100 individuals, 5 seconds for 500 individuals, 21 seconds for 1000 individuals, 84 seconds for 2000 individuals, and 194 seconds for 3000 individuals.

### Usage

```
gd.kosman(population)
```

### Arguments

`population` this is the [genind](#) object the analysis will be based on.

### Value

Returns a list with two distance matrices. The first (`geneticdist`) contains pairwise individual genetic distances for each individual within a population, the second (`loci_used`) provides the number of loci that were used to calculate pairwise individual genetic distances between a pair of individuals.

### Author(s)

Aaron Adamack, [aaron.adamack@canberra.edu.au](mailto:aaron.adamack@canberra.edu.au)

### References

Kosman E., Leonard K.J. 2005. Similarity coefficients for molecular markers in studies of genetic relationships between individuals for haploid, diploid, and polyploidy species. *Molecular Ecology* 14:415-424.

### See Also

[popgenreport](#)

**Examples**

```
#not run:
#data(bilby)
#popgenreport(bilby, mk.gd.kosman = TRUE, mk.pdf=FALSE)
#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby, mk.gd.kosman = TRUE, mk.pdf=TRUE)
```

gd.smouse

*Individual genetic distance calculation based on Smouse and Peakall 1999*

**Description**

Calculate pairwise genetic distances between all individuals using the individual genetic distance measure of Smouse and Peakall (1999). This function should produce the same results as the individual genetic distances calculated using GenAIEx and choosing the interpolate missing data option. Note that depending on your computers capabilities, you may run into memory errors when this function is used on datasets with large numbers of individuals (>1000). Additionally, the time for this function to run can be quite lengthy. Using a PC with a 3.5 GHz processor to calculate pairwise genetic distances between individuals with 36 diploid loci it took 2 seconds for 100 individuals, 51 seconds for 500 individuals, 200 seconds for 1000 individuals, 836 seconds (~14 minutes) for 2000 individuals, and 1793 seconds (~30 minutes) for 3000 individuals. Please note that for each of your population groupings there must be at least one individual with genotyped alleles for each locus (it doesn't have to be the same individual for every locus). If a population doesn't meet this requirement, it will be dropped from the analysis and a warning message will be generated.

**Usage**

```
gd.smouse(population, verbose = TRUE)
```

**Arguments**

population	this is the <a href="#">genind</a> object that the analysis will be based on.
verbose	information on progress. For large data sets this could be informative as it allows the user to estimate the amount of time remaining until the function is complete. The counter shows the number of the population for which genetic distances are currently being determined.

**Value**

Returns pairwise individual genetic distances for each individual within a population.

**Author(s)**

Aaron Adamack, aaron.adamack@canberra.edu.au

## References

Smouse PE, Peakall R. 1999. Spatial autocorrelation analysis of individual multiallele and multilocus genetic structure. *Heredity* 82: 561-573.

## See Also

[popgenreport](#)

## Examples

```
#not run:
#data(bilby)
#popgenreport(bilby, mk.gd.smouse = TRUE, mk.pdf=FALSE)
#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby, mk.gd.smouse = TRUE, mk.pdf=TRUE)
```

---

genleastcost

*Least-cost path analysis based on a friction matrix*

---

## Description

This function calculates the pairwise distances (Euclidean, cost path distances and genetic distances) of populations using a friction matrix and a spatial genind object. The genind object needs to have coordinates in the same projected coordinate system as the friction matrix. The friction matrix can be either a single raster or a stack of several layers. If a stack is provided the specified cost distance is calculated for each layer in the stack. The output of this function can be used with the functions [wassermann](#) or [lgrMMRR](#) to test for the significance of a layer on the genetic structure.

## Usage

```
genleastcost(cats, fric.raster, gen.distance, NN=NULL, pathtype="leastcost",
             plotpath=TRUE, theta=1)
```

## Arguments

cats	a spatial genind object. see <code>?popgenreport</code> how to provide coordinates in genind objects
fric.raster	a friction matrix
gen.distance	specification which genetic distance method should be used to calculate pairwise genetic distances between populations ( "D", "Gst.Nei", "Gst.Hedrick") or individuals ("Smouse", "Kosman", "propShared")
NN	Number of neighbours used when calculating the cost distance (possible values 4,8 or 16). As the default is NULL a value has to be provided if <code>pathtype='leastcost'</code> . NN=8 is most commonly used. Be aware that linear structures may cause artefacts in the least-cost paths, therefore inspect the actual least-cost paths in the provided output.

pathtype	Type of cost distance to be calculated (based on function in the <a href="#">gdistance</a> package. Available distances are 'leastcost', 'commute' or 'rSPDistance'. See functions in the gdistance package for further explanations. If the path type is set to 'leastcost' then paths and also pathlength are returned.
plotpath	switch if least cost paths should be plotted (works only if pathtype='leastcost'. Be aware this slows down the computation, but it is recommended to do this to check least cost paths visually.
theta	value needed for rSPDistance function. see <a href="#">rSPDistance</a> in package gdistance.

### Details

to be written

### Value

returns a list that consists of four pairwise distance matrixes (Euclidean, Cost, length of path and genetic) and the actual paths as spatial line objects.

### Author(s)

Bernd Gruber

### References

Cushman, S., Wasserman, T., Landguth, E. and Shirk, A. (2013). Re-Evaluating Causal Modeling with Mantel Tests in Landscape Genetics. *Diversity*, 5(1), 51-72.

Landguth, E. L., Cushman, S. A., Schwartz, M. K., McKelvey, K. S., Murphy, M. and Luikart, G. (2010). Quantifying the lag time to detect barriers in landscape genetics. *Molecular ecology*, 4179-4191.

Wasserman, T. N., Cushman, S. A., Schwartz, M. K. and Wallin, D. O. (2010). Spatial scaling and multi-model inference in landscape genetics: *Martes americana* in northern Idaho. *Landscape Ecology*, 25(10), 1601-1612.

### See Also

[landgenreport](#), [popgenreport](#), [wassermann](#), [lgrMMRR](#)

### Examples

```
## Not run:
glc <- genleastcost(cats=landgen, fric.raster, "D", NN=8)
wassermann(eucl.mat = glc$eucl.mat, cost.mat = glc$cost.mats, gen.mat = glc$gen.mat)
lgrMMRR(gen.mat = glc$gen.mat, cost.mats = glc$cost.mats, eucl.mat = glc$eucl.mat)

## End(Not run)
```

---

init.poggensim	<i>Initialise a pops object fo a a popgen simulation</i>
----------------	--

---

**Description**

initialises a time-forward, agent-based and spatially explicit genetic population simulation

**Usage**

```
init.poggensim(n.pops, n.ind, sex.ratio, n.loci, n.allels, locs, n.cov)
```

**Arguments**

n.pops	number of subpopulations
n.ind	number of individuals per subpopulation
sex.ratio	sex ratio of males and females
n.loci	number of loci
n.allels	number of maximal alleles per loci
locs	coordinates of the subpopulations
n.cov	number of covariates (defaults to 3)

**Value**

a simpops object (to be used in run.poggensim )

---

landgen	<i>A simulated genind data set with spatial coordinates</i>
---------	---

---

**Description**

This data set is used to demonstrate the use of the [landgenreport](#) and [genleastcost](#) functions. It is a simple spatial genind object with 100 individuals in 10 populations and 20 loci with up to 20 alleles per loci.

**Usage**

```
data(landgen)
```

**See Also**

[landgenreport](#), [genleastcost](#)

**Examples**

```
data(landgen)
summary(landgen)
```

---

landgenreport                      *Create a landscape genetic report*

---

### Description

This function is the landscape genetic version of the [popgenreport](#) function. It needs to be provided with a `genind` object with spatial coordinates, a friction map (raster) and a specification which type of genetic distance should be used. Once all three type of input are provided with the necessary input, a landscape genetic analysis using least cost path analysis is computed (see Cushman et al. 2010, Landguth et al. 2010). Depending on the genetic distance measurement this is done on a subpopulation basis (D, `Gst.Hedrick`, `Gst.Nei=Fst`) or on an individual basis (Kosman, Smouse).

### Usage

```
landgenreport(cats, fric.raster, gen.distance = "Gst.Nei", NN=NULL,
  pathtype="leastcost", plotpath=TRUE, theta=1, mk.resistance = TRUE ,
  mapdotcolor = "blue", mapdotsize=1, mapdotalpha = 0.4, mapdotype = 19,
  mapzoom = NULL, mk.custom = FALSE, fname = "LandGenReport", foldername = "results",
  path.pgr = NULL, mk.Rcode = FALSE, mk.complete = FALSE, mk.pdf = TRUE)
```

### Arguments

<code>cats</code>	a <code>genind</code> object with spatial coordinates in the other slot
<code>fric.raster</code>	friction (resistance) raster, that specifies the landscape where the analysis should be computed on. If <code>fric.raster</code> is a stack a cost distances are calculated for each layer in the stack.
<code>gen.distance</code>	type of genetic distance that should be used. Depending on the genetic distance measurement this is done on a subpopulation basis (D, <code>Gst.Hedrick</code> , <code>Gst.Nei=Fst</code> ) or on an individual basis (Kosman, Smouse, <code>propShared</code> ). <code>propShared</code> is the proportion of shared alleles between individuals.
<code>NN</code>	Number of neighbours used when calculating the cost distance (possible values 4,8 or 16). As the default is <code>NULL</code> a value has to be provided if <code>pathtype</code> is 'leastcost'. <code>NN=8</code> is most commonly used as it avoids a directional bias, but be aware that linear structures may cause artefacts in the least-cost paths in the <code>NN=8</code> case, therefore we strongly recommend to inspect the actual least-cost paths in the provided output.
<code>pathtype</code>	Type of cost distance to be calculated (based on function in the <a href="#">gdistance</a> package. Available distances are 'leastcost', 'commute' or 'rSPDistance'. See functions in the <code>gdistance</code> package for further explanations.
<code>plotpath</code>	switch if least cost paths should be plotted (works only if <code>pathtype='leastcost'</code> . Be aware this slows down the computation, but it is recommended to check least cost paths visually.
<code>theta</code>	value needed for <code>rSPDistance</code> function. see <a href="#">rSPDistance</a> in package <code>gdistance</code> .
<code>mk.resistance</code>	switch to do the landscape genetic analysis based on resistance matrices, should be set to <code>TRUE</code>

mapdotcolor	see <a href="#">popgenreport</a>
mapdotsize	see <a href="#">popgenreport</a>
mapdotalpha	see <a href="#">popgenreport</a>
mapdottype	see <a href="#">popgenreport</a>
mapzoom	see <a href="#">popgenreport</a>
mk.custom	switch to add a customised part to the landgenreport
fname	see <a href="#">popgenreport</a>
foldername	see <a href="#">popgenreport</a>
path.pgr	see <a href="#">popgenreport</a>
mk.Rcode	see <a href="#">popgenreport</a>
mk.complete	see <a href="#">popgenreport</a>
mk.pdf	see <a href="#">popgenreport</a>

### Details

Check the help pages of [popgenreport](#) how to include coordinates to a genind object. The coordinates need to be projected. Latlongs are not valid, because Euclidean distances are calculated based on these coordinates. For an example how to convert latlongs into a projected format have a look at the vignette that comes with this package. The friction needs to be a raster and needs to be in the same projection as the genind object. Also the type of genetic distance to be used needs to be specified.

### Value

Four distance matrices are returned. Pairwise Euclidean distances between subpopulations/individuals, cost distances, path lengths and genetic distances. Also following the approach of Wassermann et al. 2010 a series of partial mantel tests are performed. A multiple regression analysis based on Wang 2013 and Legendre 1994 is returned. The actual least-cost paths can be found under paths

### Author(s)

Bernd Gruber (bernd.gruber@canberra.edu.au)

### References

- Cushman, S., Wasserman, T., Landguth, E. and Shirk, A. (2013). Re-Evaluating Causal Modeling with Mantel Tests in Landscape Genetics. *Diversity*, 5(1), 51-72.
- Landguth, E. L., Cushman, S. A., Schwartz, M. K., McKelvey, K. S., Murphy, M. and Luikart, G. (2010). Quantifying the lag time to detect barriers in landscape genetics. *Molecular ecology*, 4179-4191.
- Wang, I 2013. Examining the full effects of landscape heterogeneity on spatial genetic variation: a multiple matrix regression approach for quantifying geographic and ecological isolation. *Evolution*: 67-12: 3403-3411.
- Wasserman, T. N., Cushman, S. A., Schwartz, M. K. and Wallin, D. O. (2010). Spatial scaling and multi-model inference in landscape genetics: *Martes americana* in northern Idaho. *Landscape Ecology*, 25(10), 1601-1612.

**See Also**

[popgenreport](#), [wassermann](#), [genleastcost](#), [lgrMMRR](#)

**Examples**

```
## Not run:
lc<-landgenreport(cats=landgen, fric.raster=fric.raster, gen.distance="D", NN=4, mk.resistance=TRUE)
names(lc$leastcost)

## End(Not run)
```

---

lgrMMRR

---

*Multiple Matrix Regression with Randomization analysis*


---

**Description**

performs Multiple Matrix Regression with Randomization analysis This method was implemented by Wang 2013 (MMRR function see references) and also by Sarah Goslee in package ecodist. lgrMMRR is a simple wrapper to have a more user friendly output.

**Usage**

```
lgrMMRR(gen.mat, cost.mats, eucl.mat = NULL, nperm = 999)
```

**Arguments**

gen.mat	a genetic distance matrix (e.g. output from <a href="#">genleastcost</a> )
cost.mats	a list of cost distance matrices
eucl.mat	pairwise Euclidean distance matrix. If not specified ignored
nperm	the number of permutations

**Details**

Performs multiple regression on distance matrices following the methods outlined in Legendre et al. 1994 and implemented by Wang 2013.

**Value**

a table with the results of the matrix regression analysis. (regression coefficients and associated p-values from the permutation test (using the pseudo-t of Legendre et al. 1994). and also r.squared from and associated p-value from the permutation test. F.test.

Finally also the F-statistic and p-value for overall F-test for lack of fit.

**Author(s)**

Bernd Gruber (bernd.gruber@canberra.edu.au) using the implementation of Wang 2013.



## References

- Legendre, P.; Lapointe, F. and Casgrain, P. 1994. Modeling brain evolution from behavior: A permutational regression approach. *Evolution* 48: 1487-1499.
- Lichstein, J. 2007. Multiple regression on distance matrices: A multivariate spatial analysis tool. *Plant Ecology* 188: 117-131.
- Wang,I 2013. Examining the full effects of landscape heterogeneity on spatial genetic variation: a multiple matrix regression approach for quantifying geographic and ecological isolation. *Evolution*: 67-12: 3403-3411.

## See Also

[MRM](#) in package [ecodist](#), [popgenreport](#), [genleastcost](#), [landgenreport](#), [wassermann](#)

## Examples

```
## Not run:
require(raster)
data(landgen)
data(fric.raster)
glc <- genleastcost(landgen, fric.raster, "D", NN=4, path="leastcost")
lgrMMRR(glc$gen.mat, glc$cost.mats, glc$eucl.mat, nperm=999)

## End(Not run)
```

---

mutation

*Function to execute mutation on a pop data.frame*

---

## Description

mutation subprocess on single populations

## Usage

```
mutation(x, n.allels, mutrate, mtype = "n.all", n.cov)
```

## Arguments

x	a pop object
n.allels	number of alleles
mutrate	the mutation rate
mtype	the mutation process (currently on n.all is implemented. (=Choose any allele from 1:n.allels))
n.cov	(number of covariates, default )

## Value

a dispersal probability matrix

---

`null.all`*Checks for the presence of and determine the frequency of null alleles*

---

**Description**

The function `null.all` determines the frequency of null alleles at each locus of a `genind` object. As an initial step, the function makes a bootstrap estimate (based on the observed allele frequencies) of the probability of seeing the number of homozygotes observed for each allele. If there are a large number of null alleles present at a locus, it would result in multiple alleles at a locus having an excess of homozygotes. The second step of the function estimates the frequency of null alleles and a bootstrap confidence interval for each locus using the methods of Chakraborty et al. (1994) and Brookfield (1996). If the 95% confidence interval includes zero, it indicates that the frequency of null alleles at a locus does not significantly differ from zero.

**Usage**

```
null.all(population)
```

**Arguments**

`population`      a `genind` object (from the package `adegenet`)

**Value**

The function returns a list with two main components: `homozygotes` and `null.allele.freq`. `Homozygotes` contains the output of the first part of the analysis: determining the observed number of homozygotes for allele at each locus (`homozygotes$observed`), generating a distribution of the expected number of homozygotes for each allele at each locus (`homozygotes$bootstrap`) based upon the observed allele frequencies at a locus, and producing a summary table given the probability of observing the number of homozygotes (`homozygotes$probability.obs`). `null.allele.freq` list contains summary tables of the null allele frequency estimates based upon the formulas of Chakraborty et al. (1994) (`summary1`), and Brookfield (1996) (`summary2`). For each summary table, the observed frequency is the null allele frequency determined from the observed heterozygosity and homozygosity at a locus. The median, 2.5th, and 97.5th percentiles are from bootstrap estimates of null allele frequencies obtained by resampling the individual genotypes from the original `genind` object.

Brookfield (1996) provides a brief discussion on which estimator should be used. In summary, it was recommended that Chakraborty et al. (1994)'s method (e.g. `summary1`) be used if there are individuals with no bands at a locus seen, but they are discounted as possible artefacts. If all individuals have one or more bands at a locus then Brookfield (1996)'s method (e.g. `summary2`) should be used.

**Author(s)**

Aaron Adamack, [aaron.adamack@canberra.edu.au](mailto:aaron.adamack@canberra.edu.au)

## References

Brookfield JFY. (1996) A simple new method for estimating null allele frequency from heterozygote deficiency. *Molecular Ecology* 5:453-455

Chakraborty R, Zhong Y, Jin L, Budowle B. (1994) Nondetectability of restriction fragments and independence of DNA fragment sizes within and between loci in RFLP typing of DNA. *American Journal of Human Genetics* 55:391-401

## See Also

[popgenreport](#)

## Examples

```
#not run:
#data(bilby)
#here we use only the first 50 individuals to speed up the example
#popgenreport(bilby, mk.null.all=TRUE, mk.pdf=FALSE)

#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby, mk.null.all=TRUE, mk.pdf=TRUE)
```

---

opt.landgen

*Function for optimising a landscape genetic analysis based on resistance layers*

---

## Description

opt.landgen places iter times nlocations in a given landscape. For each scenario the pairwise cost-distances and Euclidean distances are calculated and the standard deviation of detour (see Gruber et al. in prep) is calculated. This metric evaluates the scenerio in their ability to find a significant effect for the given resistance layer on population structure (based on the causal modelling approach of Cushman et al.). To allow for more realistic designs previously locations, a minimal distance between locations and a mask that indicates "forbidden" areas can be specified.

## Usage

```
opt.landgen(landscape, nlocations, mindist = 0, fixed = NULL, method,
  NN = 8, iter = 100, retry = 10, mask = NULL, plot = TRUE)
```

## Arguments

landscape	resistance layer as a raster object (if not projected dimensions are assumed to be in meters!!)
nlocations	the number of locations
mindist	minimal distance in map units (meter if not specified)

fixed	n fixed locations, provided as a data.frame with dimensions nx2
method	least cost path algorithm provided by the gdistance package. Options are "least-cost", "SPDistance" and "commute". see function costdistances.
NN	number of next neighboring cells to be used, default is 8. see function costdistances.
iter	number of iterations that should be used to find an optimised design. Try initially the default and if it runs fast (depends on the type of costdistance and dimensions of landscape), increase to higher values.
retry	number of retries if optimisation is not possible in a certain iteration (due to mindist and/or fixed locations). Defaults to 10, which should be sufficient in most cases.
mask	a raster object that masks positions which are not available. Areas which are not to be used for locations are coded as NA (not available), all other values are treated as suitable for placing locations.
plot	if true, some plots are presented that show the histogram, ecdf of the best (and the worst scenario).

### Value

a list object with two slots. The first slot is called opt and contains iter optimisation values (sd.detour and sd.cost) in a iter x 2 dimensional data.frame. The second slot is called scenario and contains the corresponding 1:iter scenarios, given as coordinates in a data.frame of dimensions nlocations x 2. Both slots are ordered in decreasing order of sd.detour values. So the best scenario is at 1 and the worst is at position iter.

---

p2p

*Function to calculate dispersal distances based on cost distances*

---

### Description

converts cost distances to probabilities: to reach a certain patch[ d0 average distance of p of all individuals, for example d0=100, p =0.5 -> 50% percent of all migrating individuals go up to 100 m.

### Usage

p2p(x, d0, p)

### Arguments

x	Cost (Euclidean) distance matrix
d0	dispersal distance
p	of all individuals in a population

### Value

a dispersal probability matrix

---

pairwise.fstb	<i>Calculates pairwise fstb using a genind object (very fast)</i>
---------------	---

---

**Description**

for simulation the original pairwise.fst was much to slow. The fast version works only without NAs and diploid data (so do not use it on non-simulated data)

**Usage**

```
pairwise.fstb(gsp)
```

**Arguments**

gsp                    a genind object

**Value**

a pairwise fst matrix (same as hierfstat pairwise.fst)

---

popgenreport	<i>This is the main function of the package. It analyses an object of class <a href="#">genind</a> and then creates a report containing the results of the analysis. There are several routines that can be optionally included in the analysis and there are multip output options including a PDF with the report, R-code and an object (fname.results) containing all of the results, which can be used for further analyses.</i>
--------------	--

---

**Description**

This function is used to analyse population genetic data. The main idea is to provide a framework for analysing microsatellite genetic data using a mix of existing and new functions. The function works on an object of class [genind](#). There are several ways to convert data into a [genind](#) object using existing functions provided by the [adegenet](#) package ( [import2genind](#), [df2genind](#), [read.fstat](#), [read.structure](#), [read.genetix](#), [read.genepop](#)) or refer to [read.genetable](#) how to import data from an EXCEL (csv) document. The function performs a number of different genetic analyses (e.g. counts of individuals and alleles across sub-populations, tests for heterozygosity and Hardy-Weinberg Equilibrium, differentiation statistics Fst, G'st, Jost's D, and genetic distance between individuals and populations), with users having the option to select which analysis routines are included in the report. To select a routine, the user simply turns on a switch e.g. `mk.map=TRUE` returns a map with the sampling location for each individual (if coordinates are provided).

Coordinates need to specified within the [genind](#) object. As a standard [genind](#) object does not require spatial coordinates, we extended it by using the other slot in the [genind](#) object. The easiest way to provide spatial coordinates is to use the [read.genetable](#) function and use the `lat`, `long` or `x`, `y` arguments for WGS1984 projected data or mercator projected data respectively. To calculate distances the data are internally reprojected using the [Mercator](#) function in package [dismo](#)),

which is the projection used by google maps. Or you can add data manually to your `genind` object using the mentioned (e.g. `genindobject@other$latlong <- yourlatlong data` or `genindobject@other$xy <- your_xy_data`). If you have your data in a different projection you need to reproject them into either WGS1984 or the google maps Mercator projection. If you use a different projection distance calculation may be wrong and probably the map will not be correct. See the manual for an example how to project and add spatial coordinates to your genetic data. Names for alleles (`genindobject@loc.names`) are truncated if longer than six characters. If truncated Capital letters linked by a hyphen are added to guarantee they are unique. You can rename them by providing new names by accessing the `genind@loc.names` slot prior to running `popgenreport`.

Note that the `popgenreport` function can take a long time to run if the options `mk.complete`, `mk.gd.kosman`, or `mk.gd.smouse` are set to `TRUE`. For example, running `popgenreport` with `mk.complete=TRUE` on a dataset with 500 individuals with 36 loci will take 14 to 15 minutes on a PC with a 3.5 Ghz processor and nearly 3 hours for a dataset with ~3200 individuals.

## Usage

```
popgenreport(cats = NULL, mk.counts = TRUE, mk.map=FALSE, matype="satellite",
mapdotcolor ="blue", mapdotsize=1, mapdotalpha=0.4, mapdottype=19 , mapzoom=NULL,
mk.locihz = FALSE, mk.hwe = FALSE, mk.fst = FALSE, mk.gd.smouse = FALSE,
mk.gd.kosman = FALSE, mk.pcoa=FALSE, mk.spautocor=FALSE, mk.allele.dist = FALSE,
mk.null.all=FALSE, mk.allele.rich=FALSE,mk.differ.stats=FALSE, mk.custom=FALSE,
fname = "PopGenReport", foldername="results", path.pgr=NULL, mk.Rcode = FALSE,
mk.complete=FALSE, mk.pdf=TRUE)
```

## Arguments

<code>cats</code>	this is the <code>genind</code> object the analysis will be based on.
<code>mk.counts</code>	switch is to provide overview counts of the number of individuals sampled, numbers of individuals and alleles sampled per sub-population, number of alleles per locus, mean number of alleles per locus and the percentatge of missing data.
<code>mk.map</code>	switch to produce a map with the sampling location of each individual marked. This switch requires individual coordinates (latitudes and longitudes in WGS1984) be provided (under <code>cats@other\$latlong</code> or see <code>read.genetable</code> on how to import them from a table of genetic data). An error message will be generated if you turn this routine on, but do not provide the coordinates in the right format. If the coordinates are provided in a seperate file, they must be attached to the <code>genind</code> object in the slot <code>yourgenindobject@other\$latlong &lt;- yourlatlongdata.</code> <code>yourlatlongdata</code> needs to be a data frame that has the same number and order of individuals per row as the population genetic data. Note that an internet connection is required to connect to the Google Maps server which provides the basemap for this routine.
<code>matype</code>	Defines the type of map. Default is 'satellite'. Other options are: 'roadmap', 'mobile', 'terrain', 'hybrid'.
<code>mapdotcolor</code>	Color of dots for each individual on the map. Default is 'blue'.
<code>mapdotsize</code>	Size of dots for each individual. Default is 1.

mapdotalpha	Transparency of dots. 1 is invisible, 0 is no transparency. Default is 0.4.
mapdottype	Defines the type of the symbol. For explanation see pch under <a href="#">par</a> . Default is 19 - a filled circle.
mapzoom	Zoom level of the map. If not specified the default zoom of Google maps are used. Please be aware if you set the zoom level to high, the map may not show all sample locations.
mk.locihz	switch to test for population heterozygosity
mk.hwe	switch to test for Hardy-Weinberg equilibrium for each loci and population
mk.fst	switch to calculate Fst values for each loci and pairwise Fst (Nei's 1973) over subpopulations
mk.gd.smouse	Individual pairwise genetic distances based on Smouse and Peakall (1999). Refer to gd_smouse. Spatial coordinates need to be provided to be able to run this analysis.
mk.gd.kosman	Individual pairwise genetic distances based on Kosman & Leonhard (2005). Refer to gd_kosman. Spatial coordinates need to be provided to be able to run this analysis.
mk.pcoa	Principal component analysis following Jombart et al. 2009. Spatial coordinates need to be provided to be able to run this analysis. Refer to vignettes within adegenet.
mk.spautocor	Spatial autocorrelation analysis following Smouse & Peakall 1999. Spatial coordinates need to be provided to be able to run this analysis. Refer to spautocor for more information.
mk.allele.dist	switch to look at allele distributions by loci and subpopulation
mk.null.all	check for null alleles
mk.allel.rich	calculation of allelic richness
mk.differ.stats	switch to look at population differentiation statistics (Nei's G <sub>st</sub> , Hedrick's G <sub>st</sub> , and Jost's D)
mk.custom	edit custom.snw to include your own function to a report.
fname	filename for the output files. Defaults to PopGenReport. Note that using a filename which includes a space in the name will result in the filename for each figure being printed out in the PDF report for each figure. Replacing the space with an underscore should prevent this from happening.
foldername	name of folder, where files are stored. Defaults to 'results'
path.pgr	Folder where the output files are stored. Defaults to the temporary directory (tempdir()). If you want to store the output in another directory, simply provide the path here. e.g. path.pgr=getwd() saves it in your current working directory.
mk.Rcode	switch to get the full R script that is used to generate the report. A great way to get a very detailed insight on the kind of analysis and also an easy way to generate a script which you can customize for your analytical needs.
mk.complete	switch to create a full report using all of the routines (all switches are set to TRUE, except mk.subgroups).

mk.pdf switch to create a shiny pdf output. You need a working **latex** version running on your system (e.g. MikTeX (Windows) or Texmaker (Linux, MacOSX)). For more information how to install latex on your system refer to the [www.popgenreport.org](http://www.popgenreport.org) and to the manuals of the **knitr** package and its manuals.

### Value

The function returns an object (e.g. `res`) that has all of the results produced by this function in it. The structure of the object can be accessed via `str(res)`. The main slots in this object (if you ran a full report) are:

`dataoverview`, `PopHet`, `Alleledist`, `Fst`, `HsHtdifferentiate`, `HWEResults`, `subgroups`, `GDKosman`, `GDSmouse`

Additional output is provided in the form of a PDF (if `mk.pdf=TRUE`), which will be saved to the specified subfolder (via `foldername`) in your current working directory, and maps and figures which will be placed in this folder as well. This folder will be generated automatically in your current working directory. If you do not specify a working directory via `path.pgr` then the temporary working directory of R will be used (`tempdir()`). If `mk.Rcode=T` is set, an R file named `fname.R` will be saved to your specified subfolder.

### Author(s)

Aaron Adamack & Bernd Gruber, [aaron.adamack@canberra.edu.au](mailto:aaron.adamack@canberra.edu.au), [bernd.gruber@canberra.edu.au](mailto:bernd.gruber@canberra.edu.au)

### References

Kosman E., Leonard K.J. 2005. Similarity coefficients for molecular markers in studies of genetic relationships between individuals for haploid, diploid, and polyploidy species. *Molecular Ecology* 14:415-424

Peakall R., Smouse P. 2012. GenAlEx 6.5: Genetic analysis in Excel. Population genetic software for teaching and research - an update. *Bioinformatics* 28:2537-2539

### See Also

[adegenet](#), [pegas](#), [mmod](#)

### Examples

```
#not run:
#data(bilby) # a generated data set
#res <- popgenreport(bilby, mk.counts=TRUE, mk.map=TRUE, mk.pdf=FALSE)
#check results via res or use created tables in the results folder.

### RUN ONLY with a working Latex version installed
# res <- popgenreport(bilby, mk.counts=TRUE, mk.map=TRUE, mk.pdf=TRUE, path.pgr="c:/temp")
# for a full report in a single pdf set mk.complete to TRUE
# res <- popgenreport(bilby, mk.complete=TRUE)
```



---

pops2genind	<i>Function converts pops to a genind object</i>
-------------	--

---

**Description**

converts pops into genind (to calculate Fst etc.)

**Usage**

```
pops2genind(x, locs = NULL, n.cov = 3)
```

**Arguments**

x	pops object (a list of pop)
locs	named coordinates of locations
n.cov	number of covariates (defaults to 3)

**Value**

a spatial genind object

---

read.genetable	<i>Function to convert textfiles into a <a href="#">genind</a> object (the format required for popgenreport)</i>
----------------	--

---

**Description**

This function converts genetic data provided in a tabular 'comma separated value' (.csv) file into a genind object, the data format required to run PopGenReport. At the moment it works only for codominant markers (e.g. microsatellites). This function is based on df2genind from the [adegenet](#) package.

**Usage**

```
read.genetable(filename, pop = NULL, ind = NULL, lat = NULL, long = NULL,  
x = NULL, y = NULL, other.min = NULL, other.max = NULL, oneColPerAll,  
NA.char = NA, sep = NULL, ncode = NULL, ploidy=2)
```

## Arguments

filename	the name of your file in .csv file format
pop	the column number if subpopulations are known, otherwise set to NULL
ind	the column number of an individual identifier, otherwise set to NULL
lat	the column number where the latitudinal coordinate is recorded (can be set to NULL)
long	the column number where the longitudinal coordinate is recorded (can be set to NULL)
x	the column number where the x coordinate is recorded. If not in Mercator it needs to be transformed!!! (can be set to NULL)
y	the column number where the y coordinate is recorded. If not in Mercator it needs to be transformed!!! (can be set to NULL)
other.min	if your data has some additional data (e.g. gender, size etc.) you can include this data in the genind object as well. Values in this section have to be in adjacent columns with no other columns between them. other.min is the column number where this section starts.
other.max	if your data has some additional data (e.g. gender, size etc.) then you can convert this data as well. This section has to be in a consecutive order with no other type of columns in between. other.max is the column number where this section ends.
oneColPerAll	needs to be specified. If your data is coded as a single column per allele
NA.char	can be NA, 0 or mean. See details section.
sep	a character string separating alleles. See details.
ncode	
ploidy	Ploidy of the data set. Be aware that most analysis do only run for diploid data and that missing data in polyploid data sets are ambiguous, which may give dubious results if not handled appropriately.

## Details

The format of the .csv file is very important. Make sure your **headings are exactly as provided in the example file** or the conversion will likely fail (e.g. use lower cases for all headings). Use your favourite text editor to reformat the file (e.g. Excel) to prepare the data and save it as csv file. You need to provide the number of columns for each of your data sections. These are: ind, pop, lat, long, other.min, other.max, and whether there is a single column per allele (if you use a single column for both alleles then you need to specify the separator as well), or two columns per allele. Please refer to the example files to make sure your file is in the correct format and then check the conversion by typing:

```
mydata <- read.genetable("\mygeneticdat.csv") mydata
```

The easiest way to provide spatial coordinates is to use the read.genetable function and use the lat, long arguments for WGS1984 projected data (the most common projection globally). For additional information how to use spatial data with PopGenReport refer to the help of the popgenreport function and to the popgenreport manual.

=== There are 3 treatments for missing values === - NA: kept as NA.

- 0: allelic frequencies are set to 0 on all alleles of the concerned locus. Recommended for a PCA on compositionnal data.

- "mean": missing values are replaced by the mean frequency of the corresponding allele, computed on the whole set of individuals. Recommended for a centred PCA.

=== Details for the sep argument === this character is directly used in regular expressions like gsub, and thus require some characters to be preceded by double backslashes. For instance, "\^" works but "\\^" must be coded as "\\\\".

## Value

an object of the class `genind` This kind of object is needed to be passed on to the `popgen.report` function.

## Author(s)

Bernd Gruber (bernd.gruber@canberra.edu.au)

## See Also

[import2genind](#), [df2genind](#), [read.fstat](#), [read.structure](#), [read.genetix](#) [read.genepop](#)

## Examples

```
#example file with one column per loci, seperated by forwardslash
read.csv(paste(.libPaths()[1],"/PopGenReport/extdata/platypus1c.csv", sep="" ))
platy1c <- read.genetable( paste(.libPaths()[1],"/PopGenReport/extdata/platypus1c.csv"
, sep="" ), ind=1, pop=2, lat=3, long=4, other.min=5, other.max=6, oneColPerAll=FALSE,
sep="/", )

#example file with two columns per loci
read.csv(paste(.libPaths()[1],"/PopGenReport/extdata/platypus2c.csv", sep="" ))
platy2c <- read.genetable( paste(.libPaths()[1],"/PopGenReport/extdata/platypus2c.csv",
sep="" ), ind=1, pop=2, lat=3, long=4, other.min=5, other.max=6, oneColPerAll=TRUE)

#to get a pdf output you need to have a running Latex version installed on your system.
#run a report (with a map)
#res<- popgenreport(platy2c, mk.counts=TRUE, mk.map=TRUE, mk.allele.dist=TRUE, mk.pdf=TRUE)
```

---

reproduction

*Function to execute reproduction on a pop data.frame*

---

## Description

reproduction subprocess on single populations

## Usage

```
reproduction(x, type = "K.limit", K = n.ind, n.off, n.cov)
```

**Arguments**

x	a pop object
type	type of density dependence K.limit only yet
K	Kapacity of a subpopulation
n.off	number of offspring per female
n.cov	(number of covariates, default 3)

**Value**

an updated pop object

---

run.poggensim	<i>Run forward step generations a popgen simulation</i>
---------------	---

---

**Description**

performs a time-forward, agent-based and spatially explicit genetic population simulation

**Usage**

```
run.poggensim(simpops, steps, cost.mat, n.offspring, n.ind, mig.rate, disp.max,
  disp.rate, n.allels, mut.rate, n.cov = 3, rec = "none",
  emi.table = NULL)
```

**Arguments**

simpops	pops object (a list of pop)
steps	the number of steps (generations)
cost.mat	a cost matrix (e.g. calculated via costDistance)
n.offspring	number of offsprings per female
n.ind	number of individuals
mig.rate	migration rate
disp.max	maximal dispersal distance of disp.rate individuals
disp.rate	percentage of individuals achieving disp.max
n.allels	number of maximal alleles at a loci
mut.rate	mutation rate
n.cov	number of covariates (defaults to 3)
rec	switch if emigration matrix should be recorded, either "none" or "emi"
emi.table	a emigration matrix, if provide a fixed number of migration events will take place otherwise based on disp.max, mig.rate and disp.rate, events occuring are (in that order, emigration, reproduction, mutation)

**Value**

an updated simpops object after steps steps

---

spautocor

*Spatial autocorrelation following Smouse and Peakall 1999*


---

### Description

Global spatial autocorrelation is a multivariate approach combining all loci into a single analysis. The autocorrelation coefficient  $r$  is calculated for each pairwise genetic distance pairs for all specified distance classes. For more information see Smouse and Peakall 1999, Peakall et al. 2003 and Smouse et al. 2008.

### Usage

```
spautocor(gen.m, eucl.m, shuffle=FALSE, bins=10)
```

### Arguments

gen.m	a matrix of individual pairwise genetic distances. Easiest to use <code>gd_smouse</code> or <code>gd_kosman</code> to create such a matrix, but in principle any other squared distance matrix can be used. see example
eucl.m	A euclidean distance matrix, based on the coordinates of individuals. see example
shuffle	used internally for the permutation calculation
bins	number of bins for the distance classes. Currently only even bins are supported.

### Value

Returns a data frame with  $r$  values and number of distances within each distance class.

### Author(s)

Bernd Gruber, [Bernd.Gruber@canberra.edu.au](mailto:Bernd.Gruber@canberra.edu.au)

### References

- Smouse PE, Peakall R. 1999. Spatial autocorrelation analysis of individual multiallele and multilocus genetic structure. *Heredity* 82: 561-573.
- Double, MC, et al. 2005. Dispersal, philopatry and infidelity: dissecting local genetic structure in superb fairy-wrens (*Malurus cyaneus*). *Evolution* 59, 625-635.
- Peakall, R, et al. 2003. Spatial autocorrelation analysis offers new insights into gene flow in the Australian bush rat, *Rattus fuscipes*. *Evolution* 57, 1182-1195.
- Smouse, PE, et al. 2008. A heterogeneity test for fine-scale genetic structure. *Molecular Ecology* 17, 3389-3400.
- Gonzales, E, et al. 2010. The impact of landscape disturbance on spatial genetic structure in the Guanacaste tree, *Enterolobium cyclocarpum*(Fabaceae). *Journal of Heredity* 101, 133-143.
- Beck, N, et al. 2008. Social constraint and an absence of sex-biased dispersal drive fine-scale genetic structure in white-winged choughs. *Molecular Ecology* 17, 4346-4358.

**See Also**

[popgenreport](#)

**Examples**

```
#not run:
#data(bilby)
#popgenreport(bilby, mk.spautocor=TRUE, mk.pdf=FALSE)
#to get a pdf output you need to have a running Latex version installed on your system.
#popgenreport(bilby[1:50], mk.spautocor=TRUE, mk.pdf=TRUE)
```

---

wassermann

*Partial Mantel tests on costdistance matrices*

---

**Description**

This function implements the Causal modelling approach as suggested by Wassermann et al. 2010 and Cushman et al. 2010. It tests for the effect of landscape features using a cost distance matrix on the genetic structure of subpopulation/individuals.

**Usage**

```
wassermann(gen.mat, cost.mats, eucl.mat=NULL, plot = TRUE, nperm=999)
```

**Arguments**

gen.mat	pairwise genetic distance matrix
cost.mats	pairwise cost distance matrix
eucl.mat	pairwise Eukclidean distance matrix
plot	switch for control plots of the partial mantel test
nperm	number of permutations for the partial mantel test

**Details**

see [landgenreport](#)

**Value**

A table with the results of the partial mantel test. Using plot=TRUE results in diagnostic plots for the partial mantel tests.

**Author(s)**

Bernd Gruber (bernd.gruber@canberra.edu.au)

**References**

Wassermann, T.N., Cushman, S. A., Schwartz, M. K. and Wallin, D. O. (2010). Spatial scaling and multi-model inference in landscape genetics: *Martes americana* in northern Idaho. *Landscape Ecology*, 25(10), 1601-1612.

**See Also**

[popgenreport](#), [genleastcost](#), [landgenreport](#), [lgrMMRR](#)

**Examples**

```
## Not run:  
glc <- genleastcost(landgen, fric.raster, "D", NN=8)  
wassermann(eucl.mat = glc$eucl.mat, cost.mats = glc$cost.mats, gen.mat = glc$gen.mat)  
  
## End(Not run)
```

# Index

- \*Topic **datasets**
  - fric.raster, 8
  - landgen, 13
- \*Topic **package**
  - PopGen-package, 2
- addline, 3
- addpoly, 4
- adegenet, 3, 24, 25
- allel.rich, 5
- allele.dist, 6
- bilby, 7
- costdistances, 7
- df2genind, 21, 27
- dismo, 21
- emigration, 8
- fric.raster, 8
- gd.kosman, 9
- gd.smouse, 10
- gdistance, 12, 14
- genind, 5–7, 9, 10, 18, 21, 22, 25
- genleastcost, 8, 11, 13, 16, 17, 31
- import2genind, 21, 27
- init.poggensim, 13
- knitr, 24
- landgen, 13
- landgenreport, 8, 12, 13, 14, 17, 30, 31
- lgrMMRR, 11, 12, 16, 16, 31
- Mercator, 21
- mmod, 3, 24
- MRM, 17
- mutation, 17
- null.all, 18
- opt.landgen, 19
- p2p, 20
- pairwise.fstb, 21
- par, 23
- pegas, 3, 24
- PopGen (PopGen-package), 2
- PopGen-package, 2
- popgenreport, 6, 7, 9, 11, 12, 14–17, 19, 21, 30, 31
- pops2genind, 25
- read.fstat, 21, 27
- read.genepop, 21, 27
- read.genetable, 25
- read.genetix, 21, 27
- read.structure, 21, 27
- reproduction, 27
- rSPDistance, 12, 14
- run.poggensim, 28
- spautocor, 29
- wassermann, 11, 12, 16, 17, 30