

# Package ‘fontquiver’

October 27, 2016

**Title** Set of Installed Fonts

**Version** 0.2.0

**Description** Provides a set of fonts with permissive licences. This is useful when you want to avoid system fonts to make sure your outputs are reproducible.

**Depends** R (>= 3.3.0)

**Imports** fontBitstreamVera (>= 0.1.0), fontLiberation (>= 0.1.0)

**Suggests** testthat, htmltools

**License** GPL-3 | file LICENSE

**Encoding** UTF-8

**LazyData** true

**RoxygenNote** 5.0.1

**Collate** 'font-getters.R' 'fontset.R' 'fontset-bitstream-vera.R'  
'fontset-dejavu.R' 'fontset-liberation.R' 'fontset-symbola.R'  
'html-dependency.R' 'utils.R'

**NeedsCompilation** no

**Author** Lionel Henry [cre, aut],  
RStudio [cph],  
George Douros [cph] (Symbola font)

**Maintainer** Lionel Henry <lionel@rstudio.com>

**Repository** CRAN

**Date/Publication** 2016-10-27 02:24:38

## R topics documented:

fonts . . . . .	2
fontset_info . . . . .	3
fontset_list . . . . .	3
fontset_register . . . . .	4
fontset_variants . . . . .	4
font_families . . . . .	5

font_variants . . . . .	5
htmlFontDependency . . . . .	6
splice_fonts . . . . .	7
<b>Index</b>	<b>8</b>

---

fonts	<i>Get elements of a fontset</i>
-------	----------------------------------

---

## Description

fonts() returns the list of all font objects for a given fontset (a collection of fonts provided by fontquiver, such as Liberation or Bitstream Vera). font() returns one specific font. font\_symbol() extracts the font marked as symbol font, if it exists in the fontset.

## Usage

```
fonts(fontset)

font(fontset, variant, style)

font_symbol(fontset = "Symbola")
```

## Arguments

fontset	A string giving the name of a set of fonts (e.g. "Liberation" or "Bitstream Vera"). Use <a href="#">fontset_list()</a> to obtain the list of fontsets registered in your session.
variant	Font variant, as per Fontconfig's nomenclature. Use <a href="#">fontset_variants()</a> to find out which variants are available for a fontset.
style	Font style, as per Fontconfig's nomenclature. Use <a href="#">fontset_styles()</a> to find out which variants are available for a fontset.

## Examples

```
font("Bitstream Vera", "Sans", "Roman")

f <- fonts("Liberation")
str(f, 1)

font_symbol("Symbola")
```

---

fontset_info	<i>Fontset metadata</i>
--------------	-------------------------

---

**Description**

This returns a data frame containing metadata about fonts. The columns "variant" and "style" correspond to the properties of the font as reported by fontconfig. The columns "family", "italic" and "bold" provide information in terms of R nomenclature of fonts. The column "base" gives the base filename of the font. See [fontset\\_list\(\)](#) to obtain a list of available fontsets.

**Usage**

```
fontset_info(fontset)
```

**Arguments**

fontset            A string giving the name of a set of fonts (e.g. "Liberation" or "Bitstream Vera"). Use [fontset\\_list\(\)](#) to obtain the list of fontsets registered in your session.

**See Also**

[fontset\\_list\(\)](#), [font\\_families\(\)](#), [font\\_variants\(\)](#)

---

fontset_list	<i>Get list of all registered fonts</i>
--------------	---

---

**Description**

Get list of all registered fonts

**Usage**

```
fontset_list()
```

---

fontset_register	<i>Register a font to fontquiver</i>
------------------	--------------------------------------

---

**Description**

Register a font to fontquiver

**Usage**

```
fontset_register(fontset, getter, files)
```

**Arguments**

fontset	Name of the font set.
getter	Constructor of font objects.
files	Data structure containing font information.

---

fontset_variants	<i>Fontset variants and styles</i>
------------------	------------------------------------

---

**Description**

These functions return the variants and the styles available for a given fontset.

**Usage**

```
fontset_variants(fontset)

fontset_styles(fontset, variant)
```

**Arguments**

fontset	A string giving the name of a set of fonts (e.g. "Liberation" or "Bitstream Vera"). Use <a href="#">fontset_list()</a> to obtain the list of fontsets registered in your session.
variant	Font variant, as per Fontconfig's nomenclature. Use <a href="#">fontset_variants()</a> to find out which variants are available for a fontset.

**Examples**

```
fontset_variants("Liberation")
fontset_styles("Bitstream Vera", "Sans Mono")
```

---

font_families	<i>Font families and faces</i>
---------------	--------------------------------

---

### Description

Returns families or faces as font files for a given font set. The files are organised by R nomenclature of families ("sans", "serif", "mono", and "symbol") and faces ("plain", "italic", "bold", and "bolditalic"). When a font does not have a combination, NA is reported.

### Usage

```
font_families(fontset)
```

```
font_faces(fontset, family = c("sans", "serif", "mono", "symbol"))
```

### Arguments

fontset	A string giving the name of a set of fonts (e.g. "Liberation" or "Bitstream Vera"). Use <a href="#">fontset_list()</a> to obtain the list of fontsets registered in your session.
family	One of "sans", "serif", "mono" or "symbol".

### Details

Note that the fonts returned by [font\\_faces\(\)](#) and [font\\_families\(\)](#) are constrained by R's nomenclature of fonts and are thus a subset of those returned by [font\\_variants\(\)](#) and [font\\_styles\(\)](#).

### See Also

[font\\_variants\(\)](#), [fonts\(\)](#)

### Examples

```
font_families("Bitstream Vera")$mono$bold  
font_faces("Bitstream Vera", "mono")
```

---

font_variants	<i>Font variants</i>
---------------	----------------------

---

### Description

[font\\_variants\(\)](#) returns a tree of fonts organised as per [fontconfig](#)'s nomenclature. The first level contains variants of a font and the second level contains font styles.

**Usage**

```
font_variants(fontset)

font_styles(fontset, variant)
```

**Arguments**

fontset	A string giving the name of a set of fonts (e.g. "Liberation" or "Bitstream Vera"). Use <code>fontset_list()</code> to obtain the list of fontsets registered in your session.
variant	Font variant, as per Fontconfig's nomenclature. Use <code>fontset_variants()</code> to find out which variants are available for a fontset.

**Details**

See also `font_families()` and `font_faces()` for similar collections organised according to R nomenclature of fonts. Note that variants and styles are a super set of R families and faces and may contain more fonts.

**See Also**

`font_families()`, `fonts()`

**Examples**

```
font_variants("Bitstream Vera")
font_variants("Bitstream Vera")$Sans$Oblique
font_styles("Bitstream Vera", "Sans")
```

---

htmlFontDependency     *Include font as CSS dependency*

---

**Description**

Include font as CSS dependency

**Usage**

```
htmlFontDependency(...)
```

**Arguments**

...	Fonts or collections of fonts. See <code>font_families()</code> and <code>font_variants()</code> for creating collections of fonts. You can also supply lists of individual fonts as returned by <code>fonts()</code> .
-----	---

## Examples

```
# Create an htmlDependency object:
dep <- htmlFontDependency(font_families("Bitstream Vera"))

# Use the fonts in your dependent css or html files. For example:
# body {
# font-family: 'Bitstream Vera Sans Mono', courier;
# }
```

---

splice\_fonts

*Splice fonts and font collections*

---

## Description

splice\_fonts() Reduces its arguments to a flat list. It accepts indistinctly font objects, lists of font objects (obtained with [fonts\(\)](#)), or collections of fonts produced by [font\\_variants\(\)](#) or [font\\_families\(\)](#). Duplicate fonts are removed from the result.

## Usage

```
splice_fonts(...)
```

## Arguments

...            Fonts or collections of fonts. See [font\\_families\(\)](#) and [font\\_variants\(\)](#) for creating collections of fonts. You can also supply lists of individual fonts as returned by [fonts\(\)](#).

## Examples

```
splice_fonts(font("Bitstream Vera", "Sans", "Oblique"), font_faces("Bitstream Vera", "mono"))
```

# Index

font (fonts), [2](#)  
font\_faces, [6](#)  
font\_faces (font\_families), [5](#)  
font\_families, [3](#), [5](#), [5](#), [6](#), [7](#)  
font\_styles, [5](#)  
font\_styles (font\_variants), [5](#)  
font\_symbol (fonts), [2](#)  
font\_variants, [3](#), [5](#), [5](#), [6](#), [7](#)  
fonts, [2](#), [5-7](#)  
fontset\_info, [3](#)  
fontset\_list, [2](#), [3](#), [3](#), [4-6](#)  
fontset\_register, [4](#)  
fontset\_styles, [2](#)  
fontset\_styles (fontset\_variants), [4](#)  
fontset\_variants, [2](#), [4](#), [4](#), [6](#)  
  
htmlFontDependency, [6](#)  
  
splice\_fonts, [7](#)