

Package ‘ggrepel’

November 24, 2016

Version 0.6.5

Title Repulsive Text and Label Geoms for 'ggplot2'

Description Provides text and label geoms for 'ggplot2' that help to avoid overlapping text labels. Labels repel away from each other and away from the data points.

Depends R (>= 3.0.0), ggplot2 (>= 2.0.0)

Imports grid, Rcpp, scales (>= 0.3.0)

Suggests knitr, rmarkdown

VignetteBuilder knitr

License GPL-3 | file LICENSE

URL <http://github.com/slowkow/ggrepel>

BugReports <http://github.com/slowkow/ggrepel/issues>

RoxygenNote 5.0.1

LinkingTo Rcpp

NeedsCompilation yes

Author Kamil Slowikowski [aut, cre],
Jean-Olivier Irisson [ctb]

Maintainer Kamil Slowikowski <kslowikowski@gmail.com>

Repository CRAN

Date/Publication 2016-11-24 07:47:54

R topics documented:

GeomLabelRepel	2
geom_label_repel	2
ggrepel	5

Index	6
--------------	----------

GeomLabelRepel	<i>GeomLabelRepel</i>
----------------	-----------------------

Description

GeomLabelRepel
GeomTextRepel

geom_label_repel	<i>Repulsive textual annotations.</i>
------------------	---------------------------------------

Description

geom_text_repel adds text directly to the plot. geom_label_repel draws a rectangle underneath the text, making it easier to read. The text labels repel away from each other and away from the data points.

Usage

```
geom_label_repel(mapping = NULL, data = NULL, stat = "identity",
  parse = FALSE, ..., box.padding = unit(0.25, "lines"),
  label.padding = unit(0.25, "lines"), point.padding = unit(1e-06, "lines"),
  label.r = unit(0.15, "lines"), label.size = 0.25, segment.colour = NULL,
  segment.color = NULL, segment.size = 0.5, segment.alpha = NULL,
  min.segment.length = unit(0.5, "lines"), arrow = NULL, force = 1,
  max.iter = 2000, nudge_x = 0, nudge_y = 0, na.rm = FALSE,
  show.legend = NA, inherit.aes = TRUE)
```

```
geom_text_repel(mapping = NULL, data = NULL, stat = "identity",
  parse = FALSE, ..., box.padding = unit(0.25, "lines"),
  point.padding = unit(1e-06, "lines"), segment.colour = NULL,
  segment.color = NULL, segment.size = 0.5, segment.alpha = NULL,
  min.segment.length = unit(0.5, "lines"), arrow = NULL, force = 1,
  max.iter = 2000, nudge_x = 0, nudge_y = 0, na.rm = FALSE,
  show.legend = NA, inherit.aes = TRUE)
```

Arguments

mapping	Set of aesthetic mappings created by aes or aes_ . If specified and inherit.aes = TRUE (the default), is combined with the default mapping at the top level of the plot. You only need to supply mapping if there isn't a mapping defined for the plot.
data	A data frame. If specified, overrides the default data frame defined at the top level of the plot.
stat	The statistical transformation to use on the data for this layer, as a string.

parse	If TRUE, the labels will be parsed into expressions and displayed as described in <code>?plotmath</code>
...	other arguments passed on to <code>layer</code> . There are three types of arguments you can use here: <ul style="list-style-type: none"> • Aesthetics: to set an aesthetic to a fixed value, like <code>colour = "red"</code> or <code>size = 3</code>. • Other arguments to the layer, for example you override the default stat associated with the layer. • Other arguments passed on to the stat.
box.padding	Amount of padding around bounding box. Defaults to <code>unit(0.25, "lines")</code> .
label.padding	Amount of padding around label. Defaults to 0.25 lines.
point.padding	Amount of padding around labeled point. Defaults to <code>unit(0, "lines")</code> .
label.r	Radius of rounded corners. Defaults to 0.15 lines.
label.size	Size of label border, in mm.
segment.colour, segment.color	Colour of the line segment. Defaults to the same colour as the text. In the unlikely event you specify both US and UK spellings of colour, the US spelling will take precedence.
segment.size	Width of line segment connecting the data point to the text label, in mm.
segment.alpha	Transparency of the line segment. Defaults to the same transparency as the text.
min.segment.length	Skip drawing segments shorter than this. Defaults to <code>unit(0.5, "lines")</code> .
arrow	specification for arrow heads, as created by <code>arrow</code>
force	Force of repulsion between overlapping text labels. Defaults to 1.
max.iter	Maximum number of iterations to try to resolve overlaps. Defaults to 2000.
nudge_x, nudge_y	Horizontal and vertical adjustments to nudge the starting position of each text label.
na.rm	If FALSE (the default), removes missing values with a warning. If TRUE silently removes missing values.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .

Details

These geoms are based on `geom_text` and `geom_label`. See the documentation for those functions for more details. Differences from those functions are noted here.

Text labels have height and width, but they are physical units, not data units. The amount of space they occupy on that plot is not constant in data units: when you resize a plot, labels stay the same size, but the size of the axes changes. The text labels are repositioned after resizing a plot.

`geom_label_repel`

Currently `geom_label_repel` does not support the `rot` parameter and is considerably slower than `geom_text_repel`. The `fill` aesthetic controls the background colour of the label.

Alignment

The repulsive geoms reposition text labels to avoid overlap, so the following parameters are **not supported**:

- `hjust`
- `vjust`
- `position`
- `check_overlap`

Examples

```
p <- ggplot(mtcars,
  aes(wt, mpg, label = rownames(mtcars), colour = factor(cyl))) +
  geom_point()

# Avoid overlaps by repelling text labels
p + geom_text_repel()
# Labels with background
p + geom_label_repel()

## Not run:
p + geom_text_repel(family = "Times New Roman",
  box.padding = unit(0.5, "lines"))

# Add aesthetic mappings
p + geom_text_repel(aes(alpha=wt, size=mpg))
p + geom_label_repel(aes(fill=factor(cyl)), colour="white", segment.colour="black")

# Draw all line segments
p + geom_text_repel(min.segment.length = unit(0, "lines"))

# Omit short line segments (default behavior)
p + geom_text_repel(min.segment.length = unit(0.5, "lines"))

# Omit all line segments
p + geom_text_repel(segment.colour = NA)

# Repel just the labels and totally ignore the data points
p + geom_text_repel(point.padding = NA)

# Hide some of the labels, but repel from all data points
mtcars$label <- rownames(mtcars)
mtcars$label[1:15] <- ""
p + geom_text_repel(data = mtcars, aes(wt, mpg, label = label))
```

```
# Nudge the starting positions
p + geom_text_repel(nudge_x = ifelse(mtcars$cyl == 6, 1, 0),
                  nudge_y = ifelse(mtcars$cyl == 6, 8, 0))
# Change the text size
p + geom_text_repel(aes(size = wt))
# Scale height of text, rather than sqrt(height)
p + geom_text_repel(aes(size = wt)) + scale_radius(range = c(3,6))

# You can display expressions by setting parse = TRUE. The
# details of the display are described in ?plotmath, but note that
# geom_text_repel uses strings, not expressions.
p + geom_text_repel(aes(label = paste(wt, "^(", cyl, ")", sep = "")),
                  parse = TRUE)

# Add a text annotation
p +
  geom_text_repel() +
  annotate(
    "text", label = "plot mpg vs. wt",
    x = 2, y = 15, size = 8, colour = "red"
  )

# Add arrows
p +
  geom_point(colour = "red") +
  geom_text_repel(
    arrow = arrow(length = unit(0.02, "npc")),
    box.padding = unit(1, "lines")
  )

## End(Not run)
```

ggrepel

ggrepel

Description

This package contains extra geoms for **ggplot2**.

Details

Please see the help pages listed below:

- [geom_text_repel](#)
- [geom_label_repel](#)

Also see the vignette for more usage examples:

`browseVignettes("ggrepel")`

Please report issues and suggest improvements at Github:

<https://github.com/slowkow/ggrepel>

Index

*Topic **datasets**

GeomLabelRepel, [2](#)

aes, [2](#)

aes_, [2](#)

arrow, [3](#)

borders, [3](#)

geom_label, [3](#)

geom_label_repel, [2](#), [5](#)

geom_text, [3](#)

geom_text_repel, [5](#)

geom_text_repel (geom_label_repel), [2](#)

GeomLabelRepel, [2](#)

GeomTextRepel (GeomLabelRepel), [2](#)

ggrepel, [5](#)

ggrepel-package (ggrepel), [5](#)

layer, [3](#)