

Package ‘scam’

June 2, 2016

Version 1.2-0

Author Natalya Pya <nat.pya@gmail.com>

Maintainer Natalya Pya <nat.pya@gmail.com>

Title Shape Constrained Additive Models

Date 2016-06-02

Description Routines for generalized additive modelling under shape constraints on the component functions of the linear predictor. Models can contain multiple shape constrained (univariate and/or bivariate) and unconstrained terms. The routines of `gam()` in package 'mgcv' are used for setting up the model matrix, printing and plotting the results. Penalized likelihood maximization based on Newton-Raphson method is used to fit a model with multiple smoothing parameter selection by GCV or UBRE/AIC.

Depends R (>= 2.15.0), mgcv (>= 1.8-2)

Imports methods, stats, graphics, Matrix, splines

Suggests nlme

License GPL (>= 2)

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2016-06-02 09:43:01

R topics documented:

scam-package	2
anova.scam	4
bfgs_gcv.ubre	6
check.analytical	8
derivative.scam	9
gcv.ubre_grad	10

marginal.matrices.tescv.ps	11
marginal.matrices.tesmi1.ps	13
marginal.matrices.tesmi2.ps	14
plot.scam	15
Predict.matrix.mpi.smooth	19
predict.scam	21
print.scam	25
residuals.scam	26
scam	27
scam.check	34
scam.fit	35
shape.constrained.smooth.terms	37
smooth.construct.cv.smooth.spec	39
smooth.construct.cx.smooth.spec	40
smooth.construct.mdcv.smooth.spec	42
smooth.construct.mdcx.smooth.spec	44
smooth.construct.micv.smooth.spec	45
smooth.construct.micx.smooth.spec	47
smooth.construct.mpd.smooth.spec	48
smooth.construct.mpi.smooth.spec	50
smooth.construct.tedecv.smooth.spec	51
smooth.construct.tedecx.smooth.spec	53
smooth.construct.tedmd.smooth.spec	54
smooth.construct.tedmi.smooth.spec	56
smooth.construct.temicv.smooth.spec	58
smooth.construct.temicx.smooth.spec	59
smooth.construct.tescv.smooth.spec	61
smooth.construct.tescx.smooth.spec	63
smooth.construct.tesmd1.smooth.spec	64
smooth.construct.tesmd2.smooth.spec	66
smooth.construct.tesmi1.smooth.spec	68
smooth.construct.tesmi2.smooth.spec	69
summary.scam	71
vis.scam	74
Index	77

scam-package

*Shape Constrained Additive Models***Description**

scam provides functions for generalized additive modelling under shape constraints on the component functions of the linear predictor of the GAM. Models can contain multiple shape constrained and unconstrained terms as well as bivariate smooths with double or single monotonicity. Univariate smooths under eight possible shape constraints such as monotonically increasing/decreasing, convex/concave, increasing/decreasing and convex, increasing/decreasing and concave, are available as model terms.

The model set up is the same as in `gam()` in package `mgcv` with the added shape constrained smooths, so the unconstrained smooths can be of more than one variable, and other user defined smooths can be included. Penalized log likelihood maximization is used to fit the model together with the automatic smoothness selection.

Details

Package: scam
Version: 1.1-9
Date: 2015-06-17
License: GPL (version 2 or later) See file LICENSE
LazyLoad: yes

The package provides generalized additive modelling under shape constraints on the component functions of the linear predictor. `scam` and `plot.scam` functions are based on the functions of the unconstrained GAM `gam()` and `plot.gam()` in package `mgcv` and similar in use. `summary.scam` allows to extract the results of the model fitting in the same way as in `summary.gam`. A Bayesian approach is used to obtain a covariance matrix of the model coefficients and credible intervals for each smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com> based partly on `mgcv` by Simon Wood
Maintainer: Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood S.N. (2006) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.
- Wood, S.N. (2008) Fast stable direct fitting and smoothness selection for generalized additive models. *Journal of the Royal Statistical Society (B)* 70(3):495-518
- Wood, S.N. (2011) Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society (B)* 73(1):3-36
- The package was part supported by EPSRC grants EP/I000917/1, EP/K005251/1 and the Science Committee of the Ministry of Science and Education of the Republic of Kazakhstan grant #2532/GF3.

Examples

```
## see examples for scam
```

Description

Performs hypothesis tests relating to one or more fitted scam objects. The function is a clone of `anova.gam` of the `mgcv` package.

The documentation below is similar to that of object `anova.gam`.

Usage

```
## S3 method for class 'scam'
anova(object, ..., dispersion = NULL, test = NULL,
       freq = FALSE, p.type=0)
## S3 method for class 'anova.scam'
print(x, digits = max(3, getOption("digits") - 3),...)
```

Arguments

<code>object, ...</code>	fitted model objects of class <code>scam</code> as produced by <code>scam()</code> .
<code>x</code>	an <code>anova.scam</code> object produced by a single model call to <code>anova.scam()</code> .
<code>dispersion</code>	a value for the dispersion parameter: not normally used.
<code>test</code>	what sort of test to perform for a multi-model call. One of "Chisq", "F" or "Cp".
<code>freq</code>	whether to use frequentist or Bayesian approximations for parametric term p-values. See <code>summary.gam</code> for details.
<code>p.type</code>	selects exact test statistic to use for single smooth term p-values. See <code>summary.scam</code> for details.
<code>digits</code>	number of digits to use when printing output.

Details

see `anova.gam` for details.

Value

In the multi-model case `anova.scam` produces output identical to `anova.glm`, which it in fact uses.

In the single model case an object of class `anova.scam` is produced, which is in fact an object returned from `summary.scam`.

`print.anova.scam` simply produces tabulated output.

WARNING

If models 'a' and 'b' differ only in terms with no un-penalized components then p values from `anova(a,b)` are unreliable, and usually much too low.

Default P-values will usually be wrong for parametric terms penalized using 'paraPen': use `freq=TRUE` to obtain better p-values when the penalties are full rank and represent conventional random effects.

For a single model, interpretation is similar to `drop1`, not `anova.lm`.

Author(s)

Simon N. Wood <simon.wood@r-project.org>

References

Scheipl, F., Greven, S. and Küchenhoff, H. (2008) Size and power of tests for a zero random effect variance or polynomial regression in additive and linear mixed models. *Comp. Statist. Data Anal.* 52, 3283-3299

Wood, S.N. (2013a) On p-values for smooth components of an extended generalized additive model. *Biometrika* 100:221-228

Wood, S.N. (2013b) A simple test for random effects in regression models. *Biometrika* 100:1005-1010

See Also

[scam](#), [predict.scam](#), [scam.check](#), [summary.scam](#), [anova.gam](#)

Examples

```
library(scam)
set.seed(0)
fac <- rep(1:4,20)
x1 <- runif(80)*5
x2 <- runif(80,-1,2)
x3 <- runif(80, 0, 1)
y <- fac+log(x1)/5
y <- y + exp(-1.3*x2) +rnorm(80)*0.1
fac <- factor(fac)
b <- scam(y ~ fac+s(x1,bs="mpi")+s(x2,bs="mpd")+s(x3))

b1 <- scam(y ~ fac+s(x1,bs="mpi")+s(x2,bs="mpd"))
anova(b,b1,test="F")

## b2 <- scam(y ~ fac +s(x1)+s(x2)+te(x1,x2))
```

bfgs_gcv.ubre

*Multiple Smoothing Parameter Estimation by GCV/UBRE***Description**

Function to efficiently estimate smoothing parameters of SCAM by GCV/UBRE score optimization. The procedure is outer to the model fitting by the Newton-Raphson method. The function uses the BFGS method where the Hessian matrix is updated iteratively at each step. Backtracking is included to satisfy the sufficient decrease condition.

The function is not normally called directly, but rather service routines for [scam](#).

Usage

```
bfgs_gcv.ubre(fn=gcv.ubre_grad, rho, ini.fd=TRUE, G, gamma=1, env,
             n.pen=length(rho), typx=rep(1,n.pen), typf=1,
             steptol= 1e-7, gradtol = 6.0554*1e-06, maxNstep = 5,
             maxHalf = 30, check.analytical, del)
```

Arguments

fn	GCV/UBRE Function which returns the GCV/UBRE value and its derivative wrt log smoothing parameter.
rho	log of the initial values of the smoothing parameters.
ini.fd	If TRUE, a finite difference to the Hessian is used to find the initial inverse Hessian, otherwise the initial inverse Hessian is a diagonal matrix '100*I'.
G	A list of items needed to fit a SCAM.
gamma	An ad hoc parameter of the GCV/UBRE score.
env	Get the environment for the model coefficients, their derivatives and the smoothing parameter.
n.pen	Smoothing parameter dimension.
typx	A vector whose component is a positive scalar specifying the typical magnitude of sp.
typf	A positive scalar estimating the magnitude of the gcv near the minimum.
steptol	A positive scalar giving the tolerance at which the scaled distance between two successive iterates is considered close enough to zero to terminate the algorithm.
gradtol	A scalar giving a tolerance at which the gradient is considered to be close enough to 0 to terminate the algorithm.
maxNstep	A positive scalar which gives the maximum allowable step length.
maxHalf	A positive scalar which gives the maximum number of step halving in "backtracking".
check.analytical	If this is TRUE then finite difference derivatives of GCV/UBRE score will be calculated.
del	A positive scalar (default is 1e-4) giving an increment for finite difference approximation when check.analytical=TRUE.

Value

A list is returned with the following items:

<code>gcv.ubre</code>	The optimal value of GCV/UBRE.
<code>rho</code>	The best value of the log smoothing parameter.
<code>dgcv.ubre</code>	The gradient of the GCV/UBRE.
<code>iterations</code>	The number of iterations taken until convergence.
<code>conv.bfgs</code>	Convergence information indicating why the BFGS terminated (given below).
<code>termcode</code>	An integer code indicating why the optimization process terminated. 1: relative gradient is close to zero, current iterate probably is a solution. 2: scaled distance between last two steps less than 'steptol', current iterate probably is a local minimizer, but it's possible that the algorithm is making very slow progress, or 'steptol' is too large. 3: last global step failed to locate a point lower than estimate. Either estimate is an approximate local minimum of the function or steptol is too small. 4: iteration limit exceeded. 5: five consecutive steps of length maxNstep have been taken, it's possible that 'maxstep' is too small.
<code>object</code>	A list of elements returned by the fitting procedure <code>scam.fit</code> for an optimal value of the smoothing parameter.
<code>dgcv.ubre.check</code>	If <code>check.analytical=TRUE</code> this is the finite-difference approximation of the gradient calculated by <code>gcv.ubre_grad</code> , otherwise NULL.
<code>check.grad</code>	If <code>check.analytical=TRUE</code> this is the relative difference (in and finite differenced derivatives calculated by <code>gcv.ubre_grad</code> , otherwise NULL.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood, S.N. (2011) Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society: Series B*. 73(1): 1-34

See Also

[scam](#)

check.analytical	<i>Checking the analytical gradient of the GCV/UBRE score</i>
------------------	---

Description

This function calculates the finite-difference approximation of the GCV/UBRE gradient for the fitted model and compares it with the analytical gradient.

Usage

```
check.analytical(object, data, del=1e-6)
```

Arguments

object	A fitted scam object.
data	An original data frame or list containing the model response variable and co-variates.
del	A positive scalar (default is 1e-6) giving an increment for finite difference approximation.

Value

A list is returned with the following items:

dgcv.ubre.fd	The finite-difference approximation of the gradient.
check.grad	The relative difference in percentage between the analytical and finite differenced derivatives.

Author(s)

Natalya Pya <nat.pya@gmail.com>

See Also

[scam](#)

derivative.scam	<i>Derivative of the univariate smooth model terms</i>
-----------------	--

Description

Function to get derivatives of the smooth model terms (currently only of the univariate smooths). Analytical derivatives for SCOP-splines, finite difference approximation is used for all others

Usage

```
derivative.scam(object, smooth.number=1, deriv=1)
```

Arguments

object	fitted scam object
smooth.number	ordered number of the smooth model term (1,2,...), ordered as in the formula, which derivative is needed to be calculated.
deriv	either 1 if the 1st derivative is required, or 2 if the 2nd

Value

d	values of the derivative of the smooth term.
se.d	standard errors of the derivative.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[scam](#)

Examples

```
set.seed(2)
n <- 200
x1 <- runif(n)*4-1;
f1 <- exp(4*x1)/(1+exp(4*x1)) # monotone increasing smooth
x2 <- sort(runif(n)*3-1)      # decreasing smooth
f2 <- exp(-1.3*x2)
f <- f1+ f2
y <- f+ rnorm(n)*0.2
```

```
## fit model, results, and plot...
b <- scam(y~ s(x1,k=20,bs="mpi")+s(x2,k=15,bs="mpd"),family=gaussian)

d1 <- derivative.scam(b,smooth.number=1,deriv=1)

par(mfrow=c(1,2))

xx <- sort(x1,index=TRUE)
plot(xx$x,d1$d[xx$ix],type="l",xlab=expression(x[1]),
      ylab=expression(df[1]/dx[1]))

d2 <- derivative.scam(b,smooth.number=2,deriv=1)

xx <- sort(x2,index=TRUE)
plot(xx$x,d2$d[xx$ix],type="l",xlab=expression(x[2]),
      ylab=expression(df[2]/dx[2]))
```

gcv.ubre_grad

The GCV/UBRE score value and its gradient

Description

For the estimation of the SCAM smoothing parameters the GCV/UBRE score is optimized out to the Newton-Raphson procedure of the model fitting. This function returns the value of the GCV/UBRE score and calculates its first derivative with respect to the log smoothing parameter using the method of Wood (2009).

The function is not normally called directly, but rather service routines for [bfgs_gcv.ubre](#).

Usage

```
gcv.ubre_grad(rho, G, gamma, env,
              check.analytical, del)
```

Arguments

rho	log of the initial values of the smoothing parameters.
G	a list of items needed to fit a SCAM.
gamma	A constant multiplier to inflate the model degrees of freedom in the GCV or UBRE/AIC score.
env	Get the environment for the model coefficients, their derivatives and the smoothing parameter.
check.analytical	If this is TRUE then finite difference derivatives of GCV/UBRE score will be calculated, otherwise NULL.
del	A positive scalar (default is 1e-4) giving an increment for finite difference approximation when check.analytical=TRUE, otherwise NULL.

Value

A list is returned with the following items:

dgcv.ubre	The value of GCV/UBRE gradient.
gcv.ubre	The GCV/UBRE score value.
scale.est	The value of the scale estimate.
object	The elements of the fitting procedure <code>monogam.fit</code> for a given value of the smoothing parameter.
dgcv.ubre.check	If <code>check.analytical=TRUE</code> this returns the finite-difference approximation of the gradient.
check.grad	If <code>check.analytical=TRUE</code> this returns the relative difference (in and finite differenced derivatives).

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood S.N. (2006) *Generalized Additive Models: An Introduction* with R. Chapman and Hall/CRC Press.
- Wood, S.N. (2011) Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society: Series B*. 73(1): 1-34

See Also

[scam](#), [bfgs_gcv.ubre](#)

marginal.matrices.tescv.ps

Constructs marginal model matrices for "tescv" and "tescx" bivariate smooths in case of B-splines basis functions for both unconstrained marginal smooths

Description

This function returns the marginal model matrices and the list of penalty matrices for the tensor product bivariate smooth with the single concavity or convexity restriction along the second covariate. The marginal smooth functions of both covariates are constructed using the B-spline basis functions.

Usage

```
marginal.matrices.tescv.ps(x, z, xk, zk, m, q1, q2)
```

Arguments

x	A numeric vector of the values of the first covariate at which to evaluate the B-spline marginal functions. The values in x must be between $xk[m[1]+2]$ and $xk[\text{length}(xk) - m[1] - 1]$.
z	A numeric vector of the values of the second covariate at which to evaluate the B-spline marginal functions. The values in z must be between $zk[m[2]+2]$ and $zk[\text{length}(zk) - m[2] - 1]$.
xk	A numeric vector of knot positions for the first covariate, x, with non-decreasing values.
zk	A numeric vector of knot positions for the second covariate, z, with non-decreasing values.
m	A pair of two numbers where $m[i]+1$ denotes the order of the basis of the i^{th} marginal smooth (e.g. $m[i] = 2$ for a cubic spline.)
q1	A number denoting the basis dimension of the first marginal smooth.
q2	A number denoting the basis dimension of the second marginal smooth.

Details

The function is not called directly, but is rather used internally by the constructor [smooth.construct.tescv.smooth.spec](#) and [smooth.construct.tescx.smooth.spec](#).

Value

X1	Marginal model matrix for the first unconstrained marginal smooth.
X2	Marginal model matrix for the second monotonic marginal smooth.
S	A list of penalty matrices for this tensor product smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.tescv.smooth.spec](#), [smooth.construct.tescx.smooth.spec](#), [marginal.matrices.tesmi1.ps](#), [smooth.construct.tesmd1.smooth.spec](#), [smooth.construct.tesmd2.smooth.spec](#)

 marginal.matrices.tesmi1.ps

Constructs marginal model matrices for "tesmi1" and "tesmd1" bivariate smooths in case of B-splines basis functions for both unconstrained marginal smooths

Description

This function returns the marginal model matrices and the list of penalty matrices for the tensor product bivariate smooth with the single monotone increasing or decreasing restriction along the first covariate. The marginal smooth functions of both covariates are constructed using the B-spline basis functions.

Usage

```
marginal.matrices.tesmi1.ps(x, z, xk, zk, m, q1, q2)
```

Arguments

x	A numeric vector of the values of the first covariate at which to evaluate the B-spline marginal functions. The values in x must be between $xk[m[1]+2]$ and $xk[\text{length}(xk) - m[1] - 1]$.
z	A numeric vector of the values of the second covariate at which to evaluate the B-spline marginal functions. The values in z must be between $zk[m[2]+2]$ and $zk[\text{length}(zk) - m[2] - 1]$.
xk	A numeric vector of knot positions for the first covariate, x, with non-decreasing values.
zk	A numeric vector of knot positions for the second covariate, z, with non-decreasing values.
m	A pair of two numbers where $m[i]+1$ denotes the order of the basis of the i^{th} marginal smooth (e.g. $m[i] = 2$ for a cubic spline.)
q1	A number denoting the basis dimension of the first marginal smooth.
q2	A number denoting the basis dimension of the second marginal smooth.

Details

The function is not called directly, but is rather used internally by the constructor [smooth.construct.tesmi1.smooth.spec](#) and [smooth.construct.tesmd1.smooth.spec](#).

Value

X1	Marginal model matrix for the first monotonic marginal smooth.
X2	Marginal model matrix for the second unconstrained marginal smooth.
S	A list of penalty matrices for this tensor product smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood S.N. (2006) *Generalized Additive Models: An Introduction* with R. Chapman and Hall/CRC Press.

See Also

[smooth.construct.tesmi1.smooth.spec](#), [smooth.construct.tesmi2.smooth.spec](#), [marginal.matrices.tesmi2.ps](#), [smooth.construct.tesmd1.smooth.spec](#), [smooth.construct.tesmd2.smooth.spec](#)

marginal.matrices.tesmi2.ps

Constructs marginal model matrices for "tesmi2" and "tesmd2" bivariate smooths in case of B-splines basis functions for both unconstrained marginal smooths

Description

This function returns the marginal model matrices and the list of penalty matrices for the tensor product bivariate smooth with the single monotone increasing or decreasing restriction along the second covariate. The marginal smooth functions of both covariates are constructed using the B-spline basis functions.

Usage

```
marginal.matrices.tesmi2.ps(x, z, xk, zk, m, q1, q2)
```

Arguments

- | | |
|----|--|
| x | A numeric vector of the values of the first covariate at which to evaluate the B-spline marginal functions. The values in x must be between $xk[m[1]+2]$ and $xk[\text{length}(xk) - m[1] - 1]$. |
| z | A numeric vector of the values of the second covariate at which to evaluate the B-spline marginal functions. The values in z must be between $zk[m[2]+2]$ and $zk[\text{length}(zk) - m[2] - 1]$. |
| xk | A numeric vector of knot positions for the first covariate, x, with non-decreasing values. |
| zk | A numeric vector of knot positions for the second covariate, z, with non-decreasing values. |

m	A pair of two numbers where $m[i]+1$ denotes the order of the basis of the i^{th} marginal smooth (e.g. $m[i] = 2$ for a cubic spline.)
q1	A number denoting the basis dimension of the first marginal smooth.
q2	A number denoting the basis dimension of the second marginal smooth.

Details

The function is not called directly, but is rather used internally by the constructor [smooth.construct.tesmi2.smooth.spec](#) and [smooth.construct.tesmd2.smooth.spec](#).

Value

X1	Marginal model matrix for the first unconstrained marginal smooth.
X2	Marginal model matrix for the second monotonic marginal smooth.
S	A list of penalty matrices for this tensor product smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood S.N. (2006) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.

See Also

[smooth.construct.tesmi1.smooth.spec](#), [smooth.construct.tesmi2.smooth.spec](#), [marginal.matrices.tesmi1.ps](#), [smooth.construct.tesmd1.smooth.spec](#), [smooth.construct.tesmd2.smooth.spec](#)

plot.scam

SCAM plotting

Description

The function is a clone of the `plot.gam` of the `mgcv` package with the differences in the construction of the Bayesian confidence intervals of the shape constrained smooth terms. The function takes a fitted `scam` object produced by `scam()` and plots the component smooth functions that make it up, on the scale of the linear predictor. Optionally produces term plots for parametric model components as well.

Usage

```
## S3 method for class 'scam'
plot(x, residuals=FALSE, rug=TRUE, se=TRUE, pages=0, select=NULL, scale=-1,
      n=100, n2=40, pers=FALSE, theta=30, phi=30, jit=FALSE, xlab=NULL,
      ylab=NULL, main=NULL, ylim=NULL, xlim=NULL, too.far=0.1,
      all.terms=FALSE, shade=FALSE, shade.col="gray80",
      shift=0, trans=I, seWithMean=FALSE, unconditional = FALSE,
      by.resids = FALSE, scheme=0, ...)
```

Arguments

The list of the arguments is the same as in `plot.gam` of the `mgcv` package.

a fitted `gam` object as produced by `gam()`.

<code>residuals</code>	If TRUE then partial residuals are added to plots of 1-D smooths. If FALSE then no residuals are added. If this is an array of the correct length then it is used as the array of residuals to be used for producing partial residuals. If TRUE then the residuals are the working residuals from the IRLS iteration weighted by the IRLS weights. Partial residuals for a smooth term are the residuals that would be obtained by dropping the term concerned from the model, while leaving all other estimates fixed (i.e. the estimates for the term plus the residuals).
<code>rug</code>	when TRUE (default) then the covariate to which the plot applies is displayed as a rug plot at the foot of each plot of a 1-d smooth, and the locations of the covariates are plotted as points on the contour plot representing a 2-d smooth.
<code>se</code>	when TRUE (default) upper and lower lines are added to the 1-d plots at 2 standard errors above and below the estimate of the smooth being plotted while for 2-d plots, surfaces at +1 and -1 standard errors are contoured and overlayed on the contour plot for the estimate. If a positive number is supplied then this number is multiplied by the standard errors when calculating standard error curves or surfaces. See also <code>shade</code> , below.
<code>pages</code>	(default 0) the number of pages over which to spread the output. For example, if <code>pages=1</code> then all terms will be plotted on one page with the layout performed automatically. Set to 0 to have the routine leave all graphics settings as they are.
<code>select</code>	Allows the plot for a single model term to be selected for printing. e.g. if you just want the plot for the second smooth term set <code>select=2</code> .
<code>scale</code>	set to -1 (default) to have the same y-axis scale for each plot, and to 0 for a different y axis for each plot. Ignored if <code>ylim</code> supplied.
<code>n</code>	number of points used for each 1-d plot - for a nice smooth plot this needs to be several times the estimated degrees of freedom for the smooth. Default value 100.
<code>n2</code>	Square root of number of points used to grid estimates of 2-d functions for contouring.
<code>pers</code>	Set to TRUE if you want perspective plots for 2-d terms.
<code>theta</code>	One of the perspective plot angles.
<code>phi</code>	The other perspective plot angle.

<code>jit</code>	Set to TRUE if you want rug plots for 1-d terms to be jittered.
<code>xlab</code>	If supplied then this will be used as the x label for all plots.
<code>ylab</code>	If supplied then this will be used as the y label for all plots.
<code>main</code>	Used as title (or z axis label) for plots if supplied.
<code>ylim</code>	If supplied then this pair of numbers are used as the y limits for each plot.
<code>xlim</code>	If supplied then this pair of numbers are used as the x limits for each plot.
<code>too.far</code>	If greater than 0 then this is used to determine when a location is too far from data to be plotted when plotting 2-D smooths. This is useful since smooths tend to go wild away from data. The data are scaled into the unit square before deciding what to exclude, and <code>too.far</code> is a distance within the unit square.
<code>all.terms</code>	if set to TRUE then the partial effects of parametric model components are also plotted, via a call to <code>termplot</code> . Only terms of order 1 can be plotted in this way.
<code>shade</code>	Set to TRUE to produce shaded regions as confidence bands for smooths (not available for parametric terms, which are plotted using <code>termplot</code>).
<code>shade.col</code>	define the color used for shading confidence bands.
<code>shift</code>	constant to add to each smooth (on the scale of the linear predictor) before plotting. Can be useful for some diagnostics, or with <code>trans</code> .
<code>trans</code>	function to apply to each smooth (after any shift), before plotting. <code>shift</code> and <code>trans</code> are occasionally useful as a means for getting plots on the response scale, when the model consists only of a single smooth.
<code>seWithMean</code>	if TRUE the component smooths are shown with confidence intervals that include the uncertainty about the overall mean. If FALSE then the uncertainty relates purely to the centred smooth itself. An extension of the argument presented in Nychka (1988) suggests that TRUE results in better coverage performance, and this is also suggested by simulation.
<code>unconditional</code>	if TRUE then the smoothing parameter uncertainty corrected covariance matrix is used to compute uncertainty bands, if available. Otherwise the bands treat the smoothing parameters as fixed.
<code>by.resids</code>	Should partial residuals be plotted for terms with by variables? Usually the answer is no, they would be meaningless.
<code>scheme</code>	Integer (0,1 or 2) or integer vector selecting a plotting scheme for each plot. <code>scheme == 0</code> produces a smooth curve with dashed curves indicating 2 standard error bounds. <code>scheme == 1</code> illustrates the error bounds using a shaded region. For <code>scheme==0</code> , contour plots are produced for 2-d smooths with the x-axes labelled with the first covariate name and the y axis with the second covariate name. For 2-d smooths <code>scheme==1</code> produces a perspective plot, while <code>scheme==2</code> produces a heatmap, with overlaid contours.
<code>...</code>	other graphics parameters to pass on to plotting commands.

Value

The function generates plots.

Author(s)

Natalya Pya <nat.pya@gmail.com> based on the plot.gam of the mgcv by Simon Wood

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

Wood S.N. (2006) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.

See Also

[scam](#)

Examples

```
## simulating data...
n <- 200
set.seed(1)
x0 <- rep(1:4,50)
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained smooth term
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth
x3 <- runif(n)*5;
f3 <- -log(x3)/5 # monotone decreasing smooth
f <- f1+f2+f3
y <- 2*x0 + f + rnorm(n)*0.3
x0 <- factor(x0)

## fit the model and plot ...
b <- scam(y~x0+s(x1,k=15,bs="cr")+s(x2,k=30,bs="mpi")+s(x3,k=30,bs="mpd"))
plot(b,pages=1,residuals=TRUE,all.terms=TRUE,shade=TRUE,shade.col=3)

## Not run:
## example with 2-d plots...
## simulating data...
set.seed(2)
n <- 30
x0 <- rep(1:9,100)
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
x3 <- runif(n*n, 0, 1)
f <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i]))+2*sin(pi*x2[j])}
f1 <- as.vector(t(f))
f2 <- x3*x0
```

```

e <- rnorm(length(f1))*0.1
y <- 2*x0 + f1 + f2 + e
x0 <- factor(x0)
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x0=x0,x1=x11,x2=x22,x3=x3,y=y)
## fit model and plot ...
b <- scam(y~x0+s(x1,x2,k=c(10,10),bs=c("tesmd1","ps"),m=2)+s(x3),data=dat)
op <- par(mfrow=c(2,2))
plot(b,all.terms=TRUE)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data",pch=19,cex=.3)
par(op)

## and use of schemes...
op <- par(mfrow=c(2,2))
plot(b,all.terms=TRUE,scheme=1)
par(op)
op <- par(mfrow=c(2,2))
plot(b,all.terms=TRUE,scheme=c(2,1))
par(op)

## End(Not run)

```

Predict.matrix.mpi.smooth

Predict matrix method functions for SCAMs

Description

The various built in smooth classes for use with `scam` have associate `Predict.matrix` method functions to enable prediction from the fitted model.

Usage

```

## S3 method for class 'mpi.smooth'
Predict.matrix(object, data)
## S3 method for class 'mpd.smooth'
Predict.matrix(object, data)
## S3 method for class 'cv.smooth'
Predict.matrix(object, data)
## S3 method for class 'cx.smooth'
Predict.matrix(object, data)
## S3 method for class 'micx.smooth'
Predict.matrix(object, data)
## S3 method for class 'micv.smooth'
Predict.matrix(object, data)

```

```
## S3 method for class 'mdcx.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'mdcv.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tedmd.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tedmi.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tesmd1.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tesmd2.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tesmi1.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tesmi2.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'temicx.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'temicv.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tedecx.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tedecv.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tescx.smooth'  
Predict.matrix(object, data)  
## S3 method for class 'tescv.smooth'  
Predict.matrix(object, data)
```

Arguments

object	A smooth object, usually generated by a <code>smooth.construct</code> method having processed a smooth specification object generated by an <code>s</code> term in a <code>scam</code> formula.
data	A data frame containing the values of the named covariates at which the smooth term is to be evaluated.

Value

A matrix mapping the coefficients for the smooth term to its values at the supplied data values.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood S.N. (2006) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.

predict.scam

Prediction from fitted SCAM model

Description

This function is a clone of the mgcv library code `predict.gam` with some modifications to adopt shape preserving smooth terms. It takes a fitted scam object produced by `scam()` and produces predictions given a new set of values for the model covariates or the original values used for the model fit. Predictions can be accompanied by standard errors, based on the posterior distribution of the model coefficients.

It now allows prediction outside the range of knots, and use linear extrapolation in this case.

Usage

```
## S3 method for class 'scam'
predict(object, newdata, type="link", se.fit=FALSE, terms=NULL,
        block.size=1000, newdata.guaranteed=FALSE, na.action=na.pass, ...)
```

Arguments

object	a fitted scam object as produced by <code>scam()</code> .
newdata	A data frame or list containing the values of the model covariates at which predictions are required. If this is not provided then predictions corresponding to the original data are returned. If <code>newdata</code> is provided then it should contain all the variables needed for prediction: a warning is generated if not.
type	When this has the value "link" (default) the linear predictor (possibly with associated standard errors) is returned. When <code>type="terms"</code> each component of the linear predictor is returned separately (possibly with standard errors): this includes parametric model components, followed by each smooth component, but excludes any offset and any intercept. <code>type="iterms"</code> is the same, except that any standard errors returned for unconstrained smooth components will include the uncertainty about the intercept/overall mean. When <code>type="response"</code> predictions on the scale of the response are returned (possibly with approximate standard errors). When <code>type="lpmatrix"</code> then a matrix is returned which yields the values of the linear predictor (minus any offset) when postmultiplied by the parameter vector (in this case <code>se.fit</code> is ignored). The latter option is most useful for getting variance estimates for quantities derived from the model:

	for example integrated quantities, or derivatives of smooths. A linear predictor matrix can also be used to implement approximate prediction outside R (see example code, below).
<code>se.fit</code>	when this is TRUE (not default) standard error estimates are returned for each prediction.
<code>terms</code>	if <code>type=="terms"</code> then only results for the terms given in this array will be returned.
<code>block.size</code>	maximum number of predictions to process per call to underlying code: larger is quicker, but more memory intensive. Set to < 1 to use total number of predictions as this.
<code>newdata.guaranteed</code>	Set to TRUE to turn off all checking of newdata except for sanity of factor levels: this can speed things up for large prediction tasks, but newdata must be complete, with no NA values for predictors required in the model.
<code>na.action</code>	what to do about NA values in newdata. With the default <code>na.pass</code> , any row of newdata containing NA values for required predictors, gives rise to NA predictions (even if the term concerned has no NA predictors). <code>na.exclude</code> or <code>na.omit</code> result in the dropping of newdata rows, if they contain any NA values for required predictors. If newdata is missing then NA handling is determined from <code>object\$na.action</code> .
<code>...</code>	other arguments.

Details

See [predict.gam](#) for details.

Value

If `type=="lpmatrix"` then a matrix is returned which will give a vector of linear predictor values (minus any offset) at the supplied covariate values, when applied to the model coefficient vector. Otherwise, if `se.fit` is TRUE then a 2 item list is returned with items (both arrays) `fit` and `se.fit` containing predictions and associated standard error estimates, otherwise an array of predictions is returned. The dimensions of the returned arrays depends on whether `type` is "terms" or not: if it is then the array is 2 dimensional with each term in the linear predictor separate, otherwise the array is 1 dimensional and contains the linear predictor/predicted values (or corresponding s.e.s). The linear predictor returned termwise will not include the offset or the intercept.

`newdata` can be a data frame, list or `model.frame`: if it's a model frame then all variables must be supplied.

Author(s)

Natalya Pya <nat.pya@gmail.com> based partly on `mgcv` by Simon Wood

References

- Chambers and Hastie (1993) Statistical Models in S. Chapman & Hall.
 Wood S.N. (2006) Generalized Additive Models: An Introduction with R. Chapman and Hall/CRC Press.

Pyra, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pyra, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[scam](#), [plot.scam](#)

Examples

```
## Not run:
library(scam)
set.seed(2)
n <- 200
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained term
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth
f <- f1+f2
y <- f+rnorm(n)*0.2
dat <- data.frame(x1=x1,x2=x2,y=y)
b <- scam(y~s(x1,k=15,bs="cr",m=2)+s(x2,k=30,bs="mpi",m=2),
          family=gaussian(link="identity"),data=dat)

newd <- data.frame(x1=seq(-3,3,length.out=20),x2=seq(-1,3,length.out=20))
pred <- predict(b,newd)
pred
predict(b,newd,type="terms",se=TRUE)

## linear extrapolation with predict.scam()...
set.seed(3)
n <- 100
x <- sort(runif(n)*3-1)
f <- exp(-1.3*x)
y <- rpois(n,exp(f))
dat <- data.frame(x=x,y=y)
b <- scam(y~s(x,k=15,bs="mpd",m=2),family=poisson(link="log"),data=dat)
newd <- data.frame(x=c(2.3,2.7,3.2))
fe <- predict(b,newd,type="link",se=TRUE)
ylim<- c(min(y,exp(fe$fit)),max(y,exp(fe$fit)))
plot(c(x,newd[[1]]),c(y,NA,NA,NA),ylim=ylim)
lines(c(x,newd[[1]]),c(b$fitted,exp(fe$fit)),col=3)

## Gaussian model ....
## simulating data...
set.seed(2)
n <- 200
x <- sort(runif(n)*4-1)
f <- exp(4*x)/(1+exp(4*x)) # monotone increasing smooth
y <- f+rnorm(n)*0.1
```

```

dat <- data.frame(x=x,y=y)
b <- scam(y~ s(x,k=25,bs="mpi",m=2),family=gaussian,data=dat)
newd <- data.frame(x=c(3.2,3.3,3.6))
fe <- predict(b,newd)
plot(c(x,newd[[1]]),c(y,NA,NA,NA))
lines(c(x,newd[[1]]),c(b$fitted,fe),col=3)

### passing observed data + new data...
newd <- data.frame(x=c(x,3.2,3.3,3.6))
fe <- predict(b,newd,se=TRUE)
plot(newd[[1]],c(y,NA,NA,NA))
lines(newd[[1]],fe$fit,col=2)
lines(newd[[1]],fe$fit+2*fe$se.fit,col=3)
lines(newd[[1]],fe$fit-2*fe$se.fit,col=4)

## prediction with CI...
newd <- data.frame(x=seq(-1.2,3.5,length.out=100))
fe <- predict(b,newd,se=TRUE)
ylim<- c(min(y,fe$se.fit),max(y,fe$se.fit))
plot(newd[[1]],fe$fit,type="l",ylim=ylim)
lines(newd[[1]],fe$fit+2*fe$se.fit,lty=2)
lines(newd[[1]],fe$fit-2*fe$se.fit,lty=2)

## bivariate example...
n <- 30
x1 <- sort(runif(n)); x2 <- sort(runif(n)*4-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- 2*sin(pi*x1[i]) +exp(4*x2[j])/(1+exp(4*x2[j]))}
f1 <- as.vector(t(f1)); f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n); x11[,1:n] <- x1; x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
b <- scam(y~s(x1,x2,k=c(10,10),bs="tesmi2"),family=gaussian, data=dat)
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE); plot(b,pers=TRUE,theta = 80, phi = 40)

n.out <- 20
xp <- seq(0,1.4,length.out=n.out)
zp <- seq(-1,3.4,length.out=n.out)
xp1 <- matrix(0,n.out,n.out); xp1[,1:n.out] <- xp
xp1 <- as.vector(t(xp1)); xp2 <- rep(zp,n.out)
newd <- data.frame(x1=xp1,x2=xp2)
fe <- predict(b,newd)
fc <- t(matrix(fe,n.out,n.out))
persp(xp,zp,fc,expand= 0.85,ticktype = "simple",xlab="x1",
      ylab="x2",zlab="f^",main="d", theta = 80, phi = 40)

```



```
## obtaining a 'prediction matrix'...

newd <- data.frame(x1=c(-2,-1),x2=c(0,1))
Xp <- predict(b,newdata=newd,type="lpmatrix")
fv <- Xp
fv

## End(Not run)
```

print.scam	<i>Print a SCAM object</i>
------------	----------------------------

Description

The default print method for a scam object. The code is a clone of `print.gam` of the `mgcv` package with a slight simplification since only two methods of smoothing parameter selection (by GCV or UBRE) was implemented for scam.

Usage

```
## S3 method for class 'scam'
print(x,...)
```

Arguments

x	fitted model objects of class scam as produced by scam().
...	other arguments.

Details

As for `mgcv(gam)` prints out the family, model formula, effective degrees of freedom for each smooth term, and optimized value of the smoothness selection criterion used.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Wood S.N. (2006) Generalized Additive Models: An Introduction with R. Chapman and Hall/CRC Press.

See Also

[scam](#), [summary.scam](#)

residuals.scam	<i>SCAM residuals</i>
----------------	-----------------------

Description

This function is a clone of the mgcv library code [residuals.gam](#). It returns residuals for a fitted scam model object. Pearson, deviance, working and response residuals are available.

Usage

```
## S3 method for class 'scam'  
residuals(object, type = c("deviance", "pearson", "scaled.pearson",  
                           "working", "response"),...)
```

Arguments

object	a scam fitted model object.
type	the type of residuals wanted.
...	other arguments.

Details

See `residuals.gam` for details.

Value

An array of residuals.

Author(s)

Natalya Pya <nat.pya@gmail.com>

See Also

[scam](#)

scam	<i>Shape constrained additive models (SCAM) and integrated smoothness selection</i>
------	---

Description

This function fits a SCAM to data. Univariate smooths subject to monotonicity, convexity, or monotonicity plus convexity are available as model terms, as well as bivariate smooths with double or single monotonicity. Smoothness selection is estimated as part of the fitting. Confidence/credible intervals are available for each smooth term.

All the shaped constrained smooths have been added to the `gam()` in package `mgcv` setup using the `smooth.construct` function. The routine calls a `gam()` function for the model set up, but there are separate functions for the model fitting, `scam.fit`, and smoothing parameter selection, `bfgs_gcv.ubre`. Any unconstrained smooth available in `gam` can be taken as model terms.

Usage

```
scam(formula, family = gaussian(), data = list(), gamma = 1,
      sp = NULL, weights = NULL, offset = NULL,
      optimizer="bfgs", optim.method=c("Nelder-Mead", "fd"),
      scale = 0, devtol = 1e-08, steptol= 1e-8, check.analytical=FALSE,
      del=1e-4, start= NULL, etastart, mustart,keepData=FALSE, not.exp=FALSE)
```

Arguments

formula	A SCAM formula. This is exactly like the formula for a GAM (see <code>formula.gam</code> of the <code>mgcv</code> library) except that monotone smooth terms, can be added in the expression of the form <code>s(x1,k=12,bs="mpi",by=z)</code> , where <code>bs</code> indicates the basis to use for the constrained smooth: the built in options for the monotonic smooths are described in <code>shape.constrained.smooth.terms</code> ,
family	A family object specifying the distribution and link to use in fitting etc. See <code>glm</code> and <code>family</code> for more details.
data	A data frame or list containing the model response variable and covariates required by the formula. By default the variables are taken from <code>environment(formula)</code> : typically the environment from which <code>gam</code> is called.
gamma	A constant multiplier to inflate the model degrees of freedom in the GCV or UBRE/AIC score.
sp	A vector of smoothing parameters can be provided here. Smoothing parameters must be supplied in the order that the smooth terms appear in the model formula. The default <code>sp=NULL</code> indicates that smoothing parameters should be estimated. If <code>length(sp)</code> does not correspond to the number of underlying smoothing parameters or negative values supplied then the vector is ignored and all the smoothing parameters will be estimated.
weights	Prior weights on the data.

offset	Used to supply a model offset for use in fitting. Note that this offset will always be completely ignored when predicting, unlike an offset included in formula. This conforms to the behaviour of <code>lm</code> , <code>glm</code> and <code>gam</code> .
optimizer	The numerical optimization method to use to optimize the smoothing parameter estimation criterion. "bfgs" for the built in to scam package routine <code>bfgs_gcv_ubre</code> , "optim", "nlm", "nlm.fd" (based on finite-difference approximation of the derivatives).
optim.method	In case of optimizer="optim" this specifies the numerical method to be used in <code>optim</code> in the first element, the second element of <code>optim.method</code> indicates whether the finite difference approximation should be used ("fd") or analytical gradient ("grad"). The default is <code>optim.method=c("Nelder-Mead", "fd")</code> .
scale	If this is positive then it is taken as the known scale parameter of the exponential family distribution. Negative value indicates that the scale parameter is unknown. 0 indicates that the scale parameter is 1 for Poisson and binomial and unknown otherwise. This conforms to the behaviour of <code>gam</code> .
devtol	A positive scalar giving the convergence control for the model fitting algorithm
steptol	A positive scalar giving the tolerance at which the scaled distance between two successive iterates is considered close enough to zero to terminate the model fitting algorithm.
check.analytical	If this is TRUE then finite difference derivatives of GCV/UBRE score will be calculated.
del	A positive scalar (default is 1e-4) giving an increment for finite difference approximation when <code>check.analytical=TRUE</code> .
start	Initial values for the model coefficients
etastart	Initial values for the linear predictor
mustart	Initial values for the expected values
keepData	If this is TRUE a copy of the original data argument is kept. The default is FALSE which saves space.
not.exp	if TRUE then <code>notExp()</code> function will be used in place of <code>exp</code> (default value) in positivity ensuring beta parameters re-parameterization.

Details

A shape constrained additive model (SCAM) is a generalized linear model (GLM) in which the linear predictor is given by strictly parametric components plus a sum of smooth functions of the covariates where some of the functions are assumed to be shape constrained. For example,

$$\log(E(Y_i)) = X_i^*b + f_1(x_{1i}) + m_2(x_{2i}) + f_3(x_{3i})$$

where the independent response variables Y_i follow Poisson distribution with log link function, f_1 , m_2 , and f_3 are smooth functions of the corresponding covariates, and m_2 is subject to monotone increasing constraint.

All available shape constrained smooths are described in [shape.constrained.smooth.terms](#).

Value

The function returns an object of class "scam" with the following elements (this agrees with `gamObject`):

<code>aic</code>	AIC of the fitted model: the degrees of freedom used to calculate this are the effective degrees of freedom of the model, and the likelihood is evaluated at the maximum of the penalized likelihood, not at the MLE.
<code>assign</code>	Array whose elements indicate which model term (listed in <code>pterm</code> s) each parameter relates to: applies only to non-smooth terms.
<code>bfgs.info</code>	If <code>optimizer="bfgs"</code> , a list of convergence diagnostics relating to the BFGS method of smoothing parameter selection. The items are: <code>conv</code> , indicates why the BFGS algorithm of the smoothness selection terminated; <code>iter</code> , number of iterations of BFGS taken to get convergence; <code>grad</code> , the gradient of the GCV/UBRE score at convergence.
<code>call</code>	the matched call.
<code>coefficients</code>	the coefficients of the fitted model. Parametric coefficients are first, followed by coefficients for each spline term in turn.
<code>coefficients.t</code>	the parametrized coefficients of the fitted model (exponentiated for the monotonic smooths).
<code>conv</code>	indicates whether or not the iterative fitting method converged.
<code>CPU.time</code>	indicates the real and CPU time (in seconds) taken by the fitting process in case of unknown smoothing parameters
<code>data</code>	the original supplied data argument. Only included if the <code>scam</code> argument <code>keepData</code> is set to TRUE (default is FALSE).
<code>deviance</code>	model deviance (not penalized deviance).
<code>df.null</code>	null degrees of freedom.
<code>df.residual</code>	effective residual degrees of freedom of the model.
<code>edf</code>	estimated degrees of freedom for each model parameter. Penalization means that many of these are less than 1.
<code>edf1</code>	alternative estimate of edf.
<code>family</code>	family object specifying distribution and link used.
<code>fitted.values</code>	fitted model predictions of expected value for each datum.
<code>formula</code>	the model formula.
<code>gcv.ubre</code>	the minimized GCV or UBRE score.
<code>dgcg.ubre</code>	the gradient of the GCV or UBRE score.
<code>iter</code>	number of iterations of the Newton-Raphson method taken to get convergence.
<code>linear.predictors</code>	fitted model prediction of link function of expected value for each datum.
<code>method</code>	"GCV" or "UBRE", depending on the fitting criterion used.
<code>min.edf</code>	Minimum possible degrees of freedom for whole model.
<code>model</code>	model frame containing all variables needed in original model fit.

<code>nlm.info</code>	If <code>optimizer="nlm"</code> or <code>optimizer="nlm.fd"</code> , a list of convergence diagnostics relating to the BFGS method of smoothing parameter selection. The items are: <code>conv</code> , indicates why the BFGS algorithm of the smoothness selection terminated; <code>iter</code> , number of iterations of BFGS taken to get convergence; <code>grad</code> , the gradient of the GCV/UBRE score at convergence.
<code>not.exp</code>	if TRUE then <code>notExp()</code> function will be used in place of <code>exp</code> (default value) in positivity ensuring beta parameters re-parameterization.
<code>nsdf</code>	number of parametric, non-smooth, model terms including the intercept.
<code>null.deviance</code>	deviance for single parameter model.
<code>offset</code>	model offset.
<code>optim.info</code>	If <code>optimizer="optim"</code> , a list of convergence diagnostics relating to the BFGS method of smoothing parameter selection. The items are: <code>conv</code> , indicates why the BFGS algorithm of the smoothness selection terminated; <code>iter</code> , number of iterations of BFGS taken to get convergence; <code>optim.method</code> , the numerical optimization method used.
<code>prior.weights</code>	prior weights on observations.
<code>pterm</code>	terms object for strictly parametric part of model.
<code>R</code>	Factor R from QR decomposition of weighted model matrix, unpivoted to be in same column order as model matrix.
<code>residuals</code>	the working residuals for the fitted model.
<code>scale.estimated</code>	TRUE if the scale parameter was estimated, FALSE otherwise.
<code>sig2</code>	estimated or supplied variance/scale parameter.
<code>smooth</code>	list of smooth objects, containing the basis information for each term in the model formula in the order in which they appear. These smooth objects are returned by the <code>smooth.construct</code> objects.
<code>sp</code>	estimated smoothing parameters for the model. These are the underlying smoothing parameters, subject to optimization.
<code>termcode</code>	an integer indicating why the optimization process of the smoothness selection terminated (see <code>bfgs_gcv_ubre</code>).
<code>terms</code>	terms object of model model frame.
<code>trA</code>	trace of the influence matrix, total number of the estimated degrees of freedom (<code>sum(edf)</code>).
<code>var.summary</code>	A named list of summary information on the predictor variables. See <code>gamObject</code> .
<code>Ve</code>	frequentist estimated covariance matrix for the parameter estimators.
<code>Vp</code>	estimated covariance matrix for the parameters. This is a Bayesian posterior covariance matrix that results from adopting a particular Bayesian model of the smoothing process.
<code>Ve.t</code>	frequentist estimated covariance matrix for the reparametrized parameter estimators obtained using the delta method. Particularly useful for testing whether terms are zero. Not so useful for CI's as smooths are usually biased.
<code>Vp.t</code>	estimated covariance matrix for the reparametrized parameters obtained using the delta method. Particularly useful for creating credible/confidence intervals.

weights	final weights used in the Newton-Raphson iteration.
cmX	column means of the model matrix (with elements corresponding to smooths set to zero).
y	response data.

Author(s)

Natalya Pya <nat.pya@gmail.com> based partly on mgcv by Simon Wood

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

Wood, S.N. (2011) Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society (B)* 73(1):3-36

Wood S.N. (2006a) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.

Wood, S.N. (2006b) On confidence intervals for generalized additive models based on penalized regression splines. *Australian and New Zealand Journal of Statistics*. 48(4): 445-464.

See Also

[scam-package](#), [shape.constrained.smooth.terms](#), [gam](#), [s](#), [plot.scam](#), [summary.scam](#), [scam.check](#), [predict.scam](#)

Examples

```
#####
## Gaussian model, 2 terms, 1 monotonic increasing....
## simulating data...
require(scam)

set.seed(0)
n <- 200
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained term
f1 <- (f1-min(f1))/(max(f1)-min(f1)) # function scaled to have range [0,1]
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth
f2 <- (f2-min(f2))/(max(f2)-min(f2)) # function scaled to have range [0,1]
f <- f1+f2
y <- f+rnorm(n)*0.1
dat <- data.frame(x1=x1,x2=x2,y=y)
## fit model, results, and plot...
b <- scam(y~s(x1,k=15,bs="cr",m=2)+s(x2,k=25,bs="mpi",m=2),
          family=gaussian(link="identity"),data=dat,not.exp=FALSE)
print(b)
```

```

summary(b)
plot(b,pages=1)

#####
## Gaussian model, 2 terms, increasing + decreasing convex ....
## simulating data...

set.seed(2)
n <- 200
x1 <- runif(n)*4-1;
f1 <- exp(4*x1)/(1+exp(4*x1)) # monotone increasing smooth
x2 <- runif(n)*3-1;
f2 <- exp(-3*x2)/15 # monotone decreasing and convex smooth
f <- f1+f2
y <- f+ rnorm(n)*0.2
dat <- data.frame(x1=x1,x2=x2,y=y)
## fit model, results, and plot...
b <- scam(y~ s(x1,k=25,bs="mpi",m=2)+s(x2,k=25,bs="mdcx",m=2),
         family=gaussian(link="identity"),data=dat)
print(b)
summary(b)
plot(b,pages=1,scale=0)

#####
## Not run:
## using optim() for smoothing parameter selection...
b1 <- scam(y~ s(x1,k=25,bs="mpi",m=2)+s(x2,k=25,bs="mdcx",m=2),
         family=gaussian(link="identity"),data=dat, optimizer="optim")
summary(b1)

b2 <- scam(y~ s(x1,k=25,bs="mpi",m=2)+s(x2,k=25,bs="mdcx",m=2),
         family=gaussian(link="identity"),data=dat, optimizer="optim",
         optim.method=c("BFGS","fd"))
summary(b2)

## using nlm()...
b3 <- scam(y~ s(x1,k=25,bs="mpi",m=2)+s(x2,k=25,bs="mdcx",m=2),
         family=gaussian(link="identity"),data=dat, optimizer="nlm")
summary(b3)

## End(Not run)

#####
## Poisson model ....
## simulating data...
set.seed(2)
n <- 200
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained term
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth

```



```

f <- f1+f2
y <- rpois(n,exp(f))
dat <- data.frame(x1=x1,x2=x2,y=y)
  ## fit model, results, and plot...
b <- scam(y~s(x1,k=15,bs="cr",m=2)+s(x2,k=30,bs="mpi",m=2),
          family=poisson(link="log"),data=dat,optimizer="nlm.fd")
print(b)
summary(b)
plot(b,pages=1)
scam.check(b)

## Gamma model...
  ## simulating data...
set.seed(3)
n <- 200
x1 <- runif(n)*6-3
f1 <- 1.5*sin(1.5*x1) # unconstrained term
x2 <- runif(n)*4-1;
f2 <- 1.5/(1+exp(-10*(x2+0.75)))+1.5/(1+exp(-5*(x2-0.75))) # monotone increasing smooth
x3 <- runif(n)*6-3;
f3 <- 3*exp(-x3^2) # unconstrained term
f <- f1+f2+f3
y <- rgamma(n,shape=1,scale=exp(f))
dat <- data.frame(x1=x1,x2=x2,x3=x3,y=y)
  ## fit model, results, and plot...
b <- scam(y~s(x1,k=15,bs="ps",m=2)+s(x2,k=30,bs="mpi",m=2)+
          s(x3,k=15,bs="ps",m=2),family=Gamma(link="log"),
          data=dat,optimizer="nlm")

print(b)
summary(b)
par(mfrow=c(2,2))
plot(b)

## Not run:
## bivariate example...
  ## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i]))+2*sin(pi*x2[j])}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model and plot ...
b <- scam(y~s(x1,x2,k=c(10,10),bs=c("tesmd1","ps"),m=2),
          family=gaussian(link="identity"), data=dat,sp=NULL)

```

```

summary(b)
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data",pch=".",cex=3)

## example with random effect smoother...

set.seed(2)
n <- 200
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained term
f1 <- (f1-min(f1))/(max(f1)-min(f1))
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth
f2 <- (f2-min(f2))/(max(f2)-min(f2))
f <- f1+f2
a <- factor(sample(1:10,200,replace=TRUE))
Xa <- model.matrix(~a-1) ## random main effects
y <- f + Xa
dat <- data.frame(x1=x1,x2=x2,y=y,a=a)
## fit model and plot...
b <- scam(y~s(x1,k=15,bs="cr",m=2)+s(x2,k=25,bs="mpi",m=2)+s(a,bs="re"), data=dat)
summary(b)
scam.check(b)
plot(b,pages=1)

## End(Not run)

```

scam.check

Some diagnostics for a fitted scam object

Description

Takes a fitted scam object produced by `scam()` and produces some diagnostic information about the fitting procedure and results. This function is almost the same as [gam.check](#) of the `mgcv` library.

Usage

```
scam.check(b,r1.col=3,... )
```

Arguments

<code>b</code>	a fitted scam object as produced by <code>scam()</code> .
<code>r1.col</code>	color for the reference line on the quantile-quantile plot.
<code>...</code>	extra graphics parameters to pass to plotting functions.

Details

As for `mgcv(gam)` plots 4 standard diagnostic plots, and some other convergence diagnostics. The printed information relates to the optimization process used to select smoothing parameters.

Author(s)

Natalya Pya <nat.pya@gmail.com> based partly on `mgcv` by Simon Wood

References

Wood S.N. (2006) Generalized Additive Models: An Introduction with R. Chapman and Hall/CRC Press.

See Also

[scam](#)

Examples

```
## Not run:
library(scam)
set.seed(2)
n <- 200
x1 <- runif(n)*4-1;
f1 <- exp(4*x1)/(1+exp(4*x1)) # monotone increasing smooth
x2 <- runif(n)*3-1;
f2 <- exp(-3*x2)/15 # monotone decreasing and convex smooth
f <- f1+f2
y <- f+ rnorm(n)*0.2
dat <- data.frame(x1=x1, x2=x2, y=y)
b <- scam(y~ s(x1, k=25, bs="mpi", m=2)+s(x2, k=25, bs="mdcx", m=2),
         family=gaussian(link="identity"), data=dat)
plot(b, pages=1)
scam.check(b, pch=19, cex=.3)

## End(Not run)
```

scam.fit

Newton-Raphson method to fit SCAM

Description

This routine estimates SCAM coefficients given log smoothing parameters using the Newton-Raphson method. The estimation of the smoothing parameters by the GCV/UBRE score optimization is outer to the model fitting. Routine [gcv.ubre_grad](#) evaluates the first derivatives of the smoothness selection scores with respect to the log smoothing parameters. Routine [bfgs_gcv.ubre](#) estimates the smoothing parameters using the BFGS method.

The function is not normally called directly, but rather service routines for [scam](#).

Usage

```
scam.fit(G, sp, maxit=200, devtol=1e-8, steptol=1e-8, gamma=1, start=NULL,
         etastart=NULL, mustart=NULL, env = env)
```

Arguments

G	A list of items needed to fit a SCAM.
sp	The vector of smoothing parameters.
env	Get the environment for the model coefficients, their derivatives and the smoothing parameter.
maxit	Maximum iterations in the Newton-Raphson procedure.
devtol	A positive scalar giving the tolerance at which the scaled distance between two successive penalized deviances is considered close enough to zero to terminate the algorithm.
steptol	A positive scalar giving the tolerance at which the scaled distance between two successive iterates is considered close enough to zero to terminate the algorithm.
gamma	This constant allows to inflate the model degrees of freedom in the GCV or UBRE/AIC score.
start	Initial values for the model coefficients
etastart	Initial values for the linear predictor
mustart	Initial values for the expected values

Details

The routine applies step halving to any step that increases the penalized deviance substantially.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Wood, S.N. (2008) Fast stable direct fitting and smoothness selection for generalized additive models. *Journal of the Royal Statistical Society (B)* 70(3):495-518
- Wood, S.N. (2011) Fast stable restricted maximum likelihood and marginal likelihood estimation of semiparametric generalized linear models. *Journal of the Royal Statistical Society (B)* 73(1):3-36

See Also

[scam](#)

 shape.constrained.smooth.terms

Shape preserving smooth terms in SCAM

Description

As in `mgcv(gam)`, shape preserving smooth terms are specified in a `scam` formula using `s` terms. All the shape constrained smooth terms are constructed using the B-splines basis proposed by Eilers and Marx (1996) with a discrete penalty on the basis coefficients.

The univariate single penalty built in shape constrained smooth classes are summarized as follows

- Monotone increasing P-splines `bs="mpi"`. To achieve monotone increasing smooths these reparametrize the coefficients so that they form an increasing sequence. For details see [smooth.construct.mpi.smooth](#)
- Monotone decreasing P-splines `bs="mpd"`. To achieve monotone decreasing smooths these reparametrize the coefficients so that they form a decreasing sequence. A first order difference penalty applied to the basis coefficients starting with the second is used for the monotone increasing and decreasing cases.
- Convex P-splines `bs="cx"`. These reparametrize the coefficients so that the second order differences of the basis coefficients are greater than zero. For details see [smooth.construct.cx.smooth.spec](#).
- Concave P-splines `bs="cv"`. These reparametrize the coefficients so that the second order differences of the basis coefficients are less than zero. For details see [smooth.construct.cv.smooth.spec](#).
- Monotone increasing and convex P-splines `bs="micx"`. These reparametrize the coefficients so that the first and the second order differences of the basis coefficients are greater than zero. For details see [smooth.construct.micx.smooth.spec](#).
- Monotone increasing and concave P-splines `bs="micv"`. These reparametrize the coefficients so that the first order differences of the basis coefficients are greater than zero while the second order difference are less than zero.
- Monotone decreasing and convex P-splines `bs="mdcx"`. These reparametrize the coefficients so that the first order differences of the basis coefficients are less than zero while the second order difference are greater. For details see [smooth.construct.mdcx.smooth.spec](#).
- Monotone decreasing and concave P-splines `bs="mdcv"`. These reparametrize the coefficients so that the first and the second order differences of the basis coefficients are less than zero.

For all four types of the mixed constrained smoothing a first order difference penalty applied to the basis coefficients starting with the third one is used.

Using the concept of the tensor product spline bases bivariate smooths under monotonicity constraint where monotonicity may be assumed on only one of the covariates (single monotonicity) or both of them (double monotonicity) are added as the smooth terms of the SCAM. Bivariate B-spline is constructed by expressing the coefficients of one of the marginal univariate B-spline bases as the B-spline of the other covariate. Double or single monotonicity is achieved by the corresponding re-parametrization of the bivariate basis coefficients to satisfy the sufficient conditions formulated in terms of the first order differences of the coefficients. The following explains the built in bivariate monotonic smooth classes.

- Double monotone increasing P-splines `bs="tedmi"`. See `smooth.construct.tedmi.smooth.spec` for details.
 - Double monotone decreasing P-splines `bs="tedmd"`.
 - Single monotone increasing P-splines along the first covariate direction `bs="tesmi1"`.
 - Single monotone increasing P-splines along the second covariate direction `bs="tesmi2"`.
 - Single monotone decreasing P-splines along the first covariate direction `bs="tesmd1"`.
 - Single monotone decreasing P-splines along the second covariate direction `bs="tesmd2"`.
- Double penalties for the monotonic tensor product smooths are obtained from the penalties of the marginal smooths.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences
- Eilers, P.H.C. and B.D. Marx (1996) Flexible Smoothing with B-splines and Penalties. *Statistical Science*, 11(2):89-121
- Wood S.N. (2006a) *Generalized Additive Models: An Introduction* with R. Chapman and Hall/CRC Press.
- Wood, S.N. (2006b) Low rank scale invariant tensor product smooths for generalized additive mixed models. *Biometrics* 62(4):1025-1036

See Also

`s`, `smooth.construct.mpi.smooth.spec`, `smooth.construct.mpd.smooth.spec`, `smooth.construct.cx.smooth.spec`, `smooth.construct.cv.smooth.spec`, `smooth.construct.micx.smooth.spec`, `smooth.construct.micv.smooth.spec`, `smooth.construct.mdcx.smooth.spec`, `smooth.construct.mdcv.smooth.spec`, `smooth.construct.tedmi.smooth.spec`, `smooth.construct.tedmd.smooth.spec`, `smooth.construct.tesmi1.smooth.spec`, `smooth.construct.tesmi2.smooth.spec`, `smooth.construct.tesmd1.smooth.spec`, `smooth.construct.tesmd2.smooth.spec`

Examples

```
## see examples for scam
```

 smooth.construct.cv.smooth.spec

Constructor for concave P-splines in SCAMs

Description

This is a special method function for creating smooths subject to concavity constraint which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using concave P-splines. This smooth is specified via model terms such as `s(x, k, bs="cv", m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'cv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The <code>by</code> variable is the last element.
<code>knots</code>	An optional list containing the knots supplied for basis setup. If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"cv.smooth"`.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.cx.smooth.spec](#), [smooth.construct.mpi.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micx.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#)

Examples

```

## Not run:
## Concave P-splines example
## simulating data...
set.seed(1)
n <- 100
x <- sort(2*runif(n)-1)
f <- -4*x^2
y <- f + rnorm(n)*0.45
dat <- data.frame(x=x,y=y)
b <- scam(y~s(x,k=15,bs="cv",m=2),family=gaussian,data=dat,not.exp=FALSE)
# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="cr",m=2),family=gaussian, data=dat,not.exp=FALSE)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,f)      ## the true function
lines(x,b$fitted,col=2) ## constrained fit
lines(x,b1$fitted,col=3) ## unconstrained fit

## Poisson version...
y <- rpois(n,15*exp(f))
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="cv",m=2),family=poisson(link="log"),data=dat,not.exp=FALSE)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="cr",m=2),family=poisson(link="log"), data=dat,not.exp=FALSE)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,15*exp(f))      ## the true function
lines(x,b$fitted,col=2) ## constrained fit
lines(x,b1$fitted,col=3) ## unconstrained fit

## plotting on log scale...
plot(x,log(15*exp(f)),type="l")      ## the true function
lines(x,log(b$fitted),col=2) ## constrained fit
lines(x,log(b1$fitted),col=3) ## unconstrained fit

## End(Not run)

```

smooth.construct.cx.smooth.spec

Constructor for convex P-splines in SCAMs

Description

This is a special method function for creating smooths subject to convexity constraint which is built by the mgcv constructor function for smooth terms, `smooth.construct`. It is constructed using the

mixed constrained P-splines. This smooth is specified via model terms such as $s(x, k, bs="cx", m=2)$, where k denotes the basis dimension and $m+1$ is the order of the B-spline basis.

Usage

```
## S3 method for class 'cx.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

object	A smooth specification object, generated by an s term in a GAM formula.
data	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The <code>by</code> variable is the last element.
knots	An optional list containing the knots supplied for basis setup. If it is NULL then the knot locations are generated automatically.

Value

An object of class "cx.smooth".

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.cv.smooth.spec](#), [smooth.construct.mpi.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#)

Examples

```
## Not run:

## Convex P-splines example
## simulating data...
set.seed(1)
n <- 100
x <- sort(2*runif(n)-1)
f <- 4*x^2
y <- f + rnorm(n)*0.4
dat <- data.frame(x=x,y=y)
b <- scam(y~s(x,k=15,bs="cx",m=2),family=gaussian,data=dat,not.exp=FALSE)
# UNCONSTRAINED FIT *****
```

```

b1 <- scam(y~s(x,k=15,bs="cr",m=2),family=gaussian, data=dat,not.exp=FALSE)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,f)      ## the true function
lines(x,b$fitted,col=2) ## constrained fit
lines(x,b1$fitted,col=3) ## unconstrained fit

## Poisson version...
y <- rpois(n,exp(f))
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="cx",m=2),family=poisson(link="log"),data=dat,not.exp=FALSE)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="cr",m=2),family=poisson(link="log"), data=dat,not.exp=FALSE)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,exp(f)) ## the true function
lines(x,b$fitted,col=2) ## constrained fit
lines(x,b1$fitted,col=3) ## unconstrained fit

## End(Not run)

```

```
smooth.construct.mdcv.smooth.spec
```

Constructor for monotone decreasing and concave P-splines in SCAMs

Description

This is a special method function for creating smooths subject to both monotone decreasing and concavity constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using mixed constrained P-splines. This smooth is specified via model terms such as `s(x,k,bs="mdcv",m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'mdcv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The by variable is the last element.

knots An optional list containing the knots supplied for basis setup. If it is NULL then the knot locations are generated automatically.

Value

An object of class "mdcv.smooth".

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.mpi.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#)

Examples

```
## Not run:
## Monotone decreasing and concave P-splines example
## simulating data...
set.seed(2)
n <- 100
x <- sort(runif(n))
f <- -x^4
y <- f+rnorm(n)*0.10
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="mdcv",m=2),family=gaussian(link="identity"),data=dat)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="ps",m=2),family=gaussian(link="identity"),data=dat)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,f)            ## the true function
lines(x,b$fitted.values,col=2) ## mixed constrained fit
lines(x,b1$fitted.values,col=3) ## unconstrained fit

## End(Not run)
```

 smooth.construct.mdcx.smooth.spec

Constructor for monotone decreasing and convex P-splines in SCAMs

Description

This is a special method function for creating smooths subject to both monotone decreasing and convexity constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using mixed constrained P-splines. This smooth is specified via model terms such as `s(x,k,bs="mdcx",m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'mdcx.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The <code>by</code> variable is the last element.
<code>knots</code>	An optional list containing the knots supplied for basis setup. If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"mdcx.smooth"`.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.mpi.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.micx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#)

Examples

```

## Not run:
## Monotone decreasing and convex P-splines example
## simulating data...
set.seed(2)
n <- 100
x <- sort(runif(n)*3-1)
f1 <- (x-3)^6 # monotone decreasing and convex smooth
f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(n)*0.20
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="mdcx",m=2),family=gaussian(link="identity"),data=dat)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="ps",m=2),family=gaussian(link="identity"),data=dat)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,f) # the true function
lines(x,b$fitted.values,col=2) ## mixed constrained fit
lines(x,b1$fitted.values,col=3) ## unconstrained fit

## End(Not run)

```

```
smooth.construct.micv.smooth.spec
```

Constructor for monotone increasing and concave P-splines in SCAMs

Description

This is a special method function for creating smooths subject to both monotone increasing and concavity constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using mixed constrained P-splines. This smooth is specified via model terms such as `s(x,k,bs="micv",m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'micv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The by variable is the last element.

knots An optional list containing the knots supplied for basis setup. If it is NULL then the knot locations are generated automatically.

Value

An object of class "micv.smooth".

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.mpi.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micx.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#)

Examples

```
## Not run:
## Monotone increasing and concave P-splines example
## simulating data...
set.seed(3)
n <- 100
x <- sort(runif(n)*99+1)
f1 <- log(x)
f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(n)*0.10
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="micv",m=2), data=dat)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="ps",m=2),data=dat)

## plot results ...
plot(x,y,xlab="x",ylab="y")
lines(x,f)          ## the true function
lines(x,b$fitted.values,col=2) ## mixed constrained fit
lines(x,b1$fitted.values,col=3) ## unconstrained fit

## End(Not run)
```

`smooth.construct.micx.smooth.spec`*Constructor for monotone increasing and convex P-splines in SCAMs*

Description

This is a special method function for creating smooths subject to both monotone increasing and convexity constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using the mixed constrained P-splines. This smooth is specified via model terms such as `s(x, k, bs="micx", m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'micx.smooth.spec'  
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The <code>by</code> variable is the last element.
<code>knots</code>	An optional list containing the knots supplied for basis setup. If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"micx.smooth"`.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.mpi.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#), [smooth.construct.mpd.smooth.spec](#)

Examples

```

## Not run:
## Monotone increasing and convex P-splines example
## simulating data...
set.seed(22)
n <- 100
x <- runif(n)*2
f <- x^2
y <- rpois(n,exp(f))
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="micx",m=2),family=poisson(link="log"),
          data=dat,sp=NULL,not.exp=FALSE)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="cr",m=2),family=poisson(link="log"),
          data=dat,sp=NULL)

## plot results ...
plot(x,y,xlab="x",ylab="y")
x1 <- sort(x,index=TRUE)
lines(x1$x,exp(f)[x1$ix])      ## the true function
lines(x1$x,b$fitted.values[x1$ix],col=2) ## mixed constrained fit
lines(x1$x,b1$fitted.values[x1$ix],col=3) ## unconstrained fit

## End(Not run)

```

```
smooth.construct.mpd.smooth.spec
```

Constructor for monotone decreasing P-splines in SCAMs

Description

This is a special method function for creating smooths subject to monotone decreasing constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using monotonic P-splines. This smooth is specified via model terms such as `s(x, k, bs="mpd", m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'mpd.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The by variable is the last element.

knots An optional list containing the knots supplied for basis setup. If it is NULL then the knot locations are generated automatically.

Value

An object of class "mpd.smooth".

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.mpi.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#), [smooth.construct.micx.smooth.spec](#)

Examples

```
## Not run:
## Monotone decreasing P-splines example
## simulating data...
set.seed(3)
n <- 100
x <- runif(n)*3-1
f <- exp(-1.3*x)
y <- rpois(n,exp(f))
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="mpd",m=2),family=poisson(link="log"),
          data=dat,sp=NULL)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="ps",m=2),family=poisson(link="log"),
          data=dat,sp=NULL)

## plot results ...
plot(x,y,xlab="x",ylab="y")
x1 <- sort(x,index=TRUE)
lines(x1$x,exp(f)[x1$ix])        ## the true function
lines(x1$x,b$fitted.values[x1$ix],col=2)    ## monotone fit
lines(x1$x,b1$fitted.values[x1$ix],col=3)   ## unconstrained fit

## End(Not run)
```

`smooth.construct.mpi.smooth.spec`*Constructor for monotone increasing P-splines in SCAMs*

Description

This is a special method function for creating smooths subject to a monotone increasing constraint which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed using monotonic P-splines. This smooth is specified via model terms such as `s(x,k,bs="mpi",m=2)`, where `k` denotes the basis dimension and `m+1` is the order of the B-spline basis.

Usage

```
## S3 method for class 'mpi.smooth.spec'  
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the data required by this term, with names given by <code>object\$term</code> . The <code>by</code> variable is the last element.
<code>knots</code>	An optional list containing the knots supplied for basis setup. If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"mpi.smooth"`.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.mpd.smooth.spec](#), [smooth.construct.cv.smooth.spec](#), [smooth.construct.cx.smooth.spec](#), [smooth.construct.mdcv.smooth.spec](#), [smooth.construct.mdcx.smooth.spec](#), [smooth.construct.micv.smooth.spec](#), [smooth.construct.micx.smooth.spec](#)

Examples

```
## Monotone increasing P-splines example
## simulating data...
set.seed(12)
n <- 100
x <- runif(n)*4-1
f <- 4*exp(4*x)/(1+exp(4*x))
y <- rpois(n,exp(f))
dat <- data.frame(x=x,y=y)
## fit model ...
b <- scam(y~s(x,k=15,bs="mpi",m=2),family=poisson(link="log"),
          data=dat,sp=NULL)

# UNCONSTRAINED FIT *****
b1 <- scam(y~s(x,k=15,bs="ps",m=2),family=poisson(link="log"),
          data=dat,sp=NULL)

## plot results ...
plot(x,y,xlab="x",ylab="y")
x1 <- sort(x,index=TRUE)
lines(x1$x,exp(f)[x1$ix])      ## the true function
lines(x1$x,b$fitted.values[x1$ix],col=2) ## monotone fit
lines(x1$x,b1$fitted.values[x1$ix],col=3) ## unconstrained fit
```

```
smooth.construct.tedecv.smooth.spec
```

Tensor product smoothing constructor for bivariate function subject to mixed constraints: monotone decreasing constraint wrt the first covariate and concavity wrt the second one

Description

This is a special method function for creating tensor product bivariate smooths subject to mixed constraints, monotone decreasing constraint wrt the first covariate and concavity wrt the second one, which is built by the mgcv constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1,x2,k=c(q1,q2),bs="tedecv",m=c(2,2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'tedecv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

object	A smooth specification object, generated by an s term in a GAM formula.
data	A data frame or list containing the values of the elements of object\$term, with names given by object\$term.
knots	An optional list containing the knots corresponding to object\$term. If it is NULL then the knot locations are generated automatically.

Value

An object of class "tedecv.smooth". In addition to the usual elements of a smooth class documented under smooth.construct of the mgcv library, this object contains:

p.ident	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
Zc	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.tedmd.smooth.spec](#) [smooth.construct.temicx.smooth.spec](#) [smooth.construct.tedecx.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tedecv` example
## simulating data...

set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(2*runif(n)-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i]))- 4*x2[j]^2}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
```

```

b <- scam(y~s(x1,x2,k=c(10,10),bs="tedecv",m=2), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b, theta=30)

## End(Not run)

```

```
smooth.construct.tedecx.smooth.spec
```

Tensor product smoothing constructor for bivariate function subject to mixed constraints: monotone decreasing constraint wrt the first covariate and convexity wrt the second one

Description

This is a special method function for creating tensor product bivariate smooths subject to mixed constraints, monotone decreasing constraint wrt the first covariate and convexity wrt the second one, which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tedecx", m=c(2, 2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'tedecx.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tedecx.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.tedmd.smooth.spec](#) [smooth.construct.tedecv.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tedecx' example
## simulating data...

set.seed(1)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(2*runif(n)-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i])) + 2*x2[j]^2}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tedecx",m=2), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b,theta=20,phi=20)

## End(Not run)
```

smooth.construct.tedmd.smooth.spec

Tensor product smoothing constructor for bivariate function subject to double monotone decreasing constraint

Description

This is a special method function for creating tensor product bivariate smooths subject to double monotone decreasing constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tedmd", m=c(2, 2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'tedmd.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tedmd.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tedmi.smooth.spec](#)

Examples

```

## Not run:
## tensor product `tedmd` example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i]))-2*exp(x2[j]-0.5)}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tedmd",m=2),
          family=gaussian(link="identity"), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 80, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")

## End(Not run)

```

```
smooth.construct.tedmi.smooth.spec
```

Tensor product smoothing constructor for bivariate function subject to double monotone increasing constraint

Description

This is a special method function for creating tensor product bivariate smooths subject to double monotone increasing constraints which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1,x2,k=c(q1,q2),bs="tedmi",m=c(2,2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'tedmi.smooth.spec'
smooth.construct(object, data, knots)
```


Arguments

object	A smooth specification object, generated by an s term in a GAM formula.
data	A data frame or list containing the values of the elements of object\$term, with names given by object\$term.
knots	An optional list containing the knots corresponding to object\$term. If it is NULL then the knot locations are generated automatically.

Value

An object of class "tedmi.smooth". In addition to the usual elements of a smooth class documented under smooth.construct of the mgcv library, this object contains:

p.ident	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
Zc	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tedmd.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tedmi' example
## simulating data...
set.seed(1)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- exp(4*x1[i])/(1+exp(4*x1[i]))+2*exp(x2[j]-0.5)}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
```

```

    dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
    b <- scam(y~s(x1,x2,k=c(10,10),bs="tedmi",m=2),family=gaussian, data=dat)
## plot results ...
    par(mfrow=c(2,2),mar=c(4,4,2,2))
    plot(b,se=TRUE)
    plot(b,pers=TRUE,theta = 30, phi = 40)
    plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")

## End(Not run)

```

```
smooth.construct.temicv.smooth.spec
```

Tensor product smoothing constructor for bivariate function subject to mixed constraints: monotone increasing constraint wrt the first covariate and concavity wrt the second one

Description

This is a special method function for creating tensor product bivariate smooths subject to mixed constraints, monotone increasing constraint wrt the first covariate and concavity wrt the second one, which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="temicv", m=c(2, 2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'temicv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"temicv.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.tedmd.smooth.spec](#) [smooth.construct.temicx.smooth.spec](#)

Examples

```
## Not run:
## tensor product `temicv` example
## simulating data...

set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(2*runif(n)-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- exp(4*x1[i])/(1+exp(4*x1[i])) - 4*x2[j]^2}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="temicv",m=2), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b, theta=30)

## End(Not run)
```

smooth.construct.temicx.smooth.spec

Tensor product smoothing constructor for bivariate function subject to mixed constraints: monotone increasing constraint wrt the first covariate and convexity wrt the second one

Description

This is a special method function for creating tensor product bivariate smooths subject to mixed constraints, monotone increasing constraint wrt the first covariate and convexity wrt the second one, which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths which are represented using the B-spline basis functions. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="temicx", m=c(2, 2))`, where `q1` and `q2` denote the basis dimensions for the marginal smooths.

Usage

```
## S3 method for class 'temicx.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"temicx.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.tedmd.smooth.spec](#)

Examples

```
## Not run:
## tensor product `temicx` example
## simulating data...
```

```

set.seed(1)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- exp(4*x1[i])/(1+exp(4*x1[i])) + 2*exp(x2[j]-0.5)}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="temicx",m=2), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b)

## End(Not run)

```

```
smooth.construct.tescv.smooth.spec
```

*Tensor product smoothing constructor for a bivariate function concave
in the second covariate*

Description

This is a special method function for creating tensor product bivariate smooths concave in the second covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tescv", m=c(2, 2))`, where the basis for the first marginal smooth is specified in the second element of `bs`.

Usage

```
## S3 method for class 'tescv.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .

`knots` An optional list containing the knots corresponding to `object$term`. If it is NULL then the knot locations are generated automatically.

Value

An object of class "`tescv.smooth`". In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

`p.ident` A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.

`Zc` A matrix of identifiability constraints.

`margin.class` The class of the first unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.temicv.smooth.spec](#) [smooth.construct.temicx.smooth.spec](#) [smooth.construct.tedecv.smooth.spec](#) [smooth.construct.tedecx.smooth.spec](#) [smooth.construct.tescx.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tescv' example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n))
x2 <- sort(2*runif(n)-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- 2*sin(pi*x1[i]) - 4*x2[j]^2}
f1 <- as.vector(t(f1))
f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tescv",m=2),
          family=gaussian(), data=dat)
## plot results ...
```

```

par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE, theta = 50, phi = 20)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b, theta=30)

## End(Not run)

```

```
smooth.construct.tescx.smooth.spec
```

*Tensor product smoothing constructor for a bivariate function convex
in the second covariate*

Description

This is a special method function for creating tensor product bivariate smooths convex in the second covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tescx", m=c(2, 2))`, where the basis for the first marginal smooth is specified in the second element of `bs`.

Usage

```
## S3 method for class 'tescx.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tescx.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.
<code>margin.class</code>	The class of the first unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

See Also

[smooth.construct.temicv.smooth.spec](#) [smooth.construct.temicx.smooth.spec](#) [smooth.construct.tedecv.smooth.spec](#) [smooth.construct.tedecx.smooth.spec](#) [smooth.construct.tescv.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tescx' example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n))
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- 2*sin(pi*x1[i]) + 2*exp(x2[j]-0.5)}
f1 <- as.vector(t(f1))
f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tescx",m=2),
          family=gaussian(), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE, theta = 50, phi = 20)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b, theta=30)

## End(Not run)
```

smooth.construct.tesmdl.smooth.spec

Tensor product smoothing constructor for a bivariate function monotone decreasing in the first covariate

Description

This is a special method function for creating tensor product bivariate smooths monotone decreasing in the first covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tesmd1", m=2)`.

Usage

```
## S3 method for class 'tesmd1.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tesmd1.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.
<code>margin.class</code>	The class of the second unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tesmd2.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tesmd1` example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- -exp(4*x1[i])/(1+exp(4*x1[i]))+2*sin(pi*x2[j])}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tesmd1",m=2),data=dat,sp=NULL)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")

## End(Not run)
```

```
smooth.construct.tesmd2.smooth.spec
```

Tensor product smoothing constructor for a bivariate function monotone decreasing in the second covariate

Description

This is a special method function for creating tensor product bivariate smooths monotone decreasing in the second covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1,x2,k=c(q1,q2),bs="tesmd2",m=c(2,2))`, where the basis for the first marginal smooth is specified in the second element of `bs`.

Usage

```
## S3 method for class 'tesmd2.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

object	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
data	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
knots	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tesmd2.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.
<code>margin.class</code>	The class of the first unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tesmd1.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tesmd2' example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- exp(4*x1[i])/(1+exp(4*x1[i])) - 2*exp(x2[j]-0.5)}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
```

```

x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tesmd2",m=2),data=dat,sp=NULL)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 90, phi = 60)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b,theta = 90, phi = 60)

## End(Not run)

```

```
smooth.construct.tesmi1.smooth.spec
```

Tensor product smoothing constructor for a bivariate function monotone increasing in the first covariate

Description

This is a special method function for creating tensor product bivariate smooths monotone increasing in the first covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1,x2,k=c(q1,q2),bs="tesmi1",m=2)`, where the basis for the second marginal smooth is specified in the second element of `bs`.

Usage

```
## S3 method for class 'tesmi1.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tesmi1.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.
<code>margin.class</code>	The class of the second unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tesmi2.smooth.spec](#)

Examples

```
## Not run:
## tensor product `tesmi1` example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n)*4-1)
x2 <- sort(runif(n))
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- exp(4*x1[i])/(1+exp(4*x1[i]))+2*sin(pi*x2[j])}
f <- as.vector(t(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tesmi1",m=2), data=dat,sp=NULL)
## plot results ...
par(mfrow=c(2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE,theta = 30, phi = 40)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")

## End(Not run)
```

smooth.construct.tesmi2.smooth.spec

Tensor product smoothing constructor for a bivariate function monotone increasing in the second covariate

Description

This is a special method function for creating tensor product bivariate smooths monotone increasing in the second covariate which is built by the `mgcv` constructor function for smooth terms, `smooth.construct`. It is constructed from a pair of single penalty marginal smooths. This tensor product is specified by model terms such as `s(x1, x2, k=c(q1, q2), bs="tesmi2", m=c(2, 2))`, where the basis for the first marginal smooth is specified in the second element of `bs`.

Usage

```
## S3 method for class 'tesmi2.smooth.spec'
smooth.construct(object, data, knots)
```

Arguments

<code>object</code>	A smooth specification object, generated by an <code>s</code> term in a GAM formula.
<code>data</code>	A data frame or list containing the values of the elements of <code>object\$term</code> , with names given by <code>object\$term</code> .
<code>knots</code>	An optional list containing the knots corresponding to <code>object\$term</code> . If it is <code>NULL</code> then the knot locations are generated automatically.

Value

An object of class `"tesmi2.smooth"`. In addition to the usual elements of a smooth class documented under `smooth.construct` of the `mgcv` library, this object contains:

<code>p.ident</code>	A vector of 0's and 1's for model parameter identification: 1's indicate parameters which will be exponentiated, 0's - otherwise.
<code>Zc</code>	A matrix of identifiability constraints.
<code>margin.class</code>	The class of the first unconstrained marginal smooth.

Author(s)

Natalya Pya <nat.pya@gmail.com>

References

Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559

Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[smooth.construct.tesmi1.smooth.spec](#)

Examples

```

## Not run:
## tensor product `tesmi2` example
## simulating data...
set.seed(2)
n <- 30
x1 <- sort(runif(n))
x2 <- sort(runif(n)*4-1)
f1 <- matrix(0,n,n)
for (i in 1:n) for (j in 1:n)
  { f1[i,j] <- 2*sin(pi*x1[i]) +exp(4*x2[j])/(1+exp(4*x2[j]))}
f1 <- as.vector(t(f1))
f <- (f1-min(f1))/(max(f1)-min(f1))
y <- f+rnorm(length(f))*0.1
x11 <- matrix(0,n,n)
x11[,1:n] <- x1
x11 <- as.vector(t(x11))
x22 <- rep(x2,n)
dat <- list(x1=x11,x2=x22,y=y)
## fit model ...
b <- scam(y~s(x1,x2,k=c(10,10),bs="tesmi2",m=2),
          family=gaussian(link="identity"), data=dat)
## plot results ...
par(mfrow=c(2,2),mar=c(4,4,2,2))
plot(b,se=TRUE)
plot(b,pers=TRUE, theta = 50, phi = 20)
plot(y,b$fitted.values,xlab="Simulated data",ylab="Fitted data")
x11()
vis.scam(b,theta=50,phi=20)

## End(Not run)

```

summary.scam

*Summary for a SCAM fit***Description**

Takes a fitted scam object produced by scam() and produces various useful summaries from it. The same code as in summary.gam of the mgcv package is used here with slight modifications to accept the exponentiated parameters of the shape constrained smooth terms and the corresponding covariance matrix.

Usage

```

## S3 method for class 'scam'
summary(object, dispersion=NULL, freq=FALSE, ...)

## S3 method for class 'summary.scam'
print(x,digits = max(3, getOption("digits") - 3),
      signif.stars = getOption("show.signif.stars"),...)

```

Arguments

object	a fitted scam object as produced by scam().
x	a summary.scam object produced by summary.scam().
dispersion	A known dispersion parameter. NULL to use estimate or default (e.g. 1 for Poisson).
freq	By default p-values for individual terms are calculated using the Bayesian estimated covariance matrix of the parameter estimators. If this is set to TRUE then the frequentist covariance matrix of the parameters is used instead.
digits	controls number of digits printed in output.
signif.stars	Should significance stars be printed alongside output.
...	other arguments.

Value

summary.scam produces the same list of summary information for a fitted scam object as in the unconstrained case summary.gam except for the last element BFGS termination condition.

p.coeff	is an array of estimates of the strictly parametric model coefficients.
p.t	is an array of the p.coeff's divided by their standard errors.
p.pv	is an array of p-values for the null hypothesis that the corresponding parameter is zero. Calculated with reference to the t distribution with the estimated residual degrees of freedom for the model fit if the dispersion parameter has been estimated, and the standard normal if not.
m	The number of smooth terms in the model.
chi.sq	An array of test statistics for assessing the significance of model smooth terms. See details.
s.pv	An array of approximate p-values for the null hypotheses that each smooth term is zero. Be warned, these are only approximate.
se	array of standard error estimates for all parameter estimates.
r.sq	The adjusted r-squared for the model. Defined as the proportion of variance explained, where original variance and residual variance are both estimated using unbiased estimators. This quantity can be negative if your model is worse than a one parameter constant model, and can be higher for the smaller of two nested models! Note that proportion null deviance explained is probably more appropriate for non-normal errors.
dev.expl	The proportion of the null deviance explained by the model.
edf	array of estimated degrees of freedom for the model terms.
residual.df	estimated residual degrees of freedom.
n	number of data.
gcv	minimized GCV score for the model, if GCV used.
ubre	minimized UBRE score for the model, if UBRE used.
scale	estimated (or given) scale parameter.

family	the family used.
formula	the original scam formula.
dispersion	the scale parameter.
pTerms.df	the degrees of freedom associated with each parameteric term (excluding the constant).
pTerms.chi.sq	a Wald statistic for testing the null hypothesis that the each parametric term is zero.
pTerms.pv	p-values associated with the tests that each term is zero. For penalized fits these are approximate. The reference distribution is an appropriate chi-squared when the scale parameter is known, and is based on an F when it is not.
cov.unscaled	The estimated covariance matrix of the parameters (or estimators if freq=TRUE), divided by scale parameter.
cov.scaled	The estimated covariance matrix of the parameters (estimators if freq=TRUE).
p.table	significance table for parameters
s.table	significance table for smooths
p.Terms	significance table for parametric model terms
BFGS termination condition	the value of the maximum component of the scaled GCV/UBRE gradient used as stopping condition. This value is printed if the termination code of the BFGS optimization process is not '1' (not full convergence) (see bfgs_gcv.ubre for details)

WARNING

The p-values are approximate.

Author(s)

Natalya Pya <nat.pya@gmail.com> based on mgcv by Simon Wood

References

- Wood S.N. (2006) *Generalized Additive Models: An Introduction with R*. Chapman and Hall/CRC Press.
- Pya, N. and Wood, S.N. (2015) Shape constrained additive models. *Statistics and Computing*, 25(3), 543-559
- Pya, N. (2010) Additive models with shape constraints. PhD thesis. University of Bath. Department of Mathematical Sciences

See Also

[scam](#)

Examples

```
## Not run:
## simulating data...
n <- 200
set.seed(1)
x1 <- runif(n)*6-3
f1 <- 3*exp(-x1^2) # unconstrained smooth term
x2 <- runif(n)*4-1;
f2 <- exp(4*x2)/(1+exp(4*x2)) # monotone increasing smooth
x3 <- runif(n)*5;
f3 <- -log(x3)/5 # monotone decreasing smooth
f <- f1+f2+f3
y <- f + rnorm(n)*0.3
dat <- data.frame(x1=x1,x2=x2,x3=x3,y=y)
## fit model ...
b <- scam(y~s(x1,k=15,bs="cr",m=2)+s(x2,k=30,bs="mpi",m=2)+s(x3,k=30,bs="mpd",m=2),
          data=dat)

summary(b)
plot(b,pages=1)

## End(Not run)
```

vis.scam

Visualization of SCAM objects

Description

Produces perspective or contour plot views of scam model predictions. The code is a clone of vis.gam of the mgcv package.

Usage

```
vis.scam(x,view=NULL,cond=list(),n.grid=30,too.far=0,col=NA,
         color="heat",contour.col=NULL,se=-1,type="link",
         plot.type="persp",zlim=NULL,nCol=50,...)
```

Arguments

The documentation below is the same as in documentation object [vis.gam](#).
 a scam object, produced by scam()

xview an array containing the names of the two main effect terms to be displayed on the x and y dimensions of the plot. If omitted the first two suitable terms will be used.

cond a named list of the values to use for the other predictor terms (not in view). Variables omitted from this list will have the closest observed value to the median for continuous variables, or the most commonly occurring level for factors. Parametric matrix variables have all the entries in each column set to the observed column entry closest to the column median.

n.grid	The number of grid nodes in each direction used for calculating the plotted surface.
too.far	plot grid nodes that are too far from the points defined by the variables given in view can be excluded from the plot. too.far determines what is too far. The grid is scaled into the unit square along with the view variables and then grid nodes more than too.far from the predictor variables are excluded.
col	The colours for the facets of the plot. If this is NA then if se>0 the facets are transparent, otherwise the colour scheme specified in color is used. If col is not NA then it is used as the facet colour.
color	the colour scheme to use for plots when se<=0. One of "topo", "heat", "cm", "terrain", "gray" or "bw". Schemes "gray" and "bw" also modify the colors used when se>0.
contour.col	sets the colour of contours when using plot.type="contour". Default scheme used if NULL.
se	if less than or equal to zero then only the predicted surface is plotted, but if greater than zero, then 3 surfaces are plotted, one at the predicted values minus se standard errors, one at the predicted values and one at the predicted values plus se standard errors.
type	"link" to plot on linear predictor scale and "response" to plot on the response scale.
plot.type	one of "contour" or "persp".
zlim	a two item array giving the lower and upper limits for the z-axis scale. NULL to choose automatically.
nCol	The number of colors to use in color schemes.
...	other options to pass on to persp , image or contour .

Value

Simply produces a plot.

Author(s)

Simon Wood <simon.wood@r-project.org>

See Also

[persp](#), [vis.gam](#), and [scam](#).

Examples

```
library(scam)

# Example with factor variable
set.seed(0)
fac<-rep(1:4,20)
x <- runif(80)*5;
y <- fac+log(x)/5+rnorm(80)*0.1
```

```
fac <- factor(fac)
b <- scam(y~fac+s(x,bs="mpi"))

vis.scam(b,theta=-35,color="heat") # factor example

# Example with "by" variable

z<-rnorm(80)*0.4
y<-as.numeric(fac)+log(x)*z+rnorm(80)*0.1
b<-scam(y~fac+s(x,by=z))
g <- gam(y~fac+s(x,by=z))

vis.scam(b,theta=-35,color="terrain",cond=list(z=1)) # by variable example
vis.scam(b,view=c("z","x"),theta= 65) # plot against by variable
```

Index

- *Topic **convexity**
 - scam-package, 2
- *Topic **hplot**
 - plot.scam, 15
 - vis.scam, 74
- *Topic **models**
 - anova.scam, 4
 - bfgs_gcv.ubre, 6
 - check.analytical, 8
 - derivative.scam, 9
 - gcv.ubre_grad, 10
 - marginal.matrices.tescv.ps, 11
 - marginal.matrices.tesmi1.ps, 13
 - marginal.matrices.tesmi2.ps, 14
 - plot.scam, 15
 - Predict.matrix.mpi.smooth, 19
 - predict.scam, 21
 - print.scam, 25
 - residuals.scam, 26
 - scam, 27
 - scam-package, 2
 - scam.check, 34
 - scam.fit, 35
 - smooth.construct.cv.smooth.spec, 39
 - smooth.construct.cx.smooth.spec, 40
 - smooth.construct.mdcv.smooth.spec, 42
 - smooth.construct.mdcx.smooth.spec, 44
 - smooth.construct.micv.smooth.spec, 45
 - smooth.construct.micx.smooth.spec, 47
 - smooth.construct.mpd.smooth.spec, 48
 - smooth.construct.mpi.smooth.spec, 50
 - smooth.construct.tedecv.smooth.spec, 51
 - smooth.construct.tedecx.smooth.spec, 53
 - smooth.construct.tedmd.smooth.spec, 54
 - smooth.construct.tedmi.smooth.spec, 56
 - smooth.construct.temicv.smooth.spec, 58
 - smooth.construct.temicx.smooth.spec, 59
 - smooth.construct.tescv.smooth.spec, 61
 - smooth.construct.tescx.smooth.spec, 63
 - smooth.construct.tesmd1.smooth.spec, 64
 - smooth.construct.tesmd2.smooth.spec, 66
 - smooth.construct.tesmi1.smooth.spec, 68
 - smooth.construct.tesmi2.smooth.spec, 69
 - summary.scam, 71
 - vis.scam, 74
- *Topic **monotonicity**
 - scam-package, 2
- *Topic **package**
 - scam-package, 2
- *Topic **regression**
 - anova.scam, 4
 - bfgs_gcv.ubre, 6
 - check.analytical, 8
 - derivative.scam, 9
 - gcv.ubre_grad, 10
 - marginal.matrices.tescv.ps, 11
 - marginal.matrices.tesmi1.ps, 13
 - marginal.matrices.tesmi2.ps, 14

- plot.scam, 15
- Predict.matrix.mpi.smooth, 19
- predict.scam, 21
- print.scam, 25
- residuals.scam, 26
- scam, 27
- scam-package, 2
- scam.check, 34
- scam.fit, 35
- shape.constrained.smooth.terms, 37
- smooth.construct.cv.smooth.spec, 39
- smooth.construct.cx.smooth.spec, 40
- smooth.construct.mdcv.smooth.spec, 42
- smooth.construct.mdcx.smooth.spec, 44
- smooth.construct.micv.smooth.spec, 45
- smooth.construct.micx.smooth.spec, 47
- smooth.construct.mpd.smooth.spec, 48
- smooth.construct.mpi.smooth.spec, 50
- smooth.construct.tedcv.smooth.spec, 51
- smooth.construct.tedcx.smooth.spec, 53
- smooth.construct.tedmd.smooth.spec, 54
- smooth.construct.tedmi.smooth.spec, 56
- smooth.construct.temicv.smooth.spec, 58
- smooth.construct.temicx.smooth.spec, 59
- smooth.construct.tescv.smooth.spec, 61
- smooth.construct.tescx.smooth.spec, 63
- smooth.construct.tesmd1.smooth.spec, 64
- smooth.construct.tesmd2.smooth.spec, 66
- smooth.construct.tesmi1.smooth.spec, 68
- smooth.construct.tesmi2.smooth.spec, 69
- summary.scam, 71
- vis.scam, 74
- *Topic **smooth**
 - anova.scam, 4
 - bfgs_gcv.ubre, 6
 - check.analytical, 8
 - gcv.ubre_grad, 10
 - plot.scam, 15
 - predict.scam, 21
 - print.scam, 25
 - residuals.scam, 26
 - scam, 27
 - scam-package, 2
 - scam.check, 34
 - scam.fit, 35
 - summary.scam, 71
 - vis.scam, 74
- anova.gam, 4, 5
- anova.glm, 4
- anova.scam, 4
- bfgs_gcv.ubre, 6, 10, 11, 27, 28, 30, 35, 73
- check.analytical, 8
- contour, 75
- derivative.scam, 9
- family, 27
- gam, 31
- gam.check, 34
- gamObject, 30
- gcv.ubre_grad, 7, 10, 35
- glm, 27
- image, 75
- marginal.matrices.tescv.ps, 11
- marginal.matrices.tesmi1.ps, 12, 13, 15
- marginal.matrices.tesmi2.ps, 14, 14
- persp, 75
- persp(vis.scam), 74
- plot.scam, 3, 15, 23, 31
- predict.gam, 21, 22
- Predict.matrix, 19

- Predict.matrix.cv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.cx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.mdcv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.mdcx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.micv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.micx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.mpd.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.mpi.smooth, 19
- Predict.matrix.tedecv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tedecx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tedmd.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tedmi.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.temicv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.temicx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tescv.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tescx.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tesmd1.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tesmd2.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tesmi1.smooth
(Predict.matrix.mpi.smooth), 19
- Predict.matrix.tesmi2.smooth
(Predict.matrix.mpi.smooth), 19
- predict.scam, 5, 21, 31
- print.anova.scam (anova.scam), 4
- print.scam, 25
- print.summary.scam (summary.scam), 71

- residuals.gam, 26
- residuals.scam, 26

- s, 31, 37, 38
- scam, 3, 5–9, 11, 18–20, 23, 25, 26, 27, 35–37, 73, 75
- scam-package, 2
- scam.check, 5, 31, 34
- scam.fit, 27, 35
- shape.constrained.smooth.terms, 27, 28, 31, 37
- smooth.construct, 30
- smooth.construct.cv.smooth.spec, 37, 38, 39, 41, 43, 44, 46, 47, 49, 50
- smooth.construct.cx.smooth.spec, 37–39, 40, 43, 44, 46, 47, 49, 50
- smooth.construct.mdcv.smooth.spec, 38, 39, 41, 42, 44, 46, 47, 49, 50
- smooth.construct.mdcx.smooth.spec, 37–39, 41, 43, 44, 46, 47, 49, 50
- smooth.construct.micv.smooth.spec, 38, 41, 43, 44, 45, 47, 49, 50
- smooth.construct.micx.smooth.spec, 37–39, 43, 44, 46, 47, 49, 50
- smooth.construct.mpd.smooth.spec, 38, 39, 41, 43, 44, 46, 47, 48, 50
- smooth.construct.mpi.smooth.spec, 37–39, 41, 43, 44, 46, 47, 49, 50
- smooth.construct.tedecv.smooth.spec, 51, 54, 62, 64
- smooth.construct.tedecx.smooth.spec, 52, 53, 62, 64
- smooth.construct.tedmd.smooth.spec, 38, 52, 54, 54, 57, 59, 60
- smooth.construct.tedmi.smooth.spec, 38, 55, 56
- smooth.construct.temicv.smooth.spec, 58, 62, 64
- smooth.construct.temicx.smooth.spec, 52, 59, 59, 62, 64
- smooth.construct.tescv.smooth.spec, 12, 61, 64
- smooth.construct.tescx.smooth.spec, 12, 62, 63
- smooth.construct.tesmd1.smooth.spec, 12–15, 38, 64, 67
- smooth.construct.tesmd2.smooth.spec, 12, 14, 15, 38, 65, 66
- smooth.construct.tesmi1.smooth.spec, 13–15, 38, 68, 70
- smooth.construct.tesmi2.smooth.spec, 14, 15, 38, 69, 69

`summary.gam`, [4](#)

`summary.scam`, [3–5](#), [25](#), [31](#), [71](#)

`termplot`, [17](#)

`vis.gam`, [74](#), [75](#)

`vis.scam`, [74](#)