

Package ‘Mondrian’

March 4, 2016

Type Package

Title A Simple Graphical Representation of the Relative Occurrence and Co-Occurrence of Events

Description The unique function of this package allows representing in a single graph the relative occurrence and co-occurrence of events measured in a sample.

As examples, the package was applied to describe the occurrence and co-occurrence of different species of bacterial or viral symbionts infecting arthropods at the individual level. The graphics allows determining the prevalence of each symbiont and the patterns of multiple infections (i.e. how different symbionts share or not the same individual hosts).

We named the package after the famous painter as the graphical output recalls Mondrian’s paintings.

Version 1.0-0

Date 2016-03-04

Author Aurélie Siberchicot, Delphine Charif, Gabriel Terraz and Fabrice Vavre

Maintainer Aurélie Siberchicot <aurelie.siberchicot@univ-lyon1.fr>

Imports RColorBrewer

License GPL (>= 2.0)

LazyData yes

Encoding UTF-8

URL <https://github.com/ausiber/Mondrian>

BugReports <https://github.com/ausiber/Mondrian/issues>

NeedsCompilation no

Repository CRAN

Date/Publication 2016-03-04 17:34:11

R topics documented:

Mondrian-package	2
endosymbiont_1pop	2
endosymbiont_3pop	3
mondrian	4

Index**6**

Mondrian-package	<i>A Simple Graphical Representation of the Relative Occurrence and Co-Occurrence of Events</i>
------------------	---

Description

The unique function of this package allows representing in a single graph the relative occurrence and co-occurrence of events measured in a sample.

As examples, the package was applied to describe the occurrence and co-occurrence of different species of bacterial or viral symbionts infecting arthropods at the individual level. The graphics allows determining the prevalence of each symbiont and the patterns of multiple infections (i.e. how different symbionts share or not the same individual hosts).

We named the package after the famous painter as the graphical output recalls Mondrian's paintings.

Details

Package:	Mondrian
Type:	Package
Version:	1.0-0
Date:	2016-01-07
License:	GPL (>=2)

Author(s)

Aurélie Siberchicot <aurelie.siberchicot@univ-lyon1.fr>, Delphine Charif, Gabriel Terraz and Fabrice Vavre

See Also

[mondrian](#)

endosymbiont_1pop	<i>Multiple infection profiles in one population</i>
-------------------	--

Description

Presence/absence data about 3 endosymbionts in each of 10 individuals belonging to the same population.

Usage

```
data("endosymbiont_1pop")
```

Format

A data frame with 10 observations (each individual, in rows) on the following 3 variables (each endosymbiont, in columns): C, H, and W are numeric vectors indicating if the endosymbiont is detected. The presence of a symbiont in an individual is indicated by 1 and its absence by 0.

Examples

```
data(endosymbiont_1pop)

## Compute the occurrence table of multiple infection profiles
rev(table(apply(endosymbiont_1pop, 1, paste, collapse = "")))

## 110 011 010
## 6 2 2
```

endosymbiont_3pop	<i>Multiple infection profiles in three populations</i>
-------------------	---

Description

Presence/absence data of 5 endosymbionts in each of 30 individuals belonging to three distinct populations.

Usage

```
data("endosymbiont_3pop")
```

Format

A data frame with 30 observations (each individual, in rows) on the following 6 variables (including 5 endosymbionts, in columns): pop is a factor (with 3 levels: AlxT, Ma1D and Ms1Ch) indicating which of the three populations each individuals belongs and A, C, H, R and W are numeric vectors indicating if the endosymbiont is detected. The presence of a symbiont in an individual is indicated by 1 and its absence by 0.

Examples

```
data(endosymbiont_3pop)
table(endosymbiont_3pop$pop)

## AlxT  Ma1D  Ms1Ch
## 10    10    10
```

mondrian	<i>Computes and displays the relative occurrence and co-occurrence of events</i>
----------	--

Description

This function allows representing in a single graph the relative occurrence and co-occurrence of events measured in a sample. As examples, the package was applied to describe the occurrence and co-occurrence of different species of bacterial or viral symbionts infecting arthropods at the individual level. The graphics allows determining the prevalence of each symbiont and the patterns of multiple infections (i.e. how different symbionts share or not the same individual hosts). The graphical output recalls Mondrian's paintings.

Usage

```
mondrian(data, labels = colnames(data), xlab = "", ylab = "", main = "",
         col = NULL , pop = NULL, indiv = FALSE, ...)
```

Arguments

data	a data frame or a matrix containing the infection profile of each individual for each symbiont. Rows corresponds to individuals and columns to the symbionts.
labels	a vector containing the symbionts name. By default, labels are the columns name of data.
xlab	a string of characters indicating the x-axis label.
ylab	a string of characters indicating the y-axis label.
main	a string of characters indicating the main title of the displayed output. This string is followed by the number of individuals to constitute the actual main title.
col	a vector containing as many colors as symbionts. See Details .
pop	a number index indicating the number of the column containing the population's factor in data. If it is missing, individuals are considering belonging to a unique population and data must not contain a pop column.
indiv	a logical to draw horizontal lines separating each individual profile.
...	graphical parameters. See plot and par .

Details

By default, rectangles' colors come from the Set1 palette defined by the `brewer.pal` function of the `RColorBrewer` package. This palette automatically proposes distinct colors (more than 2 and less than 10 values).

Value

The `mondrian` function yields two outputs:

- a plot representing the occurrence and co-occurrence of symbionts within individuals, recalling famous Mondrian paintings. Individuals are represented by horizontal lines, and each column represents one symbiont. Horizontal lines (representing individuals) are reordered to optimize the reading. Uninfected individuals are always represented in white. For each column, the coloured area corresponds to the total prevalence of this symbiont. When coloured areas are present in different columns, this indicates co-infection. If individuals belong to different populations (`pop` is not null), the graphical output is a layout with one display for each sub-population and one display where all individuals are considered belonging to a unique population.

- the distinct profiles of multiple infection and their prevalence (considering all symbionts in data) in the whole population and in each sub-population (when `pop` is not null).

See Also

[brewer.pal](#)

Examples

```
data(endosymbiont_1pop)
out1 <- mondrian(endosymbiont_1pop)
out1

## 110 011 010
## 0.6 0.2 0.2

data(endosymbiont_3pop)
out2 <- mondrian(endosymbiont_3pop, pop = 1)
out2

## $AlxT
## 01100
##      1
## $Ma1D
## 10111 10011 01101 00100
## 0.1 0.1 0.1 0.7
## $Ms1Ch
## 10111 10011 10010 10001 00110 00010
## 0.1 0.1 0.4 0.1 0.1 0.2
## $pop
##      10111      10011      10010      10001      01101      01100
## 0.06666667 0.06666667 0.13333333 0.03333333 0.03333333 0.33333333
##      00110      00100      00010
## 0.03333333 0.23333333 0.06666667

names(out2)
## [1] "AlxT" "Ma1D" "Ms1Ch" "pop"
```

Index

*Topic **datasets**

endosymbiont_1pop, 2

endosymbiont_3pop, 3

*Topic **dplot**

mondrian, 4

*Topic **hplot**

mondrian, 4

*Topic **package**

Mondrian-package, 2

brewer.pal, 5

endosymbiont_1pop, 2

endosymbiont_3pop, 3

Mondrian (Mondrian-package), 2

mondrian, 2, 4

Mondrian-package, 2

par, 4

plot, 4