

Package ‘aqfig’

February 19, 2015

Type Package

Title Functions to help display air quality model output and monitoring data

Version 0.8

Date 2013-11-08

Author Jenise Swall, with contributions from Kristen Foley

Maintainer Jenise Swall <jswall@vcu.edu>

Depends geoR

Suggests maps

Description This package contains functions to help display air quality model output and monitoring data, such as creating color scatterplots, color legends, etc.

License Unlimited

LazyLoad yes

NeedsCompilation no

Repository CRAN

Date/Publication 2013-11-09 11:34:23

R topics documented:

aqfig-package	2
aspect.ratio.plot	2
init.fig.dimen	3
kristen.colors	3
ozone1	4
ozone2	5
plot3d.points	5
ragged.image	8
scatterplot.density	10
vertical.image.legend	13

Index	16
--------------	-----------

aqfig-package	<i>Functions to help draw figures displaying air quality data and model output</i>
---------------	--

Description

This package contains several functions to help users draw figures to display air pollution measurements and air quality model output. These include functions to place a color legend to the right of a plot, to draw a scatterplot with the points' colors or sizes reflecting the value of a response variable, etc.

Note

Note that two functions which were previously part of this package, `init.fig.dimen()` and `aspect.plot.ratio()` have been moved to the "figdim" package, which is available from http://www.people.vcu.edu/~jswall/figdim_index.html.

<code>aspect.ratio.plot</code>	<i>This function is now defunct.</i>
--------------------------------	--------------------------------------

Description

This function is now defunct. A newer version can be found in the "figdim" package. See http://www.people.vcu.edu/~jswall/figdim_index.html.

Usage

```
aspect.ratio.plot(...)
```

Arguments

... Since the function is now defunct, a message explaining this will be returned, regardless of the arguments passed.

Details

This function is now defunct. A newer version can be found in the "figdim" package. See http://www.people.vcu.edu/~jswall/figdim_index.html.

Author(s)

Jenise Swall

See Also

[par](#), [plot](#), [image](#), [Devices](#)

init.fig.dimen	<i>Initializes a device for a figure with specified dimensions.</i>
----------------	---

Description

This function is now defunct. A newer version can be found in the "figdim" package. See http://www.people.vcu.edu/~jswall/figdim_index.html.

Usage

```
init.fig.dimen(...)
```

Arguments

... Since the function is now defunct, a message explaining this will be returned, regardless of the arguments passed.

Details

This function is now defunct. A newer version can be found in the "figdim" package. See http://www.people.vcu.edu/~jswall/figdim_index.html.

Author(s)

Jenise Swall

See Also

[par](#)

kristen.colors	<i>Sets up a color palette which is particularly appropriate for use with the <code>scatterplot.density</code> function</i>
----------------	---

Description

This function sets up a color palette with n colors, with gradually changing hues of grey, purple, blue, green, yellow, orange, red, and brown (in this order). This palette is a particularly good choice for `scatterplot.density` function, for which it is the default choice.

Usage

```
kristen.colors(n=64)
```

Arguments

n Number of colors to include in palette.

Details

This function calls [colorRampPalette](#) and returns n colors from this palette.

Value

Returns n colors (in hexadecimal).

Note

This function is called by default by the function [scatterplot.density](#), which is included in this package.

Author(s)

Original code was authored by Kristen Foley and included in the precursor to [scatterplot.density](#). Packaged into a new function by Jenise Swall.

See Also

[colorRampPalette](#)

ozone1

Daily maximum ozone concentrations

Description

This data set gives the daily maximum ozone concentrations (in ppb) observed at a subset of 23 Clean Air Status and Trends Network (CASTNET) monitoring sites on August 9, 2004.

Usage

```
ozone
```

Format

A file in CSV format containing 23 records.

Source

Hourly ozone data at CASTNET sites can be obtained from EPA's Clean Air Status and Trends Network program at <http://www.epa.gov/castnet>. Thanks to Steven Howard for his help collating and summarizing these hourly data.

`ozone2`*Daily maximum ozone concentrations*

Description

This data set gives the daily maximum ozone concentrations (in ppb) observed at a subset of 23 Clean Air Status and Trends Network (CASTNET) monitoring sites on August 10, 2004.

Usage`ozone`**Format**

A file in CSV format containing 23 records.

Source

Hourly ozone data at CASTNET sites can be obtained from EPA's Clean Air Status and Trends Network program at <http://www.epa.gov/castnet>. Thanks to Steven Howard for his help collating and summarizing these hourly data.

`plot3d.points`*Make 3-D scatterplot (using colored or differently-sized points)*

Description

Given a list of points' coordinates and the values observed at those points, return a scatterplot with points located as specified by the coordinates and coded by color and/or size to represent the observed value at the location. This code is basically a wrapper for a call to the function `points.geodata` in the `geoR` package.

Usage

```
plot3d.points(x, y, z, zlim = range(z, na.rm = TRUE),
  add = FALSE, col = heat.colors(12), xlab, ylab,
  pch = 21, cex.min = 1, cex.max = 1,
  symbol.border.col = "black",
  plt.beyond.zlim = FALSE, ...)
```

Arguments

<code>x</code>	x-coordinates of locations at which response values <code>z</code> are recorded.
<code>y</code>	y-coordinates of locations at which response values <code>z</code> are recorded.
<code>z</code>	Response values <code>z</code> observed at locations whose coordinates are given by <code>(x, y)</code> .
<code>zlim</code>	Vector of minimum and maximum values of <code>z</code> to which to assign the two most extreme colors in the <code>col</code> argument (<code>col[1]</code> and <code>col[length(col)]</code>). Default is to use the range of <code>z</code> . This is very much like the <code>zlim</code> argument to the image function.
<code>add</code>	If FALSE (default), the function will begin a new plot. If TRUE, adds scatterplot to a pre-existing plot.
<code>col</code>	Color range to use for the scatterplot, with the first color assigned to <code>zlim[1]</code> and last color assigned to <code>zlim[2]</code> . Default is “ <code>heat.colors(12)</code> ”, as it is for image .
<code>xlab</code>	The label for the x-axis. If not specified by the user, defaults to the expression the user named as parameter <code>x</code> . This behavior is similar to that for plot .
<code>ylab</code>	The label for the y-axis. If not specified by the user, defaults to the expression the user named as parameter <code>y</code> . This behavior is similar to that for plot .
<code>pch</code>	The point symbol to use. Possible values are 21, 22, 23, 24, and 25. This is because points.geodata requires these points, which have outlines around them. Default is a circle (<code>'pch=21'</code>).
<code>cex.min</code>	Minimum amount to shrink/expand the point symbols.
<code>cex.max</code>	Maximum amount to shrink/expand the point symbols. Parameters <code>cex.min</code> and <code>cex.max</code> control the minimum and maximum amounts to shrink/expand the points, based on the value of <code>z</code> . By default, these are both set to one, which makes all the points the same size. For more information, see the help page for points.geodata .
<code>symbol.border.col</code>	This controls the color of the border around the plotting symbol. By default, it is black. If a border is not desired, use <code>'symbol.border.col="transparent"'</code> .
<code>plt.beyond.zlim</code>	IF TRUE, and if <code>zlim</code> is specified by the user, <code>z</code> values beyond the limits given in <code>zlim</code> are plotted. Values less than <code>zlim[1]</code> are plotted in the same color as <code>zlim[1]</code> ; values greater than <code>zlim[2]</code> are plotted in the same color as <code>zlim[2]</code> . If TRUE, and <code>zlim</code> is not specified by the user, <code>zlim[1]</code> and <code>zlim[2]</code> will be assigned the minimum and maximum values of <code>z</code> . In this case, user is warned and <code>plt.beyond.zlim</code> is set to FALSE. Default is <code>plt.beyond.zlim==FALSE</code> .
<code>...</code>	Any other parameters the user adds will be passed to the plot function if <code>'add=FALSE'</code> , and may include options for axis labels, titles, etc.

Details

This function is a wrapper to the [points.geodata](#) function in the `geoR` package.

Value

A scatterplot with points at (x,y). These points are colored according to the corresponding value of z and the colors specified in col. They are sized according to the corresponding value of z and the minimum and maximum sizes specified by cex.min and cex.max.

Author(s)

Jenise Swall

See Also

[points.geodata](#), [points](#)

Examples

```
## Plot ozone at each location using colors from rainbow.colors
## and differently-sized points. Add a legend using function
## vertical.image.legend (included in this package).
data(ozone1)
col.rng <- rev(rainbow(n=10, start=0, end=4/6))
z.rng <- c(40, 90)
plot3d.points(x=ozone1$longitude, y=ozone1$latitude, z=ozone1$daily.max,
             xlab="longitude", ylab="latitude", col=col.rng,
             zlim=z.rng, cex.min=0.5, cex.max=1.5)
## To verify, label the points with their concentrations.
text(ozone1$longitude, ozone1$latitude+0.15, ozone1$daily.max, cex=0.7)
## If maps package is available, put on state lines.
if (require("maps")) map("state", add=TRUE, col="lightgray")
## Put on legend.
vertical.image.legend(col=col.rng, zlim=z.rng)

## Plot second day of ozone data. Note that day 2 experienced a smaller
## range of concentrations, so we plot day 2 on same scale as day 1.
data(ozone1)
data(ozone2)
z.rng <- c(40, 90)
col.rng <- rev(rainbow(n=10, start=0, end=4/6))
dev.new()
plot3d.points(x=ozone2$longitude, y=ozone2$latitude, z=ozone2$daily.max,
             xlab="longitude", ylab="latitude", col=col.rng,
             zlim=z.rng, cex.min=0.5, cex.max=1.5)
## To verify, label the points with their concentrations.
text(ozone2$longitude, ozone2$latitude+0.15, ozone2$daily.max, cex=0.7)
## If maps package is available, put on state lines.
if (require("maps")) map("state", add=TRUE, col="lightgray")
vertical.image.legend(col=col.rng, zlim=z.rng)

## When some z value(s) is/are much lower/higher than the others,
```

```

## the outlying value(s) may appear in color at the extent
## of the range, with the remainder of the data clustered in one (or
## just a few) color bin(s).
x <- 1:9
y <- 1:9
z <- c(0, 47:53, 100)
dev.new()
par(mfrow=c(1,3))
col.rng <- rev(rainbow(n=7, start=0, end=4/6))
plot3d.points(x, y, z, col=col.rng)
text(x, y+0.2, z, cex=0.8)
## In vain, you might try to "fix" this by setting zlim so that the
## color range reflects the main portion of the z values. You may
## assume that the outlying value(s) will show up in the extreme edges
## of the color range, but what will actually happen is that the
## outlying values won't be plotted.
plot3d.points(x, y, z, col=col.rng, zlim=c(47, 53))
text(x, y+0.2, z, cex=0.8)
## Instead, specify zlim to reflect the main portion of the z values,
## and set plt.beyond.zlim=TRUE. Now, z values below zlim[1] will be
## plotted in the same color as zlim[1]; those above zlim[2] will be
## plotted like z values of zlim[2]. But, remember, now there are
## outlying values whose magnitudes cannot be easily ascertained!
plot3d.points(x, y, z, zlim=c(47, 53), col=col.rng, plt.beyond.zlim=TRUE)
text(x, y+0.2, z, cex=0.8)

```

ragged.image

Produces a "ragged" image plot

Description

This code produces an image plot in the case in which there is not a known response value z for every possible combination of x and y . This ragged image plot is a variant of an image plot which is not complete across the entire rectangle of the gridded area.

Usage

```

ragged.image(x, y, z, zlim = range(z, na.rm = TRUE), add = FALSE,
            col = heat.colors(12), xlab, ylab, plt.beyond.zlim = FALSE, ...)

```

Arguments

x	x -coordinates of grid cell centers at which response values z are available.
y	y -coordinates of grid cell centers at which response values z are available.
z	Response values recorded at the grid cell centers whose coordinates are given by (x, y) .

<code>zlim</code>	Vector of minimum and maximum values of <code>z</code> to which to assign the two most extreme colors in the <code>'col'</code> argument (<code>col[1]</code> and <code>col[length(col)]</code>). Default is to use the range of <code>z</code> . This is very much like the <code>'zlim'</code> argument to the <code>image</code> function.
<code>add</code>	If <code>FALSE</code> (default), the ragged image will begin a new plot. If <code>TRUE</code> , adds ragged image to a pre-existing plot.
<code>col</code>	Color range to use for the ragged image, with the first color assigned to <code>zlim[1]</code> and last color assigned to <code>zlim[2]</code> . Default is <code>"heat.colors(12)"</code> , as it is for <code>image</code> .
<code>xlab</code>	The label for the x-axis. If not specified by the user, defaults to the expression the user named as parameter <code>x</code> . This behavior is similar to that for <code>image</code> .
<code>ylab</code>	The label for the y-axis. If not specified by the user, defaults to the expression the user named as parameter <code>y</code> . This behavior is similar to that for <code>image</code> .
<code>plt.beyond.zlim</code>	If <code>TRUE</code> , and if <code>zlim</code> is specified by the user, <code>z</code> values beyond the limits given in <code>zlim</code> are plotted. Values less than <code>zlim[1]</code> are plotted in the same color as <code>zlim[1]</code> ; values greater than <code>zlim[2]</code> are plotted in the same color as <code>zlim[2]</code> . If <code>TRUE</code> , and <code>zlim</code> is not specified by the user, <code>zlim[1]</code> and <code>zlim[2]</code> will be assigned the minimum and maximum values of <code>z</code> . In this case, user is warned and <code>plt.beyond.zlim</code> is set to <code>FALSE</code> . Default is <code>plt.beyond.zlim==FALSE</code> .
<code>...</code>	Any additional parameters to be passed to the <code>image</code> function, if <code>add=FALSE</code> .

Details

This code produces a ragged image plot. This is in contrast to the standard `image` function, which assumes that there is a known response value `z` for every combination of the elements of `x` and `y`, i.e. that there is a complete rectangular grid, or image. A ragged image plot is a variant of the regular image plot which is not complete across the entire rectangle. The user specifies vectors `x`, `y`, and `z`, such that `x` and `y` identify a portion of the grid. This function maps the vector `z` onto a matrix of the type needed for the `image` function, but has `NA` entries for combinations of `x` and `y` that are not listed. The `NA` values are not plotted by `image`, so a ragged image will appear.

Value

A ragged image, i.e. a portion of an image for which we have specified grid cell centers `x` and `y`.

Note

This function is slow if `x`, `y`, and `z` are long vectors.

Author(s)

Jenise Swall

See Also

[image](#), [heat.colors](#)

Examples

```

## Build x, y, and z.
x <- c(1, 2, 3, 1, 2, 3)
y <- c(1, 1, 1, 2, 2, 2)
z <- 1:6
z.mat <- matrix(c(1:6), ncol=2)
col.rng <- terrain.colors(6)
par(mfrow=c(1,2))
## Show complete matrix.
image(x=unique(x), y=unique(y), z.mat, zlim=range(z), col=col.rng,
      xlab="x", ylab="y")
## Plot only part of this as a ragged image. Set z range so that this
## image will use colors consistent with the previous one.
ragged.image(x=x[1:4], y=y[1:4], z=z[1:4], zlim=range(z), col=col.rng,
            xlab="x", ylab="y")

## When some z value(s) is/are much lower/higher than the others,
## the outlying value(s) may appear in color at the extent
## of the range, with the remainder of the data clustered in one (or
## just a few) color bin(s).
x <- c(1, 2, 3, 1, 3, 2, 3, 1, 3)
y <- c(4, 4, 4, 3, 3, 2, 2, 1, 1)
z <- c(0, 47:53, 100)
dev.new()
par(mfrow=c(1,3))
col.rng <- rev(rainbow(n=7, start=0, end=4/6))
ragged.image(x, y, z, col=col.rng)
text(x, y, z, cex=0.8)
## In vain, you might try to "fix" this by setting zlim so that the
## color range reflects the main portion of the z values. You may
## assume that the outlying value(s) will show up in the extreme edges
## of the color range, but what will actually happen is that the
## outlying values won't be plotted.
ragged.image(x, y, z, col=col.rng, zlim=c(47, 53))
text(x, y, z, cex=0.8)
## Instead, specify zlim to reflect the main portion of the z values,
## and set plt.beyond.zlim=TRUE. Now, z values below zlim[1] will be
## plotted in the same color as zlim[1]; those above zlim[2] will be
## plotted like z values of zlim[2]. But, remember, now there are
## outlying values whose magnitudes cannot be easily ascertained!
ragged.image(x, y, z, zlim=c(47, 53), col=col.rng, plt.beyond.zlim=TRUE)
text(x, y, z, cex=0.8)

```

Description

The plotting region of the scatterplot is divided into bins. The number of data points falling within each bin is summed and then plotted using the image function. This is particularly useful when there are so many points that each point cannot be distinctly identified.

Usage

```
scatterplot.density(x, y, zlim, ylim, num.bins=64,
  col=kristen.colors(32), xlab, ylab, main, density.in.percent=TRUE,
  col.regression.line=1, col.one.to.one.line=grey(0.4),
  col.bar.legend=TRUE, plt.beyond.zlim=FALSE, ...)
```

Arguments

x	Vector or matrix of x-coordinates of points to be plotted. Missing values are not permitted.
y	Vector or matrix of y-coordinates of points to be plotted. Missing values are not permitted.
zlim	Vector defining the minimum and maximum of the data density values, to which to assign the two most extreme colors in the col argument. If not specified, the range of the calculated density values to be plotted is used.
ylim	Specification of extreme values that the first and last bins are expected to contain in the x- and y-directions. May be a single vector of the limits for the x and y axes; e.g., using 'ylim=c(0,120)' specifies that, in both the x- and y-directions, the first bin should contain 0 and the last contain 120. May also be a list in the form: 'ylim=list(xlim=c(x1, x2), ylim=c(y1, y2))', allowing for the different ranges on the axes. If not specified, xlim is the range of x and ylim is the range of y. Note that ylim and num.bins together determine how the bins are defined. For more information, see "Details" below.
num.bins	Number of bins to be used when calculating the data density in both the x- and y-directions. May be a single number, e.g. 'num.bins=50', which produces 50 bins in each direction. May also be a list in the form 'num.bins=list(num.bins.x=n1, num.bins.y=n2)' to specify differing numbering of bins for the x- and y-directions. The default is to use 64 bins for both axes ('num.bins=64'). Note that ylim and num.bins together determine how the bins are defined. For more information, see "Details" below.
col	Color range to use when drawing bins, with the first color assigned to 'zlim[1]' and last color assigned to 'zlim[2]'. Default is 'kristen.colors(32)'.
xlab	The label for the x-axis. If not specified by the user, defaults to the expression the user named as parameter x. This behavior is similar to that for image .
ylab	The label for the y-axis. If not specified by the user, defaults to the expression the user named as parameter y. This behavior is similar to that for image .
main	The main title for the density scatterplot. If not specified, the default is "Data Density Plot (%)" when 'density.in.percent=TRUE', and "Data Frequency Plot (counts)" otherwise.

<code>density.in.percent</code>	A logical indicating whether the density values should represent a percentage of the total number of data points, rather than a count value. Default is <code>'density.in.percent=TRUE'</code> .
<code>col.regression.line</code>	A color number or color name for the regression line and estimated regression equation (y as a linear function of x) to be overlaid on density scatterplot. If NULL, the regression line and equation are not displayed. Defaults to a black line and equation text.
<code>col.one.to.one.line</code>	A color number or color name for the regression one-to-one line to be overlaid on density scatterplot. If NULL, the one-to-one line is not displayed. Defaults to a dark grey line. If the one-to-one line is displayed, it will be as a dashed line (<code>'lty=3'</code>).
<code>col.bar.legend</code>	A logical indicating whether a “color legend” of the form given by vertical.image.legend should be displayed. The default is <code>'col.bar.legend=TRUE'</code> .
<code>plt.beyond.zlim</code>	IF TRUE, and if <code>zlim</code> is specified by the user, density values beyond the limits given in <code>zlim</code> are plotted. Values less than <code>'zlim[1]'</code> are plotted in the same color as <code>'zlim[1]'</code> ; values greater than <code>'zlim[2]'</code> are plotted in the same color as <code>'zlim[2]'</code> . If TRUE, and <code>zlim</code> is not specified by the user, <code>'zlim[1]'</code> and <code>'zlim[2]'</code> will be assigned the minimum and maximum values of z . In this case, user is warned and <code>plt.beyond.zlim</code> is set to FALSE. Default is <code>'plt.beyond.zlim=FALSE'</code> .
<code>...</code>	Any additional parameters to be passed to the image function.

Details

The plotting region of the scatterplot is divided into bins. The number of data points falling within each bin is summed and then plotted using the [image](#) function. The default is to plot the percent of the data falling within each bin, rather than a raw count value. The arguments `xylim` and `num.bins` can include different settings for the x - and y -axis. This makes it easier to plot different variables on each axis, e.g. temperature vs. ozone. Note that `xylim` and `num.bins` together determine how the bins are defined.

Note that `xylim` and `num.bins` together determine how the bins are defined. This is done using the [cut](#) function. Assigning values to bins is more complicated than might be expected. For example, values that fall at cutoff points between bins are difficult to deal with. This function accepts the default setting for [cut](#), which assigns values which fall on a cutoff point to the bin on the left; that is, the intervals are open on the left and closed on the right. This means that a point with x -value equal to `'xlim[1]'` and/or y -value equal to `'ylim[1]'` would not be assigned to any interval, which is probably not what the user intends in this circumstance. Therefore, this code determines the number of bins in the x -direction so that `'xlim[1]'` and `'xlim[2]'` are at the center of the first and last bin in the x -direction (and similarly for the y -direction). This means that the first and last bins actually extend a bit past the limits specified. For most applications, which use large numbers of data points and bins, this shouldn't be noticeable, but it may be in smaller examples like the first one given below.

Value

A density scatterplot; that is, a pattern of shaded squares representing the counts/percentages of the points falling in each square.

Author(s)

Original version (plot.density.scatter.plot) by Kristen Foley, adapted for **aqfig** by Jenise Swall

See Also

[vertical.image.legend](#), [kristen.colors](#), [image](#), [cut](#)

Examples

```
## As a simple test case, build x and y vectors consisting only of the
## integers 1-3.
x <- c( rep(1, 7), rep(2, 12), rep(3, 6) )
y <- c( rep(1, 5), rep(2, 2), rep(1, 2), rep(2, 8), rep(3, 2),
        rep(2, 2), rep(3, 4) )

## For this test case, I've totaled the counts below.
count.df <- data.frame(x=rep(1:3, each=3), y=rep(1:3, times=3), ct=c(5,
2, 0, 2, 8, 2, 0, 2, 4) )

## Make a density scatterplot with counts and percentages.
par(mfrow=c(1,2))
scatterplot.density(x, y, num.bins=3, col=heat.colors(7),
                    density.in.percent=FALSE,
                    col.one.to.one.line="green")
text(count.df$x, count.df$y, count.df$ct, col="purple")
scatterplot.density(x, y, num.bins=3, col=heat.colors(7), col.one.to.one.line=1)
text(count.df$x, count.df$y, count.df$ct/sum(count.df$ct))

## An example closer to actual usage.
x <- rnorm(100000,50,5)
y <- 3 + (.89*x) + rnorm(100000,0,5)
par(mfrow=c(1,1))
scatterplot.density(x, y)
```

`vertical.image.legend` *Put color bar legend in the right plot margin.*

Description

Put color bar legend in the right-hand side margin of an existing plot.

Usage

```
vertical.image.legend(zlim, col)
```

Arguments

<code>zlim</code>	Gives the range of z values to which the colors specified in <code>col</code> are assigned.
<code>col</code>	Gives the range of colors to use. To keep multiple plots consistent in terms of the colors assigned to various values, keep <code>zlim</code> and <code>col</code> the same for each of the plots and the legend.

Details

This function works best when there is only one plot on the device, in which case the margin space is straightforward (no confusion between `oma/omi` and `mar/mai`, etc. Originally, this function also assumed that the user had already finished making the main portion of the plot before adding the legend; i.e., the user should **add the legend last**. While the author believes that this issue has been resolved, the author recommends that the user avoid changing the main plot after using this legend command. This function alters the `par` settings to draw the legend, and trying to reset them properly is not straightforward.

Value

Puts vertical color bar legend to the right of the plot.

Note

As noted in the help for `image.plot` in the `fields` package, putting a legend on a plot is harder than it might seem. The user may have to experiment with this function a bit to get it to work well for a specific application. The user may also want to try the previously mentioned `image.plot` function in the `fields` package. (To just add the legend using `image.plot`, use “`legend.only=TRUE`”.)

Author(s)

Jenise Swall

See Also

[image.plot](#)

Examples

```
## Plot ozone at each location using colors from rainbow.colors
## and differently-sized points. Add a legend using function
## vertical.image.legend (included in this package).
data(ozone1)
col.rng <- rev(rainbow(n=10, start=0, end=4/6))
z.rng <- c(40, 90)
plot3d.points(x=ozone1$longitude, y=ozone1$latitude, z=ozone1$daily.max,
              xlab="longitude", ylab="latitude", zlim=z.rng, col=col.rng,
              cex.min=0.5, cex.max=1.5)
```

```
## To verify, label the points with their concentrations.  
text(ozone1$longitude, ozone1$latitude+0.15, ozone1$daily.max, cex=0.7)  
## If maps package is available, put on state lines.  
if (require("maps")) map("state", add=TRUE, col="lightgray")  
## Put on legend.  
vertical.image.legend(col=col.rng, zlim=z.rng)
```

Index

- *Topic **aplot**
 - vertical.image.legend, 13
- *Topic **color**
 - kristen.colors, 3
 - vertical.image.legend, 13
- *Topic **datasets**
 - ozone1, 4
 - ozone2, 5
- *Topic **device**
 - aspect.ratio.plot, 2
 - init.fig.dimen, 3
- *Topic **hplot**
 - aspect.ratio.plot, 2
 - init.fig.dimen, 3
 - kristen.colors, 3
 - plot3d.points, 5
 - ragged.image, 8
 - scatterplot.density, 10
- aqfig (aqfig-package), 2
- aqfig-package, 2
- aspect.ratio.plot, 2
- colorRampPalette, 4
- cut, 12, 13
- Devices, 2
- heat.colors, 9
- image, 2, 6, 9, 11–13
- image.plot, 14
- init.fig.dimen, 3
- kristen.colors, 3, 13
- ozone1, 4
- ozone2, 5
- par, 2, 3, 14
- plot, 2, 6
- plot3d.points, 5
- points, 7
- points.geodata, 5–7
- ragged.image, 8
- scatterplot.density, 3, 4, 10
- vertical.image.legend, 12, 13, 13