

Package ‘citr’

September 20, 2016

Type Package

Title 'RStudio' Add-in to Insert Markdown Citations

Description Functions and an 'RStudio' add-in that search a 'BibTeX'-file to create and insert formatted Markdown citations into the current document.

Version 0.2.0

Date 2016-9-20

URL <https://github.com/crsh/citr>

BugReports <https://github.com/crsh/citr/issues>

Depends R (>= 3.0.0)

Imports RefManageR (>= 0.11.0), yaml (>= 2.1.13), rstudioapi (>= 0.6),
miniUI (>= 0.1.1), shiny (>= 0.13.2), assertthat (>= 0.1),
methods (>= 3.0.0), curl (>= 1.1)

Suggests testthat (>= 1.0.2)

License MIT + file LICENSE

LazyData TRUE

RoxygenNote 5.0.1

NeedsCompilation no

Author Frederik Aust [aut, cre],
Yihui Xie [ctb]

Maintainer Frederik Aust <frederik.aust@uni-koeln.de>

Repository CRAN

Date/Publication 2016-09-20 13:00:00

R topics documented:

insert_citation	2
md_cite	3
md_cite_zotero	4
query_bib	5

Index	6
--------------	----------

insert_citation	<i>Invoke RStudio add-in to insert Markdown citations</i>
-----------------	---

Description

Invoke RStudio add-in to insert Markdown citations

Usage

```
insert_citation(bib_file = getOption("citr.bibliography_path"),  
               use_betterbiblatex = getOption("citr.use_betterbiblatex"))
```

Arguments

bib_file	Character. Path to Bib(La)TeX-file. See details.
use_betterbiblatex	Logical. If use_betterbiblatex = TRUE references are imported from Zotero/Juris-M. Requires that the Better Bib(La)TeX is installed and Zotero/Juris-M is running.

Details

The path to the Bib(La)TeX-file can be set in the global options and is set to `./references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex = TRUE` references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

If `insert_citation` is called while the focus is on a R Markdown document, which includes a YAML front matter with paths to one or more bibliography files, `bib_file` is ignored. Instead the file(s) from the YAML front matter are used.

The addin caches bibliographies to avoid unnecessary hard drive access. If the specified bibliography path or the file paths in the YAML header change the files are reloaded. To manually reload a bibliography at an unchanged location click the action link.

Value

Inserts selected Markdown citation(s) at current location.

Examples

```
## Not run:  
insert_citation()  
  
## End(Not run)
```

md_cite	<i>Insert citation in Markdown format</i>
---------	---

Description

Look up entries in bibliography and insert citation in Markdown format if exactly one match is returned.

Usage

```
md_cite(x, in_paren = TRUE, bib_file = getOption("citr.bibliography_path"),
        cache = TRUE, use_betterbiblatex = getOption("citr.use_betterbiblatex"))
```

Arguments

x	Character. Search terms used to filter bibliography (by author, year, title, and journal fields); Regex is supported.
in_paren	Logical. Determines if citation is in parentheses.
bib_file	Character. Path to Bib(La)TeX-file. See details.
cache	Logical. If cache = TRUE cached bibliography is used, if available. If cache = FALSE bibliography is re-imported on every function call.
use_betterbiblatex	Logical. If use_betterbiblatex = TRUE references are imported from Zotero/Juris-M. Requires that the Better Bib(La)TeX is installed and Zotero/Juris-M is running.

Details

The path to the BibTeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex = TRUE` references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

Value

If the bibliography contains exactly one match the formatted citation is returned, otherwise returns NULL. `md_cite` returns an in-text citation ("`@foo2016`"), `md_cite` returns an in-parenthesis citation ("`[@foo2016]`").

See Also

[insert_citation](#)

Examples

```
## Not run:
  md_cite("foo 2016", bib_file = "references.bib")

## End(Not run)
```

md_cite_zotero	<i>Insert citation in Markdown format from Zotero</i>
----------------	---

Description

Look up entries in Zotero database and insert citation in Markdown format.

Usage

```
md_cite_zotero(in_paren = TRUE,
  bib_file = options("citr.bibliography_path"))
```

Arguments

in_paren	Logical. Determines if citation is in parentheses.
bib_file	Character. Path to Bib(La)TeX-file. See details.

Details

The path to the Bib(La)TeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated.

Value

If the bibliography contains exactly one match the formatted citation is returned, otherwise returns NULL. `md_cite` returns an in-text citation ("`@foo2016`"), `md_cite` returns an in-parenthesis citation ("`[@foo2016]`").

See Also

[insert_citation](#)

Examples

```
## Not run:
  md_cite_zotero(bib_file = "references.bib")

## End(Not run)
```

query_bib	<i>Query bibliography</i>
-----------	---------------------------

Description

Search entries in a bibliography.

Usage

```
query_bib(x, bib_file = getOption("citr.bibliography_path"), cache = TRUE,  
         use_betterbiblatex = getOption("citr.use_betterbiblatex"))
```

Arguments

x	Character. Search terms used to filter bibliography (by author, year, title, and journal fields); Regex is supported.
bib_file	Character. Path to Bib(La)TeX-file. See details.
cache	Logical. If cache = TRUE cached bibliography is used, if available. If cache = FALSE bibliography is re-imported on every function call.
use_betterbiblatex	Logical. If use_betterbiblatex = TRUE references are imported from Zotero/Juris-M. Requires that the Better Bib(La)TeX is installed and Zotero/Juris-M is running.

Details

The path to the BibTeX-file can be set in the global options and is set to `references.bib` when the package is loaded. Once the path is changed in the RStudio addin, the global option is updated. If `use_betterbiblatex = TRUE` references are imported from Zotero/Juris-M rather than from the Bib(La)TeX-file. The Bib(La)TeX-file is then updated to include the inserted reference.

Value

Returns list of class `BibEntry` including all matching bibliography entries.

See Also

[md_cite](#), [insert_citation](#)

Index

BibEntry, [5](#)

insert_citation, [2](#), [3–5](#)

md_cite, [3](#), [5](#)

md_cite_zotero, [4](#)

query_bib, [5](#)