

Package ‘npsurv’

November 15, 2015

Title Non-Parametric Survival Analysis

Version 0.3-4

Date 2015-11-12

Author Yong Wang

Maintainer Yong Wang <yongwang@auckland.ac.nz>

Depends lsei

Imports methods

Description Contains functions for non-parametric survival analysis of exact and interval-censored observations.

License GPL (>= 2)

URL <https://www.stat.auckland.ac.nz/~yongwang>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-11-15 18:28:12

R topics documented:

acfail	2
ap	3
cancer	4
Deltamatrix	5
gastric	6
hazuh	7
icendata	8
idf	9
km	11
leukemia	12
logLikuh	13
marijuana	14
npsurv	15
nzmort	17

plot.npsurv	18
plot.Uhaz	20
uh	23
Uhaz	24

Index	28
--------------	-----------

acfail	<i>Air Conditioner Failure Data</i>
--------	-------------------------------------

Description

Contains the number of operating hours between successive failure times of the air conditioning systems in Boeing airplanes

Usage

```
acfail
```

Format

A numeric vector storing the failure times.

Source

Proschan (1963)

References

Proschan, F. (1963). Theoretical explanation of observed decreasing failure rate. *Technometrics*, **5**, 375-383.

See Also

[Uhaz](#).

Examples

```
data(acfail)
r = Uhaz(acfail, deg=2)
plot(r$h, fn="h")
plot(r$h, fn="d")
```

ap *Angina Pectoris Survival Data*

Description

Contains the survival times in years from the time of diagnosis for 2418 male patients with angina pectoris. Some patients are lost to follow-up, hence giving right-censored observations. Each integer-valued survival time is treated as being censored within a one-year interval.

Usage

ap

Format

A data frame with 30 observations and 3 variables:
L: left-end point of an interval-censored retraction time;
R: right-end point of an interval-censored retraction time;
count: number of patients in the interval.

Source

Lee and Wang (2003), page 92.

References

Lee, E. T. and Wang, J. W. (2003). *Statistical Methods for Survival Data Analysis*. Wiley.

See Also

[npsurv](#).

Examples

```
data(ap)
r = Uhaz(ap, deg=2)           # smooth U-shaped hazard
plot(r$h, fn="h")            # hazard
plot(r$h, fn="d")            # density

# NPMLE and shape-restricted estimation
plot(npsurv(ap), fn="s")      # survival under no shape restriction
plot(r$h, fn="s", add=TRUE)   # survival with smooth U-shaped hazard
```

cancer

Breast Retraction Times after Breast Cancer Treatments.

Description

Contains the breast retraction times in months for 94 breast cancer patients who received either radiation therapy or radiation therapy plus adjuvant chemotherapy.

Usage

cancer

Format

A data frame with 94 observations and 3 variables:

L: left-end points of the interval-censored retraction times;

R: right-end points of the interval-censored retraction times;

group: either RT (radiation therapy) or RCT (radiation therapy plus adjuvant chemotherapy).

Source

Finkelstein and Wolfe (1985).

References

Finkelstein, D. M. and R. A. Wolfe (1985). A semiparametric model for regression analysis of interval-censored failure time data. *Biometrics*, **41**, pp.933-945.

See Also

[npsurv](#).

Examples

```
data(cancer)
i = cancer$group == "RT"
plot(npsurv(cancer[i,1:2]), xlim=c(0,60))
plot(npsurv(cancer[!i,1:2]), add=TRUE, col="green3")
```

Deltamatrix	<i>Delta matrix</i>
-------------	---------------------

Description

Deltamatrix computes the Delta matrix, along with maximal intersection intervals, for a set of intervals.

Usage

```
Deltamatrix(LR)
```

Arguments

LR two-column matrix, each row of which stores an censoring interval of the form $(L_i, R_i]$. If $L_i = R_i$, it is an exact observation.

Details

An intersection interval is a nonempty intersection of any combination of the given intervals, and a maximal intersection interval is an intersection interval that contains no other intersection interval.

The Delta matrix is a matrix of indicators (TRUE or FALSE). The rows correspond to the given interval-censored observations, and the columns the maximal intersection intervals. A TRUE value of the (i,j)-th element means that the i-th observation covers the j-th maximal intersection interval, and a FALSE value the otherwise.

Value

A list consisting of:

left left endpoints of the maximal intersection intervals.
right right endpoints of the maximal intersection intervals.
Delta logical matrix, for the Delta matrix.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. (2008). Dimension-reduced nonparametric maximum likelihood computation for interval-censored data. *Computational Statistics & Data Analysis*, **52**, 2388-2402.

See Also

[icendata](#), [idf](#).

Examples

```
(x = cbind(1:5,1:5*3-2))
Deltamatrix(x)
```

gastric

Gastric Cancer Survival Data

Description

Contains the survival times of 45 gastrointestinal tumor patients who were treated with both chemotherapy and radiotherapy. It has both exact and right-censored observations.

Usage

```
gastric
```

Format

A data frame with 30 observations and 3 variables:
L: left-end points of the interval-censored survival times;
R: right-end points of the interval-censored survival times.

Source

Klein and Moeschberger (2003), page 224.

References

Klein, J. P. and Moeschberger, M. L. (2003). *Survival Analysis: Techniques for Censored and Truncated Data (2nd ed.)*. Springer.

See Also

[npsurv](#), [Uhaz](#).

Examples

```
data(gastric)
plot(npsurv(gastric), col="grey")      # survival function
plot(h0<-Uhaz(gastric, deg=0)$h, fn="s", add=TRUE, col="green3")
plot(h1<-Uhaz(gastric, deg=1)$h, fn="s", add=TRUE)
plot(h2<-Uhaz(gastric, deg=2)$h, fn="s", add=TRUE, col="red3")

plot(h0, fn="h", col="green3")        # hazard function
plot(h1, fn="h", add=TRUE)
plot(h2, fn="h", add=TRUE, col="red3")

plot(h0, fn="d", col="green3")        # density function
```

```
plot(h1, fn="d", add=TRUE)
plot(h2, fn="d", add=TRUE, col="red3")
```

hazuh

Distributional Functions given a U-shaped Hazard Function

Description

Given an object of class uh:

hazuh computes the hazard values;

chazuh computes the cumulative hazard values;

survuh computes the survival function values;

denuh computes the density function values.

Usage

```
hazuh(t, h)
chazuh(t, h)
survuh(t, h)
denuh(t, h)
```

Arguments

t time points at which the function is to be evaluated.
h an object of class uh.

Value

A numeric vector of the function values.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. and Fani, S. (2015). Nonparametric maximum likelihood computation of a U-shaped hazard function. (In preparation)

See Also

[Uhaz](#), [icendata](#), [plot.uh](#)

Examples

```

data(ap)
h = Uhaz(icendata(ap), deg=2)$h
hazuh(0:15, h)      # hazard
chazuh(0:15, h)     # cumulative hazard
survuh(0:15, h)     # survival probability
denuh(0:15, h)      # density

```

icendata

Class of Interval-censored Data

Description

Function `icendata` creates an object of class 'icendata', which can save interval-censored and exact observations.

Function `is.icendata` simply checks if an object is of class 'icendata'.

Usage

```

icendata(x, w=1)
is.icendata(x)

```

Arguments

`x` vector or matrix.
`w` weights or multiplicities of the observations.

Details

If `x` is a vector, it contains only exact observations, with weights given in `w`.

If `x` is a two-column matrix, it contains interval-censored observations and stores their left and right end-points in the first and second column, respectively. If the left and right end-points are equal, then the observation is exact. Weights are provided by `w`.

If `x` is a three-column matrix, it contains interval-censored observations and stores their left and right end-points in the first and second column, respectively. The weight of each observation is the third-column value multiplied by the corresponding weight value in `w`.

It is useful to turn interval-censored (and exact) observations into the format imposed by `icendata` so that they can be processed in a standardized format. Also, exact and interval-censored observations are stored separately in this format and can hence be dealt with more easily. Most functions in the package `npSurv` first ensure that the data has this format before processing.

Observations of zero weights are removed. Identical observations are aggregated.

Value

t	numeric vector, storing exact observations.
wt	numeric vector, storing the weights of exact observations.
o	two-column numeric matrix, storing interval-censored observations.
wo	numeric vector, storing the weights of interval-censored observations.
i1	logical vector, indicating whether exact observations are less than upper.
upper	the largest finite value of t and o.
u	numeric vector, containing 0 and all unique finite values in t and o.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. (2008). Dimension-reduced nonparametric maximum likelihood computation for interval-censored data. *Computational Statistics & Data Analysis*, 52, 2388-2402.

Wang, Y. and S. Fani (2015). *Nonparametric maximum likelihood computation of a U-shaped hazard function*. (In Preparation).

See Also

[npsurv](#), [U haz](#).

Examples

```
data(ap)
(x = icendata(ap))
is.icendata(x)

data(gastric)
icendata(gastric)

data(leukemia)
i = leukemia[,"group"] == "6-MP"
icendata(leukemia[i,1:2])
```

 idf

Interval Distribution Function

Description

idf creates an object of class idf. An idf object stores a distribution function defined on a set of intervals.

Usage

```
idf(left, right, p)
## S3 method for class 'idf'
print(x, ...)
```

Arguments

left, right	left and right endpoints of intervals on which the distribution function is defined.
p	probabilities allocated to the intervals. Probability values will be normalized inside the function.
x	an object of class idf.
...	other arguments for printing.

Details

When left and right endpoints are equal, the intervals reduce to points.

`print.idf` prints an object of class `idf` as a three-column matrix.

Value

left, right	left and right endpoints of intervals on which the distribution function is defined.
p	probabilities allocated to the intervals.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

See Also

[icendata](#), [Deltamatrix](#), [npsurv](#).

Examples

```
idf(1:5, 1:5*3-2, c(1,1,2,2,4))
npsurv(cbind(1:5, 1:5*3-2))$f # NPMLE
```

km *Kaplan-Meier Estimation*

Description

km computes the nonparametric maximum likelihood estimate (NPMLE) of a survival function for right-censored data.

Usage

```
km(data, w=1)
```

Arguments

data vector or matrix, or an object of class `icendata`.
w weights/multiplicities of observations.

Details

For details about the arguments, see `icendata`.

Value

A list consisting of:

f NPMLE, an object of class `idf`.
ll log-likelihood value of the NPMLE `f`.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Kaplan, E. L. and Meier, P. (1958). Nonparametric estimation from incomplete observations. *Journal of the American Statistical Association*, **53**, 457-481.

See Also

[icendata](#), [npsurv](#), [idf](#).

Examples

```
x = cbind(1:5, c(1,Inf,3,4,Inf))
(f = km(x)$f)
plot(f)

data(leukemia)
i = leukemia[, "group"] == "Placebo"
plot(km(leukemia[i,1:2])$f, xlim=c(0,40), col="green3") # placebo
plot(km(leukemia[!i,1:2])$f, add=TRUE)                # 6-MP
```

leukemia

*Remission Times for Acute Leukemia Patients***Description**

Contains remission times in weeks of 42 acute leukemia patients, who received either the treatment of drug 6-mercaptopurine or the placebo treatment. Each remission time is either exactly observed or right-censored.

Usage

```
leukemia
```

Format

A data frame with 42 observations and 3 variables:
 L: left-end points of the interval-censored remission times in weeks;
 R: right-end points of the interval-censored remission times;
 group: either 6-MP (6-mercaptopurine) or Placebo.

Source

Freireich et al. (1963).

References

Freireich, E. O. et al. (1963). The effect of 6-mercaptopurine on the duration of steroid induced remission in acute leukemia. *Blood*, **21**, 699-716.

See Also

[npsurv](#).

Examples

```

data(leukemia)
i = leukemia[,"group"] == "Placebo"
plot(npsurv(leukemia[i,1:2]), xlim=c(0,40), col="green3") # placebo
plot(npsurv(leukemia[!i,1:2]), add=TRUE)                # 6-MP

## Treat each remission time as interval-censored:
x = leukemia
ii = x[,1] == x[,2]
x[ii,2] = x[ii,1] + 1
plot(npsurv(x[i,1:2]), xlim=c(0,40), col="green3")     # placebo
plot(npsurv(x[!i,1:2]), add=TRUE)                      # 6-MP

```

logLikuh

Computes the Log-likelihood Value of a U-shaped Hazard Function

Description

logLikuh returns the log-likelihood value of a U-shaped hazard function, given a data set.

Usage

```
logLikuh(h, data)
```

Arguments

h	an object of class uh.
data	numeric vector or matrix for exact or interval-censored observations, or an object of class icendata.

Value

Log-likelihood value evaluated at h, given data.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. and Fani, S. (2015). Nonparametric maximum likelihood computation of a U-shaped hazard function. (In preparation)

See Also

[Uhaz](#), [icendata](#), [plot.uh](#)

Examples

```
data(ap)
(h0 = uh(.2, NULL, NULL, NULL, NULL, 15, 1)) # Uniform hazard
plot(h0, ylim=c(0,.3))
logLikuh(h0, ap)

r = Uhaz(ap, deg=2)
r$l1
logLikuh(r$h, ap)
plot(r$h, add=TRUE, col="red3")
```

marijuana

Angina Pectoris Survival Data

Description

Contains the answers of 191 California high school students to the question: "When did you first use marijuana?". An answer can be an exact age, or "I have never used it", which gives rise to a right-censored observation, or "I have used it but cannot recall just when the first time was", which gives rise to a left-censored observation.

Usage

```
marijuana
```

Format

A data frame with 21 observations and 3 variables:

L: left-end point of an interval-censored time;

R: right-end point of an interval-censored time;

count: number of students in the interval.

Source

Turnbull and Weiss (1978). See also Klein and Moeschberger (1997), page 17.

References

Turnbull and Weiss (1978). A likelihood ratio statistic for testing goodness of fit with randomly censored data. *Biometrics*, **34**, 367-375.

Klein and Moeschberger (2003). *Survival Analysis: Techniques for Censored and Truncated Data* (2nd ed.). Springer

See Also

[npsurv](#).

Examples

```
data(marijuana)
r = Uhaz(marijuana, deg=2)
plot(r$h, fn="h")
plot(r$h, fn="s")
```

npsurv

Nonparametric Survival Function Estimation

Description

npsurv computes the nonparametric maximum likelihood estimate (NPMLE) of a survival function for general interval-censored data.

Usage

```
npsurv(data, w=1, maxit=100, tol=1e-6, verb=0)
```

Arguments

data	vector or matrix, or an object of class icendata.
w	weights or multiplicities of the observations.
maxit	maximum number of iterations.
tol	tolerance level for stopping the algorithm. It is used as the threshold on the increase of the log-likelihood after each iteration.
verb	verbosity level for printing intermediate results at each iteration.

Details

If data is a vector, it contains only exact observations, with weights given in w.

If data is a matrix with two columns, it contains interval-censored observations, with the two columns storing their left and right end-points, respectively. If the left and right end-points are equal, then the observation is exact. Weights are provided by w.

If data is a matrix with three columns, it contains interval-censored observations, with the first two columns storing their left and right end-points, respectively. The weight of each observation is the third-column value multiplied by the corresponding weight value in w.

The algorithm used for the computing the NPMLE is the constrained Newton method (CNM) that is proposed by Wang (2008).

Inside the function, it detects if data has only right censoring, and if so, the Kaplan-Meier estimate is computed directly by function km.

Value

An object of class npsurv, which is a list consisting of:

f	NPMLE, an object of class idf.
upper	largest finite value in the data.
convergence	= TRUE, converged successfully; = FALSE, maximum number of iterations reached.
ll	log-likelihood value of the NPMLE f.
maxgrad	maximum gradient value of the NPMLE f.
numiter	number of iterations used.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. (2008). Dimension-reduced nonparametric maximum likelihood computation for interval-censored data. *Computational Statistics & Data Analysis*, **52**, 2388-2402.

See Also

[icendata](#), [Deltamatrix](#), [idf](#), [km](#).

Examples

```
## all exact observations
data(acfail)
plot(npsurv(acfail))

## right-censored (and exact) observations
data(gastric)
plot(npsurv(gastric))

data(leukemia)
i = leukemia[,"group"] == "Placebo"
plot(npsurv(leukemia[i,1:2]), xlim=c(0,40), col="blue") # placebo
plot(npsurv(leukemia[!i,1:2]), add=TRUE, col="red")      # 6-MP

## purely interval-censored data
data(ap)
plot(npsurv(ap))

data(cancer)
cancerRT = with(cancer, cancer[group=="RT",1:2])
plot(npsurv(cancerRT), xlim=c(0,60))                  # survival of RT
cancerRCT = with(cancer, cancer[group=="RCT",1:2])
plot(npsurv(cancerRCT), add=TRUE, col="green")        # survival of RCT
```

`nzmort`*New Zealand Mortality in 2000*

Description

Contains the number of deaths of Maori and Non-Maori people at each age in New Zealand in 2000.

Usage

```
nzmort
```

Format

A data frame with 210 observations and 3 variables:

age: at which age the deaths occurred;

deaths: number of people died at the age;

ethnic: either Maori or Non-Maori.

Details

Data contains no age with zero death.

Source

<http://www.mortality.org/>

See Also

[Uhaz](#).

Examples

```
data(nzmort)
x = with(nzmort, nzmort[ethnic=="maori",,])[,1:2] # Maori mortality
# x = with(nzmort, nzmort[ethnic!="maori",,])[,1:2] # Non-Maori mortality

## As exact observations
# Plot hazard functions
h0 = Uhaz(x[,1]+0.5, x[,2], deg=0)$h # U-shaped hazard
plot(h0, fn="h", col="green3", pch=2)
h1 = Uhaz(x[,1]+0.5, x[,2], deg=1)$h # convex hazard
plot(h1, fn="h", add=TRUE, pch=1)
h2 = Uhaz(x[,1]+0.5, x[,2], deg=2)$h # smooth U-shaped hazard
plot(h2, fn="h", add=TRUE, col="red3")

# Plot densities
age = 0:max(x[,1])
count = integer(length(age))
```

```

count[x[, "age"]+1] = x[, "deaths"]
barplot(count/sum(count), space=0, col="lightgrey", ylab="Density")
axis(1, pos=NA, at=0:10*10)
plot(h0, fn="d", add=TRUE, col="green3", pch=2)
plot(h1, fn="d", add=TRUE, col="blue3", pch=1)
plot(h2, fn="d", add=TRUE, col="red3", pch=19)

## As interval-censored observations
# Plot hazard functions
x2 = cbind(x[,1], x[,1]+1, x[,2])
h0 = Uhaz(x2, deg=0)$h # U-shaped hazard
plot(h0, fn="h", col="green3", pch=2)
h1 = Uhaz(x2, deg=1)$h # convex hazard
plot(h1, fn="h", add=TRUE, pch=1)
h2 = Uhaz(x2, deg=2)$h # smooth U-shaped hazard
plot(h2, fn="h", add=TRUE, col="red3", pch=1)

# Plot densities
barplot(count/sum(count), space=0, col="lightgrey")
axis(1, pos=NA, at=0:10*10)
plot(h0, fn="d", add=TRUE, col="green3", pch=2)
plot(h1, fn="d", add=TRUE, col="blue3", pch=1)
plot(h2, fn="d", add=TRUE, col="red3", pch=19)

```

plot.npsurv

Plot Functions for Nonparametric Survival Estimation

Description

plot.npsurv and plot.idf are wrapper functions that call either plotsurvidf or plotgradidf. plotsurvidf plots the survival function of the nonparametric maximum likelihood estimate (NPMLE). plotgradidf plots the gradient function of the NPMLE.

Usage

```

## S3 method for class 'npsurv'
plot(x, ...)
## S3 method for class 'idf'
plot(x, data, fn=c("surv", "grad"), ...)
plotsurvidf(f, style=c("box", "uniform", "left", "right", "midpoint"),
            xlab="Time", ylab="Survival Probability", col="blue3", fill=NA,
            add=FALSE, lty=1, lty.inf=2, xlim, ...)
plotgradidf(f, data, w=1, col1="red3", col2="blue3",
            xlab="Survival Time", ylab="Gradient", xlim, ...)

```

Arguments

x	an object of class npsurv (i.e., an output of function npsurv) or an object of class idf.
fn	either "surv" or "grad", to indicate plotting either the survival or the gradient function.
f	an object of class idf.
style	for how to plot the survival function on a "maximal intersection interval": = box, plot a rectangle, which shows the uncertainty of probability allocation within the interval; = uniform, treat it as a uniform distribution and hence the diagonal line of the rectangle is plotted; = left, plot only the left side of the rectangle; = right, plot only the right side of the rectangle; = midpoint, plot a vertical line at the midpoint of the interval.
xlab, ylab	x- or y-axis label.
add	= TRUE, adds the curve to the existing plot; = FALSE, plots the curve in a new one.
col	color for all line segments, including box/rectangle borders.
fill	color for filling a box/rectangle.
lty	line type
lty.inf	line type for the rectangle that may extend to infinity.
data	vector or matrix that stores observations, or an object of class icendata.
w	additional weights/multiplicities of the observations stored in x.
col1	color for drawing maximal intersection intervals allocated with positive probabilities.
col2	color for drawing all gradients and the maximal intersection intervals allocated with zero probabilities.
xlim	x-coordinate limit points.
...	arguments for other graphical parameters (see par).

Details

plotsurv_{idf} by default chooses a less saturated color for fill than col.

plotgrad_{idf} plots gradient values as vertical lines located as the left endpoints of the maximal intersection intervals. Each maximal intersection interval is plotted as a wider line on the horizontal zero-gradient line, with a circle to represent the open left endpoint of the interval and a solid point the closed right endpoint of the interval. The maximal intersection intervals allocated with positive probabilities have zero gradients, and hence no vertical lines are drawn for them.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. (2008). Dimension-reduced nonparametric maximum likelihood computation for interval-censored data. *Computational Statistics & Data Analysis*, **52**, 2388-2402.

See Also

[icendata](#), [idf](#), [npsurv](#).

Examples

```
data(ap)
plot(r<-npsurv(ap))           # survival function
plot(r$f, ap, fn="g")        # all gradients virtually zeros.

data(cancer)
cancerRT = with(cancer, cancer[group=="RT",1:2])
plot(rt<-npsurv(cancerRT), xlim=c(0,60))           # survival of RT
cancerRCT = with(cancer, cancer[group=="RCT",1:2])
plot(rct<-npsurv(cancerRCT), add=TRUE, col="green3") # survival of RCT
## as uniform distributions.
plot(rt, add=TRUE, style="uniform", col="blue3")
plot(rct, add=TRUE, style="uniform", col="green3")

## plot gradients; must supply data
plot(rt, cancerRT, fn="g")      # for group RT
plotgradidf(rct$f, cancerRCT)  # or, for group RCT
```

plot.Uhaz

Plot Functions for U-shaped Hazard Estimation

Description

plot.Uhaz and plot.uh are wrapper functions that can be used to invoke plot.hazuh, plot.chazuh, plot.survuh, plot.denuh or plot.graduh.

plothazuh plots a U-shaped hazard function.

plotchazuh plots a cumulative hazard function that has a U-shaped hazard function.

plotsurvuh plots the survival function that has a U-shaped hazard function.

plotdenuh plots the density function that has a U-shaped hazard function.

plotgraduh plots the gradient function that has a U-shaped hazard function.

Usage

```
## S3 method for class 'Uhaz'
plot(x, ...)
## S3 method for class 'uh'
```

```

plot(x, data, fn=c("haz", "grad", "surv", "den", "chaz"), ...)
plothazuh(h, add=FALSE, col="darkblue", lty=1, xlim, ylim,
          lwd=2, pch=19, len=500, vert=FALSE, add.knots=TRUE,
          xlab="Time", ylab="Hazard", ...)
plotchazuh(h, add=FALSE, lwd=2, len=500, col="darkblue",
           pch=19, add.knots=TRUE, vert=FALSE, xlim, ylim, ...)
plotdenuh(h, add=FALSE, lty=1, lwd=2, col="darkblue",
          add.knots=TRUE, pch=19, ylim, len=500, vert=FALSE, ...)
plotsurvuh(h, add=FALSE, lty=1, lwd=2, len=500, vert=FALSE,
           col="darkblue", pch=19, add.knots=TRUE, xlim, ylim, ...)
plotgraduh(h, data, w=1, len=500, xlim, ylim, vert=TRUE,
           add=FALSE, xlab="Time", ylab="Gradient",
           col0="red3", col1="blue3", col2="green3", order=0, ...)

```

Arguments

x	an object of class Uhaz, i.e., an output of function Uhaz, or an object of class uh..
h	an object of class uh.
data	vector or matrix that stores observations, or an object of class icendata.
w	additional weights/multiplicities for the observations stored in x.
fn	function to be plotted. It can be = haz, for hazard function; = chaz, for cumulative hazard function; = den, for density function; = surv, for survival function; = gradient, for gradient functions.
xlim, ylim	numeric vectors of length 2, giving the x and y coordinates ranges.
xlab, ylab	x- or y-axis labels.
add	= TRUE, adds the curve to the existing plot; = FALSE, plots the curve in a new one.
col	color used for plotting the curve.
lty	line type for plotting the curve.
lwd	line width for plotting the curve.
len	number of points used to plot a curve.
add.knots	logical, indicating if knots are also plotted.
pch	point character/type for plotting knots.
vert	logical, indicating if grey vertical lines are plotted to show the interval that separates the two discrete measures.
col0	color for gradient function 0, i.e., for the hazard-constant part, or alpha.
col1	color for gradient function 1, i.e., for the hazard-decreasing part.
col2	color for gradient function 1, i.e., for the hazard-increasing part.

order = 0, the gradient functions are plotted;
 = 1, their first derivatives are plotted;
 = 2, their second derivatives are plotted.
 ... arguments for other graphical parameters (see par).

Details

A U-shaped hazard function is given by

$$h(t) = \alpha + \sum_{j=1}^k \nu_j (\tau_j - t)_+^p + \sum_{j=1}^m \mu_j (t - \eta_j)_+^p,$$

where $\alpha, \nu_j, \mu_j \geq 0$, $\tau_1 < \dots < \tau_k \leq \eta_1 < \dots < \eta_m$, and $p \geq 0$.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

Wang, Y. and Fani, S. (2015). Nonparametric maximum likelihood computation of a U-shaped hazard function. (In preparation)

See Also

[icendata](#), [uh](#), [npsurv](#).

Examples

```
## Angina Pectoris Survival Data
data(ap)
plot(r<-Uhaz(ap))           # hazard function for a convex hazard
plot(r, fn="c")             # cumulative hazard function
plot(r, fn="s")             # survival function
plot(r, fn="d")             # density function
plot(r, ap, fn="g")         # gradient functions
plot(r, ap, fn="g", order=1) # first derivatives of gradient functions
plot(r, ap, fn="g", order=2) # second derivatives of gradient functions

## New Zealand Mortality in 2000
data(nzmort)
i = nzmort$ethnic == "maori"
x = nzmort[i,1:2]           # Maori mortality
h = Uhaz(x[,1]+0.5, x[,2], deg=2)$h # smooth U-shaped hazard
plot(h)                     # hazard function
plot(h, fn="d")             # density function
plot(h, fn="s")             # survival function

x2 = nzmort[!i,1:2]        # Non-Maori mortality
h2 = Uhaz(x2[,1]+0.5, x2[,2], deg=2)$h
plot(h2, fn="s", add=TRUE, col="green3")
```

uh	<i>U-shaped Hazard Function</i>
----	---------------------------------

Description

uh creates an object of class uh, which stores a U-shaped hazard function.
`print.uh` prints an object of class uh.

Usage

```
uh(alpha, tau, nu, eta, mu, upper=Inf, deg=1, collapse=TRUE)
## S3 method for class 'uh'
print(x, ...)
```

Arguments

alpha	a nonnegative value, for the constant coefficient.
tau	vector of nonnegative real values, for left knots.
nu	vector of nonnegative values, for masses associated with the left knots.
eta	vector of nonnegative real values, for right knots.
mu	vector of nonnegative real values, for masses associated with the right knots.
upper	a positive value, at which point the hazard starts to become infinite.
deg	nonnegative real number for spline degree (i.e., p in the formula below).
collapse	logical, indicating if identical knots should be collapsed.
x	an object of class uh.
...	other arguments for printing.

Details

A U-shape hazard function, as generalized by Wang and Fani (2015), is given by

$$h(t) = \alpha + \sum_{j=1}^k \nu_j (\tau_j - t)_+^p + \sum_{j=1}^m \mu_j (t - \eta_j)_+^p,$$

where $\alpha, \nu_j, \mu_j \geq 0$, $\tau_1 < \dots < \tau_k \leq \eta_1 < \dots < \eta_m$, and $p \geq 0$ is the spline degree which determines the smoothness of the U-shaped hazard. As p increases, the family of hazard functions becomes increasingly smoother, but at the same time, smaller. When $p = 0$, the hazard function is U-shaped, as studied by Bray et al. (1967). When $p = 1$, the hazard function is convex, as studied by Jankowski and Wellner (2009a,b).

`print.uh` prints an object of class uh. While `alpha`, `upper` and `deg` are printed as they are, `tau` and `nu` are printed as a two-column matrix, and so are `eta` and `mu`.

Value

uh returns an object of class uh. It is a list having elements alpha, tau, nu, eta, mu, upper and deg, which store their corresponding values as described above.

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

- Bray, T. A., Crawford, G. B., and Proschan, F. (1967). *Maximum Likelihood Estimation of a U-shaped Failure Rate Function*. Defense Technical Information Center.
- Jankowski, H. K. and Wellner, J. A. (2009a). Computation of nonparametric convex hazard estimators via profile methods. *Journal of Nonparametric Statistics*, **21**, 505-518.
- Jankowski, H. K. and Wellner, J. A. (2009b). Nonparametric estimation of a convex bathtub-shaped hazard function. *Bernoulli*, **15**, 1010-1035.
- Wang, Y. and Fani, S. (2015). Nonparametric maximum likelihood computation of a U-shaped hazard function. (In preparation)

See Also

[Uhaz](#), [icendata](#), [plot.uh](#)

Examples

```
(h0 = uh(3, 2, 3, 4, 5, 7, deg=0))      # deg = 0
plot(h0, ylim=c(0,20))
(h1 = uh(4, 2, 3, 5, 6, 7, deg=1))    # deg = 1
plot(h1, add=TRUE, col="green3")
(h2 = uh(1, 1:2, 3:4, 5:6, 7:8, 9, deg=2)) # deg = 2
plot(h2, add=TRUE, col="red3")
```

Uhaz

U-shaped Hazard Function Estimation

Description

Uhaz computes the nonparametric maximum likelihood estimate (NPMLE) of a U-shaped hazard function from exact or interval-censored data, or a mix of the two types of data.

Usage

```
Uhaz(data, w=1, deg=1, maxit=100, tol=1e-6, verb=0)
```


Arguments

<code>data</code>	vector or matrix, or an object of class <code>icendata</code> .
<code>w</code>	weights or multiplicities of the observations.
<code>deg</code>	nonnegative real number for spline degree (i.e., p in the formula below).
<code>maxit</code>	maximum number of iterations.
<code>tol</code>	tolerance level for stopping the algorithm. It is used as the threshold on the increase of the log-likelihood after each iteration.
<code>verb</code>	verbosity level for printing intermediate results in each iteration.

Details

If `data` is a vector, it contains only exact observations, with weights given in `w`.

If `data` is a matrix with two columns, it contains interval-censored observations, with the two columns storing their left and right end-points, respectively. If the left and right end-points are equal, then the observation is exact. Weights are provided by `w`.

If `data` is a matrix with three columns, it contains interval-censored observations, with the first two columns storing their left and right end-points, respectively. The weight of each observation is the third-column value multiplied by the corresponding weight value in `w`.

The algorithm used for the computing the NPMLE of a hazard function under the U-shape restriction is proposed by Wang and Fani (2015). Such a hazard function is given by

$$h(t) = \alpha + \sum_{j=1}^k \nu_j (\tau_j - t)_+^p + \sum_{j=1}^m \mu_j (t - \eta_j)_+^p,$$

where $\alpha, \nu_j, \mu_j \geq 0$, $\tau_1 < \dots < \tau_k \leq \eta_1 < \dots < \eta_m$, and $p \geq 0$ is the spline degree which determines the smoothness of the U-shaped hazard. As p increases, the family of hazard functions becomes increasingly smoother, but at the time, smaller. When $p = 0$, the hazard function is U-shaped, as studied by Bray et al. (1967). When $p = 1$, the hazard function is convex, as studied by Jankowski and Wellner (2009a,b).

Note that `deg` (i.e., p in the above mathematical display) can take on any nonnegative real value.

Value

An object of class `Uhaz`, which is a list consisting of:

<code>convergence</code>	= TRUE, converged successfully; = FALSE, maximum number of iterations reached.
<code>grad</code>	gradient values at the knots.
<code>numiter</code>	number of iterations used.
<code>ll</code>	log-likelihood value of the NPMLE h .
<code>h</code>	NPMLE of the U-shaped hazard function, an object of class <code>uh</code> .

Author(s)

Yong Wang <yongwang@auckland.ac.nz>

References

- Bray, T. A., Crawford, G. B., and Proschan, F. (1967). *Maximum Likelihood Estimation of a U-shaped Failure Rate Function*. Defense Technical Information Center.
- Jankowski, H. K. and Wellner, J. A. (2009a). Computation of nonparametric convex hazard estimators via profile methods. *Journal of Nonparametric Statistics*, **21**, 505-518.
- Jankowski, H. K. and Wellner, J. A. (2009b). Nonparametric estimation of a convex bathtub-shaped hazard function. *Bernoulli*, **15**, 1010-1035.
- Wang, Y. and Fani, S. (2015). Nonparametric maximum likelihood computation of a U-shaped hazard function. (In preparation)

See Also

[icendata](#), [nzmort](#).

Examples

```
## Interval-censored observations
data(ap)
(r = Uhaz(ap, deg=0))
plot(r, ylim=c(0,.3))
for(i in 1:6) plot(Uhaz(ap, deg=i/2), add=TRUE, col=i+1)

## Exact observations
data(nzmort)
x = with(nzmort, nzmort[ethnic=="maori",,])[,1:2] # Maori mortality
(h0 = Uhaz(x[,1]+0.5, x[,2], deg=0)$h) # U-shaped hazard
(h1 = Uhaz(x[,1]+0.5, x[,2], deg=1)$h) # convex hazard
(h2 <- Uhaz(x[,1]+0.5, x[,2], deg=2)$h) # smooth U-shaped hazard

plot(h0, pch=2) # plot hazard functions
plot(h1, add=TRUE, col="green3", pch=1)
plot(h2, add=TRUE, col="red3", pch=19)

age = 0:max(x[,1]) # plot densities
count = integer(length(age))
count[x[,"age"]+1] = x[,"deaths"]
barplot(count/sum(count), space=0, col="lightgrey")
axis(1, pos=NA, at=0:10*10)
plot(h0, fn="d", add=TRUE, pch=2)
plot(h1, fn="d", add=TRUE, col="green3", pch=1)
plot(h2, fn="d", add=TRUE, col="red3", pch=19)

plot(h0, fn="s", pch=2) # plot survivals
plot(h1, fn="s", add=TRUE, col="green3", pch=1)
plot(h2, fn="s", add=TRUE, col="red3", pch=19)

## Exact and right-censored observations
data(gastric)
plot(h0<-Uhaz(gastric, deg=0)$h) # plot hazard functions
plot(h1<-Uhaz(gastric, deg=1)$h, add=TRUE, col="green3")
```

```
plot(h2<-Uhaz(gastric, deg=2)$h, add=TRUE, col="red3")

plot(npsurv(gastric), fn="s", col="grey") # plot survival functions
plot(h0, fn="s", add=TRUE)
plot(h1, fn="s", add=TRUE, col="green3")
plot(h2, fn="s", add=TRUE, col="red3")
```

Index

*Topic **datasets**

acfail, 2
ap, 3
cancer, 4
gastric, 6
leukemia, 12
marijuana, 14
nzmort, 17

*Topic **function**

Deltamatrix, 5
hazuh, 7
icendata, 8
idf, 9
km, 11
logLikuh, 13
npsurv, 15
plot.npsurv, 18
plot.Uhaz, 20
uh, 23
Uhaz, 24

acfail, 2
ap, 3

cancer, 4
chazuh (hazuh), 7

Deltamatrix, 5, 10, 16
denuh (hazuh), 7

gastric, 6

hazuh, 7

icendata, 5, 7, 8, 10, 11, 13, 16, 20, 22, 24, 26
idf, 5, 9, 11, 16, 20
is.icendata (icendata), 8

km, 11, 16

leukemia, 12

logLikuh, 13

marijuana, 14

npsurv, 3, 4, 6, 9–12, 14, 15, 20, 22
nzmort, 17, 26

plot.idf (plot.npsurv), 18
plot.npsurv, 18
plot.uh, 7, 13, 24
plot.uh (plot.Uhaz), 20
plot.Uhaz, 20
plotchazuh (plot.Uhaz), 20
plotdenuh (plot.Uhaz), 20
plotgradidf (plot.npsurv), 18
plotgraduh (plot.Uhaz), 20
plothazuh (plot.Uhaz), 20
plotsurvidf (plot.npsurv), 18
plotsurvuh (plot.Uhaz), 20
print.idf (idf), 9
print.uh (uh), 23

survuh (hazuh), 7

uh, 22, 23
Uhaz, 2, 6, 7, 9, 13, 17, 24, 24