

Package ‘spTimer’

August 18, 2015

Type Package

Title Spatio-Temporal Bayesian Modelling Using R

Version 2.0-1

Date 2015-08-19

Author K. Shuvo Bakar & Sujit K. Sahu

Maintainer Shuvo Bakar <shuvo.bakar@gmail.com>

Depends R (>= 2.15.0)

Description Fits, spatially predicts and temporally forecasts large amounts of space-time data using [1] Bayesian Gaussian Process (GP) Models, [2] Bayesian Auto-Regressive (AR) Models, and [3] Bayesian Gaussian Predictive Processes (GPP) based AR Models for spatio-temporal big-n problems.

License GPL (>= 2)

Imports coda, sp, grDevices, graphics, stats, utils

LazyData yes

NeedsCompilation yes

Repository CRAN

Date/Publication 2015-08-18 08:56:00

R topics documented:

spTimer-package	2
confint.spT	3
fitted.spT	4
NYdata	5
plot.spT	6
predict.spT	7
spT.check.locations	15
spT.decay	16
spT.geodist	17
spT.Gibbs	19
spT.grid.coords	29

spT.initials	30
spT.keep.morethan.dist	31
spT.pCOVER	32
spT.priors	33
spT.segment.plot	34
spT.subset	35
spT.time	36
spT.validation	36
summary.spT	37

Index 39

spTimer-package	<i>Spatio-Temporal Bayesian Modelling using R</i>
-----------------	---

Description

This package uses different hierarchical Bayesian spatio-temporal modelling strategies, namely:

- (1) Gaussian processes (GP) models,
- (2) Autoregressive (AR) models,
- (3) Gaussian predictive processes (GPP) based autoregressive models for big-n problem.

Details

Package: spTimer
Type: Package

The back-end code of this package is built under c language.

Main functions used:

> [spT.Gibbs](#)
> [predict.spT](#)

Some other important functions:

> [spT.priors](#)
> [spT.initials](#)
> [spT.decay](#)
> [spT.time](#)

Data descriptions:

> [NYdata](#)

Author(s)

K.S. Bakar & S.K. Sahu
Maintainer: K.S. Bakar <shuvo.bakar@gmail.com>

References

1. Bakar, K.S. & Sahu, S.K. (2015). spTimer: Spatio-Temporal Bayesian Modelling Using R. Journal of Statistical Software. 63(15). 1-32.
2. Sahu, S.K. & Bakar, K.S. (2012). Hierarchical Bayesian Autoregressive Models for Large Space Time Data with Applications to Ozone Concentration Modelling. Applied Stochastic Models in Business and Industry, 28, 395-415.
3. Sahu, S.K., Gelfand, A.E., & Holland, D.M. (2007). High-Resolution Space-Time Ozone Modelling for Assessing Trends. Journal of the American Statistical Association, 102, 1221-1234.
4. Bakar, K.S. (2012). Bayesian Analysis of Daily Maximum Ozone Levels. PhD Thesis, University of Southampton, Southampton, United Kingdom.

See Also

Packages 'spacetime', 'forecast'; 'spBayes'; 'maps'; 'MBA'; 'coda'; website: <http://www.r-project.org/>.

confint.spT

Credible intervals for model parameters.

Description

This function is used to obtain credible intervals for model parameters from the MCMC samples.

Usage

```
## S3 method for class 'spT'
confint(object, parm, level = 0.95, ...)

##
```

Arguments

object	Object of class inheriting from "spT".
parm	a specification of which parameters are to be given credible intervals, a vector of names. If missing, all parameters are considered.
level	The required credible interval.
...	other arguments.

See Also

[spT.Gibbs](#).

Examples

```
## Not run:
##

confint(out) # where out is the output from spT class

##

## End(Not run)
```

fitted.spT	<i>Extract model fitted values.</i>
------------	-------------------------------------

Description

Extract average fitted values and corresponding standard deviations from model.

Usage

```
## S3 method for class 'spT'
fitted(object, ...)

##
```

Arguments

object	Object of class inheriting from "spT".
...	Other arguments.

Value

Mean	Fitted mean values obtained from the MCMC samples.
SD	Corresponding standard deviations.

See Also

[spT.Gibbs.](#)

Examples

```
## Not run:
##

fitted(out) # where out is the output from spT class

##

## End(Not run)
```

NYdata	<i>Observations of ozone concentration levels, maximum temperature and wind speed.</i>
--------	--

Description

This data set contains values of daily 8-hour maximum average ozone concentrations (parts per billion (ppb)), maximum temperature (in degree Celsius), wind speed (knots), and relative humidity, obtained from 28 monitoring sites of New York, USA.

NYgrid: This dataset contains total 6200 rows for 62 days of observations for $10 \times 10 = 100$ grid points.

Usage

NYdata

Format

Columns for NYdata: each contains 1798 observations.

- 1st col = Site index (s.index),
- 2nd col = Longitude,
- 3rd col = Latitude,
- 4th col = Year,
- 5th col = Month,
- 6th col = Day,
- 7th col = Ozone (o8hrmax),
- 8th col = Maximum temperature (cMAXTMP),
- 9th col = Wind speed (WDSP).
- 10th col = Relative humidity (RH).

Source

US EPA

See Also

[NYgrid](#), [spT.Gibbs](#), [spT.subset](#).

Examples

```
## Not run:
##
  library("spTimer")
# NY data
  data(NYdata)
  head(NYdata)
# plots in NY map
  NYsite<-unique(cbind(NYdata[,1:3]))
  head(NYsite)
# map
  library(maps)
  map(database="state",regions="new york")
  points(NYsite[,2:3],pch=19)

# Grid data
  data(NYgrid)
  head(NYgrid)
  grid.coords<-unique(cbind(NYgrid[,8:9]))
  library(maps)
  plot(grid.coords,pch=19,col=1)
  map(database="state",regions="new york",add=TRUE)

##

## End(Not run)
```

plot.spT

Plots for spTimer output.

Description

This function is used to obtain MCMC summary, residual and fitted surface plots.

Usage

```
## S3 method for class 'spT'
plot(x, residuals=FALSE, ...)

##
```

Arguments

x	Object of class inheriting from "spT".
residuals	If TRUE then plot residual vs. fitted and normal qqplot of the residuals. If FALSE then plot MCMC samples of the parameters using coda package. Defaults value is FALSE.
...	Other arguments.

See Also[spT.Gibbs.](#)**Examples**

```
## Not run:
##

plot(out) # where out is the output from spT class
plot(out, residuals=TRUE) # where out is the output from spT class

##

## End(Not run)
```

predict.spT

Spatial and temporal predictions for the spatio-temporal models.

Description

This function is used to obtain spatial predictions in the unknown locations and also to get the temporal forecasts using MCMC samples.

Usage

```
## S3 method for class 'spT'
predict(object, newdata, newcoords, foreStep=NULL, type="spatial",
        nBurn, tol.dist, predAR=NULL, Summary=TRUE, ...)
```

Arguments

object	Object of class inheriting from "spT".
newdata	The data set providing the covariate values for spatial prediction or temporal forecasts. This data should have the same space-time structure as the original data frame.
newcoords	The coordinates for the prediction or forecast sites. The locations are in similar format to coords, see spT.Gibbs .
foreStep	Number of K-step (time points) ahead forecast, K=1,2, ...; Only applicable if type="temporal".
type	If the value is "spatial" then only spatial prediction will be performed at the newcoords which must be different from the fitted sites provided by coords. When the "temporal" option is specified then forecasting will be performed and in this case the newcoords may also contain elements of the fitted sites in which case only temporal forecasting beyond the last fitted time point will be performed.

nBurn	Number of burn-in. Initial MCMC samples to discard before making inference.
tol.dist	Minimum tolerance distance limit between fitted and predicted locations.
predAR	The prediction output, if forecasts are in the prediction locations. Only applicable if type="forecast" and data fitted with the "AR" model.
Summary	To obtain summary statistics for the posterior predicted MCMC samples. Default is TRUE.
...	Other arguments.

Value

pred.samples or fore.samples	Prediction or forecast MCMC samples.
pred.coords or fore.coords	prediction or forecast coordinates.
Mean	Average of the MCMC predictions
Median	Median of the MCMC predictions
SD	Standard deviation of the MCMC predictions
Low	Lower limit for the 95 percent CI of the MCMC predictions
Up	Upper limit for the 95 percent CI of the MCMC predictions
computation.time	The computation time.
model	The model method used for prediction.
type	"spatial" or "temporal".
...	Other values "obsData", "fittedData" and "residuals" are provided only for temporal prediction. This is to analyse the codespTimer forecast output using package forecast through function as.forecast.object .

References

- Bakar, K. S. and Sahu, S. K. (2014) spTimer: Spatio-Temporal Bayesian Modelling Using R. Technical Report, University of Southampton, UK. To appear in the Journal of Statistical Software.
- Sahu, S. K. and Bakar, K. S. (2012) A comparison of Bayesian Models for Daily Ozone Concentration Levels Statistical Methodology , 9, 144-157.
- Sahu, S. K. and Bakar, K. S. (2012) Hierarchical Bayesian auto-regressive models for large space time data with applications to ozone concentration modelling. Applied Stochastic Models in Business and Industry, 28, 395-415.

See Also

[spT.Gibbs](#), [as.forecast.object](#).

Examples

```

## Not run:
##

#####
## The GP models:
#####

##
## Spatial prediction/interpolation
##

# Read data
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define prediction coordinates
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# Spatial prediction using spT.Gibbs output
set.seed(11)
pred.gp <- predict(post.gp, newdata=DataValPred, newcoords=pred.coords)
print(pred.gp)
names(pred.gp)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(pred.gp$Mean))

##
## Temporal prediction/forecast
## 1. In the unobserved locations
##

# Read data
DataValFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValFore<-subset(DataValFore, with(DataValFore, (Day %in% c(30, 31) & Month == 8)))

# define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataValFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62
# in the unobserved locations using output from spT.Gibbs
set.seed(11)
fore.gp <- predict(post.gp, newdata=DataValFore, newcoords=fore.coords,
                  type="temporal", foreStep=2)
print(fore.gp)
names(fore.gp)

# Forecast validations
spT.validation(DataValFore$o8hrmax,c(fore.gp$Mean))

# Use of "forecast" class

```

```

library(forecast)
tmp<-as.forecast.object(fore.gp, site=1) # default for site 1
plot(tmp)
summary(tmp)

##
## Temporal prediction/forecast
## 2. In the observed/fitted locations
##

# Read data
DataFitFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataFitFore<-subset(DataFitFore, with(DataFitFore, (Day %in% c(30, 31) & Month == 8)))

# Define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataFitFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62,
# in the fitted locations using output from spT.Gibbs
set.seed(11)
fore.gp <- predict(post.gp, newdata=DataFitFore, newcoords=fore.coords,
type="temporal", foreStep=2)
print(fore.gp)
names(fore.gp)

# Forecast validations
spT.validation(DataFitFore$o8hrmax,c(fore.gp$Mean)) #

# Use of "forecast" class
library(forecast)
tmp<-as.forecast.object(fore.gp, site=5) # for site 5
plot(tmp)

##
## Fit and spatially prediction simultaneously
##

# Read data
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataFit<-subset(DataFit, with(DataFit, !(Day %in% c(30, 31) & Month == 8)))
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoid large data problem in R
set.seed(11)
post.gp.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSR+RH,

```

```

        data=DataFit, model="GP", coords=coords,
        newcoords=pred.coords, newdata=DataValPred,
        scale.transform="SQRT")
print(post.gp.fitpred)
summary(post.gp.fitpred)
coef(post.gp.fitpred)
plot(post.gp.fitpred,residuals=TRUE)
names(post.gp.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.gp.fitpred$prediction[,1]))

#####
## The AR models:
#####

##
## Spatial prediction/interpolation
##

# Read data
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define prediction coordinates
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# Spatial prediction using spT.Gibbs output
set.seed(11)
pred.ar <- predict(post.ar, newdata=DataValPred, newcoords=pred.coords)
print(pred.ar)
names(pred.ar)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(pred.ar$Mean))

##
## Temporal prediction/forecast
## 1. In the unobserved locations
##

# Read data
DataValFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValFore<-subset(DataValFore, with(DataValFore, (Day %in% c(30, 31) & Month == 8)))

# define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataValFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62
# in the unobserved locations using output from spT.Gibbs
set.seed(11)
fore.ar <- predict(post.ar, newdata=DataValFore, newcoords=fore.coords,
                  type="temporal", foreStep=2, predAR=pred.ar)

```

```

print(fore.ar)
names(fore.ar)

# Forecast validations
spT.validation(DataValFore$o8hrmax,c(fore.ar$Mean))

# Use of "forecast" class
tmp<-as.forecast.object(fore.ar, site=1) # default for site 1
plot(tmp)

##
## Temporal prediction/forecast
## 2. In the observed/fitted locations
##

# Read data
DataFitFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataFitFore<-subset(DataFitFore, with(DataFitFore, (Day %in% c(30, 31) & Month == 8)))

# Define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataFitFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62,
# in the fitted locations using output from spT.Gibbs
set.seed(11)
fore.ar <- predict(post.ar, newdata=DataFitFore, newcoords=fore.coords,
type="temporal", foreStep=2)
print(fore.ar)
names(fore.ar)

# Forecast validations
spT.validation(DataFitFore$o8hrmax,c(fore.ar$Mean)) #

# Use of "forecast" class
tmp<-as.forecast.object(fore.ar, site=1) # default for site 1
plot(tmp)

##
## Fit and spatially prediction simultaneously
##

# Read data
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

```

```

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoid large data problem in R
set.seed(11)
post.ar.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
  data=DataFit, model="AR", coords=coords,
  newcoords=pred.coords, newdata=DataValPred,
  scale.transform="SQRT")
print(post.ar.fitpred)
summary(post.ar.fitpred)
coef(post.ar.fitpred)
names(post.ar.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.ar.fitpred$prediction[,1]))

#####
## The GPP approximation models:
#####

##
## Spatial prediction/interpolation
##

# Read data
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define prediction coordinates
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# Spatial prediction using spT.Gibbs output
set.seed(11)
pred.gpp <- predict(post.gpp, newdata=DataValPred, newcoords=pred.coords)
print(pred.gpp)
names(pred.gpp)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(pred.gpp$Mean))

##
## Temporal prediction/forecast
## 1. In the unobserved locations
##

# Read data
DataValFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValFore<-subset(DataValFore, with(DataValFore, (Day

# define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataValFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62
# in the unobserved locations using output from spT.Gibbs

```

```

set.seed(11)
fore.gpp <- predict(post.gpp, newdata=DataValFore, newcoords=fore.coords,
                    type="temporal", foreStep=2)
print(fore.gpp)
names(fore.gpp)

# Forecast validations
spT.validation(DataValFore$o8hrmax,c(fore.gpp$Mean))

# Use of "forecast" class
tmp<-as.forecast.object(fore.gpp, site=1) # default for site 1
plot(tmp)

##
## Temporal prediction/forecast
## 2. In the observed/fitted locations
##

# Read data
DataFitFore<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataFitFore<-subset(DataFitFore, with(DataFitFore, (Day %in% c(30, 31) & Month == 8)))

# Define forecast coordinates
fore.coords<-as.matrix(unique(cbind(DataFitFore[,2:3])))

# Two-step ahead forecast, i.e., in day 61 and 62,
# in the fitted locations using output from spT.Gibbs
set.seed(11)
fore.gpp <- predict(post.gpp, newdata=DataFitFore, newcoords=fore.coords,
                    type="temporal", foreStep=2)
print(fore.gpp)
names(fore.gpp)

# Forecast validations
spT.validation(DataFitFore$o8hrmax,c(fore.gpp$Mean)) #

# Use of "forecast" class
tmp<-as.forecast.object(fore.gpp, site=1) # default for site 1
plot(tmp)

##
## Fit and spatially prediction simultaneously
##

# Read data
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28),
reverse=TRUE)
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(8,11,12,14,18,21,24,28))
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))

```

```

pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))
knots.coords<-spT.grid.coords(Longitude=c(max(coords[,1]),
      min(coords[,1])),Latitude=c(max(coords[,2]),
      min(coords[,2])), by=c(4,4))

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoid large data problem in R
set.seed(11)
post.gpp.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
      data=DataFit, model="GP", coords=coords, knots.coords=knots.coords,
      newcoords=pred.coords, newdata=DataValPred,
      scale.transform="SQRT")
print(post.gpp.fitpred)
summary(post.gpp.fitpred)
coef(post.gpp.fitpred)
plot(post.gpp.fitpred, residuals=TRUE)
names(post.gpp.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.gpp.fitpred$prediction[,1]))

##

## End(Not run)

```

spT.check.locations *Distance Monitoring Function*

Description

This function is used to check the minimum distance between two locations.

Usage

```
spT.check.locations(fit.locations, pred.locations,
  method="geodetic:km", tol = 5)
```

```
spT.check.sites.inside(coords, method, tol=0.1)
```

Arguments

fit.locations	The locations for the fitted observations.
pred.locations	The locations for the predicted observations.
method	The distance measurement. The available methods are "geodetic:km", "geodetic:mile", "euclidean", "maximum", "manhattan", "canberra", "binary" or "minkowski".
tol	The tolerance limit for the distance.
coords	The longitude and latitude positions in a matrix format.

Details

spT.check.locations is used to check minimum distance between two locations, e.g., fitted and prediction. spT.check.sites.inside is used to check distance within the location points. Here, the tol. limit is 0.01. If output shows nothing then we can say distances are alright. These functions are used to avoid of occurring non-positive definite correlation matrix.

See Also

[spT.geodist](#), [dist](#), [spT.subset](#).

Examples

```
## Not run:
##

data(NYdata)
head(NYdata)
NYsite<-unique(NYdata[,1:3])

# Sample 4 sites randomly from the data NYdata.

r4<-spT.data.selection(data=NYsite, random=TRUE, num.rs=4)

# Choose purposively sites numbered as 2, 8, and 12, 15.

p4<-spT.subset(data=NYsite, s=c(2,8,12,15))

# Check locations of datasets r4 and p4

spT.check.locations(fit.locations=r4, pred.locations=p4,
  method="geodetic:km", tol=5)

#
spT.check.sites.inside(NYsite[,2:3],method="geodetic:km")

# if nothing appears then distances are alright

##

## End(Not run)
```

spT.decay

Choice for sampling spatial decay parameter ϕ .

Description

This function initialises the sampling method for the spatial decay parameter ϕ .

Usage

```
spT.decay(distribution=Gamm(a=2,b=1), tuning=NULL, npoints=NULL, value=NULL)
```

Arguments

distribution	Prior distribution for ϕ . Currently available methods are, Gamm(a,b) and Unif(low,up). One can also used "FIXED" value for ϕ parameter.
tuning	If the Gamma prior distribution is used then we need to define the tuning parameter for sampling ϕ . The tuning is the standard deviation for the normal proposal distribution of the random-walk Metropolis algorithm used to sample ϕ on the log-scale.
npoints	If Unif distribution is used then need to define the number of segments for the range of limits by npoints. Default value is 5.
value	If distribution="FIXED" type is used then need to define the value for ϕ . The default value is 3/dmax where dmax is the maximum distance between the fitting sites provided by coords.

See Also

[spT.Gibbs.](#)

Examples

```
## Not run:
##

# input for random-walk Metropolis within Gibbs
# sampling for phi parameter
spatial.decay<-spT.decay(distribution=Gamm(2,1), tuning=0.08)

# input for discrete sampling of phi parameter
# with uniform prior distribution
spatial.decay<-spT.decay(distribution=Unif(0.01,0.02),npoints=5)

# input for spatial decay if FIXED is used
spatial.decay<-spT.decay(distribution="FIXED", value=0.01)

##

## End(Not run)
```

spT.geodist

Geodetic/geodesic Distance

Description

This geodetic distance provides the distance between the locations in Kilometers (k.m.) and Miles, using spherical law of Cosines.

Usage

```
spT.geodist(Lon, Lat, KM = TRUE)
```

```
spT.geo.dist(point1, point2)
```

```
spT.geo_dist(points)
```

Arguments

Lon	The longitude position.
Lat	The latitude position.
KM	A logical value, if 'TRUE' then output is in 'kilometers', otherwise in 'miles'.
point1	In the form of (longitude, latitude) position.
point2	In the form of (longitude, latitude) position.
points	In the form of points 1:(longitude, latitude) 2:(longitude, latitude) positions.

Details

spT.geodist is used to get geodetic distance in both miles and kilometers. spT.geo.dist is only used to get geodetic distance in kilometers with a different format. spT.geo_dist is only used to get geodetic distance in kilometers with a different format.

See Also

[NYdata](#), [spT.grid.coords](#).

Examples

```
## Not run:
##

# Load 28 ozone monitoring locations of New York.
data(NYdata)
head(NYdata)
NYsite<-unique(NYdata[,1:3])

# Find the geodetic distance in km
spT.geodist(Lon=NYsite$Longitude, Lat=NYsite$Latitude, KM=TRUE)

# Find the geodetic distance in miles
spT.geodist(Lon=NYsite$Longitude, Lat=NYsite$Latitude, KM=FALSE)

##

# using spT.geo.dist
point1<-c(-73.757,42.681)
point2<-c(-73.881,40.866)
spT.geo.dist(point1,point2)

# using spT.geo_dist
```

```

points<-c(point1,point2)
spT.geo_dist(points)

##

## End(Not run)

```

spT.Gibbs

MCMC sampling for the spatio-temporal models.

Description

This function is used to draw MCMC samples using the Gibbs sampler.

Usage

```

spT.Gibbs(formula, data=parent.frame(), model="GP", time.data=NULL,
coords, knots.coords, newcoords=NULL, newdata=NULL, priors=NULL,
initials=NULL, nItr=5000, nBurn=1000, report=1, tol.dist=0.05,
distance.method="geodetic:km", cov.fnc="exponential", scale.transform="NONE",
spatial.decay=spT.decay(distribution="FIXED"), annual.aggrn="NONE")

```

Arguments

formula	The symbolic description of the model equation of the regression part of the space-time model.
data	An optional data frame containing the variables in the model. If omitted, the variables are taken from environment(formula), typically the environment from which spT.Gibbs is called. The data should be ordered first by the time and then by the sites specified by the coords below. One can also supply coordinates through this argument, where coordinate names should be "Latitude" and "Longitude".
model	The spatio-temporal models to be fitted, current choices are: "GP", "AR", and "GPP" with the first one as the default.
time.data	Defining the segments of the time-series set up using the function spT.time .
coords	The n by 2 matrix or data frame defining the locations (e.g., longitude/easting, latitude/northing) of the fitting sites, where n is the number of fitting sites. One can also supply coordinates through a formula argument such as ~Longitude+Latitude.
knots.coords	The locations of the knots in similar format to coords above, only required if model="GPP".
newcoords	The locations of the prediction sites in similar format to coords above, only required if fit and predictions are to be performed simultaneously. If omitted, no predictions will be performed.
newdata	The covariate values at the prediction sites specified by newcoords. This should have same space-time structure as the original data frame.

priors	The prior distributions for the parameters. Default distributions are specified if these are not provided. If priors=NULL a flat prior distribution will be used with large variance. See details in spT.priors .
initials	The preferred initial values for the parameters. If omitted, default values are provided automatically. Further details are provided in spT.initials .
nItr	Number of MCMC iterations. Default value is 5000.
nBurn	Number of burn-in samples. This number of samples will be discarded before making any inference. Default value is 1000.
report	Number of reports to display while running the Gibbs sampler. Defaults to number of iterations.
distance.method	The preferred method to calculate the distance between any two locations. The available options are "geodetic:km", "geodetic:mile", "euclidean", "maximum", "manhattan", and "canberra". See details in dist . The default is "geodetic:km".
tol.dist	Minimum separation distance between any two locations out of those specified by coords, knots.coords and pred.coords. The default is 0.005. The programme will exit if the minimum distance is less than the non-zero specified value. This will ensure non-singularity of the covariance matrices.
cov.fnc	Covariance function for the spatial effects. The available options are "exponential", "gaussian", "spherical" and "matern". If "matern" is used then by default the smooth parameter (ν) is estimated from (0,1) uniform distribution using discrete samples.
scale.transform	The transformation method for the response variable. Currently implemented options are: "NONE", "SQRT", and "LOG" with "NONE" as the default.
spatial.decay	Provides the prior distribution for the spatial decay parameter ϕ . Currently implemented options are "FIXED", "Unif", or "Gamm". Further details for each of these are specified by spT.decay .
annual.aggrn	This provides the options for calculating annual summary statistics by aggregating different time segments (e.g., annual mean). Currently implemented options are: "NONE", "ave" and "an4th", where "ave" = annual average, "an4th"= annual 4th highest. Only applicable if spT.time inputs more than one segment and when fit and predict are done simultaneously.

Value

accept	The acceptance rate for the ϕ parameter if the "MH" method of sampling is chosen.
phip	MCMC samples for the parameter ϕ .
nup	MCMC samples for the parameter ν . Only available if "matern" covariance function is used.
sig2eps	MCMC samples for the parameter σ_ϵ^2 .
sig2etap	MCMC samples for the parameter σ_η^2 .
betap	MCMC samples for the parameter β .

rhop	MCMC samples for ρ for the AR or GPP model.
op	MCMC samples for the true observations.
fitted	MCMC summary (mean and sd) for the fitted values.
tol.dist	Minimum tolerance distance limit between the locations.
distance.method	Name of the distance calculation method.
cov.fnc	Name of the covariance function used in model fitting.
scale.transform	Name of the scale.transformation method.
sampling.sp.decay	The method of sampling for the spatial decay parameter ϕ .
covariate.names	Name of the covariates used in the model.
Distance.matrix	The distance matrix.
coords	The coordinate values.
n	Total number of sites.
r	Total number of segments in time, e.g., years.
T	Total points of time, e.g., days within each year.
p	Total number of model coefficients, i.e., β 's including the intercept.
initials	The initial values used in the model.
priors	The prior distributions used in the model.
PMCC	The predictive model choice criteria obtained by minimising the expected value of a loss function, see Gelfand and Ghosh (1998). Results for both goodness of fit and penalty are given.
iterations	The number of samples for the MCMC chain, without burn-in.
nBurn	The number of burn-in period for the MCMC chain.
computation.time	The computation time required for the fitted model.
model	The spatio-temporal model used for analyse the data.
Text Output	This option is only applicable when fit and predictions are done simultaneously.

For GP models:

OutGP_Values_Parameter.txt: (nItr x parameters matrix) has the MCMC samples for the parameters, ordered as: beta's, sig2eps, sig2eta, and phi.

OutGP_Stats_FittedValue.txt: (N x 2) matrix of fitted summary, with 1st column as mean and 2nd column as standard deviations, where N=nrT.

OutGP_Stats_PredValue.txt: ((predsites*r*T) x 2) matrix of prediction summary, with 1st column as mean and 2nd column as standard deviations.

OutGP_Values_Prediction.txt: (nItr x (predsites*r*T)) matrix of MCMC predicted values in the predicted sites.

If annual.aggregation="ave" then we get text output as:

OutGP_Annual_Average_Prediction.txt: (nItr x (predsites*r)) matrix.

If `annual.aggregation="an4th"` then we get text output as:
`OutGP_Annual_4th_Highest_Prediction.txt`: (nItr x (predsites*r)) matrix.

For AR models:

`OutAR_Values_Parameter.txt`: (nItr x parameters matrix) has the MCMC samples for the parameters, ordered as: beta's, rho, sig2eps, sig2eta, mu_1's, sig2l's and phi.

`OutAR_Stats_TrueValue.txt`: (N x 2) matrix of true summary values, with 1st column as mean and 2nd column as standard deviations.

`OutAR_Stats_FittedValue.txt`: (N x 2) matrix of fitted summary, with 1st column as mean and 2nd column as standard deviations.

`OutAR_Stats_PredValue.txt`: ((predsites*r*T) x 2) matrix of prediction summary, with 1st column as mean and 2nd column as standard deviations.

`OutAR_Values_Prediction.txt`: (nItr x (predsites*r*T)) matrix of MCMC predicted values in the predicted sites.

If `annual.aggregation="ave"` then we get text output as:

`OutAR_Annual_Average_Prediction.txt`: (nItr x (predsites*r)) matrix.

If `annual.aggregation="an4th"` then we get text output as:

`OutAR_Annual_4th_Highest_Prediction.txt`: (nItr x (predsites*r)) matrix.

For models using GPP approximations:

`OutGPP_Values_Parameter.txt`: (nItr x parameters matrix) has the MCMC samples for the parameters, ordered as: beta's, rho, sig2eps, sig2eta, and phi.

`OutGPP_Stats_FittedValue.txt`: (N x 2) matrix of fitted summary, with 1st column as mean and 2nd column as standard deviations.

`OutGPP_Stats_PredValue.txt`: ((predsites*r*T) x 2) matrix of prediction summary, with 1st column as mean and 2nd column as standard deviations.

`OutGPP_Values_Prediction.txt`: (nItr x (predsites*r*T)) matrix of MCMC predicted values in the predicted sites.

If `annual.aggregation="ave"` then we get text output as:

`OutGPP_Annual_Average_Prediction.txt`: (nItr x (predsites*r)) matrix.

If `annual.aggregation="an4th"` then we get text output as:

`OutGPP_Annual_4th_Highest_Prediction.txt`: (nItr x (predsites*r)) matrix.

References

1. Bakar, K.S. & Sahu, S.K. (2015). spTimer: Spatio-Temporal Bayesian Modelling Using R. *Journal of Statistical Software*. 63(15). 1-32.
2. Sahu, S.K. & Bakar, K.S. (2012). Hierarchical Bayesian Autoregressive Models for Large Space Time Data with Applications to Ozone Concentration Modelling. *Applied Stochastic Models in Business and Industry*, 28, 395-415.
3. Sahu, S.K., Gelfand, A.E., & Holland, D.M. (2007). High-Resolution Space-Time Ozone Modelling for Assessing Trends. *Journal of the American Statistical Association*, 102, 1221-1234.
4. Bakar, K.S. (2012). Bayesian Analysis of Daily Maximum Ozone Levels. PhD Thesis, University of Southampton, Southampton, United Kingdom.

See Also

[spT.priors](#), [spT.initials](#), [spT.geodist](#), [dist](#), [summary.spT](#), [plot.spT](#), [predict.spT](#).

Examples

```
## Not run:
##

#####
## Attach library spTimer
#####

library(spTimer)

#####
## The GP models:
#####

##
## Model fitting
##

# Read data
data(NYdata)

# MCMC via Gibbs using default choices
set.seed(11)
post.gp <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                    data=NYdata, model="GP", coords=~Longitude+Latitude,
                    scale.transform="SQRT")
print(post.gp)

# MCMC via Gibbs not using default choices
# Read data
s<-c(8,11,12,14,18,21,24,28)
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=s, reverse=TRUE)
DataFit<-subset(DataFit, with(DataFit, !(Day %in% c(30, 31) & Month == 8)))
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=s)
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# define the time-series
time.data<-spT.time(t.series=60,segment=1)

# hyper-parameters for the prior distributions
priors<-spT.priors(model="GP", inv.var.prior=Gamm(2,1),
                 beta.prior=Norm(0,10^4))

# initial values for the model parameters
initials<-spT.initials(model="GP", sig2eps=0.01,
                      sig2eta=0.5, beta=NULL, phi=0.001)

# input for spatial decay, any one approach from below
```

```

#spatial.decay<-spT.decay(distribution="FIXED", value=0.01)
spatial.decay<-spT.decay(distribution=Gamm(2,1), tuning=0.08)
#spatial.decay<-spT.decay(distribution=Unif(0.01,0.02),npoints=5)

# Iterations for the MCMC algorithms
nItr<-5000

# MCMC via Gibbs
set.seed(11)
post.gp <- spT.Gibbs(formula=o8hrmax ~ cMAXTMP+WDSP+RH,
  data=DataFit, model="GP", time.data=time.data,
  coords=~Longitude+Latitude, priors=priors, initials=initials,
  nItr=nItr, nBurn=0, report=nItr,
  tol.dist=2, distance.method="geodetic:km",
  cov.fnc="exponential", scale.transform="SQRT",
  spatial.decay=spatial.decay)
print(post.gp)

# Summary and plots
summary(post.gp)
summary(post.gp,pack="coda")
plot(post.gp)
plot(post.gp,residuals=TRUE)

coef(post.gp)
confint(post.gp)
terms(post.gp)
formula(post.gp)
model.frame(post.gp)
model.matrix(post.gp)

# Model selection criteria
post.gp$PMCC

##
## Fit and spatially prediction simultaneously
##

# Read data
s<-c(8,11,12,14,18,21,24,28)
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=s, reverse=TRUE)
DataFit<-subset(DataFit, !(Day %in% c(30, 31) & Month == 8))
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=s)
DataValPred<-subset(DataValPred, !(Day %in% c(30, 31) & Month == 8))

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoide large data problem in R
set.seed(11)
post.gp.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,

```



```

        data=DataFit, model="GP", coords=coords,
        newcoords=pred.coords, newdata=DataValPred,
        scale.transform="SQRT")
print(post.gp.fitpred)
summary(post.gp.fitpred)
coef(post.gp.fitpred)
plot(post.gp.fitpred)
names(post.gp.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.gp.fitpred$prediction[,1]))

#####
## The GP model for sp class data
#####

# Creating sp class data
library(sp)
data(meuse)
summary(meuse)
coordinates(meuse) <- ~x+y
class(meuse)
out<-spT.Gibbs(formula=zinc~sqrt(dist),data=meuse,
               model="GP", scale.transform="LOG")
summary(out)

# Create a dataset with spacetime class
library(spTimer)
site<-unique(NYdata[,c("Longitude","Latitude")])
library(spacetime)
row.names(site)<-paste("point",1:nrow(site),sep="")
site <- SpatialPoints(site)
ymd<-as.POSIXct(seq(as.Date("2006-07-01"),as.Date("2006-08-31"),by=1))
# introduce class STFDF
newNYdata<-STFDF(sp=site, time=ymd, data=NYdata) # full lattice
class(newNYdata)
out <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                 data=newNYdata, model="GP", scale.transform="SQRT")
summary(out)

#####
## The AR models:
#####

##
## Model fitting
##

# Read data
data(NYdata)

```

```

# Define the coordinates
coords<-as.matrix(unique(cbind(NYdata[,2:3])))

# MCMC via Gibbs using default choices
set.seed(11)
post.ar <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                    data=NYdata, model="AR", coords=coords,
                    scale.transform="SQRT")
print(post.ar)

# MCMC via Gibbs not using default choices
# define the time-series
time.data<-spT.time(t.series=62,segment=1)

# hyper-parameters for the prior distributions
priors<-spT.priors(model="AR",inv.var.prior=Gamm(2,1),
                 beta.prior=Norm(0,10^4))

# initial values for the model parameters
initials<-spT.initials(model="AR", sig2eps=0.01,
                      sig2eta=0.5, beta=NULL, phi=0.001)

# Input for spatial decay
#spatial.decay<-spT.decay(distribution="FIXED", value=0.01)
spatial.decay<-spT.decay(distribution=Gamm(2,1), tuning=0.08)
#spatial.decay<-spT.decay(distribution=Unif(0.01,0.02),npoints=5)

# Iterations for the MCMC algorithms
nItr<-5000

# MCMC via Gibbs
set.seed(11)
post.ar <- spT.Gibbs(formula=o8hrmax~cMAXTMP+WDSP+RH,
                    data=NYdata, model="AR", time.data=time.data,
                    coords=coords, priors=priors, initials=initials,
                    nItr=nItr, nBurn=0, report=nItr,
                    tol.dist=2, distance.method="geodetic:km",
                    cov.fnc="exponential", scale.transform="SQRT",
                    spatial.decay=spatial.decay)
print(post.ar)

# Summary and plots
summary(post.ar)
plot(post.ar)

# Model selection criteria
post.ar$PMCC

##
## Fit and spatially prediction simultaneously
##

# Read data

```

```

s<-c(8,11,12,14,18,21,24,28)
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=s, reverse=TRUE)
DataFit<-subset(DataFit, with(DataFit, !(Day
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=s)
DataValPred<-subset(DataValPred, with(DataValPred, !(Day

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoid large data problem in R
set.seed(11)
post.ar.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                             data=DataFit, model="AR", coords=coords,
                             newcoords=pred.coords, newdata=DataValPred,
                             scale.transform="SQRT")
print(post.ar.fitpred)
summary(post.ar.fitpred)
names(post.ar.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.ar.fitpred$prediction[,1]))

#####
## The GPP approximation models:
#####

##
## Model fitting
##

# Read data
data(NYdata);

# Define the coordinates
coords<-as.matrix(unique(cbind(NYdata[,2:3])))
# Define knots
knots<-spT.grid.coords(Longitude=c(max(coords[,1]),
                                   min(coords[,1])),Latitude=c(max(coords[,2]),
                                   min(coords[,2])), by=c(4,4))

# MCMC via Gibbs using default choices
set.seed(11)
post.gpp <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                      data=NYdata, model="GPP", coords=coords,
                      knots.coords=knots, scale.transform="SQRT")
print(post.gpp)

# MCMC via Gibbs not using default choices
# define the time-series
time.data<-spT.time(t.series=62,segment=1)

```

```

# hyper-parameters for the prior distributions
priors<-spT.priors(model="GPP",inv.var.prior=Gamm(2,1),
  beta.prior=Norm(0,10^4))

# initial values for the model parameters
initials<-spT.initials(model="GPP", sig2eps=0.01,
  sig2eta=0.5, beta=NULL, phi=0.001)

# input for spatial decay
#spatial.decay<-spT.decay(distribution="FIXED", value=0.001)
spatial.decay<-spT.decay(distribution=Gamm(2,1), tuning=0.05)
#spatial.decay<-spT.decay(distribution=Unif(0.001,0.009),npoints=10)

# Iterations for the MCMC algorithms
nItr<-5000

# MCMC via Gibbs
set.seed(11)
post.gpp <- spT.Gibbs(formula=o8hrmax~cMAXTMP+WDSP+RH,
  data=NYdata, model="GPP", time.data=time.data,
  coords=coords, knots.coords=knots,
  priors=priors, initials=initials,
  nItr=nItr, nBurn=0, report=nItr,
  tol.dist=2, distance.method="geodetic:km",
  cov.fnc="exponential", scale.transform="SQRT",
  spatial.decay=spatial.decay)
print(post.gpp)

# Summary and plots
summary(post.gpp)
plot(post.gpp)

# Model selection criteria
post.gpp$PMCC

##
## Fit and spatially prediction simultaneously
##

# Read data
s<-c(8,11,12,14,18,21,24,28)
DataFit<-spT.subset(data=NYdata, var.name=c("s.index"), s=s, reverse=TRUE)
DataFit<-subset(DataFit, with(DataFit, !(Day %in% c(30, 31) & Month == 8)))
DataValPred<-spT.subset(data=NYdata, var.name=c("s.index"), s=s)
DataValPred<-subset(DataValPred, with(DataValPred, !(Day %in% c(30, 31) & Month == 8)))

# Define the coordinates
coords<-as.matrix(unique(cbind(DataFit[,2:3])))
pred.coords<-as.matrix(unique(cbind(DataValPred[,2:3])))
knots<-spT.grid.coords(Longitude=c(max(coords[,1]),
  min(coords[,1])),Latitude=c(max(coords[,2]),
  min(coords[,2])), by=c(4,4))

```

```

# MCMC via Gibbs will provide output in *.txt format
# from C routine to avoid large data problem in R
set.seed(11)
post.gpp.fitpred <- spT.Gibbs(formula=o8hrmax ~cMAXTMP+WDSP+RH,
                             data=DataFit, model="GP", coords=coords, knots.coords=knots,
                             newcoords=pred.coords, newdata=DataValPred,
                             scale.transform="SQRT")
print(post.gpp.fitpred)
summary(post.gpp.fitpred)
plot(post.gpp.fitpred)

names(post.gpp.fitpred)

# validation criteria
spT.validation(DataValPred$o8hrmax,c(post.gpp.fitpred$prediction[,1]))

##

## End(Not run)

```

spT.grid.coords *Grid Coordinates*

Description

This function is used to obtain Longitude/x and Latitude/y coordinates in a grid set.

Usage

```

spT.grid.coords(Longitude = c(max, min),
                Latitude = c(max, min), by = c(NA,NA))

```

Arguments

Longitude	The maximum and minimum longitude position.
Latitude	The maximum and minimum latitude position.
by	The number of x and y points in each axis.

See Also

[spT.geodist.](#)

Examples

```

## Not run:
##

# Load 29 ozone monitoring locations in New York.

```

```

data(NYsite)
NYsite
coords <- as.matrix(NYsite[,c(3,2)])

# Find the knots coordinates

knots.coords <- spT.grid.coords(Longitude=c(max(coords[,1]),
      min(coords[,1])), Latitude=c(max(coords[,2]),
      min(coords[,2])),by=c(4,4))
knots.coords

##

## End(Not run)

```

spT.initials

Initial values for the spatio-temporal models.

Description

This command is useful to assign the initial values of the hyper-parameters of the prior distributions.

Usage

```
spT.initials(model, sig2eps=0.01, sig2eta=NULL, rho=NULL, beta=NULL, phi=NULL)
```

Arguments

model	The spatio-temporal models, current options are: "GP", "AR", and "GPP".
sig2eps	Initial value for the parameter σ^2_ϵ .
sig2eta	Initial value for the parameter σ^2_η .
rho	Initial value for the parameter ρ .
beta	Initial value for the parameter β .
phi	Initial value for the parameter ϕ .

Note

Initial values are automatically given if the user does not provide these.

See Also

[spT.Gibbs](#), [predict.spT](#), [spT.priors](#).

Examples

```
## Not run:
##

initials<-spT.initials(model="GPP", sig2eps=0.01,
  sig2eta=0.5, beta=NULL, phi=0.001)
initials

##

## End(Not run)
```

```
spT.keep.morethan.dist
```

Present one coordinate in a defined area for presentation

Description

This function is used to present one coordinate in a defined area to avoid cutter.

Usage

```
spT.keep.morethan.dist(coords, tol.dist=100)
```

Arguments

coords	X and Y axes/ longitude and latitude values.
tol.dist	The tolerance limit for the distance.

See Also

[spT.geodist](#), [dist](#).

Examples

```
## Not run:
##

data(NYdata)
head(NYdata)
NYsite<-unique(NYdata[,2:3])
head(NYsite)
spT.keep.morethan.dist(NYsite,tol.dist=100)

# Including values
dat<-cbind(NYsite,value=rnorm(dim(NYsite)[[1]]))
head(dat)
spT.keep.morethan.dist(dat,tol.dist=100)
```

```
##
## End(Not run)
```

spT.pCOVER	<i>Nominal Coverage</i>
------------	-------------------------

Description

This function is used to obtain nominal coverage.

Usage

```
spT.pCOVER(z=NULL, zup=NULL, zlow=NULL, zsample=NULL, level=95)
```

Arguments

z	The original values (matrix or vector).
zup	The predicted values for upper interval (matrix or vector).
zlow	The predicted values for lower interval (matrix or vector).
zsample	Predicted MCMC samples.
level	Level of coverages.

See Also

[spT.validation](#).

Examples

```
## Not run:
##

# Create `x`: the true values.
# Create `yup`: the upper interval.
# Create `ylow`: the lower interval.

x <- rnorm(1000,5,0.1)
yup <- rnorm(1000,7,2)
ylow <- rnorm(1000,3,2)

# The pCOVER is:

spT.pCOVER(z=x, zup=yup, zlow=ylow)

# create predicted MCMC samples

y <- matrix(rnorm(1000*5000,5,1),1000,5000)
```



```
# The pCOVER is:

spT.pCOVER(z=x, zsample=y)
spT.pCOVER(z=x, zsample=y, level=50)

##

## End(Not run)
```

spT.priors

Priors for the spatio-temporal models.

Description

This command is useful to assign the hyper-parameters of the prior distributions.

Usage

```
spT.priors(model="GP", inv.var.prior=Gamm(a=2,b=1),
  beta.prior=Norm(0,10^10), rho.prior=Norm(0,10^10))
```

Arguments

model	The spatio-temporal models, current input: "GP", "AR", and "GPP".
inv.var.prior	The hyper-parameter for the Gamma prior distribution (with mean = a/b) of the precision (inverse variance) model parameters (e.g., $1/\sigma^2_\epsilon$, $1/\sigma^2_\eta$).
beta.prior	The hyper-parameter for the Normal prior distribution of the β model parameters.
rho.prior	The hyper-parameter for the Normal prior distribution of the ρ model parameter.

Note

If no prior information are given (assigned as NULL), then it use flat prior values of the corresponding distributions.

Gamm and Norm refers to Gamma and Normal distributions respectively.

See Also

[spT.Gibbs](#), [predict.spT](#), [spT.initials](#).

Examples

```
## Not run:
##

priors<-spT.priors(model="GPP",inv.var.prior=Gamm(2,1),
  beta.prior=Norm(0,10^4))
priors
```

```
##  
## End(Not run)
```

spT.segment.plot	<i>Utility plot for prediction/forecast</i>
------------------	---

Description

This function is used to obtain scatter plots with 95 percent CI for predictions/forecasts.

Usage

```
spT.segment.plot(obs, est, up, low, limit = NULL)
```

Arguments

obs	Observed values.
est	Estimated values.
up	Upper limit of the estimated values.
low	Lower limit of the estimated values.
limit	x-axis and y-axis limits.

See Also

[summary.spT](#), [plot.spT](#).

Examples

```
## Not run:  
##  
  
obs<-rnorm(10,15,1)  
est<-rnorm(10,15,1.5)  
up<-rnorm(10,25,0.5)  
low<-rnorm(10,5,0.5)  
spT.segment.plot(obs,est,up,low,limit=c(0,30))  
  
##  
  
## End(Not run)
```

spT.subset	<i>Select a subset of Spatial data.</i>
------------	---

Description

This command selects a subset of the dataset using the site numbers.

Usage

```
spT.subset(data, var.name, s = NULL, reverse = FALSE)
```

Arguments

data	The dataset.
var.name	The name of the variable for which data will be sub-setted, e.g., "s.index".
s	The site numbers to be selected/deselected based on the argument reverse, e.g., c(2,8,12).
reverse	Logical value: if TRUE then num.rs will be discarded from the data.

See Also

[NYdata](#).

Examples

```
## Not run:  
##  
  
# Load ozone concentration data for New York.  
data(NYdata)  
NYdata  
# Choose sites 2, 8, and 12.  
subdata<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(2,8,12))  
# Do not choose purposively defined sites numbered as 2, 8, and 12.  
subdata<-spT.subset(data=NYdata, var.name=c("s.index"), s=c(2,8,12), reverse=TRUE)  
  
##  
  
## End(Not run)
```

spT.time *Timer series information.*

Description

This function defines the time series in the spatio-temporal data.

Usage

```
spT.time(t.series, segments=1)
```

Arguments

t.series	Number of times within each segment in each series. It could be either a scalar or a vector. It should be a scalar if the segments are of equal length and should be a vector of length segments whose entries give the length of the segments.
segments	Number of segments in each time series. This should be a scalar.

See Also

[spT.Gibbs.](#)

Examples

```
## Not run:
##

# Equal length time-series in each of 3 years
time.data<-spT.time(t.series=365,segments=3)

# Un-equal length time-series in 5 years
time.data<-spT.time(t.series=c(366, 365, 365, 365, 366),segments=5)

##

## End(Not run)
```

spT.validation *Validation Commands*

Description

The following function is used to validate the predicted observations with the actual values.

Usage

```
spT.validation(z, zhat)
```

Arguments

z	The original values (matrix or vector).
zhat	The predicted values (matrix or vector).

Value

MSE	Mean Squared Error.
RMSE	Root Mean Squared Error.
MAE	Mean Absolute Error.
MAPE	Mean Absolute Percentage Error.
BIAS	Bias.
rBIAS	Relative Bias.
rMSEP	Relative Mean Separation.

See Also

[spT.pCOVER](#).

Examples

```
## Not run:
##

# Create `x`, which is the true values.
# Create `y`, which is the predicted values.

x <- rnorm(10,5,0.1)
y <- rnorm(10,5,1)
spT.validation(x, y)

##

## End(Not run)
```

summary.spT

Summary statistics of the parameters.

Description

This function is used to obtain MCMC summary statistics.

Usage

```
## S3 method for class 'spT'
summary(object, digits=4, package="spTimer", ...)

##
```

Arguments

object	Object of class inheriting from "spT".
digits	Rounds the specified number of decimal places (default 4).
package	If "coda" then summary statistics are given using coda package. Defaults value is "spTimer".
...	Other arguments.

Value

sig2eps	Summary statistics for σ_ϵ^2 .
sig2eta	Summary statistics for σ_η^2 .
phi	Summary statistics for spatial decay parameter ϕ , if estimated using spT.decay.
...	Summary statistics for other parameters used in the models.

See Also

[spT.Gibbs](#).

Examples

```
## Not run:  
##  
  
summary(out) # where out is the output from spT class  
summary(out, digit=2) # where out is the output from spT class  
summary(out, pack="coda") # where out is the output from spT class  
  
##  
  
## End(Not run)
```

Index

- *Topic **datasets**
 - NYdata, 5
- *Topic **package**
 - spTimer-package, 2
- *Topic **spT**
 - confint.spT, 3
 - fitted.spT, 4
 - plot.spT, 6
 - predict.spT, 7
 - spT.decay, 16
 - spT.Gibbs, 19
 - spT.initials, 30
 - spT.priors, 33
 - spT.time, 36
 - summary.spT, 37
- *Topic **utility**
 - spT.check.locations, 15
 - spT.geodist, 17
 - spT.grid.coords, 29
 - spT.keep.morethan.dist, 31
 - spT.pCOVER, 32
 - spT.segment.plot, 34
 - spT.subset, 35
 - spT.validation, 36

as.forecast.object, 8

confint.spT, 3

dist, 16, 20, 23, 31

fitted.spT, 4

NYdata, 2, 5, 18, 35

NYgrid, 5

NYgrid(NYdata), 5

plot.spT, 6, 23, 34

predict.spT, 2, 7, 23, 30, 33

spT.check.locations, 15

spT.check.sites.inside
(spT.check.locations), 15

spT.decay, 2, 16, 20

spT.geo.dist(spT.geodist), 17

spT.geo_dist(spT.geodist), 17

spT.geodist, 16, 17, 23, 29, 31

spT.Gibbs, 2–5, 7, 8, 17, 19, 30, 33, 36, 38

spT.grid.coords, 18, 29

spT.initials, 2, 20, 23, 30, 33

spT.keep.morethan.dist, 31

spT.pCOVER, 32, 37

spT.priors, 2, 20, 23, 30, 33

spT.segment.plot, 34

spT.subset, 5, 16, 35

spT.time, 2, 19, 20, 36

spT.validation, 32, 36

spTimer(spTimer-package), 2

spTimer-package, 2

summary.spT, 23, 34, 37