

# Package ‘ggquiver’

August 16, 2017

**Version** 0.1.0

**Title** Quiver Plots for 'ggplot2'

**Description** An extension of 'ggplot2' to provide quiver plots to visualise vector fields. This functionality is implemented using a geom to produce a new graphical layer, which allows aesthetic options. This layer can be overlaid on a map to improve visualisation of mapped data.

**Depends** R (>= 3.2.0), ggplot2

**Imports** dplyr

**Suggests** ggmap, maps, testthat

**URL** <https://github.com/mitchelloharawild/ggquiver>

**BugReports** <https://github.com/mitchelloharawild/ggquiver/issues>

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**ByteCompile** true

**RoxygenNote** 6.0.1.9000

**NeedsCompilation** no

**Author** Mitchell O'Hara-Wild [aut, cre]

**Maintainer** Mitchell O'Hara-Wild <[mail@mitchelloharawild.com](mailto:mail@mitchelloharawild.com)>

**Repository** CRAN

**Date/Publication** 2017-08-15 22:06:53 UTC

## R topics documented:

geom_quiver . . . . .	2
<b>Index</b>	<b>4</b>

geom\_quiver

*Quiver plots for ggplot2***Description**

Displays the direction and length of vectors on a graph.

**Usage**

```
geom_quiver(mapping = NULL, data = NULL, stat = "quiver",
            position = "identity", center = FALSE, rescale = FALSE,
            vecsize = NULL, na.rm = FALSE, show.legend = NA, inherit.aes = TRUE,
            ...)
```

GeomQuiver

```
stat_quiver(mapping = NULL, data = NULL, geom = "quiver",
            position = "identity", center = FALSE, rescale = FALSE,
            vecsize = NULL, na.rm = FALSE, show.legend = NA, inherit.aes = TRUE,
            ...)
```

StatQuiver

**Arguments**

mapping	Set of aesthetic mappings created by <a href="#">aes</a> or <a href="#">aes_</a> . If specified and <code>inherit.aes = TRUE</code> (the default), it is combined with the default mapping at the top level of the plot. You must supply mapping if there is no plot mapping.
data	The data to be displayed in this layer. There are three options: If <code>NULL</code> , the default, the data is inherited from the plot data as specified in the call to <a href="#">ggplot</a> . A <code>data.frame</code> , or other object, will override the plot data. All objects will be fortified to produce a data frame. See <a href="#">fortify</a> for which variables will be created. A function will be called with a single argument, the plot data. The return value must be a <code>data.frame</code> , and will be used as the layer data.
stat	The statistical transformation to use on the data for this layer, as a string.
position	Position adjustment, either as a string, or the result of a call to a position adjustment function.
center	If <code>FALSE</code> (the default), the vector lines will start at the specified <code>x</code> and <code>y</code> . If <code>TRUE</code> , the arrows will be centered about <code>x</code> and <code>y</code> .
rescale	If <code>FALSE</code> (the default), the vectors will not be rescaled. If <code>TRUE</code> , the vectors given by <code>(u, v)</code> will be rescaled using the <code>scale</code> function.

vecsize	By default (NULL), vectors sizing is automatically determined. If a grid can be identified, they will be scaled to the grid, if not, the vectors will not be scaled. By specifying a numeric input here, the length of all arrows can be adjusted. Setting vecsize to zero will prevent scaling the arrows.
na.rm	If FALSE (the default), removes missing values with a warning. If TRUE silently removes missing values.
show.legend	logical. Should this layer be included in the legends? NA, the default, includes if any aesthetics are mapped. FALSE never includes, and TRUE always includes.
inherit.aes	If FALSE, overrides the default aesthetics, rather than combining with them. This is most useful for helper functions that define both data and aesthetics and shouldn't inherit behaviour from the default plot specification, e.g. <code>borders</code> .
...	other arguments passed on to <code>layer</code> . These are often aesthetics, used to set an aesthetic to a fixed value, like <code>color = "red"</code> or <code>size = 3</code> . They may also be parameters to the paired geom/stat.
geom	The geometric object to use display the data

### Format

An object of class `GeomQuiver` (inherits from `GeomSegment`, `Geom`, `ggproto`) of length 2.

### Computed variables

**x** centered x start position for velocity arrow  
**y** centered y start position for velocity arrow  
**xend** centered x end position for velocity arrow  
**yend** centered y end position for velocity arrow

### Examples

```
# Quiver plots of mathematical functions
expand.grid(x=seq(0,pi,pi/12), y=seq(0,pi,pi/12)) %>%
  ggplot(aes(x=x,y=y,u=cos(x),v=sin(y))) +
  geom_quiver()

# Removing automatic scaling
ggplot(seals, aes(x=long, y=lat, u=delta_long, v=delta_lat)) +
  geom_quiver(vecsize=NULL) +
  borders("state")

## Not run:
# Centering arrows is useful for plotting on maps.
library(dplyr)
library(ggmap)
wind_data <- wind %>% filter(between(lon, -96, -93) & between(lat, 28.7, 30))
qplot(lon, lat, data=wind_data, extent="panel", geom = "blank", zoom=8, maptype = "toner-lite") +
  geom_quiver(aes(u=delta_lon, v=delta_lat, colour = spd), center=TRUE)

## End(Not run)
```

# Index

## \*Topic **datasets**

geom\_quiver, 2

aes, 2

aes\_, 2

borders, 3

fortify, 2

geom\_quiver, 2

GeomQuiver (geom\_quiver), 2

ggplot, 2

layer, 3

stat\_quiver (geom\_quiver), 2

StatQuiver (geom\_quiver), 2