

Package ‘timeDate’

February 20, 2015

Title Rmetrics - Chronological and Calendar Objects

Date 2015-01-22

Version 3012.100

Author Rmetrics Core Team,
Diethelm Wuertz [aut],
Tobias Setz [cre],
Yohan Chalabi [ctb],
Martin Maechler [ctb],
Joe W. Byers [ctb]

Maintainer Tobias Setz <tobias.setz@rmetrics.org>

Description Environment for teaching
``Financial Engineering and Computational Finance".
Managing chronological and calendar objects.

Depends R (>= 2.15.1), graphics, utils, stats, methods

Suggests date, RUnit

Note SEVERAL PARTS ARE STILL PRELIMINARY AND MAY BE CHANGED IN THE
FUTURE. THIS TYPICALLY INCLUDES FUNCTION AND ARGUMENT NAMES, AS
WELL AS DEFAULTS FOR ARGUMENTS AND RETURN VALUES.

LazyData yes

License GPL (>= 2)

URL <https://www.rmetrics.org>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-01-23 09:30:30

R topics documented:

timeDate-package	3
.endpoints	13
align	14
as.timeDate	15

blockStart	16
c	17
currentYear	18
DaylightSavingTime	19
dayOfWeek	20
dayOfYear	21
diff	22
difftimeDate	23
Easter	23
finCenter	24
firstDay	25
format-methods	27
holiday	28
holidayDate	30
holidayLONDON	33
holidayNERC	34
holidayNYSE	34
holidayTSX	35
holidayZURICH	36
is.na-methods	36
isBizday	37
isRegular	38
isWeekday	39
julian	40
kurtosis	41
length	42
listFinCenter	43
listHolidays	44
midnightStandard	44
myFinCenter	45
myUnits	46
names-methods	46
nDay	47
onOrAfter	48
periods	49
plot-methods	50
rep	51
rev	52
RmetricsOptions	53
round	53
rulesFinCenter	54
sample	55
show-methods	55
skewness	56
sort	57
start	58
subset	59
summary-methods	60

<i>timeDate-package</i>	3
Sys.timeDate	60
timeCalendar	61
timeDate	62
timeDate-class	63
timeDateMathOps	67
timeSequence	69
unique	70
whichFormat	71
window	72
Index	73

timeDate-package	<i>Utilities and Tools Package</i>
------------------	------------------------------------

Description

Package of calendar, date, time tools and utilities for Rmetrics.

Overview of Topics

This help file describes the concepts and methods behind the S4 'timeDate' class used in Rmetrics for financial data and time management together with the management of public and ecclesiastical holidays.

The 'timeDate' class fulfils the conventions of the ISO 8601 standard as well as of the ANSI C and POSIX standards. Beyond these standards Rmetrics has added the "Financial Center" concept which allows to handle data records collected in different time zones and mix them up to have always the proper time stamps with respect to your personal financial center, or alternatively to the GMT reference time. It can thus also handle time stamps from historical data records from the same time zone, even if the financial centers changed day light saving times at different calendar dates.

Moreover 'timeDate' is almost compatible with the 'timeDate' class in Insightful's SPlus 'timeDate' class. If you move between the two worlds of R and SPlus, you will not have to rewrite your code. This is important for business applications.

The 'timeDate' class offers not only date and time functionality but it also offers sophisticated calendar manipulations for business days, weekends, public and ecclesiastical holidays.

This help page is presented in four sections:

1. S4 'timeDate' Class and Functions
2. Operations on 'timeDate' Objects
3. Daylight Saving Time and Financial Centers
4. Holidays and Holiday Calendars

1. S4 'timeDate' Class and Generator Functions

Date and time stamps are represented by an S4 object of class 'timeDate'.

```

setClass("timeDate",
  representation(
    Data = "POSIXct",
    format = "character",
    FinCenter = "character"
  ))

```

They have three slots. The @Data slot holds the time stamps which are POSIXct formatted as specified in the @format slot. The time stamps are local and belong to the financial center expressed through the slot @FinCenter.

There are several possibilities to generate a 'timeDate' object. The most forward procedure is to use one of the following functions:

```

timeDate – Creates a 'timeDate' object from scratch,
timeSequence – creates a sequence of 'timeDate' objects,
timeCalendar – creates a 'timeDate' object from calendar atoms,
Sys.timeDate – returns the current date and time as a 'timeDate' object.

```

With the function timeDate you can create 'timeDate' objects from scratch by specifying a character vector of time stamps and a financial center which the character vector belongs to. "GMT" is used by default as the reference for all date/time operations. But you can set the variable myFinCenter to your local financial center reference if you want to reference dates/time to it.

Examples:

```

# Show My local Financial Center - Note, by Default this is "GMT"
getRmetricsOptions("myFinCenter")

# Compose Character Vectors of Dates and Times:
Dates <- c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
Times <- c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
charvec = paste(Dates, Times)

# Create a 'timeDate' object
timeDate(charvec)

# Create a 'timeDate' object with my financial center set to Zurich
myFinCenter <- "Zurich"
timeDate(charvec)

# if the 'timeDate' was recorded in a different financial center, it
# will be automatically converted to your financial center,
# i.e. "Zurich".
timeDate(charvec, zone = "Tokyo")

# You can also convert a recorded 'timeDate' from your financial

```

```
# center "Zurich" to another one, for example "NewYork".
timeDate(charvec, FinCenter = "NewYork")
```

NOTE: Rmetrics has implemented an automated date/time format identifier for many common date/time formats which tries to automatically recognise the format for the character vector of dates and times. You can have a look at `whichFormat(charvec)`.

NOTE: Rmetrics always uses the midnight standard on dates and times. You can see it with `.midnightStandard("2008-01-31 24:00:00")`

Alternatively we can create a sequence of 'timeDate' objects with the help of the function `timeSequence`. This can be done in several ways, either by specifying the range of the data through the arguments `from` and `to`, or when `from` is missing, by setting the argument `length.out` of the desired series. Note in the case of a monthly sequence, you have further options. For example you can generate the series with the first or last day in each month, or use more complex rules like the last or n-th Friday in every month.

Examples:

```
# Lets work in an international environment:
setRmetricsOptions(myFinCenter = "GMT")

# Your 'timeDate' is now in the Financial Center "GMT"
timeDate(charvec)

# Daily January 2008 Sequence:
timeSequence(from = "2008-01-01", to = "2008-01-31", by = "day")

# Monthly 2008 Sequence:
tS = timeSequence(from = "2008-01-01", to = "2008-12-31", by = "month")
tS

# Do you want the last Day or the last Friday in Month Data ?
timeLastDayInMonth(tS)
timeLastNdayInMonth(tS, nday = 5)
```

A third possibility is to create 'timeDate' objects from calendar atoms. You can specify values or vectors of equal length of integers denoting year, month, day, hour, minute and seconds. If every day has the same time stamp, you can just add an offset.

Examples:

```
# Monthly calendar for Current Year
```

```

getRmetricsOptions("currentYear")
timeCalendar()

# Daily 'timeDate' for January data from Tokyo local time 16:00
timeCalendar(2008, m=1, d=1:31, h=16, zone="Tokyo", FinCenter="Zurich")

# Or add16 hours in seconds ...
timeCalendar(2008, m=1, d=1:31, zone="Tokyo", FinCenter="Zurich") + 16*3600

```

2. Operations on 'timeDate' Objects

Many operations can be performed on 'timeDate' objects. You can add and subtract, round and truncate, subset, coerce or transform them to other objects. These are only few options among many others.

Math Operations

Math operations can add and subtract dates and times, and perform logical operations on 'timeDate' objects.

Examples:

```

# Date and Time Now:
now = Sys.timeDate()

# One Hour Later:
now + 3600

# Which date/time is earlier or later ?
tC = timeCalendar()
tR = tC + round(3600*rnorm(12))
tR > tC

```

Lagging

You can generate suitable lagged and iterated differences:

`diff.timeDate` – Returns suitably lagged and iterated differences.

Examples:

```

# Monthly Dates 2008 and January 2009:
tC = c(timeCalendar(2008), timeCalendar(2009)[1])

# Number of days in months and total 2008:

```

```
diff(tC)
sum(as.integer(diff(tC)))
```

Rounding and Truncating

Dates and times can be rounded or truncated. This is useful lower frequencies than seconds, for example hourly.

round – rounds objects of class 'timeDate',
trunc – truncates objects of class 'timeDate'.

Examples:

```
# Round the Random Time Stamps to the Nearest Hour:
tC = timeCalendar()
tR = tC + round(3600*rnorm(12))
tR
round(tR, "h")

# Truncate by Hour or to the Next Full Hour::
trunc(tR, "h")
trunc(tR + 3600, "h")
```

Subsetting

Subsetting a 'timeDate' is a very important issue in the management of dates and times. Rmetrics offers several functions which are useful in this context:

"[" – Extracts or replaces subsets from 'timeDate' objects,
window, cut – extract a piece from a 'timeDate' object,

In this context it is also important to know the start and the end time stamp together with the total number of time stamps.

start – extracts the first entry of a 'timeDate' object,
end – extracts the last entry of a 'timeDate' object,
length – returns the length of a 'timeDate' object.

Examples:

```
# Create Monthly Calendar for next year
tC = timeCalendar(getRmetricsOptions("currentYear") + 1)
tC
```

```

# Start, end and length of 'timeDate' objects
start(tC)
end(tC)
length(tC)

# The first Quarter - Several Alternative Solutions:
tC[1:3]
tC[-(4:length(tC))]
window(tC, start = tC[1], end = tC[3])
cut(tC, from = tC[1], to = tC[3])
tC[tC < tC[4]]

# The Quarterly Series:
tC[seq(3, 12, by = 3)]

```

Weekdays, weekends, business days, and holidays can be easily obtained with the following functions:

isWeekday – tests if a date is a weekday or not,
 isWeekend – tests if a date is a weekend day or not,
 isBizday – tests if a date is a business day or not,
 isHoliday – tests if a date is a holiday day or not.

Examples:

```

# A 'timeDate' Sequence around Easter 2008
Easter(2008)
tS <- timeSequence(Easter(2008, -14), Easter(2008, +14))
tS

# Subset weekdays and business days:
tW <- tS[isWeekday(tS)]; tW
dayOfWeek(tW)
tB <- tS[isBizday(tS, holidayZURICH())]; tB
dayOfWeek(tB)

```

The functions blockStart and blockEnd gives time stamps for equally sized blocks.

blockStart – Creates start dates for equally sized blocks,
 blockEnd – Creates end dates for equally sized blocks.

Examples:

```
# 'timeDate' object for the last 365 days:
tS = timeSequence(length.out = 360)
tS

# Subset Pointers for blocks of exactly 30 days:
blockStart(tS, 30)
blockEnd(tS, 30)
Sys.timeDate()
```

Coercions and Transformations

'timeDate' objects are not living in an isolated world. Coercions and transformations allow 'timeDate' objects to communicate with other formatted time stamps. Be aware that in most cases information can be lost if the other date.time classes do not support this functionality. There exist several methods to coerce and transform timeDate objects into other objects.

as.timeDate – Implements Use Method,
 as.timeDate.default – default Method,
 as.timeDate.POSIXt – returns a 'POSIX' object as 'timeDate' object,
 as.timeDate.Date – returns a 'POSIX' object as 'timeDate' object.

as.character.timeDate – Returns a 'timeDate' object as 'character' string,
 as.double.timeDate – returns a 'timeDate' object as 'numeric' object,
 as.data.frame.timeDate – returns a 'timeDate' object as 'data.frame' object,
 as.POSIXct.timeDate – returns a 'timeDate' object as 'POSIXct' object,
 as.POSIXlt.timeDate – returns a 'timeDate' object as 'POSIXlt' object,
 as.Date.timeDate – returns a 'timeDate' object as 'Date' object.

Users or maintainers of other date/time classes can add their own generic functions. For example as.timeDate.zoo and as.zoo.timeDate.

Concatenations and Reorderings

It might be sometimes useful to concatenate or reorder 'timeDate' objects. The generic functions to concatenate, replicate, sort, re-sample, unify and revert a 'timeDate' objects are :

c – Concatenates 'timeDate' objects,
 rep – replicates a 'timeDate' object,
 sort – sorts a 'timeDate' object,
 sample – resamples a 'timeDate' object,
 unique – makes a 'timeDate' object unique,

rev – reverts a 'timeDate' object.

NOTE: The function c of a 'timeDate' objects takes care of possible different financial centers specific to each object to be concatenated. In such cases, all time stamps will be transformed to the financial center of the first time stamp used in the concatenation:

Examples:

```
# Concatenate the local time stamps to Zurich time ...
ZH = timeDate("2008-01-01 16:00:00", zone = "GMT", FinCenter = "Zurich")
NY = timeDate("2008-01-01 18:00:00", zone = "GMT", FinCenter = "NewYork")
c(ZH, NY)
c(NY, ZH)

# Rordering:
tC = timeCalendar(); tC
tS = sample(tC); tS
t0 = sort(tS); t0
tV = rev(t0); tV
tU = unique(c(tS, tS)); tU
```

3. Daylight Saving Time and Financial Centers

Each financial center worldwide has a function which returns Daylight Saving Time Rules. Almost 400 prototypes are made available through the Olson time zone data base. The cities and regions can be listed using the command listFinCenter. The DST rules for specific financial center can be viewed by their name, e.g. Zurich(). Additional financial centers can be added by the user taking care of the format specification of the DST functions.

Setting Financial Centers

All time stamps are handled according to the time zone and daylight saving time rules specified by the center through the variable myFinCenter. This variable is set by default to "GMT" but can be changed to your local financial center or to any other financial center you want to use.

NOTE: By setting the financial center to a continent/city which lies outside of the time zone used by your computer does not change any time settings or environment variables used by your computer.

To change the name of a financial center from one setting to another just assign to the variable myFinCenter the desired name of the city:

Examples:

```
# What is my current Financial Center ?
getRmetricsOptions("myFinCenter")

# Change to Zurich:
```

```
setRmetricsOptions(myFinCenter = "Zurich")
getRmetricsOptions("myFinCenter")
```

From now on, all dates and times are handled within the middle European time zone and the DST rules which are valid for Zurich.

List of Financial Centers

There are many other financial centers supported by Rmetrics. They can be displayed by the function `listFinCenter`. You can also display partial lists with wildcards and regular expressions:

Examples:

```
# List all supported Financial Centers Worldwide:
listFinCenter()

# List European Financial Centers:
listFinCenter("Europe/*")
```

DST Rules

For each financial center a function is available. It keeps the information of the time zones and the DST rules. The functions return a data.frame with 4Columns :

```
Zurich offSet isdst TimeZone
...
62 2008-03-30 01:00:00 7200 1 CEST
63 2008-10-26 01:00:00 3600 0 CET
...
```

The first column describes when the time was changed, the second gives the offset to "GMT", the third returns the daylight savings time flag which is positive if in force, zero if not, and negative if unknown. The last column gives the name of the time zone. You can have a look at the function `Zurich()` :

Examples:

```
# Show the DST Rules for Zurich:
Zurich()

# List European Financial Centers:
listFinCenter("Europe/*")
```

3. Holidays and Holiday Calendars

It is non-trivial to implement function for business days, weekends and holidays. It is not difficult in an algorithmic sense, but it can become tedious to implement the rules of the calendar themselves, for example the date of Easter.

In the following section we briefly summarise the functions which can calculate dates of ecclesiastical and public holidays. With the help of these functions we can also create business and holiday calendars.

Special Dates:

The implemented functions can compute the last day in a given month and year, the dates in a month that is a n-day (e.g. n = Sun) on or after a given date, the dates in a month that is a n-day on or before a specified date, the n-th occurrences of a n-day for a specified year/month vectors, or the last n-day for a specified year/month value or vector.

NOTE: n-days are numbered from 0 to 6 where 0 correspond to the Sunday and 6 to the Saturday.

timeFirstDayInMonth – Computes the first day in a given month and year,
 timeLastDayInMonth – Computes the last day in a given month and year,
 timeFirstDayInQuarter – Computes the first day in a given quarter and year,
 timeLastDayInQuarter – Computes the last day in a given quarter and year,

timeNdayOnOrAfter – Computes date that is a "on-or-after" n-day,
 timeNdayOnOrBefore –b Computes date that is a "on-or-before" n-day,

timeNthNdayInMonth – Computes n-th occurrence of a n-day in year/month,
 timeLastNdayInMonth – Computes the last n-day in year/month.

Holidays:

Holidays may have two origins: ecclesiastical or public/federal. The ecclesiastical calendars of Christian churches are based on cycles of movable and immovable feasts. Christmas, December 25, is the principal immovable feast. Easter is the principal movable feast, and dates of most of the other movable feasts are determined with respect to Easter. However, the movable feasts of the Advent and Epiphany seasons are Sundays reckoned from Christmas and the Feast of the Epiphany, respectively.

Examples:

```
# List Holidays available in Rmetrics
listHolidays()

# The date of Easter for the next 5 years:
currentYear <- getRmetricsOptions("currentYear")
Easter(currentYear:(currentYear+5))
```

Holiday Calendars:

holidayZURICH – Zurich Business Calendar,
holidayNYSE – NYSE Stock Exchange Holiday Calendar,
holidayZURICH – TSX Holiday Calendar.

We would like to thanks all Rmetrics users who gave us many additional information concerning local holidays.

References

- Bateman R., (2000); *Time Functionality in the Standard C Library*, Novell AppNotes, September 2000 Issue, 73–85.
- Becker R.A., Chambers J.M., Wilks A.R. (1988); *The New S Language*, Wadsworth & Brooks/Cole.
- ISO-8601, (1988); *Data Elements and Interchange Formats - Information Interchange, Representation of Dates and Time*, International Organization for Standardization, Reference Number ISO 8601, 14 pages.
- James D.A., Pregibon D. (1992), *Chronological Objects for Data Analysis*, Reprint.
- Ripley B.D., Hornik K. (2001); *Date-Time Classes*, R-News, Vol. 1/2 June 2001, 8–12.
- Zivot, E., Wang J. (2003); *Modeling Financial Time Series with S-Plus*, Springer, New-York.

.endpoints

Endpoints Indexes

Description

Returns endpoint indexes from a 'timeDate' object

Usage

```
.endpoints(x, on = c("months", "years", "quarters", "weeks", "days",  
"hours", "minutes", "seconds"), k=1)
```

Arguments

- | | |
|----|--|
| x | a timeDate object. |
| on | the periods endpoints to find as a character string. Select from: "months", "years", "quarters", "weeks", "days", "hours", "minutes", "seconds". |
| k | along every k-th element. |

Details

endpoints returns an integer vector corresponding to the last observation in each period specified by on, with a zero added to the beginning of the vector, and the index of the last observation in x at the end.

Value

returns an integer vector of endpoints beginning with 0 and ending with the a value equal to the length of the x argument.

Author(s)

Jeff Ryan, modified by Diethelm Wuertz for timeDate objects.

Examples

```
## endpoints -
# Weekly Endpoints:
.endpoints(timeCalendar(), on="w")
```

align

Making a 'timeDate' object unique

Description

Aligns a 'timeDate' object to regular date/time stamps.

Usage

```
## S4 method for signature 'timeDate'
align(x, by = "1d", offset = "0s")

alignDaily(x, include.weekends=FALSE)
alignMonthly(x, include.weekends=FALSE)
alignQuarterly(x, include.weekends=FALSE)
```

Arguments

x	an object of class timeDate.
by	a character string formed from an integer length and a period identifier. Valid values are "w", "d", "h", "m", "s", for weeks, days, hours, minutes and seconds. For example a bi-weekly period is expressed as "2w".
offset	a character string to set an offset formed from an integer length and a period identifier in the same way as for the argument by.
include.weekends	logical value indicating whether 'weekends' should be included.

Details

The functions alignDaily, alignMonthly, alignMonthly are simple to use functions which generate end-of-day, end-of-month, and end-of quarter timeDate objects. Weekends are excluded by default. Optionally they can be added setting the argument include.weekends=TRUE.

Value

returns an object of class timeDate.

Examples

```
## align -

# Align Bi-Weekly with a 3 Days Offset:
(tC <- timeCalendar())
align(tC, by = "2w", offset = "3d")

## alignDaily -

# Simple to use Functions:
alignDaily(tC)
alignDaily(tC, include.weekends=TRUE)

# Align to end-of-month Dates:
alignMonthly(tC)
```

as.timeDate

Any to 'timeDate' Coercion

Description

Coerce and transform objects of class 'timeDate'.

Usage

```
## S3 method for class 'timeDate'
as.character(x, ...)

## S3 method for class 'timeDate'
as.double(x,
  units = c("auto", "secs", "mins", "hours", "days", "weeks"), ...)
## S3 method for class 'timeDate'
as.data.frame(x, ...)

## S3 method for class 'timeDate'
as.POSIXct(x, tz = "", ...)

## S3 method for class 'timeDate'
as.POSIXlt(x, tz = "", ...)

## S3 method for class 'timeDate'
as.Date(x, method = c("trunc", "round", "next"), ...)
```

```

## Default S3 method:
as.timeDate(x, zone = "", FinCenter = "")

## S3 method for class 'POSIXt'
as.timeDate(x, zone = "", FinCenter = "")

## S3 method for class 'Date'
as.timeDate(x, zone = "", FinCenter = "")
## S3 method for class 'timeDate'
as.timeDate(x, zone = x@FinCenter, FinCenter = "")

```

Arguments

FinCenter	a character with the the location of the financial center named as "continent/city".
method	a character string denoting the method how to determine the dates.
tz	inputs the time zone to POSIX objects, i.e. the time zone, zone, or financial center string, FinCenter, as used by timeDate objects.
units	a character string denoting the date/time units in which the results are desired.
x	an object of class timeDate.
zone	the time zone or financial center where the data were recorded.
...	arguments passed to other methods.

Value

as.timeDate.POSIXt returns an object of class timeDate.
as.timeDate.Date returns an object of class timeDate.

Examples

```

## timeDate -
tC = timeCalendar()

## Convert 'timeDate' to a character strings:
as.character(tC)

## Coerce a 'Date' object into a 'timeDate' object:
as.timeDate(Sys.Date())

```

blockStart

Equally sized 'timeDate' Blocks

Description

Creates start (end) dates for equally sized 'timeDate' blocks.

Usage

```
blockStart(x, block = 20)
blockEnd(x, block = 20)
```

Arguments

block	an integer value specifying the length in number of records for numerically sized blocks of dates.
x	an object of class <code>timeDate</code> .

Details

The functions `blockStart` and `blockEnd` create vectors of start and end values for equally sized 'timeDate' blocks. Note, the functions are event counters and not a time counter between measuring time intervals between start and end dates! For equally sized blocks in time one has before to align the time stamps in equal time differences.

Value

returns an object of class "timeDate".

Examples

```
## timeSequence
# 360 Days Series:
tS <- timeSequence(length.out = 360)

## blockStart | blockEnd -
Start <- blockStart(tS, 30)
End <- blockEnd(tS, 30)
Start
End
End-Start
```

Description

Concatenates 'timeDate' objects.

Usage

```
## S3 method for class 'timeDate'
c(..., recursive = FALSE)
```

Arguments

recursive a logical. If recursive is set to TRUE, the function recursively descends through lists combining all their elements into a vector.

... arguments passed to other methods.

Value

returns an object of class "timeDate".

Examples

```
## timeCalendar -  
# Create Character Vectors:  
GMT = timeCalendar(zone = "GMT", FinCenter = "GMT") + 16*3600  
ZUR = timeCalendar(zone = "GMT", FinCenter = "Zurich") + 16*3600  
  
## c -  
# Concatenate and Replicate timeDate Objects:  
sort(c(GMT, ZUR))  
sort(c(ZUR, GMT))
```

currentYear

Current Year

Description

A variable with the current year.

Note

It is not allowed to change this variable.

Examples

```
## currentYear -  
getRmetricsOptions("currentYear")
```

DaylightSavingTime *Daylight Saving Time Rules*

Description

Functions for about 400 cities and regions which return daylight saving time rules and time zone offsets.

Details

As a selection of these functions:

Adelaide Algiers Amsterdam Anchorage Andorra Athens Auckland Bahrain Bangkok Beirut Belfast Belgrade Berlin Bogota Bratislava Brisbane Brussels Bucharest Budapest BuenosAires Cairo Calcutta Caracas Casablanca Cayman Chicago Copenhagen Darwin Denver Detroit Dubai Dublin Eastern Edmonton Frankfurt Helsinki HongKong Honolulu Indianapolis Istanbul Jakarta Jerusalem Johannesburg Kiev KualaLumpur Kuwait Lagos Lisbon Ljubljana London LosAngeles Luxembourg Madrid Manila Melbourne MexicoCity Monaco Montreal Moscow Nairobi Nassau NewYork Nicosia Oslo Pacific Paris Perth Prague Riga Riyadh Rome Seoul Shanghai Singapore Sofia Stockholm Sydney Taipei Tallinn Tehran Tokyo Tunis Vaduz Vancouver Vienna Vilnius Warsaw Winnipeg Zagreb Zurich, ...

Note

There are currently two synonymes available "Pacific" for Los Angeles and "Eastern" for New York. specific time zones (AST, CET, CST, EET, EST, MST and PST) are also available.

Note we leave the space in all double named cities like New York or Hong Kong and use an underscore for it.

All the entries are retrieved from the tzdata library which is available under GNU GPL licence.

Examples

```
## DST Rules for Zurich:
  head(Zurich())
  tail(Zurich())

## list all available centers
listFinCenter()
```

dayOfWeek	<i>Day of the Week</i>
-----------	------------------------

Description

returns the day of the year from a 'timeDate' object.

Usage

```
dayOfWeek(x)
```

Arguments

x an object of class `timeDate`.

Value

returns a three letter character string with the names in English of the day of the week,

Note

With version 2.7 the function has been renamed from `getDayOfWeek`.

See Also

[dayOfYear](#)

Examples

```
## timeCalendar -
  tC = timeCalendar()

## The days of the Year:
  dayOfWeek(tC)

## Use Deprecated Function:
  getDayOfWeek <- dayOfWeek
  getDayOfWeek(tC)
```

dayOfYear	<i>Day of the Year</i>
-----------	------------------------

Description

returns the day of the year from a 'timeDate' object.

Usage

```
dayOfYear(x)
```

Arguments

x an object of class `timeDate`.

Value

returns the day count as integer value starting January, 1st.

Note

With version 2.7 the function has been renamed from `getDayOfYear`.

See Also

[dayOfWeek](#)

Examples

```
## timeCalendar -  
tC = timeCalendar()  
  
## The days of the Year:  
dayOfYear(tC)  
  
## Use Deprecated Function:  
getDayOfYear <- dayOfYear  
getDayOfYear(tC)
```

diff

*Lagged 'timeDate' Differences***Description**

Returns suitably lagged and iterated differences.

Usage

```
## S3 method for class 'timeDate'
diff(x, lag = 1, differences = 1, ...)
```

Arguments

x	an object of class timeDate.
lag	an integer indicating which lag to use.
differences	an integer indicating the order of the difference.
...	arguments passed to other methods.

Value

For the function, `diff.timeDate`, if `x` is a vector of length `n` and `differences=1`, then the computed result is equal to the successive differences `x[(1+lag):n] - x[1:(n-lag)]`. If difference is larger than one this algorithm is applied recursively to `x`. Note that the returned value is a vector which is shorter than `x`.

Examples

```
## Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## timeDate -
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT") + 24*3600
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
ZUR

## diff -
# Suitably Lagged and Iterated Differences:
diff(GMT)
diff(GMT, lag = 2)
diff(GMT, lag = 1, diff = 2)
```

difftimeDate *Difference of two 'timeDate' Objects*

Description

Returns a difference of two 'timeDate' objects.

Usage

```
difftimeDate(time1, time2,
             units = c("auto", "secs", "mins", "hours", "days", "weeks"))
```

Arguments

time1, time2 two objects objects of class timeDate.
units a character string denoting the date/time units in which the results are desired.

Value

The function, difftimeDate, takes a difference of two timeDate objects and returns an object of class "difftime" with an attribute indicating the units.

Examples

```
## Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts

## timeDate -
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT

## diff -
# Suitably Lagged and Iterated Differences:
difftimeDate(GMT[1:2], GMT[-(1:2)])
```

Easter *Date of Easter*

Description

Returns the date of Easter.

Usage

```
Easter(year = getRmetricsOptions("currentYear"), shift = 0)
```

Arguments

year	an integer value or integer vector for the year(s).
shift	an integer value, the number of days shifted from the Easter date. Negative integers are allowed.

Details

Holidays may have two origins, ecclesiastical and public/federal. The ecclesiastical calendars of Christian churches are based on cycles of moveable and immoveable feasts. Christmas, December 25th, is the principal immoveable feast. Easter is the principal moveable feast, and dates of most other moveable feasts are determined with respect to Easter.

The date of Easter is evaluated by a complex procedure whose detailed explanation goes beyond this description. The reason that the calculation is so complicate is, because the date of Easter is linked to (an inaccurate version of) the Hebrew calendar. But nevertheless a short answer to the question "When is Easter?" is the following: Easter Sunday is the first Sunday after the first full moon after vernal equinox. For the long answer we refer to Toendering (1998).

The algorithm computes the date of Easter based on the algorithm of Oudin (1940). It is valid for any Gregorian Calendar year.

Value

returns the date of Easter as an object of class `timeDate`.

Examples

```
## Easter -

# Current Year:
Easter()

# From 2001 to 2010:
Easter(2001:2010)
```

finCenter

Financial Center of a timeDate object

Description

Print or assign new financial center to a `timeDate` object.

Usage

```
## S4 method for signature 'timeDate'
finCenter(x)
## S4 replacement method for signature 'timeDate'
finCenter(x) <- value
```

Arguments

x a timeSeries object.
 value a character with the the location of the financial center named as "continent/city".

See Also

listFinCenter

Examples

```
date <- timeDate("2008-01-01")
finCenter(date) <- "GMT"
date

finCenter(date) <- "Zurich"
date
```

 firstDay

First and Last Days

Description

Computes the first/last day in a given month/quarter.

Usage

```
timeFirstDayInMonth(charvec, format = "%Y-%m-%d", zone = "",
  FinCenter = "")
timeLastDayInMonth(charvec, format = "%Y-%m-%d", zone = "",
  FinCenter = "")

timeFirstDayInQuarter(charvec, format = "%Y-%m-%d", zone = "",
  FinCenter = "")
timeLastDayInQuarter(charvec, format = "%Y-%m-%d", zone = "",
  FinCenter = "")
```

Arguments

charvec a character vector of dates and times.
 format the format specification of the input character vector.
 zone the time zone or financial center where the data were recorded.
 FinCenter a character with the the location of the financial center named as "continent/city".

Value

returns an object of class `timeDate`.

For the functions `timeLastDayInMonth` and `timeFirstDayInMonth` return the last or first day respectively in a given month and year.

The same functionality for quarterly time horizons is returned by the functions `timeLastDayInQuarter` and `timeFirstDayInQuarter`.

Examples

```
## Date as character String:
charvec = "2006-04-16"
myFinCenter = getRmetricsOptions("myFinCenter")

## timeLastDayInMonth-
# What date has the last day in a month for a given date ?
timeLastDayInMonth(charvec, format = "%Y-%m-%d",
  zone = myFinCenter, FinCenter = myFinCenter)
timeLastDayInMonth(charvec)
timeLastDayInMonth(charvec, FinCenter = "Zurich")

## timeFirstDayInMonth -
# What date has the first day in a month for a given date ?
timeFirstDayInMonth(charvec)

## timeLastDayInQuarter -
# What date has the last day in a quarter for a given date ?
timeLastDayInQuarter(charvec)

## timeFirstDayInQuarter -
# What date has the first day in a quarter for a given date ?
timeFirstDayInQuarter(charvec)

## timeNdayOnOrAfter
# What date has the first Monday on or after March 15, 1986 ?
timeNdayOnOrAfter("1986-03-15", 1)

## timeNdayOnOrBefore
# What date has Friday on or before April 22, 1977 ?
timeNdayOnOrBefore("1986-03-15", 5)

## timeNthNdayInMonth -
# What date is the second Monday in April 2004 ?
timeNthNdayInMonth("2004-04-01", 1, 2)

## timeLastNdayInMonth -
# What date has the last Tuesday in May, 1996 ?
timeLastNdayInMonth("1996-05-01", 2)
```

format-methods *Format Methods*

Description

Formats 'timeDate' objects as ISO conform character strings.

Usage

```
## S3 method for class 'timeDate'  
format(x, format = "", tz = "", usetz = FALSE, ...)
```

Arguments

format	a character string describing the format.
tz	a timezone specification to be used for the conversion.
usetz	a logical.
x	an object of class timeDate.
...	arguments passed to other methods.

Value

returns an ISO conform formatted character string.

Note

This S3 method will become in the future a S4 method

See Also

as.character.

Examples

```
## timeCalendar -  
# Time Calendar 16:00  
tC = timeCalendar() + 16*3600  
tC  
  
## Format as ISO Character String:  
format(tC)
```

 holiday

Holiday Dates

Description

Returns the date of a holiday.

Usage

```
holiday(year = getRmetricsOptions("currentYear"), Holiday = "Easter")
```

Arguments

Holiday	the unquoted function name of an ecclestial or public holiday in the G7 countries or Switzerland, see the list below.
year	an integer value or vector of years, formatted as YYYY.

Details

Easter is the central ecclestial holiday. Many other holidays are related to this feast. The function `Easter` computes the dates of Easter and related ecclestial holidays for the requested year vector. `holiday` calculates the dates of ecclestial or public holidays in the G7 countries, e.g. `holiday(2003, "GoodFriday")`. `Rmetrics` contains holiday functions automatically loaded at startup time. The user can add easily additional holiday functions. The information for the holidays is collected from several web pages about holiday calendars. The following ecclestial and public [HOLIDAY] functions in the G7 countries and Switzerland are available:

Holidays Related to Easter:

Septuagesima, Quinquagesima, AshWednesday, PalmSunday, GoodFriday, EasterSunday, Easter, EasterMonday, RogationSunday, Ascension, Pentecost, PentecostMonday, TrinitySunday CorpusChristi.

Holidays Related to Christmas:

ChristTheKing, Advent1st, Advent1st, Advent3rd, Advent4th, ChristmasEve, ChristmasDay, BoxingDay, NewYearsDay.

Other Ecclestical Feasts:

SolemnityOfMary, Epiphany, PresentationOfLord, Annunciation, TransfigurationOfLord, AssumptionOfMary, AssumptionOfMary, BirthOfVirginMary, CelebrationOfHolyCross, MassOfArchangels, AllSaints, AllSouls.

CHZurich - Public Holidays:

CHBerchtoldsDay, CHSechselaeuten, CHAscension, CHConfederationDay, CHKnabenschiessen.

GBLondon - Public Holidays:

GBMayDay, GBBankHoliday, GBSummerBankHoliday, GBNewYearsEve.

DEFrankfurt - Public Holidays:

DEAscension, DECorpusChristi, DEGermanUnity, DEChristmasEve, DENewYearsEve.

FRParis - Public Holidays:

FRFetDeLaVictoire1945, FRAscension, FRBastilleDay, FRAssumptionVirginMary, FRAllSaints, FRArmisticeDay.

ITMilano - Public Holidays:

ITEpiphany, ITLiberationDay, ITRepublicAnniversary, ITAssumptionOfVirginMary, ITAllSaints, ITWWIVictoryAnniversary, ITStAmrose, ITImmaculateConception.

USNewYork/USChicago - Public Holidays:

USNewYearsDay, USInaugurationDay, USMLKingsBirthday, USLincolnsBirthday, USWashingtonsBirthday, USMemorialDay, USIndependenceDay, USLaborDay, USColumbusDay, USElectionDay, USVeteransDay, USThanksgivingDay, USChristmasDay, USCPulaskisBirthday, USGoodFriday.

CAToronto/CAMontreal - Public Holidays:

CAVictoriaDay, CACanadaDay, CACivicProvincialHoliday, CALabourDay, CAThanksgivingDay, CaRemembranceDay.

JPTokyo/JPOsaka - Public Holidays:

JPNewYearsDay, JPGantan, JPBankHolidayJan2, JPBankHolidayJan3, JPComingOfAgeDay, JPSeijinNoHi, JPNatFoundationDay, JPKenkokuKinenNoHi, JPGreeneryDay, JPMidoriNoHi, JPConstitutionDay, JPKenpouKinenBi, JPNationHoliday, JPKokuminNoKyujitu, JPChildrensDay, JPKodomoNoHi, JPMarineDay, JPUmiNoHi, JPRespectForTheAgedDay, JPKeirouNoHi, JPAutumnalEquinox, JPShuubun-no-hi, JPHealthandSportsDay, JPTaiikuNoHi, JPNationalCultureDay, JPBunkaNoHi, JPThanksgivingDay, JPKinrouKanshaNohi, JPKinrou-kansha-no-hi, JPEmperorsBirthday, JPTennou-tanjyou-bi, JPTennou-tanjyou-bi.

Value

The function holiday returns an object of class timeDate.

Examples

```
## holiday -
# Dates for GoodFriday from 2000 until 2010:
holiday(2000:2010, "GoodFriday")

## Easter -
Easter(2000:2010)
```

```
## GoodFriday -
  GoodFriday(2000:2010)
  Easter(2000:2010, -2)
```

 holidayDate

Public and Ecclesiastical Holidays

Description

A collection and description of functions and methods dealing with holiday dates in the G7 countries and Switzerland.

Usage

```
Septuagesima(year = getRmetricsOptions("currentYear"))
Quinquagesima(year = getRmetricsOptions("currentYear"))
AshWednesday(year = getRmetricsOptions("currentYear"))
PalmSunday(year = getRmetricsOptions("currentYear"))
GoodFriday(year = getRmetricsOptions("currentYear"))
EasterSunday(year = getRmetricsOptions("currentYear"))
EasterMonday(year = getRmetricsOptions("currentYear"))
RogationSunday(year = getRmetricsOptions("currentYear"))
Ascension(year = getRmetricsOptions("currentYear"))
Pentecost(year = getRmetricsOptions("currentYear"))
PentecostMonday(year = getRmetricsOptions("currentYear"))
TrinitySunday(year = getRmetricsOptions("currentYear"))
CorpusChristi(year = getRmetricsOptions("currentYear"))
ChristTheKing(year = getRmetricsOptions("currentYear"))
Advent1st(year = getRmetricsOptions("currentYear"))
Advent2nd(year = getRmetricsOptions("currentYear"))
Advent3rd(year = getRmetricsOptions("currentYear"))
Advent4th(year = getRmetricsOptions("currentYear"))
ChristmasEve(year = getRmetricsOptions("currentYear"))
ChristmasDay(year = getRmetricsOptions("currentYear"))
BoxingDay(year = getRmetricsOptions("currentYear"))
NewYearsDay(year = getRmetricsOptions("currentYear"))
SolemnityOfMary(year = getRmetricsOptions("currentYear"))
Epiphany(year = getRmetricsOptions("currentYear"))
PresentationOfLord(year = getRmetricsOptions("currentYear"))
Annunciation(year = getRmetricsOptions("currentYear"))
TransfigurationOfLord(year = getRmetricsOptions("currentYear"))
AssumptionOfMary(year = getRmetricsOptions("currentYear"))
BirthOfVirginMary(year = getRmetricsOptions("currentYear"))
CelebrationOfHolyCross(year = getRmetricsOptions("currentYear"))
MassOfArchangels(year = getRmetricsOptions("currentYear"))
AllSaints(year = getRmetricsOptions("currentYear"))
```

```
AllSouls(year = getRmetricsOptions("currentYear"))
LaborDay(year = getRmetricsOptions("currentYear"))
CHBerchtoldsDay(year = getRmetricsOptions("currentYear"))
CHSechselaeuten(year = getRmetricsOptions("currentYear"))
CHAscension(year = getRmetricsOptions("currentYear"))
CHConfederationDay(year = getRmetricsOptions("currentYear"))
CHKnabenschiessen(year = getRmetricsOptions("currentYear"))
GBMayDay(year = getRmetricsOptions("currentYear"))
GBBankHoliday(year = getRmetricsOptions("currentYear")) # see note in details section
GBSummerBankHoliday(year = getRmetricsOptions("currentYear"))
GBMilleniumDay(year = getRmetricsOptions("currentYear"))
DEAscension(year = getRmetricsOptions("currentYear"))
DECorpusChristi(year = getRmetricsOptions("currentYear"))
DEGermanUnity(year = getRmetricsOptions("currentYear"))
DEChristmasEve(year = getRmetricsOptions("currentYear"))
DENewYearsEve(year = getRmetricsOptions("currentYear"))
FRFetDeLaVictoire1945(year = getRmetricsOptions("currentYear"))
FRAscension(year = getRmetricsOptions("currentYear"))
FRBastilleDay(year = getRmetricsOptions("currentYear"))
FRAssumptionVirginMary(year = getRmetricsOptions("currentYear"))
FRAllSaints(year = getRmetricsOptions("currentYear"))
FRArmisticeDay(year = getRmetricsOptions("currentYear"))
ITEpiphany(year = getRmetricsOptions("currentYear"))
ITLiberationDay(year = getRmetricsOptions("currentYear"))
ITAssumptionOfVirginMary(year = getRmetricsOptions("currentYear"))
ITAllSaints(year = getRmetricsOptions("currentYear"))
ITStAmrose(year = getRmetricsOptions("currentYear"))
ITImmaculateConception(year = getRmetricsOptions("currentYear"))
USDecorationMemorialDay(year = getRmetricsOptions("currentYear"))
USPresidentsDay(year = getRmetricsOptions("currentYear"))
USNewYearsDay(year = getRmetricsOptions("currentYear"))
USInaugurationDay(year = getRmetricsOptions("currentYear"))
USMLKingsBirthday(year = getRmetricsOptions("currentYear"))
USLincolnsBirthday(year = getRmetricsOptions("currentYear"))
USWashingtonsBirthday(year = getRmetricsOptions("currentYear"))
USMemorialDay(year = getRmetricsOptions("currentYear"))
USIndependenceDay(year = getRmetricsOptions("currentYear"))
USLaborDay(year = getRmetricsOptions("currentYear"))
USColumbusDay(year = getRmetricsOptions("currentYear"))
USElectionDay(year = getRmetricsOptions("currentYear"))
USVeteransDay(year = getRmetricsOptions("currentYear"))
USThanksgivingDay(year = getRmetricsOptions("currentYear"))
USChristmasDay(year = getRmetricsOptions("currentYear"))
USCPulaskisBirthday(year = getRmetricsOptions("currentYear"))
USGoodFriday(year = getRmetricsOptions("currentYear"))
CAVictoriaDay(year = getRmetricsOptions("currentYear"))
CACanadaDay(year = getRmetricsOptions("currentYear"))
CACivicProvincialHoliday(year = getRmetricsOptions("currentYear"))
```

```

CALabourDay(year = getRmetricsOptions("currentYear"))
CAThanksgivingDay(year = getRmetricsOptions("currentYear"))
CaRemembranceDay(year = getRmetricsOptions("currentYear"))
JPVernalEquinox (year = getRmetricsOptions("currentYear"))
JPNewYearsDay(year = getRmetricsOptions("currentYear"))
JPGantan(year = getRmetricsOptions("currentYear"))
JPBankHolidayJan2(year = getRmetricsOptions("currentYear"))
JPBankHolidayJan3(year = getRmetricsOptions("currentYear"))
JPComingOfAgeDay(year = getRmetricsOptions("currentYear"))
JPSeijinNoHi(year = getRmetricsOptions("currentYear"))
JPNatFoundationDay(year = getRmetricsOptions("currentYear"))
JPKenkokuKinenNoHi(year = getRmetricsOptions("currentYear"))
JPGreeneryDay(year = getRmetricsOptions("currentYear"))
JPMidoriNoHi(year = getRmetricsOptions("currentYear"))
JPConstitutionDay(year = getRmetricsOptions("currentYear"))
JPKenpouKinenBi(year = getRmetricsOptions("currentYear"))
JPNationHoliday(year = getRmetricsOptions("currentYear"))
JPKokuminNoKyujitu(year = getRmetricsOptions("currentYear"))
JPChildrensDay(year = getRmetricsOptions("currentYear"))
JPKodomoNoHi(year = getRmetricsOptions("currentYear"))
JPMarineDay(year = getRmetricsOptions("currentYear"))
JPUmiNoHi(year = getRmetricsOptions("currentYear"))
JPRespectForTheAgedDay(year = getRmetricsOptions("currentYear"))
JPKeirouNOHi(year = getRmetricsOptions("currentYear"))
JPAutumnalEquinox(year = getRmetricsOptions("currentYear"))
JPShuubunNoHi(year = getRmetricsOptions("currentYear"))
JPHealthandSportsDay(year = getRmetricsOptions("currentYear"))
JPTaiikuNoHi(year = getRmetricsOptions("currentYear"))
JPNationalCultureDay(year = getRmetricsOptions("currentYear"))
JPBunkaNoHi(year = getRmetricsOptions("currentYear"))
JPThanksgivingDay(year = getRmetricsOptions("currentYear"))
JPKinrouKanshaNoHi(year = getRmetricsOptions("currentYear"))
JPEmperorsBirthday(year = getRmetricsOptions("currentYear"))
JPTennoTanjyouBi(year = getRmetricsOptions("currentYear"))
JPBankHolidayDec31(year = getRmetricsOptions("currentYear"))

```

Arguments

`year` an integer value or vector of year numbers including the century. These are integers of the form CCYY, e.g. 2000.

Details

Note that `GBBankHoliday()` returns GB Spring bank holiday. For GB holiday calender see `holidayGB()`.

Value

The function `listHolidays` returns a character vector with the names of the supported holidays. The holiday functions return an ISO-8601 formatted 'timeDate' of the requested holiday.

Examples

```
## listHolidays -
  listHolidays()

## CHSechselaeuten -
  # Sechselaeuten a half Day Bank Holiday in Switzerland
  CHSechselaeuten(2000:2010)
  CHSechselaeuten(getRmetricsOptions("currentYear"))

## German Unification Day:
  DEGermanUnity(getRmetricsOptions("currentYear"))
```

holidayLONDON	<i>London Bank Holidays</i>
---------------	-----------------------------

Description

Returns bank holidays in London.

Usage

```
holidayLONDON(year = getRmetricsOptions("currentYear"))
```

Arguments

year an integer value or vector of years, formatted as YYYY.

Details

There are 8 bank holidays in Britain every year: New Year's Day, Good Friday, Easter Monday, Spring (May), Last Monday of May, End of Summer (Last Monday) August, Christmas Eve, Christmas Day.

Value

returns an object of class `timeDate`.

Author(s)

Function contributed by Menon Murali

Examples

```
## holidayLONDON -
  holidayLONDON()
  holidayLONDON(2008:2010)
```

holidayNERC

NERC Holiday Calendar

Description

Returns a holiday calendar for NERC, the North American Reliability Council.

Usage

```
holidayNERC(year = getRmetricsOptions("currentYear"), FinCenter = "Eastern")
```

Arguments

year an integer value or vector of years, formatted as YYYY.
FinCenter a character value, the name of the financial center to use.

Value

returns an object of class `timeDate`.

Author(s)

Joe W. Byers

References

<http://www.nerc.com/~oc/offpeaks.html>

Examples

```
## holidayNERC -  
  holidayNERC()  
  holidayNERC(2008:2010)
```

holidayNYSE

NYSE Holiday Calendar

Description

Returns a holiday calendar for the New York Stock Exchange.

Usage

```
holidayNYSE(year = getRmetricsOptions("currentYear"))
```

Arguments

year an integer value or vector of years, formatted as YYYY.

Value

returns an object of class timeDate.

Examples

```
## holidayNYSE -  
holidayNYSE()  
holidayNYSE(2008:2010)
```

holidayTSX	<i>TSX Holiday Calendar</i>
------------	-----------------------------

Description

Returns a holiday calendar for the Toronto Stock Exchange.

Usage

```
holidayTSX(year = getRmetricsOptions("currentYear"))
```

Arguments

year an integer value or vector of years, formatted as YYYY.

Value

returns an object of class timeDate.

Examples

```
## holidayTSX -  
holidayTSX()  
holidayTSX(2008:2010)
```

holidayZURICH	<i>Zurich Holiday Calendar</i>
---------------	--------------------------------

Description

Returns a holiday calendar for Zurich.

Usage

```
holidayZURICH(year = getRmetricsOptions("currentYear"))
```

Arguments

year an integer value or vector of years, formatted as YYYY.

Details

The Zurich holiday calendar includes the following holidays: NewYearsDay, GoodFriday, EasterMonday, LaborDay, PentecostMonday, ChristmasDay, BoxingDay, CHBerchtoldsDay, CHSechse-laeuten, CHAscension, CHConfederationDay, CHKnabenschiessen.

Value

returns an object of class `timeDate`.

Examples

```
## holidayZURICH -  
  holidayZURICH()  
  holidayZURICH(2008:2010)
```

is.na-methods	<i>is.na Methods</i>
---------------	----------------------

Description

is.na methods for 'timeDate' objects.

Examples

```
# Create a timeCalendar sequence
(td <- timeCalendar())
is.na(td)

# insert NA's
is.na(td) <- 2:3
td

# test of NA's
is.na(td)
```

isBizday

*Business and Holidays***Description**

Tests if a date is a business day or not.

Usage

```
isBizday(x, holidays = holidayNYSE(), wday = 1:5)
isHoliday(x, holidays = holidayNYSE(), wday = 1:5)
```

Arguments

x	an object of class <code>timeDate</code> .
holidays	holiday dates from a holiday calendar. An object of class <code>timeDate</code> .
wday	Specify which days should be considered as weekdays. By default from Mondays to Fridays.

Value

a logical vector of the same length as `x` indicating if a date is a business day, or a holiday, respectively.

Examples

```
## Dates in April, currentYear:
currentYear = getRmetricsOptions("currentYear")
tS = timeSequence(
  from = paste(currentYear, "-03-01", sep = ""),
  to = paste(currentYear, "-04-30", sep = "")
)
tS

## Subset Business Days at NYSE:
holidayNYSE()
isBizday(tS, holidayNYSE())
tS[isBizday(tS, holidayNYSE())]
```

 isRegular

Checks if a date/time vector is regular

Description

Checks if a date/time vector is regular. i.e. if it is a daily, a monthly, or a quarterly date/time vector. If the date/time vector is regular the frequency can be determined by calling the function `frequency`.

Usage

```
## S4 method for signature 'timeDate'
isDaily(x)
## S4 method for signature 'timeDate'
isMonthly(x)
## S4 method for signature 'timeDate'
isQuarterly(x)

## S4 method for signature 'timeDate'
isRegular(x)

## S4 method for signature 'timeDate'
frequency(x, ...)
```

Arguments

`x` an R object of class `timeDate`.
`...` arguments to be passed

Details

A date/time vector is defined as daily if the vector has not more than one date/time stamp per day.

A date/time vector is defined as monthly if the vector has not more than one date/time stamp per month.

A date/time vector is defined as quarterly if the vector has not more than one date/time stamp per quarter.

A monthly date/time vector is also a daily vector, a quarterly date/time vector is also a monthly vector.

A regular date/time vector is either a monthly or a quarterly vector.

NOT yet implemented is the case of weekly vectors.

Value

The `is*` functions return TRUE or FALSE depending on whether the date/time vector fulfills the condition or not.

The function `frequency` returns in general 1, for quarterly date/time vectors 4, and for monthly vectors 12.

Examples

```
## None
```

isWeekday	<i>Weekdays and Weekends</i>
-----------	------------------------------

Description

Tests if a date is a weekday or not.

Usage

```
isWeekday(x, wday = 1:5)  
isWeekend(x, wday = 1:5)
```

Arguments

x	an object of class <code>timeDate</code> .
wday	Specify which days should be considered as weekdays. By default from Mondays to Fridays.

Value

the functions return logical vectors indicating if a date is a weekday, or a weekend day.

Examples

```
## Dates in April, currentYear:  
currentYear = getRmetricsOptions("currentYear")  
tS = timeSequence(  
  from = paste(currentYear, "-03-01", sep = ""),  
  to = paste(currentYear, "-04-30", sep = "")  
  tS  
  
## Subset of Weekends:  
isWeekend(tS)  
tS[isWeekend(tS)]
```

 julian

Julian Counts and Calendar Atoms

Description

Returns Julian day counts, date/time atoms from a 'timeDate' object, and extracts month atoms from a 'timeDate' object.

Usage

```
## S4 method for signature 'timeDate'
julian(x, origin = timeDate("1970-01-01"),
       units = c("auto", "secs", "mins", "hours", "days", "weeks"),
       zone = NULL, FinCenter = NULL, ...)

## S4 method for signature 'timeDate'
atoms(x, ...)

## S4 method for signature 'timeDate'
months(x, abbreviate = NULL)
```

Arguments

x	an object of class timeDate.
origin	a length-one object inheriting from class "timeDate" setting the origin for the julian counter.
units	a character string denoting the date/time units in which the results are desired.
zone	the time zone or financial center where the data were recorded.
FinCenter	a character with the the location of the financial center named as "continent/city".
abbreviate	currently not used.
...	arguments passed to other methods.

Value

julian returns a timeDate object as a Julian count.

atoms and months extrac from a timeDate object the calendar atoms, i.e. the year, month, day, and optionally hour, minute and second.

Examples

```
## julian -
tC = timeCalendar()
julian(tC)[1:3]

## atoms -
atoms(tC)
```

```
## months -
  months(tc)
```

kurtosis

Kurtosis

Description

Functions to compute kurtosis.

Usage

```
kurtosis(x, ...)

## Default S3 method:
kurtosis(x, na.rm = FALSE, method = c("excess", "moment", "fisher"), ...)
## S3 method for class 'data.frame'
kurtosis(x, ...)
## S3 method for class 'POSIXct'
kurtosis(x, ...)
## S3 method for class 'POSIXlt'
kurtosis(x, ...)
```

Arguments

na.rm	a logical. Should missing values be removed?
method	a character string which specifies the method of computation. These are either "moment", "fisher", or "excess". If "excess" is selected, then the value of the kurtosis is computed by the "moment" method and a value of 3 will be subtracted. The "moment" method is based on the definitions of kurtosis for distributions; these forms should be used when resampling (bootstrap or jackknife). The "fisher" method correspond to the usual "unbiased" definition of sample variance, although in the case of kurtosis exact unbiasedness is not possible.
x	a numeric vector or object.
...	arguments to be passed.

Value

kurtosis
returns the value of the statistics, a numeric value. An attribute which reports the used method is added.

See Also

[link{skewness}](#).

Examples

```
## mean -  
## var -  
# Mean, Variance:  
r = rnorm(100)  
mean(r)  
var(r)  
  
## kurtosis -  
kurtosis(r)
```

length	<i>Length of a 'timeDate' Object</i>
--------	--------------------------------------

Description

Returns the length of a 'timeDate' object.

Usage

```
## S3 method for class 'timeDate'  
length(x)
```

Arguments

x an object of class timeDate.

Value

returns an integer of length 1.

Examples

```
## timCalendar -  
tC = timeCalendar()  
  
## length -  
length(tC)
```

listFinCenter	<i>List of Financial Centers</i>
---------------	----------------------------------

Description

Lists supported financial centers.

Usage

```
listFinCenter(pattern = ".*")
```

Arguments

pattern a pattern character string as required by the [grep](#) function.

Details

The function `rulesFinCenter`, lists the daylight saving rules for a selected financial center.

There is no dependency on the POSIX implementation of your operating system because all time zone and day light saving time information is stored locally in ASCII files.

Value

returns a list of supported financial centers.

Examples

```
## myFinCenter - the global setting currently used:
getRmetricsOptions("myFinCenter")

## Other Financial Centers:
listFinCenter("Asia/")
listFinCenter("^A") # all beginning with "A"
listFinCenter("^[^A]") # all *not* beginning with "A"
listFinCenter(".*L") # cities with L*

stopifnot(identical(sort(listFinCenter()), ## 'A' and 'not A' == everything:
  sort(union(listFinCenter("^A"),
    listFinCenter("^[^A]")))))
```

listHolidays	<i>List of Holidayss</i>
--------------	--------------------------

Description

Returns the list of holidays.

Usage

```
listHolidays(pattern = ".*")
```

Arguments

pattern a pattern character string as required by the [grep](#) function.

Value

returns a list of holidays as a character vector.

Examples

```
## listHolidays -
# All Holidays:
listHolidays()

# Local Swiss Holidays:
listHolidays("CH")
```

midnightStandard	<i>Midnight Standard</i>
------------------	--------------------------

Description

Corrects 'timeDate' objects if they do not fulfill the ISO8601 midnight standard.

midnightStandard2() relies on [strptime](#) wherever possible, and there simply returns [as.POSIXct\(strptime\(charvec, f](#)

Usage

```
midnightStandard (charvec, format)
midnightStandard2(charvec, format)
```

Arguments

charvec a character string or vector of dates and times.
format a string, the format specification of the input character vector.

Value

midnightStandard returns a character and midnightStandard2 a [POSIXct](#) object.

Examples

```
ch <- "2007-12-31 24:00"
midnightStandard(ch)
(ms2 <- midnightStandard2(ch))
class(ms2)
```

myFinCenter

myFinCenter Variable

Description

A character string with the name of my financial center.

Note

Can be modified by the user to his own or any other financial center. The default is "GMT". To list all supported financial center use the function `listFinCenter`.

See Also

[listFinCenter](#)

Examples

```
## myFinCenter - the global setting currently used:
getRmetricsOptions("myFinCenter")

## Change to another Financial Center:
# setRmetricsOptions(myFinCenter = "Zurich")

## Do not take care about DST ...
# setRmetricsOptions(myFinCenter = "GMT")
```

myUnits	<i>Frequency of date/time Units</i>
---------	-------------------------------------

Description

A variable with the frequency of date/units.

Value

returns the the date/time units, a acharacter value. By default "days".

Examples

```
## myUnits -
  getRmetricsOptions("myUnits")
```

names-methods	<i>The Names of a timeDate Object</i>
---------------	---------------------------------------

Description

Functions to get or set the names of a timeDate object.

Usage

```
## S4 method for signature 'timeDate'
names(x)
## S4 replacement method for signature 'timeDate'
names(x) <- value
```

Arguments

x	an object of class timeDate.
value	a character vector of up to the same length as 'x', or 'NULL'.

Examples

```
td <- timeCalendar()
td
names(td) <- LETTERS[seq_along(td)]
td
```

nDay	<i>n-th n-day Dates</i>
------	-------------------------

Description

Computes the date for the n-th or last occurrence of a n-day in year/month.

Usage

```
timeNthNdayInMonth(charvec, nday = 1, nth = 1, format = "%Y-%m-%d",
  zone = "", FinCenter = "")
```

```
timeLastNdayInMonth(charvec, nday = 1, format = "%Y-%m-%d",
  zone = "", FinCenter = "")
```

Arguments

charvec	a character vector of dates and times.
nday	an integer vector with entries ranging from 0 (Sunday) to 6 (Saturday).
nth	an integer vector numbering the n-th occurrence.
format	the format specification of the input character vector.
zone	the time zone or financial center where the data were recorded.
FinCenter	a character with the the location of the financial center named as "continent/city".

Value

returns an object of class `timeDate`.

For function `timeNthNdayInMonth` the nth occurrence of a n-day ($nth = 1, \dots, 5$) in year, month, and for `timeLastNdayInMonth` the last nday in year, month will be returned.

Examples

```
## timeNthNdayInMonth -
# What date is the second Monday in April 2004 ?
timeNthNdayInMonth("2004-04-01", 1, 2)

## timeLastNdayInMonth -
# What date has the last Tuesday in May, 1996 ?
timeLastNdayInMonth("1996-05-01", 2)
```

onOrAfter

OnOrAfter/Before Dates

Description

Compute the date that is a "on-or-after" or "on-or-before" ans n-day.

Usage

```
timeNdayOnOrAfter(charvec, nday = 1, format = "%Y-%m-%d",
  zone = "", FinCenter = "")
```

```
timeNdayOnOrBefore(charvec, nday = 1, format = "%Y-%m-%d",
  zone = "", FinCenter = "")
```

Arguments

charvec	a character vector of dates and times.
nday	an integer vector with entries ranging from 0 (Sunday) to 6 (Saturday).
format	the format specification of the input character vector.
zone	the time zone or financial center where the data were recorded.
FinCenter	a character with the the location of the financial center named as "continent/city".

Value

returns an object of class `timeDate`.

`timeNdayOnOrAfter` returns the date in the specified month that is a n-day (e.g. Sun-day) on or after the given date. Month and date are given through the argument `charvec`.

For the function `timeNdayOnOrBefore` the date that is a n-day on or before the given date will be returned.

Examples

```
## Date as character String:
charvec = "2006-04-16"

## timeNdayOnOrAfter
# What date has the first Monday on or after March 15, 1986 ?
timeNdayOnOrAfter("1986-03-15", 1)

## timeNdayOnOrBefore
# What date has Friday on or before April 22, 1977 ?
timeNdayOnOrBefore("1986-03-15", 5)
```

 periods

Rolling periods

Description

Returns start and end dates for a rolling periods

Usage

```
periods(x, period = "12m", by = "1m", offset = "0d")
periodicallyRolling(x, period = "52w", by = "4w", offset = "0d")
monthlyRolling(x, period = "12m", by = "1m")
```

Arguments

x	an object of class <code>timeDate</code> .
period	a span string, consisting of a length integer and a unit value, e.g. "52w" for 52 weeks.
by	a span string, consisting of a length integer and a unit value, e.g. "4w" for 4 weeks.
offset	a span string, consisting of a length integer and a unit value, e.g. "0d" for no offset.

Details

Periodically Rolling - Allowed unit values are "m" for 4 weeks, "w" for weeks, "d" for days, "H" for hours, "M" for minutes, and "S" for seconds.

Monthly Calendar Rolling - The only allowed unit value is "m" for monthly periods. Express a quarterly period by "3m", a semester by "6m", a year by "12m" etc.

Examples

```
## Create Time Sequence -
x <- timeSequence(from = "2001-01-01", to = "2009-01-01", by = "day")

## Generate Periods -
periods(x, "12m", "1m")
periods(x, "52w", "4w")

## Roll Periodically -
periodicallyRolling(x)

## Roll Monthly -
monthlyRolling(x)
```

Description

Plot methods for timeDate objects.

Usage

```
## S4 method for signature 'timeDate'
plot(x, y, ...)
## S4 method for signature 'timeDate'
lines(x, y, ...)
## S4 method for signature 'timeDate'
points(x, y, ...)

axis.timeDate(side, x, at, format = NULL, labels = TRUE, ...)

## S3 method for class 'timeDate'
pretty(x, n=5, min.n=n%%3, shrink.sml=0.75,
       high.u.bias=1.5, u5.bias=0.5+1.5*high.u.bias,
       eps.correct=0, ...)
```

Arguments

x, y, at	an object of class timeDate.
side	an integer specifying which side of the plot the axis is to be drawn on. The axis is placed as follows: 1=below, 2=left, 3=above and 4=right.
format	a POSIX format string, e.g. "%Y-%m-%d".
labels	either a logical value specifying whether annotations are to be made at the tickmarks, or a vector of character strings to be placed at the tickpoints.
n	an integer giving the desired number of intervals.
min.n	a nonnegative integer giving the minimal number of intervals.
shrink.sml	a positive numeric by which a default scale is shrunk in the case when range(x) is very small.
high.u.bias	a non-negative numeric, typically > 1. Larger high.u.bias values favor larger units.
u5.bias	a non-negative numeric multiplier favoring factor 5 over 2.
eps.correct	an integer code, one of 0,1,2. If non-0, a correction is made at the boundaries.
...	arguments passed to other methods.

Value

returns a summary report of the details of a timeDate object. This includes the starting and end date, the number of dates the format and the financial center in use.

Note

These S3 methods will become S4 methods in the future.

Examples

```
## timeCalendar -
x <- timeCalendar()
y <- rnorm(12)

## Plotting :

plot(x, y, type = "l")
points(x, y, pch = 19, col = "red")

plot(x, y, type = "l", xaxt = "n")
axis.timeDate(1, at = x[c(1, 3, 5, 7, 9, 11)], format = "%b")
axis.timeDate(1, at = x[12], format = "%Y")
```

 rep

Replicating 'timeDate' Objects

Description

replicates a 'timeDate' object.

Usage

```
## S3 method for class 'timeDate'
rep(x, ...)
```

Arguments

x an object of class timeDate.
 ... arguments passed to other methods.

Value

returns an object of class "timeDate".

Examples

```
## c -
# Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms
```

```
## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
ZUR

## c -
# Concatenate and Replicate timeDate Objects:
c(GMT[1:2], ZUR[1:2])
c(ZUR[1:2], GMT[1:2])

## rep -
rep(ZUR[2], times = 3)
rep(ZUR[2:3], times = 2)
```

 rev

Reverting 'timeDate' Objects

Description

Reverts a 'timeDate' object.

Usage

```
## S3 method for class 'timeDate'
rev(x)
```

Arguments

x an object of class timeDate.

Value

returns an object of class "timeDate".

Examples

```
## c -
# Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
```

```

ZUR

## c -
# Concatenate and Replicate timeDate Objects:
c(GMT[1:2], ZUR[1:2])
c(ZUR[1:2], GMT[1:2])

## rep -
rep(ZUR[2], times = 3)
rep(ZUR[2:3], times = 2)

```

RmetricsOptions	<i>Rmetrics Option Settings</i>
-----------------	---------------------------------

Description

Allow the user to set and examine a variety of global options which affect the way in which Rmetrics functions computes and displays its results.

Usage

```

setRmetricsOptions(...)
getRmetricsOption(x, unset = "")

```

Arguments

unset	a character string holding the return value is x is not set.
x	a character string holding an option name.
...	any options can be defined, using name = value or by passing a list of such tagged values.

round	<i>Rounding and Truncating 'timeDate' Objects</i>
-------	---

Description

Rounds and truncates objects of class 'timeDate'.

Usage

```

## S3 method for class 'timeDate'
round(x, digits = c("days", "hours", "mins"))

## S3 method for class 'timeDate'
trunc(x, units = c("days", "hours", "mins"), ...)

```

Arguments

digits, units a character string denoting the date/time units in which the results are desired.
 x an object of class timeDate.
 ... arguments passed to other methods.

Value

The two functions round and trunc allow to round or to truncate timeDate objects to the specified unit and return them as timeDate objects. - Note, there is an inconsistency round uses digits as argument and not units.

Examples

```
## round -
## truncate -
```

rulesFinCenter *Financial Centers DST Rules*

Description

Returns DST rules for a financial center.

Usage

```
rulesFinCenter(FinCenter = "")
```

Arguments

FinCenter a character with the the location of the financial center named as "continent/city".

Details

The function rulesFinCenter, lists the daylight saving rules for a selected financial center.

There is no dependency on the POSIX implementation of your operating system because all time zone and day light saving time information is stored locally in ASCII files.

Value

returns a list of time zones and DST rules available in the database.

Examples

```
## rulesFinCenter -
rulesFinCenter("Zurich")
```

sample	<i>Resampling 'timeDate' Objects</i>
--------	--------------------------------------

Description

Resamples a 'timeDate' object.

Value

returns an object of class "timeDate".

Examples

```
## c -
# Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
ZUR

## c -
# Concatenate and Replicate timeDate Objects:
c(GMT[1:2], ZUR[1:2])
c(ZUR[1:2], GMT[1:2])

## rep -
rep(ZUR[2], times = 3)
rep(ZUR[2:3], times = 2)
```

show-methods	<i>Show Methods</i>
--------------	---------------------

Description

Show methods for 'timeDate' objects.

Methods

object = "ANY" Generic function.

object = "timeDate" Print function for objects of class "timeDate".

Examples

```
## print | show -
print(timeCalendar())
```

skewness	<i>Skewness</i>
----------	-----------------

Description

Functions to compute skewness.

Usage

```
skewness(x, ...)

## Default S3 method:
skewness(x, na.rm = FALSE, method = c("moment", "fisher"), ...)
## S3 method for class 'data.frame'
skewness(x, ...)
## S3 method for class 'POSIXct'
skewness(x, ...)
## S3 method for class 'POSIXlt'
skewness(x, ...)
```

Arguments

na.rm	a logical. Should missing values be removed?
method	a character string which specifies the method of computation. These are either "moment" or "fisher" The "moment" method is based on the definitions of skewness for distributions; these forms should be used when resampling (bootstrap or jackknife). The "fisher" method correspond to the usual "unbiased" definition of sample variance, although in the case of skewness exact unbiasedness is not possible.
x	a numeric vector or object.
...	arguments to be passed.

Value

skewness

returns the value of the statistics, a numeric value. An attribute which reports the used method is added.

See Also

link{kurtosis}.

Examples

```
## mean -
## var -
# Mean, Variance:
r = rnorm(100)
mean(r)
var(r)

## skewness -
skewness(r)
```

 sort

Sorting 'timeDate' Objects

Description

Sorts a 'timeDate' object.

Usage

```
## S3 method for class 'timeDate'
sort(x, ...)
```

Arguments

x an object of class timeDate.
 ... arguments passed to other methods.

Value

returns an object of class "timeDate".

Examples

```
## c -
# Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
ZUR
```

```
## c -
# Concatenate and Replicate timeDate Objects:
c(GMT[1:2], ZUR[1:2])
c(ZUR[1:2], GMT[1:2])

## rep -
rep(ZUR[2], times = 3)
rep(ZUR[2:3], times = 2)
```

start

Terminal Times and Range

Description

Extracts the time the first or last observation was taken, or computes the range.

Usage

```
## S3 method for class 'timeDate'
start(x, ...)

## S3 method for class 'timeDate'
end(x, ...)

## S3 method for class 'timeDate'
min(..., na.rm = FALSE)

## S3 method for class 'timeDate'
max(..., na.rm = FALSE)

## S3 method for class 'timeDate'
range(..., na.rm = FALSE)
```

Arguments

x	an object of class timeDate.
...	[start][end] - not used, [min][max] - 'timeDates' objects.
na.rm	not used.

Details

Note, the series will be time ordered before the start or end time stamps are extracted. Sorting is done in the way that the first observation appears in time before the last observation.

Value

returns an object of class `timeDate`.

Examples

```
## timeCalendar -  
# Random Calendar Dates:  
tR = sample(timeCalendar())  
sort(tR)  
tR  
  
## start | end -  
start(tR)  
end(tR)  
  
## The First and Last Time Stamp:  
tR[1]  
tR[length(tR)]  
rev(tR)[1]  
  
## The Range:  
c(start(tR), end(tR))  
range(tR)
```

subset

Subsetting a 'timeDate' Object

Description

Extracts or replaces subsets from 'timeDate' objects.

Value

returns an object of class `timeDate`.

Examples

```
## timeCalendar -  
tS = timeCalendar()  
  
## [ -  
# Subsetting Second Quarter:  
tS[4:6]  
  
## [<-  
# Replacing:
```

summary-methods	<i>Summary Method</i>
-----------------	-----------------------

Description

Summarizes details of a 'timeDate' object.

Usage

```
## S3 method for class 'timeDate'
summary(object, ...)
```

Arguments

object	an object of class timeDate.
...	arguments passed to other methods.

Value

returns a summary report of the details of a timeDate object. This includes the starting and end date, the number of dates the format and the financial center in use.

Note

This S3 method will become in the future a S4 method

Examples

```
## summary -
tC = timeCalendar()
summary(tC)
```

Sys.timeDate	<i>System Time as 'timeDate' Object</i>
--------------	---

Description

Returns system time as an object of class 'timeDate'.

Usage

```
Sys.timeDate(FinCenter = "")
```

Arguments

FinCenter	a character with the the location of the financial center named as "continent/city".
-----------	--

Value

returns the system time as class "timeDate" object.

Examples

```
## Sys.time -

# direct
Sys.timeDate()

# transformed from "POSIX(c)t"
timeDate(Sys.time())

# Local Time in Zurich
timeDate(Sys.time(), FinCenter = "Zurich")
```

timeCalendar	<i>'timeDate' from Calendar Atoms</i>
--------------	---------------------------------------

Description

Create a 'timeDate' object from calendar atoms.

Usage

```
timeCalendar(y = getRmetricsOptions("currentYear"), m = 1:12, d = 1,
             h = 0, min = 0, s = 0,
             zone = "", FinCenter = "")
```

Arguments

y, m, d	calendar years (e.g. 1997), defaults are 1960, calendar months (1-12), defaults are 1, and calendar days (1-31), defaults are 1,
h, min, s	hours of the days (0-23), defaults are 0, minutes of the days (0-59), defaults are 0, and seconds of the days (0-59), defaults are 0.
zone	a character string, denoting the time zone or financial center where the data were recorded.
FinCenter	a character with the the location of the financial center named as "continent/city".

Value

returns a S4 object of `class` "timeDate".

Examples

```
## timeCalendar -

# Current Year:
getRmetricsOptions("currentYear")

# 12 months of current year
timeCalendar()

timeCalendar(m = c(9, 1, 8, 2), d = c(28, 15, 30, 9),
             y = c(1989, 2001, 2004, 1990), FinCenter = "GMT")

timeCalendar(m = c(9, 1, 8, 2), d = c(28, 15, 30, 9),
             y = c(1989, 2001, 2004, 1990), FinCenter = "Europe/Zurich")

timeCalendar(h = c(9, 14), min = c(15, 23))
```

timeDate	<i>'timeDate' Objects from Scratch</i>
----------	--

Description

Create a 'timeDate' object from scratch using a character vector.

Usage

```
timeDate(charvec, format = NULL, zone = "", FinCenter = "")

strptimeDate(x, format = whichFormat(x), tz = "")
```

Arguments

charvec	a character string or vector of dates and times.
format	the format specification of the input character vector.
tz	a character with the the location of the financial center named as "continent/city", or short "city".
zone	the time zone or financial center where the data were recorded.
x	a character string or vector of dates and times.
FinCenter	a character with the the location of the financial center named as "continent/city".

Value

returns an object of class timeDate.

Examples

```
## timeDate -

# Character Vector Strings:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")

dts; tms

t1 <- timeDate(dts, format = "%Y-%m-%d", FinCenter = "GMT" )
t1

stopifnot(identical(t1, timeDate(dts, FinC = "GMT"))) # auto-format

timeDate(dts, format = "%Y-%m-%d", FinCenter = "Europe/Zurich")

timeDate(paste(dts, tms), format = "%Y-%m-%d %H:%M:%S",
          zone = "GMT", FinCenter = "GMT")

timeDate(paste(dts, tms),
          zone = "Europe/Zurich", FinCenter = "Europe/Zurich")

timeDate(paste(dts, tms), format = "%Y-%m-%d %H:%M:%S",
          zone = "GMT", FinCenter = "Europe/Zurich")

## Non Standard Format:
timeDate(paste(20:31, "03.2005", sep="."), format = "%d.%m.%Y")

## Note, ISO and American Formats are Auto-Detected:
timeDate("2004-12-31", FinCenter = "GMT")
timeDate("12/11/2004", FinCenter = "GMT")
timeDate("1/31/2004") # auto-detect American format

## From POSIX?t, and using NAs
## lsec <- as.POSIXlt(.leap.seconds) ; lsec[c(2,4:6)] <- NA
## timeDate(lsec)

## dtms <- paste(dts,tms)
## dtms[2:3] <- NA
## timeDate(dtms, FinCenter = "Europe/Zurich") # but in GMT
```

Description

The class 'timeDate' represents date and time objects.

Details

For the management of chronological objects under R three concepts are available: The first is the implementation of date and time in R's chron package neglecting locals, time zones and day light saving times. This approach is in most cases appropriate for economic time series. The second approach, available in R's base package implements the POSIX standard to date and time objects, named "POSIXt".

Unfortunately, the representation of these objects is in some cases operating system dependent and especially under MS Windows several problems appeared over the time in the management of time zones and day light saving times. Rmetrics overcomes these difficulties with POSIX objects and introduce a new S4 class of 'timeDate' objects which allow for powerful methods to represent dates and times in different financial centers around the world.

Many of the basic functionalities of these objects are in common with S-Plus' timeDate objects and thus many of your privately written functions for SPlus/FinMetrics may also be used within the R/Rmetrics environment.

A major difference is the time zone concept which is replaced by the "Financial Center" concept. The FinCenter character variable specifies where you are living and at which financial center you are working. With the variable myFinCenter you can overwrite the default setting with your personal settings. With the specification of the FinCenter your system knows what rules rules for day light saving times should be applied, what is your holiday calendar, what is your currency, what are your interest rate conventions. (Not all specifications are already implemented.) Many other aspects can be easily accessed when a financial center is named. So we can distinguish between Frankfurt and Zurich, which both belong to the same time zone, but differed in DST changes in the eighties and have different holiday calendars. Furthermore, since the underlying time refers to "GMT" and DST rules and all other information is available in local (ASCII) databases, we are sure, that R/Rmetrics delivers with such a date/time concept on every computer independent of the operating system in use, identical results.

Another important feature of the "timeDate" concept used here is the fact that we don't rely on American or European ways to write dates. We use consequently the ISO-8601 standard for date and time notations.

Generation of 'timeDate' Objects

We have defined a timeDate class which is in many aspects similar to the S-Plus class with the same name, but has also some important advantageous differences. The S4 class has four Slots, the Data slot which holds date and time as 'POSIXct' objects in the standard ISO-8601 format, the Dim slot which gives the dimension of the data object (i.e. its length), the format specification slot and the FinCenter slot which holds the name of the financial center. By default this is the value

Three functions allow to generate date/time objects: timeDate from character vectors, timeCalendar from date and time atoms, and timeSequence from a "from/to" or from a "from/length" sequence specification. Note, time zone transformations are easily handled by the timeDate functions which can also take timeDate and POSIXt objects as inputs, while transforming them between financial centers and/or time zones specified by the arguments zone and FinCenter. Finally the

function `Sys.timeDate` returns current system time in form of a `timeDate` object.

Tests and Representation of timeDate Objects:

Rmetrics has implemented several methods to represent `timeDate` objects. For example, the `print` method returns the date/time in square `"[]"` brackets to distinguish the output from other date and time objects. On top of the date and time output the name of the `FinCenter` is printed. The `summary` method returns a printed report with information about the `timeDate` object. Finally, the `format` methods allows to transform objects into a ISO conform formatted character strings.

Mathematical Operations:

Rmetrics supports methods to perform many mathematical operations. Included are methods to extract or to replace subsets from `timeDate` objects, to perform arithmetic `"+"` and `"-"` operations, to group `Ops` generic functions, to return suitably lagged and iterated differences `diff`, to return differences `difftimeDate` of two `timeDate` objects, to concatenate objects, to replicate objects, to `round` objects, to truncate objects using `trunc`, to extract the first or last entry of a vector, to `sort` the objects of the elements of a date/time vector, and to revert 'timeDate' vector objects, among other functions.

Transformation of Objects:

Rmetrics has also functions to transform date/time objects between different representations. Included are methods to transform `timeDate` objects to character strings, to data frames, to `POSIXct` or `POSIXlt` objects, to `julian` counts. One can extract date/time atoms from calendar dates, and the `months` atoms from a `timeDate` object.

Objects from the Class

Objects can be created for example by calls of the functions `timeDate`, `timeCalender` and `timeCalendar` among others.

Slots

Data: Object of class `"POSIXct"`: a vector of `POSIXct` dates and times always related to `"GMT"`.

format: Object of class `"character"`: a character string denoting the format specification of the input `Data` character vector.

FinCenter: Object of class `"character"`: a character string with the the location of the financial center named as `"continent/city"`, or just `"city"`.

Methods

show `signature(object = "timeDate")`: prints an object of class 'timeDate'.

Note

Originally, these functions were written for Rmetrics users using R and Rmetrics under Microsoft's Windows XP operating system where time zones, daylight saving times and holiday calendars are not or insufficiently supported.

The usage of the Ical Library and the introduction of the FinCenter concept was originally developed for R Version 1.5. The timeDate and timeSeries objects were added for R Version 1.8.1. Minor changes were made to adapt the functions for R Version 1.9.1. As a consequence, newer concepts like the Date objects were not yet considered and included in this collection of date and time concepts. With R Version 2.3.0 a major update has been made adding many new generic functions and renaming a few already existing functions, please be aware of this.

Note, the date/time conversion from an arbitrary time zone to GMT cannot be unique, since date/time objects appear twice during the hour when DST changes and the isdt flag was not recorded. A bookkeeping which takes care if DST is effective or not is not yet included. However, in most applications this is not necessary since the markets are closed on weekends, especially at times when DST usually changes. It is planned for the future to implement the DST supporting this facility.

The ISO-8601 midnight standard has been implemented. Note, that for example "2005-01-01 24:00:00" is accepted as a valid date/time string.

Also available is an automated format recognition, so the user has not longer specify the format string for the most common date/time formats.

Examples

```
## Examples for Objects of class 'timeDate':

## timeDate -

Sys.timeDate()      # direct
timeDate(Sys.time()) # transformed from "POSIX(c)t"

# Local Time in Zurich
timeDate(Sys.time(), FinCenter = "Zurich")

# Character Vector Strings:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

t1 <- timeDate(dts, format = "%Y-%m-%d", FinCenter = "GMT" )
t1

stopifnot(identical(t1, timeDate(dts, FinC = "GMT"))) # auto-format

timeDate(dts, format = "%Y-%m-%d", FinCenter = "Europe/Zurich")

timeDate(paste(dts, tms), format = "%Y-%m-%d %H:%M:%S",
  zone = "GMT", FinCenter = "GMT")

timeDate(paste(dts, tms),
  zone = "Europe/Zurich", FinCenter = "Europe/Zurich")

timeDate(paste(dts, tms), format = "%Y-%m-%d %H:%M:%S",
  zone = "GMT", FinCenter = "Europe/Zurich")
```

```

## Non Standard Format:
timeDate(paste(20:31, "03.2005", sep="."), format = "%d.%m.%Y")

# Note, ISO and American Formats are Auto-Detected:
timeDate("2004-12-31", FinCenter = "GMT")
timeDate("12/11/2004", FinCenter = "GMT")
timeDate("1/31/2004") # auto-detect American format

## ... from POSIX?t, and Using NAs:
## lsec <- as.POSIXlt(.leap.seconds)
## lsec[c(2,4:6)] <- NA
## timeDate(lsec)

## dtms <- paste(dts,tms)
## dtms[2:3] <- NA
## timeDate(dtms, FinCenter = "Europe/Zurich") # but in GMT

## timeCalendar -

getRmetricsOptions("currentYear")
timeCalendar() # 12 months of current year
timeCalendar(m = c(9, 1, 8, 2), d = c(28, 15, 30, 9),
  y = c(1989, 2001, 2004, 1990), FinCenter = "GMT")
timeCalendar(m = c(9, 1, 8, 2), d = c(28, 15, 30, 9),
  y = c(1989, 2001, 2004, 1990), FinCenter = "Europe/Zurich")
timeCalendar(h = c(9, 14), min = c(15, 23))

## timeSequence -

timeSequence(from = "2004-03-12", to = "2004-04-11",
  format = "%Y-%m-%d", FinCenter = "GMT")
timeSequence(from = "2004-03-12", to = "2004-04-11",
  format = "%Y-%m-%d", FinCenter = "Europe/Zurich")

## print | summary | format -

tC = timeCalendar()
print(tC)
summary(tC)
format(tC)

```

Description

Functions for mathematical and logical operations on 'timeDate' objects.

The functions are:

Ops, timeDate	Group 'Ops' generic functions for 'timeDate' objects,
+, timeDate	Performs arithmetic + operation on 'timeDate' objects,
-, timeDate	Performs arithmetic - operation on 'timeDate' objects.

Usage

```
## S4 method for signature 'timeDate,timeDate'
Ops(e1, e2)
```

Arguments

e1, e2 usually objects of class timeDate, in the case of addition and subtraction e2 may be of class numeric.

Value

Ops.timeDate
these are functions for mathematical operations. Group Ops are generic functions which manage mathematical operations.

+.timeDate

-.timeDate

The plus operator "+" performs arithmetic "+" operation on timeDate objects, and the minus operator "-" returns a difftime object if both arguments e1 and e2 are "timeDate" objects, or returns a "timeDate" object e2 seconds earlier than e1.

Examples

```
## Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
```

```
ZUR
GMT + 24*3600
ZUR[2] - ZUR[1]
```

timeSequence	<i>Regularly spaced 'timeDate' objects</i>
--------------	--

Description

Create a regularly spaced object of class `timeDate`.

Usage

```
timeSequence(from, to = Sys.timeDate(), by, length.out = NULL,
             format = NULL, zone = "", FinCenter = "")
```

```
## S3 method for class 'timeDate'
seq(from, to, by, length.out = NULL, along.with = NULL, ...)
```

Arguments

<code>from, to</code>	starting date, required, and end date, optional. If supplied, <code>to</code> must be after (later than) <code>from</code> .
<code>by</code>	<ul style="list-style-type: none"> a character string, containing one of "sec", "min", "hour", "day", "week", "month" or "year". This can optionally be preceded by an integer and a space, or followed by "s". character string "quarter" that is equivalent to "3 months". A number, taken to be in seconds. A object of class 'difftime'
<code>length.out</code>	<code>length.out</code> integer, optional. Desired length of the sequence, if specified "to" will be ignored.
<code>along.with</code>	Take the length from the length of this argument.
<code>format</code>	the format specification of the input character vector.
<code>zone</code>	the time zone or financial center where the data were recorded.
<code>FinCenter</code>	a character with the the location of the financial center named as "continent/city".
<code>...</code>	arguments passed to other methods.

Value

an object of class `"timeDate"`.

Note

`timeSequence()` is a wrapper for the `"timeDate"` method of `seq()`, and that has been closely modeled after base R's POSIXt method, `seq.POSIXt`.

Examples

```
## timeSequence -

## autodetection of format :
(t1 <- timeSequence(from = "2004-03-12", to = "2004-04-11"))

stopifnot( ## different formats even:
  identical(t1, timeSequence(from = "2004-03-12", to = "11-Apr-2004")),
  identical(t1, ## explicit format and FinCenter :
    timeSequence(from = "2004-03-12", to = "2004-04-11",
      format = "%Y-%m-%d", FinCenter = "GMT")))

## observe "switch to summer time":
timeSequence(from = "2004-03-12", to = "2004-04-11",
  FinCenter = "Europe/Zurich")
```

 unique

Making a 'timeDate' object unique

Description

Makes a 'timeDate' object unique.

Usage

```
## S3 method for class 'timeDate'
unique(x, ...)
```

Arguments

```
x          an object of class timeDate.
...        arguments passed to other methods.
```

Value

returns an object of class "timeDate".

Examples

```
## c -
# Create Character Vectors:
dts = c("1989-09-28", "2001-01-15", "2004-08-30", "1990-02-09")
dts
tms = c("23:12:55", "10:34:02", "08:30:00", "11:18:23")
tms

## "+/-" -
# Add One Day to a Given timeDate Object:
GMT = timeDate(dts, zone = "GMT", FinCenter = "GMT")
```

```
GMT
ZUR = timeDate(dts, zone = "GMT", FinCenter = "Europe/Zurich")
ZUR

## c -
# Concatenate and Replicate timeDate Objects:
c(GMT[1:2], ZUR[1:2])
c(ZUR[1:2], GMT[1:2])

## rep -
rep(ZUR[2], times = 3)
rep(ZUR[2:3], times = 2)
```

whichFormat

Format Recognition

Description

Trys to recognize the date/time format.

Usage

```
whichFormat(charvec, silent = FALSE)
```

Arguments

charvec a character string or vector of dates and times.
silent a logical flag. Should a warning be printed if the format cannot be recognized?

Value

returns a format string.

Examples

```
## midnightStandard -
whichFormat("2007-12-31 24:00")
```

window

Time Windows

Description

Extract the subset of a 'timeDate' object observed between two time stamps.

Usage

```
## S3 method for class 'timeDate'  
window(x, start , end, ...)
```

```
## S3 method for class 'timeDate'  
cut(x, from , to, ...)
```

Arguments

from, to	starting date, required, and end date, ptional. If supplied to must be after from.
start, end	starting date, required, and end date, ptional. If supplied to must be after from.
x	an object of class timeDate.
...	arguments passed to other methods.

Value

returns an object of class timeDate.

Examples

```
## timeCalendar -  
# Monthly Dates in Current Year:  
tS = timeCalendar()  
tS  
  
## window -  
# 2nd Quarter Window:  
tS[4:6]  
window(tS, tS[4], tS[6])
```

Index

*Topic **chron**

- align, 14
- as.timeDate, 15
- blockStart, 16
- c, 17
- currentYear, 18
- dayOfWeek, 20
- dayOfYear, 21
- diff, 22
- difftimeDate, 23
- Easter, 23
- firstDay, 25
- format-methods, 27
- holiday, 28
- holidayDate, 30
- holidayLONDON, 33
- holidayNERC, 34
- holidayNYSE, 34
- holidayTSX, 35
- holidayZURICH, 36
- is.na-methods, 36
- isBizday, 37
- isRegular, 38
- isWeekday, 39
- julian, 40
- length, 42
- listFinCenter, 43
- listHolidays, 44
- midnightStandard, 44
- myFinCenter, 45
- myUnits, 46
- nDay, 47
- onOrAfter, 48
- plot-methods, 50
- rep, 51
- rev, 52
- round, 53
- rulesFinCenter, 54
- sample, 55

- show-methods, 55
- sort, 57
- start, 58
- subset, 59
- summary-methods, 60
- Sys.timeDate, 60
- timeCalendar, 61
- timeDate, 62
- timeDate-class, 63
- timeDateMathOps, 67
- timeSequence, 69
- unique, 70
- whichFormat, 71
- window, 72

*Topic **data**

- DaylightSavingTime, 19

*Topic **hplot**

- plot-methods, 50

*Topic **package**

- timeDate-package, 3

*Topic **programming**

- .endpoints, 13

*Topic **univar**

- kurtosis, 41
- skewness, 56

- +, numeric, timeDate-method
(timeDateMathOps), 67
- +, timeDate, numeric-method
(timeDateMathOps), 67
- +, timeDate, timeDate-method
(timeDateMathOps), 67
- , numeric, timeDate-method
(timeDateMathOps), 67
- , timeDate, numeric-method
(timeDateMathOps), 67
- , timeDate, timeDate-method
(timeDateMathOps), 67
- .endpoints, 13
- [, timeDate, ANY, missing-method (subset),

- 59
- [, timeDate, character, missing-method (subset), 59
- [, timeDate, logical, missing-method (subset), 59
- [, timeDate, missing, missing-method (subset), 59
- [, timeDate, numeric, missing-method (subset), 59
- [<- .timeDate (subset), 59
- Abidjan (DaylightSavingTime), 19
- abline, ANY, ANY, ANY, timeDate-method (plot-methods), 50
- Accra (DaylightSavingTime), 19
- Adak (DaylightSavingTime), 19
- Addis_Ababa (DaylightSavingTime), 19
- Adelaide (DaylightSavingTime), 19
- Aden (DaylightSavingTime), 19
- Advent1st (holidayDate), 30
- Advent2nd (holidayDate), 30
- Advent3rd (holidayDate), 30
- Advent4th (holidayDate), 30
- Algiers (DaylightSavingTime), 19
- align, 14
- align, ANY-method (align), 14
- align, timeDate-method (align), 14
- alignDaily (align), 14
- alignMonthly (align), 14
- alignQuarterly (align), 14
- AllSaints (holidayDate), 30
- AllSouls (holidayDate), 30
- Almaty (DaylightSavingTime), 19
- Amman (DaylightSavingTime), 19
- Amsterdam (DaylightSavingTime), 19
- Anadyr (DaylightSavingTime), 19
- Anchorage (DaylightSavingTime), 19
- Andorra (DaylightSavingTime), 19
- Anguilla (DaylightSavingTime), 19
- Annunciation (holidayDate), 30
- Antananarivo (DaylightSavingTime), 19
- Antigua (DaylightSavingTime), 19
- Any to 'timeDate' Coercion (as.timeDate), 15
- Apia (DaylightSavingTime), 19
- Aqtau (DaylightSavingTime), 19
- Aqtobe (DaylightSavingTime), 19
- Araguaina (DaylightSavingTime), 19
- Aruba (DaylightSavingTime), 19
- as.character.timeDate (as.timeDate), 15
- as.data.frame.timeDate (as.timeDate), 15
- as.Date.timeDate (as.timeDate), 15
- as.double.timeDate (as.timeDate), 15
- as.list.timeDate (as.timeDate), 15
- as.POSIXct, 44
- as.POSIXct.timeDate (as.timeDate), 15
- as.POSIXlt.timeDate (as.timeDate), 15
- as.timeDate, 15
- Ascension (holidayDate), 30
- Ashgabat (DaylightSavingTime), 19
- AshWednesday (holidayDate), 30
- Asmara (DaylightSavingTime), 19
- AssumptionOfMary (holidayDate), 30
- AST (DaylightSavingTime), 19
- Asuncion (DaylightSavingTime), 19
- Athens (DaylightSavingTime), 19
- Atikokan (DaylightSavingTime), 19
- atoms (julian), 40
- atoms, ANY-method (julian), 40
- atoms, timeDate-method (julian), 40
- Auckland (DaylightSavingTime), 19
- axis.timeDate (plot-methods), 50
- Azores (DaylightSavingTime), 19
- Baghdad (DaylightSavingTime), 19
- Bahia (DaylightSavingTime), 19
- Bahrain (DaylightSavingTime), 19
- Baku (DaylightSavingTime), 19
- Bamako (DaylightSavingTime), 19
- Bangkok (DaylightSavingTime), 19
- Bangui (DaylightSavingTime), 19
- Banjul (DaylightSavingTime), 19
- Barbados (DaylightSavingTime), 19
- Beirut (DaylightSavingTime), 19
- Belem (DaylightSavingTime), 19
- Belgrade (DaylightSavingTime), 19
- Belize (DaylightSavingTime), 19
- Berlin (DaylightSavingTime), 19
- Bermuda (DaylightSavingTime), 19
- BirthOfVirginMary (holidayDate), 30
- Bishkek (DaylightSavingTime), 19
- Bissau (DaylightSavingTime), 19
- Blanc-Sablon (DaylightSavingTime), 19
- Blantyre (DaylightSavingTime), 19
- blockEnd (blockStart), 16
- blockStart, 16
- Boa_Vista (DaylightSavingTime), 19
- Bogota (DaylightSavingTime), 19

- Boise (DaylightSavingTime), 19
- BoxingDay (holidayDate), 30
- Bratislava (DaylightSavingTime), 19
- Brazzaville (DaylightSavingTime), 19
- Brisbane (DaylightSavingTime), 19
- Broken_Hill (DaylightSavingTime), 19
- Brunei (DaylightSavingTime), 19
- Brussels (DaylightSavingTime), 19
- Bucharest (DaylightSavingTime), 19
- Budapest (DaylightSavingTime), 19
- Buenos_Aires (DaylightSavingTime), 19
- BuenosAires (DaylightSavingTime), 19
- Bujumbura (DaylightSavingTime), 19
- c, 17
- CACanadaDay (holidayDate), 30
- CACivicProvincialHoliday (holidayDate), 30
- CAFFamilyDay (holidayDate), 30
- Cairo (DaylightSavingTime), 19
- CALabourDay (holidayDate), 30
- Calcutta (DaylightSavingTime), 19
- Cambridge_Bay (DaylightSavingTime), 19
- Campo_Grande (DaylightSavingTime), 19
- Canary (DaylightSavingTime), 19
- Cancun (DaylightSavingTime), 19
- Cape_Verde (DaylightSavingTime), 19
- Caracas (DaylightSavingTime), 19
- CaRemembranceDay (holidayDate), 30
- Casablanca (DaylightSavingTime), 19
- Casey (DaylightSavingTime), 19
- Catamarca (DaylightSavingTime), 19
- CAThanksgivingDay (holidayDate), 30
- CAVictoriaDay (holidayDate), 30
- Cayenne (DaylightSavingTime), 19
- Cayman (DaylightSavingTime), 19
- CelebrationOfHolyCross (holidayDate), 30
- Center (DaylightSavingTime), 19
- CET (DaylightSavingTime), 19
- Ceuta (DaylightSavingTime), 19
- Chagos (DaylightSavingTime), 19
- CHAscension (holidayDate), 30
- Chatham (DaylightSavingTime), 19
- CHBerchtoldsDay (holidayDate), 30
- CHConfederationDay (holidayDate), 30
- Chicago (DaylightSavingTime), 19
- Chihuahua (DaylightSavingTime), 19
- Chisinau (DaylightSavingTime), 19
- CHKnabenschiessen (holidayDate), 30
- Choibalsan (DaylightSavingTime), 19
- Chongqing (DaylightSavingTime), 19
- Christmas (DaylightSavingTime), 19
- ChristmasDay (holidayDate), 30
- ChristmasEve (holidayDate), 30
- ChristTheKing (holidayDate), 30
- CHSechselaeuten (holidayDate), 30
- class, 61, 69
- Cocos (DaylightSavingTime), 19
- coerce, ANY, timeDate-method (as.timeDate), 15
- coerce, Date, timeDate-method (as.timeDate), 15
- coerce, POSIXt, timeDate-method (as.timeDate), 15
- coerce, timeDate, character-method (as.timeDate), 15
- coerce, timeDate, data.frame-method (as.timeDate), 15
- coerce, timeDate, Date-method (as.timeDate), 15
- coerce, timeDate, list-method (as.timeDate), 15
- coerce, timeDate, numeric-method (as.timeDate), 15
- coerce, timeDate, POSIXct-method (as.timeDate), 15
- coerce, timeDate, POSIXlt-method (as.timeDate), 15
- Colombo (DaylightSavingTime), 19
- Comoro (DaylightSavingTime), 19
- Conakry (DaylightSavingTime), 19
- Copenhagen (DaylightSavingTime), 19
- Cordoba (DaylightSavingTime), 19
- CorpusChristi (holidayDate), 30
- Costa_Rica (DaylightSavingTime), 19
- CST (DaylightSavingTime), 19
- Cuiaba (DaylightSavingTime), 19
- Curacao (DaylightSavingTime), 19
- currentYear, 18
- Currie (DaylightSavingTime), 19
- cut.timeDate (window), 72
- Dakar (DaylightSavingTime), 19
- Damascus (DaylightSavingTime), 19
- Danmarkshavn (DaylightSavingTime), 19
- Dar_es_Salaam (DaylightSavingTime), 19
- Darwin (DaylightSavingTime), 19
- Davis (DaylightSavingTime), 19

- Dawson (DaylightSavingTime), 19
- Dawson_Creek (DaylightSavingTime), 19
- DaylightSavingTime, 19
- dayOfWeek, 20, 27
- dayOfYear, 20, 21
- DEAscension (holidayDate), 30
- DEChristmasEve (holidayDate), 30
- DECorpusChristi (holidayDate), 30
- DEGermanUnity (holidayDate), 30
- DENewYearsEve (holidayDate), 30
- Denver (DaylightSavingTime), 19
- Detroit (DaylightSavingTime), 19
- Dhaka (DaylightSavingTime), 19
- diff, 22, 65
- difftoDate, 23, 65
- Dili (DaylightSavingTime), 19
- Djibouti (DaylightSavingTime), 19
- Dominica (DaylightSavingTime), 19
- Douala (DaylightSavingTime), 19
- Dubai (DaylightSavingTime), 19
- Dublin (DaylightSavingTime), 19
- DumontDUrville (DaylightSavingTime), 19
- Dushanbe (DaylightSavingTime), 19
- Easter, 23
- EasterMonday (holidayDate), 30
- Eastern (DaylightSavingTime), 19
- EasterSunday (holidayDate), 30
- Edmonton (DaylightSavingTime), 19
- EET (DaylightSavingTime), 19
- Efate (DaylightSavingTime), 19
- Eirunepe (DaylightSavingTime), 19
- El_Aaiun (DaylightSavingTime), 19
- El_Salvador (DaylightSavingTime), 19
- end (start), 58
- Enderbury (DaylightSavingTime), 19
- Epiphany (holidayDate), 30
- EST (DaylightSavingTime), 19
- Eucla (DaylightSavingTime), 19
- Fakaofu (DaylightSavingTime), 19
- Faroe (DaylightSavingTime), 19
- Fiji (DaylightSavingTime), 19
- finCenter, 24
- finCenter, timeDate-method (finCenter), 24
- finCenter<- (finCenter), 24
- finCenter<- , timeDate-method (finCenter), 24
- firstDay, 25
- format (format-methods), 27
- format-methods, 27
- Fortaleza (DaylightSavingTime), 19
- FRAllSaints (holidayDate), 30
- Frankfurt (DaylightSavingTime), 19
- FRArmisticeDay (holidayDate), 30
- FRAscension (holidayDate), 30
- FRAssumptionVirginMary (holidayDate), 30
- FRBastilleDay (holidayDate), 30
- Freetown (DaylightSavingTime), 19
- frequency (isRegular), 38
- frequency, timeDate-method (isRegular), 38
- FRFetDeLaVictoire1945 (holidayDate), 30
- Funafuti (DaylightSavingTime), 19
- Gaborone (DaylightSavingTime), 19
- Galapagos (DaylightSavingTime), 19
- Gambier (DaylightSavingTime), 19
- Gaza (DaylightSavingTime), 19
- GBBankHoliday (holidayDate), 30
- GBMayDay (holidayDate), 30
- GBMilleniumDay (holidayDate), 30
- GBSummerBankHoliday (holidayDate), 30
- getDataPart, timeDate-method (timeDate), 62
- getRmetricsOption (RmetricsOptions), 53
- getRmetricsOptions (RmetricsOptions), 53
- Gibraltar (DaylightSavingTime), 19
- Glace_Bay (DaylightSavingTime), 19
- Godthab (DaylightSavingTime), 19
- GoodFriday (holidayDate), 30
- Goose_Bay (DaylightSavingTime), 19
- Grand_Turk (DaylightSavingTime), 19
- Grenada (DaylightSavingTime), 19
- grep, 43, 44
- Guadalcanal (DaylightSavingTime), 19
- Guadeloupe (DaylightSavingTime), 19
- Guam (DaylightSavingTime), 19
- Guatemala (DaylightSavingTime), 19
- Guayaquil (DaylightSavingTime), 19
- Guernsey (DaylightSavingTime), 19
- Guyana (DaylightSavingTime), 19
- Halifax (DaylightSavingTime), 19
- Harare (DaylightSavingTime), 19
- Harbin (DaylightSavingTime), 19
- Havana (DaylightSavingTime), 19

- Helsinki (DaylightSavingTime), 19
- Hermosillo (DaylightSavingTime), 19
- Hobart (DaylightSavingTime), 19
- holiday, 28
- holidayDate, 30
- holidayLONDON, 33
- holidayNERC, 34
- holidayNYSE, 34
- holidayTSX, 35
- holidayZURICH, 36
- Hong_Kong (DaylightSavingTime), 19
- HongKong (DaylightSavingTime), 19
- Honolulu (DaylightSavingTime), 19
- Hovd (DaylightSavingTime), 19

- Indianapolis (DaylightSavingTime), 19
- initialize, timeDate-method (timeDate), 62
- Inuvik (DaylightSavingTime), 19
- Iqaluit (DaylightSavingTime), 19
- Irkutsk (DaylightSavingTime), 19
- is.na, timeDate-method (is.na-methods), 36
- is.na-methods, 36
- isBizday, 37
- isDaily (isRegular), 38
- isDaily, timeDate-method (isRegular), 38
- isHoliday (isBizday), 37
- Isle_of_Man (DaylightSavingTime), 19
- isMonthly (isRegular), 38
- isMonthly, timeDate-method (isRegular), 38
- isQuarterly (isRegular), 38
- isQuarterly, timeDate-method (isRegular), 38
- isRegular, 38
- isRegular, timeDate-method (isRegular), 38
- Istanbul (DaylightSavingTime), 19
- isWeekday, 39
- isWeekend (isWeekday), 39
- ITAllSaints (holidayDate), 30
- ITAssumptionOfVirginMary (holidayDate), 30
- ITEpiphany (holidayDate), 30
- ITImmaculateConception (holidayDate), 30
- ITLiberationDay (holidayDate), 30
- ITStAmrose (holidayDate), 30
- Jakarta (DaylightSavingTime), 19
- Jamaica (DaylightSavingTime), 19
- Jayapura (DaylightSavingTime), 19
- Jersey (DaylightSavingTime), 19
- Jerusalem (DaylightSavingTime), 19
- Johannesburg (DaylightSavingTime), 19
- Johnston (DaylightSavingTime), 19
- JPAutumnalEquinox (holidayDate), 30
- JPBankHolidayDec31 (holidayDate), 30
- JPBankHolidayJan2 (holidayDate), 30
- JPBankHolidayJan3 (holidayDate), 30
- JPBunkaNoHi (holidayDate), 30
- JPChildrensDay (holidayDate), 30
- JPComingOfAgeDay (holidayDate), 30
- JPConstitutionDay (holidayDate), 30
- JPEmperorsBirthday (holidayDate), 30
- JPGantan (holidayDate), 30
- JPGreeneryDay (holidayDate), 30
- JPHealthandSportsDay (holidayDate), 30
- JPKeirouNOhi (holidayDate), 30
- JPKenkokuKinenNoHi (holidayDate), 30
- JPKenpouKinenBi (holidayDate), 30
- JPKinrouKanshaNoHi (holidayDate), 30
- JKodomoNoHi (holidayDate), 30
- JKokuminNoKyujitu (holidayDate), 30
- JPMarineDay (holidayDate), 30
- JPMidoriNoHi (holidayDate), 30
- JPNatFoundationDay (holidayDate), 30
- JPNationalCultureDay (holidayDate), 30
- JPNationHoliday (holidayDate), 30
- JPNNewYearsDay (holidayDate), 30
- JPRespectForTheAgedDay (holidayDate), 30
- JPSeijinNoHi (holidayDate), 30
- JPShuubunNoHi (holidayDate), 30
- JPTaiikuNoHi (holidayDate), 30
- JPTennouTanjyouBi (holidayDate), 30
- JPThanksgivingDay (holidayDate), 30
- JPUniNoHi (holidayDate), 30
- JPVernalEquinox (holidayDate), 30
- Jujuy (DaylightSavingTime), 19
- julian, 40, 65
- julian, timeDate-method (julian), 40
- Juneau (DaylightSavingTime), 19

- Kabul (DaylightSavingTime), 19
- Kaliningrad (DaylightSavingTime), 19
- Kamchatka (DaylightSavingTime), 19
- Kampala (DaylightSavingTime), 19
- Karachi (DaylightSavingTime), 19

- Kashgar (DaylightSavingTime), 19
- Katmandu (DaylightSavingTime), 19
- Kerguelen (DaylightSavingTime), 19
- Khartoum (DaylightSavingTime), 19
- Kiev (DaylightSavingTime), 19
- Kigali (DaylightSavingTime), 19
- Kinshasa (DaylightSavingTime), 19
- Kiritimati (DaylightSavingTime), 19
- Knox (DaylightSavingTime), 19
- Kosrae (DaylightSavingTime), 19
- Krasnoyarsk (DaylightSavingTime), 19
- Kuala_Lumpur (DaylightSavingTime), 19
- KualaLumpur (DaylightSavingTime), 19
- Kuching (DaylightSavingTime), 19
- kurtosis, 41
- Kuwait (DaylightSavingTime), 19
- Kwajalein (DaylightSavingTime), 19

- La_Paz (DaylightSavingTime), 19
- La_Rioja (DaylightSavingTime), 19
- LaborDay (holidayDate), 30
- Lagos (DaylightSavingTime), 19
- lastDay (firstDay), 25
- length, 42
- Libreville (DaylightSavingTime), 19
- Lima (DaylightSavingTime), 19
- Lindeman (DaylightSavingTime), 19
- lines, timeDate-method (plot-methods), 50
- Lisbon (DaylightSavingTime), 19
- listFinCenter, 43, 45
- listHolidays, 44
- Ljubljana (DaylightSavingTime), 19
- Lome (DaylightSavingTime), 19
- London (DaylightSavingTime), 19
- Longyearbyen (DaylightSavingTime), 19
- Lord_Howe (DaylightSavingTime), 19
- Los_Angeles (DaylightSavingTime), 19
- LosAngeles (DaylightSavingTime), 19
- Louisville (DaylightSavingTime), 19
- Luanda (DaylightSavingTime), 19
- Lubumbashi (DaylightSavingTime), 19
- Lusaka (DaylightSavingTime), 19
- Luxembourg (DaylightSavingTime), 19

- Macau (DaylightSavingTime), 19
- Maceio (DaylightSavingTime), 19
- Madeira (DaylightSavingTime), 19
- Madrid (DaylightSavingTime), 19
- Magadan (DaylightSavingTime), 19
- Mahe (DaylightSavingTime), 19
- Majuro (DaylightSavingTime), 19
- Makassar (DaylightSavingTime), 19
- Malabo (DaylightSavingTime), 19
- Maldives (DaylightSavingTime), 19
- Malta (DaylightSavingTime), 19
- Managua (DaylightSavingTime), 19
- Manaus (DaylightSavingTime), 19
- Manila (DaylightSavingTime), 19
- Maputo (DaylightSavingTime), 19
- Marengo (DaylightSavingTime), 19
- Mariehamn (DaylightSavingTime), 19
- Marigot (DaylightSavingTime), 19
- Marquesas (DaylightSavingTime), 19
- Martinique (DaylightSavingTime), 19
- Maseru (DaylightSavingTime), 19
- MassOfArchangels (holidayDate), 30
- Mauritius (DaylightSavingTime), 19
- Mawson (DaylightSavingTime), 19
- max.timeDate (start), 58
- Mayotte (DaylightSavingTime), 19
- Mazatlan (DaylightSavingTime), 19
- Mbabane (DaylightSavingTime), 19
- McMurdo (DaylightSavingTime), 19
- Melbourne (DaylightSavingTime), 19
- Mendoza (DaylightSavingTime), 19
- Menominee (DaylightSavingTime), 19
- Merida (DaylightSavingTime), 19
- Mexico_City (DaylightSavingTime), 19
- MexicoCity (DaylightSavingTime), 19
- midnightStandard, 44
- midnightStandard2 (midnightStandard), 44
- Midway (DaylightSavingTime), 19
- min.timeDate (start), 58
- Minsk (DaylightSavingTime), 19
- Miquelon (DaylightSavingTime), 19
- Mogadishu (DaylightSavingTime), 19
- Monaco (DaylightSavingTime), 19
- Moncton (DaylightSavingTime), 19
- Monrovia (DaylightSavingTime), 19
- Monterrey (DaylightSavingTime), 19
- Montevideo (DaylightSavingTime), 19
- monthlyRolling (periods), 49
- months, 65
- months, timeDate-method (julian), 40
- Monticello (DaylightSavingTime), 19
- Montreal (DaylightSavingTime), 19
- Montserrat (DaylightSavingTime), 19

- Moscow (DaylightSavingTime), 19
- MST (DaylightSavingTime), 19
- Muscat (DaylightSavingTime), 19
- myFinCenter, 45
- myUnits, 46

- Nairobi (DaylightSavingTime), 19
- names, timeDate-method (names-methods), 46
- names-methods, 46
- names<-, timeDate-method (names-methods), 46
- Nassau (DaylightSavingTime), 19
- Nauru (DaylightSavingTime), 19
- nDay, 47
- Ndjamena (DaylightSavingTime), 19
- New_Salem (DaylightSavingTime), 19
- New_York (DaylightSavingTime), 19
- NewYearsDay (holidayDate), 30
- NewYork (DaylightSavingTime), 19
- Niamey (DaylightSavingTime), 19
- Nicosia (DaylightSavingTime), 19
- Nipigon (DaylightSavingTime), 19
- Niue (DaylightSavingTime), 19
- Nome (DaylightSavingTime), 19
- Norfolk (DaylightSavingTime), 19
- Noronha (DaylightSavingTime), 19
- Nouakchott (DaylightSavingTime), 19
- Noumea (DaylightSavingTime), 19
- Novosibirsk (DaylightSavingTime), 19

- Omsk (DaylightSavingTime), 19
- onOrAfter, 48
- onOrBefore (onOrAfter), 48
- Ops, 65
- Ops, timeDate, timeDate-method (timeDateMathOps), 67
- Oral (DaylightSavingTime), 19
- Oslo (DaylightSavingTime), 19
- Ouagadougou (DaylightSavingTime), 19

- Pacific (DaylightSavingTime), 19
- Pago_Pago (DaylightSavingTime), 19
- Palau (DaylightSavingTime), 19
- Palmer (DaylightSavingTime), 19
- PalmSunday (holidayDate), 30
- Panama (DaylightSavingTime), 19
- Pangnirtung (DaylightSavingTime), 19
- Paramaribo (DaylightSavingTime), 19

- Paris (DaylightSavingTime), 19
- Pentecost (holidayDate), 30
- PentecostMonday (holidayDate), 30
- periodicallyRolling (periods), 49
- periods, 49
- Perth (DaylightSavingTime), 19
- Petersburg (DaylightSavingTime), 19
- Phnom_Penh (DaylightSavingTime), 19
- Phoenix (DaylightSavingTime), 19
- Pitcairn (DaylightSavingTime), 19
- plot, timeDate-method (plot-methods), 50
- plot-methods, 50
- Podgorica (DaylightSavingTime), 19
- points, timeDate-method (plot-methods), 50

- Ponape (DaylightSavingTime), 19
- Pontianak (DaylightSavingTime), 19
- Port-au-Prince (DaylightSavingTime), 19
- Port_Moresby (DaylightSavingTime), 19
- Port_of_Spain (DaylightSavingTime), 19
- Porto-Novo (DaylightSavingTime), 19
- Porto_Velho (DaylightSavingTime), 19
- POSIXct, 45
- Prague (DaylightSavingTime), 19
- PresentationOfLord (holidayDate), 30
- pretty.timeDate (plot-methods), 50
- PST (DaylightSavingTime), 19
- Puerto_Rico (DaylightSavingTime), 19
- Pyongyang (DaylightSavingTime), 19

- Qatar (DaylightSavingTime), 19
- Quinquagesima (holidayDate), 30
- Qyzylorda (DaylightSavingTime), 19

- Rainy_River (DaylightSavingTime), 19
- range.timeDate (start), 58
- Rangoon (DaylightSavingTime), 19
- Rankin_Inlet (DaylightSavingTime), 19
- Rarotonga (DaylightSavingTime), 19
- Recife (DaylightSavingTime), 19
- Regina (DaylightSavingTime), 19
- rep, 51
- Resolute (DaylightSavingTime), 19
- Reunion (DaylightSavingTime), 19
- rev, 52
- Reykjavik (DaylightSavingTime), 19
- Riga (DaylightSavingTime), 19
- Rio_Branco (DaylightSavingTime), 19
- Rio_Gallegos (DaylightSavingTime), 19

- Riyadh (DaylightSavingTime), 19
- RmetricsOptions, 53
- RogationSunday (holidayDate), 30
- Rome (DaylightSavingTime), 19
- Rothera (DaylightSavingTime), 19
- round, 53, 65
- rulesFinCenter, 54
- Saigon (DaylightSavingTime), 19
- Saipan (DaylightSavingTime), 19
- Sakhalin (DaylightSavingTime), 19
- Samara (DaylightSavingTime), 19
- Samarkand (DaylightSavingTime), 19
- sample, 55
- sample, timeDate-method (sample), 55
- San_Juan (DaylightSavingTime), 19
- San_Marino (DaylightSavingTime), 19
- Santiago (DaylightSavingTime), 19
- Santo_Domingo (DaylightSavingTime), 19
- Sao_Paulo (DaylightSavingTime), 19
- Sao_Tome (DaylightSavingTime), 19
- Sarajevo (DaylightSavingTime), 19
- Scoresbysund (DaylightSavingTime), 19
- Seoul (DaylightSavingTime), 19
- Septuagesima (holidayDate), 30
- seq, 69
- seq.POSIXt, 69
- seq.timeDate (timeSequence), 69
- setRmetricsOptions (RmetricsOptions), 53
- Shanghai (DaylightSavingTime), 19
- Shiprock (DaylightSavingTime), 19
- show, ANY-method (show-methods), 55
- show, timeDate-method (show-methods), 55
- show-methods, 55
- show.timeDate (show-methods), 55
- Simferopol (DaylightSavingTime), 19
- Singapore (DaylightSavingTime), 19
- skewness, 56
- Skopje (DaylightSavingTime), 19
- Sofia (DaylightSavingTime), 19
- SolemnityOfMary (holidayDate), 30
- sort, 57, 65
- South_Georgia (DaylightSavingTime), 19
- South_Pole (DaylightSavingTime), 19
- St_Barthelemy (DaylightSavingTime), 19
- St_Helena (DaylightSavingTime), 19
- St_Johns (DaylightSavingTime), 19
- St_Kitts (DaylightSavingTime), 19
- St_Lucia (DaylightSavingTime), 19
- St_Thomas (DaylightSavingTime), 19
- St_Vincent (DaylightSavingTime), 19
- Stanley (DaylightSavingTime), 19
- start, 58
- Stockholm (DaylightSavingTime), 19
- strptime, 44
- strptimeDate (timeDate), 62
- subset, 59
- summary-methods, 60
- summary.timeDate (summary-methods), 60
- Swift_Current (DaylightSavingTime), 19
- Sydney (DaylightSavingTime), 19
- Syowa (DaylightSavingTime), 19
- Sys.timeDate, 60
- Tahiti (DaylightSavingTime), 19
- Taipei (DaylightSavingTime), 19
- Tallinn (DaylightSavingTime), 19
- Tarawa (DaylightSavingTime), 19
- Tashkent (DaylightSavingTime), 19
- Tbilisi (DaylightSavingTime), 19
- Tegucigalpa (DaylightSavingTime), 19
- Tehran (DaylightSavingTime), 19
- Tell_City (DaylightSavingTime), 19
- Thimphu (DaylightSavingTime), 19
- Thule (DaylightSavingTime), 19
- Thunder_Bay (DaylightSavingTime), 19
- Tijuana (DaylightSavingTime), 19
- timeCalendar, 61
- timeDate, 62, 69
- timeDate, ANY-method (timeDate), 62
- timeDate, character-method (timeDate), 62
- timeDate, Date-method (timeDate), 62
- timeDate, missing-method (timeDate), 62
- timeDate, numeric-method (timeDate), 62
- timeDate, POSIXt-method (timeDate), 62
- timeDate, timeDate-method (timeDate), 62
- timeDate-class, 63
- timeDate-package, 3
- timeDateMathOps, 67
- timeFirstDayInMonth (firstDay), 25
- timeFirstDayInQuarter (firstDay), 25
- timeLastDayInMonth (firstDay), 25
- timeLastDayInQuarter (firstDay), 25
- timeLastNdayInMonth (nDay), 47
- timeNdayOnOrAfter (onOrAfter), 48
- timeNdayOnOrBefore (onOrAfter), 48
- timeNthNdayInMonth (nDay), 47
- timeSequence, 69

Tirane (DaylightSavingTime), 19
Tokyo (DaylightSavingTime), 19
Tongatapu (DaylightSavingTime), 19
Toronto (DaylightSavingTime), 19
Tortola (DaylightSavingTime), 19
TransfigurationOfLord (holidayDate), 30
TrinitySunday (holidayDate), 30
Tripoli (DaylightSavingTime), 19
Truk (DaylightSavingTime), 19
trunc, 65
trunc (round), 53
Tucuman (DaylightSavingTime), 19
Tunis (DaylightSavingTime), 19

Ulaanbaatar (DaylightSavingTime), 19
unique, 70
Urumqi (DaylightSavingTime), 19
USChristmasDay (holidayDate), 30
USColumbusDay (holidayDate), 30
USCPulaskisBirthday (holidayDate), 30
USDecorationMemorialDay (holidayDate),
30
USElectionDay (holidayDate), 30
USGoodFriday (holidayDate), 30
Ushuaia (DaylightSavingTime), 19
USInaugurationDay (holidayDate), 30
USIndependenceDay (holidayDate), 30
USLaborDay (holidayDate), 30
USLincolnsBirthday (holidayDate), 30
USMemorialDay (holidayDate), 30
USMLKingsBirthday (holidayDate), 30
USNewYearsDay (holidayDate), 30
USPresidentsDay (holidayDate), 30
USThanksgivingDay (holidayDate), 30
USVeteransDay (holidayDate), 30
USWashingtonsBirthday (holidayDate), 30
Uzhgorod (DaylightSavingTime), 19

Vaduz (DaylightSavingTime), 19
Vancouver (DaylightSavingTime), 19
Vatican (DaylightSavingTime), 19
Vevay (DaylightSavingTime), 19
Vienna (DaylightSavingTime), 19
Vientiane (DaylightSavingTime), 19
Vilnius (DaylightSavingTime), 19
Vincennes (DaylightSavingTime), 19
Vladivostok (DaylightSavingTime), 19
Volgograd (DaylightSavingTime), 19
Vostok (DaylightSavingTime), 19

Wake (DaylightSavingTime), 19
Wallis (DaylightSavingTime), 19
Warsaw (DaylightSavingTime), 19
whichFormat, 71
Whitehorse (DaylightSavingTime), 19
Winamac (DaylightSavingTime), 19
Windhoek (DaylightSavingTime), 19
window, 72
Winnipeg (DaylightSavingTime), 19

Yakutat (DaylightSavingTime), 19
Yakutsk (DaylightSavingTime), 19
Yekaterinburg (DaylightSavingTime), 19
Yellowknife (DaylightSavingTime), 19
Yerevan (DaylightSavingTime), 19

Zagreb (DaylightSavingTime), 19
Zaporozhye (DaylightSavingTime), 19
Zurich (DaylightSavingTime), 19