

# Package ‘zeallot’

August 25, 2017

**Type** Package

**Title** Multiple, Unpacking, and Destructuring Assignment

**Version** 0.0.5

**Description** Provides a `%<-%` operator to perform multiple, unpacking, and destructuring assignment in R. The operator unpacks the right-hand side of an assignment into multiple values and assigns these values to variables on the left-hand side of the assignment.

**URL** <https://github.com/nteetor/zeallot>

**BugReports** <https://github.com/nteetor/zeallot/issues>

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 6.0.1

**VignetteBuilder** knitr

**Suggests** testthat, knitr, rmarkdown, purrr, magrittr

**NeedsCompilation** no

**Author** Nathan Teetor [aut, cre],  
Paul Teetor [ctb]

**Maintainer** Nathan Teetor <nathanteetor@gmail.com>

**Repository** CRAN

**Date/Publication** 2017-08-25 14:39:44 UTC

## R topics documented:

destructure . . . . .	2
operator . . . . .	3
zeallot . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

---

destructure	<i>Destructure an object</i>
-------------	------------------------------

---

### Description

destructure is used during unpacking assignment to coerce an object into a list. Individual elements of the list are assigned to names on the left-hand side of the unpacking assignment expression.

### Usage

```
destructure(x)
```

### Arguments

x                    An R object.

### Details

If x is atomic destructure expects `length(x)` to be 1. If a vector with length greater than 1 is passed to destructure an error is raised.

New implementations of destructure can be very simple. A new destructure implementation might only strip away the class of a custom object and return the underlying list structure. Alternatively, an object might destructure into a nested set of values and may require a more complicated implementation. In either case, new implementations must return a list object so `%<-%` can handle the returned value(s).

### See Also

[%<-%](#)

### Examples

```
# data frames become a list of columns
destructure(
  data.frame(x = 0:4, y = 5:9)
)

# strings are split into list of characters
destructure("abcdef")

# dates become list of year, month, and day
destructure(Sys.Date())

# create a new destructure implementation
shape <- function(sides = 4, color = "red") {
  structure(
    list(sides = sides, color = color),
    class = "shape"
  )
}
```

```
}

## Not run:
# cannot destructure the shape object yet
c(sides, color) %<-% shape()

## End(Not run)

# implement `destructure` for shapes
destructure.shape <- function(x) {
  list(x$sides, x$color)
}

# now we can destructure shape objects
c(sides, color) %<-% destructure(shape())

sides # 4
color # "red"

c(sides, color) %<-% destructure(shape(3, "green"))

sides # 3
color # 'green'
```

---

operator

*Multiple assignment operators*

---

### Description

Assign values to name(s).

### Usage

```
x %<-% value
```

```
value %->% x
```

### Arguments

x	A name structure, see section below.
value	A list of values, vector of values, or R object to assign.

### Value

%<-% and %->% invisibly return value.

These operators are used primarily for their assignment side-effect. %<-% and %->% assign into the environment in which they are evaluated.

## Name Structure

### the basics

At its simplest, the name structure may be a single variable name, in which case `%<-%` and `%->%` perform regular assignment, `x %<-% list(1, 2, 3)` or `list(1, 2, 3) %->% x`.

To specify multiple variable names use a call to `c()`, for example `c(x, y, z) %<-% c(1, 2, 3)`.

When value is neither an atomic vector nor a list, `%<-%` and `%->%` will try to destructure value into a list before assigning variables, see [destructure\(\)](#).

### nested names

One can also nest calls to `c()` when needed, `c(x, c(y, z))`. This nested structure is used to unpack nested values, `c(x, c(y, z)) %<-% list(1, list(2, 3))`.

### collector variables

To gather extra values from the beginning, middle, or end of value use a collector variable. Collector variables are indicated with a `...` prefix, `c(...start, z) %<-% list(1, 2, 3, 4)`.

### skipping values

Use `.` in place of a variable name to skip a value without raising an error or assigning the value, `c(x, ., z) %<-% list(1, 2, 3)`.

Use `...` to skip multiple values without raising an error or assigning the values, `c(w, ..., z) %<-% list(1, NA, NA, 4)`.

### default values

Use `=` to specify a default value for a variable, `c(x, y = NULL) %<-% tail(1, 2)`.

## See Also

For more on unpacking custom objects please refer to [destructure\(\)](#).

## Examples

```
# basic usage
c(a, b) %<-% list(0, 1)

a # 0
b # 1

# unpack and assign nested values
c(c(e, f), c(g, h)) %<-% list(list(2, 3), list(3, 4))

e # 2
f # 3
g # 4
h # 5

# can assign more than 2 values at once
c(j, k, l) %<-% list(6, 7, 8)

# assign columns of data frame
c(erupts, wait) %<-% faithful
```

```
erupts # 3.600 1.800 3.333 ..
wait   # 79 54 74 ..

# assign only specific columns, skip
# other columns
c(mpg, cyl, disp, ...) %<-% mtcars

mpg    # 21.0 21.0 22.8 ..
cyl    # 6 6 4 ..
disp   # 160.0 160.0 108.0 ..

# skip initial values, assign final value
TODOs <- list("make food", "pack lunch", "save world")

c(..., task) %<-% TODOs

task   # "save world"

# assign first name, skip middle initial,
# assign last name
c(first, ., last) %<-% c("Ursula", "K", "Le Guin")

first  # "Ursula"
last   # "Le Guin"

# simple model and summary
mod <- lm(hp ~ gear, data = mtcars)

# extract call and fstatistic from
# the summary
c(modcall, ..., modstat, .) %<-% summary(mod)

modcall
modstat

# unpack nested values w/ nested names
fibs <- list(1, list(2, list(3, list(5))))

c(f2, c(f3, c(f4, c(f5)))) %<-% fibs

f2    # 1
f3    # 2
f4    # 3
f5    # 5

# unpack first numeric, leave rest
c(f2, fibcdr) %<-% fibs

f2     # 1
fibcdr # list(2, list(3, list(5)))

# swap values without using temporary variables
c(a, b) %<-% c("eh", "bee")
```

```

a # "eh"
b # "bee"

c(a, b) %<-% c(b, a)

a # "bee"
b # "eh"

# unpack `strsplit` return value
names <- c("Nathan,Maria,Matt,Polly", "Smith,Peterson,Williams,Jones")

c(firsts, lasts) %<-% strsplit(names, ",")

firsts # c("Nathan", "Maria", ..
lasts  # c("Smith", "Peterson", ..

# handle missing values with default values
parse_time <- function(x) {
  strsplit(x, " ")[[1]]
}

c(hour, period = NA) %<-% parse_time("10:00 AM")

hour   # "10:00"
period # "AM"

c(hour, period = NA) %<-% parse_time("15:00")

hour   # "15:00"
period # NA

# right operator
list(1, 2, "a", "b", "c") %>-% c(x, y, ...chars)

x      # 1
y      # 2
chars  # list("a", "b", "c")

# magrittr chains, install.packages("magrittr") for this example
if (requireNamespace("magrittr", quietly = TRUE)) {
  library(magrittr)

  c("hello", "world!") %>%
    paste0("\n") %>%
    lapply(toupper) %>-%
    c(greeting, subject)

  greeting # "HELLO\n"
  subject  # "WORLD!\n"
}

```

---

zeallot

*Multiple, unpacking, and destructuring assignment in R*

---

### Description

zeallot provides a `%<-%` operator to perform multiple assignment in R. To get started with zeallot be sure to read over the introductory vignette on unpacking assignment, `vignette('unpacking-assignment')`.

### Author(s)

**Maintainer:** Nathan Teetor <nathanteetor@gmail.com>

Other contributors:

- Paul Teetor [contributor]

### See Also

[%<-%](#)

# Index

`%->%` (operator), [3](#)

`%<-%` (operator), [3](#)

`destructure`, [2](#)

`destructure()`, [4](#)

operator, [3](#)

`zeallot`, [7](#)

`zeallot-package` (`zeallot`), [7](#)