

Package ‘Countr’

November 20, 2017

Type Package

Title Flexible Univariate Count Models Based on Renewal Processes

Version 3.4.1

Date 2017-11-18

Author Tarak Kharrat, Georgi N. Boshnakov

Maintainer Tarak Kharrat <tarak.kharrat@gmail.com>

Description Flexible univariate count models based on renewal processes. The models may include covariates and can be specified with familiar formula syntax as in `glm()`.

License GPL (>= 2)

Depends R (>= 3.3.0)

Imports Matrix, Rcpp (>= 0.11.3), flexsurv, Formula, VGAM, optimx, numDeriv, boot, MASS, car, utils, Rdpack, lattice, RColorBrewer, dplyr, standardize, pscl, lmtest, xtable

LinkingTo Rcpp, RcppArmadillo

Suggests testthat, knitr

RdMacros Rdpack

VignetteBuilder knitr

LazyData true

RoxygenNote 6.0.1

NeedsCompilation yes

Collate 'Countr.R' 'RcppExports.R' 'coefnames.R' 'convCount_loglik.R' 'convCount_moments.R' 'convCount_probs.R' 'dWeibull.R' 'dWeibullgamma.R' 'data.R' 'renewal_IV.R' 'renewal_tools.R' 'renewal_cstr.R' 'tools.R' 'renewal_methods.R'

Repository CRAN

Date/Publication 2017-11-20 17:32:24 UTC

R topics documented:

addBootSampleObject	2
chiSq_gof	3
chiSq_pearson	4
compareToGLM	5
Countr	6
count_table	6
dCount_conv_bi	7
dCount_conv_loglik_bi	9
dmodifiedCount_bi	10
dWeibullCount	12
dWeibullgammaCount_mat_Covariates	13
evCount_conv_bi	14
fertility	15
football	16
frequency_plot	17
getParNames	17
predict.renewal	18
renewal	19
renewalCoef	19
renewalCoefList	20
renewalCount	21
renewalNames	24
renewal_methods	24
residuals_plot	26
se.coef	27
surv	28
Index	30

addBootSampleObject *Create a bootstrap sample for coefficient estimates*

Description

Create a bootstrap sample from coefficient estimates.

Usage

```
addBootSampleObject(object, ...)
```

Arguments

object	an object to add boot object to
...	extra parameters to be passed to the boot::boot() function other than data and statistic.

Details

The information in object is used to prepare the arguments and then boot is called to generate the bootstrap sample. The bootstrap sample is stored in object as component "boot". Arguments in "... " can be used to customise the boot() call.

Value

object with additional component "boot"

See Also

[renewal_methods](#)

Examples

```
## see renewal_methods
```

chiSq_gof

Formal Chi-square goodness-of-fit test

Description

Carry out the formal chi-square goodness-of-fit test described by Cameron (2013).

Usage

```
chiSq_gof(object, breaks, ...)

## S3 method for class 'renewal'
chiSq_gof(object, breaks, ...)

## S3 method for class 'negbin'
chiSq_gof(object, breaks, ...)

## S3 method for class 'glm'
chiSq_gof(object, breaks, ...)
```

Arguments

object	an object from class renewal
breaks	integer values at which the breaks should happen. The function will compute the observed frequencies in the intervals [breaks[i], breaks[i + 1]).
...	currently not used

Details

The test is a conditional moment test described in details in Cameron (2013, Section 5.3.4). We compute the asymptotically equivalent outer product of the gradient version which is justified for renewal models (fully parametric + parameters based on MLE).

Value

data.frame

References

Cameron AC and Trivedi PK (2013). *Regression analysis of count data*, volume 53. Cambridge university press.

See Also

[chiSq_pearson](#)

chiSq_pearson	<i>Pearson Chi-Square test</i>
---------------	--------------------------------

Description

Carry out Pearson Chi-Square test and compute the Pearson statistic.

Usage

```
chiSq_pearson(object, ...)

## S3 method for class 'renewal'
chiSq_pearson(object, ...)

## S3 method for class 'glm'
chiSq_pearson(object, ...)
```

Arguments

object	an object from class renewal
...	currently not used

Details

The computation is inspired from Cameron(2013) Chapter 5.3.4. Observed and fitted frequencies are computed and the contribution of every observed cell to the Pearson's chi-square test statistic is reported. The idea is to check if the fitted model has a tendency to over or under predict some ranges of data

Value

data.frame with 5 columns given the count values (Counts), observed frequencies (Actual), model's prediction (Predicted), the difference (Diff) and the contribution to the Pearson's statistic (Pearson).

References

Cameron AC and Trivedi PK (2013). *Regression analysis of count data*, volume 53. Cambridge university press.

See Also

[chiSq_gof](#)

compareToGLM	<i>Compare renewals fit to glm models fit</i>
--------------	---

Description

Compare renewals fit to glm models fit on the same data.

Usage

```
compareToGLM(poisson_model, breaks, nbinom_model, ...)
```

Arguments

poisson_model	fitted Poisson glm model
breaks	integer values at which the breaks should happen. The function will compute the observed frequencies in the intervals <code>[breaks[i],breaks[i + 1]]</code> .
nbinom_model	fitted negative binomial (fitted using <code>MASS::glm.nb()</code>). This argument is optional.
...	renewal models to be considered.

Details

This function computes a data.frame similar to Table 5.6 in Cameron(2013), using the observed frequencies and predictions from different models. Supported models accepted are Poisson and negative binomial (fitted using `MASS::glm.nb()`) from the glm family and any model from the renewal family (passed in ...).

Value

data.frame with columns Counts, Actual (observed probability) and then 2 columns per model passed (predicted probability and pearson statistic) for the associated count value.

References

Cameron AC and Trivedi PK (2013). *Regression analysis of count data*, volume 53. Cambridge university press.

Countr	<i>Flexible Univariate Count Models Based on Renewal Processes</i>
--------	--

Description

The main function is [renewalCount](#), see its documentation for examples.

Goodness of fit chi-square (likelihood ratio and Pearson) tests for glm and count renewal models are implemented in [chiSq_gof](#) and [chiSq_pearson](#).

Details

Flexible univariate count models based on renewal processes. The models may include covariates and can be specified with familiar formula syntax as in `glm()` and `'flexsurv'`.

References

Baker R and Kharrat T (2017). “Event count distributions from renewal processes: fast computation.” *IMA Journal of Management Mathematics*.

Boshnakov G, Kharrat T and McHale IG (2017). “A bivariate Weibull count model for forecasting association football scores.” *International Journal of Forecasting*, **33**(2), pp. 458–466.

Cameron AC and Trivedi PK (2013). *Regression analysis of count data*, volume 53. Cambridge university press.

McShane B, Adrian M, Bradlow ET and Fader PS (2008). “Count models based on Weibull inter-arrival times.” *Journal of Business & Economic Statistics*, **26**(3), pp. 369–378.

Winkelmann R (1995). “Duration dependence and dispersion in count-data models.” *Journal of Business & Economic Statistics*, **13**(4), pp. 467–474.

count_table	<i>Summary of a count variable</i>
-------------	------------------------------------

Description

Summary of a count variable.

Usage

```
count_table(count, breaks, formatChar = FALSE)
```

Arguments

count	integer, observed count value for every individual in the sample.
breaks	integer, values at which the breaks should happen. The function will compute the observed frequency in [breaks[i], breaks[i + 1]).
formatChar	logical, should the values be converted to character and formatted?

Details

The function does a similar job to `table()` with more flexibility introduced by the argument `breaks`. The user can decide how to break the count values and decide to merge some cells if needed.

Value

matrix with 2 rows and `length(breaks)` columns. The column names are the cells names. The rows are the observed frequencies and relative frequencies (probabilities).

dCount_conv_bi	<i>Compute count probabilities using convolution</i>
----------------	--

Description

Compute count probabilities using one of several convolution methods. `dCount_conv_bi` does the computations for the distributions with builtin support in this package.

`dCount_conv_user` does the same using a user defined survival function.

Usage

```
dCount_conv_bi(x, distPars, dist = c("weibull", "gamma", "gengamma", "burr"),
  method = c("dePril", "direct", "naive"), nsteps = 100, time = 1,
  extrap = TRUE, log = FALSE)
```

```
dCount_conv_user(x, distPars, extrapolPars, survR, method = c("dePril",
  "direct", "naive"), nsteps = 100, time = 1, extrap = TRUE,
  log = FALSE)
```

Arguments

x	integer (vector), the desired count values.
distPars	Rcpp::List with distribution specific slots, see details.
dist	character name of the built-in distribution, see details.
method	character string, the method to use, see Details.
nsteps	unsigned integer, number of steps used to compute the integral.
time	double, time at which to compute the probabilities. Set to 1 by default.

extrap	logical, if TRUE, Richardson extrapolation will be applied to improve accuracy.
log	logical, if TRUE the log-probability will be returned.
extrapolPars	vector of length 2, the extrapolation values.
survR	function, user supplied survival function; should have signature function(t, distPars), where t is a positive real number (the time where the survival function is evaluated) and distPars is a list of distribution parameters. It should return a double value.

Details

dCount_conv_bi computes count probabilities using one of several convolution methods for the distributions with builtin support in this package.

The following convolution methods are implemented: "dePril", "direct", and "naive".

The builtin distributions currently are Weibull, gamma, generalised gamma and Burr.

Value

vector of probabilities $P(x(i), i = 1, \dots, n)$ where n is the length of x .

Examples

```
x <- 0:10
lambda <- 2.56
p0 <- dpois(x, lambda)
ll <- sum(dpois(x, lambda, TRUE))

err <- 1e-6
## all-probs convolution approach
distPars <- list(scale = lambda, shape = 1)
pmat_bi <- dCount_conv_bi(x, distPars, "weibull", "direct",
                          nsteps = 200)

## user pwei
pwei_user <- function(tt, distP) {
  alpha <- exp(-log(distP[["scale"]])) / distP[["shape"]]
  pweibull(q = tt, scale = alpha, shape = distP[["shape"]],
          lower.tail = FALSE)
}

pmat_user <- dCount_conv_user(x, distPars, c(1, 2), pwei_user, "direct",
                             nsteps = 200)

max((pmat_bi - p0)^2 / p0)
max((pmat_user - p0)^2 / p0)

## naive convolution approach
pmat_bi <- dCount_conv_bi(x, distPars, "weibull", "naive",
                          nsteps = 200)
pmat_user <- dCount_conv_user(x, distPars, c(1, 2), pwei_user, "naive",
                              nsteps = 200)

max((pmat_bi - p0)^2 / p0)
```



```

max((pmat_user- p0)^2 / p0)

## dePril conv approach
pmat_bi <- dCount_conv_bi(x, distPars, "weibull", "dePril",
                          nsteps = 200)
pmat_user <- dCount_conv_user(x, distPars, c(1, 2), pwei_user, "dePril",
                              nsteps = 200)

max((pmat_bi- p0)^2 / p0)
max((pmat_user- p0)^2 / p0)

```

dCount_conv_loglik_bi *Log-likelihood of a count probability computed by convolution (bi)*

Description

Compute the log-likelihood of a count model using convolution methods to compute the probabilities. `dCount_conv_loglik_bi` is for the builtin distributions. `dCount_conv_loglik_user` is for user defined survival functions.

Usage

```

dCount_conv_loglik_bi(x, distPars, dist = c("weibull", "gamma", "gengamma",
      "burr"), method = c("dePril", "direct", "naive"), nsteps = 100,
      time = 1, extrap = TRUE, na.rm = TRUE, weights = NULL)

dCount_conv_loglik_user(x, distPars, extrapolPars, survR, method = c("dePril",
      "direct", "naive"), nsteps = 100, time = 1, extrap = TRUE,
      na.rm = TRUE, weights = NULL)

```

Arguments

<code>x</code>	integer (vector), the desired count values.
<code>distPars</code>	list of the same length as <code>x</code> with each slot being itself a named list containing the distribution parameters corresponding to <code>x[i]</code> .
<code>dist</code>	character name of the built-in distribution, see details.
<code>method</code>	character, convolution method to be used; choices are "dePril" (section 3.2), "direct" (section 2) or "naive" (section 3.1).
<code>nsteps</code>	unsigned integer number of steps used to compute the integral.
<code>time</code>	double time at which to compute the probabilities. Set to 1 by default.
<code>extrap</code>	logical if TRUE, Richardson extrapolation will be applied to improve accuracy.
<code>na.rm</code>	logical, if TRUE, NAs (produced by taking the log of very small probabilities) will be replaced by the smallest allowed probability; default is TRUE.
<code>weights</code>	numeric, vector of weights to apply. If NULL, a vector of ones.

extrapolPars list of same length as x where each slot is a vector of length 2 (the extrapolation values to be used) corresponding to x[i].

survR a user defined survival function; should have the signature function(t, distPars) where t is a real number (>0) where the survival function is evaluated and distPars is a list of distribution parameters. It should return a double value.

Value

numeric, the log-likelihood of the count process

Examples

```
x <- 0:10
lambda <- 2.56
distPars <- list(scale = lambda, shape = 1)
distParsList <- lapply(seq(along = x), function(ind) distPars)
extrapolParsList <- lapply(seq(along = x), function(ind) c(2, 1))
## user pwei
pwei_user <- function(tt, distP) {
  alpha <- exp(-log(distP[["scale"]])) / distP[["shape"]]
  pweibull(q = tt, scale = alpha, shape = distP[["shape"]],
    lower.tail = FALSE)
}

## log-likelihood allProbs Poisson
dCount_conv_loglik_bi(x, distParsList,
  "weibull", "direct", nsteps = 400)

dCount_conv_loglik_user(x, distParsList, extrapolParsList,
  pwei_user, "direct", nsteps = 400)

## log-likelihood naive Poisson
dCount_conv_loglik_bi(x, distParsList,
  "weibull", "naive", nsteps = 400)

dCount_conv_loglik_user(x, distParsList, extrapolParsList,
  pwei_user, "naive", nsteps = 400)

## log-likelihood dePril Poisson
dCount_conv_loglik_bi(x, distParsList,
  "weibull", "dePril", nsteps = 400)

dCount_conv_loglik_user(x, distParsList, extrapolParsList,
  pwei_user, "dePril", nsteps = 400)
## see dCount_conv_loglik_bi()
```

Description

Compute count probabilities based on modified renewal process using dePril algorithm. dmodifiedCount_bi does it for the builtin distributions.

dmodifiedCount_user does the same for a user specified distribution.

Usage

```
dmodifiedCount_bi(x, distPars, dist, distPars0, dist0, nsteps = 100L,
  time = 1, extrap = TRUE, cdfout = FALSE, logFlag = FALSE)
```

```
dmodifiedCount_user(x, distPars, survR, distPars0, survR0, extrapolPars,
  nsteps = 100L, time = 1, extrap = TRUE, cdfout = FALSE,
  logFlag = FALSE)
```

Arguments

x	integer (vector), the desired count values.
distPars0, distPars	Rcpp: :List with distribution specific slots for the first arrival and the rest of the process respectively.
dist0, dist	character, name of the first and following survival distributions.
nsteps	unsigned integer number of steps used to compute the integral.
time	double time at which to compute the probabilities. Set to 1 by default.
extrap	logical if TRUE, Richardson extrapolation will be applied to improve accuracy.
cdfout	TODO
logFlag	logical if TRUE the log-probability will be returned.
survR0, survR	user supplied survival function; should have signature function(t, distPars), where t is a positive real number (the time at which the survival function is evaluated) and distPars is a list of distribution parameters. It should return a double value (first arrival and following arrivals respectively).
extrapolPars	list of same length as x, where each slot is a vector of length 2 (the extrapolation values to be used) corresponding to x[i].

Details

For the modified renewal process the first arrival is allowed to have a different distribution from the time between subsequent arrivals. The renewal assumption is kept.

Value

vector of probabilities $P(x(i))$ for $i = 1, \dots, n$ where n is the length of x .

dWeibullCount

Probability calculations for Weibull count models

Description

Probability computations for the univariate Weibull count process. Several methods are provided. dWeibullCount computes probabilities.

dWeibullCount_loglik computes the log-likelihood.

evWeibullCount computes the expected value and variance.

Usage

```
dWeibullCount(x, shape, scale, method = c("series_acc", "series_mat",
  "conv_direct", "conv_naive", "conv_dePril"), time = 1, log = FALSE,
  conv_steps = 100, conv_extrap = TRUE, series_terms = 50,
  series_acc_niter = 300, series_acc_eps = 1e-10)
```

```
dWeibullCount_loglik(x, shape, scale, method = c("series_acc", "series_mat",
  "conv_direct", "conv_naive", "conv_dePril"), time = 1, na.rm = TRUE,
  conv_steps = 100, conv_extrap = TRUE, series_terms = 50,
  series_acc_niter = 300, series_acc_eps = 1e-10, weights = NULL)
```

```
evWeibullCount(xmax, shape, scale, method = c("series_acc", "series_mat",
  "conv_direct", "conv_naive", "conv_dePril"), time = 1, conv_steps = 100,
  conv_extrap = TRUE, series_terms = 50, series_acc_niter = 300,
  series_acc_eps = 1e-10)
```

Arguments

x	integer (vector), the desired count values.
shape	numeric (length 1), shape parameter of the Weibull count.
scale	numeric (length 1), scale parameter of the Weibull count.
method	character, one of the available methods, see details.
time	double, length of the observation window (defaults to 1).
log	logical, if TRUE, the log of the probability will be returned.
conv_steps	numeric, number of steps used for the extrapolation.
conv_extrap	logical, should Richardson extrappolation be applied ?
series_terms	numeric, number of terms in the series expansion.
series_acc_niter	numeric, number of iterations in the Euler-van Wijngaarden algorithm.
series_acc_eps	numeric, tolerance of convergence in the Euler-van Wijngaarden algorithm.
na.rm	logical, if TRUE NA's (produced by taking the log of very small probabilities) will be replaced by the smallest allowed probaility; default is TRUE.
weights	numeric, vector of weights to apply. If NULL, a vector of one's will be applied.
xmax	unsigned integer, maximum count to be used.

Details

Argument method can be used to specify the desired method, as follows:

"series_mat" - series expansion using matrix techniques,
 "series_acc" - Euler-van Wijngaarden accelerated series expansion (default),
 "conv_direct" - direct convolution method of section 2,
 "conv_naive" - naive convolution described in section 3.1,
 "conv_dePril" - dePril convolution described in section 3.2.

The arguments have sensible default values.

Value

for dWeibullCount, a vector of probabilities $P(x(i)), i = 1, \dots, n$, where $n = \text{length}(x)$.

for dWeibullCount_loglik, a double, the log-likelihood of the count process.

for evWeibullCount, a list with components:

ExpectedValue expected value,

Variance variance.

dWeibullgammaCount_mat_Covariates

Univariate Weibull Count Probability with gamma and covariate heterogeneity

Description

Univariate Weibull Count Probability with gamma and covariate heterogeneity

Usage

```
dWeibullgammaCount_mat_Covariates(x, cc, r, alpha, Xcovar, beta, t = 1,
  logFlag = FALSE, jmax = 100L)
```

Arguments

x, cc, t, logFlag, jmax	TODO keywords internal
r	numeric shape of the gamma distribution
alpha	numeric rate of the gamma distribution
Xcovar	matrix covariates value
beta	numeric vector of slopes

evCount_conv_bi *Expected value and variance of renewal count process*

Description

Compute numerically expected values and variances of renewal count processes.

Usage

```
evCount_conv_bi(xmax, distPars, dist = c("weibull", "gamma", "gengamma",
    "burr"), method = c("dePril", "direct", "naive"), nsteps = 100,
    time = 1, extrap = TRUE)
```

```
evCount_conv_user(xmax, distPars, extrapolPars, survR, method = c("dePril",
    "direct", "naive"), nsteps = 100, time = 1, extrap = TRUE)
```

Arguments

xmax	unsigned integer maximum count to be used.
distPars	TODO
dist	TODO
method	TODO
nsteps	unsigned integer, number of steps used to compute the integral.
time	double, time at which to compute the probabilities. Set to 1 by default.
extrap	logical, if TRUE, Richardson extrapolation will be applied to improve accuracy.
extrapolPars	ma::vec of length 2. The extrapolation values.
survR	function, user supplied survival function; should have signature <code>function(t, distPars)</code> , where <code>t</code> is a positive real number (the time where the survival function is evaluated) and <code>distPars</code> is a list of distribution parameters. It should return a double value.

Details

evCount_conv_bi computes the expected value and variance of renewal count processes for the builtin distributions of inter-arrival times.

evCount_conv_user computes the expected value and variance for a user specified distribution of the inter-arrival times.

Value

a named list with components "ExpectedValue" and "Variance".

Examples

```

pwei_user <- function(tt, distP) {
  alpha <- exp(-log(distP[["scale"]]) / distP[["shape"]])
  pweibull(q = tt, scale = alpha, shape = distP[["shape"]],
    lower.tail = FALSE)
}

## ev convolution Poisson count
lambda <- 2.56
beta <- 1
distPars <- list(scale = lambda, shape = beta)

evbi <- evCount_conv_bi(20, distPars, dist = "weibull")
evu <- evCount_conv_user(20, distPars, c(2, 2), pwei_user, "dePril")

c(evbi[["ExpectedValue"]], lambda)
c(evu[["ExpectedValue"]], lambda )
c(evbi[["Variance"]], lambda    )
c(evu[["Variance"]], lambda    )

## ev convolution weibull count
lambda <- 2.56
beta <- 1.35
distPars <- list(scale = lambda, shape = beta)

evbi <- evCount_conv_bi(20, distPars, dist = "weibull")
evu <- evCount_conv_user(20, distPars, c(2.35, 2), pwei_user, "dePril")

x <- 1:20
px <- dCount_conv_bi(x, distPars, "weibull", "dePril",
  nsteps = 100)
ev <- sum(x * px)
var <- sum(x^2 * px) - ev^2

c(evbi[["ExpectedValue"]], ev)
c(evu[["ExpectedValue"]], ev )
c(evbi[["Variance"]], var    )
c(evu[["Variance"]], var    )

```

fertility

Fertility data

Description

Fertility data analysed by Winkelmann(1995). The data comes from the second (1985) wave of German Socio-Economic Panel. The sample is formed by 1,243 women aged 44 or older in 1985. The response variable is the number of children per woman and explanatory variables are described in more details below.

Usage

fertility

Format

A data frame with 9 variables (5 factors, 4 integers) and 1243 observations:

children integer; response variable: number of children per woman (integer).

german factor; is the mother German? (yes or no).

years_school integer; education measured as years of schooling.

voc_train factor; vocational training ? (yes or no)

university factor; university education ? (yes or no)

Religion factor; mother's religion: Catholic, Protestant, Muslim or Others (reference).

rural factor; rural (yes or no ?)

year_birth integer; year of birth (last 2 digits)

age_marriage integer; age at marriage

For further details, see Winlemann(1995).

References

Winkelmann R (1995). "Duration dependence and dispersion in count-data models." *Journal of Business & Economic Statistics*, **13**(4), pp. 467–474.

football

Football data

Description

Final scores of all matches in the English Premier League from seasons 2009/2010 to 2016/2017.

Usage

football

Format

a data.frame with 6 columns and 1104 observations:

seasonId integer season identifier (year of the first month of competition).

gameDate POSIXct game date and time.

homeTeam, awayTeam character home and away team name.

homeTeamGoals, awayTeamGoals integer number of goals scored by the home and the away team.

Details

The data were collected from <http://www.football-data.co.uk/englandm.php> and slightly formatted and simplified.

frequency_plot	<i>Plot a frequency chart</i>
----------------	-------------------------------

Description

Plot a frequency chart to compare actual and predicted values.

Usage

```
frequency_plot(count_labels, actual, pred, colours)
```

Arguments

count_labels	character, labels to be used.
actual	numeric, the observed probabilities for the different count specified in count_labels.
pred	data.frame of predicted values. Should have the same number of rows as actual and one column per model. The columns' names will be used as labels for the different models.
colours	character vector of colour codes with length ncol(pred) + 2.

Details

In order to compare actual and fitted values, a barchart plot is created. It is the user's responsibility to provide the count, observed and fitted values.

getParNames	<i>Return the names of distribution parameters</i>
-------------	--

Description

Return the names of the parameters of a count distribution.

Usage

```
getParNames(dist, ...)
```

Arguments

dist	character, name of the distribution.
...	parameters to pass when dist == "custom".

Value

character vector with the names of the distribution parameters.

predict.renewal *Predict method for renewal objects*

Description

Compute predictions from renewal objects.

Usage

```
## S3 method for class 'renewal'
predict(object, newdata = NULL, type = c("response",
    "prob"), se.fit = FALSE, terms = NULL, na.action = na.pass, time = 1,
    ...)
```

Arguments

object	Object of class inheriting from "lm"
newdata	An optional data frame in which to look for variables with which to predict. If omitted, the fitted values are used.
type	type of prediction. If equal to "response", give the mean probability associated with the individual covariates. If "prob", give the probability of the observed count.
se.fit	A switch indicating if standard errors are required.
terms	If type = "terms", which terms (default is all terms), a character vector.
na.action	function determining what should be done with missing values in newdata. The default is to predict NA.
time	TODO
...	further arguments passed to or from other methods.

Examples

```
fn <- system.file("extdata", "McShane_Wei_results_boot.RDS", package = "Countr")
object <- readRDS(fn)
data <- object$data
## old data
predOld.response <- predict(object, type = "response", se.fit = TRUE)
predOld.prob <- predict(object, type = "prob", se.fit = TRUE)

## newData (extracted from old Data)
newData <- head(data)
predNew.response <- predict(object, newdata = newData,
    type = "response", se.fit = TRUE)
predNew.prob <- predict(object, newdata = newData,
    type = "prob", se.fit = TRUE)

cbind(head(predOld.response$values),
```

```

      head(predOld.response$se$scale),
      head(predOld.response$se$shape),
      predNew.response$values,
      predNew.response$se$scale,
      predNew.response$se$shape)

cbind(head(predOld.prob$values),
      head(predOld.prob$se$scale),
      head(predOld.prob$se$shape),
      predNew.prob$values,
      predNew.prob$se$scale,
      predNew.prob$se$shape)

```

renewal	<i>Deprecated old name of renewalCount()</i>
---------	--

Description

Deprecated old name of renewalCount()

Usage

```
renewal(...)
```

Arguments

... same arguments as renewalCount().

Details

This function is now renamed to renewalCount().

renewalCoef	<i>Get named vector of coefficients for renewal objects</i>
-------------	---

Description

Get named vector of coefficients for renewal objects.

Usage

```
renewalCoef(object, ...)
```

Arguments

object an object, there are methods for several classes, see Details.
 ... further arguments to be passed to renewalNames, usually something like target = "weibull".

Details

This is a convenience function for constructing named vector of coefficients for renewal count models. Such vectors are needed, for example, for starting values in the model fitting procedures. The simplest way to get a suitably named vector is to take the coefficients of a fitted model but if the fitting procedure requires initial values, this is seemingly a circular situation.

The overall idea is to take coefficients specified by `object` and transform them to coefficients suitable for a renewal count model as specified by the arguments "...". The provided methods eliminate the need for tedious manual preparation of such vectors and in the most common cases allow the user to do this in a single line.

The default method extracts the coefficients of `object` using

```
co <- coef(object) (an error is raised if this fails). It prepares a named numeric vector with names requested by the arguments in "...". The provided methods eliminate the need for tedious manual preparation of such vectors and in the most common cases allow the user to do this in a single line.
```

The net effect is that the coefficients of a model can be initialised from the coefficients of a nested model. For example a Poisson regression model can be used to initialise a Weibull count model. Of course the non-zero shape parameter(s) of the Weibull model need to be set separately.

If `object` is from class `glm`, the method is identical to the default method.

If `object` is from class `renewalCoefList`, its elements are simply concatenated in one long vector.

See Also

`renewalNames`

`renewalCoefList`

Split a vector using the prefixes of the names for grouping

Description

Split a vector using the prefixes of the names for grouping.

Usage

```
renewalCoefList(coef)
```

Arguments

`coef` a named vector

Details

The names of the coefficients of renewal regression models are prefixed with the names of the parameters to which they refer. This function splits such vectors into a list with one component for each parameter. For example, for a Weibull renewal regression model this will create a list with components "scale" and "shape".

This is a convenience function allowing users to manipulate the coefficients related to a parameter more easily. `renewalCoef` can convert this list back to a vector.

renewalCount	<i>Fit renewal count processes regression models</i>
--------------	--

Description

Fit renewal regression models for count data via maximum likelihood.

Usage

```
renewalCount(formula, data, subset, na.action, weights, offset,
  dist = c("weibull", "weibullgam", "custom", "gamma", "gengamma"),
  anc = NULL, convPars = NULL, link = NULL, time = 1,
  control = renewal.control(...), customPars = NULL, seriesPars = NULL,
  weiMethod = NULL, computeHessian = TRUE, standardise = FALSE,
  standardise_scale = 1, model = TRUE, y = TRUE, x = FALSE, ...)
```

Arguments

formula	single response formula object.
data, subset, na.action,	arguments controlling formula processing via model.frame.
weights	optional numeric vector of weights.
offset	optional numeric vector with an a priori known component to be included in the linear predictor of the count model. Currently not used.
dist	character, built-in distribution to be used as the inter-arrival time distribution or "custom" for a user defined distribution, see Details. Currently the built-in distributions are "weibull", "weibullgam", "gamma", "gengamma" (generalized-gamma) and "burr".
anc	named list of formulas for ancillary regressions, if any, otherwise NULL. The formulas associated with the (exact) parameter names are used.
convPars	a list of convolution parameters arguments with slots nsteps, extrapol and convMethod, see dCount_conv_bi. If NULL, default parameters will be applied.
link	named list of character strings specifying the name of the link functions to be used in the regression. If NULL, the canonical link function will be used, i.e, log if the parameter is supposed to be positive, identity otherwise.
time	numeric, time at which the count is observed; default to unity (1).
control	a list of control arguments specified via renewal.control.
customPars	list, user inputs if dist = "custom", see details.
seriesPars	list, series expansion input parameters with slots terms (number of terms in the series expansion), iter (number of iteration in the accelerated series expansion algorithm) and eps (tolerance in the accelerated series expansion algorithm), Only used if dist = "weibull" and weiMethod = c("series_mat", "series_acc").
weiMethod	character, computation method to be used if dist = "weibull" or "weibullgam", see dWeibullCount and dWeibullgammaCount.

<code>computeHessian</code>	logical, should the hessian (and hence the covariance matrix) be computed numerically at the fitted values.
<code>standardise</code>	logical should the covariates be standardised using <code>standardize::standardize()</code> function.
<code>standardise_scale</code>	numeric the desired scale for the covariates; default to 1
<code>model, y, x</code>	logicals. If TRUE the corresponding components of the fit (model frame, response, model matrix) are returned.
<code>...</code>	arguments passed to <code>renewal.control</code> in the default setup.

Details

`renewal` re-uses design and functionality of the basic R tools for fitting regression model (`lm`, `glm`) and is highly inspired by `hurdle()` and `zeroinfl()` from package `pscl`. Package `Formula` is used to handle formulas.

Distributions for inter-arrival times supported internally by this package can be chosen by setting argument `"dist"` to a suitable character string. Currently the built-in distributions are `"weibull"`, `"weibullgam"`, `"gamma"`, `"gengamma"` (generalized-gamma) and `"burr"`.

Users can also provide their own inter-arrival distribution. This is done by setting argument `"dist"` to `"custom"`, specifying the initial values and giving argument `customPars` as a list with the following components:

parNames character, the names of the parameters of the distribution. The location parameter should be the first one.

survivalFct function object containing the survival function. It should have signature `function(t, distPars)` where `t` is the point where the survival function is evaluated and `distPars` is the list of the distribution parameters. It should return a double value.

extrapolFct function object computing the extrapolation values (numeric of length 2) from the value of the distribution parameters (in `distPars`). It should have signature `function(distPars)` and return a numeric vector of length 2. Only required if the extrapolation is set to TRUE in `convPars`.

Some checks are done to validate `customPars` but it is user's responsibility to make sure the the functions have the appropriate signatures.

Note: The Weibull-gamma distribution is an experimental version and should be used with care! It is very sensitive to initial values and there is no guarantee of convergence. It has also been reparameterized in terms of $(1/r, 1/\alpha, c)$ instead of (r, α, c) , where r and α are the shape and scale of the gamma distribution and c is the shape of the Weibull distribution.

(2017-08-04(Georgi) experimental feature: probability residuals in component `'probResiduals'`. I also added type `'prob'` to the method for `residuals()` to extract them.

`probResiduals[i]` is currently $1 - \text{Prob}(Y[i] \text{ given the covariates})$. "one minus", so that values close to zero are "good". On its own this is probably not very useful but when comparing two models, if one of them has mostly smaller values than the other, there is some reason to claim that the former is superior. For example (see below), `gamModel < poisModel` in 3:1

Value

An S3 object of class "renewal", which is a list with components including:

coefficients values of the fitted coefficients.

residuals vector of weighted residuals $\omega * (observed - fitted)$.

fitted.values vector of fitted means.

optim data.frame output of optimx.

method optimisation algorithm.

control the control arguments, passed to optimx.

start starting values, passed to optimx.

weights weights to apply, if any.

n number of observations (with weights > 0).

iterations number of iterations in the optimisation algorithm.

execTime duration of the optimisation.

loglik log-likelihood of the fitted model.

df.residual residuals' degrees of freedom for the fitted model.

vcoc covariance matrix of all coefficients, computed numerically from the hessian at the fitted coefficients (if computeHessian is TRUE).

dist name of the inter-arrival distribution.

link list, inverse link function corresponding to each parameter in the inter-arrival distribution.

converged logical, did the optimisation algorithm converge?

data data used to fit the model.

formula the original formula.

call the original function call.

anc named list of formulas to model regression on ancillary parameters.

score_fct function to compute the vector of scores defined in Cameron(2013) equation 2.94.

convPars convolution inputs used.

customPars named list, user passed distribution inputs, see Details.

time observed window used, default is 1.0 (see inputs).

model the full model frame (if model = TRUE).

y the response count vector (if y = TRUE).

x the model matrix (if x = TRUE).

References

Cameron AC and Trivedi PK (2013). *Regression analysis of count data*, volume 53. Cambridge university press.

renewalNames	<i>Get names of parameters of renewal regression models</i>
--------------	---

Description

Get names of parameters of renewal regression models

Usage

```
renewalNames(object, ...)
```

Arguments

object	an object.
...	further arguments.

Details

renewalNames gives the a character vector of names of parameters for renewal regression models. There are two main use scenarios: `renewalNames(object, target = "dist")` and `renewalNames(object, ...)`. In the first scenario `target` can be a count distribution, such as "weibull" or a parameter name, such as `shape`. In this case `renewalNames` transforms coefficient names of `object` to those specified by `target`. In the second scenario the argument list is the same that would be used to call `renewalCount`. In this case `renewalNames` returns the names that would be used by `renewalCount` for the coefficients of the fitted model.

renewal_methods	<i>Methods for renewal objects</i>
-----------------	------------------------------------

Description

Methods for renewal objects.

Usage

```
## S3 method for class 'renewal'
coef(object, ...)

## S3 method for class 'renewal'
vcov(object, ...)

## S3 method for class 'renewal'
residuals(object, type = c("pearson", "response", "prob"),
  ...)
```



```

## S3 method for class 'renewal'
residuals_plot(object, type = c("pearson", "response",
  "prob"), ...)

## S3 method for class 'renewal'
fitted(object, ...)

## S3 method for class 'renewal'
confint(object, parm, level = 0.95, type = c("asymptotic",
  "boot"), bootType = c("norm", "bca", "basic", "perc"), ...)

## S3 method for class 'renewal'
summary(object, ...)

## S3 method for class 'renewal'
print(x, digits = max(3, getOption("digits") - 3), ...)

## S3 method for class 'summary.renewal'
print(x, digits = max(3, getOption("digits") - 3),
  width = getOption("width"), ...)

## S3 method for class 'renewal'
model.matrix(object, ...)

## S3 method for class 'renewal'
logLik(object, ...)

## S3 method for class 'renewal'
nobs(object, ...)

## S3 method for class 'renewal'
extractAIC(fit, scale, k = 2, ...)

## S3 method for class 'renewal'
addBootSampleObject(object, ...)

## S3 method for class 'renewal'
df.residual(object, ...)

```

Arguments

object	an object from class "renewal".
...	further arguments for methods
type, parm, level, bootType, x, digits	see the corresponding generics and section Details.
width	numeric width length
fit, scale, k	same as in the generic.

Details

Objects from class "renewal" represent fitted count renewal models and are created by calls to "renewalCount()". There are methods for this class for many of the familiar functions for interacting with fitted models.

Examples

```
fn <- system.file("extdata", "McShane_Wei_results_boot.RDS", package = "Countr")
object <- readRDS(fn)
class(object) # "renewal"

coef(object)
vcov(object)

## Pearson residuals: rescaled by sd
head(residuals(object, "pearson"))
## response residuals: not rescaled
head(residuals(object, "response"))

head(fitted(object))

## loglik, nobs, AIC, BIC
c(loglik = as.numeric(logLik(object)), nobs = nobs(object),
  AIC = AIC(object), BIC = BIC(object))

asym <- se.coef(object, , "asymptotic")
boot <- se.coef(object, , "boot")
cbind(asym, boot)
## CI for coefficients
asym <- confint(object, type = "asymptotic")
## Commenting out for now, see the note in the code of confint.renewal():
## boot <- confint(object, type = "boot", bootType = "norm")
## list(asym = asym, boot = boot)
summary(object)
print(object)
## see renewal_methods
## see renewal_methods
```

residuals_plot

Method to visualise the residuals

Description

A method to visualise the residuals

Usage

```
residuals_plot(object, type, ...)
```

Arguments

object	object returned by one of the count-modeling functions
type	character type of residuals to be used.
...	further arguments for methods.

se.coef

*Extract Standard Errors of Model Coefficients***Description**

Extract standard errors of model coefficients from objects returned by count-modeling functions.

Usage

```
se.coef(object, parm, type, ...)

## S3 method for class 'renewal'
se.coef(object, parm, type = c("asymptotic", "boot"), ...)
```

Arguments

object	object returned by one of the count-modeling functions
parm	parameter's name or index
type	type of standard error: asymptotic normal standard errors ("asymptotic") or bootstrap ("boot").
...	further arguments for methods.

Details

The method for class "renewal" extracts standard errors of model coefficients from objects returned by renewal. When bootstrap standard error are requested, the function checks for the bootstrap sample in object. If it is not found, the bootstrap sample is created and a warning is issued. Users can choose between asymptotic normal standard errors (asymptotic) or bootstrap (boot).

Value

a named numeric vector

Examples

```
## see examples for renewal_methods
```

 surv

Wrapper to built in survival functions

Description

Wrapper to built in survival functions

Usage

```
surv(t, distPars, dist)
```

Arguments

t	double, time point where the survival is to be evaluated at.
distPars	Rcpp::List with distribution specific slots, see details.
dist	character name of the built-in distribution, see details.

Details

The function wraps all builtin-survival distributions. User can choose between the weibull, gamma, gengamma (generalized gamma) and burr (Burr type XII distribution). It is the user responsibility to pass the appropriate list of parameters as follows:

weibull scale (the scale) and shape (the shape) parameters.

burr scale (the scale) and shape1 (the shape1) and shape2 (the shape2) parameters.

gamma scale (the scale) and shape (the shape) parameter.

gengamma mu (location), sigma (scale) and Q (shape) parameters.

Value

a double giving the value of the survival function at time point t at the parameters' values.

Examples

```
tt <- 2.5
## weibull

distP <- list(scale = 1.2, shape = 1.16)
alpha <- exp(-log(distP[["scale"]]) / distP[["shape"]])
pweibull(q = tt, scale = alpha, shape = distP[["shape"]],
         lower.tail = FALSE)
surv(tt, distP, "weibull") ## (almost) same

## gamma
distP <- list(shape = 0.5, rate = 1.0 / 0.7)
pgamma(q = tt, rate = distP[["rate"]], shape = distP[["shape"]],
       lower.tail = FALSE)
```

```
surv(tt, distP, "gamma") ## (almost) same

## generalized gamma
distP <- list(mu = 0.5, sigma = 0.7, Q = 0.7)
flexsurv::pgengamma(q = tt, mu = distP[["mu"]],
                    sigma = distP[["sigma"]],
                    Q = distP[["Q"]],
                    lower.tail = FALSE)
surv(tt, distP, "gengamma") ## (almost) same
```

Index

*Topic **datasets**

- fertility, [15](#)
 - football, [16](#)
- addBootSampleObject, [2](#)
addBootSampleObject.renewal
(renewal_methods), [24](#)
- character, [18](#)
chiSq_gof, [3](#), [5](#), [6](#)
chiSq_pearson, [4](#), [4](#), [6](#)
coef.renewal (renewal_methods), [24](#)
compareToGLM, [5](#)
confint.renewal (renewal_methods), [24](#)
count_table, [6](#)
Countr, [6](#)
Countr-package (Countr), [6](#)
- dCount_conv_bi, [7](#)
dCount_conv_loglik_bi, [9](#)
dCount_conv_loglik_user
(dCount_conv_loglik_bi), [9](#)
dCount_conv_user (dCount_conv_bi), [7](#)
df.residual.renewal (renewal_methods),
[24](#)
dmodifiedCount_bi, [10](#)
dmodifiedCount_user
(dmodifiedCount_bi), [10](#)
dWeibullCount, [12](#)
dWeibullCount_loglik (dWeibullCount), [12](#)
dWeibullgammaCount_mat_Covariates, [13](#)
- evCount_conv_bi, [14](#)
evCount_conv_user (evCount_conv_bi), [14](#)
evWeibullCount (dWeibullCount), [12](#)
extractAIC.renewal (renewal_methods), [24](#)
- fertility, [15](#)
fitted.renewal (renewal_methods), [24](#)
football, [16](#)
frequency_plot, [17](#)
getParNames, [17](#)
logLik.renewal (renewal_methods), [24](#)
model.matrix.renewal (renewal_methods),
[24](#)
nobs.renewal (renewal_methods), [24](#)
predict.renewal, [18](#)
print.renewal (renewal_methods), [24](#)
print.summary.renewal
(renewal_methods), [24](#)
renewal, [19](#)
renewal_methods, [3](#), [24](#)
renewalCoef, [19](#), [20](#)
renewalCoefList, [20](#), [20](#)
renewalCount, [6](#), [21](#)
renewalNames, [24](#)
residuals.renewal (renewal_methods), [24](#)
residuals_plot, [26](#)
residuals_plot.renewal
(renewal_methods), [24](#)
se.coef, [27](#)
summary.renewal (renewal_methods), [24](#)
surv, [28](#)
vcov.renewal (renewal_methods), [24](#)