

# Package ‘tuber’

November 19, 2017

**Title** Client for the YouTube API

**Version** 0.9.2

**Maintainer** Gaurav Sood <gsood07@gmail.com>

**Description** Get comments posted on YouTube videos, information on how many times a video has been liked, search for videos with particular content, and much more. You can also scrape captions from a few videos. To learn more about the YouTube API, see <<https://developers.google.com/youtube/v3/>>.

**URL** <http://github.com/soodoku/tuber>

**BugReports** <http://github.com/soodoku/tuber/issues>

**Depends** R (>= 3.4.1)

**License** MIT + file LICENSE

**LazyData** true

**Imports** httr, plyr

**VignetteBuilder** knitr

**Suggests** knitr (>= 1.11), testthat, rmarkdown, xml2, lintr

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** Gaurav Sood [aut, cre]

**Repository** CRAN

**Date/Publication** 2017-11-19 22:35:16 UTC

## R topics documented:

delete_captions . . . . .	2
delete_channel_sections . . . . .	3
delete_comments . . . . .	4
delete_playlists . . . . .	4
delete_playlist_items . . . . .	5
delete_videos . . . . .	6
get_captions . . . . .	6

get_channel_stats . . . . .	7
get_comments . . . . .	8
get_comment_threads . . . . .	9
get_playlists . . . . .	10
get_playlist_items . . . . .	11
get_related_videos . . . . .	12
get_stats . . . . .	13
get_subscriptions . . . . .	14
get_video_details . . . . .	15
list_abuse_report_reasons . . . . .	16
list_caption_tracks . . . . .	17
list_channel_activities . . . . .	18
list_channel_resources . . . . .	19
list_channel_sections . . . . .	20
list_channel_videos . . . . .	21
list_guidecats . . . . .	22
list_langs . . . . .	23
list_regions . . . . .	23
list_videocats . . . . .	24
list_videos . . . . .	25
tuber . . . . .	26
tuber_check . . . . .	26
tuber_DELETE . . . . .	27
tuber_GET . . . . .	27
tuber_POST . . . . .	28
yt_check_token . . . . .	28
yt_oauth . . . . .	29
yt_search . . . . .	30
yt_topic_search . . . . .	31

**Index** **33**

---

delete_captions	<i>Delete a Particular Caption Track</i>
-----------------	--

---

**Description**

Delete a Particular Caption Track

**Usage**

```
delete_captions(id = NULL, ...)
```

**Arguments**

id	String. Required. id of the caption track that is being retrieved
...	Additional arguments passed to <a href="#">tuber_DELETE</a> .

## References

<https://developers.google.com/youtube/v3/docs/captions/delete>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_captions(id = "y3E1XcEME3lSISz6izkWVT5GvxjPu8pA")  
  
## End(Not run)
```

---

delete\_channel\_sections  
*Delete Channel Sections*

---

## Description

Delete a Channel Section

## Usage

```
delete_channel_sections(id = NULL, ...)
```

## Arguments

id	Required. ID of the channel section.
...	Additional arguments passed to <code>tuber_DELETE</code> .

## References

<https://developers.google.com/youtube/v3/docs/channelSections/delete>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_channel_sections(c(channel_id = "UCRw8bIz2wMLmfgAgWm903cA"))  
  
## End(Not run)
```

---

delete\_comments      *Delete a Particular Comment*

---

### Description

Delete a Particular Comment

### Usage

```
delete_comments(id = NULL, ...)
```

### Arguments

id	String. Required. id of the comment being retrieved
...	Additional arguments passed to <code>tuber_DELETE</code> .

### References

<https://developers.google.com/youtube/v3/docs/comments/delete>

### Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_comments(id = "y3E1XcEME3lSISz6izkWWT5GvxjPu8pA")  
  
## End(Not run)
```

---

delete\_playlists      *Delete a Playlist*

---

### Description

Delete a Playlist

### Usage

```
delete_playlists(id = NULL, ...)
```

### Arguments

id	String. Required. id of the playlist that is to be deleted
...	Additional arguments passed to <code>tuber_DELETE</code> .

## References

<https://developers.google.com/youtube/v3/docs/playlists/delete>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_playlists(id = "y3E1XcEME3lSISz6izkWVT5GvxjPu8pA")  
  
## End(Not run)
```

---

delete\_playlist\_items *Delete a Playlist Item*

---

## Description

Delete a Playlist Item

## Usage

```
delete_playlist_items(id = NULL, ...)
```

## Arguments

id	String. Required. id of the playlist item that is to be deleted
...	Additional arguments passed to <code>tuber_DELETE</code> .

## References

<https://developers.google.com/youtube/v3/docs/playlistItems/delete>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_playlist_items(id = "y3E1XcEME3lSISz6izkWVT5GvxjPu8pA")  
  
## End(Not run)
```

---

`delete_videos`*Delete a Video*

---

**Description**

Delete a Video

**Usage**

```
delete_videos(id = NULL, ...)
```

**Arguments**

<code>id</code>	String. Required. id of the video that is to be deleted
<code>...</code>	Additional arguments passed to <code>tuber_DELETE</code> .

**References**

<https://developers.google.com/youtube/v3/docs/playlistItems/delete>

**Examples**

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
delete_videos(id = "y3E1XcEME3lSISz6izkWVT5GvxjPu8pA")  
  
## End(Not run)
```

---

`get_captions`*Get Particular Caption Track*

---

**Description**

For getting captions from the v3 API, you must specify the id resource. Check [list\\_caption\\_tracks](#) for more information.

**Usage**

```
get_captions(id = NULL, lang = "en", format = "sbv", ...)
```

**Arguments**

id	String. Required. id of the caption track that is being retrieved
lang	Optional. Default is en.
format	Optional. Default is sbv.
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

String.

**References**

<https://developers.google.com/youtube/v3/docs/captions/download>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_captions(id = "y3E1XcEME3lSISz6izkWVT5GvxjPu8pA")

## End(Not run)
```

---

get_channel_stats	<i>Get statistics of a Channel</i>
-------------------	------------------------------------

---

**Description**

Get statistics of a Channel

**Usage**

```
get_channel_stats(channel_id = NULL, ...)
```

**Arguments**

channel_id	Character. Id of the channel
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

nested named list with top element names: kind, etag, id, snippet (list of details of the channel including title, description, etc.)  
If the channel\_id is mistyped or there is no information, an empty list is returned

## References

<https://developers.google.com/youtube/v3/docs/channels/list>

## Examples

```
## Not run:

# Set API token via yt_oauth() first

get_channel_stats(channel_id="UCMtFAi84ehTSYSE9XoHefig")
get_channel_stats(channel_id="UCMtFAi84ehTSYSE9Xo") # Incorrect channel ID

## End(Not run)
```

---

get\_comments

*Get Comments*

---

## Description

Get Comments

## Usage

```
get_comments(filter = NULL, part = "snippet", max_results = 100,
             text_format = "html", page_token = NULL, simplify = TRUE, ...)
```

## Arguments

filter	string; Required. named vector of length 1 potential names of the entry in the vector: comment_id: comment ID. parent_id: parent ID.
part	Comment resource requested. Required. Comma separated list of one or more of the following: id, snippet. e.g., "id, snippet", "id", etc. Default: snippet.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 20 and 100. Default is 100.
text_format	Data Type: Character. Default is "html". Only takes "html" or "plainText". Optional.
page_token	Specific page in the result set that should be returned. Optional.
simplify	Data Type: Boolean. Default is TRUE. If TRUE, the function returns a data frame. Else a list with all the information returned.
...	Additional arguments passed to <code>tuber_GET</code> .



**Value**

Nested named list. The entry items is a list of comments along with meta information. Within each of the items is an item snippet which has an item topLevelComment\$snippet\$textDisplay that contains the actual comment.

When filter is comment\_id, and simplify is TRUE, and there is a correct comment id, it returns a data.frame with the following cols: id, authorDisplayName, authorProfileImageUrl, authorChannelUrl, value, publishedAt, updatedAt

**References**

<https://developers.google.com/youtube/v3/docs/comments/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_comments(filter = c(comment_id = "z13dh13j5rr0wbmq04cifrhtuypw14hsk"))
get_comments(filter = c(parent_id = "z13ds5yxjq3zzptyx04chlkbx2yh3ezxtc0k"))
get_comments(filter =
c(comment_id = "z13dh13j5rr0wbmq04cifrhtuypw14hsk,
      z13dh13j5rr0wbmq04cifrhtuypw14hsk"))

## End(Not run)
```

---

get_comment_threads	<i>Get Comments Threads</i>
---------------------	-----------------------------

---

**Description**

Get Comments Threads

**Usage**

```
get_comment_threads(filter = NULL, part = "snippet", text_format = "html",
  simplify = TRUE, max_results = 100, page_token = NULL, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: video_id: video ID. channel_id: channel ID. thread_id: comma-separated list of comment thread IDs threads_related_to_channel: channel ID.
part	Comment resource requested. Required. Comma separated list of one or more of the following: id, snippet. e.g., "id, snippet", "id", etc. Default: snippet.

text_format	Data Type: Character. Default is "html". Only takes "html" or "plainText". Optional.
simplify	Data Type: Boolean. Default is TRUE. If TRUE, the function returns a data frame. Else a list with all the information returned.
max_results	Maximum number of items that should be returned. Integer. Optional. Default is 100. If the value is greater than 100 then the function fetches all the results. The outcome is a simplified data.frame.
page_token	Specific page in the result set that should be returned. Optional.
...	Additional arguments passed to <code>tuber_GET</code> .

### Value

Nested named list. The entry `items` is a list of comments along with meta information. Within each of the `items` is an `item snippet` which has an `item topLevelComment$snippet$textDisplay` that contains the actual comment.

If `simplify` is TRUE, a `data.frame` with the following columns: `authorDisplayName`, `authorProfileImageUrl`, `authorCh`

### References

<https://developers.google.com/youtube/v3/docs/commentThreads/list>

### Examples

```
## Not run:

# Set API token via yt_oauth() first

get_comment_threads(filter = c(video_id = "N708P-A45D0"))
get_comment_threads(filter = c(video_id = "N708P-A45D0"), max_results = 101)

## End(Not run)
```

---

get\_playlists

*Get Playlists*

---

### Description

Get Playlists

### Usage

```
get_playlists(filter = NULL, part = "snippet", max_results = 50,
             hl = NULL, page_token = NULL, simplify = TRUE, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: channel_id: ID of the channel playlist_id: YouTube playlist ID.
part	Required. One of the following: contentDetails, id, localizations, player, snippet, status. Default: contentDetails.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
page_token	specific page in the result set that should be returned, optional
simplify	Data Type: Boolean. Default is TRUE. If TRUE and if part requested is contentDetails, the function returns a data.frame. Else a list with all the information returned.
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

playlists When simplify is TRUE, a data.frame with 4 columns is returned: kind, etag, id, contentDetails.itemCount

**References**

<https://developers.google.com/youtube/v3/docs/playlists/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_playlists(filter=c(channel_id="UCMtFAi84ehTSYSE9XoHefig"))
get_playlists(filter=c(channel_id="UCMtFAi84ehTSYSE9X")) # incorrect Channel ID

## End(Not run)
```

---

get\_playlist\_items      *Get Playlist Items*

---

**Description**

Get Playlist Items

**Usage**

```
get_playlist_items(filter = NULL, part = "contentDetails",
  max_results = 50, video_id = NULL, page_token = NULL, simplify = TRUE,
  ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: item_id: comma-separated list of one or more unique playlist item IDs. playlist_id: YouTube playlist ID.
part	Required. Comma separated string including one or more of the following: contentDetails, id, snippet, status. Default: contentDetails.
max_results	Maximum number of items that should be returned. Integer. Optional. Default is 50. If over 50, all the results are returned.
video_id	Optional. request should return only the playlist items that contain the specified video.
page_token	specific page in the result set that should be returned, optional
simplify	returns a data.frame rather than a list.
...	Additional arguments passed to <code>tuber_GET</code> .

**Value**

playlist items

**References**

<https://developers.google.com/youtube/v3/docs/playlists/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_playlist_items(filter =
  c(playlist_id = "PLrEnWoR732-CN09YykVof2lxdI3ML0Zda"))
get_playlist_items(filter =
  c(playlist_id = "PL0f01XVeVW9QM03GoESky4yDgQfK2SsXN"),
  max_results = 51)

## End(Not run)
```

---

get\_related\_videos      *Get Related Videos*

---

**Description**

Takes a video id and returns related videos

**Usage**

```
get_related_videos(video_id = NULL, max_results = 50,
  safe_search = "none", ...)
```

**Arguments**

video_id	Character. Required. No default.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
safe_search	Character. Optional. Takes one of three values: 'moderate', 'none' (default) or 'strict'
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

data.frame with 16 columns: video\_id, publishedAt, channelId, title, description, thumbnails.default.url

**References**

<https://developers.google.com/youtube/v3/docs/search/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_related_videos(video_id = "yJXTXN4xrI8")

## End(Not run)
```

---

get_stats	<i>Get statistics of a Video</i>
-----------	----------------------------------

---

**Description**

Get statistics of a Video

**Usage**

```
get_stats(video_id = NULL, ...)
```

**Arguments**

video_id	Character. Id of the video. Required.
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

list with 6 elements: id, viewCount, likeCount, dislikeCount, favoriteCount, commentCount

**References**

<https://developers.google.com/youtube/v3/docs/videos/list#parameters>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_stats(video_id="N708P-A45D0")

## End(Not run)
```

---

get_subscriptions	<i>Get Subscriptions</i>
-------------------	--------------------------

---

**Description**

Get Subscriptions

**Usage**

```
get_subscriptions(filter = NULL, part = "contentDetails",
  max_results = 50, for_channel_id = NULL, order = NULL,
  page_token = NULL, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: channel_id: ID of the channel. Required. No default. subscription_id: YouTube subscription ID
part	Part of the resource requested. Required. Character. A comma separated list of one or more of the following: contentDetails, id, snippet, subscriberSnippet. e.g. "id, snippet", "id", etc. Default: contentDetails.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
for_channel_id	Optional. String. A comma-separated list of channel IDs. Limits response to subscriptions matching those channels.
order	method that will be used to sort resources in the API response. Takes one of the following: alphabetical, relevance, unread
page_token	Specific page in the result set that should be returned. Optional. String.
...	Additional arguments passed to <code>tuber_GET</code> .

**Value**

named list of subscriptions

## References

<https://developers.google.com/youtube/v3/docs/subscriptions/list>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
get_subscriptions(filter = c(channel_id = "UChTJTbr5kf3hYazJZ0-euHg"))  
  
## End(Not run)
```

---

get_video_details	<i>Get Details of a Video or Videos</i>
-------------------	---

---

## Description

Get details such as when the video was published, the title, description, thumbnails, category etc.

## Usage

```
get_video_details(video_id = NULL, part = "snippet", ...)
```

## Arguments

video_id	Comma separated list of IDs of the videos for which details are requested. Required.
part	Comma-separated list of video resource properties requested. Options include: contentDetails, fileDetails, id, liveStreamingDetails, localizations, player, process
...	Additional arguments passed to <a href="#">tuber_GET</a> .

## Value

list. If part is snippet, the list will have the following elements: id (video id that was passed), publishedAt, channelId, title, description, thumbnails, channelTitle, categoryId, liveBroadcastContent

## References

<https://developers.google.com/youtube/v3/docs/videos/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

get_video_details(video_id = "yJXTXN4xrI8")
get_video_details(video_id = "yJXTXN4xrI8", part = "contentDetails")

## End(Not run)
```

---

```
list_abuse_report_reasons
```

*List reasons that can be used to report abusive videos*

---

**Description**

List reasons that can be used to report abusive videos

**Usage**

```
list_abuse_report_reasons(part = "id, snippet", hl = "en-US", ...)
```

**Arguments**

part	Caption resource requested. Required. Comma separated list of one or more of the following: id, snippet. e.g., "id, snippet", "id", etc. Default: snippet.
hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

If no results, empty data.frame returned If part requested = "id, snippet" or "snippet", data.frame with 4 columns: etag, id, label, secReasons If part requested = "id", data.frame with 2 columns: etag, id

**References**

<https://developers.google.com/youtube/v3/docs/videoAbuseReportReasons/list>



**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_abuse_report_reasons()
list_abuse_report_reasons(part="id")
list_abuse_report_reasons(part="snippet")

## End(Not run)
```

---

list\_caption\_tracks    *List Captions of a Video*

---

**Description**

List Captions of a Video

**Usage**

```
list_caption_tracks(part = "snippet", video_id = NULL, lang = "en",
  id = NULL, simplify = TRUE, ...)
```

**Arguments**

part	Caption resource requested. Required. Comma separated list of one or more of the following: id, snippet. e.g., "id, snippet", "id" Default: snippet.
video_id	ID of the video whose captions are requested. Required. No default.
lang	Language of the caption; required; default is english ("en")
id	comma-separated list of IDs that identify the caption resources that should be retrieved; optional; string
simplify	Boolean. Default is TRUE. When TRUE, and part is snippet, a data.frame is returned
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

list of caption tracks. When simplify is TRUE, a data.frame is returned with following columns: videoId, lastUpdated, trackKind, language, name, audioTrackType, isCC, isLarge, isEasyReader, isDraft, (caption id)

**References**

<https://developers.google.com/youtube/v3/docs/captions/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_caption_tracks(video_id = "yJTXN4xrI8")

## End(Not run)
```

---

```
list_channel_activities
      List Channel Activity
```

---

**Description**

Returns a list of channel events that match the request criteria.

**Usage**

```
list_channel_activities(filter = NULL, part = "snippet", max_results = 50,
  page_token = NULL, published_after = NULL, published_before = NULL,
  region_code = NULL, simplify = TRUE, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: channel_id: ID of the channel. Required. No default.
part	specify which part do you want. It can only be one of the three: contentDetails, id, snippet. Default is snippet.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
page_token	specific page in the result set that should be returned, optional
published_after	Character. Optional. RFC 339 Format. For instance, "1970-01-01T00:00:00Z"
published_before	Character. Optional. RFC 339 Format. For instance, "1970-01-01T00:00:00Z"
region_code	ISO 3166-1 alpha-2 country code, optional, see also <a href="#">list_regions</a>
simplify	Data Type: Boolean. Default is TRUE. If TRUE and if part requested is contentDetails, the function returns a data.frame. Else a list with all the information returned.
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

named list If simplify is TRUE, a data.frame is returned with 18 columns: publishedAt, channelId, title, description

**References**

<https://developers.google.com/youtube/v3/docs/activities/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_channel_activities(filter = c(channel_id = "UCRw8bIz2wMLmfgAgWm903cA"))
list_channel_activities(filter = c(channel_id = "UCRw8bIz2wMLmfgAgWm903cA", regionCode="US"))
list_channel_activities(filter = c(channel_id = "UCMtFAi84ehTSYSE9XoHefig"),
                        published_before = "2016-02-10T00:00:00Z",
                        published_after = "2016-01-01T00:00:00Z")

## End(Not run)
```

---

list\_channel\_resources

*Returns List of Requested Channel Resources*

---

**Description**

Returns List of Requested Channel Resources

**Usage**

```
list_channel_resources(filter = NULL, part = "contentDetails",
                      max_results = 50, page_token = NULL, hl = "en-US", ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: category_id: YouTube guide category that returns channels associated with that category username: YouTube username that returns channel associated with that username. channel_id: a comma-separated list of the YouTube channel ID(s) for the resource(s) that are being retrieved
part	a comma separated list of channel resource properties that response will include string. Required. One of the following: auditDetails, brandingSettings, contentDetails, content
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
page_token	specific page in the result set that should be returned, optional
hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

list

**References**<https://developers.google.com/youtube/v3/docs/channels/list>**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_channel_resources(filter = c(channel_id = "UCT5Cx1l4IS3wHkJXNyuj4TA"))
list_channel_resources(filter = c(username = "latenight"), part = "id, contentDetails")
list_channel_resources(filter = c(username = "latenight"), part = "id, contentDetails",
max_results = 10)

## End(Not run)
```

---

list\_channel\_sections *List Channel Sections*

---

**Description**

Returns list of channel sections that channel id belongs to.

**Usage**

```
list_channel_sections(filter = NULL, part = "snippet", hl = NULL, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: channel_id: Channel ID id: Section ID
part	specify which part do you want. It can only be one of the following: contentDetails, id, localization. Default is snippet.
hl	language that will be used for text values, optional, default is en-US. See also <a href="#">list_langs</a>
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

captions for the video from one of the first track

## References

<https://developers.google.com/youtube/v3/docs/activities/list>

## Examples

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
list_channel_sections(c(channel_id = "UCRw8bIz2wMLmfgAgWm903cA"))  
  
## End(Not run)
```

---

list\_channel\_videos *Returns List of Requested Channel Videos*

---

## Description

Iterate through the `max_results` number of playlists in channel and get the videos for each of the playlists.

## Usage

```
list_channel_videos(channel_id = NULL, max_results = 50,  
  page_token = NULL, hl = "en-US", ...)
```

## Arguments

<code>channel_id</code>	String. ID of the channel. Required.
<code>max_results</code>	Maximum number of videos returned. Integer. Default is 50. If the number is over 50, all the videos will be returned.
<code>page_token</code>	Specific page in the result set that should be returned. Optional.
<code>hl</code>	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a>
<code>...</code>	Additional arguments passed to <code>tuber_GET</code> .

## Value

list of `data.frame` with each list corresponding to a different playlist

## References

<https://developers.google.com/youtube/v3/docs/channels/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_channel_videos(channel_id = "UCX0KEdfOFxsHO_-Su3K8SHg")
list_channel_videos(channel_id = "UCX0KEdfOFxsHO_-Su3K8SHg", max_results = 10)

## End(Not run)
```

---

list_guidecats	<i>Get list of categories that can be associated with YouTube channels</i>
----------------	--

---

**Description**

Get list of categories that can be associated with YouTube channels

**Usage**

```
list_guidecats(filter = NULL, hl = NULL, ...)
```

**Arguments**

filter	string; Required. named vector of length 1 potential names of the entry in the vector: region_code: Character. Required. Has to be a ISO 3166-1 alpha-2 code (see <a href="https://www.iso.org/obp/ui/#search">https://www.iso.org/obp/ui/#search</a> ) category_id: YouTube channel category ID
hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

data.frame with 5 columns: region\_code, channelId, title, etag, id

**References**

<https://developers.google.com/youtube/v3/docs/guideCategories/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_guidecats(c(region_code = "JP"))

## End(Not run)
```

---

list_langs	<i>List Languages That Youtube Currently Supports</i>
------------	---

---

**Description**

List Languages That Youtube Currently Supports

**Usage**

```
list_langs(hl = NULL, ...)
```

**Arguments**

hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

data.frame with 3 columns: hl (two letter abbreviation), name (of the language), etag

**References**

<https://developers.google.com/youtube/v3/docs/i18nLanguages/list>

**Examples**

```
## Not run:  
  
# Set API token via yt_oauth() first  
  
list_langs()  
  
## End(Not run)
```

---

list_regions	<i>List Content Regions That Youtube Currently Supports</i>
--------------	---

---

**Description**

List Content Regions That Youtube Currently Supports

**Usage**

```
list_regions(hl = NULL, ...)
```

**Arguments**

hl Language used for text values. Optional. Default is en-US. For other allowed language codes, see [list\\_langs](#).

... Additional arguments passed to [tuber\\_GET](#).

**Value**

data.frame with 3 columns: gl (two letter abbreviation), name (of the region), etag

**References**

<https://developers.google.com/youtube/v3/docs/i18nRegions/list>

**Examples**

```
## Not run:
# Set API token via yt_oauth() first
list_regions()
## End(Not run)
```

---

list_videocats	<i>List of Categories That Can be Associated with Videos</i>
----------------	--

---

**Description**

List of Categories That Can be Associated with Videos

**Usage**

```
list_videocats(filter = NULL, ...)
```

**Arguments**

filter string; Required. named vector of length 1 potential names of the entry in the vector: region\_code: Character. Required. Has to be a ISO 3166-1 alpha-2 code (see <https://www.iso.org/obp/ui/#search>) category\_id: video category ID

... Additional arguments passed to [tuber\\_GET](#).

**Value**

data.frame with 6 columns: region\_code, channelId, title, assignable, etag, id



## References

<https://developers.google.com/youtube/v3/docs/videoCategories/list>

## Examples

```
## Not run:

# Set API token via yt_oauth() first

list_videocats(c(region_code = "JP"))
list_videocats() # Will throw an error asking for a valid filter with valid region_code

## End(Not run)
```

---

list_videos	<i>List (Most Popular) Videos</i>
-------------	-----------------------------------

---

## Description

List (Most Popular) Videos

## Usage

```
list_videos(part = "contentDetails", max_results = 50, page_token = NULL,
            hl = NULL, region_code = NULL, video_category_id = NULL, ...)
```

## Arguments

part	Required. Comma separated string including one or more of the following: contentDetails, fileDetails, id, liveStreamingDetails, localizations, player, processingDetails. Default: contentDetails.
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50.
page_token	specific page in the result set that should be returned, optional
hl	Language used for text values. Optional. Default is en-US. For other allowed language codes, see <a href="#">list_langs</a> .
region_code	Character. Required. Has to be a ISO 3166-1 alpha-2 code (see <a href="https://www.iso.org/obp/ui/#search">https://www.iso.org/obp/ui/#search</a> ).
video_category_id	the video category for which the chart should be retrieved. See also <a href="#">list_videocats</a> .
...	Additional arguments passed to <a href="#">tuber_GET</a> .

## Value

data.frame with 5 columns: channelId, title, assignable, etag, id

**References**

<https://developers.google.com/youtube/v3/docs/search/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

list_videos()

## End(Not run)
```

---

tuber	<i>tuber provides access to the YouTube API V3.</i>
-------	---

---

**Description**

**tuber** provides access to the YouTube API V3.

---

tuber_check	<i>Request Response Verification</i>
-------------	--------------------------------------

---

**Description**

Request Response Verification

**Usage**

```
tuber_check(req)
```

**Arguments**

req	request
-----	---------

**Value**

in case of failure, a message

---

tuber_DELETE	<i>DELETE</i>
--------------	---------------

---

**Description**

DELETE

**Usage**

tuber\_DELETE(path, query, ...)

**Arguments**

path	path to specific API request URL
query	query list
...	Additional arguments passed to <a href="#">GET</a> .

**Value**

list

---

tuber_GET	<i>Base POST AND GET functions. Not exported.</i>
-----------	---

---

**Description**

GET

**Usage**

tuber\_GET(path, query, ...)

**Arguments**

path	path to specific API request URL
query	query list
...	Additional arguments passed to <a href="#">GET</a> .

**Value**

list

---

tuber_POST	<i>POST</i>
------------	-------------

---

**Description**

POST

**Usage**

tuber\_POST(path, query, body = "", ...)

**Arguments**

path	path to specific API request URL
query	query list
body	passing image through body
...	Additional arguments passed to <a href="#">GET</a> .

**Value**

list

---

yt_check_token	<i>Check if authentication token is in options</i>
----------------	--

---

**Description**

Check if authentication token is in options

**Usage**

yt\_check\_token()

yt\_oauth

*Set up Authorization***Description**

The function looks for `.httr-oauth` in the working directory. If it doesn't find it, it expects an application ID and a secret. If you want to remove the existing `.httr-oauth`, set `remove_old_oauth` to `TRUE`. By default, it is set to `FALSE`. The function launches a browser to allow you to authorize the application

**Usage**

```
yt_oauth(app_id = NULL, app_secret = NULL, scope = "ssl",
         token = ".httr-oauth", ...)
```

**Arguments**

<code>app_id</code>	client id; required; no default
<code>app_secret</code>	client secret; required; no default
<code>scope</code>	Character. <code>ssl</code> , <code>basic</code> , <code>own_account_readonly</code> , <code>upload_and_manage_own_videos</code> and <code>partner_audit</code> . Required. <code>ssl</code> and <code>basic</code> are basically interchangeable. Default is <code>ssl</code> .
<code>token</code>	path to file containing the token. If a path is given, the function will first try to read from it. Default is <code>.httr-oauth</code> in the local directory. So if there is such a file, the function will first try to read from it.
<code>...</code>	Additional arguments passed to <code>oauth2.0_token</code>

**Value**

sets the `google_token` option and also saves `.httr_oauth` in the working directory (find out the working directory via `getwd()`)

**References**

<https://developers.google.com/youtube/v3/docs/>

<https://developers.google.com/youtube/v3/guides/auth/client-side-web-apps> for different scopes

**Examples**

```
## Not run:
yt_oauth("998136489867-5t3tq1g7hbovoj46dreqd6k5kd35ctjn.apps.googleusercontent.com",
        "Mb0St6cQhhFkwETXKur-L9rN")

## End(Not run)
```

yt\_search

*Search YouTube***Description**

Search for videos, channels and playlists. (By default, the function searches for videos.)

**Usage**

```
yt_search(term = NULL, max_results = 50, channel_id = NULL,
  channel_type = NULL, type = "video", event_type = NULL,
  location = NULL, location_radius = NULL, published_after = NULL,
  published_before = NULL, video_definition = "any",
  video_caption = "any", video_license = "any", video_syndicated = "any",
  video_type = "any", simplify = TRUE, get_all = TRUE,
  page_token = NULL, ...)
```

**Arguments**

term	Character. Search term; required; no default
max_results	Maximum number of items that should be returned. Integer. Optional. Can be between 0 and 50. Default is 50. Search results are constrained to a maximum of 500 videos if type is video and we have a value of channel_id.
channel_id	Character. Only return search results from this channel; Optional.
channel_type	Character. Optional. Takes one of two values: 'any', 'show'. Default is 'any'
type	Character. Optional. Takes one of three values: 'video', 'channel', 'playlist'. Default is 'video'.
event_type	Character. Optional. Takes one of three values: 'completed', 'live', 'upcoming'
location	Character. Optional. Latitude and Longitude within parentheses, e.g. "(37.42307,-122.08427)"
location_radius	Character. Optional. e.g. "1500m", "5km", "10000ft", "0.75mi"
published_after	Character. Optional. RFC 339 Format. For instance, "1970-01-01T00:00:00Z"
published_before	Character. Optional. RFC 339 Format. For instance, "1970-01-01T00:00:00Z"
video_definition	Character. Optional. Takes one of three values: 'any' (return all videos; Default), 'high', 'standard'
video_caption	Character. Optional. Takes one of three values: 'any' (return all videos; Default), 'closedCaption', 'none'. Type must be set to video.

video_license	Character. Optional. Takes one of three values: 'any' (return all videos; Default), 'creativeCommon' (return videos with Creative Commons license), 'youtube' (return videos with standard YouTube license).
video_syndicated	Character. Optional. Takes one of two values: 'any' (return all videos; Default), 'true' (return only syndicated videos)
video_type	Character. Optional. Takes one of three values: 'any' (return all videos; Default), 'episode' (return episode of shows), 'movie' (return movies)
simplify	Boolean. Return a data.frame if TRUE. Default is TRUE. If TRUE, it returns a list that carries additional information.
get_all	get all results, iterating through all the results pages. Default is TRUE. Result is a data.frame. Optional.
page_token	specific page in the result set that should be returned, optional
...	Additional arguments passed to <code>tuber_GET</code> .

**Value**

data.frame with 16 elements: video\_id, publishedAt, channelId, title, description, thumbnails.default.url,

**References**

<https://developers.google.com/youtube/v3/docs/search/list>

**Examples**

```
## Not run:

# Set API token via yt_oauth() first

yt_search(term = "Barack Obama")
yt_search(term = "Barack Obama", published_after = "2016-10-01T00:00:00Z")
yt_search(term = "Barack Obama", published_before = "2016-09-01T00:00:00Z")
yt_search(term = "Barack Obama", published_before = "2016-03-01T00:00:00Z",
          published_after = "2016-02-01T00:00:00Z")
yt_search(term = "Barack Obama", published_before = "2016-02-10T00:00:00Z",
          published_after = "2016-01-01T00:00:00Z")

## End(Not run)
```

---

yt\_topic\_search

*Search YouTube by Topic It uses the Freebase list of topics*

---

**Description**

Search YouTube by Topic It uses the Freebase list of topics

**Usage**

```
yt_topic_search(topic = NULL, ...)
```

**Arguments**

topic	topic being searched for; required; no default
...	Additional arguments passed to <a href="#">tuber_GET</a> .

**Value**

a list

**Examples**

```
## Not run:  
  
# Set API token via yt_oauth() first  
yt_topic_search(topic = "Barack Obama")  
  
## End(Not run)
```



# Index

delete\_captions, 2  
delete\_channel\_sections, 3  
delete\_comments, 4  
delete\_playlist\_items, 5  
delete\_playlists, 4  
delete\_videos, 6

GET, 27, 28  
get\_captions, 6  
get\_channel\_stats, 7  
get\_comment\_threads, 9  
get\_comments, 8  
get\_playlist\_items, 11  
get\_playlists, 10  
get\_related\_videos, 12  
get\_stats, 13  
get\_subscriptions, 14  
get\_video\_details, 15

list\_abuse\_report\_reasons, 16  
list\_caption\_tracks, 6, 17  
list\_channel\_activities, 18  
list\_channel\_resources, 19  
list\_channel\_sections, 20  
list\_channel\_videos, 21  
list\_guidecats, 22  
list\_langs, 11, 16, 19–23, 23, 24, 25  
list\_regions, 18, 23  
list\_videocats, 24, 25  
list\_videos, 25

oauth2.0\_token, 29

tuber, 26  
tuber-package (tuber), 26  
tuber\_check, 26  
tuber\_DELETE, 2–6, 27  
tuber\_GET, 7, 8, 10–25, 27, 31, 32  
tuber\_POST, 28

yt\_check\_token, 28  
yt\_oauth, 29  
yt\_search, 30  
yt\_topic\_search, 31