

Package ‘betaper’

February 19, 2015

Type Package

Title Functions to incorporate taxonomic uncertainty on multivariate analyses of ecological data

Version 1.1-0

Date 2009-07-21

Author Luis Cayuela and Marcelino de la Cruz

Maintainer Luis Cayuela <lucayuela@ugr.es>

Depends vegan, ellipse

Description Permutational method to incorporate taxonomic uncertainty and some functions to assess its effects on parameters of some widely used multivariate methods in ecology

License GPL (>= 2)

LazyLoad yes

Repository CRAN

Date/Publication 2012-10-29 08:58:17

NeedsCompilation no

R topics documented:

adonis.pertables	2
Amazonia	3
cca.pertables	4
HCP	6
mantel.pertables	7
pertables	9
rda.pertables	10

Index	13
--------------	-----------

adonis.pertables	<i>Function to assess the effects of taxonomic uncertainty on permutational multivariate analysis of variance using distance matrices</i>
------------------	---

Description

This function assesses the effects of taxonomic uncertainty on the R2 coefficients and the p-values of a permutational multivariate analysis of variance using distance matrices.

Usage

```
adonis.pertables(formula = X ~ ., data, permutations = 5, method = "bray")
## S3 method for class 'adonis.pertables'
plot(x, ...)
```

Arguments

formula	A typical model formula such as 'Y ~ A + B*C', but where 'Y' is a pertables object (i.e. a list of simulated community data matrices obtained with pertables ; 'A', 'B', and 'C' may be factors or continuous variables.
data	The data frame from which 'A', 'B', and 'C' would be drawn.
permutations	Number of replicate permutations used for the hypothesis tests (F tests) for each simulated community data matrices obtained with pertables .
method	The name of any method used in 'vegdist' to calculate pairwise distances.
x	adonis.pertables object to plot.
...	Additional graphical parameters passed to plot.

Value

adonis.pertables returns an object of class `adonis.pertables`, basically a list with the following components:

raw	An object of class <code>adonis</code> , i.e. the results of applying mantel to the original biological data table without the unidentified species. This includes p-values for each explanatory variable showing the probability of obtaining the same F statistic under different scenarios of taxonomic uncertainty.
simulation	A list with the results of the simulation: F, i.e. a data.frame with all the simulated pseudo-F (columns) for each explanatory variable (rows); R2, i.e. a data.frame with all the simulated R2 coefficients (columns) for each explanatory variable (rows); pvalue, i.e. a data.frame with all the simulated p-values (columns) for each explanatory variable (rows); R2.quant, i.e. a data.frame with the summary of R2 by quantiles; p.quant, i.e. a data.frame with the summary of pvalue by quantiles.

The objects of class `adonis.pertables` have `print` and `plot` S3 methods for a simple access to results. See the examples.

Author(s)

Luis Cayuela and Marcelino de la Cruz

References

Cayuela, L., De la Cruz, M. and Ruokolainen, K. A method to incorporate the effect of taxonomic uncertainty on multivariate analyses of ecological data (*Ecography, submitted*)

See Also

pertables, [adonis](#)

Examples

```
## Not run:
require(vegan)

data(Amazonia)
data(soils)

# Define a new index that includes the terms used in the \code{Amazonia} dataset to define undetermined taxa at di
index.Amazon <- c(paste("sp.", rep(1:20), sep=""), "Indet.", "indet.")

#Generate a pertables object (i.e. a list of biological data tables simulated from taxonomic uncertainty)
Amazonia100 <- pertables(Amazonia, index=index.Amazon, nsim=100)

# Assess the effects of taxonomic uncertainty on a Mantel test of biological dissimilarity correlated to soil dis

Amazonia.adonis <- adonis.pertables(Amazonia100 ~ Ca + K + Mg + Na, data=soils)

Amazonia.adonis

plot(Amazonia.adonis)

## End(Not run)
```

Amazonia

Tree abundance and soil data in Western Amazonia

Description

The `Amazonia` data frame has tree counts in nine 0.16-hectare inventory plots in Western Amazonia. `soils` contains data on soil cations at each location.

Usage

```
data(Amazonia)
data(soils)
```

Format

Amazonia is a data frame with 1188 observations (species) and 12 columns (taxonomic description and sites). The three first columns refer to family, genus and specific species Latin names. Columns 4 to 12 have tree abundance data for nine inventory plots.

soils is a data frame with 9 observations (inventory plots) and 4 columns (variables). Soil variables (Ca, K, Mg, Na) are given in cmol/kg.

Details

Data from Western Amazonia includes tree inventories at nine lowland sites (approximately 100-150 m above sea level) near Iquitos, Peru. The sites were selected to represent regional variations in geology and were distributed along a soil nutrient gradient ranging from poor loamy soils to richer clayey soils. Each inventory consisted of 20 x 20 m plots (0.16 ha total area) distributed along 1.3-km transects. At each site, K. Ruokolainen and colleagues identified to species or morphospecies all woody, free-standing stems of > 2.5 cm dbh. The full inventories sampled 3980 individuals from 1188 species or morphospecies.

References

Higgins, M.A. & Ruokolainen, K. 2004. Rapid tropical forest inventory: a comparison of techniques based on inventory data from western Amazonia. *Conservation Biology* 18(3): 799-811.

Ruokolainen, K., Tuomisto, H., Macia, M.J., Higgins, M.A. & Yli-Halla, M. 2007. Are floristic and edaphic patterns in Amazonian rain forests congruent for trees, pteridophytes and Melastomataceae? *Journal of Tropical Ecology* 23: 13-25.

Examples

```
data(Amazonia)
data(soils)
```

cca.pertables	<i>Function to assess the effects of taxonomic uncertainty on [Partial] Constrained Correspondence Analysis</i>
---------------	---

Description

This function assesses the effects of taxonomic uncertainty on two widely used parameters of a [Partial] Constrained Correspondence Analysis, i.e. the 'percentage explained variance' (sometimes referred to as *R-squared*) and the *pseudo-F*.

Usage

```
cca.pertables(formula, data, ...)
## S3 method for class 'cca.pertables'
plot(x, pch = 18, ...)
```

Arguments

formula	Model formula, where the left hand side gives a pertables object (i.e. a list of simulated community data matrices obtained with pertables , right hand side gives the constraining variables, and conditioning variables can be given within a special function <code>Condition</code>).
data	Data frame containing the variables on the right hand side of the model formula.
x	<code>cca.pertables</code> object to plot.
pch	Plotting 'character', i.e., symbol to use in the CCA plot. See points for examples of use of this graphical argument.
...	Additional graphical parameters passed to plot.

Details

This function is a wrapper to submit a [pertables](#) object to `cca` function of the **vegan** package. See the documentation of `cca` for details about formula and `Condition` use.

Value

`cca.pertables` returns an object of class `cca.pertables`, basically a list with the following components:

raw	An object of class <code>classcca</code> . The results of applying <code>cca</code> to the original biological data table without the unidentified species.
simulation	A list with the results of the simulation: <code>results</code> , i.e. a <code>data.frame</code> with all the simulated R-squared and pseudo-F values; <code>cca.quant</code> , i.e. a <code>data.frame</code> with the summary of <code>results</code> by quantiles; <code>sites</code> i.e. a list with the scores of the sites of all the simulated data tables and <code>biplot</code> , i.e. a list with the scores of the environmental data in all the analyses

The objects of class `cca.pertables` have `print` and `plot` S3 methods for a simple access to results. See the examples.

Author(s)

Luis Cayuela and Marcelino de la Cruz

References

Cayuela, L., De la Cruz, M. and Ruokolainen, K. A method to incorporate the effect of taxonomic uncertainty on multivariate analyses of ecological data (*Ecography, submitted*)

See Also

[pertables](#), [cca](#)

Examples

```

## Not run:
require(vegan)

data(Amazonia)
data(soils)

# Define a new index that includes the terms used in the \code{Amazonia} dataset to define undetermined
# taxa at different taxonomic levels
index.Amazon <- c(paste("sp.", rep(1:20), sep=""), "Indet.", "indet.")

#Generate a pertables object (i.e. a list of biological data tables simulated from taxonomic uncertainty)
Amazonia100 <- pertables(Amazonia, index=index.Amazon, nsim=100)

# Assess the effects of taxonomic uncertainty on a CCA analysis of biological data explained by all the
# environmental variables of the soil data:

Amazonia.cca <- cca.pertables(Amazonia100 ~., data=soils)

Amazonia.cca

plot(Amazonia.cca)

## End(Not run)

```

HCP

Tree counts in tropical montane forest fragments

Description

HCP has tree abundance data from 16 forest fragments located in the Highlands of Chiapas, southern Mexico. HCP.coords contains the geographical UTM coordinates for the 16 forest fragments' centroids.

Usage

```

data(HCP)
data(HCP.coords)

```

Format

HCP is a data frame with 231 observations and 19 variables. The three first columns contain family, genus and specific species Latin names. Columns 4 to 19 have tree abundance data for the 16 forest fragments. HCP.coords is a data frame with two columns and 16 rows.

References

Cayuela, L., Golicher, D.J., Rey Benayas, J.M., Gonzalez-Espinosa, M. & Ramirez-Marcial, N. 2006. Fragmentation, disturbance and tree diversity conservation in tropical montane forests. *Journal of Applied Ecology* 43: 1172-1181.

Examples

```
data(HCP)
data(HCP.coords)
```

mantel.pertables	<i>Function to assess the effects of taxonomic uncertainty on Mantel tests</i>
------------------	--

Description

This function assesses the effects of taxonomic uncertainty on the coefficient of correlation and the p-values of a Mantel test.

Usage

```
mantel.pertables(pertab, env, dist.method = "bray", binary = FALSE, cor.method = "pearson", permutati
## S3 method for class 'mantel.pertables'
plot(x, xlab = "Environmental distance", ylab = "Sorensen's similarity index", pch = 19, ...)
```

Arguments

pertab	A pertables object (i.e. a list of simulated community data matrices obtained with pertables).
env	Data frame with the environmental variables.
dist.method	Method to compute the dissimilarity matrices from the biological and environmental data tables. One of the methods described in function vegdist of the package vegan .
binary	Value for the argument binary in the function vegdist of the package vegan .
cor.method	Correlation method, as accepted by cor : "pearson", "spearman" or "kendall".
permutations	Number of permutations in assessing significance.
x	mantel.pertables object to plot.
xlab	Label to name x-axis
ylab	Label to name y-axis
pch	Plotting 'character', i.e., symbol to use in the distance decay plot. See points for examples of use of this graphical argument.
...	Additional graphical parameters passed to plot.

Value

`mantel.pertables` returns an object of class `mantel.pertables`, basically a list with the following components:

<code>mantel</code>	A list with two components: <code>mantel.raw</code> , an object of class 'mantel', i.e. the results of applying <code>mantel</code> to the original biological data table without the unidentified species, and <code>ptax</code> , a p-value showing the probability of obtaining the same mantel statistic under different scenarios of taxonomic uncertainty.
<code>simulation</code>	A list with the results of the simulation: <code>results</code> , i.e. a <code>data.frame</code> with all the simulated mantel statistics and p-values; <code>mantel.quant</code> , i.e. a <code>data.frame</code> with the summary of results by quantiles; <code>vegdist</code> , i.e. a list with all the dissimilarity matrices employed.

The objects of class `mantel.pertables` have `print` and `plot` S3 methods for a simple access to results. See the examples.

Author(s)

Luis Cayuela and Marcelino de la Cruz

References

Cayuela, L., De la Cruz, M. and Ruokolainen, K. A method to incorporate the effect of taxonomic uncertainty on multivariate analyses of ecological data (*Ecography*, *submitted*)

See Also

`pertables`, `mantel`

Examples

```
## Not run:
require(vegan)

data(Amazonia)
data(soils)

# Define a new index that includes the terms used in the \code{Amazonia} dataset to define undetermined taxa at di
index.Amazon <- c(paste("sp.", rep(1:20), sep=""), "Indet.", "indet.")

#Generate a pertables object (i.e. a list of biological data tables simulated from taxonomic uncertainty)
Amazonia100 <- pertables(Amazonia, index=index.Amazon, nsim=100)

# Assess the effects of taxonomic uncertainty on a Mantel test of biological dissimilarity correlated to soil dis

Amazonia.mantel <- mantel.pertables(pertab=Amazonia100, env=soils, dist.method = "bray")

Amazonia.mantel

plot(Amazonia.mantel)
```



```
## End(Not run)
```

pertables	<i>Function to incorporate the effect of taxonomic uncertainty on multi-variate analyses of ecological data.</i>
-----------	--

Description

This function implements a permutational method to incorporate taxonomic uncertainty on multi-variate analyses typically used in the analysis of ecological data. The procedure is based on iterative randomizations that randomly re-assign non identified species in each site to any of the other species found in the remaining sites.

Usage

```
pertables(data, index = NULL, nsim = 100)
```

Arguments

data	Community data matrix. The three first columns are factors referring to the family, genus and species specific names. The remaining columns are numeric vectors indicating species abundances at each site.
index	List of additional parameters to determine the level at which species have been identified. Default values include 'Indet', 'indet', 'sp', 'sp1' to 'sp100', 'sp 1' to 'sp 100', ", and ' ' ' .
nsim	Number of simulations of species' identities, i.e., number of data tables to simulate.

Details

The procedure is implemented in two sequential steps:

Step 1. Morphospecies identified only to genus are randomly re-assigned with the same probability within the group of species and morphospecies that share the same genus, provided they are not found in the same sites. In the re-assignment of the species identity, the species considered can also receive its own identity. For instance, let's assume we have three floristic inventories. In site A we have *Eugenia sp1* and *E. nesiotica*. In site B we have *Eugenia nesiotica*, *E. principium* and *E. salamensis*. In site C we have *Eugenia sp2* and *E. salamensis*. *Eugenia sp1* can be thus re-identified with equal probability as *Eugenia sp2*, *E. principium*, *E. salamensis* or just maintain its own identity (*Eugenia sp1*). In the latter case, this means that we assume that *E. sp1* is a completely different species, although we do not know its true identity. On the contrary, we cannot re-identify *E. sp1* as *E. nesiotica* because they were found in the same site, so we are quite certain that *E. sp1* is different from *E. nesiotica*. The same is applied to species identified only to family and fully unidentified species. Note that when collating inventories from different researchers, we must rename all unidentified species. This is because two researchers can use the same label, e.g. *Eugenia sp1*, even though this name does not necessarily refer to the same species. For a verification of the

biological identity of *Eugenia sp1* one would need to cross-check the vouchers bearing the same name.

Step 2. Step 1 is iterated *nsim* times. As a result, *nsim* matrices are obtained, all of which contain the same number of sites but variable number of species depending on the resulting re-assignment of morphospecies, The process can be time-consuming if community data matrices are large.

Value

The function return a list of class pertables with the following components

taxunc	Summary of the number of species fully identified (0), identified to genus (1), identified to family (2), or fully undetermined (3).
pertables	A list with all the simulated data matrices.
raw	The raw data matrix, without the unidentified especies.

Author(s)

Luis Cayuela and Marcelino de la Cruz

References

Cayuela, L., De la Cruz, M. and Ruokolainen, K. A method to incorporate the effect of taxonomic uncertainty on multivariate analyses of ecological data (*Ecography*, *submitted*)

Examples

```
## Not run:
require(vegan)

data(Amazonia)
data(soils)

# Define a new index that includes the terms used in the \code{Amazonia} dataset to define undetermined taxa at di
index.Amazon <- c(paste("sp.", rep(1:20), sep=""), "Indet.", "indet.")

#Generate a pertables object (i.e. a list of biological data tables simulated from taxonomic uncertainty)
Amazonia100 <- pertables(Amazonia, index=index.Amazon, nsim=100)

## End(Not run)
```

rda.pertables	<i>Function to assess the effects of taxonomic uncertainty on [Partial] Redundance Analysis</i>
---------------	---

Description

This function assesses the effects of taxonomic uncertainty on two widely used parameters of a [Partial] Redundance Analysis, i.e. the 'percentage explained variance' (sometimes referred to as *R-squared*) and the '*pseudo-F*'.

Usage

```
rda.pertables(formula, data, scale=FALSE, ...)
## S3 method for class 'rda.pertables'
plot(x, pch = 18, ...)
```

Arguments

formula	Model formula, where the left hand side gives a pertables object (i.e. a list of simulated community data matrices obtained with pertables , right hand side gives the constraining variables, and conditioning variables can be given within a special function <code>Condition</code>).
data	Data frame containing the variables on the right hand side of the model formula.
scale	Scale species to unit variance (like correlations).
x	rda.pertables object to plot.
pch	Plotting 'character', i.e., symbol to use in the RDA plot. See points for examples of use of this graphical argument.
...	Additional graphical parameters passed to plot.

Details

This function is a wrapper to submit a [pertables](#) object to `rda` function of the **vegan** package. See the documentation of `rda` for details about `formula` and `Condition` use.

Value

`rda.pertables` returns an object of class 'rda.pertables', basically a list with the following components:

raw	An object of class <code>class 'rda'</code> . The results of applying <code>rda</code> to the original biological data table without the unidentified species.
simulation	A list with the results of the simulation: 'results', i.e. a data.frame with all the simulated R-squared and pseudo-F values; 'rda.quant', i.e. a data.frame with the summary of 'results' by quantiles; 'sites' i.e. a list with the scores of the sites of all the simulated data tables and 'biplot', i.e. a list with the scores of the environmental data in all the analyses

The objects of class 'rda.pertables' have `print` and `plot` S3 methods for a simple access to results. See the examples.

Author(s)

Luis Cayuela and Marcelino de la Cruz

References

Cayuela, L., De la Cruz, M. and Ruokolainen, K. A method to incorporate the effect of taxonomic uncertainty on multivariate analyses of ecological data (*Ecography, submitted*)

See Also

pertables, [rda](#)

Examples

```
## Not run:
require(vegan)

data(Amazonia)
data(soils)

# Define a new index that includes the terms used in the \code{Amazonia} dataset to define undetermined taxa at di
index.Amazon <- c(paste("sp.", rep(1:20), sep=""), "Indet.", "indet.")

#Generate a pertables object (i.e. a list of biological data tables simulated from taxonomic uncertainty)
Amazonia100 <- pertables(Amazonia, index=index.Amazon, nsim=100)

# Assess the effects of taxonomic uncertainty on a RDA analysis of biological data explained by all the environmen

Amazonia.rda <- rda.pertables(Amazonia100 ~., data=soils)

Amazonia.rda

plot(Amazonia.rda)

## End(Not run)
```

Index

*Topic **datasets**

Amazonia, [3](#)

HCP, [6](#)

*Topic **multivariate**

adonis.pertables, [2](#)

cca.pertables, [4](#)

mantel.pertables, [7](#)

pertables, [9](#)

rda.pertables, [10](#)

adonis, [3](#)

adonis.pertables, [2](#)

Amazonia, [3](#)

cca, [5](#)

cca.pertables, [4](#)

cor, [7](#)

HCP, [6](#)

mantel, [2, 8](#)

mantel.pertables, [7](#)

pertables, [2, 5, 7, 9, 11](#)

plot.adonis.pertables

(adonis.pertables), [2](#)

plot.cca.pertables (cca.pertables), [4](#)

plot.mantel.pertables

(mantel.pertables), [7](#)

plot.rda.pertables (rda.pertables), [10](#)

points, [5, 7, 11](#)

print.adonis.pertables

(adonis.pertables), [2](#)

print.cca.pertables (cca.pertables), [4](#)

print.mantel.pertables

(mantel.pertables), [7](#)

print.pertables (pertables), [9](#)

print.rda.pertables (rda.pertables), [10](#)

rda, [11, 12](#)

rda.pertables, [10](#)

soils (Amazonia), [3](#)

vegdist, [7](#)