

Package ‘primerTree’

January 12, 2016

Version 1.0.3

Maintainer Jim Hester <james.f.hester@gmail.com>

Author Jim Hester

Title Visually Assessing the Specificity and Informativeness of Primer Pairs

Description Identifies potential target sequences for a given set of primers and generates taxonomically annotated phylogenetic trees with the predicted amplification products.

Depends R (>= 3.0.0), directlabels, gridExtra

Imports ggplot2, grid, XML, ape, httr, lubridate, plyr, scales, stringr, foreach

LazyData true

License GPL-2

RoxygenNote 5.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2016-01-12 22:04:30

R topics documented:

accession2gi	2
bryophytes_trnL	2
clustalo	3
filter_seqs	3
get_sequence	4
get_sequences	5
get_taxonomy	5
gi2taxid	6
identify.primerTree_plot	6
layout_tree_ape	7
mammals_16S	7
plot.primerTree	7

plot_tree	8
plot_tree_ranks	9
primerTree	10
primer_search	10
search_primer_pair	11
seq_lengths	12
seq_lengths.primerTree	13
summary.primerTree	13
tree_from_alignment	14

Index **15**

accession2gi	<i>Maps a genbank accession to a nuclotide database gi.</i>
--------------	---

Description

Maps a genbank accession to a nuclotide database gi.

Usage

```
accession2gi(accession)
```

Arguments

accession accession character vector to lookup.

Value

named vector of gis.

bryophytes_trnL	<i>PrimerTree results for the bryophyte trnL primers</i>
-----------------	--

Description

PrimerTree results for the bryophyte trnL primers

clustalo	<i>Multiple sequence alignment with clustal omega</i>
----------	---

Description

Calls clustal omega to align a set of sequences of class DNABin. Run without any arguments to see all the options you can pass to the command line clustal omega.

Usage

```
clustalo(x, exec = "clustalo", quiet = TRUE, original.ordering = TRUE,
  ...)
```

Arguments

x	an object of class 'DNABin'
exec	a character string with the name or path to the program
quiet	whether to suppress output to stderr or stdout
original.ordering	use the original ordering of the sequences
...	additional arguments passed to the command line clustalo

filter_seqs	<i>Filter out sequences retrieved by search_primer_pair() that are either too short or too long. The alignment and tree will be recalculated after removing unwanted reads.</i>
-------------	---

Description

Filter out sequences retrieved by search_primer_pair() that are either too short or too long. The alignment and tree will be recalculated after removing unwanted reads.

Usage

```
filter_seqs(x, ...)

## S3 method for class 'primerTree'
filter_seqs(x, min_length = 0, max_length = Inf, ...)
```

Arguments

x	a primerTree object
...	additional arguments passed to methods.
min_length	the minimum sequence length to keep
max_length	the maximum sequence length to keep

Value

a primerTree object

Methods (by class)

- primerTree: Method for primerTree objects

Examples

```
## Not run:  
# filter out sequences longer or shorter than desired:  
mammals_16S_filtered <- filter_seqs(mammals_16S, min_length=131, max_length=156)  
  
## End(Not run)
```

get_sequence	<i>Retrieves a fasta sequence from NCBI nucleotide database.</i>
--------------	--

Description

Retrieves a fasta sequence from NCBI nucleotide database.

Usage

```
get_sequence(gi, start = NULL, stop = NULL)
```

Arguments

gi	nucleotide gi to retrieve.
start	start base to retrieve, numbered beginning at 1. If NULL the beginning of the sequence.
stop	last base to retrieve, numbered beginning at 1. if NULL the end of the sequence.

Value

an DNABin object.

See Also

[DNABin](#)

get_sequences	<i>Retrieves fasta sequences from NCBI nucleotide database.</i>
---------------	---

Description

Retrieves fasta sequences from NCBI nucleotide database.

Usage

```
get_sequences(gi, start = NULL, stop = NULL, simplify = TRUE,  
             .parallel = FALSE, .progress = "none")
```

Arguments

gi	the gi number of the sequence to retrieve
start	start bases to retrieve, numbered beginning at 1. If NULL the beginning of the sequence.
stop	stop bases to retrieve, numbered beginning at 1. if NULL the stop of the sequence.
simplify	simplify the FASTA headers to include only the genbank accession.
.parallel	if 'TRUE', perform in parallel, using parallel backend provided by foreach
.progress	name of the progress bar to use, see 'create_progress_bar'

Value

an DNABin object.

See Also

[DNABin](#)

get_taxonomy	<i>Retrieve the taxonomy information from NCBI for a set of nucleotide gis.</i>
--------------	---

Description

Retrieve the taxonomy information from NCBI for a set of nucleotide gis.

Usage

```
get_taxonomy(gis)
```

Arguments

`gis` a character vector of the gis to retrieve

Value

data.frame of the 'gis, taxIds, and taxonomy

<code>gi2taxid</code>	<i>Maps a nucleotide database gi to a taxonomy database taxId</i>
-----------------------	---

Description

Maps a nucleotide database gi to a taxonomy database taxId

Usage

```
gi2taxid(gi)
```

Arguments

`gi` gi character vector to lookup.

Value

named vector of taxIds.

<code>identify.primerTree_plot</code>	<i>identify the point closest to the mouse click only works on single ranks</i>
---------------------------------------	---

Description

identify the point closest to the mouse click only works on single ranks

Usage

```
## S3 method for class 'primerTree_plot'
identify(x, ...)
```

Arguments

`x` the plot to identify
`...` additional arguments passed to annotate

layout_tree_ape	<i>layout a tree using ape, return an object to be plotted by plot_tree</i>
-----------------	---

Description

layout a tree using ape, return an object to be plotted by [plot_tree](#)

Usage

```
layout_tree_ape(tree, ...)
```

Arguments

tree	The phylo tree to be plotted
...	additional arguments to plot.phylo

Value

edge	list of x, y and xend, yend coordinates as well as ids for the edges
tips	list of x, y, label and id for the tips
nodes	list of x, y and id for the nodes

mammals_16S	<i>PrimerTree results for the mammalian 16S primers</i>
-------------	---

Description

PrimerTree results for the mammalian 16S primers

plot.primerTree	<i>plot function for a primerTree object, calls plot_tree_ranks</i>
-----------------	---

Description

plot function for a primerTree object, calls [plot_tree_ranks](#)

Usage

```
## S3 method for class 'primerTree'
plot(x, ranks = NULL, main = NULL, ...)
```

Arguments

x	primerTree object to plot
ranks	The ranks to include, defaults to all common ranks, if NULL print all ranks. If 'none' just print the layout.
main	an optional title to display, if NULL displays the name as the title
...	additional arguments passed to plot_tree_ranks

See Also

[plot_tree_ranks](#), [plot_tree](#)

Examples

```
library(gridExtra)
library(directlabels)
#plot with all common ranks
plot(mammals_16S)

#plot only the class
plot(mammals_16S, 'class')

#plot the layout only
plot(mammals_16S, 'none')
```

plot_tree	<i>plots a tree, optionally with colored and labeled points by taxonomic rank</i>
-----------	---

Description

plots a tree, optionally with colored and labeled points by taxonomic rank

Usage

```
plot_tree(tree, type = "unrooted", main = NULL, guide_size = NULL,
  rank = NULL, taxonomy = NULL, size = 2, legend_cutoff = 25, ...)
```

Arguments

tree	to be plotted, use layout_tree to layout tree.
type	The type of tree to plot, default unrooted.
main	An optional title for the plot
guide_size	The size of the length guide. If NULL auto detects a reasonable size.
rank	The rank to include, if null only the tree is plotted
taxonomy	A data.frame with an accession field corresponding to the tree tip labels.

size	The size of the colored points
legend_cutoff	The number of different taxa names after which the names are no longer printed.
...	additional arguments passed to layout_tree_ape

Value

plot to be printed.

plot_tree_ranks	<i>plots a tree along with a series of taxonomic ranks</i>
-----------------	--

Description

plots a tree along with a series of taxonomic ranks

Usage

```
plot_tree_ranks(tree, taxonomy, main = NULL, type = "unrooted",
  ranks = common_ranks, size = 2, guide_size = NULL, legend_cutoff = 25,
  ...)
```

Arguments

tree	to be plotted, use <code>layout_tree</code> to layout tree.
taxonomy	A data.frame with an accession field corresponding to the tree tip labels.
main	An optional title for the plot
type	The type of tree to plot, default unrooted.
ranks	The ranks to include, defaults to all common ranks, if null print all ranks.
size	The size of the colored points
guide_size	The size of the length guide. If NULL auto detects a reasonable size.
legend_cutoff	The number of different taxa names after which the names are no longer printed.
...	additional arguments passed to layout_tree_ape

See Also

[plot_tree](#) to plot only a single rank or the just the tree layout.

Examples

```
library(gridExtra)
library(directlabels)
#plot all the common ranks
plot_tree_ranks(mammals_16S$tree, mammals_16S$taxonomy)
#plot specific ranks, with a larger dot size
plot_tree_ranks(mammals_16S$tree, mammals_16S$taxonomy,
  ranks=c('kingdom', 'class', 'family'), size=3)
```

primerTree	primerTree <i>Visually Assessing the Specificity and Informativeness of Primer Pairs</i>
------------	---

Description

primerTree has two main commands: `search_primer_pair` which takes a primer pair and returns an primerTree object of the search results `plot.primerTree` a S3 method for plotting the primerTree object obtained using `search_primer_pair`

primer_search	<i>Query a pair of primers using ncbi's Primer-BLAST, if primers contain iupac</i>
---------------	--

Description

ambiguity codes, enumerate all possible combinations and combine the results.

Usage

```
primer_search(forward, reverse, num_aligns = 500, num_permutations = 25,
  ..., .parallel = FALSE, .progress = "none")
```

Arguments

forward	forward primer to search by 5'-3' on plus strand
reverse	reverse primer to search by 5'-3' on minus strand
num_aligns	number of alignment results to keep
num_permutations	the number of primer permutations to search, if the degenerate bases cause more than this number of permutations to exist, this number will be sampled from all possible permutations.
...	additional arguments passed to Primer-Blast
.parallel	if 'TRUE', perform in parallel, using parallel backend provided by foreach
.progress	name of the progress bar to use, see 'create_progress_bar'

Value

data.frame of primer hits

search_primer_pair	<i>Automatic primer searching Search a given primer pair, retrieving the alignment results, their product sequences, the taxonomic information for the sequences, a multiple alignment of the products</i>
--------------------	--

Description

Automatic primer searching Search a given primer pair, retrieving the alignment results, their product sequences, the taxonomic information for the sequences, a multiple alignment of the products

Usage

```
search_primer_pair(forward, reverse, name = NULL, num_aligns = 500,
  num_permutations = 25, simplify = TRUE, clustal_options = list(),
  distance_options = list(model = "raw"), ..., .parallel = FALSE,
  .progress = "none")
```

Arguments

forward	forward primer to search by 5'-3' on plus strand
reverse	reverse primer to search by 5'-3' on minus strand
name	name to give to the primer pair
num_aligns	number of alignment results to keep
num_permutations	the number of primer permutations to search, if the degenerate bases cause more than this number of permutations to exist, this number will be sampled from all possible permutations.
simplify	use simple names for primer hit results or complex
clustal_options	a list of options to pass to clustal omega, see link{clustalo} for a list of options
distance_options	a list of options to pass to dist.dna, see link{dist.dna} for a list of options
...	additional arguments passed to Primer-Blast
.parallel	if 'TRUE', perform in parallel, using parallel backend provided by foreach
.progress	name of the progress bar to use, see create_progress_bar

Value

A list with the following elements,

name	name of the primer pair
BLAST_result	html blast results from Primer-BLAST as 'a response object.

taxonomy	taxonomy for the primer products from NCBI
sequence	sequence of the primer products
alignment	multiple alignment of the primer products
tree	phylogenetic tree of the reconstructed from the 'multiple alignment

See Also

[primer_search](#), [clustalo](#)

Examples

```
## Not run:
#simple search
mammals_16S = search_primer_pair(name='Mammals 16S',
  'CGGTTGGGGTGACCTCGGA', 'GCTGTTATCCCTAGGGTAACT')
#returning 1000 alignments, allow up to 3 mismatches in primer
mammals_16S = search_primer_pair(name='Mammals 16S',
  'CGGTTGGGGTGACCTCGGA', 'GCTGTTATCCCTAGGGTAACT',
  num_aligns=1000, total_primer_specificity_mismatch=3)

## End(Not run)
```

seq_lengths

Get a summary of sequence lengths from a primerTree object

Description

Get a summary of sequence lengths from a primerTree object

Usage

```
seq_lengths(x, summarize = TRUE)
```

Arguments

x a primerTree object.
 summarize a logical indicating if a summary should be displayed

Value

a table of sequence length frequencies

Examples

```
# Show the counts for each length
seq_lengths(mammals_16S)

# Plot the distribution of lengths
seqLengths <- seq_lengths(mammals_16S)
barplot(seqLengths,
  main = "Frequency of sequence lengths for 16S mammal primers",
  xlab="Amplicon length (in bp)",
  ylab="Frequency")
```

```
seq_lengths.primerTree
```

Method for primerTree objects

Description

Method for primerTree objects

Usage

```
## S3 method for class 'primerTree'
seq_lengths(x, summarize = TRUE)
```

Arguments

x a primerTree object.
 summarize a logical indicating if a summary should be displayed

```
summary.primerTree
```

Summarize a primerTree result, printing quantiles of sequence length and pairwise differences.

Description

Summarize a primerTree result, printing quantiles of sequence length and pairwise differences.

Usage

```
## S3 method for class 'primerTree'
summary(object, ..., probs = c(0, 0.05, 0.5, 0.95, 1),
  ranks = common_ranks)
```

Arguments

object	the primerTree object to summarise
...	Ignored options
probs	quantile probabilities to compute, defaults to 0, 5, 50, 95, and 100 probabilities.
ranks	ranks to show unique counts for, defaults to the common ranks

Value

invisibly returns a list containing the printed results

tree_from_alignment *Construct a neighbor joining tree from a dna alignment*

Description

Construct a neighbor joining tree from a dna alignment

Usage

```
tree_from_alignment(dna, pairwise.deletion = TRUE, ...)
```

Arguments

dna	fasta dna object the tree is to be constructed from
pairwise.deletion	a logical indicating if the distance matrix should be constructed using pairwise deletion
...	further arguments to dist.dna

See Also

[dist.dna](#), [nj](#)

Index

accession2gi, [2](#)

bryophytes_trnL, [2](#)

clustalo, [3](#), [12](#)

create_progress_bar, [11](#)

dist.dna, [14](#)

DNABin, [4](#), [5](#)

filter_seqs, [3](#)

get_sequence, [4](#)

get_sequences, [5](#)

get_taxonomy, [5](#)

gi2taxid, [6](#)

identify.primerTree_plot, [6](#)

layout_tree_ape, [7](#), [9](#)

mammals_16S, [7](#)

nj, [14](#)

phylo, [7](#)

plot.phylo, [7](#)

plot.primerTree, [7](#), [10](#)

plot_tree, [7](#), [8](#), [8](#), [9](#)

plot_tree_ranks, [8](#), [9](#)

primer_search, [10](#), [12](#)

primerTree, [10](#)

primerTree-package (primerTree), [10](#)

response, [11](#)

search_primer_pair, [10](#), [11](#)

seq_lengths, [12](#)

seq_lengths.primerTree, [13](#)

summary.primerTree, [13](#)

tree_from_alignment, [14](#)