

# Package ‘worldmet’

February 16, 2018

**Type** Package

**Title** Import Surface Meteorological Data from NOAA Integrated Surface Database (ISD)

**Version** 0.8.3

**Date** 2018-02-08

**ByteCompile** true

**Depends** R (>= 3.2.0)

**Imports** openair, doParallel, parallel, foreach, dplyr, leaflet, readr, zoo

**Maintainer** David Carslaw <david.carslaw@york.ac.uk>

**Description** Functions to import data from more than 30,000 surface meteorological sites around the world managed by the National Oceanic and Atmospheric Administration (NOAA) Integrated Surface Database (ISD, see <<https://www.ncdc.noaa.gov/isd>>).

**License** GPL (>= 2)

**URL** <http://github.com/davidcarslaw/worldmet>

**BugReports** <http://github.com/davidcarslaw/worldmet/issues>

**LazyLoad** true

**LazyData** true

**RoxygenNote** 6.0.1

**NeedsCompilation** no

**Author** David Carslaw [aut, cre]

**Repository** CRAN

**Date/Publication** 2018-02-16 12:42:06 UTC

## R topics documented:

exportADMS	2
getMeta	3

importNOAA . . . . .	4
meta . . . . .	6
weatherCodes . . . . .	7
worldmet . . . . .	7
<b>Index</b>	<b>9</b>

---

exportADMS	<i>Export a meteorological data frame in ADMS format</i>
------------	--

---

## Description

Export a meteorological data frame in ADMS format

## Usage

```
exportADMS(dat, out = "./ADMS_met.MET", interp = FALSE, maxgap = 2)
```

## Arguments

dat	A data frame imported by <a href="#">importNOAA</a> .
out	A file name for the ADMS file. The file is written to the working directory by default.
interp	Should interpolation of missing values be undertaken? If TRUE linear interpolation is carried out for gaps of up to and including maxgap.
maxgap	The maximum gap in hours that should be interpolated where there are missing data when <code>interp = TRUE</code> . Data with gaps more than maxgap are left as missing.

## Value

Writes a text file to a location of the user's choosing.

## Examples

```
## Not run:
## import some data then export it
dat <- importNOAA(year = 2012)
exportADMS(dat, file = "~/temp/adms_met.MET")

## End(Not run)
```

---

getMeta	<i>Find a ISD site code and other meta data</i>
---------	---

---

### Description

Get information on meteorological sites

### Usage

```
getMeta(site = "heathrow", lat = NA, lon = NA, country = NA,
        state = NA, n = 10, end.year = "current", plot = TRUE, fresh = TRUE,
        returnMap = FALSE)
```

### Arguments

site	A site name search string e.g. site = "heathrow". The search strings and be partial and can be upper or lower case e.g. site = "HEATHR".
lat	A latitude in decimal degrees to search. Takes the values -90 to 90.
lon	A longitude in decimal degrees to search. Takes values -180 to 180. Negative numbers are west of the Greenwich meridian.
country	The country code. This is a two letter code. For a full listing see <a href="ftp://ftp.ncdc.noaa.gov/pub/data/noaa/country-list.txt">ftp://ftp.ncdc.noaa.gov/pub/data/noaa/country-list.txt</a> .
state	The state code. This is a two letter code.
n	The number of nearest sites to search based on latitude and longitude.
end.year	To help filter sites based on how recent the available data are. end.year can be "current", "any" or a numeric year such as 2016, or a range of years e.g. 1990:2016 (which would select any site that had an end date in that range. <b>By default only sites that have some data for the current year are returned.</b>
plot	If TRUE will plot sites on an interactive leaflet map.
fresh	Should the meta data be read from the NOAA server or the worldmet package?. If FALSE it is read from the package version, which is fast but might be out of date. If TRUE the data are read from the NOAA server.
returnMap	Should the leaflet map be returned instead of the meta data? Default is FALSE.

### Details

This function is primarily used to find a site code that can be used to access data using [importNOAA](#). Sites searches of approximately 30,000 sites can be carried out based on the site name and based on the nearest locations based on user-supplied latitude and logitude.

### Value

A data frame is returned with all available meta data, mostly importantly including a code that can be supplied to [importNOAA](#). If latitude and longitude searches are made an approximate distance, dist in km is also returned.

**Author(s)**

David Carslaw

**Examples**

```

## Not run:
## search for sites with name beijing
getMeta(site = "beijing")

## End(Not run)

## Not run:
## search for near a specified lat/lon - near Beijing airport
## returns 'n' nearest by default
getMeta(lat = 40, lon = 116.9)

## End(Not run)

```

importNOAA

*Import meteorological data***Description**

Main function for importing meteorological data

**Usage**

```

importNOAA(code = "037720-99999", year = 2014, hourly = TRUE,
  precip = FALSE, PWC = FALSE, parallel = TRUE, quiet = FALSE)

```

**Arguments**

code	The identifying code as a character string. The code is a combination of the USAF and the WBAN unique identifiers. The codes are sperated by a "-" e.g. code = "037720-99999".
year	The year to import. This can be a vector of years e.g. year = 2000:2005.
hourly	Should hourly means be calculated? The default is TRUE. If FALSE then the raw data are returned.
precip	Should precipitation measurements be returned? If TRUE the 12-hourly and 6-hourly totals are returned (if available). In addition, an hourly sequence is also returned, as described below.
PWC	Description of the present weather conditions (if available).
parallel	Should the importing use mutiple processors? By default the number of cores - 1 are used.
quiet	If FALSE, print missing sites / years to the screen.

## Details

This is the main function to import data from the NOAA Integrated Surface Database (ISD). The ISD contains detailed surface meteorological data from around the world for over 30,000 locations. For general information of the ISD see <https://www.ncdc.noaa.gov/isd> and the map here <https://gis.ncdc.noaa.gov/map/viewer/#app=cdo&cfg=cdo&theme=hourly&layers=1>.

Note the following units for the main variables:

**date** Date/time in POSIXct format. **Note the time zone is GMT (UTC) and may need to be adjusted to merge with other local data. See details below.**

**lat** Latitude in decimal degrees (-90 to 90).

**lon** Longitude in decimal degrees (-180 to 180). Negative numbers are west of the Greenwich Meridian.

**elev** Elevation of site in metres.

**wd** Wind direction in degrees. 90 is from the east.

**ws** Wind speed in m/s.

**sky\_ceiling** The height above ground level (AGL) of the lowest cloud or obscuring phenomena layer aloft with 5/8 or more summation total sky cover, which may be predominantly opaque, or the vertical visibility into a surface-based obstruction.

**visibility** The visibility in metres.

**air\_temp** Air temperature in degrees Celcius.

**dew\_point** The dew point temperature in degrees Celcius.

**sea\_level\_press** The sea level pressure in millibars.

**RH** The relative humidity (%).

**cl\_1, ..., cl\_3** Cloud cover for different layers in Oktas (1-8).

**cl** Maximum of cl\_1 to cl\_3 cloud cover in Oktas (1-8).

**cl\_1\_height, ..., cl\_3\_height** Height of the cloud base for each later in metres.

**precip\_12** 12-hour precipitation in mm.

**precip\_6** 6-hour precipitation in mm.

**precip** Based on the 12 hourly and 6 hourly totals, precip spreads the 6-hourly totals across the previous 6-hours to provide an indication of hourly precipitation.

**pwc** The description of the present weather description (if available).

The data are returned in GMT (UTC). It may be necessary to adjust the time zone when coming with other data. For example, if air quality data were available for Beijing with time zone set to "Etc/GMT-8" (note the negative offset even though Beijing is ahead of GMT. See the `openair` package and manual for more details), then the time zone of the met data can be changed to be the same. One way of doing this would be `attr(met$date, "tzone") <- "Etc/GMT-8"` for a meteorological data frame called `met`. The two data sets could then be merged based on date.

## Value

Returns a data frame of surface observations. The data frame is consistent for use with the `openair` package. NOTE! the data are returned in GMT (UTC) time zone format. Users may wish to express the data in other time zones e.g. to merge with air pollution data.

**Author(s)**

David Carslaw

**See Also**[getMeta](#) to obtain the codes based on various site search approaches.**Examples**

```
## Not run:
## use Beijing airport code (see getMeta example)
dat <- importNOAA(code = "545110-99999", year = 2010:2011)

## End(Not run)
```

meta

*ISD meta data***Description**

This data frame consists of the meta data from the ISD from <ftp://ftp.ncdc.noaa.gov/pub/data/noaa/isd-history.csv>. It is updated in the worldmet package for each release. Users can access specific meta data from the most up to date file by using the [getMeta](#) function. This data frame exists for fast access.

**Format**

Data frame with 65533 observations (rows) on the following 10 variables:

**USAF** USAF site id.

**WBAN** WBAN id.

**STATION** Name of measurement site.

**CTRY** Country code.

**ST** State.

**CALL** Airport id if available.

**LAT** Latitude in decimal degrees.

**LON** Longitude in decimal degrees.

**ELEV(M)** Elevation of site in metres.

**BEGIN** Date the measurements started, in Date format.

**END** Date the measurements ended, in Date format.

**code** The unique code that is used in [importNOAA](#) that is a combination of the USAF and WBAN codes.

**Details**

meta is supplied with the worldmet package and consists of the following information.

**Source**

meta was compiled from <ftp://ftp.ncdc.noaa.gov/pub/data/noaa/isd-history.csv>.

**Examples**

```
## basic structure
head(meta)
```

---

weatherCodes	<i>Codes for weather types</i>
--------------	--------------------------------

---

**Description**

This data frame consists of the weather description codes used in the ISD. It is not of general use to most users.

**Examples**

```
## basic structure
head(weatherCodes)
```

---

worldmet	<i>Access surface meteorological data from the NOAA Integrated Surface Database from around the world</i>
----------	---

---

**Description**

This package contains functions to import surface meteorological data from over 30,000 sites around the world. These data are curated by NOAA as part of the Integrated Surface Database (ISD).

**Details**

If you access these data using the worldmet package please give full acknowledgement to NOAA ISD. Users should also take a note of the usage restrictions.

These data work well with the openair package that has been developed to analyse air pollution data.

**Author(s)**

David Carslaw

**References**

For general information of the ISD see <https://www.ncdc.noaa.gov/isd> and the map here <https://gis.ncdc.noaa.gov/map/viewer/#app=cdo&cfg=cdo&theme=hourly&layers=1>.

**See Also**

See <https://github.com/davidcarslaw/openair> for information on the related openair package.



# Index

\*Topic **datasets**

meta, [6](#)

weatherCodes, [7](#)

\*Topic **methods**

worldmet, [7](#)

exportADMS, [2](#)

getMeta, [3](#), [6](#)

importNOAA, [2](#), [3](#), [4](#), [6](#)

meta, [6](#)

weatherCodes, [7](#)

worldmet, [7](#)

worldmet-package (worldmet), [7](#)