

Package ‘SeerMapperEast’

April 12, 2017

Type Package

Version 1.2.0

Date 2017-04-10

Title Supplemental U. S. 2000 Census Tract Boundaries for 23 Eastern States without Seer Registries

Author ``Jim Pearson" <jpearson@statnetconsulting.com>
with data provided by ``U. S. Census Bureau" <geo.tiger@census.gov>

Maintainer ``Jim Pearson" <jpearson@statnetconsulting.com>

Depends R (>= 3.2.0)

Imports sp

Suggests

Description Provides supplemental 2000 census tract boundaries for the 23 states without Seer Registries that are east of the Mississippi river for use with the 'SeerMapper' package.
The data contained in this package is derived from U. S. Census data and is in the public domain.

License GPL (>= 2)

LazyData no

LazyLoad no

BuildResaveData yes

ByteCompile yes

NeedsCompilation no

Repository CRAN

Date/Publication 2017-04-12 14:15:09 UTC

R topics documented:

SeerMapperEast-package	2
trXX_dXX	3

Index	7
--------------	----------

SeerMapperEast-package

SeerMapper-Supplemental 2000 Census Tract East States boundary datasets

Description

The *SeerMapperEast* package provides supplemental 2000 Census Tract boundary datasets for state without Seer registries that are east of the Mississippi river use with *SeerMapper* package. This

The *SeerMapperWest* data only package contains the 2000 census tract boundary dataset for 14 states west of the Mississippi river that do not contain NCI Seer Registries. The *SeerMapperRegs* data only package contains the 2000 census trace boundary datasets for the 15 states with Seer Registries.

By loading these packages (via the library function) expands the *SeerMapper* package abilities to map 2000 census tract level data in any of the 50 states, the District of Columbia and Puerto Rico.

Details

Package:	SeerMapperEast
Type:	Package
Version:	1.2.0
Date:	2017-04-10
License:	GPL-2
LazyLoad:	no

No special action is required by the user to install this package or load it when running *SeerMapper*. The defined interdependencies of the packages automatically install the supplemental 2000 census tract boundary packages when *SeerMapper* is install. When *SeerMapper* is called, if it determines that one or more supplemental packages need to be loaded, it initiates the loading for the caller.

```
library(SeerMapper)

rateDate <- data.frame(FIBS=stateFibs,
                      Rate=stateRateVector,
                      pValue=stateRatePValue)

SeerMapper(rateData, Title=c("Test Map"))
```

If the package attachment or dataset load fails, the caller is notified of the problem and mapping is terminated.

The *SeerMapperEast* package contains the 2000 census tract boundary dataset for:

FIPS	Name
------	------

01	Alabama
10	Delaware
11	District of Columbia
12	Florida
17	Illinois
18	Indiana
23	Maine
24	Maryland
25	Massachusetts
28	Mississippi
33	New Hampshire
36	New York
37	North Carolina
39	Ohio
42	Pennsylvania
44	Rhode Island
45	South Carolina
47	Tennessee
50	Vermont
51	Virginia
54	West Virginia
55	Wisconsin
72	Puerto Rico

Author(s)

Jim Pearson <jpearson@statnetconsulting.com>

Maintainer: "Jim Pearson" <jpearson@statnetconsulting.com>

Package compiled by "Jim Pearson" <jpearson@statnetconsulting.com>

| trXX_dXX |

Provides the U.S. 2000 Census Tract Boundary data datasets for 23 States East of the Mississippi River for use with SeerMapper Package

Description

There are six supplemental census tract boundary packages for use with *SeerMapper*. The are *SeerMapperRegs*, *SeerMapperEast*, *SeerMapperWest* for the 2000 census and *Seer2010MapperRegs*, *Seer2010MapperEast* and *SeerMapper2010West* for the 2010 census. The combination of the either three provide a set of census tract boundaries for one U. S. census year (either 2000 or 2010). The *SeerMapperRegs* and *Seer2010MapperRegs* packages contain the census tract boundaries for the 15 states the have U. S. Seer Registries. The remaining census tract boundaries are split into two packages for each census year based on whether the state is east or west of the Mississippi river. The census tracts for 23 states without registries east of the Mississippi river at contained in the *SeerMapperEast* and *Seer2010MapperEast* packages. The tract boundaries for the 14 states west of the Mississippi river are in the *SeerMapperWest* and *Seer2010MapperWest* packages. The

states include the District of Columbia and Puerto Rico. This package provides the 2000 census tract boundaries for the 23 states without registries east of the Mississippi river.

Usage

```
data(tr10_d00)
```

Format

Each file contains a set of SpatialPolygons structures for the 23 states east of the Mississippi that do not have Seer Registries. Each state structure is a list of the census tracts boundaries that the state. Refer to the documentation on the *sp* package for details on the structures. Each list element is a "polygons" class structure containing attributes of the census tract (label point, area, ID, etc.) and a list of "Polygons" class elements that define the boundary polygons.

Details

The *SeerMapperEast* and *SeerMapper2010East* packages contains 23 eastern states including:

FIPS	Name
01	Alabama
10	Delaware
11	District of Columbia
12	Florida
17	Illinois
18	Indiana
23	Maine
24	Maryland
25	Massachusetts
28	Mississippi
33	New Hampshire
36	New York
37	North Carolina
39	Ohio
42	Pennsylvania
44	Rhode Island
45	South Carolina
47	Tennessee
50	Vermont
51	Virginia
54	West Virginia
55	Wisconsin
72	Puerto Rico

The *SeerMapper* package contains the state and county boundary data for all 51 states and DC and the Seer Registry boundary data for the 20 established registries. Due to space limitations, the base packages cannot contain the census tract boundary data.

Three supplemental data packages are used for each census year to provide the census tract boundary data to *SeerMapper* package.

Each state ".rda" file (dataset) contains state's census tract boundary data. The file name structure is trXX_dYY, where tr identifies the file as census tract boundary data, "XX" is the state (2 digits) fips code and "YY" represents the census year (e.g., 00 = 2000 or 10 for 2010)

To conserve disk space and downloading/installation time, the rda files are compressed using the "xy" method.

The U. S. Census Bureau census tract boundary shape file data was pre- processed by "www.MapShaper.org" website version 01.15 using modified Visvalingam method with the intersection repair and prevent shape removal options enabled, the coordinate precision value set to 0.0 and the simplify parameter set to 10 by 85 alignments.

When the *SeerMapper* package is install, the six (6) census tract boundary supplement packages are also install automatically by R. The *SeerMapper* package then manages the loading of the packages to ensure the needed boundary files are available.

Source

The census tract boundary shapefiles were downloaded from the CENSUS.GOV web site for the 2000 Census census tract boundary shapefiles, https://www2.census.gov/geo/tiger/PREVGENZ/tr/tr00shp/trXX_d00_shp.zip where XX is the state FIPS code.

Examples

```
#
# These examples are a test to ensure each census tract file
# can be read and a plot of the state generated.
#
require("sp")

#
# If you want to save and see the example output PDF files, change the
# the following "tempDir()" to the path you want to save the output files.
# For Example: outDir <- "c:/RTestPDFs"
outDir <- tempdir()
cat("Output Directory:",outDir,"\n")

stList <- c("01","10","11","12","17",
            "18","23","24","25","28",
            "33","36","37","39","42",
            "44","45","47","50","51",
            "54","55","72"
            )
stName <- c("Alabama","Delaware","Dist.of Columbia","Florida","Illinois",
            "Indiana","Maine","Maryland","Massachusetts","Mississippi",
            "New Hampshire","New York","North Carolina","Ohio","Pennsylvania",
            "Rhode Island","South Carolina","Tennessee","Vermont","Virginia",
            "West Virginia","Wisconsin","Puerto Rico"
            )
cY <- "00"
```

```
outFile <- paste0("SeerMapperEast",cY,"-CT.pdf")
outFN    <- file.path(outDir,outFile)
cat("Output example PDF file:",outFN,"\n")

pdf(outFN,width=7,height=10)

for (stN in seq(from=1, to=length(stList), by=8)) { # Test draw 3 of 23 states (1, 9, and 17)

  stID <- stList[stN]
  stNa <- stName[stN]
  trFN <- paste0("tr",stID,"_d",cY)
  TT_tr <- paste0("U. S. Census Tracts - ",stNa," Fips=",stID," file=",trFN)

  data(list=trFN)

  wrSP <- get(trFN)
  #str(wrSP)

  plot(wrSP,main=TT_tr)
  rm(list=trFN)
}

dev.off()
```

Index

*Topic **Census2000**

trXX_dXX, [3](#)

*Topic **Census2010**

trXX_dXX, [3](#)

*Topic **SeerMapper**

trXX_dXX, [3](#)

*Topic **datasets**

trXX_dXX, [3](#)

SeerMapperEast-package, [2](#)

tr01_d00 (trXX_dXX), [3](#)

tr10_d00 (trXX_dXX), [3](#)

tr11_d00 (trXX_dXX), [3](#)

tr12_d00 (trXX_dXX), [3](#)

tr17_d00 (trXX_dXX), [3](#)

tr18_d00 (trXX_dXX), [3](#)

tr23_d00 (trXX_dXX), [3](#)

tr24_d00 (trXX_dXX), [3](#)

tr25_d00 (trXX_dXX), [3](#)

tr28_d00 (trXX_dXX), [3](#)

tr33_d00 (trXX_dXX), [3](#)

tr36_d00 (trXX_dXX), [3](#)

tr37_d00 (trXX_dXX), [3](#)

tr39_d00 (trXX_dXX), [3](#)

tr42_d00 (trXX_dXX), [3](#)

tr44_d00 (trXX_dXX), [3](#)

tr45_d00 (trXX_dXX), [3](#)

tr47_d00 (trXX_dXX), [3](#)

tr50_d00 (trXX_dXX), [3](#)

tr51_d00 (trXX_dXX), [3](#)

tr54_d00 (trXX_dXX), [3](#)

tr55_d00 (trXX_dXX), [3](#)

tr72_d00 (trXX_dXX), [3](#)

trXX_d00 (trXX_dXX), [3](#)

trXX_dXX, [3](#)