

# Package ‘crunch’

May 2, 2018

**Type** Package

**Title** Crunch.io Data Tools

**Description** The Crunch.io service <<http://crunch.io>> provides a cloud-based data store and analytic engine, as well as an intuitive web interface. Using this package, analysts can interact with and manipulate Crunch datasets from within R. Importantly, this allows technical researchers to collaborate naturally with team members, managers, and clients who prefer a point-and-click interface.

**Version** 1.22.0

**URL** <http://crunch.io/r/crunch/>, <https://github.com/Crunch-io/rcrunch>

**BugReports** <https://github.com/Crunch-io/rcrunch/issues>

**License** LGPL (>= 3)

**Depends** R (>= 3.0.0)

**Imports** crayon, curl, grDevices, httr (>= 1.0.0), httpcache (>= 0.1.4), jsonlite (>= 0.9.15), methods

**Suggests** covr, devtools, haven, httpptest (>= 3.0.0), knitr, magrittr, miniUI, rmarkdown, rstudioapi, shiny, spelling, testthat (>= 2.0.0)

**VignetteBuilder** knitr

**Language** en-US

**Encoding** UTF-8

**RoxygenNote** 6.0.1

**Collate** 'AllClasses.R' 'AllGenerics.R' 'variable-definition.R'  
'R-to-variable.R' 'abstract-categories.R' 'abstract-category.R'  
'add-subvariable.R' 'add-variable.R' 'api.R' 'append-dataset.R'  
'as-data-frame.R' 'auth.R' 'batches.R' 'case-variables.R'  
'categories.R' 'category.R' 'change-category-id.R'  
'combine-categories.R' 'compare-categories.R'  
'compare-datasets.R' 'compare-subvariables.R'  
'compare-variables.R' 'compare.R' 'conditional-transform.R'  
'consent.R' 'context-manager.R' 'copy.R' 'crunch-data-frame.R'

'crunch.R' 'crunchbox.R' 'cube-dims.R' 'cube-index-table.R'  
 'cube-query.R' 'cube-residuals.R' 'cube-result.R'  
 'cube-subset.R' 'cube-transforms.R' 'cube-variables.R' 'cut.R'  
 'dataset-catalog.R' 'dataset-extract.R' 'dataset-order.R'  
 'dataset-stream.R' 'dataset-update.R' 'dataset.R'  
 'dichotomize.R' 'drop-rows.R' 'edit-lock.R' 'export-dataset.R'  
 'expressions.R' 'filters.R' 'folders.R' 'fork-and-merge.R'  
 'formula.R' 'gadgets.R' 'geo.R' 'get-datasets.R' 'github.R'  
 'hide-variables.R' 'insertions.R' 'interact.R' 'join-dataset.R'  
 'json.R' 'make-array.R' 'members.R' 'merge-crunch-data-frame.R'  
 'misc.R' 'multitables.R' 'new-dataset.R' 'ordering.R'  
 'permission-catalog.R' 'pretty-print.R' 'progress.R'  
 'projects.R' 'search.R' 'session.R' 'share.R' 'shoji-catalog.R'  
 'shoji-entity.R' 'shoji-folder.R' 'shoji-order-slots.R'  
 'shoji-order.R' 'shoji.R' 'show.R' 'subtotals-and-headings.R'  
 'subvariables.R' 'summary-insertions.R' 'tab-book.R' 'teams.R'  
 'transform-calculate.R' 'transform.R' 'tuple.R' 'univariate.R'  
 'user.R' 'variable-as-methods.R' 'variable-catalog.R'  
 'variable-delete.R' 'variable-derivation.R' 'variable-folder.R'  
 'variable-metadata.R' 'variable-order.R' 'variable-summary.R'  
 'variable-to-R.R' 'variable-type.R' 'variable-update.R'  
 'variable.R' 'versions.R' 'weight.R' 'zcl.R'

**NeedsCompilation** no

**Author** Neal Richardson [aut, cre],  
 Jonathan Keane [ctb],  
 Gordon Shotwell [ctb]

**Maintainer** Neal Richardson <neal@crunch.io>

**Repository** CRAN

**Date/Publication** 2018-05-02 20:33:05 UTC

## R topics documented:

|   |    |
|---|----|
| addGeoMetadata . . . . .                      | 6  |
| addSubvariable . . . . .                      | 7  |
| addSummaryStat . . . . .                      | 8  |
| addVariables . . . . .                        | 10 |
| appendDataset . . . . .                       | 11 |
| appendStream . . . . .                        | 11 |
| as.environment,CrunchDataset-method . . . . . | 12 |
| as.vector,CrunchExpr-method . . . . .         | 12 |
| availableGeodataFeatures . . . . .            | 13 |
| batches . . . . .                             | 14 |
| c-categories . . . . .                        | 14 |
| catalog-dataframes . . . . .                  | 15 |
| catalog-extract . . . . .                     | 16 |
| catalog-length . . . . .                      | 19 |

|                                  |    |
|----------------------------------|----|
| Categories-class . . . . .       | 20 |
| categoriesFromLevels . . . . .   | 21 |
| cd . . . . .                     | 22 |
| changeCategoryID . . . . .       | 23 |
| cleanseBatches . . . . .         | 24 |
| collapseCategories . . . . .     | 24 |
| combine . . . . .                | 25 |
| compareDatasets . . . . .        | 26 |
| conditionalTransform . . . . .   | 27 |
| consent . . . . .                | 28 |
| ContextManager . . . . .         | 29 |
| copyOrder . . . . .              | 30 |
| copyVariable . . . . .           | 30 |
| createWithPreparedData . . . . . | 31 |
| crtabs . . . . .                 | 32 |
| crunch . . . . .                 | 32 |
| crunch-cut . . . . .             | 33 |
| crunch-uni . . . . .             | 34 |
| crunchBox . . . . .              | 35 |
| CrunchDataFrame . . . . .        | 37 |
| CrunchDataset-class . . . . .    | 38 |
| CrunchGeography-class . . . . .  | 38 |
| CrunchVariable-class . . . . .   | 39 |
| cube-computing . . . . .         | 40 |
| cube-methods . . . . .           | 41 |
| cube-missingness . . . . .       | 43 |
| cube-residuals . . . . .         | 43 |
| dashboard . . . . .              | 44 |
| dataset-extract . . . . .        | 45 |
| dataset-owner . . . . .          | 46 |
| dataset-to-R . . . . .           | 47 |
| dataset-update . . . . .         | 48 |
| dataset-variables . . . . .      | 50 |
| DatasetOrder-class . . . . .     | 51 |
| datasets . . . . .               | 51 |
| dedupeOrder . . . . .            | 52 |
| delete . . . . .                 | 53 |
| deleteDataset . . . . .          | 54 |
| deleteSubvariables . . . . .     | 55 |
| deleteVariables . . . . .        | 55 |
| derivations . . . . .            | 56 |
| describe . . . . .               | 58 |
| dichotomize . . . . .            | 60 |
| dim-dataset . . . . .            | 61 |
| dropRows . . . . .               | 62 |
| duplicated . . . . .             | 63 |
| embedCrunchBox . . . . .         | 63 |
| exclusion . . . . .              | 64 |

|   |     |
|---|-----|
| exportDataset . . . . .                             | 65  |
| expressions . . . . .                               | 66  |
| expropriateUser . . . . .                           | 68  |
| filter-catalog . . . . .                            | 68  |
| flattenOrder . . . . .                              | 69  |
| flipArrays . . . . .                                | 69  |
| folder . . . . .                                    | 70  |
| forkDataset . . . . .                               | 71  |
| fortify . . . . .                                   | 71  |
| getTeams . . . . .                                  | 72  |
| grouped . . . . .                                   | 72  |
| hiddenVariables . . . . .                           | 73  |
| hide . . . . .                                      | 73  |
| hideVariables . . . . .                             | 74  |
| http-methods . . . . .                              | 75  |
| importMultitable . . . . .                          | 75  |
| index.table . . . . .                               | 76  |
| Insertions-class . . . . .                          | 77  |
| interactVariables . . . . .                         | 79  |
| is-na-categories . . . . .                          | 80  |
| is-public . . . . .                                 | 81  |
| is-selected-categories . . . . .                    | 82  |
| is.archived,DatasetCatalog-method . . . . .         | 83  |
| is.dataset . . . . .                                | 84  |
| is.editor . . . . .                                 | 85  |
| joinDatasets . . . . .                              | 86  |
| listDatasets . . . . .                              | 87  |
| loadDataset . . . . .                               | 88  |
| locateEntity . . . . .                              | 89  |
| lock . . . . .                                      | 89  |
| login . . . . .                                     | 90  |
| logout . . . . .                                    | 90  |
| makeArray . . . . .                                 | 91  |
| makeCaseVariable . . . . .                          | 91  |
| makeMRFromText . . . . .                            | 93  |
| makeWeight . . . . .                                | 93  |
| matchCatToFeat . . . . .                            | 95  |
| me . . . . .  | 95  |
| members<-,CrunchTeam,MemberCatalog-method . . . . . | 96  |
| merge . . . . .                                     | 97  |
| mergeFork . . . . .                                 | 98  |
| modifyWeightVariables . . . . .                     | 98  |
| moveToGroup . . . . .                               | 99  |
| multitable-catalog . . . . .                        | 100 |
| mv . . . . .  | 101 |
| na-omit-categories . . . . .                        | 102 |
| name,AbstractCategory-method . . . . .              | 103 |
| names,BatchCatalog-method . . . . .                 | 104 |

|                                  |     |
|----------------------------------|-----|
| newDataset                       | 106 |
| newFilter                        | 107 |
| newMultitable                    | 107 |
| newProject                       | 108 |
| noTransforms                     | 109 |
| ordering                         | 110 |
| owners                           | 111 |
| pendingStream                    | 111 |
| permissions                      | 112 |
| pk                               | 112 |
| pollProgress                     | 113 |
| population                       | 113 |
| preCrunchBoxCheck                | 114 |
| prepareDataForCrunch             | 115 |
| project-icon                     | 116 |
| projects                         | 116 |
| refresh                          | 117 |
| removeEmptyGroups                | 117 |
| resetPassword                    | 118 |
| restoreVersion                   | 119 |
| rmdir                            | 119 |
| saveVersion                      | 120 |
| scoreCatToFeat                   | 121 |
| searchDatasets                   | 121 |
| self                             | 122 |
| session                          | 122 |
| session-extract                  | 123 |
| setOrder                         | 124 |
| settings                         | 124 |
| share                            | 125 |
| shoji-index                      | 126 |
| ShojiObject-class                | 126 |
| ShojiOrder-extract               | 127 |
| ShojiOrder-length                | 129 |
| ShojiOrder-slots                 | 130 |
| show,ShojiFolder-method          | 131 |
| showTransforms,CrunchCube-method | 133 |
| Subtotal-class                   | 134 |
| subtotalArray,CrunchCube-method  | 136 |
| Subvariables-class               | 138 |
| subvars-extract                  | 139 |
| SummaryStat-class                | 141 |
| tabBook                          | 142 |
| tabbook-methods                  | 143 |
| table                            | 144 |
| temp.options                     | 145 |
| tojson-crunch                    | 145 |
| toVariable                       | 146 |

|   |     |
|---|-----|
| Transforms-class . . . . .                          | 148 |
| type . . . . .                                      | 149 |
| unbind . . . . .                                    | 150 |
| unshare . . . . .                                   | 151 |
| var-categories . . . . .                            | 151 |
| variable-as-methods . . . . .                       | 152 |
| variable-update . . . . .                           | 154 |
| VariableCatalog-class . . . . .                     | 156 |
| VariableDefinition . . . . .                        | 156 |
| variableMetadata . . . . .                          | 157 |
| VariableOrder-class . . . . .                       | 157 |
| versions . . . . .                                  | 158 |
| webApp . . . . .                                    | 159 |
| weight . . . . .                                    | 159 |
| weightVariables . . . . .                           | 160 |
| which . . . . .                                     | 161 |
| with-context-manager . . . . .                      | 161 |
| write.csv.gz . . . . .                              | 162 |
| [,CrunchExpr,CrunchLogicalExpr,ANY-method . . . . . | 162 |
| \$.AbstractCategory-method . . . . .                | 163 |

## Index 165

---

|                |  |
|----------------|--|
| addGeoMetadata | <i>Add geodata metadata to a crunch variable</i> |
|----------------|--|

---

### Description

If the variable matches a single geographic shapefile hosted by crunch, addGeoMetadata will make the appropriate [CrunchGeography](#) to add to a variable's `geo()` metadata. It matches based on how well the contents of the variable match the feature properties that are in each shapefile.

### Usage

```
addGeoMetadata(variable, ...)
```

### Arguments

|          |  |
|----------|--|
| variable | a Crunch variable to use for matching. This must be either a text or a categorical variable.   |
| ...      | arguments passed on to <code>matchCatToFeat()</code> for example a set of available geographic features as <code>all_features</code> if you want to limit the number of features to be considered. |

**Details**

If more than one property of the same geographic shapefile has the same highest matching score, the first one will be used.

If more than one geographic shapefile has the same highest matching score, an error will be printed listing the geographic shapefiles that matched. Information from this error can be used to setup an appropriate [CrunchGeography](#) by hand to connect a variable with the metadata needed.

**Value**

a [CrunchGeography](#) object that can be assigned into `geo(variable)`

**Examples**

```
## Not run:  
geo(ds$state) <- addGeoMetadata(ds$state)  
  
## End(Not run)
```

---

|                |                                    |
|----------------|------------------------------------|
| addSubvariable | <i>Add subvariable to an array</i> |
|----------------|------------------------------------|

---

**Description**

Add subvariable to an array

**Usage**

```
addSubvariable(variable, subvariable)  
  
addSubvariables(variable, subvariable)
```

**Arguments**

|             |  |
|-------------|--|
| variable    | the array variable to modify   |
| subvariable | the subvariable to add, or a list of those to add, or a dataset subset. You can supply variables, variable definitions or lists of variables and variable definitions. |

**Value**

variable with the indicated subvariables added.

**See Also**

[subvariables](#)

**Examples**

```
## Not run:
ds$allpets <- addSubvariable(ds$allpets, ds$allpets_4)
ds$petloc <- addSubvariables(ds$petloc, ds[c("petloc_school", "petloc_daycare")])

## End(Not run)
```

---

|                             |   |
|-----------------------------|---|
| <code>addSummaryStat</code> | <i>Add summary statistics to a CrunchCube</i> |
|-----------------------------|---|

---

**Description**

Use `addSummaryStat()` to add a summary statistic to a `CrunchCube` object. If not otherwise specified, the summary statistic will be mean and be placed at the bottom of the cube. You can change those defaults by passing any value you can use with `SummaryStat()` (e.g. `position`, `categories`, `after`).

**Usage**

```
addSummaryStat(cube, stat = c("mean", "median"), var, ...)
```

**Arguments**

|                   |   |
|-------------------|---|
| <code>cube</code> | a <code>CrunchCube</code> to add stats to   |
| <code>stat</code> | a character with the summary statistic to include (default: "mean")   |
| <code>var</code>  | a character with the name of the dimension variable to add the summary statistic for generally the alias of the variable in Crunch, but might include Crunch functions like <code>rollup()</code> , <code>bin()</code> , etc. |
| <code>...</code>  | options to pass to <code>SummaryStat()</code> (e.g., <code>position</code> , <code>after</code> , etc.)   |

**Value**

a `CrunchCube` with the summary statistic Insertion added to the transforms of the variable specified

**See Also**

`SummaryStat`

**Examples**

```
## Not run:
pet_feelings
#
#feelings      animals
#  cats dogs
# extremely happy      9   5
# somewhat happy     12  12
# neutral             12   7
```



```

# somewhat unhappy 10 10
# extremely unhappy 11 12

# add a mean summary statistic to a CrunchCube
addSummaryStat(pet_feelings, stat = "mean", var = "feelings")
#
# animals
#feelings cats dogs
# extremely happy 9 5
# somewhat happy 12 12
# neutral 12 7
# somewhat unhappy 10 10
#extremely unhappy 11 12
# mean 4.90740740740741 4.34782608695652

# we can also store the CrunchCube for use elsewhere
pet_feelings <- addSummaryStat(pet_feelings, stat = "mean", var = "feelings")
pet_feelings
#
# animals
#feelings cats dogs
# extremely happy 9 5
# somewhat happy 12 12
# neutral 12 7
# somewhat unhappy 10 10
#extremely unhappy 11 12
# mean 4.90740740740741 4.34782608695652

# `addSummaryStat` returns a CrunchCube that has had the summary statistic
# added to it, so that you can still use the Crunch logic for multiple
# response variables, missingness, etc.
class(pet_feelings)
#[1] "CrunchCube"
#attr(,"package")
#[1] "crunch"

# Since `pet_feelings` is a CrunchCube, although it has similar properties
# and behaviors to arrays, it is not a R array:
is.array(pet_feelings)
#[1] FALSE

# cleanup transforms
transforms(pet_feelings) <- NULL
# add a median summary statistic to a CrunchCube
pet_feelings <- addSummaryStat(pet_feelings, stat = "median", var = "feelings")
pet_feelings
#
# animals
#feelings cats dogs
# extremely happy 9 5
# somewhat happy 12 12
# neutral 12 7
# somewhat unhappy 10 10
#extremely unhappy 11 12
# median 5 5

```

```

# additionally, if you want a true matrix object from the CrunchCube, rather
# than the CrunchCube object itself, `applyTransforms()` will return the
# array with the summary statistics (just like subtotals and headings)
pet_feelings_array <- applyTransforms(pet_feelings)
pet_feelings_array
#           animals
#feelings   cats   dogs
# extremely happy     9     5
# somewhat happy     12    12
#           neutral     12     7
# somewhat unhappy    10    10
#extremely unhappy    11    12
#           median     5     5

# and we can see that this is an array and no longer a CrunchCube
is.array(pet_feelings_array)
#[1] TRUE

## End(Not run)

```

---

addVariables

*Add multiple variables to a dataset*


---

### Description

This function lets you add more than one variable at a time to a dataset. If you have multiple variables to add, this function will be faster than doing `ds$var <- value` assignment because it doesn't refresh the dataset's state in between variable POST requests.

### Usage

```
addVariables(dataset, ...)
```

### Arguments

dataset            a CrunchDataset  
...                [VariableDefinitions](#) or a list of VariableDefinitions.

### Value

dataset with the new variables added (invisibly)

---

|               |   |
|---------------|---|
| appendDataset | <i>Append one Crunch dataset to another</i> |
|---------------|---|

---

**Description**

Append one Crunch dataset to another

**Usage**

```
appendDataset(dataset1, dataset2, autorollback)
```

**Arguments**

|              |   |
|--------------|---|
| dataset1     | a CrunchDataset   |
| dataset2     | another CrunchDataset, or possibly a data.frame. If dataset2 is not a Crunch dataset, it will be uploaded as a new dataset before appending. If it is a Crunch-Dataset, it may be subsetted with a filter expression on the rows and a selection of variables on the columns. |
| autorollback | Deprecated. This option no longer does anything.  |

**Value**

dataset1, updated with dataset2, potentially filtered on rows and variables, appended to it.

---

|              |   |
|--------------|---|
| appendStream | <i>Manually trigger a pending append to a dataset</i> |
|--------------|---|

---

**Description**

Crunch allows you to stream data to a dataset. Streaming data is useful for datasets which have frequent updates (see the [Crunch API documentation](#) for more information). Crunch automatically appends streamed data periodically; however, if you would like to trigger appending pending streamed data to a dataset, you can call `appendStream()`.

**Usage**

```
appendStream(ds)
```

**Arguments**

|    |                 |
|----|-----------------|
| ds | a CrunchDataset |
|----|-----------------|

**Value**

the dataset with pending stream data appended.

---

as.environment, CrunchDataset-method  
*as.environment method for CrunchDataset*

---

### Description

This method allows you to eval within a Dataset.

### Usage

```
## S4 method for signature 'CrunchDataset'
as.environment(x)
```

### Arguments

x                      CrunchDataset

### Value

an environment in which named objects are (promises that return) CrunchVariables.

---

as.vector, CrunchExpr-method  
*Convert Variables to local R objects*

---

### Description

Crunch Variables reside on the server, allowing you to work with datasets that are too big to bring into memory on your machine. Many functions, such as max, mean, and `crtabs()`, translate your commands into API queries and return only the result. But, not every operation you'll want to perform has been implemented on the Crunch servers. If you need to do something beyond what is currently supported, you can bring a variable's data into R with `as.vector(ds$var)` and work with it like any other R vector.

### Usage

```
## S4 method for signature 'CrunchExpr'
as.vector(x, mode = "any")

## S4 method for signature 'CrunchVariable'
as.vector(x, mode = "any")
```

**Arguments**

|      |   |
|------|---|
| x    | a CrunchVariable  |
| mode | for Categorical variables, one of either "factor" (default, which returns the values as factor); "numeric" (which returns the numeric values); or "id" (which returns the category ids). If "id", values corresponding to missing categories will return as the underlying integer codes; i.e., the R representation will not have any NA elements. Otherwise, missing categories will all be returned NA. For non-Categorical variables, the mode argument is ignored. |

**Details**

as.vector transfers data from Crunch to a local R session. Note: as.vector returns the vector in the row order of the dataset. If filters are set that specify an order that is different from the row order of the dataset, the results will ignore that order. If you need the vector ordered in that way, use syntax like as.vector(ds\$var)[c(10, 5, 2)] instead.

**Value**

an R vector of the type corresponding to the Variable. E.g. CategoricalVariable yields type factor by default, NumericVariable yields numeric, etc.

**See Also**

[as.data.frame](#) for another interface for (lazily) fetching data from the server as needed; [exportDataset\(\)](#) for pulling all of the data from a dataset.

---

availableGeodataFeatures

*Get the property features for available geographies*

---

**Description**

Get the property features for available geographies

**Usage**

```
availableGeodataFeatures(x = getAPIRoot(), geodatum_fields = c("name",
  "description", "location"))
```

**Arguments**

|                 |   |
|-----------------|---|
| x               | an API root address (default: the R-session default)  |
| geodatum_fields | character, what pieces of information about each geodatum should be retained? (default: 'c("name", "description", "location")') |

**Value**

a dataframe with all of the available features and geographies for matching

---

|         |   |
|---------|---|
| batches | <i>See the appended batches of this dataset</i> |
|---------|---|

---

**Description**

See the appended batches of this dataset

**Usage**

```
batches(x)
```

**Arguments**

x                    a CrunchDataset

**Value**

a BatchCatalog

---

|              |   |
|--------------|---|
| c-categories | <i>S3 method to concatenate Categories and Category objects</i> |
|--------------|---|

---

**Description**

S3 method to concatenate Categories and Category objects

**Usage**

```
## S3 method for class 'Categories'
c(...)

## S3 method for class 'Category'
c(...)
```

**Arguments**

...                    see [c](#)

**Value**

An object of class [Categories](#)

**Examples**

```

cat.a <- Category(name="First", id=1, numeric_value=1, missing=FALSE)
cat.b <- Category(name="Second", id=2)
cat.c <- Category(name="Third", id=3, missing=TRUE)
cats.1 <- Categories(cat.a, cat.b)
identical(cats.1, c(cat.a, cat.b))
identical(c(cats.1, cat.c), Categories(cat.a, cat.b, cat.c))

```

---

catalog-dataframes      *as.data.frame* method for catalog objects

---

**Description**

This method gives you a view of a catalog, such as a `VariableCatalog`, as a `data.frame` in order to facilitate further exploration.

**Usage**

```

## S3 method for class 'VariableCatalog'
as.data.frame(x, row.names = NULL,
  optional = FALSE, keys = c("alias", "name", "type"), ...)

## S3 method for class 'ShojiCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  ...)

## S3 method for class 'BatchCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  keys = c("id", "status"), ...)

## S3 method for class 'FilterCatalog'
as.data.frame(x, row.names = NULL, optional = FALSE,
  keys = c("name", "id", "is_public"), ...)

```

**Arguments**

|                        |  |
|------------------------|--|
| <code>x</code>         | A catalog object   |
| <code>row.names</code> | A character vector of elements to use as row labels for the resulting <code>data.frame</code> , or <code>NULL</code> , the default, adds no row labels.  |
| <code>optional</code>  | part of <code>as.data.frame</code> signature. Ignored.   |
| <code>keys</code>      | A character vector of the catalog attributes that you would like included in the <code>data.frame</code> . To include all attributes, set <code>keys</code> to <code>TRUE</code> , which is the default for some catalogs. Other catalog classes specify a narrower default: <ul style="list-style-type: none"> <li>• <code>VariableCatalog</code>: <code>c("alias", "name", "type")</code></li> <li>• <code>BatchCatalog</code>: <code>c("id", "status")</code></li> <li>• <code>FilterCatalog</code>: <code>c("name", "id", "is_public")</code></li> </ul> |
| <code>...</code>       | Additional arguments passed to <code>data.frame</code>   |

**Details**

Modifying the `data.frame` produced by this function will not update the objects on the Crunch server. Other methods exist for updating the metadata in the variable catalog, for example. See `vingette("variables", package = "crunch")`.

**Value**

A `data.frame` including metadata about each entity contained in the catalog. The fields in the `data.frame` match the `keys` argument provided to the function, and each row represents an entity.

**Examples**

```
## Not run:
ds <- loadDataset("iris")
vars <- variables(ds)
var_df <- as.data.frame(vars, keys = TRUE)
# With row names
as.data.frame(vars, row.names = urls(vars))

## End(Not run)
```

---

catalog-extract

*Extract and modify subsets of Catalog-type objects*

---

**Description**

Extract and modify subsets of Catalog-type objects

**Usage**

```
## S4 method for signature 'DatasetCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'DatasetCatalog,character,missing,DatasetTuple'
x[[i, j]] <- value

## S4 method for signature 'FilterCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'FilterCatalog,character,missing,CrunchLogicalExpr'
x[[i,
  j]] <- value

## S4 replacement method for signature 'FilterCatalog,numeric,missing,CrunchLogicalExpr'
x[[i,
  j]] <- value
```



```
## S4 replacement method for signature 'FilterCatalog,character,missing,CrunchFilter'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'FilterCatalog,numeric,missing,CrunchFilter'  
x[[i, j]] <- value  
  
## S4 method for signature 'MemberCatalog,character'  
x[[i, j, ...]]  
  
## S4 replacement method for signature 'MemberCatalog,ANY,missing,ANY'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'MemberCatalog,character,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 method for signature 'MultitableCatalog,numeric'  
x[[i, j, ...]]  
  
## S4 replacement method for signature 'MultitableCatalog,character,missing,formula'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'MultitableCatalog,numeric,missing,formula'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'MultitableCatalog,ANY,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 method for signature 'PermissionCatalog,character'  
x[[i, j, ...]]  
  
## S4 method for signature 'ProjectCatalog,numeric'  
x[[i, j, ...]]  
  
## S4 replacement method for signature 'ProjectCatalog,character,missing,list'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ProjectCatalog,character,missing,CrunchProject'  
x[[i,  
  j]] <- value  
  
## S4 method for signature 'ShojiCatalog,character,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'ShojiCatalog,numeric,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'ShojiCatalog,logical,ANY'  
x[i, j, ..., drop = TRUE]
```

```
## S4 method for signature 'ShojiCatalog,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiCatalog,ANY'
x[[i, j, ...]]

## S4 method for signature 'ShojiCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'ShojiCatalog'
x$name

## S4 replacement method for signature 'ShojiCatalog'
x$name <- value

## S4 replacement method for signature 'ShojiCatalog,ANY,missing,ShojiCatalog'
x[i, j] <- value

## S4 method for signature 'ShojiFolder,numeric'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'ShojiFolder,character'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'TeamCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'TeamCatalog,character,missing,list'
x[[i, j]] <- value

## S4 replacement method for signature 'TeamCatalog,character,missing,CrunchTeam'
x[[i, j]] <- value

## S4 method for signature 'UserCatalog,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'UserCatalog,character'
x[[i, j, ...]]

## S4 method for signature 'VariableCatalog,numeric'
x[[i, j, ...]]

## S4 replacement method for signature 'VariableCatalog,character,missing,VariableTuple'
x[[i,
  j]] <- value

## S4 replacement method for signature 'VariableCatalog,character,missing,CrunchVariable'
```

```

x[[i,
  j]] <- value

## S4 method for signature 'VariableCatalog,VariableOrder,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'VariableCatalog,VariableGroup,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature
## 'VariableCatalog,VariableOrder,missing,VariableCatalog'
x[i,
  j] <- value

## S4 replacement method for signature
## 'VariableCatalog,VariableGroup,missing,VariableCatalog'
x[i,
  j] <- value

```

### Arguments

|       |  |
|-------|--|
| x     | a Catalog object   |
| i     | which catalog elements to extract  |
| j     | Invalid  |
| ...   | additional arguments (for example secondary a vector of elements to match against like emails(x) or owners(x) by default this is names(x)) |
| value | For updating, an object of the appropriate class and size to insert  |
| drop  | Invalid  |
| name  | for \$, the same as i for []   |

### Value

A subset of x if extracting, otherwise x duly modified

---

|                |                          |
|----------------|--------------------------|
| catalog-length | <i>Length of Catalog</i> |
|----------------|--------------------------|

---

### Description

Length of Catalog

### Usage

```

## S4 method for signature 'ShojiCatalog'
length(x)

```

**Arguments**

x                    a Catalog

**Value**

Integer: the number of elements in the index list

---

Categories-class            *Categories in CategoricalVariables*

---

**Description**

CategoricalVariables, as well as the array types composed from Categoricals, contain Categories. Categories are a subclass of list that contains only Category objects. Category objects are themselves subclasses of lists and contain the following fields: "name", "id", "numeric\_value", "missing", and optionally "selected".

**Usage**

```
Categories(..., data = NULL)

Category(..., data = NULL)

## S4 method for signature 'AbstractCategories,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'AbstractCategories,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'AbstractCategories,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'AbstractCategories,character,ANY,ANY'
x[i, j, ...] <- value

## S4 method for signature 'AbstractCategories,character'
x[[i, j, ...]]

## S4 replacement method for signature 'AbstractCategories,character,ANY,ANY'
x[[i, j, ...]] <- value

## S4 method for signature 'AbstractCategories'
names(x)

## S4 replacement method for signature 'AbstractCategories'
names(x) <- value
```

```
## S4 method for signature 'AbstractCategories'
ids(x)

## S4 replacement method for signature 'Categories,ANY,ANY,ANY'
x[i, j, ...] <- value

## S4 replacement method for signature 'Categories'
ids(x) <- value

## S4 method for signature 'Categories'
values(x)

## S4 replacement method for signature 'Categories'
values(x) <- value
```

### Arguments

|       |   |
|-------|---|
| ...   | additional arguments to [, ignored  |
| data  | For the constructor functions <code>Category</code> and <code>Categories</code> , you can either pass in attributes via ... or you can create the objects with a fully defined list representation of the objects via the <code>data</code> argument. See the examples. |
| x     | For the attribute getters and setters, an object of class <code>Category</code> or <code>Categories</code>  |
| i     | For the [ methods, just as with list extract methods  |
| j     | Invalid argument to [, but in the generic's signature   |
| drop  | Invalid argument to [, but in the generic's signature   |
| value | For [ <code>&lt;-</code> , the replacement <code>Category</code> to insert  |

### Examples

```
cat.a <- Category(name="First", id=1, numeric_value=1, missing=FALSE)
cat.b <- Category(data=list(name="First", id=1, numeric_value=1, missing=FALSE))
identical(cat.a, cat.b)
cat.c <- Category(name="Second", id=2)
cats.1 <- Categories(cat.a, cat.c)
cats.2 <- Categories(data=list(cat.a, cat.c))
identical(cats.1, cats.2)
```

---

categoriesFromLevels *Convert a factor's levels into Crunch categories.*

---

### Description

Crunch categorical variables have slightly richer metadata than R's factor variables. This function generates a list of category data from a factor's levels which can then be further manipulated in R before being imported into Crunch.

**Usage**

```
categoriesFromLevels(level_vect)
```

**Arguments**

level\_vect      A character vector containing the levels of a factor. Usually obtained by running `base::levels()`

**Value**

A list with each category levels id, name, numeric\_value, and missingness.

**Examples**

```
categoriesFromLevels(levels(iris$Species))
```

---

|    |                                   |
|----|-----------------------------------|
| cd | <i>Change to different folder</i> |
|----|-----------------------------------|

---

**Description**

Like cd in a file system, this function takes you to a different folder, given a relative path specification.

**Usage**

```
cd(x, path, create = FALSE)
```

**Arguments**

x                      A CrunchDataset or VariableFolder

path                    A character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default, configurable via `options(crunch.delimiter)`). The path is interpreted as relative to the location of the folder x (when x is a dataset, that means the root, top-level folder). path may also be a VariableFolder object.

create                 logical: if the folder indicated by path does not exist, should it be created? Default is FALSE. Argument mainly exists for the convenience of `mv()`, which moves variables to a folder and ensures that the folder exists. You can call cd directly with `create=TRUE`, though that seems unnatural.

**Value**

A VariableFolder

**See Also**

`mv()` to move entities to a folder; `rmdir()` to delete a folder; `base::setwd()` if you literally want to change your working directory in your local file system, which `cd()` does not do

**Examples**

```
## Not run:
ds <- loadDataset("Example survey")
demo <- cd(ds, "Demographics")
names(demo)
# Or with %>%
require(magrittr)
ds <- ds %>%
  cd("Demographics") %>%
  names()
# Can combine with mv() and move things with relative paths
ds %>%
  cd("Key Performance Indicators/Brand X") %>%
  mv("nps_x", "../Net Promoters")

## End(Not run)
```

---

changeCategoryID

---

*Change the id of a category for a categorical variable*


---

**Description**

Changes the id of a category from an existing value to a new one. The variable can be a categorical, categorical array, or multiple response variable. The category changed will have the same numeric value and missing status as before. The one exception to this is if the numeric value is the same as the id, then the new numeric value will be the same as the new id.

**Usage**

```
changeCategoryID(variable, from, to)
```

**Arguments**

|          |   |
|----------|---|
| variable | the variable in a crunch dataset that will be changed (note: the variable must be categorical, categorical array, or multiple response) |
| from     | the (old) id identifying the category you want to change  |
| to       | the (new) id for the category   |

**Value**

variable with category from and all associated data values mapped to id to

### Examples

```
## Not run:  
ds$country <- changeCategoryID(ds$country, 2, 6)  
  
## End(Not run)
```

---

|                |                                      |
|----------------|--------------------------------------|
| cleanseBatches | <i>Remove batches from a dataset</i> |
|----------------|--------------------------------------|

---

### Description

Sometimes append operations do not succeed, whether due to conflicts between the two datasets or other server-side issues. Failed appends can leave behind "error" status batch records, which can cause confusion. This function lets you delete batches that don't match the status or statuses you want to keep.

### Usage

```
cleanseBatches(dataset, keep = c("imported", "appended"))
```

### Arguments

|         |   |
|---------|---|
| dataset | CrunchDataset   |
| keep    | character the statuses that you want to keep. By default, batches that don't have either "imported" or "appended" status will be deleted. |

### Value

dataset with the specified batches removed.

---

|                    |                                    |
|--------------------|------------------------------------|
| collapseCategories | <i>Combine Categories in place</i> |
|--------------------|------------------------------------|

---

### Description

This function allows you to combine the categories of a variable without making a copy of the variable.

### Usage

```
collapseCategories(var, from, to)
```



**Arguments**

|      |   |
|------|---|
| var  | A categorical Crunch variable                         |
| from | A character vector of categories you want to combine. |
| to   | A character string with the destination category.     |

**Value**

the variable duly modified

**See Also**

[combine\(\)](#)

---

|         |  |
|---------|--|
| combine | <i>Combine categories or responses</i> |
|---------|--|

---

**Description**

Crunch allows you to create a new categorical variable by combining the categories of another variable. For instance, you might want to recode a categorical variable with three categories small, medium, and large to one that has just small and large.

**Usage**

```
combine(variable, combinations = list(), ...)
```

**Arguments**

|              |   |
|--------------|---|
| variable     | Categorical, Categorical Array, or Multiple Response variable   |
| combinations | list of named lists containing <ol style="list-style-type: none"> <li>1. "categories": category ids or names for categorical types, or for multiple response, "responses": subvariable names, aliases, or positional indices;</li> <li>2. a "name" for the new category or response; and</li> <li>3. optionally, other category ("missing", "numeric_value") or subvariable ("alias", "description") attributes. If combinations is omitted, the resulting variable will essentially be a copy (but see <a href="#">copy()</a> for a more natural way to copy variables.</li> </ol> |
| ...          | Additional variable metadata for the new derived variable   |

**Value**

A [VariableDefinition](#) that will create the new combined-category or -response derived variable. Categories/responses not referenced in combinations will be appended to the end of the combinations.

## Examples

```
## Not run:
ds$fav_pet2 <- combine(ds$fav_pet, name="Pets (combined)",
  combinations=list(list(name="Mammals", categories=c("Cat", "Dog")),
    list(name="Reptiles", categories=c("Snake", "Lizard"))))
ds$pets_owned2 <- combine(ds$allpets, name="Pets owned (collapsed)",
  combinations=list(list(name="Mammals", responses=c("Cat", "Dog"))))

## End(Not run)
```

---

compareDatasets

*Compare two datasets to see how they will append*

---

## Description

When one dataset is appended to another, variables and subvariables are matched on their aliases, and then categories for variables that have them are matched on category name. This function lines up the metadata between two datasets as the append operation will so that you can inspect how well the datasets will align before you do the append.

## Usage

```
compareDatasets(A, B)
```

## Arguments

|   |               |
|---|---------------|
| A | CrunchDataset |
| B | CrunchDataset |

## Details

Calling `summary` on the return of this function will print an overview of places where the matching on variable alias and category name may lead to undesired outcomes, enabling you to alter one or both datasets to result in better alignment.

## Value

An object of class 'compareDatasets', a list of three elements: (1) 'variables', a data.frame of variable metadata joined on alias; (2) 'categories', a list of data.frames of category metadata joined on category name, one for each variable with categories; and (3) 'subvariables', a list of data.frames of subvariable metadata joined on alias, one for each array variable.

Summary output reports on (1) variables that, when matched across datasets by alias, have different types; (2) variables that have the same name but don't match on alias; (3) for variables that match and have categories, any categories that have the same id but don't match on name; (4) for array variables that match, any subvariables that have the same name but don't match on alias; and (5) array variables that, after assembling the union of their subvariables, point to subvariables that belong to other arrays.

**Examples**

```
## Not run:
  comp <- compareDataset(ds1, ds2)
  summary(comp)

## End(Not run)
```

---

conditionalTransform *Conditional transformation*

---

**Description**

Create a new variable that has values when specific conditions are met. Conditions are specified using a series of formulas: the left-hand side is the condition that must be true (a `CrunchLogicalExpr`) and the right-hand side is where to get the value if the condition on the left-hand side is true. This is commonly a Crunch variable but may be a string or numeric value, depending on the type of variable you're constructing.

**Usage**

```
conditionalTransform(..., data, else_condition = NA, type = NULL,
  categories = NULL, formulas = NULL)
```

**Arguments**

|                             |  |
|-----------------------------|--|
| <code>...</code>            | a list of conditions to evaluate (as formulas, see <a href="#">Details</a> ) as well as other properties to pass to the new conditional variable (i.e. alias, description)   |
| <code>data</code>           | a Crunch dataset object to use   |
| <code>else_condition</code> | a default value to use if none of the conditions are true (default: NA)  |
| <code>type</code>           | a character that is either "categorical", "text", "numeric" what type of output should be returned? If NULL, the type of the source variable will be used. (default: NULL) The source variables will be converted to this type if necessary. |
| <code>categories</code>     | a vector of characters if <code>type="categorical"</code> , these are all of the categories that should be in the resulting variable, in the order they should be in the resulting variable or a set of Crunch categories.                   |
| <code>formulas</code>       | a list of conditions to evaluate (as formulas, see <a href="#">Details</a> ). If specified, <code>...</code> must not contain other formulas specifying conditions.  |

**Details**

The type of the new variable can depend on the type(s) of the source variable(s). By default (`type=NULL`), the type of the new variable will be the type of all of the source variables (that is, if all of the source variables are text, the new variable type will be text, if all of the source variables are categorical, the new variable will be categorical). If there are multiple types in the source variables, the result will be a text variable. The default behavior can be overridden by specifying `type = "categorical", "text", or "numeric"`.

conditionalTransform is similar to makeCaseVariable; however, conditionalTransform can use other Crunch variables as a source of a variable, whereas, makeCaseVariable can only use characters. This additional power comes at a cost: makeCaseVariable can be executed entirely on Crunch servers, so no data needs to be downloaded or uploaded to/from the local R session. conditionalTransform on the other hand will download the data necessary to construct the new variable.

## Value

a Crunch VariableDefinition

## Examples

```
## Not run:

ds$cat_opinion <- conditionalTransform(pet1 == 'Cat' ~ Opinion1,
                                       pet2 == 'Cat' ~ Opinion2,
                                       pet3 == 'Cat' ~ Opinion3,
                                       data = ds,
                                       name = "Opinion of Cats")

## End(Not run)
```

---

consent

*Give consent to do things that require permission*

---

## Description

Potentially destructive actions require that you confirm that you really want to do them. If you're running a script and you know that you want to perform those actions, you can preemptively provide consent.

## Usage

```
consent()

with_consent(expr)
```

## Arguments

expr                    Code to evaluate with consent

## Value

consent returns an S3 class "contextManager" object, which you can use with with. with\_consent evaluates its arguments inside the consent context.

**See Also**

[with-context-manager ContextManager](#)

**Examples**

```
## Not run:  
with(consent(), delete(ds))  
# Equivalent to:  
with_consent(delete(ds))  
  
## End(Not run)
```

---

|                |                         |
|----------------|-------------------------|
| ContextManager | <i>Context managers</i> |
|----------------|-------------------------|

---

**Description**

Context managers

**Usage**

```
ContextManager(enter = function() { }, exit = function() { },  
error = NULL, as = NULL)
```

**Arguments**

|       |  |
|-------|--|
| enter | function to run before taking actions  |
| exit  | function to run after taking actions   |
| error | optional function to run if an error is thrown   |
| as    | character optional way to specify a default name for assigning the return of the enter function. |

**Value**

an S3 class "contextManager" object

**See Also**

[with-context-manager](#)

---

`copyOrder`*Copy the variable order from one dataset to another.*

---

**Description**

Copy the variable order from one dataset to another.

**Usage**

```
copyOrder(source, target)
```

**Arguments**

|                     |   |
|---------------------|---|
| <code>source</code> | the dataset you want to copy the order from |
| <code>target</code> | the dataset you want to copy the order to   |

**Value**

returns an object of class `VariableOrder` (which can be assigned to a dataset with `ordering`)

**Examples**

```
## Not run:  
ordering(ds) <- copyOrder(ds1, ds)  
  
## End(Not run)
```

---

`copyVariable`*Copy a variable*

---

**Description**

Makes a copy of a Crunch variable on the server.

**Usage**

```
copyVariable(x, deep = FALSE, ...)  
  
copy(x, deep = FALSE, ...)
```

**Arguments**

|      |   |
|------|---|
| x    | a CrunchVariable to copy  |
| deep | logical: should this be a deep copy, in which there is no dependence on the original variable, or a shallow one, in which the copy is more of a symbolic link? Default is FALSE, meaning symlink.                         |
| ...  | Additional metadata to give to the new variable. If not given, the new variable will have a name that is the same as the original but with " (copy)" appended, and its alias will be the old alias with "_copy" appended. |

**Details**

Copies can be shallow (linked) or deep. Shallow copying is faster and is preferable unless a true hard copy is required. Shallow copies are effectively pointers to the original variable, and then you append data to the original variable or otherwise alter its values, the values in the copy automatically update. This linking may be desirable, but it comes with some limitations. First, you cannot edit the values of the copy independently of the original. Second, some attributes of the copy are immutable: of note, properties of categories cannot be altered independently in the copy, but you can alter Subvariable names and ordering within arrays.

**Value**

a VariableDefinition for the copied variable. Assign into a Dataset to make the copy happen.

---

```
createWithPreparedData
```

*Upload a prepared data.frame with metadata to Crunch*

---

**Description**

If you have manually created a Crunch dataset object with [prepareDataForCrunch\(\)](#) this function allows you to upload it to the app.

**Usage**

```
createWithPreparedData(data, metadata = attr(data, "metadata"))
```

**Arguments**

|          |  |
|----------|--|
| data     | a data.frame that meets the Crunch API specification, as returned by <a href="#">prepareDataForCrunch()</a> , or a character path to a file or URL where such data has been written as CSV.                                      |
| metadata | list of Crunch metadata that corresponds to data. Default is the "metadata" attribute of data, as returned by <a href="#">prepareDataForCrunch</a> , or a character path to a file where such metadata has been written as JSON. |

**Value**

A CrunchDataset.

---

|        |   |
|--------|---|
| crtabs | <i>Crunch xtabs: Crosstab and otherwise aggregate variables in a Crunch Dataset</i> |
|--------|---|

---

### Description

Create a contingency table or other aggregation from cross-classifying variables in a `CrunchDataset`.

### Usage

```
crtabs(formula, data, weight = crunch::weight(data), useNA = c("no",
  "ifany", "always"))
```

### Arguments

|         |  |
|---------|--|
| formula | an object of class 'formula' object with the cross-classifying variables separated by '+' on the right side of the "~". If aggregating by functions other than counts, include the aggregation expression on the left-hand side. Compare to <a href="#">stats::xtabs()</a> . |
| data    | an object of class <code>CrunchDataset</code>  |
| weight  | a <code>CrunchVariable</code> that has been designated as a potential weight variable for data, or NULL for unweighted results. Default is the currently applied <a href="#">weight</a> .  |
| useNA   | whether to include missing values in tabular results. See <a href="#">base::table()</a> .  |

### Value

an object of class `CrunchCube`

### See Also

[weight\(\)](#)

---

|        |  |
|--------|--|
| crunch | <i>Crunch.io: instant, visual, collaborative data analysis</i> |
|--------|--|

---

### Description

**Crunch.io** provides a cloud-based data store and analytic engine. It has a **web client** for interactive data exploration and visualization. The `crunch` package for R allows analysts to interact with and manipulate Crunch datasets from within R. Importantly, this allows technical researchers to collaborate naturally with team members, managers, and clients who prefer a point-and-click interface: because all connect to the same dataset in the cloud, there is no need to email files back and forth continually to share results.



**See Also**

To learn more about using the package, see `vignette("getting-started", package="crunch")`.  
 To sign up for a Crunch.io account, visit <https://app.crunch.io/>.

---

 crunch-cut

---

*Cut a numeric Crunch variable*


---

**Description**

`crunch::cut()` is equivalent to `base::cut()` except that it operates on Crunch variables instead of in-memory R objects. The function takes a numeric variable and derives a new categorical variable from it based on the `breaks` argument. You can either break the variable into evenly spaced categories by specifying the number of breaks, or specify a numeric vector identifying the start and end point of each category. For example, specifying `breaks = 5` will break the numeric data into five evenly spaced portions while `breaks = c(1, 5, 10)` will recode the data into two groups based on whether the numeric vector falls between 1 and 5 or 5 and 10.

**Usage**

```
## S4 method for signature 'NumericVariable'
cut(x, breaks, labels = NULL, name,
    include.lowest = FALSE, right = TRUE, dig.lab = 3,
    ordered_result = FALSE, ...)
```

**Arguments**

|                             |   |
|-----------------------------|---|
| <code>x</code>              | A Crunch <code>NumericVariable</code>   |
| <code>breaks</code>         | Either a numeric vector of two or more unique cut points or a single number giving the number of intervals into which <code>x</code> is to be cut. If specifying cut points, values that are less than the smallest value in <code>breaks</code> or greater than the largest value in <code>breaks</code> will be marked missing in the resulting categorical variable.   |
| <code>labels</code>         | A character vector representing the labels for the levels of the resulting categories. The length of the labels argument should be the same as the number of categories, which is one fewer than the number of breaks. If not specified, labels are constructed using interval notation. For example, <code>[1, 5)</code> indicates that the category goes from 1 to 5. The bracket shape indicates whether the boundary value is included in the category, i.e. whether it is "closed". <code>[1, 5)</code> indicates that the interval includes (is closed on) 1 but does not include (is open on) 5. If <code>labels = FALSE</code> , simple integer codes are returned instead of a factor. |
| <code>name</code>           | The name of the resulting Crunch variable as a character string.  |
| <code>include.lowest</code> | logical, indicating if an <code>x[i]</code> equal to the lowest (or highest, for <code>right = FALSE</code> ) <code>breaks</code> value should be included.   |
| <code>right</code>          | logical, indicating if the intervals should be closed on the right (and open on the left) or vice versa.  |

`dig.lab` integer which is used when labels are not given. It determines the number of digits used in formatting the break numbers.

`ordered_result` Ignored.

`...` further arguments passed to [makeCaseVariable](#)

### Value

a Crunch [VariableDefinition](#). Assign it into the dataset to create it as a derived variable on the server.

### Examples

```
## Not run:
ds <- loadDataset("mtcars")
ds$cat_var <- cut(ds$mpg, breaks = c(10, 15, 20),
  labels = c("small", "medium"), name = "Fuel efficiency")
ds$age <- sample(1:100, 32)
ds$age4 <- cut(df$age, c(0, 30, 45, 65, 200),
  c("Youth", "Adult", "Middle-aged", "Elderly"),
  name = "Age (4 category)")

## End(Not run)
```

---

crunch-uni

*Univariate statistics on Crunch objects*

---

### Description

Univariate statistics on Crunch objects

### Usage

```
## S4 method for signature 'CrunchVariable'
mean(x, ...)

## S4 method for signature 'NumericVariable'
mean(x, ...)

## S4 method for signature 'CrunchVariable'
sd(x, na.rm = FALSE)

## S4 method for signature 'NumericVariable'
sd(x, na.rm = FALSE)

## S4 method for signature 'CrunchVariable'
min(x, na.rm)

## S4 method for signature 'NumericVariable'
```

```

min(x, na.rm = FALSE)

## S4 method for signature 'DatetimeVariable'
min(x, na.rm = FALSE)

## S4 method for signature 'CrunchVariable'
max(x, na.rm)

## S4 method for signature 'NumericVariable'
max(x, na.rm = FALSE)

## S4 method for signature 'DatetimeVariable'
max(x, na.rm = FALSE)

```

### Arguments

|       |  |
|-------|--|
| x     | a NumericVariable, or for min and max, a NumericVariable or DatetimeVariable |
| ...   | additional arguments to summary statistic function                           |
| na.rm | logical: exclude missings?   |

### See Also

[base::mean\(\)](#) [stats::sd\(\)](#) [stats::median\(\)](#) [base::min\(\)](#) [base::max\(\)](#)

---

crunchBox

*Make a CrunchBox*

---

### Description

CrunchBoxes allow you to publish results to the world.

### Usage

```
crunchBox(dataset, filters = crunch::filters(dataset), brand_colors,
          static_colors, category_color_lookup, ...)
```

```
CrunchBox(dataset, filters = crunch::filters(dataset), brand_colors,
           static_colors, category_color_lookup, ...)
```

### Arguments

|              |   |
|--------------|---|
| dataset      | A CrunchDataset, potentially a selection of variables from it   |
| filters      | FilterCatalog, or NULL for no filters. Default all filters in your catalog, <code>filters(dataset)</code> .   |
| brand_colors | an optional color vector of length 3 or less, or a named list with names 'primary', 'secondary', and 'message'. See "Details" for more about color specification. |

`static_colors` an optional vector of colors to use for categorical plots. Bars and lines are colored in the order of `static_colors`. See "Details" for more about color specification.

`category_color_lookup` an optional list of category names to colors to use for that category, wherever it appears in the data. This allows you to always see a category displayed in a specific color. See "Details" for more about color specification.

... additional metadata for the box, such as "title", "header", etc.

## Details

In addition to specifying the variables and filters to include in your `CrunchBox`, you can provide custom color palettes. The arguments `brand_colors`, `static_colors`, and `category_color_lookup` allow you to provide color lists to use. Colors should be either a valid hexadecimal string representation, like "#fa1af1", or they may also be an R named color, such as "darkgreen".

## Value

The URL to the newly created box.

## See Also

[preCrunchBoxCheck\(\)](#) to provide guidance on what you're including in the

## Examples

```
## Not run:
# Creating a CrunchBox with three variables
crunchBox(ds[c("var1", "var2", "var3")], title="New CrunchBox")

# Creating a CrunchBox changing primary, secondary, and message brand colors
crunchBox(ds[c("var1", "var2", "var3")],
          title="Branded CrunchBox",
          brand_colors = c("#ff0aa4", "#af17ff", "#260aff"))

# Creating a CrunchBox changing category-specific colors
crunchBox(ds[c("var1", "var2", "var3")],
          title="CrunchBox with category colors",
          category_color_lookup = list("agree" = "#ff0aa4",
                                       "disagree" = "#af17ff",
                                       "don't know" = "#260aff"))

## End(Not run)
```

---

|                 |                        |
|-----------------|------------------------|
| CrunchDataFrame | <i>CrunchDataFrame</i> |
|-----------------|------------------------|

---

## Description

CrunchDataFrames are designed to mimic the ways that `data.frames` are used. They should be a drop-in replacement in many places where `data.frames` are used.

## Usage

```
## S3 method for class 'CrunchDataFrame'
dim(x)

## S3 method for class 'CrunchDataFrame'
names(x)

## S3 method for class 'CrunchDataFrame'
x[i, j, drop = TRUE]

## S3 replacement method for class 'CrunchDataFrame'
x[i, j] <- value

## S3 method for class 'CrunchDataFrame'
x[[i]]

## S3 replacement method for class 'CrunchDataFrame'
x[[i]] <- value

## S3 method for class 'CrunchDataFrame'
x$i

## S3 replacement method for class 'CrunchDataFrame'
x$i <- value
```

## Arguments

|       |  |
|-------|--|
| x     | a <code>CrunchDataFrame</code>   |
| i     | indicators for rows (integers or logicals)   |
| j     | indicators for columns (names, integers, or logicals)  |
| drop  | logical. If TRUE the result is coerced to the lowest possible dimension. The default is to drop if only one column is left, but not to drop if only one row is left. |
| value | value to place (or replace) in the <code>CrunchDataFrame</code>  |

**Details**

CrunchDataFrames are generated not by downloading all of the variables from a dataset, but rather only the variables that are needed by subsequent functions. So, if you create a CrunchDataFrame, and then run a linear model using `lm()`, only the variables used by the linear model will be downloaded.

CrunchDataFrames can be altered (that is: adding more columns, removing columns, subsetting rows, etc.) with the same `[]`, `[[`, and `$` syntax as `data.frames`.

---

CrunchDataset-class    *Crunch Datasets*

---

**Description**

Crunch Datasets

---

CrunchGeography-class    *Geography properties for crunch variables*

---

**Description**

Crunch stores geographic data as variable metadata. There are a number of functions that help access and change this metadata.

**Usage**

```
CrunchGeography(..., data = NULL)

## S4 method for signature 'CrunchVariable'
geo(x)

## S4 replacement method for signature 'CrunchVariable,CrunchGeography'
geo(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
geo(x) <- value

availableGeodata(x = getAPIRoot())
```

**Arguments**

|                    |   |
|--------------------|---|
| <code>...</code>   | for CrunchGeography, named arguments from which to construct a CrunchGeography: <code>geodatum</code> , <code>feature_key</code> , and <code>match_field</code>         |
| <code>data</code>  | for CrunchGeography, list of named arguments from which to construct a CrunchGeography: <code>geodatum</code> , <code>feature_key</code> , and <code>match_field</code> |
| <code>x</code>     | a crunch variable   |
| <code>value</code> | value of the geography property to set  |

## Details

geo retrieves the geographic information associate with a variable. If there is geographic information it returns an object of class CrunchGeography otherwise it returns NULL.

CrunchGeography objects store geography metadata from a variable. There are three slots:

- geodatum an object of class CrunchGeodata which stores references to the Crunch-hosted (geotopo)json to use
- feature\_key a character string representing the feature inside of the (geotopo)json which is used to match match\_field (e.g. properties.name)
- match\_field a character string representing the variable metadata information which is used to match feature\_key to (e.g. name)

## Value

geographic information of class CrunchGeography (NULL if there is none)

## Examples

```
## Not run:  
geo(ds$location)  
  
geo(ds$location)$feature_key <- "properties.name"  
geo(ds$location)$match_field <- "name"  
  
## End(Not run)
```

---

CrunchVariable-class    *Variables in Crunch*

---

## Description

Variables are S4 objects. All inherit from the base class CrunchVariable.

## Slots

filter either NULL or CrunchLogicalExpr

tuple VariableTuple

**Description**

These functions provide an interface like `base::margin.table()` and `base::prop.table()` for the `CrunchCube` object. `CrunchCubes` contain richer metadata than standard R array objects, and they also conceal certain complexity in the data structures from the user. In particular, multiple-response variables are generally represented as single dimensions in result tables, but in the actual data, they may comprise two dimensions. These methods understand the subtleties in the `Crunch` data types and correctly compute margins and percentages off of them.

**Usage**

```
## S4 method for signature 'CrunchCube'
margin.table(x, margin = NULL)

## S4 method for signature 'CrunchCube'
prop.table(x, margin = NULL)

## S4 method for signature 'CrunchCube'
round(x, digits = 0)

## S4 method for signature 'CrunchCube'
bases(x, margin = NULL)

## S4 method for signature 'MultitableResult'
prop.table(x, margin = NULL)

## S4 method for signature 'TabBookResult'
prop.table(x, margin = NULL)

## S4 method for signature 'TabBookResult'
bases(x, margin = NULL)

## S4 method for signature 'MultitableResult'
bases(x, margin = NULL)
```

**Arguments**

|                     |  |
|---------------------|--|
| <code>x</code>      | a <code>CrunchCube</code>  |
| <code>margin</code> | index, or vector of indices to generate margin for. See <code>base::prop.table()</code> . <code>bases()</code> accepts <code>0</code> as an additional valid value for margin, which yields the unweighted counts for the query. |
| <code>digits</code> | For round, the number of decimal places to round to. See <code>base::round()</code>  |



**Details**

These functions also generalize to `MultiTableResults` and `TabBookResults`, which are returned from a `tabBook()` request. When called on one of those objects, they effectively apply over each `CrunchCube` contained in them.

`bases` is an additional method for `CrunchCubes`. When making weighted requests, `bases` allows you to access the unweighted counts for every cell in the resulting table (array). The `bases` function takes a "margin" argument to work like `margin.table`, or with `margin=0` gives all cell counts.

**Value**

When called on `CrunchCubes`, these functions return an array. Calling `prop.table` on a `MultiTableResult` returns a list of `prop.tables` of the `CrunchCubes` it contains. Likewise, `prop.table` on a `TabBookResult` returns a list of lists of `prop.tables`.

**See Also**

[base::margin.table\(\)](#) [base::prop.table\(\)](#)

---

cube-methods

*Methods on Cube objects*

---

**Description**

These methods provide an array-like interface to the `CrunchCube` object.

**Usage**

```
## S4 method for signature 'CubeDims'
dimnames(x)

## S4 method for signature 'CubeDims'
dim(x)

## S4 method for signature 'CubeDims'
is.na(x)

## S4 method for signature 'CrunchCube'
dimensions(x)

## S4 replacement method for signature 'CrunchCube,CubeDims'
dimensions(x) <- value

## S4 method for signature 'CubeDims,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchCube'
```

```

dim(x)

## S4 method for signature 'CrunchCube'
dimnames(x)

## S4 method for signature 'CrunchCube,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CubeDims'
variables(x)

## S4 method for signature 'CrunchCube'
measures(x)

## S4 method for signature 'CrunchCube'
variables(x)

## S4 method for signature 'CrunchCube'
names(x)

## S4 method for signature 'CrunchCube'
aliases(x)

## S4 method for signature 'CrunchCube'
descriptions(x)

## S4 method for signature 'CrunchCube'
types(x)

## S4 method for signature 'CrunchCube'
notes(x)

```

### Arguments

|       |   |
|-------|---|
| x     | a CrunchCube or its CubeDims component.                                 |
| value | for dimensions<- a CubeDims object to overwrite a CrunchCube dimensions |
| i     | used with [] to extract a dimension                                     |
| j     | not used  |
| ...   | not used  |
| drop  | not used  |

### Value

Generally, the same shape of result that each of these functions return when applied to an array object.

**See Also**

[cube-computing base::array](#)

---

cube-missingness      *Modify cube missing behavior*

---

**Description**

By default, CrunchCubes do not show entries for missing categories. You can include missing values in a cube with `showMissing(cube)` and hide them again with `hideMissing(cube)`.

**Usage**

```
## S4 method for signature 'CrunchCube'
showMissing(cube)

## S4 method for signature 'CrunchCube'
hideMissing(cube)

## S4 method for signature 'CrunchCube'
showIfAny(cube)
```

**Arguments**

cube                    a CrunchCube

---

cube-residuals      *Calculate standardized residuals from a CrunchCube*

---

**Description**

Standardized residuals,  $(\text{observed} - \text{expected}) / \sqrt{V}$ , where  $V$  is the residual cell variance (Agresti, 2007, section 2.4.5). Special care is taken for multiple-response variables which are in effect a series of separate tables where ‘not selected’ cells for each item are hidden.

**Usage**

```
## S4 method for signature 'CrunchCube'
rstandard(model)
```

**Arguments**

model                    A CrunchCube representing a contingency table

**Value**

an array of standardized residuals or Z-scores from the hypothesis being tested. The default method is that the joint distributions of (weighted) counts are equal to the marginal distributions of the table.

**References**

Agresti, A. (2007) *An Introduction to Categorical Data Analysis, 2nd ed.*, New York: John Wiley & Sons. Page 38.

**See Also**

[stats::chisq.test](#)

---

dashboard

*View or set a dashboard URL*

---

**Description**

You can designate a dashboard that will show when the dataset is loaded in the Crunch web app. This dashboard could be a Crunch Shiny ("Crunchy") app, a CrunchBox, an RMarkdown website or something else.

**Usage**

```
dashboard(x)
```

```
setDashboardURL(x, value)
```

```
dashboard(x) <- value
```

**Arguments**

x                   CrunchDataset

value               For the setter, a URL (character) or NULL to unset the dashboard.

**Value**

The getter returns a URL (character) or NULL. The setter returns the dataset (x).

**Examples**

```
## Not run:
dashboard(ds) <- "https://shiny.crunch.io/example/"

## End(Not run)
```

---

dataset-extract      *Subset datasets and extract variables*

---

## Description

Subset datasets and extract variables

## Usage

```
## S4 method for signature 'CrunchDataset,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,logical,missing'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,VariableGroup,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,VariableOrder,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchDataset,missing,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset,CrunchLogicalExpr,missing'
x[i, j, ...,
  drop = FALSE]

## S4 method for signature 'CrunchDataset,CrunchLogicalExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchDataset'
subset(x, ...)

## S4 method for signature 'CrunchDataset,ANY'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'CrunchDataset,character'
x[[i, ..., drop = FALSE]]

## S4 method for signature 'CrunchDataset'
x$name
```

**Arguments**

|      |   |
|------|---|
| x    | a CrunchDataset   |
| i    | As with a data.frame, there are two cases: <ol style="list-style-type: none"> <li>if no other arguments are supplied (i.e x[i], i provides for as.list extraction: columns of the dataset rather than rows. If character, identifies variables to extract based on their aliases (by default: set options(crunch.namekey.dataset="name") to use variable names); if numeric or logical, extracts variables accordingly.</li> <li>If j is specified as either x[i, j] or x[i, ], i is an object of class CrunchLogicalExpr that will define a subset of rows.</li> </ol> |
| j    | columnar extraction, as described above   |
| ...  | additional arguments  |
| drop | logical: automatically simplify a 1-column Dataset to a Variable? Default is FALSE, and the TRUE option is in fact not implemented.   |
| name | columnar extraction for \$  |

**Value**

[ yields a Dataset; [[ and \$ return a Variable

---

dataset-owner

*Get and set the owner of a dataset*

---

**Description**

Get and set the owner of a dataset

**Usage**

```
## S4 method for signature 'CrunchDataset'
owner(x)
```

```
## S4 replacement method for signature 'CrunchDataset'
owner(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | CrunchDataset   |
| value | For the setter, either a URL (character) or a Crunch object with a self method. Users and Projects are valid objects to assign as dataset owners. |

**Value**

The dataset.

---

dataset-to-R

*as.data.frame method for CrunchDataset*


---

## Description

This method is defined principally so that you can use a `CrunchDataset` as a data argument to other R functions (such as `stats::lm()`) without needing to download the whole dataset. You can, however, choose to download a true `data.frame`.

## Usage

```
## S3 method for class 'CrunchDataset'
as.data.frame(x, row.names = NULL, optional = FALSE,
  force = FALSE, categorical.mode = "factor", include.hidden = FALSE,
  row.order = NULL, ...)

## S3 method for class 'CrunchDataFrame'
as.data.frame(x, row.names = NULL,
  optional = FALSE, ...)
```

## Arguments

|                               |  |
|-------------------------------|--|
| <code>x</code>                | a <code>CrunchDataset</code> or <code>CrunchDataFrame</code>   |
| <code>row.names</code>        | part of <code>as.data.frame</code> signature. Ignored.   |
| <code>optional</code>         | part of <code>as.data.frame</code> signature. Ignored.   |
| <code>force</code>            | logical: actually coerce the dataset to <code>data.frame</code> , or leave the columns as unevaluated promises. Default is <code>FALSE</code> .  |
| <code>categorical.mode</code> | what mode should categoricals be pulled as? One of <code>factor</code> , <code>numeric</code> , <code>id</code> (default: <code>factor</code> )  |
| <code>include.hidden</code>   | logical: should hidden variables be included? (default: <code>FALSE</code> )   |
| <code>row.order</code>        | vector of indices. Which, and their order, of the rows of the dataset should be presented as (default: <code>NULL</code> ). If <code>NULL</code> , then the <code>CrunchDataset</code> order will be used. |
| <code>...</code>              | additional arguments passed to <code>as.data.frame</code> (default method).  |

## Details

By default, the `as.data.frame` method for `CrunchDataset` does not return a `data.frame` but instead `CrunchDataFrame`, which behaves like a `data.frame` without bringing the whole dataset into memory. When you access the variables of a `CrunchDataFrame`, you get an R vector, rather than a `CrunchVariable`. This allows modeling functions that require select columns of a dataset to retrieve only those variables from the remote server, rather than pulling the entire dataset into local memory.

If you call `as.data.frame` on a `CrunchDataset` with `force = TRUE`, you will instead get a true `data.frame`. You can also get this `data.frame` by calling `as.data.frame` on a `CrunchDataFrame` (effectively calling `as.data.frame` on the dataset twice)

When a `data.frame` is returned, the function coerces `Crunch Variable` values into their R equivalents using the following rules:

- Numeric variables become numeric vectors
- Text variables become character vectors
- Datetime variables become either `Date` or `POSIXt` vectors
- Categorical variables become either factors with levels matching the `Crunch Variable`'s categories (the default), or, if `categorical.mode` is specified as "id" or "numeric", a numeric vector of category ids or numeric values, respectively
- Array variables (`Categorical Array`, `Multiple Response`) are decomposed into their constituent categorical subvariables. An array with three subvariables, for example, will result in three columns in the `data.frame`.

Column names in the `data.frame` are the variable/subvariable aliases.

### Value

When called on a `CrunchDataset`, the method returns an object of class `CrunchDataFrame` unless `force = TRUE`, in which case the return is a `data.frame`. For `CrunchDataFrame`, the method returns a `data.frame`.

### See Also

[as.vector\(\)](#)

---

dataset-update

*Update a variable or variables in a dataset*

---

### Description

Update a variable or variables in a dataset

### Usage

```
## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchVariable'
x[[i]] <- value
```

```
## S4 replacement method for signature 'CrunchDataset,ANY,missing,CrunchVariable'
x[[i]] <- value
```

```
## S4 replacement method for signature 'CrunchDataset,character,missing,ANY'
x[[i]] <- value
```



```

## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchLogicalExpr'
x[[
  i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,ANY,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,character,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset'
x$name <- value

## S4 replacement method for signature 'CrunchDataset,character,missing,CrunchGeography'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,CrunchGeography'
x[[i]] <- value

## S4 replacement method for signature 'CrunchDataset,ANY,missing,list'
x[i, j] <- value

## S4 replacement method for signature 'CrunchDataset,CrunchExpr,ANY,ANY'
x[i, j] <- value

```

### Arguments

|       |  |
|-------|--|
| x     | a <code>CrunchDataset</code>   |
| i     | For <code>[</code> , a <code>CrunchLogicalExpr</code> , numeric, or logical vector defining a subset of the rows of x. For <code>[[</code> , see j for the <code>as.list</code> column subsetting.   |
| value | replacement values to insert. These can be <code>crunchExprs</code> or R vectors of the corresponding type   |
| name  | like j but for <code>\$</code>   |
| j     | if character, identifies variables to extract based on their aliases (by default: set <code>options(crunch.namekey.dataset="name")</code> to use variable names); if numeric or logical, extracts variables accordingly. Note that this is the <code>as.list</code> extraction, columns of the dataset rather than rows. |

### Value

x, modified.

---

dataset-variables      *Access a Dataset's Variables Catalog*

---

## Description

Datasets contain collections of variables. For a few purposes, such as editing variables' metadata, it is helpful to access these variable catalogs more directly.

## Usage

```
## S4 method for signature 'CrunchDataset'  
variables(x)  
  
## S4 replacement method for signature 'CrunchDataset,VariableCatalog'  
variables(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
allVariables(x)  
  
## S4 replacement method for signature 'CrunchDataset,VariableCatalog'  
allVariables(x) <- value  
  
## S4 method for signature 'SearchResults'  
variables(x)
```

## Arguments

|       |   |
|-------|---|
| x     | a Dataset                                     |
| value | For the setters, a VariableCatalog to assign. |

## Details

`variables` gives just the active variables in the dataset, while `allVariables` returns all variables, including hidden variables.

## Value

Getters return VariableCatalog; setters return x duly modified.

---

DatasetOrder-class      *Organize Datasets*

---

### Description

A DatasetOrder object is a subclass of `list` that contains DatasetGroups. DatasetGroup objects contain a group name and an set of "entities", which can be dataset references or other nested DatasetGroups.

### Slots

`group` character, the name of the DatasetGroup. In the constructor and more generally, this field can be referenced as "name" as well.

`entities` a character vector of dataset URLs, or a list containing a combination of dataset URLs and DatasetGroup objects.

---

`datasets`                      *Get the dataset catalog*

---

### Description

Crunch datasets are associated with catalogs. A project catalog will have a set of datasets associated with it, as will a user or team. This function allows you to get or modify the datasets associated with a catalog.

### Usage

```
datasets(x = getAPIRoot())
```

```
datasets(x) <- value
```

### Arguments

`x`                      a ShojiObject, such as a CrunchProject. If omitted, the function will load the user's primary dataset catalog. #'

`value`                CrunchDataset for the setter

### Value

An object of class DatasetCatalog. The setter returns the project (or other object that contains a dataset catalog with the given dataset added to it (via changing its owner to be the specified object, `x`).

## Examples

```
## Not run:
# Get the primary dataset catalog
mydatasets <- datasets()
# Can load a dataset from that
ds <- loadDataset(mydatasets[["Dataset name"]])
# Can use the same function to get the dataset catalog for a project
proj <- projects()[["Project name"]]
projdatasets <- datasets(proj)
# The assignment method lets you move a dataset to a project
datasets(proj) <- ds

## End(Not run)
```

---

dedupeOrder

*Remove duplicated entities from an order/group*

---

## Description

This function recurses through a `ShojiOrder` or `OrderGroup` and removes any duplicate entities. As with `base::duplicated`, the first appearance of an entity is kept, and subsequent occurrences are marked as duplicated and removed. (Unlike `duplicated`, there is no option to reverse that order.) The first occurrence of an entity is determined by the function's recursion: within each group, nested groups are processed first, in order, and their nested groups are processed recursively. See the test suite, in `test-variable-order.R`, for an example that illustrates which entities are dropped as duplicate.

## Usage

```
dedupeOrder(x)
```

## Arguments

x VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup

## Value

x with duplicate entities removed.

## See Also

`duplicates`, which when set to `FALSE` also calls this function.

---

|        |   |
|--------|---|
| delete | <i>Delete a Crunch object from the server</i> |
|--------|---|

---

### Description

These methods delete entities, notably Datasets and Variables within them, from the server. This action is permanent and cannot be undone, so it should not be done lightly. Consider instead using `archive` for datasets and `hide` for variables.

### Usage

```
## S4 method for signature 'CrunchDataset'  
delete(x, ...)
```

```
## S4 method for signature 'Multitable'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchProject'  
delete(x, ...)
```

```
## S4 method for signature 'ShojiFolder'  
delete(x, ...)
```

```
## S4 method for signature 'ShojiObject'  
delete(x, ...)
```

```
## S4 method for signature 'ANY'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchTeam'  
delete(x, ...)
```

```
## S4 method for signature 'CrunchVariable'  
delete(x, ...)
```

```
## S4 method for signature 'VariableTuple'  
delete(x, ...)
```

### Arguments

|     |                                      |
|-----|--------------------------------------|
| x   | a Crunch object                      |
| ... | additional arguments, in the generic |

### Details

Deleting requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to delete objects from a non-interactive session, wrap the call in `with_consent()` to give your permission to delete.

**See Also**[hide deleteDataset](#)

---

|               |   |
|---------------|---|
| deleteDataset | <i>Delete a dataset from the dataset list</i> |
|---------------|---|

---

**Description**

This function lets you delete a dataset without first loading it. If you have a dataset that somehow is corrupted and won't load, you can delete it this way.

**Usage**

```
deleteDataset(x, ...)
```

**Arguments**

|     |   |
|-----|---|
| x   | The name (character) of a dataset, its (numeric) position in the return of <a href="#">listDatasets()</a> , or an object of class <code>CrunchDataset</code> . x can only be of length 1—this function is not vectorized (for your protection). |
| ... | additional parameters passed to delete  |

**Details**

The function also works on `CrunchDataset` objects, just like [delete\(\)](#), which may be useful if you have loaded another package that masks the [delete\(\)](#) method.

**Value**

(Invisibly) the API response from deleting the dataset

**See Also**[delete](#)

---

deleteSubvariables      *Delete subvariables from an array*

---

### Description

Deleting variables requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to delete subvariables from a non-interactive session, wrap the call in [with\\_consent\(\)](#) to give your permission to delete.

### Usage

```
deleteSubvariables(variable, to.delete)
```

```
deleteSubvariable(variable, to.delete)
```

### Arguments

|           |   |
|-----------|---|
| variable  | the array variable  |
| to.delete | aliases (following <code>crunch.namekey.dataset</code> ) or indices of variables to delete. |

### Details

To delete the subvariables the function unbinds the array, deletes the subvariable, and then binds the remaining subvariables into a new array.

### Value

a new version of variable without the indicated subvariables

---

deleteVariables      *Delete Variables Within a Dataset*

---

### Description

This function permanently deletes a variable from a dataset. For a non-destructive alternative see [hide\(\)](#).

### Usage

```
deleteVariables(dataset, variables)
```

```
deleteVariable(dataset, variables)
```

**Arguments**

`dataset`            the Dataset to modify  
`variables`          aliases (following `crunch.namekey.dataset`) or indices of variables to delete.

**Details**

In an interactive session, you will be prompted to confirm that you wish to delete the variable. To avoid that prompt, or to delete variables from a non-interactive session, wrap the call in `with_consent()` to give your permission to delete.

**Value**

(invisibly) dataset with the specified variables deleted

**See Also**

[hide](#)

---

derivations                      *Get or set a derived variable's expression*

---

**Description**

Get a derived variable's derivation formula as a [CrunchExpr](#) with `derivation(variable)`. Set (change) a derived variable's derivation with `derivation(variable) <- expression`.

**Usage**

```
## S4 method for signature 'CrunchVariable'
derivation(x)

## S4 replacement method for signature 'CrunchVariable,ANY'
derivation(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
derivation(x) <- value

## S4 method for signature 'CrunchVariable'
is.derived(x)

## S4 replacement method for signature 'CrunchVariable,logical'
is.derived(x) <- value
```



**Arguments**

|       |   |
|-------|---|
| x     | a variable  |
| value | a CrunchExpr to be used as the derivation (for the setter only) or NULL to integrate a derived variable. For is.derived, FALSE can be used to integrate a derived variable. |

**Details**

To break a derivation link between a derived variable and the originating variable, set the derivation value of the derived variable to NULL with `derivation(variable) <- NULL`

`is.derived` can be used to see if a variable is derived or not. Additionally setting a derived variable's `is.derived` to FALSE will break the derivation link between two variables.

**Value**

a CrunchExpr of the derivation for `derivation`; a logical for `is.derived`; the variable given in `x` for `is.derived<-` returns

**Examples**

```
## Not run:

ds$derived_v1 <- ds$v1 + 5

derivation(ds$derived_v1)
# Crunch expression: v1 + 5

derivation(ds$derived_v1) <- ds$v1 + 10
derivation(ds$derived_v1)
# Crunch expression: v1 + 10

is.derived(ds$derived_v1)
# TRUE

# to integrate or instantiate the variable in place (remove the link between
# variable v1 and the derivation) you can:
derivation(ds$derived_v1) <- NULL

# after integrating, the derived variable is no longer derived.
is.derived(ds$derived_v1)
# FALSE

## End(Not run)
```

---

|          |  |
|----------|--|
| describe | <i>Name, alias, and description for Crunch objects</i> |
|----------|--|

---

**Description**

Name, alias, and description for Crunch objects

**Usage**

```
## S4 method for signature 'CrunchDataset'  
name(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
name(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
description(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
description(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
startDate(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
startDate(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
endDate(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
endDate(x) <- value  
  
## S4 method for signature 'CrunchDataset'  
id(x)  
  
## S4 method for signature 'CrunchDataset'  
notes(x)  
  
## S4 replacement method for signature 'CrunchDataset'  
notes(x) <- value  
  
## S4 method for signature 'Geodata'  
description(x)  
  
## S4 replacement method for signature 'Multitable'  
name(x) <- value
```

```
## S4 replacement method for signature 'ShojiFolder'
name(x) <- value

## S4 method for signature 'ShojiObject'
name(x)

## S4 method for signature 'CrunchVariable'
name(x)

## S4 replacement method for signature 'CrunchVariable'
name(x) <- value

## S4 method for signature 'CrunchVariable'
id(x)

## S4 method for signature 'CrunchVariable'
description(x)

## S4 replacement method for signature 'CrunchVariable'
description(x) <- value

## S4 method for signature 'CrunchVariable'
alias(object)

## S4 replacement method for signature 'CrunchVariable'
alias(x) <- value

## S4 method for signature 'CrunchVariable'
notes(x)

## S4 replacement method for signature 'CrunchVariable'
notes(x) <- value

## S4 method for signature 'CrunchVariable'
digits(x)

## S4 replacement method for signature 'NumericVariable'
digits(x) <- value

## S4 replacement method for signature 'CrunchVariable'
digits(x) <- value

## S4 method for signature 'MultipleResponseVariable'
uniformBasis(x)

## S4 replacement method for signature 'MultipleResponseVariable'
uniformBasis(x) <- value
```

**Arguments**

|        |  |
|--------|--|
| x      | a Dataset or Variable.   |
| value  | For the setters, a length-1 character vector to assign   |
| object | Same as x but for the alias method, in order to match the generic from another package. Note that alias and digits are only defined for Variables. |

**Value**

Getters return the character object in the specified slot; setters return x duly modified.

**See Also**

[Categories describe-catalog](#)

---

dichotomize

*Indicate how categories represent a dichotomized value*


---

**Description**

Multiple Response variables are essentially Categorical Arrays in which one or more categories are set as "selected". These methods allow you set that state.

**Usage**

```
## S4 method for signature 'Categories'
is.dichotomized(x)

## S4 method for signature 'Categories,numeric'
dichotomize(x, i)

## S4 method for signature 'Categories,logical'
dichotomize(x, i)

## S4 method for signature 'Categories,character'
dichotomize(x, i)

## S4 method for signature 'Categories'
undichotomize(x)

## S4 method for signature 'CategoricalVariable,ANY'
dichotomize(x, i)

## S4 method for signature 'CategoricalArrayVariable,ANY'
dichotomize(x, di)

## S4 method for signature 'CategoricalVariable'
```

```
undichotomize(x)
```

```
## S4 method for signature 'CategoricalArrayVariable'
undichotomize(x)
```

### Arguments

**x** Categories or a Variable subclass that has Categories

**i** For the dichotomize methods, the numeric or logical indices of the categories to mark as "selected", or if character, the Category "names". Note that unlike some other categorical variable methods, numeric indices are positional, not with reference to category ids.

### Details

dichotomize lets you specify which categories are "selected", while undichotomize strips that selection information. Dichotomize converts a Categorical Array to a Multiple Response, and undichotomize does the reverse.

### Value

Categories or the Variable, (un)dichotomized accordingly

### See Also

[describe-category](#)

---

dim-dataset

*Dataset dimensions*

---

### Description

Dataset dimensions

### Usage

```
## S4 method for signature 'CrunchDataset'
dim(x)
```

```
## S4 method for signature 'CrunchDataset'
ncol(x)
```

### Arguments

**x** a Dataset

**Value**

integer vector of length 2, indicating the number of rows and non-hidden variables in the dataset. Array subvariables are excluded from the column count.

**See Also**

[base::dim\(\)](#)

---

|          |   |
|----------|---|
| dropRows | <i>Permanently delete rows from a dataset</i> |
|----------|---|

---

**Description**

Permanently delete rows from a dataset

**Usage**

```
dropRows(dataset, expr)
```

**Arguments**

|         |                     |
|---------|---------------------|
| dataset | a CrunchDataset     |
| expr    | a CrunchLogicalExpr |

**Value**

dataset without the rows indicated by expr

**See Also**

[exclusion](#) for a non-destructive way to suppress rows

**Examples**

```
## Not run:  
ds <- dropRows(ds, ds$gender == "Male")  
  
## End(Not run)
```

---

|            |   |
|------------|---|
| duplicated | <i>"duplicated" method for Crunch objects</i> |
|------------|---|

---

**Description**

"duplicated" method for Crunch objects

**Usage**

```
## S4 method for signature 'CrunchVariable'
duplicated(x, incomparables = FALSE, ...)
```

```
## S4 method for signature 'CrunchExpr'
duplicated(x, incomparables = FALSE, ...)
```

**Arguments**

|               |                              |
|---------------|------------------------------|
| x             | CrunchVariable or CrunchExpr |
| incomparables | Ignored                      |
| ...           | Ignored                      |

**Value**

A `CrunchLogicalExpr` that evaluates TRUE for all repeated entries after the first occurrence of a value.

**See Also**

[base::duplicated\(\)](#)

---

|                |   |
|----------------|---|
| embedCrunchBox | <i>Get HTML for embedding a CrunchBox</i> |
|----------------|---|

---

**Description**

`crunchBox()` returns a URL to the box data that it generates, but in order to view it in a `CrunchBox` or to embed it on a website, you'll need to translate that to the Box's public URL and wrap it in some HTML. This function takes a `CrunchBox` and returns the HTML which you can embed in a website.

**Usage**

```
embedCrunchBox(box, title = NULL, logo = NULL, ...)
```

**Arguments**

|                    |  |
|--------------------|--|
| <code>box</code>   | character URL of the box data, as returned by <code>crunchBox()</code>   |
| <code>title</code> | character title for the Box, to appear above the iframe. Default is NULL, meaning no title shown   |
| <code>logo</code>  | character URL of a logo to show instead of a title. Default is NULL, meaning no logo shown. If both <code>logo</code> and <code>title</code> are provided, only the logo will be shown. Note also that <code>logo</code> must be a URL of a hosted image: it cannot be a path to a local file. |
| <code>...</code>   | Additional arguments, not currently used.  |

**Value**

Prints the HTML markup to the screen and also returns it invisibly.

**See Also**

[crunchBox\(\)](#)

**Examples**

```
## Not run:
box <- crunchBox(ds)
embedCrunchBox(box, logo="//myco.example/img/logo_200px.png")

## End(Not run)
```

---

exclusion

*View and set exclusion filters*

---

**Description**

Exclusion filters express logic that defines a set of rows that should be dropped from the dataset. The rows aren't permanently deleted—you can recover them at any time by removing the exclusion filter—but they are omitted from all views and calculations, as if they had been deleted.

**Usage**

```
exclusion(x)
```

```
exclusion(x) <- value
```

**Arguments**

|                    |   |
|--------------------|---|
| <code>x</code>     | a Dataset   |
| <code>value</code> | an object of class <code>CrunchLogicalExpr</code> , or NULL |



**Details**

Note that exclusion filters work opposite from how "normal" filters work. That is, a regular filter expression defines the subset of rows to operate on: it says "keep these rows." An exclusion filter defines which rows to omit. Applying a filter expression as a query filter will have the opposite effect if applied as an exclusion. Indeed, applying it as both query filter and exclusion at the same time will result in 0 rows.

**Value**

exclusion returns a `CrunchFilter` if there is one, else `NULL`. The setter returns `x` with the filter set.

---

|               |                                   |
|---------------|-----------------------------------|
| exportDataset | <i>Export a dataset to a file</i> |
|---------------|-----------------------------------|

---

**Description**

This function allows you to write a `CrunchDataset` to a `.csv` or SPSS `.sav` file.

**Usage**

```
exportDataset(dataset, file, format = c("csv", "spss"),
  categorical = c("name", "id"), na = NULL, varlabel = c("name",
  "description"), ...)

## S4 method for signature 'CrunchDataset'
write.csv(x, ...)
```

**Arguments**

|             |   |
|-------------|---|
| dataset     | <code>CrunchDataset</code> , which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.  |
| file        | character local filename to write to  |
| format      | character export format: currently supported values are "csv" and "spss".   |
| categorical | character: export categorical values to CSV as category "name" (default) or "id". Ignored by the SPSS exporter.   |
| na          | Similar to the argument in <code>utils::write.table()</code> , 'na' lets you control how missing values are written into the CSV file. Supported values are: <ol style="list-style-type: none"> <li>1. <code>NULL</code>, the default, which means that categorical variables will have the category name or id as the value, and numeric, text, and datetime variables will have the missing reason string;</li> <li>2. A string to use for missing values.</li> <li>3. <code>" "</code> means that empty cells will be written for missing values for all types.</li> </ol> |
| varlabel    | For SPSS export, which Crunch metadata field should be used as variable labels? Default is "name", but "description" is another valid value.  |

- ... additional options. See the API documentation. Currently supported boolean options include 'include\_personal' for personal variables (default: FALSE) and 'prefix\_subvariables' for SPSS format: whether to include the array variable's name in each of its subvariables "varlabels" (default: FALSE).
- x (for write.csv) CrunchDataset, which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.

**Value**

Invisibly, file.

---

expressions

*Construct Crunch Expressions*

---

**Description**

Crunch Expressions, i.e. `CrunchExpr` and `CrunchLogicalExpr`, encapsulate derivations of Crunch variables, which are only evaluated when passed to a function like `as.vector`. They allow you to compose functional expressions of variables and evaluate them against the server only when appropriate.

**Usage**

```
## S4 method for signature 'CrunchExpr'
!x

## S4 method for signature 'CategoricalVariable,character'
x %in% table

## S4 method for signature 'CategoricalVariable,factor'
x %in% table

## S4 method for signature 'TextVariable,character'
x %in% table

## S4 method for signature 'NumericVariable,numeric'
x %in% table

## S4 method for signature 'DatetimeVariable,Date'
x %in% table

## S4 method for signature 'DatetimeVariable,POSIXt'
x %in% table

## S4 method for signature 'DatetimeVariable,character'
x %in% table
```

```

## S4 method for signature 'CategoricalVariable,numeric'
x %in% table

## S4 method for signature 'CategoricalVariable,numeric'
e1 == e2

## S4 method for signature 'CategoricalVariable,character'
e1 == e2

## S4 method for signature 'CategoricalVariable,factor'
e1 == e2

## S4 method for signature 'CategoricalVariable,numeric'
e1 != e2

## S4 method for signature 'CategoricalVariable,character'
e1 != e2

## S4 method for signature 'CategoricalVariable,factor'
e1 != e2

## S4 method for signature 'CrunchVariable'
is.na(x)

bin(x)

rollup(x, resolution = rollupResolution(x))

rollupResolution(x)

## S4 replacement method for signature 'DatetimeVariable'
rollupResolution(x) <- value

```

### Arguments

|            |   |
|------------|---|
| x          | an input  |
| table      | For %in%. See <a href="#">base::match()</a>   |
| e1         | an input  |
| e2         | an input  |
| resolution | For rollup. Either NULL or a character in c("Y", "Q", "M", "W", "D", "h", "m", "s", "ms") indicating the unit of time at which a Datetime variable should be aggregated. If NULL, the server will determine an appropriate resolution based on the range of the data. |
| value      | for the rollupResolution() setter, the default resolution for this variable.  |

### Value

Most functions return a `CrunchExpr` or `CrunchLogicalExpr`. `as.vector` returns an R vector.

---

|                 |   |
|-----------------|---|
| expropriateUser | <i>Expropriate all Crunch objects from a user</i> |
|-----------------|---|

---

### Description

If you want to transfer all teams, projects, and datasets owned by one user to another you can with `expropriateUser`. To use `expropriateUser` you must be an account admin and be from the same account as the user who is being expropriated. This is useful if a user leaves your organization and you want to transfer all of the teams, projects, and datasets they own to someone else.

### Usage

```
expropriateUser(from, to)
```

### Arguments

|      |  |
|------|--|
| from | a character of the email address of the user to expropriate from         |
| to   | a character of the email address of the user who should be the new owner |

### Details

Expropriating requires confirmation. In an interactive session, you will be asked to confirm. To avoid that prompt, or to expropriate datasets from a non-interactive session, wrap the call in `with_consent()` to give your permission to expropriate

### Value

None

---

|                |                                       |
|----------------|---------------------------------------|
| filter-catalog | <i>Get or set a dataset's filters</i> |
|----------------|---------------------------------------|

---

### Description

You can build and save filters in the Crunch web app, and these filters are stored in a `FilterCatalog`. This function allows you to retrieve and modify those filters.

### Usage

```
## S4 method for signature 'CrunchDataset'
filters(x)

## S4 replacement method for signature 'CrunchDataset'
filters(x) <- value
```

**Arguments**

x                    a CrunchDataset  
 value                for the setter, a FilterCatalog

**Value**

an object of class FilterCatalog containing references to Filter entities usable in the web application.  
 (Setter returns the Dataset.)

---

|              |   |
|--------------|---|
| flattenOrder | <i>Remove nesting of groups within an order/group</i> |
|--------------|---|

---

**Description**

This function reduces a potentially nested order to its flattened representation, containing no nested groups. Entities are ordered in the result by their first appearance in the order object.

**Usage**

```
flattenOrder(x)
```

**Arguments**

x                    VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup; or a Crunch-Dataset or catalog that has an ordering property.

**Value**

x, or its order resource, flattened.

---

|            |                                     |
|------------|-------------------------------------|
| flipArrays | <i>Rearrange array subvariables</i> |
|------------|-------------------------------------|

---

**Description**

Sometimes it is useful to group subvariables across arrays in order to compare them more easily. This function generates a set of derived views of common subvariables across arrays. Because they are derived, they share data with the underlying array variables, and they are thus automatically updated when new data is appended.

**Usage**

```
flipArrays(variables, suffix = ", flipped")
```

**Arguments**

|           |   |
|-----------|---|
| variables | List of variables, a variable catalog, or a dataset subset containing the categorical array or multiple response variables you want to rearrange. |
| suffix    | character string to append to the new variable names. Pass "" if you don't want it to append anything.  |

**Value**

A list of derived VariableDefinitions, one per unique subvariable name across all variables. Each variable in variables that contains this subvariable will appear as a subvariable in these new derived array definitions. Use [addVariables](#) to add these to your dataset.

**Examples**

```
## Not run:
ds <- addVariables(ds, flipArrays(ds[c("petloc", "petloc2")], suffix=", rearranged"))

## End(Not run)
```

---

 folder

---

*Find and move variables to a new folder*


---

**Description**

Find and move variables to a new folder

**Usage**

```
folder(x)
```

```
folder(x) <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | For folder, a Variable to find. For folder assignment, a Variable, selection of variables in a Dataset, or any other object that can be moved to a folder.             |
| value | For assignment, a character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default) |

**Value**

folder returns the parent folder of x, or NULL if the x is the root level. folder<- returns the x input, having been moved to the requested location.

**See Also**

[mv\(\)](#) [cd\(\)](#)

**Examples**

```
## Not run:
ds <- loadDataset("Example survey")
folder(ds$income) <- "Demographics/Economic"
folder(ds$income)
## [1] "Demographics" "Economic"

## End(Not run)
```

---

|             |                                   |
|-------------|-----------------------------------|
| forkDataset | <i>Create a fork of a dataset</i> |
|-------------|-----------------------------------|

---

**Description**

As with many other version control systems, in Crunch you can fork a dataset's revision history, effectively making a copy on which you can work independently of the original dataset. You can then merge those change back to the original dataset or keep working independently.

**Usage**

```
forkDataset(dataset, name = defaultForkName(dataset), draft = FALSE, ...)
```

**Arguments**

|         |  |
|---------|--|
| dataset | The CrunchDataset to fork  |
| name    | character name to give the fork. If omitted, one will be provided for you            |
| draft   | logical: Should the dataset be a draft, available only to editors? Default is FALSE. |
| ...     | Additional dataset metadata  |

**Value**

The new fork, a CrunchDataset.

---

|         |   |
|---------|---|
| fortify | <i>Fortify crunch objects for use with ggplot</i> |
|---------|---|

---

**Description**

Fortify crunch objects for use with ggplot

**Usage**

```
fortify.CrunchDataFrame(model, data, ...)
```

```
fortify.CrunchDataset(model, data, ...)
```

**Arguments**

|       |  |
|-------|--|
| model | model or other R object to convert to data frame |
| data  | original dataset, if needed                      |
| ...   | other arguments passed to methods                |

---

|          |                            |
|----------|----------------------------|
| getTeams | <i>Retrieve your teams</i> |
|----------|----------------------------|

---

**Description**

Retrieve your teams

**Usage**

```
getTeams()
```

**Value**

A TeamCatalog. Extract an individual team by name. Create a team by assigning in with a new name.

**See Also**

[teams](#)

---

|         |   |
|---------|---|
| grouped | <i>Get grouped or ungrouped OrderGroups</i> |
|---------|---|

---

**Description**

"ungrouped" is an OrderGroup that contains all entities not found in groups at a given level of nesting.

**Usage**

```
grouped(order.obj)
ungrouped(order.obj)
```

**Arguments**

|           |   |
|-----------|---|
| order.obj | an subclass of ShojiOrder or OrderGroup |
|-----------|---|



**Value**

For grouped(), an Order/Group, respectively, with "ungrouped" omitted. For ungrouped(), an OrderGroup subclass.

**See Also**

[VariableOrder](#)

---

|                 |   |
|-----------------|---|
| hiddenVariables | <i>Show the names of a dataset's hidden variables</i> |
|-----------------|---|

---

**Description**

Show the names of a dataset's hidden variables

**Usage**

```
hiddenVariables(dataset, key = namekey(dataset))
```

**Arguments**

|         |  |
|---------|--|
| dataset | the Dataset  |
| key     | the Variable attribute to return. Default is "alias", following <code>getOption("crunch.namekey.dataset")</code> . |

**Value**

a vector of the names of Variables marked as hidden.

---

|      |                                  |
|------|----------------------------------|
| hide | <i>Hide and Unhide Variables</i> |
|------|----------------------------------|

---

**Description**

Hide and Unhide Variables

**Usage**

```
## S4 method for signature 'CrunchVariable'
hide(x)

## S4 method for signature 'VariableCatalog'
hide(x)

## S4 method for signature 'CrunchVariable'
unhide(x)

## S4 method for signature 'VariableCatalog'
unhide(x)
```

**Arguments**

x a Variable or subset of a VariableCatalog to hide or unhide

**Value**

(invisibly) the Variable or VariableCatalog, hidden or unhidden

**See Also**

[hideVariables](#)

---

|               |   |
|---------------|---|
| hideVariables | <i>Hide and unhide variables within a dataset</i> |
|---------------|---|

---

**Description**

Hide and unhide variables within a dataset

**Usage**

```
hideVariables(dataset, variables)
```

```
hiddenVariables(x) <- value
```

```
unhideVariables(dataset, variables)
```

**Arguments**

dataset the Dataset to modify

variables names or indices of variables to (un)hide

x same as dataset, for hiddenVariables<-

value same as variables, for hiddenVariables<-

**Value**

(invisibly) dataset with the specified variables (un)hidden

**See Also**

[hide](#)

---

`http-methods`*HTTP methods for communicating with the Crunch API*

---

**Description**

These methods let you communicate with the Crunch API, for more background see [Crunch Internals](#).

**Usage**`crGET(...)``crPUT(...)``crPATCH(...)``crPOST(...)``crDELETE(...)`**Arguments**

... see [crunchAPI](#) for details. `url` is the first named argument and is required; `body` is also required for PUT, PATCH, and POST.

**Value**

Depends on the response status of the HTTP request and any custom handlers.

---

`importMultitable`*Import a Multitable*

---

**Description**

Allows you to import a multitable from a different dataset

**Usage**`importMultitable(data, multitable, ...)`**Arguments**

`data` a `CrunchDataset` in which to create the multitable

`multitable` an object of class `Multitable` that you want copied to the new dataset

... Additional multitable attributes to set. Options include `name` and `is_public`.

**Value**

An object of class `Multitable`

**Examples**

```
## Not run:
m <- newMultitable(~ gender + age4 + marstat, data=ds)
copied_m <- importMultitable(another_ds, m)
name(copied_m) # [1] "gender + age4 + marstat"

## End(Not run)
```

---

index.table

*Calculate an index table for a CrunchCube*

---

**Description**

Index tables are percentages of percentages. They take the percentage from `prop.table()` and divide that by the proportions of the other margin.

**Usage**

```
index.table(x, margin)
```

**Arguments**

`x` A `CrunchCube` to calculate index table for  
`margin` which margin to index against (1 for rows, 2 for columns)

**Details**

`index.table()` is only implemented for 2 dimensional cubes. If you need to calculate indexes for a higher dimension Cube, please slice the cube first.

**Value**

an array of percentages indexed to the margin provided

**Examples**

```
## Not run:
cube_object
# v7
# v4 C E
# B 5 2
# C 5 3
index.table(cube_object, 1)
# v7
```

```

# v4      C      E
# B 1.071429 0.8571429
# C 0.937500 1.1250000
index.table(cube_object, 2)
# v7
# v4      C      E
# B 1.071429 0.8571429
# C 0.937500 1.1250000
#

## End(Not run)

```

---

Insertions-class      *Insert categories in transformations*

---

### Description

Insertions allow you to insert new categories into a categorical-like response on a variable's [transformations](#).

### Usage

```

Insertions(..., data = NULL)

Insertion(...)

.Insertion(..., data = NULL)

## S4 replacement method for signature 'Insertion'
anchor(x) <- value

## S4 replacement method for signature 'Subtotal'
anchor(x) <- value

## S4 replacement method for signature 'Heading'
anchor(x) <- value

## S4 replacement method for signature 'SummaryStat'
anchor(x) <- value

## S4 replacement method for signature 'Insertion,ANY'
subtotals(x) <- value

## S4 replacement method for signature 'Insertion'
arguments(x) <- value

## S4 replacement method for signature 'Subtotal'

```

```
arguments(x) <- value

## S4 replacement method for signature 'Heading'
arguments(x) <- value

## S4 replacement method for signature 'SummaryStat'
arguments(x) <- value

## S4 method for signature 'Insertion'
arguments(x)

## S4 method for signature 'Subtotal'
arguments(x, var_categories)

## S4 method for signature 'Heading'
arguments(x)

## S4 method for signature 'SummaryStat'
arguments(x, var_categories)

## S4 method for signature 'Insertion'
anchor(x)

## S4 method for signature 'Subtotal'
anchor(x, var_categories)

## S4 method for signature 'Heading'
anchor(x, var_categories)

## S4 method for signature 'SummaryStat'
anchor(x, var_categories)

## S4 method for signature 'Insertion'
func(x)

## S4 method for signature 'Subtotal'
func(x)

## S4 method for signature 'Heading'
func(x)

## S4 method for signature 'SummaryStat'
func(x)

## S4 method for signature 'Insertions'
anchors(x)

## S4 method for signature 'Insertions'
```

```
funcs(x)
```

### Arguments

|                |  |
|----------------|--|
| ...            | additional arguments to [, ignored   |
| data           | For the constructor functions Insertion and Insertions, you can either pass in attributes via ... or you can create the objects with a fully defined list representation of the objects via the data argument. See the examples. |
| x              | For the attribute getters and setters, an object of class Insertion or Insertions  |
| value          | For [<-, the replacement Insertion to insert   |
| var_categories | categories (from <code>categories()</code> ) to used by the arguments and anchor methods when needed to translate between category names and category ids.   |

### Working with Insertions

Insertions are used to add information about a variable or CrunchCube that extends the data in the dataset but does not alter it. This new data includes: aggregations like [subtotals](#) that sum the count of more than on category together or [headings](#) which can be added between categories.

Insertions objects are containers for individual Insertion objects. The individual Insertions contain all the information needed to calculate, apply, and display insertions to CrunchCubes and categorical variables.

An Insertion must have two properties:

- anchor - which is the id of the category the insertion should follow
- name - the string to display

Additionally, Insertions may also have the following two properties (though if they have one, they must have the other):

- function - the function to use to aggregate (e.g. "subtotal")
- args - the category ids to use as operands to the function above.

Although it is possible to make both subtotals and headings using Insertion alone, it is much easier and safer to use the functions [Subtotal\(\)](#) and [Heading\(\)](#) instead. Not only are they more transparent, they also are quicker to type, accept both category names as well as ids, and have easier to remember argument names.

---

interactVariables      *Create a variable by interacting categorical variables*

---

### Description

interactVariables takes two or more variables and creates a new one that is the cartesian product expansion of their unique values. For example, if we cross ethnicity (with 2 categories) and race (with 4 categories), the new variable would have 8 valid categories (e.g. black:hispanic, white:hispanic, black:non-hispanic, etc.) and 7 categories where at least one of the variables is missing (e.g. white:No Data).

**Usage**

```
interactVariables(..., name, sep = " : ")
```

**Arguments**

|      |   |
|------|---|
| ...  | a sequence of categorical variables to make an interaction from as well as other properties to pass about the case variable (i.e. alias, description) |
| name | a character to use as the name for the interaction variable   |
| sep  | a character to separate the values of the individual variables (default: :)   |

**Value**

A [VariableDefinition](#) that creates the new interaction variable.

**Examples**

```
## Not run:
ds$ethn_race <- interactVariables(ds$ethnicity, ds$race, name="Interaction of ethnicity and race")

## End(Not run)
```

---

is-na-categories      *is.na for Categories*

---

**Description**

Crunch categorical variables allow you to set multiple categories as missing. For instance, you might have "not answered" and "doesn't know" both coded as missing. This function returns a logical vector of all dataset entries that fall into any of the missing categories. It also allows you to append additional categories to the list of missing categories using the setter.

**Usage**

```
## S4 method for signature 'Categories'
is.na(x)

## S4 method for signature 'Categories'
is.na(x)

## S4 replacement method for signature 'Categories,character'
is.na(x) <- value

## S4 replacement method for signature 'Categories,logical'
is.na(x) <- value

## S4 method for signature 'Category'
is.na(x)
```



```
## S4 replacement method for signature 'Category,logical'
is.na(x) <- value
```

### Arguments

|       |   |
|-------|---|
| x     | Categories or a single Category   |
| value | To change the missingness of categories, supply either: <ol style="list-style-type: none"> <li>1. a logical vector of equal length of the categories (or length 1 for the Category method); or</li> <li>2. the names of the categories to mark as missing. If supplying the latter, any categories already indicated as missing will remain missing.</li> </ol> |

### Value

Getters return logical, a named vector in the case of the Categories method; setters return x duly modified.

---

|           |   |
|-----------|---|
| is-public | <i>View and modify "public" attribute</i> |
|-----------|---|

---

### Description

View and modify whether all dataset viewers have access to the dataset. This will return FALSE if the dataset is in draft.

### Usage

```
## S4 method for signature 'CrunchFilter'
is.public(x)

## S4 replacement method for signature 'CrunchFilter'
is.public(x) <- value

## S4 method for signature 'MultitableCatalog'
is.public(x)

## S4 replacement method for signature 'MultitableCatalog'
is.public(x) <- value

## S4 method for signature 'Multitable'
is.public(x)

## S4 replacement method for signature 'Multitable'
is.public(x) <- value
```

**Arguments**

|       |                     |
|-------|---------------------|
| x     | a Crunch object     |
| value | an attribute to set |

**Value**

For `is.public`, a logical value for whether the object is flagged as shared with all dataset viewers. (Its setter thus takes a logical value as well.) Catalogs of datasets return a vector of logicals corresponding to the length of the catalog, while entities return a single value.

---

`is-selected-categories`

*is.selected for Categories*

---

**Description**

Crunch Multiple Response variables identify one or more categories as "selected". These methods allow you to get or set which categories should indicate a selection.

**Usage**

```
## S4 method for signature 'Categories'
is.selected(x)

## S4 replacement method for signature 'Categories'
is.selected(x) <- value

## S4 replacement method for signature 'Category'
is.selected(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | Categories or a single Category   |
| value | A logical vector indicating whether the category should be selected. For a single category the value should be either TRUE or FALSE to change the selection status for a Categories object, supply a logical vector which is the same length as the number of categories. |

**Value**

Getters return a logical vector indicating selection status. Setters return the Categories or Category object, duly modified.

---

`is.archived, DatasetCatalog-method`*Get and set "archived" and "published" status of a dataset*

---

**Description**

"Archived" datasets are excluded from some views. "Draft" datasets are visible only to editors, while published datasets are available to all viewers. A dataset can either be published or in draft, but not both. These properties are accessed and set with the "is" methods. You can also set the properties by assigning into the function. The verb functions `archive` and `publish` are alternate versions of the setters.

**Usage**

```
## S4 method for signature 'DatasetCatalog'
is.archived(x)

## S4 method for signature 'DatasetCatalog'
is.draft(x)

## S4 method for signature 'DatasetCatalog'
is.published(x)

## S4 replacement method for signature 'DatasetCatalog,logical'
is.archived(x) <- value

## S4 replacement method for signature 'DatasetCatalog,logical'
is.draft(x) <- value

## S4 replacement method for signature 'DatasetCatalog,logical'
is.published(x) <- value

## S4 method for signature 'CrunchDataset'
is.archived(x)

## S4 method for signature 'CrunchDataset'
is.draft(x)

## S4 method for signature 'CrunchDataset'
is.published(x)

## S4 replacement method for signature 'CrunchDataset,logical'
is.archived(x) <- value

archive(x)

## S4 replacement method for signature 'CrunchDataset,logical'
```

```

is.draft(x) <- value

## S4 replacement method for signature 'CrunchDataset,logical'
is.published(x) <- value

publish(x)

```

### Arguments

|       |               |
|-------|---------------|
| x     | CrunchDataset |
| value | logical       |

### Value

For the getters, the logical value of whether the dataset is archived, in draft mode, or published, where draft and published are inverses. The setters return the dataset.

### Examples

```

## Not run:
ds <- loadDataset("mtcars")
is.draft(ds)      # FALSE
is.published(ds) # TRUE
identical(is.draft(ds), !is.published(ds))
# Can make a dataset a "draft" by:
is.draft(ds) <- TRUE
is.published(ds) # FALSE
# Could also have set is.published(ds) <- FALSE
# Now, can go the other way by setting is.draft, is.published, or:
ds <- publish(ds)
is.published(ds) # TRUE

is.archived(ds) # FALSE
is.archived(ds) <- TRUE
is.archived(ds) # TRUE
# Could have achieved the same effect by:
ds <- archive(ds)

## End(Not run)

```

---

is.dataset

*Test whether a Crunch object belongs to a class*


---

### Description

Test whether a Crunch object belongs to a class

**Usage**

- is.dataset(x)
- is.CrunchExpr(x)
- is.Expr(x)
- is.Geodata(x)
- is.shoji(x)
- is.variable(x)
- is.Numeric(x)
- is.Categorical(x)
- is.Text(x)
- is.Datetime(x)
- is.Multiple(x)
- is.MR(x)
- is.MultipleResponse(x)
- is.CA(x)
- is.Array(x)
- is.CategoricalArray(x)

**Arguments**

x                    an object

**Value**

logical

---

is.editor                    *Read and set edit privileges*

---

**Description**

Read and set edit privileges

**Usage**

```
## S4 method for signature 'MemberCatalog'
is.editor(x)

## S4 replacement method for signature 'MemberCatalog,logical'
is.editor(x) <- value

## S4 method for signature 'PermissionCatalog'
is.editor(x)

## S4 method for signature 'PermissionTuple'
is.editor(x)
```

**Arguments**

|       |   |
|-------|---|
| x     | PermissionCatalog or MemberCatalog  |
| value | For the setter, logical: should the indicated users be allowed to edit the associated object? |

**Value**

is.editor returns a logical vector corresponding to whether the users in the catalog can edit or not.is.editor<- returns the catalog, modified.

---

|              |  |
|--------------|--|
| joinDatasets | <i>Add columns from one dataset to another, joining on a key</i> |
|--------------|--|

---

**Description**

As [merge](#) does for data.frames, this function takes two datasets, matches rows based on a specified key variable, and adds columns from one to the other.

**Usage**

```
joinDatasets(x, y, by = intersect(names(x), names(y)), by.x = by,
  by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, copy = TRUE)

extendDataset(x, y, by = intersect(names(x), names(y)), by.x = by,
  by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, ...)

## S3 method for class 'CrunchDataset'
merge(x, y, by = intersect(names(x), names(y)),
  by.x = by, by.y = by, all = FALSE, all.x = TRUE, all.y = FALSE, ...)
```

**Arguments**

|       |  |
|-------|--|
| x     | CrunchDataset to add data to   |
| y     | CrunchDataset to copy data from. May be filtered by rows and/or columns.   |
| by    | character, optional shortcut for specifying by.x and by.y by alias if the key variables have the same alias in both datasets.  |
| by.x  | CrunchVariable in x on which to join, or the alias (following crunch.namekey.dataset) of a variable. Must be type numeric or text and have all unique, non-missing values. |
| by.y  | CrunchVariable in y on which to join, or the alias (following crunch.namekey.dataset) of a variable. Must be type numeric or text and have all unique, non-missing values. |
| all   | logical: should all rows in x and y be kept, i.e. a "full outer" join? Only FALSE is currently supported.  |
| all.x | logical: should all rows in x be kept, i.e. a "left outer" join? Only TRUE is currently supported.   |
| all.y | logical: should all rows in y be kept, i.e. a "right outer" join? Only FALSE is currently supported.   |
| copy  | logical: make a virtual or materialized join. Default is TRUE, which means materialized. Virtual joins are experimental and not advised.                                   |
| ...   | additional arguments, ignored  |

**Value**

x extended by the columns of y, matched on the "by" variables.

---

listDatasets

*Show the names of all Crunch datasets associated with a catalog*

---

**Description**

If shiny is TRUE the function launches a shiny gadget which allows you to navigate your Crunch projects and datasets. This is useful if you can't remember a dataset's project and also saves typing long dataset names.

**Usage**

```
listDatasets(kind = c("active", "all", "archived"), project = NULL,
             refresh = FALSE, shiny = FALSE)
```

**Arguments**

|         |   |
|---------|---|
| kind    | character specifying whether to look in active, archived, or all datasets. Default is "active", i.e. non-archived.  |
| project | CrunchProject entity, character name of a project, or NULL, the default. If a Project entity or reference is supplied, the function will display datasets from that Project's datasets. If NULL, the primary dataset catalog for the user will be used. |
| refresh | logical: should the function check the Crunch API for new datasets? Default is FALSE.   |
| shiny   | logical: launch a shiny gadget to help select the right dataset. The gadget will return a valid loadDataset() call which loads the selected dataset.  |

**Value**

Character vector of dataset names, each of which would be a valid input for `loadDataset()`

---

|             |                              |
|-------------|------------------------------|
| loadDataset | <i>Load a Crunch Dataset</i> |
|-------------|------------------------------|

---

**Description**

Load a Crunch Dataset

**Usage**

```
loadDataset(dataset, kind = c("active", "all", "archived"), project = NULL,
  refresh = FALSE)
```

**Arguments**

|         |   |
|---------|---|
| dataset | character, the name of a Crunch dataset that you have access to, or a DatasetTuple.   |
| kind    | character specifying whether to look in active, archived, or all datasets. Default is "active", i.e. non-archived.  |
| project | CrunchProject entity, character name of a project, or NULL, the default. If a Project entity or reference is supplied, the function will display datasets from that Project's datasets. If NULL, the primary dataset catalog for the user will be used. |
| refresh | logical: should the function check the Crunch API for new datasets? Default is FALSE.   |

**Value**

An object of class CrunchDataset



**Examples**

```
## Not run:
dsName <- listDatasets()[1]
ds <- loadDatasets(dsName)

## End(Not run)
```

---

|              |  |
|--------------|--|
| locateEntity | <i>Find an entity in an order object</i> |
|--------------|--|

---

**Description**

Find an entity in an order object

**Usage**

```
locateEntity(x, ord)
```

**Arguments**

|     |  |
|-----|--|
| x   | Variable or Dataset, depending on the type of order, or URL for it |
| ord | ShojiOrder (VariableOrder or DatasetOrder)                         |

**Value**

If x is found in ord, a character vector of group names that provide the "path" to the entity. The length of the vector corresponds to the depth of nesting. If not found, NA is returned

---

|      |  |
|------|--|
| lock | <i>Lock and unlock a dataset for editing</i> |
|------|--|

---

**Description**

Crunch allows a single active editor. If you have edit privileges but are not currently editing the dataset, you must unlock the dataset before making changes. You may then lock the dataset when you're done editing.

**Usage**

```
lock(dataset)

unlock(dataset)
```

**Arguments**

|         |                 |
|---------|-----------------|
| dataset | a CrunchDataset |
|---------|-----------------|

**Value**

dataset, invisibly, after having set the current editor.

---

|       |   |
|-------|---|
| login | <i>Authenticate with the Crunch API</i> |
|-------|---|

---

**Description**

Note that you can store your Crunch account info in your `.Rprofile` under `crunch.email` and `crunch.pw` for convenience. If you do so, you can simply `login()` to authenticate. For running batch jobs, this could be particularly useful. However, be warned that storing your password in a plain text file such as `.Rprofile` is a security risk (though perhaps less so than in every `.R` script you write), and we cannot officially recommend that you do so.

**Usage**

```
login(email = envOrOption("crunch.email"),
      password = envOrOption("crunch.pw"), ...)
```

**Arguments**

|                       |  |
|-----------------------|--|
| <code>email</code>    | the email address associated with the user's Crunch account                                    |
| <code>password</code> | the password associated with the user's Crunch account   |
| <code>...</code>      | additional parameters passed in the authentication. Not currently supported by the Crunch API. |

**Details**

Additionally, your email and password can be stored in and read from the environmental variables `R_CRUNCH_EMAIL` and `R_CRUNCH_PW` respectively.

If a password is not supplied (or, if no arguments are supplied and only the `crunch.email` is specified in `.Rprofile`), and you are in an interactive session, you will be prompted to enter your password. At present, this is the most secure practice as your password is not stored locally.

---

|        |                                       |
|--------|---------------------------------------|
| logout | <i>Kill the active Crunch session</i> |
|--------|---------------------------------------|

---

**Description**

Kill the active Crunch session

**Usage**

```
logout()
```

---

|           |   |
|-----------|---|
| makeArray | <i>Make a Categorical Array or Multiple Response variable</i> |
|-----------|---|

---

### Description

Array variables are composed of a set of "subvariables" bound together for display in the app. For example, you might have a set of survey questions that ask how the respondent would rate a tv show from 1-5. Array variables allow you to display all of their ratings in a compact table rather than a set of distinct variables.

### Usage

```
makeArray(subvariables, name, ...)
```

```
makeMR(subvariables, name, selections, ...)
```

```
deriveArray(subvariables, name, selections, ...)
```

### Arguments

|              |   |
|--------------|---|
| subvariables | a list of Variable objects to bind together, or a Dataset subset which contains only the Variables to bind.   |
| name         | character, the name that the new Categorical Array variable should have.  |
| ...          | Optional additional attributes to set on the new variable.  |
| selections   | character, for makeMR and deriveArray the names of the categories to mark as the dichotomous selections. Required for makeMR; optional for deriveArray; ignored in makeArray. |

### Value

A VariableDefinition that when added to a Dataset will create the categorical-array or multiple-response variable. deriveArray will make a derived array expression (or a derived multiple response expression if selections are supplied), while makeArray and makeMR return an expression that "binds" variables together, removing them from independent existence.

---

|                  |                             |
|------------------|-----------------------------|
| makeCaseVariable | <i>Make a case variable</i> |
|------------------|-----------------------------|

---

### Description

The makeCaseVariable function derives a variable using values from other variables. These are evaluated in the order they are supplied in the list as the cases argument (they proceed in an IF, ELSE IF, ELSE IF, ..., ELSE fashion); the first one that matches selects the corresponding value from the case list.

**Usage**

```
makeCaseVariable(..., cases, data = NULL, name)
```

**Arguments**

|       |  |
|-------|--|
| ...   | a sequence of named expressions to use as cases as well as other properties to pass about the case variable (i.e. alias, description)  |
| cases | a list of lists with each case condition to use each must include at least a name and an expression element. Cases may also include missing (logical) and numeric_value (numeric). |
| data  | (optional) a crunch dataset to use. Specifying this means you don't have to put dataset\$ in front of each variable name.  |
| name  | a character to use as the name of the case variable to create  |

**Details**

There are two ways to specify cases, but you must pick only one (note these two will produce the same case variable):

1. When you just want to specify conditions, you can use named conditions: `makeCaseVariable(case1=ds$v1 == 1, ca`
2. You can also use the cases argument, which is useful when you want to provide category ids, numeric values, or missingness: `makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),`

Rows in the dataset that do not match any of the provided "cases" will be assigned to an "else" category. By default, Crunch will use the system missing "No Data" category. Alternatively, you can provide an else case definition for these rows by including as the last "case" you provide one with its expression set to the string "else". See the examples for details.

**Value**

A [VariableDefinition](#) that will create the new case variable when assigned into the Dataset.

**Examples**

```
## Not run:
makeCaseVariable(case1=ds$v1 == 1, case2=ds$v2 == 2, name="new case")
makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),
                             list(expression=ds$v2 == 2, name="case2")),
                 name="new case")

# different ways to specify else cases
makeCaseVariable(cases=list(list(expression=ds$v1 == 1, name="case1"),
                             list(expression=ds$v2 == 2, name="case2"),
                             list(expression="else", name="other")),
                 name="new case")
makeCaseVariable(case1=ds$v1 == 1, case2=ds$v2 == 2, other="else", name="new case")

# the dataset can be specified with data=
makeCaseVariable(case1=v1 == 1, case2=v2 == 2, data=ds, name="new case")
```

```
## End(Not run)
```

---

|                |   |
|----------------|---|
| makeMRFromText | <i>Create Multiple Response Variable from Delimited lists</i> |
|----------------|---|

---

### Description

Surveys often record multiple response questions in delimited lists where each respondent's selections are separated by a delimiter like ; or |. This function breaks the delimited responses into subvariables, uploads those subvariables to Crunch, and finally creates a multiple response variable from them.

### Usage

```
makeMRFromText(var, delim, name, selected = "selected",
  not_selected = "not_selected", unanswered = NA, ...)
```

### Arguments

|              |   |
|--------------|---|
| var          | The variable containing the delimited responses                         |
| delim        | The delimiter separating the responses                                  |
| name         | The name of the resulting MR variable                                   |
| selected     | A character string used to indicate a selection, defaults to "selected" |
| not_selected | Character string identifying non-selection, defaults to "not_selected"  |
| unanswered   | Character string indicating non-response, defaults to NA.               |
| ...          | Other arguments to be passed on to <a href="#">makeMR()</a>             |

### Value

a Multiple response variable definition

---

|            |                                   |
|------------|-----------------------------------|
| makeWeight | <i>Generate a weight variable</i> |
|------------|-----------------------------------|

---

### Description

This function allows you to generate a weight variable by supplying a set of categorical variables and the target distribution for each of the variables' categories. Weights are computed by iteratively 'raking' conditional 'cells' to the provided marginal targets.

### Usage

```
makeWeight(..., name)
```

**Arguments**

|      |  |
|------|--|
| ...  | A series of expressions of the form <code>variable ~ target_weights</code> . The variable must be a categorical Crunch variable, and the target weights must be a numeric vector whose length should be equal to the number of categories contained in the variable, and whose sum is equal to 100 or 1. If you supply fewer target weights than there are categories <code>makeWeight</code> will pad the target weight vector with 0s. |
| name | The name of the resulting variable   |

**Details**

For instance, if you wanted to create a weight variable which equally weighted four categories stored in `ds$var` you would call `ds$weight1 <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight1")`. Note that `makeWeight` returns a `VariableDefinition`, an expression that when assigned into your Dataset becomes a derived variable. This does not on its own set the new variable as "the weight" for your dataset. To set that attribute, use `weight()`. Alternatively, you can also create the variable and set the weight attribute in one step with `weight(ds) <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight1")`

**Value**

A crunch `VariableDefinition()` of the weight variable

**See Also**

`weight<-()`; `settings()` for the "default weight" for other dataset viewers.

**Examples**

```
## Not run:
mtcars$cyl <- as.factor(mtcars$cyl)
mtcars$gear <- as.factor(mtcars$gear)
ds <- newDataset(mtcars)
# Create a new "raked" variable
ds$weight <- makeWeight(ds$cyl ~ c(30, 30, 40, 0),
  ds$gear ~ c(20, 20, 60, 0), name = "weight")
summary(ds$weight)
# ds$weight is not "the weight" for the dataset unless you set it:
weight(ds) <- ds$weight
# Or, you can create the variable and set as weight in one step:
weight(ds) <- makeWeight(ds$var ~ c(25, 25, 25, 25), name = "weight2")

## End(Not run)
```

---

|                |  |
|----------------|--|
| matchCatToFeat | <i>Match categories with features from geodata</i> |
|----------------|--|

---

**Description**

Match categories with features from geodata

**Usage**

```
matchCatToFeat(categories, all_features = availableGeodataFeatures())
```

**Arguments**

|              |  |
|--------------|--|
| categories   | a vector of categories to match  |
| all_features | a dataframe of all available geodata features. (default: downloaded from Crunch servers) |

**Value**

geodatum to associate with the variable that produced categories

---

|    |                       |
|----|-----------------------|
| me | <i>My user entity</i> |
|----|-----------------------|

---

**Description**

Get the user entity of the currently authenticated user.

**Usage**

```
me()
```

**Value**

A UserEntity

---

```
members<- ,CrunchTeam,MemberCatalog-method
```

*Teams*

---

**Description**

Teams contain users and datasets. You can share a dataset with a group of users by sharing the dataset with a team. You can also share a set of datasets with a user all at once by adding the user to a team that contains those datasets.

**Usage**

```
## S4 replacement method for signature 'CrunchTeam,MemberCatalog'
members(x) <- value

## S4 replacement method for signature 'CrunchTeam,character'
members(x) <- value

## S4 method for signature 'CrunchProject'
members(x)

## S4 replacement method for signature 'CrunchProject,MemberCatalog'
members(x) <- value

## S4 replacement method for signature 'CrunchProject,character'
members(x) <- value

## S4 method for signature 'CrunchTeam'
members(x)
```

**Arguments**

|       |   |
|-------|---|
| x     | a <i>CrunchTeam</i>   |
| value | for <i>members&lt;-</i> , a character vector of emails or URLs of users to add to the team. |

**Details**

These methods allow you to work with teams. Find your teams with the [getTeams\(\)](#) function, which returns your *TeamCatalog*. You can extract an individual team by name, or create a team by assigning into the function. To create a team by assignment, assign a list to `teams("myteam") <- value_list`, the `value_list` can either empty (to just create a team with that name), or can contain a "members" element with the emails or URLs of users to add to the team. Users can be also be added later with the *members<-* method.

**Value**

*members* returns a *MemberCatalog*, which has references to the users that are members of the team. *members<-* returns `x` with the given users added to the members catalog.



**See Also**[getTeams](#)

---

**merge***Merge a CrunchDataFrame*

---

**Description**

merging a `CrunchDataFrame` with a local dataframe is useful in situations where you have new information in your local R session that you want to connect with Crunch data. For example, for making plots with Crunch and non-Crunch data. It produces a hybrid `CrunchDataFrame` that has the local data attached to it, but like normal `CrunchDataFrames` it is still judicious about downloading data from the server only when it is needed.

**Usage**

```
## S3 method for class 'CrunchDataFrame'
merge(x, y, by = intersect(names(x), names(y)),
      by.x = by, by.y = by, sort = c("x", "y"), ...)
```

**Arguments**

|                   |  |
|-------------------|--|
| <code>x</code>    | a <code>CrunchDataFrame</code>   |
| <code>y</code>    | a standard <code>data.frame</code>   |
| <code>by</code>   | name of the variable to match in both data sources (default: the intersection of the names of <code>x</code> and <code>y</code> )  |
| <code>by.x</code> | name of the variable to match in <code>x</code>  |
| <code>by.y</code> | name of the variable to match in <code>y</code>  |
| <code>sort</code> | character, either "x" or "y" (default: "x"). Which of the inputs should be used for the output order. Unlike <code>merge.data.frame</code> , <code>merge.CrunchDataFrame</code> will not re-sort the order of the output. It will use the order of either <code>x</code> or <code>y</code> . |
| <code>...</code>  | ignored  |

**Details**

Merging a `CrunchDataFrame` with a local dataframe does not allow specifying all rows from both sources. Instead, the resulting `CrunchDataFrame` will include all of the rows in whichever source is used for sorting (`x` or `y`). So if you specify `sort="x"` (the default) all rows of `x` will be present but rows in `y` that do not match with rows in `x` will not be present.

Merging a `CrunchDataFrame` with a local dataframe is experimental and might result in unexpected results. One known issue is that using `merge` on a `CrunchDataFrame` will change the both the `CrunchDataFrame` used as input as well as create a new `CrunchDataFrame`.

**Value**

a `CrunchDataFrame` with columns from both `x` and `y`

---

|           |   |
|-----------|---|
| mergeFork | <i>Merge changes to a dataset from a fork</i> |
|-----------|---|

---

**Description**

Merge changes to a dataset from a fork

**Usage**

```
mergeFork(dataset, fork, autorollback = TRUE, force = FALSE)
```

**Arguments**

|              |  |
|--------------|--|
| dataset      | The CrunchDataset to merge to  |
| fork         | The CrunchDataset, perhaps forked from dataset, that is to be merged in.   |
| autorollback | logical If the merge fails, should dataset be restored to its state prior to the merge, or should it be left in its partially merged state for debugging and manual fixing? Default is TRUE.   |
| force        | logical Attempt to push through merge conflicts by dropping all changes to dataset that occurred after fork diverged from and take only the changes from fork? Default is FALSE. You should only use force=TRUE after first attempting and failing to merge without forcing. |

**Value**

dataset with changes from fork merged to it.

---

|                       |   |
|-----------------------|---|
| modifyWeightVariables | <i>Change which variables can be set as a dataset's weight.</i> |
|-----------------------|---|

---

**Description**

modifyWeightVariables allows you to change the variables which are eligible to be used as a dataset's weight. You can also add variables to the weight variables catalog by assignment with `weightVariables(ds) <- "weight"` or `is.weightVariable(ds$weight) <- TRUE`.

**Usage**

```
modifyWeightVariables(x, vars, type = "append")

## S4 replacement method for signature 'CrunchDataset'
weightVariables(x) <- value

is.weightVariable(x)

## S4 replacement method for signature 'NumericVariable'
is.weightVariable(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | a CrunchDataset   |
| vars  | Variables to add or remove this can be a numeric Crunch variable, list of numeric Crunch variables or a character vector with the aliases of numeric Crunch variables. Setting vars to NULL clears a datasets weightVariables   |
| type  | a character string determining how the weightVariables will be modified: <ul style="list-style-type: none"> <li>• "append" : add vars to the current weight variables</li> <li>• "remove" : remove vars from the current list of weight variables</li> <li>• "replace": replace the current weight variables with vars</li> </ul> |
| value | For the weightVariables() and is.weightVariable setters the variables to append to a dataset's weightVariables.   |

**Details**

Editors can change which variables can be set as the weighting variable for a dataset. For instance if several weights have been calculated they can let the user choose which of those variables to use a weight, but prevent the user from choosing other variables as weight. This function allows you to change the weightVariables of a dataset.

**Value**

a CrunchDataset

**Examples**

```
## Not run:
modifyweightVariables(ds, "weight", "append")
weightVariables(ds) <- list(ds$weight, ds$weight2)
weightVariables(ds) <- NULL
weightVariables(ds) <- c("weight", "weight2")
is.weightVariables(ds$weight) <- TRUE

## End(Not run)
```

---

moveToGroup

*Move entities to a group*

---

**Description**

Shoji entities can be placed into groups, this is mostly used for grouping variables for display in the app, but is technically possible for any of the order catalogs. This function moves an entity to one of these groups.

**Usage**

```
moveToGroup(x, value)
```

```
moveToGroup(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | VariableGroup                                       |
| value | Variable, VariableCatalog subset, or Dataset subset |

**Details**

The function has two versions: a regular function and a setter. They do the same thing, but the setter is probably more succinct.

**Value**

x with the entities in value appended to it. If the containing order object has `duplicates=FALSE`, the entities will be "moved" to this group. Otherwise, their references will be copied to the group.

**Examples**

```
## Not run:
moveToGroup(ordering(ds)[["Demographics"]]) <- ds[c("gender", "age")]

## End(Not run)
```

---

multitable-catalog      *Multitable entities for a dataset*

---

**Description**

Multitable entities for a dataset

**Usage**

```
## S4 method for signature 'CrunchDataset'
multitables(x)

## S4 replacement method for signature 'CrunchDataset'
multitables(x) <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | a CrunchDataset                                |
| value | for the assignment method, a MultitableCatalog |

**Value**

an object of class `MultitableCatalog` containing references to `Multitable` entities. (Setter returns the `Dataset`.)

## Description

Variables in Crunch datasets are organized into folders, like in a file system. These functions allow you to create new folders and move objects into folders. Their names, `mv` and `mkdir`, suggest their Unix file utility inspiration.

## Usage

```
mv(x, variables, path)
```

```
mkdir(x, path)
```

## Arguments

|                        |   |
|------------------------|---|
| <code>x</code>         | A <code>CrunchDataset</code> or <code>VariableFolder</code>   |
| <code>variables</code> | A <code>Variable</code> , selection of variables from dataset, or any other object that can be moved to a folder.   |
| <code>path</code>      | A character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default, configurable via <code>options(crunch.delimiter)</code> ). The path is interpreted as relative to the location of the folder <code>x</code> (when <code>x</code> is a dataset, that means the root, top-level folder). <code>path</code> may also be a <code>VariableFolder</code> object. |

## Details

The functions have some differences from the strict behavior of their Unix ancestors. For one, they work recursively, without additional arguments: `mkdir` will make every directory necessary to construct the requested path, even if all parent directories didn't already exist; and `mv` doesn't require that the directory to move to already exist—it will effectively call `mkdir` along the way.

## Value

`x`, with the folder at `path` guaranteed to be created, and for `mv`, containing `variables` moved into it.

## See Also

`cd()` to select a folder by path; `rmdir()` to delete a folder; `folder()` to identify and set an object's parent folder; `base::dir.create()` if you literally want to create a directory in your local file system, which `mkdir()` does not do

**Examples**

```
## Not run:
ds <- loadDataset("Example survey")
ds <- mv(ds, c("gender", "age", "educ"), "Demographics")
ds <- mkdir(ds, "Key Performance Indicators/Brand X")
# These can also be chained together
require(magrittr)
ds <- ds %>%
  mv(c("aware_x", "nps_x"), "Key Performance Indicators/Brand X") %>%
  mv(c("aware_y", "nps_y"), "Key Performance Indicators/Brand Y")
# Can combine with cd() and move things with relative paths
ds %>%
  cd("Key Performance Indicators/Brand X") %>%
  mv("nps_x", "../Net Promoters")
# Can combine with folder() to move objects to the same place as something else
ds %>% mv("nps_y", folder(ds$nps_x))

## End(Not run)
```

---

na-omit-categories      *Omit missing categories*

---

**Description**

Omit missing categories

**Usage**

```
## S4 method for signature 'Categories'
na.omit(object, ...)
```

**Arguments**

|        |                               |
|--------|-------------------------------|
| object | Categories                    |
| ...    | additional arguments, ignored |

**Value**

object with any categories that have missing: TRUE excluded

---

name, AbstractCategory-method  
*Category attributes*

---

## Description

Functions to access and set category attributes.

## Usage

```
## S4 method for signature 'AbstractCategory'  
name(x)  
  
## S4 replacement method for signature 'AbstractCategory'  
name(x) <- value  
  
## S4 replacement method for signature ``NULL``  
name(x) <- value  
  
## S4 method for signature 'AbstractCategory'  
id(x)  
  
## S4 method for signature 'Category'  
value(x)  
  
## S4 replacement method for signature 'Category'  
value(x) <- value  
  
## S4 method for signature 'Category'  
is.selected(x)
```

## Arguments

|       |  |
|-------|--|
| x     | a Category                                   |
| value | For the setters, an appropriate value to set |

## Value

name returns character; value and id return numeric; value but not id may be NA; is.selected returns logical indicating whether this Category is a "selected" dichotomy. Setters return x duly modified.

## See Also

[Categories dichotomize](#)

---

names, BatchCatalog-method

*Get and set names, aliases on Catalog-type objects*

---

### Description

These methods let you get and set names and aliases for variables in a Dataset's catalog, or within [Subvariables](#) in an array variable. They work like the base R names methods.

### Usage

```
## S4 method for signature 'BatchCatalog'
names(x)

## S4 method for signature 'CrunchDataset'
names(x)

## S4 replacement method for signature 'MultitableCatalog'
names(x) <- value

## S4 method for signature 'ShojiCatalog'
names(x)

## S4 replacement method for signature 'ShojiCatalog'
names(x) <- value

## S4 method for signature 'ShojiCatalog'
emails(x)

## S4 method for signature 'ShojiFolder'
types(x)

## S4 method for signature 'CategoricalArrayVariable'
names(x)

## S4 method for signature 'VariableCatalog'
aliases(x)

## S4 replacement method for signature 'VariableCatalog'
aliases(x) <- value

## S4 method for signature 'VariableCatalog'
notes(x)

## S4 replacement method for signature 'VariableCatalog'
notes(x) <- value
```



```
## S4 method for signature 'VariableCatalog'  
descriptions(x)  
  
## S4 replacement method for signature 'VariableCatalog'  
descriptions(x) <- value  
  
## S4 method for signature 'VariableCatalog'  
types(x)  
  
## S4 method for signature 'VariableCatalog'  
ids(x)  
  
## S4 method for signature 'VariableFolder'  
aliases(x)  
  
## S4 method for signature 'VersionCatalog'  
names(x)  
  
## S4 method for signature 'VersionCatalog'  
descriptions(x)  
  
## S4 method for signature 'VersionCatalog'  
timestamps(x)
```

### Arguments

|       |   |
|-------|---|
| x     | a VariableCatalog, Subvariables, or similar object                |
| value | For the setters, an appropriate-length character vector to assign |

### Details

Note that the Dataset names method returns the aliases of its variables by default. This behavior is controlled by `getOption("crunch.namekey.dataset")`. Set `options(crunch.namekey.dataset="name")` if you wish to use variable names. See the variables vignette for more information.

### Value

Getters return the character object in the specified slot; setters return x duly modified.

### See Also

[Subvariables Categories](#) `base::names()` `vignette("variables", package="crunch")`

---

`newDataset`*Upload data to Crunch to make a new dataset*

---

### Description

This function creates a new dataset on the Crunch server with either a `data.frame` or similar object in your R session, a file, or a URL to a file. It captures available metadata from your R object and translates it into Crunch types.

### Usage

```
newDataset(x, name = NULL, ...)
```

### Arguments

|                   |   |
|-------------------|---|
| <code>x</code>    | a <code>data.frame</code> or other rectangular R data object, or a string file name or URL to upload to create a dataset. The file may be a compressed Zip file containing a single file in CSV or SPSS format. |
| <code>name</code> | character name to give the new Crunch dataset. By default the function uses the name of the R object, or, if passing a file, the file name.   |
| <code>...</code>  | additional arguments passed to <code>createDataset()</code>   |

### Details

If you have an SPSS file, it is better specify the file name directly rather than first reading it into R. Uploading SPSS files directly to Crunch will preserve metadata that is stripped by the R import, regardless of the library used to read it into R.

### Value

If successful, an object of class `CrunchDataset`.

### See Also

[newDatasetFromFile\(\)](#); [newDatasetByColumn\(\)](#) for an alternate upload method.

### Examples

```
## Not run:  
ds <- newDataset(mtcars, "cars")  
ds <- newDataset("mysurvey.sav")  
  
## End(Not run)
```

---

|           |                            |
|-----------|----------------------------|
| newFilter | <i>Create a new filter</i> |
|-----------|----------------------------|

---

### Description

This function creates a new filter for a `CrunchDataset`. You can achieve the same results by assigning into a dataset's filters catalog using `filters()`, but this may be a more natural way to think of the action, particularly when you want to do something with the filter entity after you create it.

### Usage

```
newFilter(name, expression, catalog = NULL, ...)
```

### Arguments

|            |   |
|------------|---|
| name       | character name for the filter   |
| expression | <code>CrunchLogicalExpr</code> with which to make a filter entity   |
| catalog    | <code>FilterCatalog</code> in which to create the new filter. May also provide a dataset entity. If omitted, the function will attempt to infer the dataset (and thus its <code>FilterCatalog</code> ) from the contents of expression. |
| ...        | Additional filter attributes to set, such as <code>is_public</code> .   |

### Value

A `CrunchFilter` object.

---

|               |                                |
|---------------|--------------------------------|
| newMultitable | <i>Create a new Multitable</i> |
|---------------|--------------------------------|

---

### Description

Multitables, or "banners" or "crossbreaks", define a set of variables or or query expressions to crosstab with as a unit. They are used in the Crunch web app to display tables side by side, as well as to define one dimension of a tab book.

### Usage

```
newMultitable(formula, data, name, ...)
```

**Arguments**

|         |  |
|---------|--|
| formula | an object of class 'formula' object with the cross-classifying variables separated by '+' on the right-hand side. Following how <code>stats::formula()</code> works in R, it should start with "~". Variables on left-hand side of the formula have no meaning in this function. |
| data    | an object of class <code>CrunchDataset</code> in which to create the multitable, and to which the variables referenced in <code>formula</code> belong.   |
| name    | character name to give the new multitable object. If omitted, a default name will be derived from <code>formula</code> .   |
| ...     | Additional multitable attributes to set. Options include <code>is_public</code> .  |

**Value**

An object of class `Multitable`

**See Also**

[stats::formula](#)

**Examples**

```
## Not run:
m <- newMultitable(~ gender + age4 + marstat, data=ds)
name(m) # [1] "gender + age4 + marstat"

## End(Not run)
```

---

newProject

*Create a new project*

---

**Description**

This function creates a new project. You can achieve the same results by assigning into the projects catalog, but this may be a more natural way to think of the action, particularly when you want to do something with the project entity after you create it.

**Usage**

```
newProject(name, members = NULL, catalog = projects(), ...)
```

**Arguments**

|         |   |
|---------|---|
| name    | character name for the project  |
| members | Optional character vector of emails or user URLs to add as project members.   |
| catalog | ProjectCatalog in which to create the new project. There is only one project catalog currently, <code>projects()</code> , but this is left here so that all new* functions follow the same pattern. |
| ...     | Additional project attributes to set  |

**Value**

A CrunchProject object.

**Examples**

```
## Not run:
proj <- newProject("A project name")
# That is equivalent to doing:
p <- projects()
p[["A project name"]] <- list()
proj <- p[["A project name"]]

proj2 <- newProject("Another project", members="you@yourco.com")
# That is equivalent to doing:
p[["Another project"]] <- list(members="you@yourco.com")
proj <- p[["Another project"]]

## End(Not run)
```

---

noTransforms

*Remove transformations from a CrunchCube*

---

**Description**

Remove transformations from a CrunchCube

**Usage**

```
noTransforms(cube)
```

**Arguments**

cube            a CrunchCube

**Value**

the CrunchCube with no transformations

**Removing transforms**

noTransforms() is useful if you don't want to see or use any transformations like Subtotals and Headings. This action only applies to the CrunchCube object in R: it doesn't actually change the variables on Crunch servers or the query that generated the CrunchCube.

**Examples**

```
## Not run:
# A CrunchCube with a heading and subtotals
crtabs(~opinion, ds)
#           All opinions
#           Strongly Agree 23
#           Somewhat Agree 24
#           Agree 47
# Neither Agree nor Disagree 18
#           Somewhat Disagree 16
#           Strongly Disagree 19
#           Disagree 35

noTransforms(crtabs(~opinion, ds))
#           Strongly Agree           Somewhat Agree Neither Agree nor Disagree
#           23                   24
#           Somewhat Disagree Strongly Disagree
#           16                   19

## End(Not run)
```

---

 ordering

*Get and set VariableOrder*


---

**Description**

The ordering methods allow you to get and set a [VariableOrder](#) on a [CrunchDataset](#) or on the [VariableCatalog](#) that the dataset contains.

**Usage**

```
## S4 method for signature 'CrunchDataset'
ordering(x)

## S4 replacement method for signature 'CrunchDataset'
ordering(x) <- value

## S4 method for signature 'VariableCatalog'
ordering(x)

## S4 replacement method for signature 'VariableCatalog'
ordering(x) <- value

## S4 method for signature 'DatasetCatalog'
ordering(x)

## S4 replacement method for signature 'DatasetCatalog'
ordering(x) <- value
```

**Arguments**

x a VariableCatalog or CrunchDataset  
 value a valid VariableOrder object

**Value**

ordering returns a VariableOrder object, while ordering<- sets the VariableOrder

---

owners *See who owns these datasets*

---

**Description**

See who owns these datasets

**Usage**

owners(x)  
 ownerNames(x)

**Arguments**

x DatasetCatalog

**Value**

For owners, the URLs of the users or projects that own these datasets. For ownerNames, their names.

---

pendingStream *Get the pending streams for a dataset*

---

**Description**

Retrieves the number of pending messages. Use [appendStream\(\)](#) to append all pending streamed rows to the dataset.

**Usage**

pendingStream(ds)

**Arguments**

ds a CrunchDataset

**Value**

number of pending messages in the stream for the dataset

---

|             |  |
|-------------|--|
| permissions | <i>See who has access to a dataset</i> |
|-------------|--|

---

**Description**

See who has access to a dataset

**Usage**

```
## S4 method for signature 'CrunchDataset'
permissions(x)
```

**Arguments**

|   |               |
|---|---------------|
| x | CrunchDataset |
|---|---------------|

**Value**

A PermissionCatalog containing information on the users and teams that have access to this dataset.

---

|    |   |
|----|---|
| pk | <i>Get and set the primary key for a Crunch dataset</i> |
|----|---|

---

**Description**

A primary key is a variable in a dataset that has a unique value for every row. A variable must be either numeric or text type and have no duplicate or missing values. A primary key on a dataset causes updates to that dataset that have the rows with the same primary key value(s) as the first dataset to update the existing rows rather than inserting new ones.

**Usage**

```
## S4 method for signature 'CrunchDataset'
pk(x)

## S4 replacement method for signature 'CrunchDataset'
pk(x) <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | a Dataset  |
| value | For the setter, a single Variable to use as the primary key or NULL to remove the primary key. |



**Value**

Getter returns the Variable object that is used as the primary key (NULL if there is no primary key); setter returns x duly modified.

---

|              |  |
|--------------|--|
| pollProgress | <i>Check a Crunch progress URL until it finishes</i> |
|--------------|--|

---

**Description**

You'll probably only call this function if progress polling times out and its error message tells you to call pollProgress to resume.

**Usage**

```
pollProgress(progress_url, wait = 0.5)
```

**Arguments**

|              |  |
|--------------|--|
| progress_url | A Crunch progress URL  |
| wait         | Number of seconds to wait between polling. This time is increased 20 percent on each poll. |

**Value**

The percent completed of the progress. Assuming the options(crunch.timeout) (default: 15 minutes) hasn't been reached, this will be 100. If the timeout is reached, it will be the last reported progress value.

---

|            |  |
|------------|--|
| population | <i>Get and set the market size for Crunch datasets</i> |
|------------|--|

---

**Description**

Crunch Datasets allow you to set a target population size in order to extrapolate population estimates from survey percentages. These functions let you work with the population size and magnitude.

**Usage**

```
## S4 method for signature 'CrunchDataset'
popSize(x)

## S4 replacement method for signature 'CrunchDataset'
popSize(x) <- value

## S4 method for signature 'CrunchDataset'
popMagnitude(x)

## S4 replacement method for signature 'CrunchDataset'
popMagnitude(x) <- value

## S4 method for signature 'CrunchDataset'
setPopulation(x, size, magnitude)
```

**Arguments**

|           |   |
|-----------|---|
| x         | a Crunch Dataset  |
| value     | For the setters, the size or magnitude to be set  |
| size      | the target population size, to remove a population set to NULL  |
| magnitude | the order of magnitude with which to display the population size. Must be either 3, 6, or 9 for thousands, millions, and billions respectively. |

**Value**

popSize and popMagnitude return the population size or magnitude. setPopulation returns the modified dataset.

---

|                   |  |
|-------------------|--|
| preCrunchBoxCheck | <i>Check if a dataset will make a good CrunchBox</i> |
|-------------------|--|

---

**Description**

CrunchBoxes allows you to share data with the world in a simple, easy to embed format. However, not all datasets naturally translate to the CrunchBox format. This function checks your dataset to see if it

**Usage**

```
preCrunchBoxCheck(dataset)
```

**Arguments**

|         |   |
|---------|---|
| dataset | CrunchDataset, potentially subsetted on variables |
|---------|---|

**Value**

Invisibly, the dataset. Called for side-effect of printing things.

**See Also**

[CrunchBox](#)

---

prepareDataForCrunch *Translate a data.frame to Crunch format*

---

**Description**

This is called within `newDataset` to extract the Crunch metadata from the data and to transform the data to match the extracted metadata. You can call this directly in order to tailor the data import flow more finely.

**Usage**

```
prepareDataForCrunch(data, ...)
```

**Arguments**

|                   |  |
|-------------------|--|
| <code>data</code> | A <code>data.frame</code> or other rectangular R object  |
| <code>...</code>  | additional arguments passed to <code>createDataset</code> . "name" will be required by the Crunch server but is not required by this function. |

**Value**

A `data.frame` that is a transformation of data suitable for uploading to Crunch, also containing a "metadata" attribute that is the associated Crunch metadata.

**See Also**

`createWithPreparedData` `writePreparedData`

---

|              |                                    |
|--------------|------------------------------------|
| project-icon | <i>Get or set a project's icon</i> |
|--------------|------------------------------------|

---

**Description**

This function allows you to change a project's icon. Note that you must first upload the icon to a website, as this function does not allow you to upload a local file.

**Usage**

```
icon(x)
```

```
icon(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | a CrunchProject                                   |
| value | character file path of the icon image file to set |

**Value**

The URL of the project's icon. The setter returns the project after having uploaded the specified file as the new icon.

---

|          |                                |
|----------|--------------------------------|
| projects | <i>Get the project catalog</i> |
|----------|--------------------------------|

---

**Description**

Get the project catalog

**Usage**

```
projects(x = getAPIRoot())
```

**Arguments**

|   |  |
|---|--|
| x | a ShojiObject that has an associated project catalog. If omitted, the default value for x means that you will load the user's primary project catalog. (Currently, there are no other project catalogs to load.) |
|---|--|

**Value**

An object of class ProjectCatalog.

**Examples**

```
## Not run:
myprojects <- projects()
proj <- myprojects[["Project name"]]

## End(Not run)
```

---

|         |   |
|---------|---|
| refresh | <i>Get a fresh copy from the server</i> |
|---------|---|

---

**Description**

Crunch objects generally keep themselves in sync with the server when you manipulate them, but some operations cause the local version to diverge from the version on the server. For instance, someone else may have modified the dataset you're working on, or maybe you have modified a variable outside of the context of its dataset. `refresh()` allows you to get back in sync.

**Usage**

```
## S4 method for signature 'CrunchDataset'
refresh(x)

## S4 method for signature 'ShojiObject'
refresh(x)

## S4 method for signature 'CrunchVariable'
refresh(x)
```

**Arguments**

x                    pretty much any Crunch object

**Value**

a new version of x

---

|                   |  |
|-------------------|--|
| removeEmptyGroups | <i>Remove OrderGroups with no entities</i> |
|-------------------|--|

---

**Description**

This function recurses through a `ShojiOrder/OrderGroup` and removes any groups that contain no entities.

**Usage**

```
removeEmptyGroups(x)
```

**Arguments**

x VariableOrder, DatasetOrder, VariableGroup, or DatasetGroup

**Value**

x with empty groups removed.

---

|               |                            |
|---------------|----------------------------|
| resetPassword | <i>Reset your password</i> |
|---------------|----------------------------|

---

**Description**

Trigger the password reset process. Password reset instructions will be emailed to you.

**Usage**

```
resetPassword(email)
```

**Arguments**

email Your email

**Value**

NULL, invisibly. Called for its side effects.

**Examples**

```
## Not run:  
resetPassword("me@example.com")  
  
## End(Not run)
```

---

|                |  |
|----------------|--|
| restoreVersion | <i>Restore a dataset to a previously saved version</i> |
|----------------|--|

---

### Description

You can save a version of a dataset using [saveVersion\(\)](#). Savepoints are also created automatically by certain Crunch functions that make major changes to the dataset. You can get the list of saved versions with the [versions\(\)](#) function.

### Usage

```
restoreVersion(dataset, version)
```

### Arguments

|         |   |
|---------|---|
| dataset | a CrunchDataset   |
| version | either the name ("description") of the version to restore to or the integer index of the version, as given by <a href="#">versions(dataset)</a> |

### Value

dataset, rolled back to version.

### See Also

[versions](#) [saveVersion](#)

---

|       |                        |
|-------|------------------------|
| rmdir | <i>Delete a folder</i> |
|-------|------------------------|

---

### Description

Like `rmdir` in a file system, this function removes a folder. Unlike the file-system version, it does not require the folders to be empty.

### Usage

```
rmdir(x, path)
```

### Arguments

|      |   |
|------|---|
| x    | A CrunchDataset or VariableFolder   |
| path | A character "path" to the folder: either a vector of nested folder names or a single string with nested folders separated by a delimiter ("/" default, configurable via <code>options(crunch.delimiter)</code> ). The path is interpreted as relative to the location of the folder x (when x is a dataset, that means the root, top-level folder). path may also be a VariableFolder object. |

**Value**

NULL

**See Also**

[mv\(\)](#) to move entities to a folder; [cd\(\)](#) to select a folder; [base::file.remove\(\)](#) if you literally want to delete a directory from your local file system, which [rmdir\(\)](#) does not do

**Examples**

```
## Not run:
ds <- loadDataset("Example survey")
rmdir(ds, "Demographics")
# Or with %>%
require(magrittr)
ds <- ds %>%
  rmdir("Demographics")

## End(Not run)
```

---

saveVersion

---

*Create a new saved version*


---

**Description**

Crunch datasets can be saved and restored using [saveVersion](#) and [restoreVersion\(\)](#). Some Crunch functions, such as [appendDataset\(\)](#) create new savepoints automatically. To see the list of savepoints use [versions\(\)](#).

**Usage**

```
saveVersion(dataset, description = paste("Version", length(versions(dataset))
+ 1))
```

**Arguments**

|             |   |
|-------------|---|
| dataset     | a CrunchDataset   |
| description | character name to give the saved version, as in a commit message. You are encouraged, though not strictly required, to give versions unique descriptions. |

**Value**

invisibly, the URL of the newly created version

**See Also**

[versions](#) [restoreVersion](#)



---

|                |  |
|----------------|--|
| scoreCatToFeat | <i>Score similarity between a feature dataframe and categories</i> |
|----------------|--|

---

**Description**

Implemented using the Jaccard index, where a number closer to 1 is more similar.

**Usage**

```
scoreCatToFeat(features, categories)
```

**Arguments**

|            |  |
|------------|--|
| features   | a vector of features to match (usually from a subset of the output [availableGeodataFeatures]) with a single property for a single geodatum. |
| categories | a vector of categories to match  |

**Value**

the Jaccard index for the values of the property given in feat\_df and the vector of categories

---

|                |                                    |
|----------------|------------------------------------|
| searchDatasets | <i>Search Crunch for datasets.</i> |
|----------------|------------------------------------|

---

**Description**

searchDatasets searches datasets' metadata for matches to the query argument. This search will include variable names, aliases, categories, but not the content of text variables. See [the API Documentation](#) for more information about searching Crunch.

**Usage**

```
searchDatasets(query, ...)
```

**Arguments**

|       |  |
|-------|--|
| query | the text to search for in datasets and their variables (note: only alpha characters will be used, numbers and other characters will be discarded.) |
| ...   | additional options provided to the search endpoint.  |

**Value**

If successful, an object of class SearchResults

---

|      |                                   |
|------|-----------------------------------|
| self | <i>Get the URL of this object</i> |
|------|-----------------------------------|

---

**Description**

Get the URL of this object

**Usage**

```
## S4 method for signature 'ShojiObject'  
self(x)  
  
## S4 method for signature 'CrunchVariable'  
self(x)
```

**Arguments**

x                    a Crunch object

**Value**

the URL for x

---

|         |   |
|---------|---|
| session | <i>Get various catalogs for your Crunch session</i> |
|---------|---|

---

**Description**

Get various catalogs for your Crunch session

**Usage**

```
session()
```

**Value**

A Session object. Access dataset and project catalogs from it.

**Examples**

```
## Not run:  
cr <- session()  
cr$datasets  
cr$projects  
  
## End(Not run)
```

---

|                 |   |
|-----------------|---|
| session-extract | <i>Extract catalogs from a Session object</i> |
|-----------------|---|

---

**Description**

Extract catalogs from a Session object

**Usage**

```
## S4 method for signature 'Session,ANY'  
x[[i, ..., drop = FALSE]]  
  
## S4 method for signature 'Session'  
x$name  
  
## S4 replacement method for signature 'Session,ANY,ANY,ANY'  
x[[i]] <- value  
  
## S4 replacement method for signature 'Session'  
x$name <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | a Session object   |
| i     | which catalog to load. Supported values are "datasets" and "projects"  |
| ...   | additional arguments, ignored.   |
| drop  | Invalid  |
| name  | for \$, the same as i for []   |
| value | For updating, an object of the appropriate class and size to insert. In practice value is ignored; Session objects hold no state and it is assumed that any state modification on the server happens in other methods. |

**Value**

The requested catalog when extracting; a Session object if assigning.

**See Also**

session

---

|          |   |
|----------|---|
| setOrder | <i>Change the order of entities in folder</i> |
|----------|---|

---

**Description**

Change the order of entities in folder

**Usage**

```
setOrder(folder, ord)
```

**Arguments**

|        |  |
|--------|--|
| folder | A VariableFolder or other *Folder object   |
| ord    | A vector of integer indices or character references to objects contained in the folder |

**Value**

folder with the order dictated by ord. The function also persists that order on the server.

---

|          |   |
|----------|---|
| settings | <i>View and modify dataset-level settings</i> |
|----------|---|

---

**Description**

These methods allow access and control over dataset settings. Currently supported settings include:

- User Authorizations for view-only users ('viewers\_can\_export', 'viewers\_can\_share', and 'viewers\_can\_change\_weight'); and
- 'weight', which determines the default weighting variable for the dataset. Additional settings will be added in the future. See <http://docs.crunch.io/#fragments>, under 'Settings', for an up-to-date list of settings supported throughout the Crunch system. Clients may also provide and use custom settings if they choose.

**Usage**

```
settings(x)
```

```
settings(x) <- value
```

**Arguments**

|       |   |
|-------|---|
| x     | CrunchDataset                                   |
| value | A settings object (ShojiEntity), for the setter |

**Value**

The getter returns a settings object (`ShojiEntity`). The setter returns the dataset (`x`), duly modified.

**Examples**

```
## Not run:
settings(ds)
settings(ds)$viewers_can_export <- TRUE
settings(ds)$weight <- ds$myWeightVariable

## End(Not run)
```

---

|       |                        |
|-------|------------------------|
| share | <i>Share a dataset</i> |
|-------|------------------------|

---

**Description**

Share a dataset

**Usage**

```
share(dataset, users, edit = FALSE, notify = TRUE, message = NULL)
```

**Arguments**

|         |   |
|---------|---|
| dataset | a <code>CrunchDataset</code>  |
| users   | character: email address(es) or URLs of the users or teams with whom to share the dataset. If there is no Crunch user associated with an email, an invitation will be sent.   |
| edit    | logical: should the specified user(s) be given edit privileges on the dataset? Default is FALSE. edit can be a single value or, if inviting multiple users, a vector of logical values of equal length of the number of emails given. |
| notify  | logical: should users who are getting new privileges on this dataset be sent an email informing them of this fact? Default is TRUE.   |
| message | character: a message to send to the users who are receiving new privileges.   |

**Value**

Invisibly, the dataset.

**See Also**

[unshare](#)

---

|             |                                  |
|-------------|----------------------------------|
| shoji-index | <i>Get the body of a Catalog</i> |
|-------------|----------------------------------|

---

### Description

The core of Catalog data is in its "index". These methods get and set that slot.

### Usage

```
## S4 method for signature 'ShojiCatalog'
index(x)

## S4 replacement method for signature 'ShojiCatalog'
index(x) <- value
```

### Arguments

|       |  |
|-------|--|
| x     | a Catalog (VariableCatalog, Subvariables, or similar object) |
| value | For the setters, an appropriate-length list to assign        |

### Value

Getters return the list object in the "index" slot; setters return x duly modified.

---

|                   |   |
|-------------------|---|
| ShojiObject-class | <i>Mix-in class for multiple inheritance of variables and datasets.</i> |
|-------------------|---|

---

### Description

Exists for common methods in interacting with Crunch API only. Has no Extract methods declared so as not to conflict with the vector/list/data.frame methods jointly inherited in CrunchVariable and CrunchDataset.

---

ShojiOrder-extract      *Extract and update in VariableOrders and VariableGroups*

---

## Description

Extract and update in VariableOrders and VariableGroups

## Usage

```
## S4 method for signature 'ShojiOrder,ANY,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiOrder,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'ShojiOrder,ANY'
x[[i, j, ...]]

## S4 method for signature 'ShojiOrder,character'
x[[i, j, ...]]

## S4 method for signature 'ShojiOrder'
x$name

## S4 replacement method for signature 'ShojiOrder,character,missing,ShojiOrder'
x[i, j] <- value

## S4 replacement method for signature 'ShojiOrder,ANY,missing,ShojiOrder'
x[i, j] <- value

## S4 replacement method for signature 'ShojiOrder,character,missing,list'
x[[i, j]] <- value

## S4 replacement method for signature 'ShojiOrder,character,missing,character'
x[[i, j]] <- value

## S4 replacement method for signature 'ShojiOrder,character,missing,OrderGroup'
x[[i, j]] <- value

## S4 replacement method for signature 'ShojiOrder,ANY,missing,OrderGroup'
x[[i, j]] <- value

## S4 replacement method for signature 'ShojiOrder,ANY,missing,ANY'
x[[i, j]] <- value

## S4 replacement method for signature 'ShojiOrder,ANY,missing,`NULL`'
x[[i, j]] <- value
```

```
## S4 replacement method for signature 'ShojiOrder,character,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder,character,missing,ShojiOrder'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'ShojiOrder'  
x$name <- value  
  
## S4 method for signature 'OrderGroup,ANY,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'OrderGroup,character,ANY'  
x[i, j, ..., drop = TRUE]  
  
## S4 method for signature 'OrderGroup,character'  
x[[i, j, ...]]  
  
## S4 method for signature 'OrderGroup,ANY'  
x[[i, j, ...]]  
  
## S4 method for signature 'OrderGroup'  
x$name  
  
## S4 replacement method for signature 'OrderGroup,character,missing,list'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,character,missing,character'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,character,missing,ShojiOrder'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,character,missing,OrderGroup'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,ANY,missing,OrderGroup'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,numeric,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup,character,missing,`NULL`'  
x[[i, j]] <- value  
  
## S4 replacement method for signature 'OrderGroup'  
x$name <- value
```



```
## S4 replacement method for signature 'VariableOrder,character,missing,CrunchDataset'
x[[i, j]] <- value

## S4 replacement method for signature 'VariableGroup,character,missing,CrunchDataset'
x[[i, j]] <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | a VariableOrder or VariableGroup   |
| i     | an index. Numeric and logical indexing supported for both classes; character indexing supported for VariableOrder, matching on VariableGroup names |
| j     | Invalid  |
| ...   | additional arguments   |
| drop  | Ignored  |
| name  | Same as i but for \$   |
| value | For update methods, an object equivalent in class to what is being updated   |

**Value**

[[ and \$ on a VariableOrder return the VariableGroup. [[ on VariableGroup returns the entity within, either a character (URL) or nested VariableGroup. [ and assignment methods return objects of the same class as x

---

|                   |                           |
|-------------------|---------------------------|
| ShojiOrder-length | <i>Length of an Order</i> |
|-------------------|---------------------------|

---

**Description**

Length of an Order

**Usage**

```
## S4 method for signature 'ShojiOrder'
length(x)

## S4 method for signature 'OrderGroup'
length(x)
```

**Arguments**

|   |              |
|---|--------------|
| x | a ShojiOrder |
|---|--------------|

**Value**

Integer: the number of elements in the Order

---

ShojiOrder-slots      *Manipulate VariableGroup and VariableOrder*

---

**Description**

Manipulate VariableGroup and VariableOrder

**Usage**

```
## S4 method for signature 'OrderGroup'  
entities(x, simplify = FALSE)  
  
## S4 method for signature 'ShojiOrder'  
entities(x, simplify = FALSE)  
  
## S4 method for signature 'list'  
entities(x, simplify = FALSE)  
  
## S4 replacement method for signature 'OrderGroup'  
entities(x) <- value  
  
## S4 replacement method for signature 'ShojiOrder'  
entities(x) <- value  
  
## S4 method for signature 'OrderGroup'  
name(x)  
  
## S4 replacement method for signature 'OrderGroup'  
name(x) <- value  
  
## S4 method for signature 'ShojiOrder'  
names(x)  
  
## S4 method for signature 'OrderGroup'  
names(x)  
  
## S4 replacement method for signature 'ShojiOrder'  
names(x) <- value  
  
## S4 method for signature 'ShojiOrder'  
duplicates(x)  
  
## S4 method for signature 'OrderGroup'  
duplicates(x)  
  
## S4 method for signature 'VariableCatalog'  
duplicates(x)
```

```
## S4 replacement method for signature 'ShojiOrder,logical'  
duplicates(x) <- value  
  
## S4 replacement method for signature 'OrderGroup,logical'  
duplicates(x) <- value  
  
## S4 replacement method for signature 'VariableCatalog,logical'  
duplicates(x) <- value
```

### Arguments

|          |  |
|----------|--|
| x        | a VariableGroup or VariableOrder   |
| simplify | logical: should variable URLs inside of groups be flattened or preserved in their nested lists? Default isFALSE.   |
| value    | <ol style="list-style-type: none"><li>1. For name, a character (length-1 vector); for names, a character vector of equal length to the number of VariableGroups being modified; for entities, either a character vector of variable URLs or a list containing a combination of variable URLs and VariableGroups. Note that group names must be unique, should be greater than 0 characters long, and "ungrouped" is a reserved group name.</li><li>2. For duplicates, logical for whether duplicate variable entries should be allowed in the VariableOrder.</li></ol> |

### Value

- entities returns Variable references and VariableGroups;
- names returns group names;
- duplicates returns logical for whether duplicate variable entries should be allowed

### See Also

[VariableOrder grouped](#)

---

show,ShojiFolder-method

*Show methods for Crunch objects*

---

### Description

Show methods for Crunch objects

**Usage**

```
## S4 method for signature 'ShojiFolder'  
show(object)  
  
## S4 method for signature 'ShojiObject'  
show(object)  
  
## S4 method for signature 'CrunchVariable'  
show(object)  
  
## S4 method for signature 'Category'  
show(object)  
  
## S4 method for signature 'Categories'  
show(object)  
  
## S4 method for signature 'Insertion'  
show(object)  
  
## S4 method for signature 'Insertions'  
show(object)  
  
## S4 method for signature 'CrunchExpr'  
show(object)  
  
## S4 method for signature 'CrunchLogicalExpr'  
show(object)  
  
## S4 method for signature 'CrunchCube'  
show(object)  
  
## S4 method for signature 'OrderGroup'  
show(object)  
  
## S4 method for signature 'CrunchGeography'  
show(object)  
  
## S4 method for signature 'MultitableResult'  
show(object)
```

**Arguments**

object            the object

**Value**

invisibly

**See Also**

[methods::show](#)

---

showTransforms, CrunchCube-method

*Show transformations on a Crunch object*

---

**Description**

showTransforms([variable]) shows a summary of a categorical variable that has transforms with the transforms calculated and applied. This is useful to see what kind transforms exist before including the variable in a CrunchCube.

**Usage**

```
## S4 method for signature 'CrunchCube'
showTransforms(x)

## S4 method for signature 'CategoricalVariable'
showTransforms(x)
```

**Arguments**

x                    a Categorical variable or CrunchCube

**Details**

showTransforms([CrunchCube]) shows the CrunchCube with all transforms calculated and applied. This is the default display method for cubes, so should not be frequently needed.

In both cases, an array is returned that includes the values of both the underlying data (either category counts or CrunchCube cell values) as well as the transformations applied.

**Value**

summary of the variable, or the full CrunchCube with transforms applied

**Examples**

```
## Not run:
showTransforms(ds$variable)

## End(Not run)
```

---

|                |                               |
|----------------|-------------------------------|
| Subtotal-class | <i>Subtotals and headings</i> |
|----------------|-------------------------------|

---

### Description

Subtotals and headings for categorical Variables and CrunchCubes. These are especially useful for making aggregates across multiple categories (sometimes referred to as *nets*, *top box*, or *top 2 box*).

### Usage

```
Subtotal(name, categories, position = c("relative", "top", "bottom"),
  after = NULL)

Heading(name, position = c("relative", "top", "bottom"), after = NULL)

Subtotal(name, categories, position = c("relative", "top", "bottom"),
  after = NULL)

is.Subtotal(x)

is.Heading(x)

are.Subtotals(x)

are.Headings(x)

Heading(name, position = c("relative", "top", "bottom"), after = NULL)

## S4 method for signature 'CrunchVariable'
subtotals(x)

## S4 method for signature 'VariableTuple'
subtotals(x)

## S4 replacement method for signature 'CrunchVariable,ANY'
subtotals(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
subtotals(x) <- value
```

### Arguments

|            |  |
|------------|--|
| name       | character the name of the subtotal or heading  |
| categories | character or numeric the category names or ids for subtotal only   |
| position   | character one of "relative", "top", or "bottom". Determines the position of the subtotal or heading, either at the top, bottom, or relative to another category in the cube (default). |

|       |   |
|-------|---|
| after | character or numeric if position is "relative", then the category name or id to position the subtotal or heading after. If not supplied this defaults to the last of the categories supplied to Subtotal. |
| x     | either a variable or CrunchCube object to add or get subtotal transforms for, for <code>is.Subtotal()</code> and <code>is.Heading()</code> an object to test if it is either a Subtotal or Heading        |
| value | For [ <code>&lt;-</code> , the replacement Subtotal to insert   |
| ...   | additional arguments to [, ignored  |

### Details

To see the subtotals or headings set for a variable, use `subtotals(variable)`

### Adding Subtotals and Headings

Subtotals and headings can be added either by passing a list of Subtotals or Headings, or they can be added one at a time by passing Subtotal or Heading to `subtotals(variable)` alone.

Adding subtotals or headings is additive; meaning that subtotals or headings that are already set on the variable are not removed when new subtotals or headings are added. To remove all subtotals and headings, set `subtotals(variable)` to NULL.

To get an array of just the subtotal rows from a CrunchCube, use the function `subtotalArray(CrunchCube)`.

### Working with Subtotals and headings

When interacting programmatically with Subtotals and Headings, it can be useful to be able to tell if something is a Subtotal or a Heading. The `is.*` family of methods are useful here: the singular versions (`is.Subtotal` and `is.Heading`) take a single object and returns TRUE if the object is either a Subtotal or a Heading and FALSE if not; the plural versions (`are.Subtotals` and `are.Headings`) take a list of objects (including an Insertions object) and returns a vector of TRUE/FALSEs.

### Removing transforms

`noTransforms()` is useful if you don't want to see or use any transformations like Subtotals and Headings. This action only applies to the CrunchCube object in R: it doesn't actually change the variables on Crunch servers or the query that generated the CrunchCube.

### Examples

```
## Not run:
# given a variable ds$opinion, with categories: Strongly Agree, Somewhat
# Agree, Neither Agree nor Disagree, Somewhat Disagree, and Strongly Disagree,
# to make two subtotals for Agree and Disagree:
subtotals(ds$opinion) <- list(
  Subtotal(name = "Agree",
           categories = c("Strongly Agree", "Somewhat Agree"),
           after = "Somewhat Agree"),
  Subtotal(name = "Disagree",
           categories = c("Strongly Disagree", "Somewhat Disagree"),
           after = "Strongly Disagree")
)
```

```

)

# headings can also be added:
subtotals(ds$opinion) <- Heading(name = "All opinions", position = "top")

# to see the subtotals and headings associated with a variable
subtotals(ds$opinion)
#      anchor      name      func      args
# 1      2      Agree subtotal 1 and 2
# 2      4      Disagree subtotal 4 and 5
# 3      0 All opinions      <NA>      NA

# when you use a variable with subtotals and headings in a cube, you see them
# by default
opinion_cube <- crtabs(~opinion, ds)
opinion_cube
#           All opinions
#           Strongly Agree 23
#           Somewhat Agree 24
#           Agree 47
# Neither Agree nor Disagree 18
#           Somewhat Disagree 16
#           Strongly Disagree 19
#           Disagree 35

# to get just the subtotals,
subtotalArray(opinion_cube)
#   Agree Disagree
#   47      35

# to remove all subtotals and headings
subtotals(ds$opinion) <- NULL
crtabs(~opinion, ds)
#           Strongly Agree 23
#           Somewhat Agree 24
# Neither Agree nor Disagree 18
#           Somewhat Disagree 16
#           Strongly Disagree 19

# if you want to temporarily remove subtotals and headings, you can with `noTransforms`
noTransforms(crtabs(~opinion, ds))
#           Strongly Agree           Somewhat Agree Neither Agree nor Disagree
#           23           24           18
#           Somewhat Disagree           Strongly Disagree
#           16           19

## End(Not run)

```

---



subtotalArray, CrunchCube-method

*Calculate the transforms from a CrunchCube*

---

## Description

applyTransforms calculates transforms (e.g. [Subtotals](#)) on a CrunchCube. Currently only the row transforms are supported. This is useful if you want to use the values from the subtotals of the CrunchCube in an analysis.

## Usage

```
## S4 method for signature 'CrunchCube'
subtotalArray(x, headings = FALSE)

applyTransforms(x, array = cubeToArray(x), ...)
```

## Arguments

|          |  |
|----------|--|
| x        | a CrunchCube   |
| headings | for subtotalArray: a logical indicating if the headings should be included with the subtotals (default: FALSE)                   |
| array    | an array to use, if not using the default array from the cube itself. (Default: not used, pulls an array from the cube directly) |
| ...      | arguments to pass to calcTransforms, for example include   |

## Details

Including the include argument allows you to specify which parts of the CrunchCube to return. The options can be any of the following: "cube\_cells" for the untransformed values from the cube itself, "subtotals" for the subtotal insertions, and "headings" for any additional headings. Any combination of these can be given, by default all will be given.

subtotalArray(cube) is a convenience function that is equivalent to applyTransforms(cube, include = c("subtotals"

## Value

an array with any transformations applied

## Examples

```
## Not run:
# to get an array of just the subtotals
subtotalArray(crtabs(~opinion, ds))
#   Agree Disagree
#   47          35

# to get the full array with the subtotals but not headings
applyTransforms(crtabs(~opinion, ds), include = c("cube_cells", "subtotals"))
```

```

#           Strongly Agree           Somewhat Agree           Agree
#           23                       24                       47
# Neither Agree nor Disagree       Strongly Disagree       Disagree
#           18                       19                       35
#           Somewhat Disagree
#           16
# to get the full array with the headings but not subtotals
applyTransforms(crtabs(~opinion, ds), include = c("cube_cells", "headings"))
#           All opinions           Strongly Agree           Somewhat Agree
#           NA                       23                       24
# Neither Agree nor Disagree       Strongly Disagree       Somewhat Disagree
#           18                       19                       16

## End(Not run)

```

---

Subvariables-class      *Subvariables in Array Variables*

---

## Description

Multiple-response and categorical-array variables are higher order variables which are made up of sets of subvariables. These methods allow you to retrieve and change the subvariables of a multiple-response or categorical-array variable.

## Usage

```

## S4 method for signature 'CategoricalArrayVariable'
subvariables(x)

## S4 method for signature 'VariableTuple'
subvariables(x)

## S4 replacement method for signature 'CategoricalArrayVariable,ANY'
subvariables(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,Subvariables'
subvariables(x) <- value

```

## Arguments

x                    A Variable or Subvariables object

value                For the setters, the appropriate values to set

**Details**

Subvariables can be accessed from array variables (including multiple response) with the `subvariables` method. They can be assigned back with the `subvariables<-` setter, but there are limitations to what is supported. Specifically, you can reorder subvariables, but you cannot add or remove subvariables by `subvariables<-` assignment. See [deleteSubvariable](#) to remove subvariables from an array.

Subvariables have a `names` attribute that can be accessed, showing the display names of the subvariables. These can be set with the `names<-` method.

Finally, subvariables can be accessed as regular (categorical) variables with the `$` and `[[` extract methods.

See the vignette on array variables for further details and examples.

**See Also**

[subvars-extract](#) [describe-catalog](#) [deleteSubvariable](#) `vignette("array-variables", package="crunch")`

---

|                 |   |
|-----------------|---|
| subvars-extract | <i>Extract and modify subsets of subvariables</i> |
|-----------------|---|

---

**Description**

Extract and modify subsets of subvariables

**Usage**

```
## S4 method for signature 'Subvariables,character'
x[[i, j, ...]]

## S4 method for signature 'Subvariables,numeric'
x[[i, j, ...]]

## S4 method for signature 'Subvariables,character,ANY'
x[i, j, ..., drop = TRUE]

## S4 replacement method for signature 'Subvariables,character,missing,CrunchVariable'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,CrunchVariable'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,`NULL`'
x[[i]] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,ANY'
x[[i]] <- value
```

```

## S4 replacement method for signature 'Subvariables,character,missing,Subvariables'
x[i] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,Subvariables'
x[i] <- value

## S4 replacement method for signature 'Subvariables,ANY,missing,ANY'
x[i] <- value

## S4 method for signature 'CategoricalArrayVariable,character,ANY'
x[i, j, ...,
  drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,missing,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,missing,character'
x[i, j, ...,
  drop = TRUE]

## S4 method for signature 'CategoricalArrayVariable,ANY'
x[[i, j, ...]]

## S4 method for signature 'CategoricalArrayVariable,character'
x[[i, j, ...]]

## S4 method for signature 'CategoricalArrayVariable'
x$name

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,character,missing,ANY'
x[[i]] <- value

## S4 replacement method for signature 'CategoricalArrayVariable'
x$name <- value

```

### Arguments

|       |   |
|-------|---|
| x     | Subvariables or an array Variable which contains subvariables |
| i     | which subvariables to extract                                 |
| j     | Invalid   |
| ...   | additional arguments  |
| drop  | Invalid   |
| value | For updating, a CrunchExpr                                    |
| name  | For \$, the name (not alias) of the subvariable to extract    |

**Value**

A subset of x if extracting, otherwise x duly modified

---

SummaryStat-class      *Summary insertions*

---

**Description**

Just like `subtotals()`s, summary statistics can be inserted into cubes. `SummaryStat()` makes an object of type `SummaryStat` which can be added on to a `CrunchCube`'s insertions to add the specified summary statistic. Currently only mean and median are supported; both use weighted algorithms to go from counts and numeric values of categories to the expected statistic. Although `SummaryStat` objects can be made by hand, it is recommended instead to use the `addSummaryStat()` function which is much quicker and easier to simply add a summary statistic to an existing `CrunchCube`.

**Usage**

```
SummaryStat(name, stat, categories = NULL, position = c("relative", "top",
  "bottom"), after = NULL, includeNA = FALSE)
```

```
SummaryStat(name, stat, categories = NULL, position = c("relative", "top",
  "bottom"), after = NULL, includeNA = FALSE)
```

```
is.SummaryStat(x)
```

```
are.SummaryStats(x)
```

**Arguments**

|                         |   |
|-------------------------|---|
| <code>name</code>       | character the name of the summary statistic   |
| <code>stat</code>       | a function to calculate the summary (e.g. mean or median)   |
| <code>categories</code> | character or numeric the category names or ids to be included in the summary statistic, if empty all categories   |
| <code>position</code>   | character one of "relative", "top", or "bottom". Determines the position of the subtotal or heading, either at the top, bottom, or relative to another category in the cube (default) |
| <code>after</code>      | character or numeric if position is "relative", then the category name or id to position the subtotal or heading after  |
| <code>includeNA</code>  | should missing categories be included in the summary?   |
| <code>x</code>          | for <code>is.SummaryStat()</code> only, an object to test if it is a <code>SummaryStat</code> object  |

**Details**

Summary statistics are intended only for `CrunchCube` objects, and are not able to be set on `Crunch` variables.

## Removing transforms

`noTransforms()` is useful if you don't want to see or use any transformations like Subtotals and Headings. This action only applies to the `CrunchCube` object in R: it doesn't actually change the variables on Crunch servers or the query that generated the `CrunchCube`.

---

tabBook

*Compute a Tab Book*

---

## Description

This function allows you to generate a tab book from a multitable and data. As with other functions, you can select the rows and columns you want to work with by subsetting the dataset you pass into the function.

## Usage

```
tabBook(multitable, dataset, weight = crunch::weight(dataset),
        format = c("json", "xlsx"), file, ...)
```

## Arguments

|                         |   |
|-------------------------|---|
| <code>multitable</code> | a <code>Multitable</code> object  |
| <code>dataset</code>    | <code>CrunchDataset</code> , which may have been subsetted with a filter expression on the rows and a selection of variables on the columns.  |
| <code>weight</code>     | a <code>CrunchVariable</code> that has been designated as a potential weight variable for <code>dataset</code> , or <code>NULL</code> for unweighted results. Default is the currently applied <a href="#">weight</a> . |
| <code>format</code>     | character export format: currently supported values are "json" (default) and "xlsx".  |
| <code>file</code>       | character local filename to write to. A default filename will be generated from the <code>multitable</code> 's name if one is not supplied and the "xlsx" format is requested. Not required for "json" format export.   |
| <code>...</code>        | Additional "options" passed to the tab book POST request.   |

## Details

By specifying a "json" format, instead of generating an Excel workbook, you'll get a `TabBookResult` object, containing nested `CrunchCube` results. You can then further format these and construct custom tab reports.

## Value

If "json" format is requested, the function returns an object of class `TabBookResult`, containing a list of `MultitableResult` objects, which themselves contain `CrunchCubes`. If "xlsx" is requested, the function invisibly returns the filename (`file`, if specified, or the the autogenerated file name). If you request "json" and wish to access the JSON data underlying the `TabBookResult`, pass in a path for `file` and you will get a JSON file written there as well.

**Examples**

```
## Not run:
m <- newMultitable(~ gender + age4 + marstat, data=ds)
tabBook(m, ds[ds$income > 1000000,], format="xlsx", file="wealthy-tab-book.xlsx")
book <- tabBook(m, ds) # Returns a TabBookResult
tables <- prop.table(book, 2)

## End(Not run)
```

---

|                 |   |
|-----------------|---|
| tabbook-methods | <i>TabBookResult and MultitableResult methods</i> |
|-----------------|---|

---

**Description**

TabBookResult and MultitableResult methods

**Usage**

```
## S4 method for signature 'TabBookResult'
length(x)

## S4 method for signature 'TabBookResult,numeric'
x[[i, j, ...]]

## S4 method for signature 'TabBookResult,character'
x[[i, j, ...]]

## S4 method for signature 'TabBookResult'
dim(x)

## S4 method for signature 'TabBookResult'
names(x)

## S4 method for signature 'TabBookResult'
aliases(x)

## S4 method for signature 'TabBookResult'
descriptions(x)

## S4 method for signature 'MultitableResult'
length(x)

## S4 method for signature 'MultitableResult,ANY'
x[[i, j, ...]]

## S4 method for signature 'MultitableResult'
names(x)
```

```
## S4 method for signature 'MultitableResult'
aliases(x)
```

```
## S4 method for signature 'MultitableResult'
descriptions(x)
```

### Arguments

|     |                                     |
|-----|-------------------------------------|
| x   | a TabBookResult or MultitableResult |
| i   | an index into x                     |
| j   | an index into x, ignored            |
| ... | also ignored                        |

### Value

Returns what you'd expect.

---

|       |  |
|-------|--|
| table | <i>Table function for Crunch objects</i> |
|-------|--|

---

### Description

Table function for Crunch objects

### Usage

```
table(..., exclude, useNA = c("no", "ifany", "always"), dnn, deparse.level)
```

### Arguments

|               |                                 |
|---------------|---------------------------------|
| ...           | CrunchVariables to tabulate     |
| exclude       | see <a href="#">base::table</a> |
| useNA         | see <a href="#">base::table</a> |
| dnn           | see <a href="#">base::table</a> |
| deparse.level | see <a href="#">base::table</a> |

### Value

a table object

### See Also

[base::table](#)



---

|              |  |
|--------------|--|
| temp.options | <i>Set some global options temporarily</i> |
|--------------|--|

---

**Description**

Set some global options temporarily

**Usage**

```
temp.options(...)
```

```
temp.option(...)
```

**Arguments**

...            named options to set

**Value**

an S3 class "contextManager" object

**See Also**

[with-context-manager](#) [ContextManager](#)

---

|               |  |
|---------------|--|
| tojson-crunch | <i>toJSON methods for Crunch objects</i> |
|---------------|--|

---

**Description**

crunch uses the jsonlite package for JSON serialization and deserialization. Unfortunately, `jsonlite::toJSON()` does not allow for defining S4 methods for other object types. So, `crunch::toJSON` wraps `jsonprep`, which exists to translate objects to base R objects, which `jsonlite::toJSON` can handle. `jsonprep` is defined as an S4 generic, and it is exported, so you can define methods for it if you have other objects that you want to successfully serialize to JSON.

**Usage**

```
jsonprep(x, ...)
```

```
## S4 method for signature 'AbstractCategories'
```

```
jsonprep(x, ...)
```

```
## S4 method for signature 'ANY'
```

```
jsonprep(x, ...)
```

```
## S4 method for signature 'ShojiOrder'
jsonprep(x, ...)

## S4 method for signature 'OrderGroup'
jsonprep(x, ...)

toJSON(x, ...)
```

### Arguments

|     |                      |
|-----|----------------------|
| x   | the object           |
| ... | additional arguments |

### Value

jsonprep returns a base R object that jsonlite::toJSON can handle. toJSON returns the JSON-serialized character object.

### See Also

[jsonlite::toJSON\(\)](#)

---

toVariable

*Generic method for converting objects to Crunch representations*

---

### Description

R objects are converted to Crunch objects using the following rules:

### Usage

```
toVariable(x, ...)

## S4 method for signature 'character'
toVariable(x, ...)

## S4 method for signature 'numeric'
toVariable(x, ...)

## S4 method for signature 'factor'
toVariable(x, ...)

## S4 method for signature 'Date'
toVariable(x, ...)

## S4 method for signature 'POSIXt'
toVariable(x, ...)
```

```
## S4 method for signature 'AsIs'  
toVariable(x, ...)  
  
## S4 method for signature 'VariableDefinition'  
toVariable(x, ...)  
  
## S4 method for signature 'logical'  
toVariable(x, ...)  
  
## S4 method for signature 'labelled'  
toVariable(x, ...)  
  
## S4 method for signature 'labelled_spss'  
toVariable(x, ...)  
  
## S4 method for signature 'CrunchExpr'  
toVariable(x, ...)
```

### Arguments

|     |   |
|-----|---|
| x   | An R vector you want to turn into a Crunch variable   |
| ... | Additional metadata fields for the variable, such as "name" and "description". See the <a href="#">API documentation</a> for a complete list of valid attributes. |

### Details

- Character vectors are converted into Crunch text variables
- Numeric vectors are converted into Crunch numeric variables
- Factors are converted to categorical variables
- Date and POSIXt vectors are converted into Crunch datetime variables
- Logical vectors are converted to Crunch categorical variables
- `VariableDefinition()`s are not converted, but the function can still append additional meta-data

If you have other object types you wish to convert to Crunch variables, you can declare methods for `toVariable`.

### Value

A `VariableDefinition` object. To add this to a dataset, either assign it into the dataset (like `ds$newvar <- toVariable(...)`) or call `addVariables()`. If you're adding a column of data to a dataset, it must be as long as the number of rows in the dataset, or it may be a single value to be recycled for all rows.

### See Also

[VariableDefinition\(\)](#) [addVariables\(\)](#)

**Examples**

```

var1 <- rnorm(10)
toVariable(var1)
toVariable(var1, name="Random", description="Generated in R")
## Not run:
ds$random <- toVariable(var1, name="Random")
# Or, this way:
ds <- addVariables(ds, toVariable(var1, name="Random"))

## End(Not run)

```

---

Transforms-class

*Transformations of variable and cube views*


---

**Description**

Transformations allow you to change how a variable or cube is displayed without changing the underlying data.

**Usage**

```

Transforms(..., data = NULL)

## S4 method for signature 'CrunchCube'
transforms(x)

## S4 method for signature 'VariableCatalog'
transforms(x)

## S4 replacement method for signature 'CrunchCube,list'
transforms(x) <- value

## S4 replacement method for signature 'CrunchCube,`NULL`'
transforms(x) <- value

## S4 method for signature 'CrunchVariable'
transforms(x)

## S4 method for signature 'VariableTuple'
transforms(x)

## S4 replacement method for signature 'CrunchVariable,Transforms'
transforms(x) <- value

## S4 replacement method for signature 'CrunchVariable,`NULL`'
transforms(x) <- value

```

**Arguments**

|                    |   |
|--------------------|---|
| ...                | For the constructor function <code>Transforms</code> you can pass in attributes via ...   |
| <code>data</code>  | For the constructor function <code>Transforms</code> you can either pass in attributes via ... or you can create the objects with a fully defined <code>list</code> representation of the objects via the <code>data</code> argument. See the examples. |
| <code>x</code>     | For the attribute getters and setters, an object of class <code>Transforms</code>   |
| <code>value</code> | For <code>[&lt;-</code> , the replacement <code>Transforms</code> to insert   |

**Getting transformations**

The `transforms(x)` methods can be used with `Variables` and `CrunchCubes` to get what transformations are currently set. For variables, they return a single `Transforms` object that includes all transformations for the variable. For `CrunchCubes`, it returns a named list with the same length as the number of dimensions of the cube with each dimension's transformations.

Currently, [Insertions](#) (e.g. [Subtotal\(\)](#) and [Heading\(\)](#)) are the only type of transformations that are supported.

**Setting transformations on a variable**

The `transforms(x) <- value` methods can be used to assign transformations for a specific variable. `value` must be a `Transforms` object. This allows you to set transformations on categorical variables. These transformations will automatically show up in any new `CrunchCubes` that contain this variable.

**Setting transformations on a CrunchCube**

The `transforms(x) <- value` methods can also be used to assign transformations to a `CrunchCube` that has already been calculated. `value` must be a named list of `Transforms` objects. The names of this list must correspond to dimensions in the cube (those dimensions correspondences are matched based on variable aliases). You don't have to provide an entry for each dimension, but any dimension you do provide will be overwritten fully.

**Removing transformations**

To remove transformations from a variable or `CrunchCube`, use `transforms(x) <- NULL`.

---

|      |                                     |
|------|-------------------------------------|
| type | <i>Change Crunch variable types</i> |
|------|-------------------------------------|

---

**Description**

Numeric, text, and categorical variables can be cast to one another by assigning them a new "type". This modifies the storage of the data on the server and should only be done in narrow circumstances, as in when importing data from a different file format has resulted in incorrect types being specified.

**Usage**

```
## S4 method for signature 'CrunchVariable'
type(x)

## S4 method for signature 'VariableEntity'
type(x)

## S4 replacement method for signature 'CrunchVariable'
type(x) <- value
```

**Arguments**

|       |  |
|-------|--|
| x     | a Variable   |
| value | For the setter, a character value in c("numeric", "text", "categorical") |

**Value**

Getter returns character; setter returns x duly modified.

---

|        |   |
|--------|---|
| unbind | <i>Split an array or multiple-response variable into its CategoricalVariables</i> |
|--------|---|

---

**Description**

Split an array or multiple-response variable into its CategoricalVariables

**Usage**

```
unbind(x)
```

**Arguments**

|   |  |
|---|--|
| x | a CategoricalArrayVariable or MultipleResponseVariable |
|---|--|

**Value**

invisibly, the API response from DELETEing the array variable definition. If you [refresh\(\)](#) the corresponding dataset after unbinding, you should see the array variable removed and its subvariables promoted to regular variables.

---

|         |  |
|---------|--|
| unshare | <i>Revoke a user's access to a dataset</i> |
|---------|--|

---

**Description**

Revoke a user's access to a dataset

**Usage**

```
unshare(dataset, users)
```

**Arguments**

|         |   |
|---------|---|
| dataset | a CrunchDataset   |
| users   | character: email address(es) or URLs of the users or teams to unshare with. |

**Value**

Invisibly, the dataset.

**See Also**

[share](#)

---

|                |  |
|----------------|--|
| var-categories | <i>Get and set Categories on Variables</i> |
|----------------|--|

---

**Description**

Get and set Categories on Variables

**Usage**

```
## S4 method for signature 'VariableTuple'
categories(x)

## S4 method for signature 'CrunchVariable'
categories(x)

## S4 method for signature 'CategoricalVariable'
categories(x)

## S4 method for signature 'CategoricalArrayVariable'
categories(x)

## S4 method for signature 'VariableEntity'
```

```

categories(x)

## S4 replacement method for signature 'CategoricalVariable,Categories'
categories(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,Categories'
categories(x) <- value

## S4 replacement method for signature 'CategoricalVariable,numeric'
categories(x) <- value

## S4 replacement method for signature 'CategoricalVariable,character'
categories(x) <- value

## S4 replacement method for signature 'CategoricalVariable,ANY'
categories(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,numeric'
categories(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,character'
categories(x) <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY'
categories(x) <- value

## S4 replacement method for signature 'CrunchVariable,ANY'
categories(x) <- value

```

### Arguments

|       |  |
|-------|--|
| x     | a Variable   |
| value | for the setters, an object of class Categories to set. |

### Value

Getters return Categories; setters return x duly modified.

---

variable-as-methods    *as.\* methods for variables*

---

### Description

Use the *as.\** family of functions to make a derived copy of a variable that has been converted into a new type.



**Usage**

```
## S4 method for signature 'CrunchVariable'
as.Numeric(x)

## S4 method for signature 'CrunchVariable'
as.Text(x, format)

## S4 method for signature 'CrunchVariable'
as.Categorical(x, format)

## S4 method for signature 'CrunchVariable'
as.Datetime(x, format = "%Y-%m-%d %H:%M:%S",
            resolution, offset)

## S3 method for class 'CrunchVariable'
as.double(x, ...)

## S3 method for class 'CrunchVariable'
as.character(x, ...)
```

**Arguments**

|            |  |
|------------|--|
| x          | a Crunch variable to derive and convert to a new type  |
| format     | for <code>as.Datetime</code> , when the variable in <code>x</code> is a text or categorical variable, <code>format</code> is the typographical format that the datetime is already formatted in that needs to be parse from (default: "%Y-%m-%d %H:%M:%S"); for <code>as.Text</code> and <code>as.Categorical</code> , is the typographical format that the datetime is to be formatted as (e.g. "%Y-%m-%d %H:%M:%S" for "2018-01-08 12:39:57", the default if no rollup resolution is specified on the source variable. If a rollup resolution is specified, a reasonable default will be used.). |
| resolution | for <code>as.Datetime</code> , when the variable in <code>x</code> is a numeric variable, the resolution of the number (e.g. "ms" for milliseconds, "s" for seconds, etc. see <a href="#">expressions</a> for more information about valid values.)  |
| offset     | for <code>as.Datetime</code> , when the variable in <code>x</code> is a numeric the, a character of the offset to count from in the shape "2018-01-08 12:39:57". If not supplied, Crunch's default of 1970-01-01 00:00:00 will be used.  |
| ...        | additional arguments for <code>as.character</code> and <code>as.numeric</code> , ignored when used with Crunch variables   |

**Details**

Each type of Crunch variable (text, numeric, categorical, etc.) has an `as.*` function (`as.Text`, `as.Numeric`, and `as.Categorical` respectively) that takes the input given as `x`, and makes a new derived variable that is now of the type specified. See below for detailed examples.

For `as.Text` and `as.Numeric`, aliases to the R-native functions `as.character` and `as.numeric` are provided for convenience.

**Value**

a VariableDefinition to be used as the derivation

**Examples**

```
## Not run:
# ds$v1 is of type Text
is.Text(ds$v1)
# [1] TRUE

# that has strings of numbers
as.vector(ds$v1)
# [1] "32" "8" "4096" "1024"

# convert this to a numeric variable with the alias `v1_numeric`
ds$v1_numeric <- as.Numeric(ds$v1)

# the values are the same, but are now numerics and the type is Numeric
as.vector(ds$v1_numeric)
# [1] 32 8 4096 1024
is.Numeric(ds$v1_numeric)
# [1] TRUE

# this new variable is derived, so if new data is appended or streamed, the
# new rows of data will be updated.
is.derived(ds$v1_numeric)
# [1] TRUE

## End(Not run)
```

---

variable-update

*Update variables with expressions or values*


---

**Description**

Update variables with expressions or values

**Usage**

```
## S4 replacement method for signature 'CrunchVariable,ANY,missing,ANY'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,`NULL`'
x[i, j] <- value

## S4 replacement method for signature 'TextVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'NumericVariable,ANY,missing,numeric'
```

```

x[i, j] <- value

## S4 replacement method for signature 'DatetimeVariable,ANY,missing,Date'
x[i, j] <- value

## S4 replacement method for signature 'DatetimeVariable,ANY,missing,POSIXt'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchExpr'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchVariable'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,CrunchLogicalExpr'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,numeric'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalVariable,ANY,missing,factor'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,numeric'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,character'
x[i, j] <- value

## S4 replacement method for signature 'CategoricalArrayVariable,ANY,missing,factor'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY,missing,logical'
x[i, j] <- value

## S4 replacement method for signature 'CrunchVariable,ANY'
is.na(x) <- value

```

### Arguments

|       |  |
|-------|--|
| x     | a Variable                                       |
| i     | a CrunchLogicalExpr or R index, optionally       |
| j     | Invalid  |
| value | an R vector or a CrunchExpr with which to update |

**Value**

x duly modified

---

VariableCatalog-class *Collection of Variables within a Dataset*

---

**Description**

A VariableCatalog contains references to all variables in a dataset, plus some descriptive metadata about each. Each VariableCatalog also contains a [VariableOrder](#) that governs how variables within it are organized.

---

VariableDefinition *Construct a variable definition*

---

**Description**

Crunch variables are created by posting a VariableDefinition to the Crunch server. The VariableDefinition contains the information the server requires to calculate the variable. This can information can either be in the form of the actual data which you would like to include in the variable, or a derivation which tells the server how to derive the new variable from existing ones. This function converts an R vector or set of attributes into a variable definition which can be posted to the server.

**Usage**

```
VariableDefinition(data, ...)
```

```
VarDef(data, ...)
```

**Arguments**

|      |  |
|------|--|
| data | an R vector of data to convert to the Crunch payload format. See <a href="#">toVariable</a> for how R data types are converted. This function can also be used to construct a VariableDefinition directly by passing attributes to ... This is only recommended for advanced users who are familiar with the Crunch API. |
| ...  | additional attributes to be included in the VariableDefinition   |

**Value**

a VariableDefinition object, ready to POST to Crunch.

**See Also**

[toVariable](#)

**Examples**

```
VariableDefinition(rnorm(5), name="Some numbers",
  description="Generated pseudorandomly from the normal distribution")
VarDef(name="Integers", values=1:5, type="numeric",
  description="When creating variable definitions with 'values', you must
  specify 'type', and categorical variables will require 'categories'.")
```

---

|                  |  |
|------------------|--|
| variableMetadata | <i>Get all variable metadata for a dataset</i> |
|------------------|--|

---

**Description**

Crunch stores variable information in several catalogs containing information about the variable class, its missingness and subvariables. This function allows you to access that information.

**Usage**

```
variableMetadata(dataset)
```

**Arguments**

|         |               |
|---------|---------------|
| dataset | CrunchDataset |
|---------|---------------|

**Value**

A VariableCatalog with all variable properties, including categories and subvariables.

---

|                     |  |
|---------------------|--|
| VariableOrder-class | <i>Organize Variables within a Dataset</i> |
|---------------------|--|

---

**Description**

Variables in the Crunch web application can be viewed in an ordered, hierarchical list. These objects and methods allow you to modify that order from R.

**Details**

A VariableOrder object is a subclass of list that contains VariableGroups. VariableGroup objects contain a group name and an set of "entities", which can be variable references or other nested VariableGroups.

**Slots**

`group` character, the name of the VariableGroup. In the constructor and more generally, this field can be referenced as "name" as well.

`entities` a character vector of variable URLs, or a list containing a combination of variable URLs and VariableGroup objects.

`duplicates` logical: should duplicate variable references be allowed in this object? Default is FALSE.

`vars` either NULL or a [VariableCatalog](#). If not NULL, it will be used to look up variable names from the URLs.

---

versions

*Access the saved versions of a dataset*

---

**Description**

This function allows you to see a dataset's savepoints. These can then be passed to [restoreVersion\(\)](#) to load the previously saved version of a dataset.

**Usage**

```
versions(x)
```

**Arguments**

`x` a `CrunchDataset`

**Value**

an object of class `VersionCatalog`. Supported methods on the catalog include "names" and "timestamps".

**See Also**

[saveVersion](#) [restoreVersion](#)

---

webApp

*View a Crunch Object in the Web Application*


---

**Description**

Convenience function that will use your system's "open" command to open a Crunch object in our web application in your default browser.

**Usage**

```
webApp(x)
```

**Arguments**

x                    a Crunch Dataset or Variable

**Value**

Nothing; called for side effect of opening your web browser.

---

weight

*Dataset weights*


---

**Description**

weight lets you view and set your user's currently applied weight on the server. weightVariables lets you view all of the variables that have been designated as valid to use as weights.

**Usage**

```
weight(x)
```

```
weight(x) <- value
```

```
is.weight(x)
```

```
## S4 replacement method for signature 'NumericVariable'
```

```
is.weight(x) <- value
```

**Arguments**

x                    a Dataset

value                a Variable, VariableDefinition, or NULL. If a VariableDefinition is passed, the variable will first be created and then set as the datasets weight. Set to NULL to remove existing weights from the dataset.

**Value**

For the weight getter, a Variable if there is a weight, else NULL. For the setter, x, modified accordingly. weightVariables returns the aliases (or names, according to options(crunch.namekey.dataset)), of the variables designated as weights.

**See Also**

[weightVariables\(\)](#) [makeWeight\(\)](#)

---

|                 |  |
|-----------------|--|
| weightVariables | <i>Get a dataset's weightVariables</i> |
|-----------------|--|

---

**Description**

Get a dataset's weightVariables

**Usage**

```
## S4 method for signature 'CrunchDataset'
weightVariables(x)

## S4 method for signature 'VariableCatalog'
weightVariables(x)
```

**Arguments**

x                    a CrunchDataset

**Value**

weightVariables returns a character vector of the aliases of the variables that are eligible to be used as weights.

**See Also**

[weight\(\)](#) [makeWeight\(\)](#) [modifyWeightVariables\(\)](#)



---

|       |   |
|-------|---|
| which | <i>"which" method for CrunchLogicalExpr</i> |
|-------|---|

---

**Description**

"which" method for CrunchLogicalExpr

**Usage**

```
## S4 method for signature 'CrunchLogicalExpr'
which(x, arr.ind = FALSE, useNames = TRUE)
```

**Arguments**

|          |                   |
|----------|-------------------|
| x        | CrunchLogicalExpr |
| arr.ind  | Ignored           |
| useNames | Ignored           |

**Value**

Integer row indices where x is true. Note that this does not return a Crunch expression. Use this when you need to translate to R values. For filtering a Crunch expression by x, don't use which.

---

|                      |  |
|----------------------|--|
| with-context-manager | <i>Context manager's "with" method</i> |
|----------------------|--|

---

**Description**

Context manager's "with" method

**Usage**

```
## S3 method for class 'contextManager'
with(data, expr, ...)
```

**Arguments**

|      |   |
|------|---|
| data | <a href="#">contextManager</a>  |
| expr | code to evaluate within that context  |
| ...  | additional arguments. One additional supported argument is "as", which lets you assign the return of your "enter" function to an object you can access. |

**Value**

Nothing.

**See Also**[ContextManager](#)


---

|              |                                       |
|--------------|---------------------------------------|
| write.csv.gz | <i>Write CSV to a compressed file</i> |
|--------------|---------------------------------------|

---

**Description**

Write CSV to a compressed file

**Usage**

```
write.csv.gz(x, file, na = "", row.names = FALSE, ...)
```

**Arguments**

|           |   |
|-----------|---|
| x         | A data.frame or similar CSV-writable object   |
| file      | character destination to write the gzipped CSV to   |
| na        | See <a href="#">utils::write.csv</a> . This just changes the default to a Crunch-friendly empty string. |
| row.names | logical: write out row names? See <a href="#">utils::write.csv</a> .                                    |
| ...       | Additional arguments passed to <code>write.csv</code> .   |

**Value**

A csv file written to dist

---

|   |                            |
|---|----------------------------|
| [,CrunchExpr,CrunchLogicalExpr,ANY-method | <i>"Subset" a Variable</i> |
|---|----------------------------|

---

**Description**

These methods subset variables by creating Expressions, which can be composed and evaluated as needed.

**Usage**

```
## S4 method for signature 'CrunchExpr,CrunchLogicalExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchExpr,logical,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchExpr,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchVariable,CrunchExpr,ANY'
x[i, j, ..., drop = FALSE]

## S4 method for signature 'CrunchVariable,numeric,ANY'
x[i, j, ..., drop = TRUE]

## S4 method for signature 'CrunchVariable,logical,ANY'
x[i, j, ..., drop = TRUE]
```

**Arguments**

|      |                                   |
|------|-----------------------------------|
| x    | a Variable                        |
| i    | a CrunchExpr, logical, or numeric |
| j    | Invalid                           |
| ...  | additional arguments, ignored     |
| drop | Invalid                           |

**Value**

a CrunchExpr containing references to the variable x and the filter logic contained in i

---

```
$,AbstractCategory-method
```

*Access Category fields directly*

---

**Description**

Don't do this. Instead, use the category setters.

**Usage**

```
## S4 method for signature 'AbstractCategory'
x$name

## S4 replacement method for signature 'AbstractCategory'
x$name <- value
```

**Arguments**

|       |                                  |
|-------|----------------------------------|
| x     | a Category                       |
| name  | a field within x                 |
| value | a value for that field to update |

**Value**

\$ returns the value of the desired field. Setter returns x duly modified.

**See Also**

[describe-category](#)

# Index

- !,CrunchExpr-method (expressions), 66
- !=,CategoricalVariable,character-method (expressions), 66
- !=,CategoricalVariable,factor-method (expressions), 66
- !=,CategoricalVariable,numeric-method (expressions), 66
- .Insertion (Insertions-class), 77
- ==,CategoricalVariable,character-method (expressions), 66
- ==,CategoricalVariable,factor-method (expressions), 66
- ==,CategoricalVariable,numeric-method (expressions), 66
- [,AbstractCategories,ANY,ANY-method (Categories-class), 20
- [,AbstractCategories,character,ANY-method (Categories-class), 20
- [,AbstractCategories,numeric,ANY-method (Categories-class), 20
- [,CategoricalArrayVariable,character,ANY-method (subvars-extract), 139
- [,CategoricalArrayVariable,missing,ANY-method (subvars-extract), 139
- [,CategoricalArrayVariable,missing,character-method (subvars-extract), 139
- [,CrunchCube,ANY,ANY-method (cube-methods), 41
- [,CrunchDataset,ANY,ANY-method (dataset-extract), 45
- [,CrunchDataset,CrunchLogicalExpr,ANY-method (dataset-extract), 45
- [,CrunchDataset,CrunchLogicalExpr,missing-method (dataset-extract), 45
- [,CrunchDataset,VariableGroup,ANY-method (dataset-extract), 45
- [,CrunchDataset,VariableOrder,ANY-method (dataset-extract), 45
- [,CrunchDataset,character,ANY-method (dataset-extract), 45
- [,CrunchDataset,logical,missing-method (dataset-extract), 45
- [,CrunchDataset,missing,ANY-method (dataset-extract), 45
- [,CrunchExpr,CrunchLogicalExpr,ANY-method, 162
- [,CrunchExpr,logical,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), 162
- [,CrunchExpr,numeric,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), 162
- [,CrunchVariable,CrunchExpr,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), 162
- [,CrunchVariable,logical,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), 162
- [,CrunchVariable,numeric,ANY-method ([,CrunchExpr,CrunchLogicalExpr,ANY-method), 162
- [,CubeDims,ANY,ANY-method (cube-methods), 41
- [,OrderGroup,ANY,ANY-method (ShojiOrder-extract), 127
- [,OrderGroup,character,ANY-method (ShojiOrder-extract), 127
- [,ShojiCatalog,ANY,ANY-method (catalog-extract), 16
- [,ShojiCatalog,character,ANY-method (catalog-extract), 16
- [,ShojiCatalog,logical,ANY-method (catalog-extract), 16
- [,ShojiCatalog,numeric,ANY-method (catalog-extract), 16
- [,ShojiOrder,ANY,ANY-method (ShojiOrder-extract), 127
- [,ShojiOrder,character,ANY-method

- (ShojiOrder-extract), 127
- [,Subvariables,character,ANY-method  
(subvars-extract), 139
- [,UserCatalog,character,ANY-method  
(catalog-extract), 16
- [,VariableCatalog,VariableGroup,ANY-method  
(catalog-extract), 16
- [,VariableCatalog,VariableOrder,ANY-method  
(catalog-extract), 16
- [.CrunchDataFrame (CrunchDataFrame), 37
- [<-,AbstractCategories,character,ANY,ANY-method  
(Categories-class), 20
- [<-,CategoricalArrayVariable,ANY,missing,character-method  
(variable-update), 154
- [<-,CategoricalArrayVariable,ANY,missing,factor-method  
(variable-update), 154
- [<-,CategoricalArrayVariable,ANY,missing,numeric-method  
(variable-update), 154
- [<-,CategoricalVariable,ANY,missing,character-method  
(variable-update), 154
- [<-,CategoricalVariable,ANY,missing,factor-method  
(variable-update), 154
- [<-,CategoricalVariable,ANY,missing,numeric-method  
(variable-update), 154
- [<-,Categories,ANY,ANY,ANY-method  
(Categories-class), 20
- [<-,CrunchDataset,ANY,missing,list-method  
(dataset-update), 48
- [<-,CrunchDataset,CrunchExpr,ANY,ANY-method  
(dataset-update), 48
- [<-,CrunchVariable,ANY,missing,ANY-method  
(variable-update), 154
- [<-,CrunchVariable,ANY,missing,CrunchExpr-method  
(variable-update), 154
- [<-,CrunchVariable,ANY,missing,CrunchLogicalExpr-method  
(variable-update), 154
- [<-,CrunchVariable,ANY,missing,CrunchVariableExpr-method  
(variable-update), 154
- [<-,CrunchVariable,ANY,missing,NULL-method  
(variable-update), 154
- [<-,CrunchVariable,ANY,missing,logical-method  
(variable-update), 154
- [<-,DatetimeVariable,ANY,missing,Date-method  
(variable-update), 154
- [<-,DatetimeVariable,ANY,missing,POSIXt-method  
(variable-update), 154
- [<-,NumericVariable,ANY,missing,numeric-method  
(variable-update), 154
- [<-,ShojiCatalog,ANY,missing,ShojiCatalog-method  
(catalog-extract), 16
- [<-,ShojiOrder,ANY,missing,ShojiOrder-method  
(ShojiOrder-extract), 127
- [<-,ShojiOrder,character,missing,ShojiOrder-method  
(ShojiOrder-extract), 127
- [<-,Subvariables,ANY,missing,ANY-method  
(subvars-extract), 139
- [<-,Subvariables,ANY,missing,Subvariables-method  
(subvars-extract), 139
- [<-,Subvariables,character,missing,Subvariables-method  
(subvars-extract), 139
- [<-,TextVariable,ANY,missing,character-method  
(variable-update), 154
- [<-,VariableCatalog,VariableGroup,missing,VariableCatalog-  
method (catalog-extract), 16
- [<-,VariableCatalog,VariableOrder,missing,VariableCatalog-  
method (catalog-extract), 16
- [<-,CrunchDataFrame (CrunchDataFrame),  
method 37
- [<-,AbstractCategories,character-method  
(Categories-class), 20
- [<-,CategoricalArrayVariable,ANY-method  
(subvars-extract), 139
- [,CategoricalArrayVariable,character-method  
(subvars-extract), 139
- [,CategoricalArrayVariable,ANY-method  
(dataset-extract), 45
- [,CategoricalArrayVariable,character-method  
(dataset-extract), 45
- [,DatasetCatalog,numeric-method  
(catalog-extract), 16
- [,FilterCatalog,numeric-method  
(catalog-extract), 16
- [,MethodCatalog,character-method  
(catalog-extract), 16
- [,MultitableCatalog,numeric-method  
(catalog-extract), 16
- [,MultitableResult,ANY-method  
(tabbook-methods), 143
- [,OrderGroup,ANY-method  
(ShojiOrder-extract), 127
- [,OrderGroup,character-method  
(ShojiOrder-extract), 127
- [,PermissionCatalog,character-method  
(catalog-extract), 16
- [,ProjectCatalog,numeric-method  
(catalog-extract), 16

- [[, Session, ANY-method  
(session-extract), 123
- [[, ShojiCatalog, ANY-method  
(catalog-extract), 16
- [[, ShojiCatalog, character-method  
(catalog-extract), 16
- [[, ShojiFolder, character-method  
(catalog-extract), 16
- [[, ShojiFolder, numeric-method  
(catalog-extract), 16
- [[, ShojiOrder, ANY-method  
(ShojiOrder-extract), 127
- [[, ShojiOrder, character-method  
(ShojiOrder-extract), 127
- [[, Subvariables, character-method  
(subvars-extract), 139
- [[, Subvariables, numeric-method  
(subvars-extract), 139
- [[, TabBookResult, character-method  
(tabbook-methods), 143
- [[, TabBookResult, numeric-method  
(tabbook-methods), 143
- [[, TeamCatalog, numeric-method  
(catalog-extract), 16
- [[, UserCatalog, character-method  
(catalog-extract), 16
- [[, VariableCatalog, numeric-method  
(catalog-extract), 16
- [[. CrunchDataFrame (CrunchDataFrame), 37
- [[<-, AbstractCategories, character, ANY, ANY-method  
(Categories-class), 20
- [[<-, CategoricalArrayVariable, ANY, missing, ANY-method  
(subvars-extract), 139
- [[<-, CategoricalArrayVariable, character, missing, ANY-method  
(subvars-extract), 139
- [[<-, CrunchDataset, ANY, ANY, ANY-method  
(dataset-update), 48
- [[<-, CrunchDataset, ANY, missing, CrunchGeography-method  
(dataset-update), 48
- [[<-, CrunchDataset, ANY, missing, CrunchVariable-method  
(dataset-update), 48
- [[<-, CrunchDataset, ANY, missing, NULL-method  
(dataset-update), 48
- [[<-, CrunchDataset, character, missing, ANY-method  
(dataset-update), 48
- [[<-, CrunchDataset, character, missing, CrunchGeography-method  
(dataset-update), 48
- [[<-, CrunchDataset, character, missing, CrunchLogicalExpr-method  
(dataset-update), 48
- [[<-, CrunchDataset, character, missing, CrunchVariable-method  
(dataset-update), 48
- [[<-, CrunchDataset, character, missing, NULL-method  
(dataset-update), 48
- [[<-, DatasetCatalog, character, missing, DatasetTuple-method  
(catalog-extract), 16
- [[<-, FilterCatalog, character, missing, CrunchFilter-method  
(catalog-extract), 16
- [[<-, FilterCatalog, character, missing, CrunchLogicalExpr-method  
(catalog-extract), 16
- [[<-, FilterCatalog, numeric, missing, CrunchFilter-method  
(catalog-extract), 16
- [[<-, FilterCatalog, numeric, missing, CrunchLogicalExpr-method  
(catalog-extract), 16
- [[<-, MemberCatalog, ANY, missing, ANY-method  
(catalog-extract), 16
- [[<-, MemberCatalog, character, missing, NULL-method  
(catalog-extract), 16
- [[<-, MultitableCatalog, ANY, missing, NULL-method  
(catalog-extract), 16
- [[<-, MultitableCatalog, character, missing, formula-method  
(catalog-extract), 16
- [[<-, MultitableCatalog, numeric, missing, formula-method  
(catalog-extract), 16
- [[<-, OrderGroup, ANY, missing, OrderGroup-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, character, missing, NULL-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, character, missing, OrderGroup-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, character, missing, ShojiOrder-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, character, missing, character-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, character, missing, list-method  
(ShojiOrder-extract), 127
- [[<-, OrderGroup, numeric, missing, NULL-method  
(ShojiOrder-extract), 127
- [[<-, ProjectCatalog, character, missing, CrunchProject-method  
(catalog-extract), 16
- [[<-, ProjectCatalog, character, missing, list-method  
(catalog-extract), 16
- [[<-, Session, ANY, ANY, ANY-method  
(session-extract), 123
- [[<-, ShojiOrder, ANY, missing, ANY-method  
(ShojiOrder-extract), 127
- [[<-, ShojiOrder, ANY, missing, NULL-method  
(ShojiOrder-extract), 127





- aliases, MultitableResult-method  
(tabbook-methods), 143
- aliases, TabBookResult-method  
(tabbook-methods), 143
- aliases, VariableCatalog-method  
(names, BatchCatalog-method),  
104
- aliases, VariableFolder-method  
(names, BatchCatalog-method),  
104
- aliases<- (names, BatchCatalog-method),  
104
- aliases<-, VariableCatalog-method  
(names, BatchCatalog-method),  
104
- allVariables (dataset-variables), 50
- allVariables, CrunchDataset-method  
(dataset-variables), 50
- allVariables<- (dataset-variables), 50
- allVariables<-, CrunchDataset, VariableCatalog-method  
(dataset-variables), 50
- anchor (Insertions-class), 77
- anchor, Heading-method  
(Insertions-class), 77
- anchor, Insertion-method  
(Insertions-class), 77
- anchor, Subtotal-method  
(Insertions-class), 77
- anchor, SummaryStat-method  
(Insertions-class), 77
- anchor<- (Insertions-class), 77
- anchor<-, Heading-method  
(Insertions-class), 77
- anchor<-, Insertion-method  
(Insertions-class), 77
- anchor<-, Subtotal-method  
(Insertions-class), 77
- anchor<-, SummaryStat-method  
(Insertions-class), 77
- anchors (Insertions-class), 77
- anchors, Insertions-method  
(Insertions-class), 77
- appendDataset, 11
- appendDataset(), 120
- appendStream, 11
- appendStream(), 111
- applyTransforms  
(subtotalArray, CrunchCube-method),  
137
- archive  
(is.archived, DatasetCatalog-method),  
83
- archive-and-publish  
(is.archived, DatasetCatalog-method),  
83
- are.Headings (Subtotal-class), 134
- are.Subtotals (Subtotal-class), 134
- are.SummaryStats (SummaryStat-class),  
141
- arguments (Insertions-class), 77
- arguments, Heading-method  
(Insertions-class), 77
- arguments, Insertion-method  
(Insertions-class), 77
- arguments, Subtotal-method  
(Insertions-class), 77
- arguments, SummaryStat-method  
(Insertions-class), 77
- arguments<- (Insertions-class), 77
- arguments<-, Heading-method  
(Insertions-class), 77
- arguments<-, Insertion-method  
(Insertions-class), 77
- arguments<-, Subtotal-method  
(Insertions-class), 77
- arguments<-, SummaryStat-method  
(Insertions-class), 77
- as.Categorical (variable-as-methods),  
152
- as.Categorical, CrunchVariable-method  
(variable-as-methods), 152
- as.character.CrunchVariable  
(variable-as-methods), 152
- as.data.frame, 13
- as.data.frame.BatchCatalog  
(catalog-dataframes), 15
- as.data.frame.CrunchDataFrame  
(dataset-to-R), 47
- as.data.frame.CrunchDataset  
(dataset-to-R), 47
- as.data.frame.FilterCatalog  
(catalog-dataframes), 15
- as.data.frame.ShojiCatalog  
(catalog-dataframes), 15
- as.data.frame.VariableCatalog  
(catalog-dataframes), 15

- as.Datetime (variable-as-methods), 152
- as.Datetime, CrunchVariable-method (variable-as-methods), 152
- as.double.CrunchVariable (variable-as-methods), 152
- as.environment, CrunchDataset-method, 12
- as.Numeric (variable-as-methods), 152
- as.Numeric, CrunchVariable-method (variable-as-methods), 152
- as.Text (variable-as-methods), 152
- as.Text, CrunchVariable-method (variable-as-methods), 152
- as.vector(), 48
- as.vector, CrunchExpr-method, 12
- as.vector, CrunchVariable-method (as.vector, CrunchExpr-method), 12
- availableGeodata (CrunchGeography-class), 38
- availableGeodataFeatures, 13
- base::array, 43
- base::dim(), 62
- base::dir.create(), 101
- base::duplicated, 52
- base::duplicated(), 63
- base::file.remove(), 120
- base::levels(), 22
- base::margin.table(), 40, 41
- base::match(), 67
- base::max(), 35
- base::mean(), 35
- base::min(), 35
- base::names(), 105
- base::prop.table(), 40, 41
- base::round(), 40
- base::setwd(), 23
- base::table, 144
- base::table(), 32
- bases (cube-computing), 40
- bases, CrunchCube-method (cube-computing), 40
- bases, MultitableResult-method (cube-computing), 40
- bases, TabBookResult-method (cube-computing), 40
- batches, 14
- bin (expressions), 66
- c, 14
- c-categories, 14
- c.Categories (c-categories), 14
- c.Category (c-categories), 14
- catalog-dataframes, 15
- catalog-extract, 16
- catalog-length, 19
- CategoricalArrayVariable (CrunchVariable-class), 39
- CategoricalArrayVariable-class (CrunchVariable-class), 39
- CategoricalVariable (CrunchVariable-class), 39
- CategoricalVariable-class (CrunchVariable-class), 39
- Categories, 14, 60, 103, 105
- Categories (Categories-class), 20
- categories (var-categories), 151
- categories(), 79
- categories, CategoricalArrayVariable-method (var-categories), 151
- categories, CategoricalVariable-method (var-categories), 151
- categories, CrunchVariable-method (var-categories), 151
- categories, VariableEntity-method (var-categories), 151
- categories, VariableTuple-method (var-categories), 151
- Categories-class, 20
- categories<- (var-categories), 151
- categories<- , CategoricalArrayVariable, ANY-method (var-categories), 151
- categories<- , CategoricalArrayVariable, Categories-method (var-categories), 151
- categories<- , CategoricalArrayVariable, character-method (var-categories), 151
- categories<- , CategoricalArrayVariable, numeric-method (var-categories), 151
- categories<- , CategoricalVariable, ANY-method (var-categories), 151
- categories<- , CategoricalVariable, Categories-method (var-categories), 151
- categories<- , CategoricalVariable, character-method (var-categories), 151
- categories<- , CategoricalVariable, numeric-method (var-categories), 151
- categories<- , CrunchVariable, ANY-method

- (var-categories), 151
- categoriesFromLevels, 21
- Category (Categories-class), 20
- Category-class (Categories-class), 20
- category-extract
  - (\$, AbstractCategory-method), 163
- cd, 22
- cd(), 70, 101, 120
- changeCategoryID, 23
- cleanseBatches, 24
- collapseCategories, 24
- combine, 25
- combine(), 25
- compareDatasets, 26
- conditionalTransform, 27
- consent, 28
- ContextManager, 29, 29, 145, 162
- contextManager, 161
- contextManager (ContextManager), 29
- copy (copyVariable), 30
- copy(), 25
- copyOrder, 30
- copyVariable, 30
- crDELETE (http-methods), 75
- createDataset, 115
- createDataset(), 106
- createWithPreparedData, 31
- crGET (http-methods), 75
- crPATCH (http-methods), 75
- crPOST (http-methods), 75
- crPUT (http-methods), 75
- crtabs, 32
- crtabs(), 12
- crunch, 32
- crunch-cut, 33
- crunch-package (crunch), 32
- crunch-uni, 34
- crunchAPI, 75
- CrunchBox, 115
- CrunchBox (crunchBox), 35
- crunchBox, 35
- crunchBox(), 63, 64
- CrunchDataFrame, 37
- CrunchDataset, 110
- CrunchDataset (CrunchDataset-class), 38
- CrunchDataset-class, 38
- CrunchExpr, 56
- CrunchGeography, 6, 7
- CrunchGeography
  - (CrunchGeography-class), 38
- CrunchGeography-class, 38
- CrunchVariable-class, 39
- cube-computing, 40
- cube-methods, 41
- cube-missingness, 43
- cube-residuals, 43
- cut, NumericVariable-method
  - (crunch-cut), 33
- dashboard, 44
- dashboard<- (dashboard), 44
- data.frame, 37
- dataset-extract, 45
- dataset-owner, 46
- dataset-to-R, 47
- dataset-update, 48
- dataset-variables, 50
- DatasetGroup (DatasetOrder-class), 51
- DatasetGroup-class
  - (DatasetOrder-class), 51
- DatasetOrder (DatasetOrder-class), 51
- DatasetOrder-class, 51
- datasets, 51
- datasets<- (datasets), 51
- DatetimeVariable
  - (CrunchVariable-class), 39
- DatetimeVariable-class
  - (CrunchVariable-class), 39
- dedupeOrder, 52
- delete, 53, 54
- delete(), 54
- delete, ANY-method (delete), 53
- delete, CrunchDataset-method (delete), 53
- delete, CrunchProject-method (delete), 53
- delete, CrunchTeam-method (delete), 53
- delete, CrunchVariable-method (delete), 53
- delete, Multitable-method (delete), 53
- delete, ShojiFolder-method (delete), 53
- delete, ShojiObject-method (delete), 53
- delete, VariableTuple-method (delete), 53
- deleteDataset, 54, 54
- deleteSubvariable, 139
- deleteSubvariable (deleteSubvariables), 55
- deleteSubvariables, 55

- deleteVariable (deleteVariables), 55
- deleteVariables, 55
- derivation (derivations), 56
- derivation, CrunchVariable-method  
(derivations), 56
- derivation<- (derivations), 56
- derivation<-, CrunchVariable, ANY-method  
(derivations), 56
- derivation<-, CrunchVariable, NULL-method  
(derivations), 56
- derivations, 56
- deriveArray (makeArray), 91
- describe, 58
- describe-catalog  
(names, BatchCatalog-method),  
104
- describe-category  
(name, AbstractCategory-method),  
103
- description (describe), 58
- description, CrunchDataset-method  
(describe), 58
- description, CrunchVariable-method  
(describe), 58
- description, Geodata-method (describe),  
58
- description<- (describe), 58
- description<-, CrunchDataset-method  
(describe), 58
- description<-, CrunchVariable-method  
(describe), 58
- descriptions  
(names, BatchCatalog-method),  
104
- descriptions, CrunchCube-method  
(cube-methods), 41
- descriptions, MultitableResult-method  
(tabbook-methods), 143
- descriptions, TabBookResult-method  
(tabbook-methods), 143
- descriptions, VariableCatalog-method  
(names, BatchCatalog-method),  
104
- descriptions, VersionCatalog-method  
(names, BatchCatalog-method),  
104
- descriptions<-  
(names, BatchCatalog-method),  
104
- descriptions<- , VariableCatalog-method  
(names, BatchCatalog-method),  
104
- dichotomize, 60, 103
- dichotomize, CategoricalArrayVariable, ANY-method  
(dichotomize), 60
- dichotomize, CategoricalVariable, ANY-method  
(dichotomize), 60
- dichotomize, Categories, character-method  
(dichotomize), 60
- dichotomize, Categories, logical-method  
(dichotomize), 60
- dichotomize, Categories, numeric-method  
(dichotomize), 60
- digits (describe), 58
- digits, CrunchVariable-method  
(describe), 58
- digits<- (describe), 58
- digits<-, CrunchVariable-method  
(describe), 58
- digits<-, NumericVariable-method  
(describe), 58
- dim, CrunchCube-method (cube-methods), 41
- dim, CrunchDataset-method (dim-dataset),  
61
- dim, CubeDims-method (cube-methods), 41
- dim, TabBookResult-method  
(tabbook-methods), 143
- dim-dataset, 61
- dim. CrunchDataFrame (CrunchDataFrame),  
37
- dimensions (cube-methods), 41
- dimensions, CrunchCube-method  
(cube-methods), 41
- dimensions<- (cube-methods), 41
- dimensions<-, CrunchCube, CubeDims-method  
(cube-methods), 41
- dimnames, CrunchCube-method  
(cube-methods), 41
- dimnames, CubeDims-method  
(cube-methods), 41
- dropRows, 62
- duplicated, 63
- duplicated, CrunchExpr-method  
(duplicated), 63
- duplicated, CrunchVariable-method  
(duplicated), 63

- duplicates, [52](#)
- duplicates (ShojiOrder-slots), [130](#)
- duplicates, OrderGroup-method  
(ShojiOrder-slots), [130](#)
- duplicates, ShojiOrder-method  
(ShojiOrder-slots), [130](#)
- duplicates, VariableCatalog-method  
(ShojiOrder-slots), [130](#)
- duplicates<- (ShojiOrder-slots), [130](#)
- duplicates<-, OrderGroup, logical-method  
(ShojiOrder-slots), [130](#)
- duplicates<-, ShojiOrder, logical-method  
(ShojiOrder-slots), [130](#)
- duplicates<-, VariableCatalog, logical-method  
(ShojiOrder-slots), [130](#)
  
- emails (names, BatchCatalog-method), [104](#)
- emails, ShojiCatalog-method  
(names, BatchCatalog-method),  
[104](#)
- embedCrunchBox, [63](#)
- endDate (describe), [58](#)
- endDate, CrunchDataset-method  
(describe), [58](#)
- endDate<- (describe), [58](#)
- endDate<-, CrunchDataset-method  
(describe), [58](#)
- entities (ShojiOrder-slots), [130](#)
- entities, list-method  
(ShojiOrder-slots), [130](#)
- entities, OrderGroup-method  
(ShojiOrder-slots), [130](#)
- entities, ShojiOrder-method  
(ShojiOrder-slots), [130](#)
- entities<- (ShojiOrder-slots), [130](#)
- entities<-, OrderGroup-method  
(ShojiOrder-slots), [130](#)
- entities<-, ShojiOrder-method  
(ShojiOrder-slots), [130](#)
- exclusion, [62](#), [64](#)
- exclusion<- (exclusion), [64](#)
- exportDataset, [65](#)
- exportDataset(), [13](#)
- expressions, [66](#), [153](#)
- expropriateUser, [68](#)
- extendDataset (joinDatasets), [86](#)
  
- filter-catalog, [68](#)
- filters (filter-catalog), [68](#)
- filters(), [107](#)
- filters, CrunchDataset-method  
(filter-catalog), [68](#)
- filters<- (filter-catalog), [68](#)
- filters<-, CrunchDataset-method  
(filter-catalog), [68](#)
- flattenOrder, [69](#)
- flipArrays, [69](#)
- folder, [70](#)
- folder(), [101](#)
- folder<- (folder), [70](#)
- forkDataset, [71](#)
- fortify, [71](#)
- func (Insertions-class), [77](#)
- func, Heading-method (Insertions-class),  
[77](#)
- func, Insertion-method  
(Insertions-class), [77](#)
- func, Subtotal-method  
(Insertions-class), [77](#)
- func, SummaryStat-method  
(Insertions-class), [77](#)
- func<- (Insertions-class), [77](#)
- funcs (Insertions-class), [77](#)
- funcs, Insertions-method  
(Insertions-class), [77](#)
  
- geo (CrunchGeography-class), [38](#)
- geo(), [6](#)
- geo, CrunchVariable-method  
(CrunchGeography-class), [38](#)
- geo<- (CrunchGeography-class), [38](#)
- geo<-, CrunchVariable, CrunchGeography-method  
(CrunchGeography-class), [38](#)
- geo<-, CrunchVariable, NULL-method  
(CrunchGeography-class), [38](#)
- Geodata (CrunchGeography-class), [38](#)
- Geodata-class (CrunchGeography-class),  
[38](#)
- getTeams, [72](#), [97](#)
- getTeams(), [96](#)
- grouped, [72](#), [131](#)
  
- Heading (Subtotal-class), [134](#)
- Heading(), [79](#), [149](#)
- Heading-class (Subtotal-class), [134](#)
- headings, [79](#)
- hiddenVariables, [73](#)
- hiddenVariables<- (hideVariables), [74](#)

- hide, [54](#), [56](#), [73](#), [74](#)
- hide(), [55](#)
- hide, CrunchVariable-method (hide), [73](#)
- hide, VariableCatalog-method (hide), [73](#)
- hideMissing (cube-missingness), [43](#)
- hideMissing, CrunchCube-method (cube-missingness), [43](#)
- hideVariables, [74](#), [74](#)
- http-methods, [75](#)
  
- icon (project-icon), [116](#)
- icon<- (project-icon), [116](#)
- id (name, AbstractCategory-method), [103](#)
- id, AbstractCategory-method (name, AbstractCategory-method), [103](#)
- id, CrunchDataset-method (describe), [58](#)
- id, CrunchVariable-method (describe), [58](#)
- id, AbstractCategory (Categories-class), [20](#)
- ids (Categories-class), [20](#)
- ids, AbstractCategories-method (Categories-class), [20](#)
- ids, VariableCatalog-method (names, BatchCatalog-method), [104](#)
- ids, AbstractCategories (Categories-class), [20](#)
- ids<- (Categories-class), [20](#)
- ids<-, Categories-method (Categories-class), [20](#)
- importMultitable, [75](#)
- index (shoji-index), [126](#)
- index, ShojiCatalog-method (shoji-index), [126](#)
- index.table, [76](#)
- index<- (shoji-index), [126](#)
- index<-, ShojiCatalog-method (shoji-index), [126](#)
- Insertion (Insertions-class), [77](#)
- Insertion-class (Insertions-class), [77](#)
- Insertions, [149](#)
- Insertions (Insertions-class), [77](#)
- Insertions-class, [77](#)
- interactVariables, [79](#)
- is-na-categories, [80](#)
- is-public, [81](#)
- is-selected-categories, [82](#)
  
- is.archived (is.archived, DatasetCatalog-method), [83](#)
- is.archived, CrunchDataset-method (is.archived, DatasetCatalog-method), [83](#)
- is.archived, DatasetCatalog-method, [83](#)
- is.archived<- (is.archived, DatasetCatalog-method), [83](#)
- is.archived<-, CrunchDataset, logical-method (is.archived, DatasetCatalog-method), [83](#)
- is.archived<-, DatasetCatalog, logical-method (is.archived, DatasetCatalog-method), [83](#)
- is.Array (is.dataset), [84](#)
- is.CA (is.dataset), [84](#)
- is.Categorical (is.dataset), [84](#)
- is.CategoricalArray (is.dataset), [84](#)
- is.CrunchExpr (is.dataset), [84](#)
- is.dataset, [84](#)
- is.Datetime (is.dataset), [84](#)
- is.derived (derivations), [56](#)
- is.derived, CrunchVariable-method (derivations), [56](#)
- is.derived<- (derivations), [56](#)
- is.derived<-, CrunchVariable, logical-method (derivations), [56](#)
- is.dichotomized (dichotomize), [60](#)
- is.dichotomized, Categories-method (dichotomize), [60](#)
- is.draft (is.archived, DatasetCatalog-method), [83](#)
- is.draft, CrunchDataset-method (is.archived, DatasetCatalog-method), [83](#)
- is.draft, DatasetCatalog-method (is.archived, DatasetCatalog-method), [83](#)
- is.draft<- (is.archived, DatasetCatalog-method), [83](#)
- is.draft<-, CrunchDataset, logical-method (is.archived, DatasetCatalog-method), [83](#)
- is.draft<-, DatasetCatalog, logical-method

- (is.archived, DatasetCatalog-method), 83
- is.editor, 85
- is.editor, MemberCatalog-method (is.editor), 85
- is.editor, PermissionCatalog-method (is.editor), 85
- is.editor, PermissionTuple-method (is.editor), 85
- is.editor<- (is.editor), 85
- is.editor<-, MemberCatalog, logical-method (is.editor), 85
- is.Expr (is.dataset), 84
- is.Geodata (is.dataset), 84
- is.Heading (Subtotal-class), 134
- is.MR (is.dataset), 84
- is.Multiple (is.dataset), 84
- is.MultipleResponse (is.dataset), 84
- is.na, Categories-method (is-na-categories), 80
- is.na, Category-method (is-na-categories), 80
- is.na, CrunchVariable-method (expressions), 66
- is.na, CubeDims-method (cube-methods), 41
- is.na<-, Categories, character-method (is-na-categories), 80
- is.na<-, Categories, logical-method (is-na-categories), 80
- is.na<-, Category, logical-method (is-na-categories), 80
- is.na<-, CrunchVariable, ANY-method (variable-update), 154
- is.Numeric (is.dataset), 84
- is.public (is-public), 81
- is.public, CrunchFilter-method (is-public), 81
- is.public, Multitable-method (is-public), 81
- is.public, MultitableCatalog-method (is-public), 81
- is.public<- (is-public), 81
- is.public<-, CrunchFilter-method (is-public), 81
- is.public<-, Multitable-method (is-public), 81
- is.public<-, MultitableCatalog-method (is-public), 81
- is.published (is.archived, DatasetCatalog-method), 83
- is.published, CrunchDataset-method (is.archived, DatasetCatalog-method), 83
- is.published, DatasetCatalog-method (is.archived, DatasetCatalog-method), 83
- is.published<- (is.archived, DatasetCatalog-method), 83
- is.published<-, CrunchDataset, logical-method (is.archived, DatasetCatalog-method), 83
- is.published<-, DatasetCatalog, logical-method (is.archived, DatasetCatalog-method), 83
- is.selected (name, AbstractCategory-method), 103
- is.selected, Categories-method (is-selected-categories), 82
- is.selected, Category-method (name, AbstractCategory-method), 103
- is.selected<- (is-selected-categories), 82
- is.selected<-, Categories-method (is-selected-categories), 82
- is.selected<-, Category-method (is-selected-categories), 82
- is.shoji (is.dataset), 84
- is.Subtotal (Subtotal-class), 134
- is.SummaryStat (SummaryStat-class), 141
- is.Text (is.dataset), 84
- is.variable (is.dataset), 84
- is.weight (weight), 159
- is.weight<- (weight), 159
- is.weight<-, NumericVariable-method (weight), 159
- is.weightVariable (modifyWeightVariables), 98
- is.weightVariable<- (modifyWeightVariables), 98
- is.weightVariable<-, NumericVariable-method (modifyWeightVariables), 98
- joinDatasets, 86

- jsonlite::toJSON(), [145](#), [146](#)
- jsonprep (tojson-crunch), [145](#)
- jsonprep,AbstractCategories-method (tojson-crunch), [145](#)
- jsonprep,ANY-method (tojson-crunch), [145](#)
- jsonprep,OrderGroup-method (tojson-crunch), [145](#)
- jsonprep,ShojiOrder-method (tojson-crunch), [145](#)
  
- length,MultitableResult-method (tabbook-methods), [143](#)
- length,OrderGroup-method (ShojiOrder-length), [129](#)
- length,ShojiCatalog-method (catalog-length), [19](#)
- length,ShojiOrder-method (ShojiOrder-length), [129](#)
- length,TabBookResult-method (tabbook-methods), [143](#)
- listDatasets, [87](#)
- listDatasets(), [54](#)
- loadDataset, [88](#)
- loadDataset(), [88](#)
- locateEntity, [89](#)
- lock, [89](#)
- login, [90](#)
- logout, [90](#)
  
- makeArray, [91](#)
- makeCaseVariable, [34](#), [91](#)
- makeMR (makeArray), [91](#)
- makeMR(), [93](#)
- makeMRFromText, [93](#)
- makeWeight, [93](#)
- makeWeight(), [160](#)
- margin.table (cube-computing), [40](#)
- margin.table,CrunchCube-method (cube-computing), [40](#)
- matchCatToFeat, [95](#)
- matchCatToFeat(), [6](#)
- max (crunch-uni), [34](#)
- max,CrunchVariable-method (crunch-uni), [34](#)
- max,DatetimeVariable-method (crunch-uni), [34](#)
- max,NumericVariable-method (crunch-uni), [34](#)
- me, [95](#)
  
- mean (crunch-uni), [34](#)
- mean,CrunchVariable-method (crunch-uni), [34](#)
- mean,NumericVariable-method (crunch-uni), [34](#)
- measures (cube-methods), [41](#)
- measures,CrunchCube-method (cube-methods), [41](#)
- median (crunch-uni), [34](#)
- members (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members,CrunchProject-method (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members,CrunchTeam-method (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members<- ,CrunchTeam,MemberCatalog-method, [96](#)
- members<- (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members<- ,CrunchProject,character-method (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members<- ,CrunchProject,MemberCatalog-method (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- members<- ,CrunchTeam,character-method (members<- ,CrunchTeam,MemberCatalog-method), [96](#)
- merge, [86](#), [97](#)
- merge.CrunchDataset (joinDatasets), [86](#)
- mergeFork, [98](#)
- methods::show, [133](#)
- min (crunch-uni), [34](#)
- min,CrunchVariable-method (crunch-uni), [34](#)
- min,DatetimeVariable-method (crunch-uni), [34](#)
- min,NumericVariable-method (crunch-uni), [34](#)
- mkdir (mv), [101](#)
- modifyWeightVariables, [98](#)
- modifyWeightVariables(), [160](#)
- moveToGroup, [99](#)
- moveToGroup<- (moveToGroup), [99](#)



- MultipleResponseVariable  
(CrunchVariable-class), 39
- MultipleResponseVariable-class  
(CrunchVariable-class), 39
- multitable-catalog, 100
- multitables (multitable-catalog), 100
- multitables, CrunchDataset-method  
(multitable-catalog), 100
- multitables<- (multitable-catalog), 100
- multitables<-, CrunchDataset-method  
(multitable-catalog), 100
- mv, 101
- mv(), 23, 70, 120
  
- na-omit-categories, 102
- na.omit, Categories-method  
(na-omit-categories), 102
- name (describe), 58
- name, AbstractCategory-method, 103
- name, CrunchDataset-method (describe), 58
- name, CrunchVariable-method (describe), 58
- name, OrderGroup-method  
(ShojiOrder-slots), 130
- name, ShojiObject-method (describe), 58
- name<- (describe), 58
- name<-, AbstractCategory-method  
(name, AbstractCategory-method), 103
- name<-, CrunchDataset-method (describe), 58
- name<-, CrunchVariable-method  
(describe), 58
- name<-, Multitable-method (describe), 58
- name<-, NULL-method  
(name, AbstractCategory-method), 103
- name<-, OrderGroup-method  
(ShojiOrder-slots), 130
- name<-, ShojiFolder-method (describe), 58
- names, AbstractCategories-method  
(Categories-class), 20
- names, BatchCatalog-method, 104
- names, CategoricalArrayVariable-method  
(names, BatchCatalog-method), 104
- names, CrunchCube-method (cube-methods), 41
- names, CrunchDataset-method  
(names, BatchCatalog-method), 104
- names, MultitableResult-method  
(tabbook-methods), 143
- names, OrderGroup-method  
(ShojiOrder-slots), 130
- names, ShojiCatalog-method  
(names, BatchCatalog-method), 104
- names, ShojiOrder-method  
(ShojiOrder-slots), 130
- names, TabBookResult-method  
(tabbook-methods), 143
- names, VersionCatalog-method  
(names, BatchCatalog-method), 104
- names.CrunchDataFrame  
(CrunchDataFrame), 37
- names<-, AbstractCategories-method  
(Categories-class), 20
- names<-, MultitableCatalog-method  
(names, BatchCatalog-method), 104
- names<-, ShojiCatalog-method  
(names, BatchCatalog-method), 104
- names<-, ShojiOrder-method  
(ShojiOrder-slots), 130
- ncol, CrunchDataset-method  
(dim-dataset), 61
- newDataset, 106
- newDatasetByColumn(), 106
- newDatasetFromFile(), 106
- newFilter, 107
- newMultitable, 107
- newProject, 108
- notes (describe), 58
- notes, CrunchCube-method (cube-methods), 41
- notes, CrunchDataset-method (describe), 58
- notes, CrunchVariable-method (describe), 58
- notes, VariableCatalog-method  
(names, BatchCatalog-method), 104
- notes<- (describe), 58

- notes<- ,CrunchDataset-method  
(describe), 58
- notes<- ,CrunchVariable-method  
(describe), 58
- notes<- ,VariableCatalog-method  
(names, BatchCatalog-method),  
104
- noTransforms, 109
- NumericVariable (CrunchVariable-class),  
39
- NumericVariable-class  
(CrunchVariable-class), 39
- ordering, 30, 110
- ordering, CrunchDataset-method  
(ordering), 110
- ordering, DatasetCatalog-method  
(ordering), 110
- ordering, VariableCatalog-method  
(ordering), 110
- ordering<- (ordering), 110
- ordering<- ,CrunchDataset-method  
(ordering), 110
- ordering<- ,DatasetCatalog-method  
(ordering), 110
- ordering<- ,VariableCatalog-method  
(ordering), 110
- owner (dataset-owner), 46
- owner, CrunchDataset-method  
(dataset-owner), 46
- owner<- (dataset-owner), 46
- owner<- ,CrunchDataset-method  
(dataset-owner), 46
- ownerNames (owners), 111
- owners, 111
- pendingStream, 111
- permissions, 112
- permissions, CrunchDataset-method  
(permissions), 112
- pk, 112
- pk, CrunchDataset-method (pk), 112
- pk<- (pk), 112
- pk<- ,CrunchDataset-method (pk), 112
- pollProgress, 113
- popMagnitude (population), 113
- popMagnitude, CrunchDataset-method  
(population), 113
- popMagnitude<- (population), 113
- popMagnitude<- ,CrunchDataset-method  
(population), 113
- population, 113
- preCrunchBoxCheck, 114
- preCrunchBoxCheck(), 36
- prepareDataForCrunch, 115
- prepareDataForCrunch(), 31
- project-icon, 116
- projects, 116
- projects(), 108
- prop.table (cube-computing), 40
- prop.table, CrunchCube-method  
(cube-computing), 40
- prop.table, MultitableResult-method  
(cube-computing), 40
- prop.table, TabBookResult-method  
(cube-computing), 40
- publish  
(is.archived, DatasetCatalog-method),  
83
- refresh, 117
- refresh(), 150
- refresh, CrunchDataset-method (refresh),  
117
- refresh, CrunchVariable-method  
(refresh), 117
- refresh, ShojiObject-method (refresh),  
117
- removeEmptyGroups, 117
- resetPassword, 118
- restoreVersion, 119, 120, 158
- restoreVersion(), 120, 158
- rmdir, 119
- rmdir(), 23, 101
- rollup (expressions), 66
- rollupResolution (expressions), 66
- rollupResolution<- (expressions), 66
- rollupResolution<- ,DatetimeVariable-method  
(expressions), 66
- round (cube-computing), 40
- round, CrunchCube-method  
(cube-computing), 40

- rstandard, CrunchCube-method  
(cube-residuals), 43
- saveVersion, 119, 120, 158
- saveVersion(), 119
- scoreCatToFeat, 121
- sd (crunch-uni), 34
- sd, CrunchVariable-method (crunch-uni),  
34
- sd, NumericVariable-method (crunch-uni),  
34
- searchDatasets, 121
- self, 122
- self, CrunchVariable-method (self), 122
- self, ShojiObject-method (self), 122
- session, 122
- session-extract, 123
- setDashboardURL (dashboard), 44
- setOrder, 124
- setPopulation (population), 113
- setPopulation, CrunchDataset-method  
(population), 113
- settings, 124
- settings(), 94
- settings<- (settings), 124
- share, 125, 151
- shoji-index, 126
- ShojiObject (ShojiObject-class), 126
- ShojiObject-class, 126
- ShojiOrder-extract, 127
- ShojiOrder-length, 129
- ShojiOrder-slots, 130
- show, Categories-method  
(show, ShojiFolder-method), 131
- show, Category-method  
(show, ShojiFolder-method), 131
- show, CrunchCube-method  
(show, ShojiFolder-method), 131
- show, CrunchExpr-method  
(show, ShojiFolder-method), 131
- show, CrunchGeography-method  
(show, ShojiFolder-method), 131
- show, CrunchLogicalExpr-method  
(show, ShojiFolder-method), 131
- show, CrunchVariable-method  
(show, ShojiFolder-method), 131
- show, Insertion-method  
(show, ShojiFolder-method), 131
- show, Insertions-method  
(show, ShojiFolder-method), 131
- show, MultitableResult-method  
(show, ShojiFolder-method), 131
- show, OrderGroup-method  
(show, ShojiFolder-method), 131
- show, ShojiFolder-method, 131
- show, ShojiObject-method  
(show, ShojiFolder-method), 131
- show-crunch (show, ShojiFolder-method),  
131
- showIfAny (cube-missingness), 43
- showIfAny, CrunchCube-method  
(cube-missingness), 43
- showMissing (cube-missingness), 43
- showMissing, CrunchCube-method  
(cube-missingness), 43
- showTransforms  
(showTransforms, CrunchCube-method),  
133
- showTransforms, CategoricalVariable-method  
(showTransforms, CrunchCube-method),  
133
- showTransforms, CrunchCube-method, 133
- startDate (describe), 58
- startDate, CrunchDataset-method  
(describe), 58
- startDate<- (describe), 58
- startDate<-, CrunchDataset-method  
(describe), 58
- stats::chisq.test, 44
- stats::formula, 108
- stats::formula(), 108
- stats::lm(), 47
- stats::median(), 35
- stats::sd(), 35
- stats::xtabs(), 32
- subset, CrunchDataset-method  
(dataset-extract), 45
- Subtotal (Subtotal-class), 134
- Subtotal(), 79, 149
- Subtotal-class, 134
- subtotalArray  
(subtotalArray, CrunchCube-method),  
137
- subtotalArray, CrunchCube-method, 136
- Subtotals, 137
- subtotals, 79

- subtotals (Subtotal-class), 134
- subtotals, CrunchVariable-method (Subtotal-class), 134
- subtotals, VariableTuple-method (Subtotal-class), 134
- subtotals<- (Subtotal-class), 134
- subtotals<-, CrunchVariable, ANY-method (Subtotal-class), 134
- subtotals<-, CrunchVariable, NULL-method (Subtotal-class), 134
- subtotals<-, Insertion, ANY-method (Insertions-class), 77
- SubtotalsHeadings (Subtotal-class), 134
- Subvariables, 104, 105
- Subvariables (Subvariables-class), 138
- subvariables, 7
- subvariables (Subvariables-class), 138
- subvariables, CategoricalArrayVariable-method (Subvariables-class), 138
- subvariables, VariableTuple-method (Subvariables-class), 138
- Subvariables-class, 138
- subvariables<- (Subvariables-class), 138
- subvariables<-, CategoricalArrayVariable, ANY-method (Subvariables-class), 138
- subvariables<-, CategoricalArrayVariable, Subvariables-method (Subvariables-class), 138
- subvars-extract, 139
- SummaryStat (SummaryStat-class), 141
- SummaryStat-class, 141
  
- tabBook, 142
- tabBook(), 41
- tabbook-methods, 143
- table, 144
- teams, 72
- teams
  - (members<-, CrunchTeam, MemberCatalog-method), 96
- temp.option (temp.options), 145
- temp.options, 145
- TextVariable (CrunchVariable-class), 39
- TextVariable-class (CrunchVariable-class), 39
- timestamps (names, BatchCatalog-method), 104
- timestamps, VersionCatalog-method (names, BatchCatalog-method), 104
  
- toJSON (tojson-crunch), 145
- tojson-crunch, 145
- toVariable, 146, 156
- toVariable, AsIs-method (toVariable), 146
- toVariable, character-method (toVariable), 146
- toVariable, CrunchExpr-method (toVariable), 146
- toVariable, Date-method (toVariable), 146
- toVariable, factor-method (toVariable), 146
- toVariable, labelled-method (toVariable), 146
- toVariable, labelled\_spss-method (toVariable), 146
- toVariable, logical-method (toVariable), 146
- toVariable, numeric-method (toVariable), 146
- toVariable, POSIXt-method (toVariable), 146
- toVariable, VariableDefinition-method (toVariable), 146
- transformations, 77
- Transforms (Transforms-class), 148
- transforms (Transforms-class), 148
- transforms, CrunchCube-method (Transforms-class), 148
- transforms, CrunchVariable-method (Transforms-class), 148
- transforms, VariableCatalog-method (Transforms-class), 148
- transforms, VariableTuple-method (Transforms-class), 148
- Transforms-class, 148
- transforms<- (Transforms-class), 148
- transforms<-, CrunchCube, list-method (Transforms-class), 148
- transforms<-, CrunchCube, NULL-method (Transforms-class), 148
- transforms<-, CrunchVariable, NULL-method (Transforms-class), 148
- transforms<-, CrunchVariable, Transforms-method (Transforms-class), 148
- type, 149
- type, CrunchVariable-method (type), 149
- type, VariableEntity-method (type), 149
- type<- (type), 149

- type<- ,CrunchVariable-method (type), 149
- types (names, BatchCatalog-method), 104
- types, CrunchCube-method (cube-methods), 41
- types, ShojiFolder-method (names, BatchCatalog-method), 104
- types, VariableCatalog-method (names, BatchCatalog-method), 104
- unbind, 150
- undichotomize (dichotomize), 60
- undichotomize, CategoricalArrayVariable-method (dichotomize), 60
- undichotomize, CategoricalVariable-method (dichotomize), 60
- undichotomize, Categories-method (dichotomize), 60
- ungrouped (grouped), 72
- unhide (hide), 73
- unhide, CrunchVariable-method (hide), 73
- unhide, VariableCatalog-method (hide), 73
- unhideVariables (hideVariables), 74
- uniformBasis (describe), 58
- uniformBasis, MultipleResponseVariable-method (describe), 58
- uniformBasis<- (describe), 58
- uniformBasis<- , MultipleResponseVariable-method (describe), 58
- unlock (lock), 89
- unshare, 125, 151
- utils::write.csv, 162
- utils::write.table(), 65
- value (name, AbstractCategory-method), 103
- value, Category-method (name, AbstractCategory-method), 103
- value<- (name, AbstractCategory-method), 103
- value<- , Category-method (name, AbstractCategory-method), 103
- values (Categories-class), 20
- values, Categories-method (Categories-class), 20
- values<- (Categories-class), 20
- values<- , Categories-method (Categories-class), 20
- var-categories, 151
- VarDef (VariableDefinition), 156
- variable-as-methods, 152
- variable-extract ([, CrunchExpr, CrunchLogicalExpr, ANY-method), 162
- variable-to-R (as.vector, CrunchExpr-method), 12
- variable-update, 154
- VariableCatalog, 110, 158
- VariableCatalog (VariableCatalog-class), 156
- VariableCatalog-class, 156
- VariableDefinition, 10, 25, 34, 80, 92, 156
- VariableDefinition(), 94, 147
- VariableGroup (VariableOrder-class), 157
- VariableGroup-class (VariableOrder-class), 157
- variableMetadata, 157
- VariableOrder, 30, 73, 110, 131, 156
- VariableOrder (VariableOrder-class), 157
- VariableOrder-class, 157
- variables (dataset-variables), 50
- variables, CrunchCube-method (cube-methods), 41
- variables, CrunchDataset-method (dataset-variables), 50
- variables, CubeDims-method (cube-methods), 41
- variables, SearchResults-method (dataset-variables), 50
- variables<- (dataset-variables), 50
- variables<- , CrunchDataset, VariableCatalog-method (dataset-variables), 50
- versions, 119, 120, 158
- versions(), 119, 120
- webApp, 159
- weight, 32, 142, 159
- weight(), 32, 94, 160
- weight<- (weight), 159
- weightVariables, 160
- weightVariables(), 160
- weightVariables, CrunchDataset-method (weightVariables), 160

weightVariables, VariableCatalog-method  
    (weightVariables), 160

weightVariables<-  
    (modifyWeightVariables), 98

weightVariables<-, CrunchDataset-method  
    (modifyWeightVariables), 98

which, 161

which, CrunchLogicalExpr-method (which),  
    161

with-context-manager, 161

with.contextManager  
    (with-context-manager), 161

with\_consent (consent), 28

with\_consent(), 53, 55, 56, 68

write.csv (exportDataset), 65

write.csv, CrunchDataset-method  
    (exportDataset), 65

write.csv.gz, 162