

Package ‘ITGM’

August 5, 2017

Type Package

Title Individual Tree Growth Modeling

Version 0.6

Author Clayton Vieira Fraga Filho, Miqueias Fernandes

Maintainer Clayton Vieira Fraga Filho <forestgrowthsoftware@gmail.com>

Description Individual tree model is an instrument to support the decision with regard to forest management. This package provides functions that let you work with data for this model. Also other support functions and extension related to this model are available.

License GPL-2

LazyData TRUE

Depends Fgmutils (>= 0.8), R (>= 3.0)

Imports gsubfn, data.table, sqldf, plyr, randomcoloR, rbokeh, ggplot2

RoxygenNote 6.0.1

Suggests testthat

NeedsCompilation no

Repository CRAN

Date/Publication 2017-08-04 22:40:17 UTC

R topics documented:

addSettings	2
avaliaModeloEspecial	3
avaliaVolumeAvancado2	3
criaModeloExclusivo2	4
criaModeloGenerico2	5
firstsMeasurements	5
getAllEstatisticsFn	6
getAllGraphicsFn	6
getggplot2GraphicObservadoXEstimadoTotal	7
getGraphicVolumeTotal	8

getModelosLiteraturaExclusivos	9
getModelosLiteraturaGenericos	9
getModelsExclusiveOfLiterature	10
getModelsGenericOfLiterature	10
maiTOMdd	11
plotRB	12
preparaFormula	13
project	13
removeColsSuspicious	14
runAndReport	14

Index	15
--------------	-----------

addSettings	<i>Add Settings to list param</i>
-------------	-----------------------------------

Description

This function assigns if the parameter does not exist or adds the parameter to the configuration. The variable assigned to the parameter is present in the last line of the script

Usage

```
addSettings(script, tipo, configuracao = NULL)
```

Arguments

script	Script is a string that contains the script
tipo	Type is one of the possibilities of parameter of evaluationVolumeAdvanced like: "models" or "graphs" or "statistics" or "save"
configuracao	Configuration is a list that contains the settings for evaluation in the function EvaluateSpecial ()

Value

list of settings

avaliaModeloEspecial *Avalia Model Special*

Description

This function is a wizard to use the function `ValueValueAdvanced2` configuration: a list of configurations that will be passed as parameter to function `avaliaVolumeAvancado2`

Usage

```
avaliaModeloEspecial(configuracao)
```

Arguments

configuracao It is the list of settings

Value

result of `avaliaVolumeAvancado2`

avaliaVolumeAvancado2 *evaluates Volume Advanced*

Description

this function performs an assessment of estimates of a variable as the forcefulness with expected

Usage

```
avaliaVolumeAvancado2(base = NULL, basePredicao = NULL,
  baseProjecao = NULL, mapeamento = list(dap1 = "dap1", dap2 = "dap2", ht1 =
  "ht1", ht2 = "ht2", idade2 = "idadearred2", parcela = "parcela", areacorr =
  "areacorr"), modelos = NULL, salvar = NULL, graficos = NULL,
  estatisticas = NULL, forcePredict = F, dividirEm = NULL,
  percentualDeTreino = 0.7, agruparPor = NULL,
  fnCalculaVolume = calculaVolumeDefault, rmColsSuspicious = F)
```

Arguments

base	data.frame with data in case of fragment base
basePredicao	data.frame with data to use in ajust
baseProjecao	data.frame with data to use in validation
mapeamento	name of fields on base
modelos	list of exclusive for base models

salvar	list of param to save the files
graficos	list of param to plot graphics
estatisticas	list of param to caclc estatistics
forcePredict	force the calculation without using predict?
dividirEm	how divide the base in training and validation
percentualDeTreino	how many percent will stay in the training group?
agruparPor	name field of base is group of individuals
fnCalculaVolume	
	list of estatistics results
rmColsSuspicious	
	remove fields b0, b1, b2, b2 ... of bases?

Value

will be returned a result of statistics and ranking of volume

criaModeloExclusivo2 *Create Exclusive Model for a database*

Description

this function returns a unique model is variable receive each mapeda variable ex .: criaModeloExclusivo (modeloCamposLeite, c ("age1", "age2", "bai1", "s"))

Usage

```
criaModeloExclusivo2(modeloGenerico, variaveis, palpate = NULL)
```

Arguments

modeloGenerico	model of pattern criaModeloGenerico
variaveis	list of name fields (strings) in database and model, the order of variables matter
palpate	string containing start values of function of regression

Value

will be returned a function with exclusive model

criaModeloGenerico2 *Create function with generic model*

Description

This function creates a generic model that will be a funcao that has parameters for the variables that can be mapped to each different base. her return will be a generic model that should be mapped to be used by the function avaliaEstimativas

Usage

```
criaModeloGenerico2(nome, formula, funcaoRegressao, variaveis, palpite = NULL,
  maisParametros = NULL, requires = NULL)
```

Arguments

nome	is the name of model
formula	is the string formula begin with y2~y1
funcaoRegressao	is the function that will make the regression, ex.: 'nlsLM'
variaveis	list variables that are present in the model that are field database
palpite	param start of funcaoRegressao
maisParametros	string add in funcaoRegressao, ex lm(y2~y1, data=base, maisParametros)
requires	list of string of packages used to work with funcaoRegressao

Value

will be returned function with generic model to map to a base

firstsMeasurements *First Measurements per Group*

Description

this function generates a field "primeiraMedicao" that contains the lowest age for each item in the group both derived from dtFrame

Usage

```
firstsMeasurements(dtFrame, group = "parcela", age = "idadearred")
```

Arguments

dtFrame	It is the database that contains the data
group	is the field that represents the groups default parcela
age	default idadearred is the name of field containing the values of the group

Value

data.frame dtFrame with the field "primeiraMedicao"

Examples

```
dtf = data.frame(
  grupo = c(1,2,3,4,1,2,3,4),
  medicoes= c(10,20,30,40,5,30,1,52))
firstsMeasurements(dtf, group = "grupo", age = "medicoes")
```

getAllEstatisticsFn *Get All Functions of Statistics of ITGM*

Description

this function allows you to obtain all functions available in ITGM for model evaluation.

Usage

```
getAllEstatisticsFn()
```

Value

collection of functions statistics

getAllGraphicsFn *Get All Functions of Graphics of ITGM*

Description

this function allows you to obtain all functions available in ITGM for model evaluation.

Usage

```
getAllGraphicsFn()
```

Value

collection of functions graphics

 getggplot2GraphicObservadoXEstimadoTotal

Get ggplot2 Grapic observed versus estimated of Total

Description

this function displays/saves/returns a Graphical ggplot2 illustrating the difference between the observed and estimated

Usage

```
getggplot2GraphicObservadoXEstimadoTotal(titulo = "observadoXestimado",
  nome = "observadoXestimado", observado, estimado,
  identificadorIndividual = NULL, identificadorGrupal = NULL,
  showTestF = TRUE, TestFposition = 4, titleIdentificadorGrupal = NULL,
  save = NULL, labsX = "observado", labsy = "estimado",
  nomeParaExibir = NULL, environ = 1, extensao = ".png", desc = NULL,
  data = NULL, mapeamento = list(idade2 = "idadearred2", parcela =
  "parcela", areacorr = "areacorr"), ...)
```

Arguments

titulo	is the title graphic
nome	name of file case save
observado	list containing the observations of variable
estimado	list containing estimates of variable
identificadorIndividual	list containing 'id' of individuals
identificadorGrupal	list containing group of individuals
showTestF	draw results of test F in graphic?
TestFposition	show one of the four corners of the graph clockwise
titleIdentificadorGrupal	title of Legend of the groups
save	If you want to save enter the directory as a string
labsX	label x
labsy	label y
nomeParaExibir	This is the name to display the graph as a function after the completion of this
environ	environment in which the function to display the ggplot2 must be saved
extensao	type of image that will be saved
desc	description of plot geted from avaliavolumeavancado
data	database to retireve fields to id
mapeamento	name of fields on base
...	only for compatibility with other functions

Value

will be returned the graphical generated by ggplot2

getGraphicVolumeTotal *Get rbokeh graphic observed versus estimated*

Description

this function displays/saves/returns a Graphical rbokeh illustrating the difference between the observed and estimated

Usage

```
getGraphicVolumeTotal(titulo = "observadoXestimado",
  nome = "observadoXestimado", observado, estimado, showTestF = TRUE,
  save = NULL, labsX = "observado", labsy = "estimado", vetorial = T,
  desc = NULL, data = NULL, mapeamento = list(idade2 = "idadearred2",
  parcela = "parcela", areacorr = "areacorr"), ...)
```

Arguments

titulo	is the title graphic
nome	name of file case save
observado	list containing the observations of variable
estimado	list containing estimates of variable
showTestF	draw results of test F in graphic?
save	If you want to save enter the directory as a string
labsX	label x
labsy	label y
vetorial	save picture in vector type? (Default TRUE)
desc	description of plot geted from avaliavolumeavancado
data	database to retireve fields to id
mapeamento	name of fields on base
...	optionals params to plot graphic in ITGM

Value

will be returned a rbokeh graphic

`getModelosLiteraturaExclusivos`
get Models Literature Exclusives

Description

This function creates and returns an array with the usual models mapped to the mapping vector

Usage

```
getModelosLiteraturaExclusivos(mapeamento = c("idade1", "idade2", "bai1",  
"s"))
```

Arguments

`mapeamento` list of names fields of database will work "idade1", "idade2", "bai1", "s"

Value

will be returned list of function with exclusive model

`getModelosLiteraturaGenericos`
get Generic Model Literature

Description

This function creates and returns an array with the usual models of literature

Usage

```
getModelosLiteraturaGenericos()
```

Value

will be returned list of models generic

`getModelsExclusiveOfLiterature`
get Models Literature Exclusives

Description

This function creates and returns an array with the usual models mapped to the mapping vector

Usage

```
getModelsExclusiveOfLiterature(mapper = c("idade1", "idade2", "bai1", "s"))
```

Arguments

`mapper` list of names fields of database will work "idade1", "idade2", "bai1", "s"

Value

will be returned list of function with exclusive model

`getModelsGenericOfLiterature`
get Generic Model Literature

Description

This function creates and returns an array with the usual models of literature

Usage

```
getModelsGenericOfLiterature()
```

Value

will be returned list of models generic

`maiTOMdd`*Individual Tree Model to Diameter Distribution Model*

Description

this function add fields to returned base "inventario" in order to make it usable for diameter distribution models

Usage

```
maiTOMdd(projeto, talhao, parcela, fila, cova, fuste, idade, dap, volume,
          espacamento, amplitude = 1, verbose = FALSE)
```

Arguments

<code>projeto</code>	is the field that contains the cod project of individuals
<code>talhao</code>	is the field that contains the cod of project subdivision
<code>parcela</code>	is the field that contains the cod of talhao subdivision
<code>fila</code>	is the field that contains the cod row where the tree is
<code>cova</code>	is the field that contains the cod pit where the tree is
<code>fuste</code>	is the field that contains the cod shaft of tree
<code>idade</code>	is the field that contains the age of individuals the observation
<code>dap</code>	is the field that contains the diameter of individuals the observation
<code>volume</code>	is the field that contains the volume of individuals the observation
<code>espacamento</code>	is the field that contains the distance in METROS between one and another individual for ex.:c("3 x 3", "3,3 x 3", ...
<code>amplitude</code>	default 1 is the amplitude of diameter classes
<code>verbose</code>	use TRUE to status presentation

Value

data.table what is "inventario" with some added fields

 plotRB

Get rbokeh graphic observed versus estimated

Description

this function displays/saves/returns a Graphical rbokeh illustrating the difference between the observed and estimated

Usage

```
plotRB(titulo = "observadoXestimado", nome = "observadoXestimado",
       observado, estimado, id = NULL, save = NULL, labsX = "observado",
       labsy = "estimado", showTestF = TRUE, colID = "idLabel",
       sobnome = "ObservadoXEstimado", data = NULL, diretorio = NULL,
       datadiretorio = NULL, HTTPS = FALSE, totalizar = NULL, campoID = NULL,
       mapeamento = list(idade2 = "idadearred2", parcela = "parcela", areacorr =
       "areacorr"), ...)
```

Arguments

titulo	is the title graphic
nome	name of file case save
observado	list containing the observations of variable
estimado	list containing estimates of variable
id	list containing 'id' of individuals
save	If you want to save enter the directory as a string
labsX	label x
labsy	label y
showTestF	draw results of test F in graphic?
colID	label of ids
sobnome	optional name to append of file name graphic
data	database to retrieve fields to id
diretorio	database to retrieve fields to id
datadiretorio	optional abstract path of directory
HTTPS	script in https?
totalizar	generat graphic of volume total
campoID	name of parcela field in data
mapeamento	name of fields on base
...	optionals params to plot graphic in ITGM

Value

will be returned a rbokeh graphic

preparaFormula	<i>Prepare formula</i>
----------------	------------------------

Description

this function prepare formula to use in models

Usage

```
preparaFormula(formula)
```

Arguments

formula It is the string formula to use in modelo

Value

formula handled

project	<i>Project Volume based in Ages</i>
---------	-------------------------------------

Description

this function provides a list of volume projections in a future age or from one to another future age

Usage

```
project(firstAge = NaN, lastAge, fitDAP, fitHT, base, mapper = list(age1 =
  "idade1", age2 = "idade2", dap1 = "dap1", dap2 = "dap2", ht1 = "ht1", ht2 =
  "ht2"), calcVolume = calculaVolumeDefault, withoutBaseFields = F)
```

Arguments

firstAge early age. if only one age use NaN

lastAge late age for project or the age at which one wants to get the volume

fitDAP an adjustment of the return type of a function lm() from dap

fitHT an adjustment of the return type of a function lm() from ht

base a dataset to project

mapper the mapping for the name of the old fields age, dap and ht in base

calcVolume function to calc volume based base, dap e ht, default calculaVolumeDefault of Fgmutils

withoutBaseFields want returned projected volume no contains the fields of the base? default no

removeColsSuspicious *Create function with generic model*

Description

This function creates a generic model that will be a funcao that has parameters for the variables that can be mapped to each different base. her return will be a generic model that should be mapped to be used by the function avaliaEstimativas

Usage

```
removeColsSuspicious(base, colsRm)
```

Arguments

base	is the data with fields to remove
colsRm	is the collections of name fields suspicius to remove of base

Value

will be returned function with generic model to map to a base

runAndReport *Evaluate avaliation and report result*

Description

This function tries to execute the script and stores the result of the execution in a report script is a string that contains the script in R to be executed report is the file to be saved with the report the function saves a file in the local directory with report name, Which is a JSON relatory.

Usage

```
runAndReport(script, report, environment, showWarnings = F)
```

Arguments

script	It is the script to evaluate
report	is the name of file to save reports
environment	the environment to evaluate script
showWarnings	show thrown warnings?

Value

will be returned implicit var

Index

[addSettings](#), [2](#)
[avaliaModeloEspecial](#), [3](#)
[avaliaVolumeAvancado2](#), [3](#)

[criaModeloExclusivo2](#), [4](#)
[criaModeloGenerico2](#), [5](#)

[firstsMeasurements](#), [5](#)

[getAllEstatisticsFn](#), [6](#)
[getAllGraphicsFn](#), [6](#)
[getggplot2GraphicObservadoXEstimadoTotal](#),
[7](#)
[getGraphicVolumeTotal](#), [8](#)
[getModelosLiteraturaExclusivos](#), [9](#)
[getModelosLiteraturaGenericos](#), [9](#)
[getModelsExclusiveOfLiterature](#), [10](#)
[getModelsGenericOfLiterature](#), [10](#)

[maiT0mdd](#), [11](#)

[plotRB](#), [12](#)
[preparaFormula](#), [13](#)
[project](#), [13](#)

[removeColsSuspicious](#), [14](#)
[runAndReport](#), [14](#)