

Package ‘estudy2’

February 16, 2018

Type Package

Title An Implementation of Parametric and Nonparametric Event Study

Version 0.8.4

Date 2018-02-16

Description An implementation of a most commonly used event study methodology, including both parametric and nonparametric tests. It contains variety aspects of the rate of return estimation (the core calculation is done in C++), as well as three classical for event study market models: mean adjusted returns, market adjusted returns and single-index market models. There are 6 parametric and 6 nonparametric tests provided, which examine cross-sectional daily abnormal return (see the documentation of the functions for more information). Parametric tests include tests proposed by Brown and Warner (1980) <DOI:10.1016/0304-405X(80)90002-1>, Brown and Warner (1985) <DOI:10.1016/0304-405X(85)90042-X>, Boehmer et al. (1991) <DOI:10.1016/0304-405X(91)90032-F>, Patell (1976) <DOI:10.2307/2490543>, and Lamb (1995) <DOI:10.2307/253695>. Nonparametric tests covered in estudy2 are tests described in Corrado and Zivney (1992) <DOI:10.2307/2331331>, McConnell and Muscarella (1985) <DOI:10.1016/0304-405X(85)90006-6>, Boehmer et al. (1991) <DOI:10.1016/0304-405X(91)90032-F>, Cowan (1992) <DOI:10.1007/BF00939016>, Corrado (1989) <DOI:10.1016/0304-405X(89)90064-0>, Campbell and Wasley (1993) <DOI:10.1016/0304-405X(93)90025-7>, Savickas (2003) <DOI:10.1111/1475-6803.00052>, Kolari and Pynnonen (2010) <DOI:10.1093/rfs/hhq072>. Furthermore, tests for the cumulative abnormal returns proposed by Brown and Warner (1985) <DOI:10.1016/0304-405X(85)90042-X> and Lamb (1995) <DOI:10.2307/253695> are included.

License GPL-3

LazyData TRUE

URL <http://github.com/irudnyts/estudy2>

BugReports <http://github.com/irudnyts/estudy2/issues>

Depends R (>= 3.1)

Imports tseries (>= 0.10-42), zoo (>= 1.8-0), matrixStats (>= 0.52.2), Rcpp (>= 0.12.13)

LinkingTo Rcpp

RoxygenNote 6.0.1

Suggests knitr, rmarkdown, magrittr

VignetteBuilder knitr

NeedsCompilation yes

Author Iegor Rudnytskyi [aut, cre]

Maintainer Iegor Rudnytskyi <iegor.rudnytskyi@gmail.com>

Repository CRAN

Date/Publication 2018-02-16 18:32:52 UTC

R topics documented:

apply_market_model	3
boehmer	6
brown_warner_1980	7
brown_warner_1985	9
car_brown_warner_1985	11
car_lamb	13
car_parametric_tests	14
corrado_sign_test	16
generalized_sign_test	18
get_prices_from_tickers	20
get_rates_from_prices	21
lamb	23
modified_rank_test	24
nonparametric_tests	26
parametric_tests	28
patell	30
prices	32
prices_indx	33
rank_test	33
rates	35
rates_indx	36
returns	36
securities_returns	39
sign_test	40
t_test	42
wilcoxon_test	43
Index	46

apply_market_model *Apply a market model and return a list of returns objects.*

Description

The function applies a given market model to securities' rates of returns and returns a list of returns objects for each security, which can be passed directly to a whole battery of tests.

Usage

```
apply_market_model(rates, regressors, same_regressor_for_all = TRUE,  
  market_model = c("mean_adj", "mrkt_adj", "sim"),  
  estimation_method = c("ols"), estimation_start, estimation_end)
```

Arguments

`rates` an object of `list`, `data.frame`, `zoo` containing rates of returns of securities.

`regressors` an object of the same class as `rates` containing regressors. The argument can be omitted, if market model is `mean_adj`. regressors must have the same number of components as `rates` except cases when the same regressor is used for all securities.

`same_regressor_for_all` logical. Should the same regressor be used for each security? The default value is `TRUE`.

`market_model` a character indicating the market model among `mean_adj`, `mrkt_adj`, and `sim`.

`estimation_method` a character specifying an estimation method for `sim` model.

`estimation_start` an object of `Date` class giving the first date of the estimation period.

`estimation_end` an object of `Date` class giving the last date of the estimation period.

Details

The generic function is dispatched for such classes as `list`, `data.frame`, and `zoo`. If `same_regressor_for_all` is `TRUE`, and `regressors` has the length greater than one, the first element of `regressors` will be applied for each security in `rates`.

Value

A list of returns objects.

References

Brown S.J., Warner J.B. *Using Daily Stock Returns, The Case of Event Studies*. Journal of Financial Economics, 14:3-31, 1985.

See Also[returns](#)**Examples**

```
## 1. Mean-adjusted-returns model
## Not run:
library("magrittr")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
securities_returns <- get_prices_from_tickers(tickers,
                                             start = as.Date("2000-01-01"),
                                             end = as.Date("2002-01-01"),
                                             quote = "Close",
                                             retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(market_model = "mean_adj",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates)
securities_returns <- apply_market_model(
  rates,
  market_model = "mean_adj",
  estimation_start = as.Date("2001-03-26"),
  estimation_end = as.Date("2001-09-10")
)

## 2. Market-adjusted-returns model
## Not run:
library("magrittr")
rates_idx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
securities_returns <- get_prices_from_tickers(tickers,
                                             start = as.Date("2000-01-01"),
                                             end = as.Date("2002-01-01"),
                                             quote = "Close",
                                             retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
```

```

        compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "mrkt_adj",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates, rates_indx)
securities_returns <- apply_market_model(
  rates = rates,
  regressor = rates_indx,
  same_regressor_for_all = TRUE,
  market_model = "mrkt_adj",
  estimation_start = as.Date("2001-03-26"),
  estimation_end = as.Date("2001-09-10")
)

## 3. Single-index market model
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
securities_returns <- get_prices_from_tickers(tickers,
                                             start = as.Date("2000-01-01"),
                                             end = as.Date("2002-01-01"),
                                             quote = "Close",
                                             retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates, rates_indx)
securities_returns <- apply_market_model(
  rates = rates,
  regressor = rates_indx,

```

```

same_regressor_for_all = TRUE,
market_model = "sim",
estimation_method = "ols",
estimation_start = as.Date("2001-03-26"),
estimation_end = as.Date("2001-09-10")
)

```

boehmer

Boehmer's parametric test (1991).

Description

An event study parametric test described in Boehmer 1991.

Usage

```
boehmer(list_of_returns, event_start, event_end)
```

Arguments

<code>list_of_returns</code>	a list of objects of S3 class returns, each element of which is treated as a security.
<code>event_start</code>	an object of Date class giving the first date of the event period.
<code>event_end</code>	an object of Date class giving the last date of the event period.

Details

Performs a parametric test for event study, which is described in Boehmer 1991. Also called hybrid test or standardized cross-sectional test. This test performs t-test based on Patell's standardized residuals. By combining Patell's and t-tests, this test allows for event-induced variance changes, but still assumes cross-sectional independence. The test examines the hypothesis whether the theoretical cross-sectional expected value for a given day is equal to zero. It calculates statistics even if event window and estimation period are overlapped (intersect). The critical values has Student's t-distribution. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

- Patell J.M. *Corporate forecasts of earnings per share and stock price behavior: empirical tests*. Journal of Accounting Research, 14(2):246- 276, 1976.
- Boehmer E., Musumeci J., Poulsen A.B. *Event-study methodology under conditions of event-induced variance*. Journal of Financial Economics, 30(2):253-272, 1991.

See Also

[parametric_tests](#), [brown_warner_1980](#), [brown_warner_1985](#), [t_test](#), [patell](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  boehmer(event_start = as.Date("2001-09-11"),
          event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
boehmer(list_of_returns = securities_returns,
        event_start = as.Date("2001-09-11"),
        event_end = as.Date("2001-09-28"))
```

brown_warner_1980

Brown and Warner parametric test (1980).

Description

An event study parametric test described in Brown and Warner 1980.

Usage

```
brown_warner_1980(list_of_returns, event_start, event_end)
```

Arguments

```
list_of_returns      a list of objects of S3 class returns, each element of which is treated as a
                    security.
event_start          an object of Date class giving the first date of the event period.
event_end            an object of Date class giving the last date of the event period.
```

Details

Performs a parametric test for the event study, which is described in Brown and Warner 1980. The test assumes a cross-sectional independence and an insignificance of event-induced variance. The test examines the hypothesis whether the theoretical cross-sectional expected value for a given day is equal to zero. The standard deviation in statistics is calculated as the cross-sectional mean of companies' variances, estimated on the estimation period. It calculates statistics even if the event window and the estimation period are overlapped (intersect). The critical values are Student's t-distributed (no approximation in limit). The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***). It was designed to measure monthly data: for daily data look at Brown and Warner 1985 and brown_warner_1985.

Value

A data frame of test's statistics and significances.

References

Brown S.J., Warner J.B. *Measuring security price performance*. Journal of Financial Economics, 8:205-258, 1980.

See Also

[parametric_tests](#), [brown_warner_1985](#), [t_test](#), [patell](#), [boehmer](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
```



```

get_prices_from_tickers(tickers,
                        start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous") %>%
apply_market_model(regressor = rates_indx,
                   same_regressor_for_all = TRUE,
                   market_model = "sim",
                   estimation_method = "ols",
                   estimation_start = as.Date("2001-03-26"),
                   estimation_end = as.Date("2001-09-10")) %>%
brown_warner_1980(event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
brown_warner_1980(list_of_returns = securities_returns,
                  event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

```

brown_warner_1985 *Brown and Warner parametric test (1985).*

Description

An event study parametric test described in Brown and Warner 1985.

Usage

```
brown_warner_1985(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

Performs a parametric test for event study, which is described in Brown and Warner 1985, which is a traditional event study approach. Assumes cross-sectional independence and is non-robust to an event-induced variance. The test examines the hypothesis whether the theoretical cross-sectional expected value for a given day is equal to zero. The standard deviation in statistics is estimated as the cross-sectional standard deviation of companies' means, estimated on the estimation period. It calculates statistics even if event window and estimation period are overlapped (intersect). The critical values are Student's t-distributed (no approximation in limit). The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

Brown S.J., Warner J.B. *Using Daily Stock Returns, The Case of Event Studies*. Journal of Financial Economics, 14:3-31, 1985.

See Also

[parametric_tests](#), [brown_warner_1980](#), [t_test](#), [patell](#), [boehmer](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
```

```

    brown_warner_1985(event_start = as.Date("2001-09-11"),
                      event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
brown_warner_1985(list_of_returns = securities_returns,
                  event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

```

car_brown_warner_1985 *Brown and Warner (1985) CAR test.*

Description

A parametric test proposed by Brown and Warner 1995 that examines whether or not cumulative abnormal return (CAR) significantly differs from zero.

Usage

```
car_brown_warner_1985(list_of_returns, car_start, car_end, percentage = 90)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
car_start	an object of Date class giving the first date of the CAR period.
car_end	an object of Date class giving the last date of the CAR period.
percentage	a lowest allowed percentage of non-missing observation for each day to be incorporated into CAR. The default value is 90 percent.

Details

This function performs a test proposed by Brown and Warner 1985 to investigate whether CAR significantly differs from zero. This tests uses the variance, specified by Lamb 1995. The advantage of this test is allowance for correlated cross-sectional returns. The test statistic is close enough to statistic, produced by `car_lamb`. The critical values are standard normal. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A list of fist date, last date, average percentage of non-missing observation over each day, the value of statistics, the length of the time period, and the significance.

References

Brown S.J., Warner J.B. *Using Daily Stock Returns, The Case of Event Studies*. Journal of Financial Economics, 14:3-31, 1985.

See Also

[car_lamb](#) and [car_parametric_tests](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                        start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  car_brown_warner_1985(car_start = as.Date("2001-09-11"),
                       car_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
car_brown_warner_1985(
  list_of_returns = securities_returns,
  car_start = as.Date("2001-09-11"),
  car_end = as.Date("2001-09-28")
)
```

car_lamb	<i>Lamb's CAR test (1995).</i>
----------	--------------------------------

Description

A parametric test proposed by Lamb 1995 that examines whether or not the cumulative abnormal return (CAR) significantly differs from zero.

Usage

```
car_lamb(list_of_returns, car_start, car_end, percentage = 90)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
car_start	an object of Date class giving the first date of the CAR period.
car_end	an object of Date class giving the last date of the CAR period.
percentage	a lowest allowed percentage of non-missing observation for each day to be incorporated into CAR. The default value is 90 percent.

Details

This function performs a test proposed by Lamb 1995 to investigate whether CAR significantly differs from zero. This test uses the variance, specified by Lamb 1995. The advantage of this test is allowance for correlated cross-sectional returns. The test statistic is close enough to statistic, produced by [car_brown_warner_1985](#). The critical values are standard normal. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A list of first date, last date, average percentage of non-missing observation over each day, the value of statistics, the length of the time period, and the significance.

References

Lamb R.P. *An Exposure-Based Analysis of Property-Liability Insurer Stock Values around Hurricane Andrew*. Journal of Risk and Insurance, 62(1):111-123, 1995.

See Also

[car_brown_warner_1985](#) and [car_parametric_tests](#).

Examples

```

## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  car_lamb(car_start = as.Date("2001-09-11"),
          car_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
car_lamb(
  list_of_returns = securities_returns,
  car_start = as.Date("2001-09-11"),
  car_end = as.Date("2001-09-28")
)

```

car_parametric_tests *Returns the result of given event study parametric CAR tests.*

Description

Performs given tests to examine whether cumulative abnormal return (CAR) significantly differs from zero.

Usage

```
car_parametric_tests(list_of_returns, car_start, car_end, percentage = 90,
  all = TRUE, tests)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
car_start	an object of Date class giving the first date of the CAR period.
car_end	an object of Date class giving the last date of the CAR period.
percentage	a lowest allowed percentage of non-missing observation for each day to be incorporated into CAR. The default value is 90 percent.
all	a logical value indicating whether all tests should be performed. The default value is TRUE.
tests	a list of tests' functions among car_brown_warner_1985 and car_lamb.

Details

car_parametric_tests performs specified tests among car_brown_warner_1985 and lamb and returns a list of these tests' results. If all = TRUE (by default), the function ignores the value of tests.

Value

A list of results of given tests.

References

- Brown S.J., Warner J.B. *Using Daily Stock Returns, The Case of Event Studies*. Journal of Financial Economics, 14:3-31, 1985.
- Lamb R.P. *An Exposure-Based Analysis of Property-Liability Insurer Stock Values around Hurricane Andrew*. Journal of Risk and Insurance, 62(1):111-123, 1995.

See Also

[car_brown_warner_1985](#) and [car_lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
  start = as.Date("2000-01-01"),
  end = as.Date("2002-01-01"),
  quote = "Close",
  retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
```

```

        multi_day = TRUE,
        compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
nine_eleven_car_param <- get_prices_from_tickers(tickers,
                                                start = as.Date("2000-01-01"),
                                                end = as.Date("2002-01-01"),
                                                quote = "Close",
                                                retclass = "zoo") %>%

  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  car_parametric_tests(car_start = as.Date("2001-09-11"),
                      car_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
nine_eleven_car_param <- car_parametric_tests(
  list_of_returns = securities_returns,
  car_start = as.Date("2001-09-11"),
  car_end = as.Date("2001-09-28")
)

```

corrado_sign_test *Corrado's sign test (1992).*

Description

An event study nonparametric test described in Corrado and Zivney 1992.

Usage

```
corrado_sign_test(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

Performs a nonparametric test for the event study, which is described in Corrado and Zivney 1992. This test is similar to procedure, described in Brown and Warner 1985 (t-ratio), but instead of using abnormal returns, the test uses $G_{i,t} = \text{sign}(A_{i,t} - \text{median}(A_i))$. `sign` and `median` are ones, which have the same definition as R functions. For this test the estimation period and the event period must not overlap, otherwise an error will be thrown. The sign test procedure avoids the misspecification of tests, which assumes symmetry around zero of abnormal returns (the median equals to zero). For a single day the performance of this test is proven to be better than classical Brown and Warner's test (without event-induced variance). This test is dominated by rank test. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

Corrado C.J., Zivney T.L. *The Specification and Power of the Sign Test in Event Study Hypothesis Tests Using Daily Stock Returns*. *Journal of Financial and Quantitative Analysis*, 27(3):465-478, 1992.

See Also

[nonparametric_tests](#), [sign_test](#), [generalized_sign_test](#), [rank_test](#), [modified_rank_test](#), and [wilcoxon_test](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
```

```

        estimation_method = "ols",
        estimation_start = as.Date("2001-03-26"),
        estimation_end = as.Date("2001-09-10")) %>%
corrado_sign_test(event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
corrado_sign_test(list_of_returns = securities_returns,
                  event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

```

generalized_sign_test *An event study binomial sign test.*

Description

A binomial sign test which determines whether the frequency of positive abnormal returns in the event period is significantly different from the frequency in the estimation period.

Usage

```
generalized_sign_test(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

This test is application of the binomial test to the event study, which indicates whether the cross-sectional frequency of positive abnormal returns is significantly different from the expected. This test is stable to outliers, in other words allows for checking if the result is driven by few companies with extremely large abnormal performance. For this test the estimation period and the event period must not overlap, otherwise an error will be thrown. This test uses an estimate from the estimation period instead of using naive value of expected frequency 0.5. The test statistic is assumed to have a normal distribution. Typically the test is used together with parametric tests. The test is well-specified for the case, when cross-sectional abnormal returns are not symmetric. Also this procedure is less sensitive to extreme returns than the rank test. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).


```
event_end = as.Date("2001-09-28"))
```

```
get_prices_from_tickers
```

Get daily prices of securities.

Description

Returns daily Open or Close prices between start and end date for given tickers.

Usage

```
get_prices_from_tickers(..., start, end, quote = c("Open", "Close"),
  retclass = c("list", "zoo", "data.frame"))
```

Arguments

<code>...</code>	character vectors indicating tickers (should be valid in Yahoo Finance).
<code>start</code>	an object of Date class specifying the first date of the observed time period.
<code>end</code>	an object of Date class specifying the last date of the observed time period.
<code>quote</code>	a character indicating the type of the price: "Open" (default) or "Close".
<code>retclass</code>	a character specifying the return class: "list" (default), "zoo" or "data.frame".

Details

This function uses the function `get.hist.quote` from the `tseries` package. The provider is set automatically to Yahoo Finance. The function returns the data in different class-containers: list of zoo's, zoo, or data.frame.

Value

Prices of securities as "list", "zoo", or "data.frame".

See Also

[get.hist.quote](#)

Examples

```
## Download historical prices of nine European insurance companies'
## stocks:
## Not run:
library("magrittr")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
  "MUV2.DE", "RSA.L", "TOP.CO")
prices <- tickers %>%
```

```

get_prices_from_tickers(start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo")

## End(Not run)
## The result of the above code is stored in:
data(prices)

## Download historical prices of ESTX50 EUR P index:
## Not run:
prices_indx <- get_prices_from_tickers("^STOXX50E",
                                       start = as.Date("2000-01-01"),
                                       end = as.Date("2002-01-01"),
                                       quote = "Close",
                                       retclass = "zoo")

## End(Not run)
## The result of the above code is stored in:
data(prices_indx)

```

get_rates_from_prices *Calculate rates of return for given prices.*

Description

get_rates_from_prices is used for computing rates of return from prices for different classes.

Usage

```
get_rates_from_prices(prices, quote = c("Open", "Close"), multi_day = TRUE,
                     compounding = c("discrete", "continuous"))
```

Arguments

prices	an object containing prices of securities. Three classes are allowed: list, data.frame, and zoo.
quote	a character vector specifying the type of the quote: "Open" (default) or "Close".
multi_day	logical, is a rate of return between more than 1 day is allowed?
compounding	a character vector defining the type of compounding: "continuous" (default) or "discrete".

Details

This is a generic function, dispatched for such classes as list, data.frame, and zoo that represent prices.

The calculation is made in C++ (Rcpp) in favor of speed.

If prices is a data frame, than the first column should be of the class Date and contain ordered dates of prices.

The correspondence between dates and values of the rates depends on the quote, which can be either Open or Close. If the quote is Open, than the value of rate belongs to the former date. Otherwise, to the latter one. This is also applied for the algorithm, if multiday is allowed: the value of the rate of return is assigned to the latter day in case of Close price, and to the former day in in case of Open quote.

The multi_day parameter specifies how to handle missing values and weekends. If the value is TRUE, the function ignores missing values and the rates are calculated between non-missing prices. If it is FALSE, then only one-day period rates of return are computed (between two consecutive calendar dates).

The function uses either continuous (by default) or discrete (periodic) compounding.

Value

Rates of returns of the same class as prices.

Examples

```
## Download historical prices of nine European insurance companies'
## stocks and estimate rates of returns form prices:
## Not run:
library("magrittr")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
rates <- tickers %>%
  get_prices_from_tickers(start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous")

## End(Not run)
## The result of the above code is stored in:
data(rates)

## Download historical prices of ESTX50 EUR P index and estimate rates of
## returns from prices:
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                    start = as.Date("2000-01-01"),
                                    end = as.Date("2002-01-01"),
                                    quote = "Close",
                                    retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous")
```

```
## End(Not run)
## The result of the above code is stored in:
data(rates_indx)
```

lamb	<i>Lamb's parametric test (1995).</i>
------	---------------------------------------

Description

An event study parametric test described in Lamb 1995.

Usage

```
lamb(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

Performs a parametric test for the event study, which is described in Lamb 1995. The author refers to Warner and Brown 1985 and Henderson 1990. However, this test was not observed in neither papers. The test statistics are very close to the statistics produced by `brown_warner_1985` and typically has the same significance. The test examines the hypothesis whether the theoretical cross-sectional expected value for a given day is equal to zero. It calculates statistics even if event window and estimation period are overlapped (intersect). The critical values are standard normal. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

Lamb R.P. *An Exposure-Based Analysis of Property-Liability Insurer Stock Values around Hurricane Andrew*. Journal of Risk and Insurance, 62(1):111-123, 1995.

See Also

[parametric_tests](#), [brown_warner_1980](#), [brown_warner_1985](#), [t_test](#), [patell](#) and [boehmer](#).

Examples

```

## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  lamb(event_start = as.Date("2001-09-11"),
       event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
lamb(list_of_returns = securities_returns,
     event_start = as.Date("2001-09-11"),
     event_end = as.Date("2001-09-28"))

```

modified_rank_test *An event study modified rank test.*

Description

The test is the modification of the original rank test, proposed by Corrado 1989. This test is adapted to missing values in abnormal returns.

Usage

```
modified_rank_test(list_of_returns, event_start, event_end)
```


Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

In addition to the original rank test, the procedure divides corresponding ranks by the number of nonmissing returns plus one for each security. This leads to order statistics with uniform distribution. In limit overall statistics under a null hypothesis is approximately normally distributed. For this test the estimation period and the event period must not overlap, otherwise an error will be thrown. The test is well-specified for the case, when cross-sectional abnormal returns are not symmetric. The test is stable to variance increase during the event window. This test is more sensitive to extreme values than the sign test. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

- Corrado C.J., Zivney T.L. *The Specification and Power of the Sign Test in Event Study Hypothesis Tests Using Daily Stock Returns*. Journal of Financial and Quantitative Analysis, 27(3):465-478, 1992.
- Kolari J.W., Pynnonen S. *Event Study Testing with Cross-sectional Correlation of Abnormal Returns*. The Review of Financial Studies, 23(11):3996-4025, 2010.

See Also

[nonparametric_tests](#), [sign_test](#), [generalized_sign_test](#), [corrado_sign_test](#), [rank_test](#), and [wilcoxon_test](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
```

```

get_prices_from_tickers(tickers,
                        start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous") %>%
apply_market_model(regressor = rates_indx,
                   same_regressor_for_all = TRUE,
                   market_model = "sim",
                   estimation_method = "ols",
                   estimation_start = as.Date("2001-03-26"),
                   estimation_end = as.Date("2001-09-10")) %>%
modified_rank_test(event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
modified_rank_test(list_of_returns = securities_returns,
                  event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

```

nonparametric_tests *Returns the result of given event study nonparametric tests.*

Description

Performs main nonparametric tests for each date in the event window and returns a data frame of their statistics and significance.

Usage

```
nonparametric_tests(list_of_returns, event_start, event_end, all = TRUE,
                    tests)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.
all	a logical vector of length one indicating whether all tests should be performed. The default value is TRUE.
tests	a list of tests' functions among sign_test , generalized_sign_test , corrado_sign_test , rank_test , modified_rank_test , and wilcoxon_test .


```

                                end = as.Date("2002-01-01"),
                                quote = "Close",
                                retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                        multi_day = TRUE,
                        compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
nine_eleven_nparam <- get_prices_from_tickers(tickers,
                                              start = as.Date("2000-01-01"),
                                              end = as.Date("2002-01-01"),
                                              quote = "Close",
                                              retclass = "zoo") %>%

  get_rates_from_prices(quote = "Close",
                        multi_day = TRUE,
                        compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  nonparametric_tests(event_start = as.Date("2001-09-11"),
                      event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
nine_eleven_nparam <- nonparametric_tests(list_of_returns = securities_returns,
                                          event_start = as.Date("2001-09-11"),
                                          event_end = as.Date("2001-09-28"))

```

parametric_tests

Returns the result of given event study parametric tests.

Description

Performs main parametric tests for each date in the event window and returns a data frame of their statistics and significance.

Usage

```
parametric_tests(list_of_returns, event_start, event_end, all = TRUE, tests)
```

Arguments

list_of_returns

a list of objects of S3 class returns, each element of which is treated as a security.

event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.
all	a logical vector of length one indicating whether all tests should be performed. The default value is TRUE.
tests	a list of tests' functions among brown_warner_1980, brown_warner_1985, t_test, patell, boehmer, and lamb.

Details

parametric_tests performs given tests among brown_warner_1980, brown_warner_1985, t_test, patell, boehmer, lamb and merge result to a single data frame. If all = TRUE (the default value), the function ignores the value of tests.

Value

A data frame containing all statistics and significances of tests.

References

- Brown S.J., Warner J.B. *Measuring security price performance*. Journal of Financial Economics, 8:205-258, 1980.
- Brown S.J., Warner J.B. *Using Daily Stock Returns, The Case of Event Studies*. Journal of Financial Economics, 14:3-31, 1985.
- Boehmer E., Musumeci J., Poulsen A.B. *Event-study methodology under conditions of event-induced variance*. Journal of Financial Economics, 30(2):253-272, 1991.
- Patell J.M. *Corporate forecasts of earnings per share and stock price behavior: empirical tests*. Journal of Accounting Research, 14(2):246- 276, 1976.
- Lamb R.P. *An Exposure-Based Analysis of Property-Liability Insurer Stock Values around Hurricane Andrew*. Journal of Risk and Insurance, 62(1):111-123, 1995.

See Also

[brown_warner_1980](#), [brown_warner_1985](#), [t_test](#), [patell](#), [boehmer](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_idx <- get_prices_from_tickers("^STOXX50E",
                                   start = as.Date("2000-01-01"),
                                   end = as.Date("2002-01-01"),
                                   quote = "Close",
                                   retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
```

```

nine_eleven_param <- get_prices_from_tickers(tickers,
                                             start = as.Date("2000-01-01"),
                                             end = as.Date("2002-01-01"),
                                             quote = "Close",
                                             retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  parametric_tests(event_start = as.Date("2001-09-11"),
                  event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
nine_eleven_param <- parametric_tests(list_of_returns = securities_returns,
                                     event_start = as.Date("2001-09-11"),
                                     event_end = as.Date("2001-09-28"))

```

patell

Patell's parametric test (1976).

Description

An event study parametric test described in Patell 1976.

Usage

```
patell(list_of_returns, event_start, event_end)
```

Arguments

<code>list_of_returns</code>	a list of objects of S3 class returns, each element of which is treated as a security.
<code>event_start</code>	an object of Date class giving the first date of the event period.
<code>event_end</code>	an object of Date class giving the last date of the event period.

Details

Performs a parametric test for event study, which is described in Patell 1976, which is called standardized-residuals method in Boehmer 1991. Test's assumptions are a cross-sectional independence and an insignificance of an event-induced variance. The standardization smooths the effect of the event-induced variance comparing to Brown and Warner tests. Also standardization incorporates the situation, when a highly volatile security dominates the test. The test examines the hypothesis whether the theoretical cross-sectional expected value for a given day is equal to zero. It calculates statistics even if event window and estimation period are overlapped (intersect). The critical values are standard normal. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

- Patell J.M. *Corporate forecasts of earnings per share and stock price behavior: empirical tests*. Journal of Accounting Research, 14(2):246- 276, 1976.
- Boehmer E., Musumeci J., Poulsen A.B. *Event-study methodology under conditions of event-induced variance*. Journal of Financial Economics, 30(2):253-272, 1991.

See Also

[parametric_tests](#), [brown_warner_1980](#), [brown_warner_1985](#), [t_test](#), and [boehmer](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
```

```

        market_model = "sim",
        estimation_method = "ols",
        estimation_start = as.Date("2001-03-26"),
        estimation_end = as.Date("2001-09-10")) %>%
patell(event_start = as.Date("2001-09-11"),
       event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
patell(list_of_returns = securities_returns,
       event_start = as.Date("2001-09-11"),
       event_end = as.Date("2001-09-28"))

```

prices	<i>Stock prices of nine major European insurance companies from 2000-01-03 to 2002-01-01</i>
--------	--

Description

A zoo object of nine columns containing daily Close stock prices of nine major European insurance companies from 2000-01-03 to 2002-01-01. See examples of [get_prices_from_tickers](#) for the dataset generation.

Usage

```
prices
```

Format

A zoo object of nine columns:

- ALV.DE
- CS.PA
- ELE.PA
- G.MI
- HNR1.HA
- HSX.L
- MUV2.DE
- RSA.L
- TOP.CO

prices_indx	<i>Prices of of ESTX50 EUR P index from 2000-01-03 to 2001-12-31</i>
-------------	--

Description

A zoo object containing daily prices of ESTX50 EUR P index from 2000-01-03 to 2001-12-31. See examples of [get_prices_from_tickers](#) for the dataset generation.

Usage

```
prices_indx
```

Format

A zoo object.

rank_test	<i>An event study rank test.</i>
-----------	----------------------------------

Description

An original rank test applied to an event study, which is based on Wilcoxon (1945) rank test.

Usage

```
rank_test(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

This procedure uses ranks of abnormal returns to examine significance of each day in the event window. In order to get ranks of corresponding abnormal returns, the procedure uses regular R function [rank](#) with parameter `ties.method = "average"` and `na.last = "keep"`. For this test the estimation period and the event period must not overlap, otherwise an error will be thrown. The test statistic is assumed to have a normal distribution (as an approximation). The test is well-specified for the case, when cross-sectional abnormal returns are not symmetric. The test is stable to variance increase during event window. This test is more sensitive to extreme values than sign test. For data with missing data see the [modified_rank_test](#). The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

- Corrado C.J. *A Nonparametric Test for Abnormal Security-Price Performance in Event Studies*. Journal of Financial Economics 23:385-395, 1989.
- Cowan A.R. *Nonparametric Event Study Tests*. Review of Quantitative Finance and Accounting, 2:343-358, 1992.
- Campbell C.J., Wasley C.E. *Measuring Security Price Performance Using Daily NASDAQ Returns*. Journal of Financial Economics 33:73-92, 1993.
- Savickas R. *Event-Induced Volatility and Tests for Abnormal Performance*. The Journal of Financial Research, 26(2):156-178, 2003.

See Also

[nonparametric_tests](#), [sign_test](#), [generalized_sign_test](#), [corrado_sign_test](#), [modified_rank_test](#), and [wilcoxon_test](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  rank_test(event_start = as.Date("2001-09-11"),
           event_end = as.Date("2001-09-28"))
```

```
## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
rank_test(list_of_returns = securities_returns,
          event_start = as.Date("2001-09-11"),
          event_end = as.Date("2001-09-28"))
```

rates	<i>Rates of returns of nine major European insurance companies from 2000-01-04 to 2002-01-01</i>
-------	--

Description

A zoo object of nine columns containing daily rates of returns of nine major European insurance companies from 2000-01-04 to 2002-01-01. See examples of [get_rates_from_prices](#) for the dataset generation.

Usage

```
rates
```

Format

A zoo object of nine columns:

- ALV.DE
- CS.PA
- ELE.PA
- G.MI
- HNR1.HA
- HSX.L
- MUV2.DE
- RSA.L
- TOP.CO

rates_indx	<i>Rates of returns of ESTX50 EUR P index from 2000-01-04 to 2001-12-31</i>
------------	---

Description

A zoo object containing daily rates of returns of ESTX50 EUR P index from 2000-01-04 to 2001-12-31. See examples of [get_rates_from_prices](#) for the dataset generation.

Usage

```
rates_indx
```

Format

A zoo object.

returns	<i>Constructor of an object of S3 class returns.</i>
---------	--

Description

Constructs an object of S3 class returns.

Usage

```
returns(rates, regressor, market_model = c("mean_adj", "mrkt_adj", "sim"),
        estimation_method = c("ols"), estimation_start, estimation_end)
```

Arguments

rates	an object of class either zoo or data.frame giving observed rates of returns of security.
regressor	an object of the same class as rates representing rates of returns of the market model, if needed.
market_model	a character indicating the market model among mean_adj, mrkt_adj, and sim.
estimation_method	a character specifying an estimation method for sim model.
estimation_start	an object of Date class giving the first date of the estimation period.
estimation_end	an object of Date class giving the last date of the estimation period.


```

                                quote = "Close",
                                retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous") %>%
returns(market_model = "mean_adj",
        estimation_start = as.Date("2001-03-26"),
        estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates)
single_return <- returns(rates[, "ALV.DE", drop = FALSE],
                        market_model = "mean_adj",
                        estimation_start = as.Date("2001-03-26"),
                        estimation_end = as.Date("2001-09-10"))

## 2. Market-adjusted-returns model
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous")

single_return <- get_prices_from_tickers("ALV.DE",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous") %>%
returns(regressor = rates_indx,
        market_model = "mrkt_adj",
        estimation_start = as.Date("2001-03-26"),
        estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates, rates_indx)
single_return <- returns(rates = rates[, "ALV.DE", drop = FALSE],
                        regressor = rates_indx,
                        market_model = "mrkt_adj",
                        estimation_method = "ols",
                        estimation_start = as.Date("2001-03-26"),
                        estimation_end = as.Date("2001-09-10"))

## 3. Single-index market model

```

```

## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")

single_return <- get_prices_from_tickers("ALV.DE",
                                         start = as.Date("2000-01-01"),
                                         end = as.Date("2002-01-01"),
                                         quote = "Close",
                                         retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  returns(regressor = rates_indx,
          market_model = "sim",
          estimation_method = "ols",
          estimation_start = as.Date("2001-03-26"),
          estimation_end = as.Date("2001-09-10"))

## End(Not run)
## The result of the code above is equivalent to:
data(rates, rates_indx)
single_return <- returns(rates = rates[, "ALV.DE", drop = FALSE],
                       regressor = rates_indx,
                       market_model = "sim",
                       estimation_method = "ols",
                       estimation_start = as.Date("2001-03-26"),
                       estimation_end = as.Date("2001-09-10"))

```

securities_returns	<i>Returns of nine major insurance companies from 2000-01-04 to 2001-12-29</i>
--------------------	--

Description

A list of length nine, elements of which are objects of the class `returns`. The list contains all necessary returns of nine major insurance companies from 2000-01-04 to 2001-12-29. See examples of [apply_market_model](#) for the dataset generation.

Usage

```
securities_returns
```

Format

A list of nine zoo elements:

- ALV.DE
- CS.PA
- ELE.PA
- G.MI
- HNR1.HA
- HSX.L
- MUV2.DE
- RSA.L
- TOP.CO

sign_test

An event study simple binomial sign test.

Description

A binomial sign test which determines whether the frequency of positive abnormal returns in the event period is significantly different from one-half.

Usage

```
sign_test(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

This test is application of the simple binomial test to the event study, which indicates whether the cross-sectional frequency of positive abnormal returns is significantly different from 0.5. This test is stable to outliers, in other words allows for checking if the result is driven by few companies with extremely large abnormal performance. For this test the estimation period and the event period must not overlap, otherwise an error will be thrown. The test statistic is assumed to have a normal distribution in approximation under a null hypothesis, if the number of securities is large. Typically the test is used together with parametric tests. The test is well-specified for the case, when cross-sectional abnormal returns are not symmetric. Also this procedure is less sensitive to extreme returns than the rank test. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

Boehmer E., Musumeci J., Poulsen A.B. *Event-study methodology under conditions of event-induced variance*. Journal of Financial Economics, 30(2):253-272, 1991.

See Also

[nonparametric_tests](#), [generalized_sign_test](#), [corrado_sign_test](#), [rank_test](#), [modified_rank_test](#), and [wilcoxon_test](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  sign_test(event_start = as.Date("2001-09-11"),
           event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
sign_test(list_of_returns = securities_returns,
         event_start = as.Date("2001-09-11"),
         event_end = as.Date("2001-09-28"))
```

t_test	<i>An event study t-test.</i>
--------	-------------------------------

Description

A classical t-test that examines each date in the event window.

Usage

```
t_test(list_of_returns, event_start, event_end)
```

Arguments

list_of_returns	a list of objects of S3 class returns, each element of which is treated as a security.
event_start	an object of Date class giving the first date of the event period.
event_end	an object of Date class giving the last date of the event period.

Details

Performs a t-test for the event study. The procedure of this test is described in Boehmer et al. 1991, sometimes is called a cross-sectional test. Assumes independence of securities, however is stable to event-induced variance. This test examines the equality of the cross-sectional expected value to zero. The standard deviation, which is used in this test, is simply a cross-sectional standard deviation for a given day in the event window. It calculates statistics even if event window and estimation period are overlapped (intersect). The critical values are Student's t-distributed (no approximation in limit). The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

Warning

This test strongly requires cross-sectional independence and sensitive to the size of the sample.

References

Boehmer E., Musumeci J., Poulsen A.B. *Event-study methodology under conditions of event-induced variance*. Journal of Financial Economics, 30(2):253-272, 1991.

See Also

[parametric_tests](#), [brown_warner_1980](#), [brown_warner_1985](#), [patell](#), [boehmer](#), and [lamb](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                       start = as.Date("2000-01-01"),
                       end = as.Date("2002-01-01"),
                       quote = "Close",
                       retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
                       multi_day = TRUE,
                       compounding = "continuous") %>%
  apply_market_model(regressor = rates_indx,
                    same_regressor_for_all = TRUE,
                    market_model = "sim",
                    estimation_method = "ols",
                    estimation_start = as.Date("2001-03-26"),
                    estimation_end = as.Date("2001-09-10")) %>%
  t_test(event_start = as.Date("2001-09-11"),
        event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
t_test(list_of_returns = securities_returns,
      event_start = as.Date("2001-09-11"),
      event_end = as.Date("2001-09-28"))
```

 wilcoxon_test

An event study Wilcoxon signed rank test.

Description

Performs Wilcoxon test on the event period for abnormal returns (abnormal returns are considered as differences).

Usage

```
wilcoxon_test(list_of_returns, event_start, event_end)
```

Arguments

<code>list_of_returns</code>	a list of objects of S3 class <code>returns</code> , each element of which is treated as a security.
<code>event_start</code>	an object of Date class giving the first date of the event period.
<code>event_end</code>	an object of Date class giving the last date of the event period.

Details

The estimation periods can overlap with event windows, because the procedure takes into account only abnormal returns from the event window. The test has the same algorithm as built-in R `wilcox.test`. The critical values are exact values, which are obtained from `qsignrank`. The algorithm is the following: for each day in event window the cross-sectional abnormal returns treated as sample of differences. Firstly the absolute value of these differences are computed, and corresponding ranks of non-zero values are calculated. The test statistic is the sum of ranks, corresponding to positive abnormal returns. The significance levels of α are 0.1, 0.05, and 0.01 (marked respectively by *, **, and ***).

Value

A data frame of test's statistics and significances.

References

- Wilcoxon F. *Individual Comparisons by Ranking Methods*. Biometrics Bulletin 1(6):80-83, 1945.
- Kolari J.W., Pynnonen S. *Event Study Testing with Cross-sectional Correlation of Abnormal Returns*. The Review of Financial Studies, 23(11):3996-4025, 2010.
- Lehmann E.L. *Nonparametrics: Statistical Methods Based on Ranks*. San Francisco: Holden-Day, 1975.
- Hollander M., Wolfe D.A. *Nonparametric Statistical Methods*. New York: John Wiley & Sons, 1973.

See Also

[nonparametric_tests](#), [sign_test](#), [generalized_sign_test](#), [corrado_sign_test](#), [rank_test](#), and [modified_rank_test](#).

Examples

```
## Not run:
library("magrittr")
rates_indx <- get_prices_from_tickers("^STOXX50E",
                                     start = as.Date("2000-01-01"),
                                     end = as.Date("2002-01-01"),
                                     quote = "Close",
                                     retclass = "zoo") %>%
  get_rates_from_prices(quote = "Close",
```

```
        multi_day = TRUE,
        compounding = "continuous")
tickers <- c("ALV.DE", "CS.PA", "ELE.PA", "G.MI", "HNR1.HA", "HSX.L",
            "MUV2.DE", "RSA.L", "TOP.CO")
get_prices_from_tickers(tickers,
                        start = as.Date("2000-01-01"),
                        end = as.Date("2002-01-01"),
                        quote = "Close",
                        retclass = "zoo") %>%
get_rates_from_prices(quote = "Close",
                      multi_day = TRUE,
                      compounding = "continuous") %>%
apply_market_model(regressor = rates_indx,
                   same_regressor_for_all = TRUE,
                   market_model = "sim",
                   estimation_method = "ols",
                   estimation_start = as.Date("2001-03-26"),
                   estimation_end = as.Date("2001-09-10")) %>%
wilcoxon_test(event_start = as.Date("2001-09-11"),
              event_end = as.Date("2001-09-28"))

## End(Not run)
## The result of the code above is equivalent to:
data(securities_returns)
wilcoxon_test(list_of_returns = securities_returns,
              event_start = as.Date("2001-09-11"),
              event_end = as.Date("2001-09-28"))
```

Index

*Topic **datasets**

- prices, [32](#)
 - prices_indx, [33](#)
 - rates, [35](#)
 - rates_indx, [36](#)
 - securities_returns, [39](#)
- apply_market_model, [3](#), [37](#), [39](#)
- boehmer, [6](#), [8](#), [10](#), [23](#), [29](#), [31](#), [42](#)
- brown_warner_1980, [7](#), [7](#), [10](#), [23](#), [29](#), [31](#), [42](#)
- brown_warner_1985, [7](#), [8](#), [9](#), [23](#), [29](#), [31](#), [42](#)
- car_brown_warner_1985, [11](#), [13](#), [15](#)
- car_lamb, [11](#), [12](#), [13](#), [15](#)
- car_parametric_tests, [12](#), [13](#), [14](#)
- corrado_sign_test, [16](#), [19](#), [25–27](#), [34](#), [41](#), [44](#)
- generalized_sign_test, [17](#), [18](#), [25–27](#), [34](#),
[41](#), [44](#)
- get.hist.quote, [20](#)
- get_prices_from_tickers, [20](#), [32](#), [33](#)
- get_rates_from_prices, [21](#), [35](#), [36](#)
- lamb, [7](#), [8](#), [10](#), [23](#), [29](#), [31](#), [42](#)
- modified_rank_test, [17](#), [19](#), [24](#), [26](#), [27](#), [33](#),
[34](#), [41](#), [44](#)
- nonparametric_tests, [17](#), [19](#), [25](#), [26](#), [34](#), [41](#),
[44](#)
- parametric_tests, [7](#), [8](#), [10](#), [23](#), [28](#), [31](#), [42](#)
- patell, [7](#), [8](#), [10](#), [23](#), [29](#), [30](#), [42](#)
- prices, [32](#)
- prices_indx, [33](#)
- qsignrank, [44](#)
- rank, [33](#)
- rank_test, [17](#), [19](#), [25–27](#), [33](#), [41](#), [44](#)
- rates, [35](#)
- rates_indx, [36](#)
- returns, [4](#), [36](#)
- securities_returns, [39](#)
- sign_test, [17](#), [19](#), [25–27](#), [34](#), [40](#), [44](#)
- t_test, [7](#), [8](#), [10](#), [23](#), [29](#), [31](#), [42](#)
- wilcox.test, [44](#)
- wilcoxon_test, [17](#), [19](#), [25–27](#), [34](#), [41](#), [43](#)