

Package ‘tinytex’

April 16, 2018

Type Package

Title Helper Functions to Install and Maintain 'TeX Live', and Compile 'LaTeX' Documents

Version 0.5

Description Helper functions to install and maintain the 'LaTeX' distribution named 'TinyTeX' (<<https://yihui.name/tinytex/>>), a lightweight, cross-platform, portable, and easy-to-maintain version of 'TeX Live'. This package also contains helper functions to compile 'LaTeX' documents, and install missing 'LaTeX' packages automatically.

Suggests testit

License MIT + file LICENSE

URL <https://github.com/yihui/tinytex>

BugReports <https://github.com/yihui/tinytex/issues>

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

NeedsCompilation no

Author Yihui Xie [aut, cre, cph] (<<https://orcid.org/0000-0003-0645-5666>>),
RStudio, Inc. [cph],
Fernando Cagua [ctb]

Maintainer Yihui Xie <xie@yihui.name>

Repository CRAN

Date/Publication 2018-04-16 19:53:03 UTC

R topics documented:

install_tinytex	2
latexmk	2
parse_packages	4
r_texmf	5
tlmgr	5
tl_sizes	7

install_tinytex	<i>Install/Uninstall TinyTeX</i>
-----------------	----------------------------------

Description

The function `install_tinytex()` downloads the installation script from <https://github.com/yihui/tinytex> according to the platform (Unix or Windows), and executes it to install TinyTeX (a custom LaTeX distribution based on TeX Live). The function `uninstall_tinytex()` removes TinyTeX.

Usage

```
install_tinytex(force = FALSE, dir, repository = "ctan")
```

```
uninstall_tinytex(force = FALSE, dir = texlive_root())
```

Arguments

<code>force</code>	Whether to force to install (override) or uninstall TinyTeX.
<code>dir</code>	The directory to install or uninstall TinyTeX (should not exist unless <code>force = TRUE</code>).
<code>repository</code>	The CTAN repository to be used. By default, a fast mirror is automatically chosen. You can manually set one if the automatic mirror is not really fast enough, e.g., if you are in China, you may consider <code>'http://mirrors.tuna.tsinghua.edu.cn/CTAN/systems/</code>

References

See the TinyTeX documentation (<https://yihui.name/tinytex/>) for the default installation directories on different platforms.

latexmk	<i>Compile a LaTeX document to PDF</i>
---------	--

Description

The function `latexmk()` emulates the system command `latexmk` (<https://ctan.org/pkg/latexmk>) to compile a LaTeX document to PDF. The functions `pdflatex()`, `xelatex()`, and `lualatex()` are wrappers of `latexmk(engine = , emulation = TRUE)`.

Usage

```
latexmk(file, engine = c("pdflatex", "xelatex", "lualatex"), bib_engine = c("bibtex",
  "biber"), engine_args = NULL, emulation = TRUE, max_times = 10,
  install_packages = emulation && tlmgr_available(), pdf_file = gsub("tex$",
  "pdf", file), clean = TRUE)
```

```
pdflatex(...)
```

```
xelatex(...)
```

```
lualatex(...)
```

Arguments

<code>file</code>	A LaTeX file path.
<code>engine</code>	A LaTeX engine (can be set in the global option <code>tinytex.engine</code> , e.g., <code>options(tinytex.engine = 'xelatex')</code>).
<code>bib_engine</code>	A bibliography engine (can be set in the global option <code>tinytex.bib_engine</code>).
<code>engine_args</code>	Command-line arguments to be passed to engine (can be set in the global option <code>tinytex.engine_args</code> , e.g., <code>options(tinytex.engine_args = '-shell-escape')</code>).
<code>emulation</code>	Whether to emulate the executable <code>latexmk</code> using R.
<code>max_times</code>	The maximum number of times to rerun the LaTeX engine when using emulation. You can set the global option <code>tinytex.compile.max_times</code> , e.g., <code>options(tinytex.compile.max_times = 3)</code> .
<code>install_packages</code>	Whether to automatically install missing LaTeX packages found by <code>parse_packages()</code> from the LaTeX log. This argument is only for the emulation mode and TeX Live.
<code>pdf_file</code>	Path to the PDF output file. By default, it is under the same directory as the input file and also has the same base name.
<code>clean</code>	Whether to clean up auxiliary files after compilation (can be set in the global option <code>tinytex.clean</code> , which defaults to TRUE).
<code>...</code>	Arguments to be passed to <code>latexmk()</code> (other than engine and emulation).

Details

The `latexmk` emulation works like this: run the LaTeX engine once (e.g., `pdflatex`), run `makeindex` to make the index if necessary (the `*.idx` file exists), run the bibliography engine `bibtex` or `biber` to make the bibliography if necessary (the `*.aux` or `*.bcf` file exists), and finally run the LaTeX engine a number of times (the maximum is 10 by default) to resolve all cross-references.

If `emulation = FALSE`, you need to make sure the executable `latexmk` is available in your system, otherwise `latexmk()` will fall back to `emulation = TRUE`. You can set the global option `options(tinytex.latexmk.emulation = FALSE)` to always avoid emulation (i.e., always use the executable `latexmk`).

Value

A character string of the path of the PDF output file (i.e., the value of the `pdf_file` argument).

parse_packages	<i>Find missing LaTeX packages from a LaTeX log file</i>
----------------	--

Description

Analyze the error messages in a LaTeX log file to figure out the names of missing LaTeX packages that caused the errors. These packages can be installed via `tlmgr_install()`. Searching for missing packages is based on `tlmgr_search()`.

Usage

```
parse_packages(log, text = readLines(log), files = detect_files(text),
              quiet = rep(FALSE, 3))
```

Arguments

log	Path to the LaTeX log file (typically named <code>*.log</code>).
text	A character vector of the error log (read from the file provided by the log argument by default).
files	A character vector of names of the missing files (automatically detected from the log by default).
quiet	Whether to suppress messages when finding packages. It should be a logical vector of length 3: the first element indicates whether to suppress the message when no missing LaTeX packages could be detected from the log, the second element indicate whether to suppress the message when searching for packages via <code>tlmgr_search()</code> , and the third element indicates whether to warn if no packages could be found via <code>tlmgr_search()</code> .

Value

A character vector of LaTeX package names.

r_texmf	<i>Add/remove R's texmf tree to/from TeX Live</i>
---------	---

Description

R ships a custom texmf tree containing a few LaTeX style and class files, which are required when compiling R packages manuals ('Rd.sty') or Sweave documents ('Sweave.sty'). This tree can be found under the directory `file.path(R.home('share'), 'texmf')`. This function can be used to add/remove R's texmf tree to/from TeX Live via `tlmgr_conf('auxtrees')`.

Usage

```
r_texmf(action = c("add", "remove"))
```

Arguments

action	Add/remove R's texmf tree to/from TeX Live.
--------	---

References

See the **tlmgr** manual for detailed information about `tlmgr conf auxtrees`. Check out <https://tex.stackexchange.com/q/77720/9128> if you don't know what texmf means.

Examples

```
r_texmf("remove")
r_texmf("add")

# all files under R's texmf tree
list.files(file.path(R.home("share"), "texmf"), recursive = TRUE, full.names = TRUE)
```

tlmgr	<i>Run the TeX Live Manager</i>
-------	---------------------------------

Description

Execute the `tlmgr` command to search for LaTeX packages, install packages, update packages, and so on.

Usage

```

tlmgr(args = character(), usermode = FALSE, ..., .quiet = FALSE)

tlmgr_search(what, file = TRUE, all = FALSE, global = TRUE, word = FALSE, ...)

tlmgr_install(pkgs = character(), usermode = FALSE, path = !usermode && os != "windows")

tlmgr_remove(pkgs = character(), usermode = FALSE)

tlmgr_update(all = TRUE, self = TRUE, more_args = character(), usermode = FALSE,
             run_fmtutil = TRUE)

tlmgr_path(action = c("add", "remove"))

tlmgr_conf(more_args = character())

```

Arguments

args	A character vector of arguments to be passed to the command <code>tlmgr</code> .
usermode	(For expert users only) Whether to use TeX Live's user mode . If TRUE, you must have run <code>tlmgr('init-usertree')</code> once before. This option allows you to manage a user-level texmf tree, e.g., install a LaTeX package to your home directory instead of the system directory, to which you do not have write permission. This option should not be needed on personal computers, and has some limitations, so please read the tlmgr manual very carefully before using it.
...	Additional arguments passed to <code>system2()</code> (e.g., <code>stdout = TRUE</code> to capture stdout).
.quiet	Whether to hide the actual command before executing it.
what	A search keyword as a (Perl) regular expression.
file	Whether to treat <code>what</code> as a filename (pattern).
all	For <code>tlmgr_search()</code> , whether to search in everything, including package names, descriptions, and filenames. For <code>tlmgr_update()</code> , whether to update all installed packages.
global	Whether to search the online TeX Live Database or locally.
word	Whether to restrict the search of package names and descriptions to match only full words.
pkgs	A character vector of LaTeX package names.
path	Whether to run <code>tlmgr_path('add')</code> after installing packages (<code>path = TRUE</code> is a conservative default: it is only necessary to do this after a binary package is installed, such as the metafont package, which contains the executable <code>mf</code> , but it does not hurt even if no binary packages were installed).
self	Whether to update the TeX Live Manager itself.
more_args	A character vector of more arguments to be passed to the command <code>tlmgr update</code> or <code>tlmgr conf</code> .

run_fmtutil	Whether to run <code>fmtutil-sys --all</code> to (re)create format and hyphenation files after updating tlmgr .
action	On Unix, add/remove symlinks of binaries to/from the system's PATH. On Windows, add/remove the path to the TeXLive binary directory to/from the system environment variable PATH.

Details

The `tlmgr()` function is a wrapper of `system2('tlmgr')`. All other `tlmgr_*` functions are based on `tlmgr` for specific tasks. Please consult the **tlmgr** manual for full details.

References

The **tlmgr** manual: <https://www.tug.org/texlive/doc/tlmgr.html>

Examples

```
# search for a package that contains titling.sty
tlmgr_search("titling.sty")

#' to match titling.sty exactly, add a slash before the keyword, e.g.
#' tlmgr_search('/titling.sty')

#' use a regular expression if you want to be more precise, e.g.
#' tlmgr_search('/titling\\.sty$')

# list all installed LaTeX packages
tlmgr(c("info", "--list", "--only-installed", "--data", "name"))
```

tl_sizes	<i>Sizes of LaTeX packages in TeX Live</i>
----------	--

Description

Use the command `tlmgr info --list --only-installed` to obtain the sizes of installed LaTeX packages.

Usage

```
tl_sizes(show_total = TRUE)
```

Arguments

`show_total` Whether to show the total size.

Value

A data frame of three columns: `package` is the package names, `size` is the sizes in bytes, and `size_h` is the human-readable version of sizes.

Index

`install_tinytex`, 2

`latexmk`, 2

`lualatex` (`latexmk`), 2

`parse_packages`, 3, 4

`pdflatex` (`latexmk`), 2

`r_texmf`, 5

`system2`, 6

`tl_sizes`, 7

`tlmgr`, 5

`tlmgr_conf`, 5

`tlmgr_conf` (`tlmgr`), 5

`tlmgr_install`, 4

`tlmgr_install` (`tlmgr`), 5

`tlmgr_path` (`tlmgr`), 5

`tlmgr_remove` (`tlmgr`), 5

`tlmgr_search`, 4

`tlmgr_search` (`tlmgr`), 5

`tlmgr_update` (`tlmgr`), 5

`uninstall_tinytex` (`install_tinytex`), 2

`xelatex` (`latexmk`), 2