

# Package ‘DJL’

April 17, 2018

**Type** Package

**Title** Distance Measure Based Judgment and Learning

**Version** 2.7

**Date** 2018-4-18

**Author** Dong-Joon Lim, PhD

**Depends** R (>= 3.4.0), car, lpSolveAPI

**Maintainer** Dong-Joon Lim <tgno3.com@gmail.com>

**Description** Implements various decision support tools related to the new product development. Subroutines include correlation reliability test, Mahalanobis distance measure for outlier detection, combinatorial search (all possible subset regression), non-parametric efficiency analysis measures: DDF (directional distance function), DEA (data envelopment analysis), HDF (hyperbolic distance function), SBM (slack-based measure), and SF (shortage function), benchmarking, risk analysis, technology adoption model, new product target setting, etc.

**License** GPL-2

**LazyData** true

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2018-04-17 15:21:40 UTC

## R topics documented:

dataset.airplane.2017 . . . . .	2
dataset.engine.2015 . . . . .	3
dataset.hev.2013 . . . . .	4
dm.ddf . . . . .	5
dm.dea . . . . .	6
dm.hdf . . . . .	8
dm.mahalanobis . . . . .	10
dm.sbm . . . . .	11
dm.sf . . . . .	13
ma.aps.reg . . . . .	15
map.corr . . . . .	16

map.soa.ddf . . . . .	17
map.soa.dea . . . . .	18
map.soa.hdf . . . . .	20
map.soa.sbm . . . . .	21
map.soa.sf . . . . .	23
roc.dea . . . . .	24
roc.hdf . . . . .	26
roc.malmquist . . . . .	28
roc.sf . . . . .	30
target.arrival.dea . . . . .	32
target.arrival.hdf . . . . .	34
target.arrival.sf . . . . .	35
target.spec.dea . . . . .	37
<b>Index</b>	<b>40</b>

---

dataset.airplane.2017 *Dataset of commercial airplanes from 1965 to 2017.*

---

## Description

Commercial airplanes from 1965 to 2017.

## Usage

```
data(dataset.airplane.2017)
```

## Columns

[,1] Name	Airplane name
[,2] EIS	Entry into service
[,3] Range	Maximum range at full payload in 1,000km
[,4] P. cap	Passenger capacity
[,5] PFE	Passenger fuel efficiency in passengers*km/L (log scale)
[,6] C. spd	Cruising speed in km/hr
[,7] M. spd	Maximum speed in km/hr

## Author(s)

Dong-Joon Lim, PhD

## Source

<http://www.airbus.com/aircraftfamilies>  
<http://www.boeing.com/commercial>

## References

Lim, Dong-Joon, and Timothy R. Anderson. Time series benchmarking analysis for new product scheduling: who are the competitors and how fast are they moving forward?. Advances in DEA Theory and Applications: with Examples in Forecasting Models. Wiley (*forthcoming*), 2016.

## Examples

```
# Load dataset
data(dataset.airplane.2017)
```

---

```
dataset.engine.2015
```

*Dataset of auto engines from MY2005 to MY2015.*

---

## Description

Auto engines from MY2005 to MY2015.

## Usage

```
data(dataset.engine.2015)
```

## Columns

[,1]	Name	Vehicle name
[,2]	MY	Model year
[,3]	Cylinder	The number of cylinder
[,4]	Displacement	Displacement in liter
[,5]	CO2	CO2 emission in gram/mile
[,6]	Power	Engine power in HP
[,7]	Torque	Engine torque in lb.ft
[,8]	Type	Engine system and fuel type

## Author(s)

Dong-Joon Lim, PhD

## Source

<http://www.fueleconomy.gov>  
<http://www.autoevolution.com>

## References

D.-J. Lim, Internal combustion engine race: naturally aspirated vs turbo/super-charged, *working paper* (2015).

**Examples**

```
# Load dataset
data(dataset.engine.2015)
```

---

dataset.hev.2013      *Dataset of hybrid electric vehicles from MY1997 to MY2013.*

---

**Description**

Hybrid electric vehicles from MY1997 to MY2013.

**Usage**

```
data(dataset.hev.2013)
```

**Columns**

[,1] Name	Vehicle name
[,2] MY	Model year
[,3] MSRP.2013	MSRP converted to 2013 value
[,4] Acc	Acceleration (0-100km) in km/h/s
[,5] MPG	MPG in mile/gallon
[,6] MPGe	MPG equivalence for PHEV in mile/gallon

**Author(s)**

Dong-Joon Lim, PhD

**Source**

<http://www.fueleconomy.gov>

**References**

Lim, Dong-Joon, et al. "Comparing technological advancement of hybrid electric vehicles (HEV) in different market segments." *Technological Forecasting and Social Change* 97 (2015): 140~153.

**Examples**

```
# Load dataset
data(dataset.hev.2013)
```

---

dm.ddf	<i>Distance measure using DDF</i>
--------	-----------------------------------

---

**Description**

Implements *Chambers'* directional distance function (non-radial & non-oriented measure).

**Usage**

```
dm.ddf(xdata, ydata, rts="crs", g=NULL,
       wd=NULL, se=FALSE, sg="ssm", date=NULL, cv="convex", o=NULL)
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
se	Implements super-efficiency model alike <i>Anderson &amp; Peterson's</i> model if TRUE
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
date	Production date ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
o	DMU index to calc. NULL(default) will calc for all

**Value**

\$eff	Efficiency score
\$lambda	Intensity vector
\$mu	Secondary intensity vector for weak disposability under VRS
\$beta	Input reduction factor
\$gamma	Output augmentation factor
\$xslack	Input slack
\$yslack	Output slack

**Author(s)**

Dong-Joon Lim, PhD

**References**

Chambers, Robert G., Yangho Chung, and Rolf Fare. "Profit, directional distance functions, and Nerlovian efficiency." *Journal of optimization theory and applications* 98.2 (1998): 351~364.

Fare, Rolf, and Shawna Grosskopf. "Directional distance functions and slacks-based measures of efficiency." *European journal of operational research* 200.1 (2010): 320~322.

**See Also**

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

**Examples**

```
# Additive form directional distance function
# ready
x <- matrix(c(5, 1, 4), ncol = 1)
y <- matrix(c(8, 3, 5, 6, 4, 1), ncol = 2)
g <- matrix(c(1), nrow = 3, ncol = 3)
w <- matrix(c(1, 0), ncol = 2)
# go
dm.ddf(x, y, "crs", g, w)

# Multiplicative form directional distance function
# ready
g <- cbind(x, y)
# go
dm.ddf(x, y, "crs", g, w)
```

---

dm.dea

*Distance measure using DEA*


---

**Description**

Implements *Charnes & Cooper's* data envelopment analysis (radial & oriented measure).

**Usage**

```
dm.dea(xdata, ydata, rts="crs", orientation,
       se=FALSE, sg="ssm", date=NULL, ncv=NULL, env=NULL, cv="convex", o=NULL)
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "i" Input-orientation "o" Output-orientation
se	Implements <i>Anderson &amp; Peterson's</i> super-efficiency model if TRUE
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
date	Production date ( $n$ by $1$ )
ncv	Non-controllable variable index(binary) for internal NDF ( $1$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
o	DMU index to calc. NULL(default) will calc for all

**Value**

\$eff	Efficiency score
\$lambda	Intensity vector
\$xslack	Input slack
\$yslack	Output slack
\$vx	Input (dual) weight
\$uy	Output (dual) weight
\$w	Free (dual) variable

**Author(s)**

Dong-Joon Lim, PhD

**References**

Charnes, Abraham, William W. Cooper, and Edwardo Rhodes. "Measuring the efficiency of decision making units." *European journal of operational research* 2.6 (1978): 429-444.

Charnes, Abraham, William W. Cooper, and Edwardo Rhodes. "Evaluating program and managerial efficiency: an application of data envelopment analysis to program follow through." *Management science* 27.6 (1981): 668~697.

Banker, Rajiv D., and Richard C. Morey. "Efficiency analysis for exogenously fixed inputs and outputs." *Operations Research* 34.4 (1986): 513~521.

Ruggiero, John. "On the measurement of technical efficiency in the public sector." *European Journal of Operational Research* 90.3 (1996): 553~565.

Fried, Harold O., CA Knox Lovell, and Shelton S. Schmidt, eds. The measurement of productive efficiency and productivity growth. *Oxford University Press*, 2008.

### See Also

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

### Examples

```
# Reproduce Table 3.9 (p.348) in Fried, H.O. et al.(2008)
# ready
X <- data.frame(x1 = c(8, 6, 3, 10, 6, 8, 8, 4),
                x2 = c(8, 4.6, 1.9, 9, 3.6, 3.6, 9, 1.9))
Y <- data.frame(y1 = c(8, 5, 2, 9, 4.5, 4.5, 7, 2))
C <- data.frame(x1 = 0, x2 = 1, y1 = 0)

# go
data.frame(ALL_CRS = dm.dea(X, Y, "crs", "i")$eff,
           ALL_VRS = dm.dea(X, Y, "vrs", "i")$eff,
           NDF_CRS = dm.dea(X, Y, "crs", "i", ncv = C)$eff,
           NDF_VRS = dm.dea(X, Y, "vrs", "i", ncv = C)$eff,
           row.names = LETTERS[1 : 8])
```

---

dm.hdf

*Distance measure using HDF*

---

### Description

Implements *Fare's* hyperbolic distance function (semi-radial & non-oriented measure).

### Usage

```
dm.hdf(xdata, ydata, rts="crs",
       wd=NULL, se=FALSE, sg="ssm", date=NULL, cv="convex", o=NULL)
```



**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
se	Implements super-efficiency model alike <i>Anderson &amp; Peterson's</i> model if TRUE
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
date	Production date ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
o	DMU index to calc. NULL(default) will calc for all

**Value**

\$eff	Efficiency score
\$lambda	Intensity vector
\$mu	Secondary intensity vector for weak disposability under VRS
\$xslack	Input slack
\$yslack	Output slack
\$iteration	The number of iteration to obtain the hyperbolic efficiency score

**Author(s)**

Dong-Joon Lim, PhD

**References**

- Fare, R., Shawna Grosskopf, and CA Knox Lovell. The Measurement of Efficiency of Production. *Boston: Kulwer-Nijhoff* (1985).
- Fare, Rolf, et al. "Estimating the hyperbolic distance function: A directional distance function approach." *European Journal of Operational Research* 254.1 (2016): 312-319.

**See Also**

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

**Examples**

```

# Reproduce Table 2 in Fare et al.(2016)
# ready
x <- data.frame(x1 = c(2, 4, 9, 6.5, 10, 6, 9))
y <- data.frame(y1 = c(3, 7, 10, 8.5, 4, 2, 8))

# go
sf <- dm.sf(x, y, "vrs")$eff
hdf <- dm.hdf(x, y, "vrs")$eff
matrix(t(cbind(sf, hdf)), 2, 7,
       dimnames = list(c("SF", "HDF"),
                       paste0("DMU_", c(letters[1:4], "o", "p", "q"))))
  
```

dm.mahalanobis

*Distance measure using Mahalanobis distance for outlier detection***Description**

Implements *Mahalanobis* distance measure for outlier detection. In addition to the basic distance measure, boxplots are provided with potential outlier(s) to give an insight into the early stage of data cleansing task.

**Usage**

```
dm.mahalanobis(data, from="median", p=10, plot=FALSE, v.index=NULL, layout=NULL)
```

**Arguments**

data	Dataframe
from	Datum point from which the distance is measured "mean" Mean of each column "median" Median of each column (default)
p	Percentage to which outlier point(s) is noted (default of 10)
plot	Switch for boxplot(s)
v.index	Numeric vector indicating column(s) to be printed in the boxplot. Default value of NULL will present all.
layout	Numeric vector indicating dimension of boxplots. Default value of NULL will find an optimal layout.

**Value**

\$dist	Mahalanobis distance from from
\$excluded	Excluded row(s) in row number
\$order	Distance order (decreasing) in row number
\$suspect	Potential outlier(s) in row number

**Author(s)**

Dong-Joon Lim, PhD

**References**

Hair, Joseph F., et al. Multivariate data analysis. Vol. 7. *Upper Saddle River*, NJ: Pearson Prentice Hall, 2006.

**Examples**

```
# Generate a sample dataframe
df <- data.frame(replicate(6, sample(0 : 100, 50)))

# go
dm.mahalanobis(df, plot = TRUE)
```

---

dm.sbm

*Distance measure using SBM*


---

**Description**

Implements *Tone's* slack-based model (non-radial & (non-)oriented measure).

**Usage**

```
dm.sbm(xdata, ydata, rts="crs",
        orientation="n", se=FALSE, sg="ssm", date=NULL, cv="convex", o=NULL)
```

**Arguments**

xdata	Input(s) vector ( <i>n</i> by <i>m</i> )
ydata	Output(s) vector ( <i>n</i> by <i>s</i> )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS

orientation	Orientation of the measurement "n" Non-orientation (default) "i" Input-orientation "o" Output-orientation
se	Implements super-efficiency model alike <i>Anderson &amp; Peterson's</i> model if TRUE
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
date	Production date ( <i>n</i> by <i>I</i> )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
o	DMU index to calc. NULL(default) will calc for all

**Value**

\$eff	Efficiency score
\$lambda	Intensity vector
\$xslack	Input slack
\$yslack	Output slack
\$xtarget	Input target
\$ytarget	Output target

**Author(s)**

Dong-Joon Lim, PhD

**References**

Tone, Kaoru. "A slacks-based measure of efficiency in data envelopment analysis." *European journal of operational research* 130.3 (2001): 498~509.

Tone, Kaoru. "A slacks-based measure of super-efficiency in data envelopment analysis." *European journal of operational research* 143 (2002): 32~41.

**See Also**

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

**Examples**

```

# Reproduce Table 2 in Tone.(2001)
# ready
X <- data.frame(x1 = c(4, 6, 8, 8, 2),
                x2 = c(3, 3, 1, 1, 4))
Y <- data.frame(y1 = c(2, 2, 6, 6, 1),
                y2 = c(3, 3, 2, 1, 4))

# go
dm.sbm(X, Y)

# Reproduce Table 1 in Tone.(2002)
# Published input slacks are alternate optima (confirmed by Tone)
# ready
X <- data.frame(x1 = c(4, 7, 8, 4, 2, 10, 12),
                x2 = c(3, 3, 1, 2, 4, 1, 1))
Y <- data.frame(y1 = c(1, 1, 1, 1, 1, 1, 1))
# go
dm.sbm(X, Y, se = TRUE)

# Reproduce Table 4 in Tone.(2002)
# ready
X <- data.frame(x1 = c(80, 65, 83, 40, 52, 94),
                x2 = c(600, 200, 400, 1000, 600, 700),
                x3 = c(54, 97, 72, 75, 20, 36),
                x4 = c(8, 1, 4, 7, 3, 5))
Y <- data.frame(y1 = c(90, 58, 60, 80, 72, 96),
                y2 = c(5, 1, 7, 10, 8, 6))

# go
dm.sbm(X, Y, "crs", "i", se = TRUE)

```

dm.sf

*Distance measure using SF***Description**

Implements *Luenberger's* shortage (benefit) function (radial & non-oriented measure).

**Usage**

```
dm.sf(xdata, ydata, rts="crs", g=NULL,
      wd=NULL, se=FALSE, sg="ssm", date=NULL, cv="convex", o=NULL)
```

**Arguments**

xdata	Input(s) vector ( <i>n</i> by <i>m</i> )
ydata	Output(s) vector ( <i>n</i> by <i>s</i> )

rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
se	Implements super-efficiency model alike <i>Anderson &amp; Peterson's</i> model if TRUE
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
date	Production date ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
o	DMU index to calc. NULL(default) will calc for all

**Value**

\$eff	Efficiency score
\$lambda	Intensity vector
\$mu	Secondary intensity vector for weak disposability under VRS
\$xslack	Input slack
\$yslack	Output slack
\$w	Input (dual) weight
\$p	Output (dual) weight
\$u	Free (dual) variable

**Author(s)**

Dong-Joon Lim, PhD

**References**

- Luenberger, David G. "Benefit functions and duality." *Journal of mathematical economics* 21.5 (1992): 461~481.
- Chambers, Robert G., Yangho Chung, and Rolf Fare. "Profit, directional distance functions, and Nerlovian efficiency." *Journal of optimization theory and applications* 98.2 (1998): 351~364.

**See Also**

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

**Examples**

```

# Additive form shortage function
# ready
x <- matrix(c(5, 1, 4), ncol = 1)
y <- matrix(c(8, 3, 5, 6, 4, 1), ncol = 2)
g <- matrix(c(1), nrow = 3, ncol = 3)
w <- matrix(c(1, 0), ncol = 2)
# go
dm.sf(x, y, "crs", g, w)

# Multiplicative form shortage function
# ready
g <- cbind(x, y)
# go
dm.sf(x, y, "crs", g, w)

```

---

ma.aps.reg

*Combinatorial search (all possible subset) for regression analysis*


---

**Description**

Implements combinatorial (exhaustive) search algorithm, aka all-possible-subsets regression. As opposed to the sequential approach (stepwise, forward addition, or backward elimination) that has a potential bias resulting from considering only one variable for selection at a time, all possible combinations of the independent variables are examined, and sets satisfying designated conditions are returned.

**Usage**

```

ma.aps.reg(dv, iv, min=1, max, mad=FALSE, aic=FALSE, bic=FALSE,
           model.sig=TRUE, coeff.sig=TRUE, coeff.vif=TRUE, coeff.cor=FALSE)

```

**Arguments**

dv	Dependent variable ( <i>r</i> by <i>I</i> )
iv	Independent variable(s) ( <i>r</i> by <i>c</i> )
min	Minimum number of independent variable to explore ( $\geq 1$ )
max	Maximum number of independent variable to explore ( $\leq r/10$ )
mad	Returns mean absolute deviation when TRUE

aic	Returns Akaike's information criterion when TRUE
bic	Returns Bayesian information criterion when TRUE
model.sig	Returns models statistically significant only when TRUE
coeff.sig	Returns models with statistically significant coefficients only when TRUE
coeff.vif	Returns models with allowable level of multicollinearity only when TRUE
coeff.cor	Returns models without suppression effects only when TRUE

**Author(s)**

Dong-Joon Lim, PhD

**References**

Hair, Joseph F., et al. Multivariate data analysis. Vol. 7. *Upper Saddle River*, NJ: Pearson Prentice Hall, 2006.

**Examples**

```
# Load airplane dataset
df <- dataset.airplane.2017

# ready
dv <- subset(df, select = 2)
iv <- subset(df, select = 3 : 7)

# go
ma.aps.reg(dv, iv, 1, 3, mad = TRUE, coeff.cor = TRUE)
```

---

map.corr

*Correlation mapping for reliability test*

---

**Description**

Implements a series of correlation analysis by dropping extreme data points one by one using *Mahalanobis* distance measure. Correlation reliability can be investigated with identified anchoring point(s). Correlation map as well as summary table is provided.

**Usage**

```
map.corr(data, from = "median", threshold = 0.3, r.name = FALSE)
```

**Arguments**

data	Dataframe
from	Datum point from which the distance is measured "mean" Mean of each column "median" Median of each column (default)
threshold	Threshold of correlation change to be noted on the map
r.name	Dropped points are shown in row name when TRUE



**Value**

\$reliability Summary table

**Author(s)**

Dong-Joon Lim, PhD

**See Also**

[dm.mahalanobis](#) Distance measure using Mahalanobis distance

**Examples**

```
# Generate a sample dataframe
df <- data.frame(replicate(2, sample(0 : 100, 50)))

# go
map.corr(df)
```

---

map.soa.ddf

*SOA mapping using DDF*


---

**Description**

Employs dm.ddf over time to generate a state-of-the-art map.

**Usage**

```
map.soa.ddf(xdata, ydata, date,
            rts="crs", g=NULL, wd=NULL, sg="ssm", cv="convex", mk="dmu")
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )

sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
mk	Marker on the map "dmu" DMU index (default) "eff" Efficiency score

**Author(s)**

Dong-Joon Lim, PhD

**See Also**

[map.soa.ddf](#) SOA mapping using DDF  
[map.soa.dea](#) SOA mapping using DEA  
[map.soa.hdf](#) SOA mapping using HDF  
[map.soa.sbm](#) SOA mapping using SBM  
[map.soa.sf](#) SOA mapping using SF

**Examples**

```
# Load engine dataset
df <- dataset.engine.2015

# Subset for forced induction systems
fis <- subset(df, grepl("^C..", df[, 8]))

# Parameters
x <- subset(fis, select = 4)
y <- subset(fis, select = 6 : 7)
d <- subset(fis, select = 2)
g <- matrix(c(1), nrow = nrow(x), ncol = 3)

# Generate an SOA map
map.soa.ddf(x, y, d, "crs", g)
```

---

map.soa.dea

*SOA mapping using DEA*


---

**Description**

Employs dm.dea over time to generate a state-of-the-art map.

**Usage**

```
map.soa.dea(xdata, ydata, date, rts="crs", orientation,
            sg="ssm", ncv=NULL, env=NULL, cv="convex", mk="dmu")
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "i" Input-orientation "o" Output-orientation
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
ncv	Non-controllable variable index(binary) for internal NDF ( $1$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
mk	Marker on the map "dmu" DMU index (default) "eff" Efficiency score

**Author(s)**

Dong-Joon Lim, PhD

**See Also**

[map.soa.ddf](#) SOA mapping using DDF  
[map.soa.dea](#) SOA mapping using DEA  
[map.soa.hdf](#) SOA mapping using HDF  
[map.soa.sbm](#) SOA mapping using SBM  
[map.soa.sf](#) SOA mapping using SF

**Examples**

```
# Load engine dataset
df <- dataset.engine.2015

# Subset for forced induction systems
fis <- subset(df, grepl("^C..", df[, 8]))

# Parameters
x <- subset(fis, select = 4)
y <- subset(fis, select = 6 : 7)
d <- subset(fis, select = 2)

# Generate an SOA map
map.soa.dea(x, y, d, "crs", "o")
```

map.soa.hdf

*SOA mapping using HDF***Description**

Employs dm.hdf over time to generate a state-of-the-art map.

**Usage**

```
map.soa.hdf(xdata, ydata, date,
            rts="crs", wd=NULL, sg="ssm", cv="convex", mk="dmu")
```

**Arguments**

xdata	Input(s) vector ( <i>n</i> by <i>m</i> )
ydata	Output(s) vector ( <i>n</i> by <i>s</i> )
date	Production date ( <i>n</i> by <i>l</i> )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
wd	Weak disposability vector indicating (an) undesirable output(s) ( <i>l</i> by <i>s</i> )
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
mk	Marker on the map "dmu" DMU index (default) "eff" Efficiency score

**Author(s)**

Dong-Joon Lim, PhD

**References**

D.-J. Lim, Internal combustion engine race: naturally aspirated vs turbo/super-charged, *working paper* (2015).

**See Also**

[map.soa.ddf](#) SOA mapping using DDF  
[map.soa.dea](#) SOA mapping using DEA  
[map.soa.hdf](#) SOA mapping using HDF  
[map.soa.sbm](#) SOA mapping using SBM  
[map.soa.sf](#) SOA mapping using SF

**Examples**

```
# Load engine dataset
df <- dataset.engine.2015

# Subset for SC/TC 8 cylinder engines
stc.8 <- subset(df, grepl("^C..", df[, 8]) & df[, 3] == 8)

# Parameters
x <- subset(stc.8, select = 4)
y <- subset(stc.8, select = 5:7)
d <- subset(stc.8, select = 2)

# Generate an SOA map
map.soa.hdf(x, y, d, "vrs")
```

---

map.soa.sbm

*SOA mapping using SBM*

---

**Description**

Employs dm.sbm over time to generate a state-of-the-art map.

**Usage**

```
map.soa.sbm(xdata, ydata, date,
            rts="crs", orientation="n", sg="ssm", cv="convex", mk="dmu")
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "n" Non-orientation (default) "i" Input-orientation "o" Output-orientation
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
mk	Marker on the map "dmu" DMU index (default) "eff" Efficiency score

**Author(s)**

Dong-Joon Lim, PhD

**See Also**

[map.soa.ddf](#) SOA mapping using DDF  
[map.soa.dea](#) SOA mapping using DEA  
[map.soa.hdf](#) SOA mapping using HDF  
[map.soa.sbm](#) SOA mapping using SBM  
[map.soa.sf](#) SOA mapping using SF

**Examples**

```
# Load engine dataset
df <- dataset.engine.2015

# Subset for forced induction systems
fis <- subset(df, grepl("^C.", df[, 8]))

# Parameters
x <- subset(fis, select = 4)
y <- subset(fis, select = 6 : 7)
```

```
d <- subset(fis, select = 2)

# Generate an SOA map
map.soa.sbm(x, y, d)
```

---

map.soa.sf                      *SOA mapping using SF*

---

### Description

Employs dm.sf over time to generate a state-of-the-art map.

### Usage

```
map.soa.sf(xdata, ydata, date,
           rts="crs", g=NULL, wd=NULL, sg="ssm", cv="convex", mk="dmu")
```

### Arguments

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization (only if date is defined) "min" Date-sum minimization (only if date is defined)
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
mk	Marker on the map "dmu" DMU index (default) "eff" Efficiency score

### Author(s)

Dong-Joon Lim, PhD

## References

D.-J. Lim, Internal combustion engine race: naturally aspirated vs turbo/super-charged, *working paper* (2015).

## See Also

[map.soa.ddf](#) SOA mapping using DDF  
[map.soa.dea](#) SOA mapping using DEA  
[map.soa.hdf](#) SOA mapping using HDF  
[map.soa.sbm](#) SOA mapping using SBM  
[map.soa.sf](#) SOA mapping using SF

## Examples

```
# Reproduce Table 2 in Lim, D-J. (2015)
# Load engine dataset
df <- dataset.engine.2015

# Subset for 4 cylinder engines
fce <- subset(df, df[, 3] == 4)

# Parameters
x <- subset(fce, select = 4)
y <- subset(fce, select = 5 : 7)
d <- subset(fce, select = 2)
g <- data.frame(0, y)
w <- matrix(c(1, 0, 0), ncol = 3)

# Generate an SOA map
map.soa.sf(x, y, d, "crs", g, w, mk = "eff")
```

---

roc.dea

*Rate of change (RoC) calculation using DEA*

---

## Description

Employs `dm.dea` over time to calculate RoCs.

## Usage

```
roc.dea(xdata, ydata, date, t, rts="crs", orientation,
        sg="ssm", ftype="d", ncv=NULL, env=NULL, cv="convex")
```

## Arguments

<code>xdata</code>	Input(s) vector ( <i>n</i> by <i>m</i> )
<code>ydata</code>	Output(s) vector ( <i>n</i> by <i>s</i> )
<code>date</code>	Production date ( <i>n</i> by <i>1</i> )



t	A vantage point from which the RoC is captured
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "i" Input-orientation "o" Output-orientation
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
f type	Frontier type "d" Dynamic frontier (default) "s" Static frontier
ncv	Non-controllable variable index(binary) for internal NDF ( $I$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $I$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

### Value

\$eff_r	Efficiency at release (i.e., at each production date)
\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_past	RoC observed from the obsolete DMUs in the past
\$roc_avg	Average RoC
\$roc_local	Local RoC

### Author(s)

Dong-Joon Lim, PhD

### References

- Lim, Dong-Joon, Timothy R. Anderson, and Oliver Lane Inman. "Choosing effective dates from multiple optima in Technology Forecasting using Data Envelopment Analysis (TFDEA)." *Technological Forecasting and Social Change* 88 (2014): 91~97.
- Lim, Dong-Joon, et al. "Comparing technological advancement of hybrid electric vehicles (HEV) in different market segments." *Technological Forecasting and Social Change* 97 (2015): 140~153.
- Lim, Dong-Joon, et al. Technometrics Study Using DEA on Hybrid Electric Vehicles (HEVs). Handbook of Operations Analytics Using Data Envelopment Analysis. *Springer (forthcoming)*, 2016.

**See Also**

[dm.dea](#) Distance measure using DEA  
[roc.dea](#) RoC calculation using DEA  
[map.soa.dea](#) SOA mapping using DEA  
[target.arrival.dea](#) Arrival target setting using DEA  
[target.spec.dea](#) Spec target setting using DEA

**Examples**

```

# Reproduce Table 3 in Lim, D-J. et al.(2014)
# Load airplane dataset
df <- dataset.airplane.2017

# ready
x <- data.frame(Flew = rep(1, 28))
y <- subset(df, select = 3 : 7)
d <- subset(df, select = 2)

# go
roc.dea(x, y, d, 2007, "vrs", "o", "min", "d")$roc_past

# Reproduce Table 3 in Lim, D-J. et al.(2015)
# Load hev dataset
df <- dataset.hev.2013

# ready
x <- subset(df, select = 3)
y <- subset(df, select = 4 : 6)
d <- subset(df, select = 2)
c <- subset(df, select = 7)

# go
results <- roc.dea(x, y, d, 2013, "vrs", "o", "min", "d", env = c)
hev <- which(results$roc_local > 0)
data.frame(Class = c[hev, ],
           SOA = hev,
           LocalRoC = results$roc_local[hev, ])[order(c[hev, ]), ]
# NOTE: the published results include a typo on roc_local[82,]
#       this will be corrected in forthcoming book chapter(Lim, D-J. et al., 2016).

```

roc.hdf

*Rate of change (RoC) calculation using HDF***Description**

Employs dm.hdf over time to calculate RoCs.

**Usage**

```
roc.hdf(xdata, ydata, date, t,
        rts="crs", wd=NULL, sg="ssm", ftype="d", cv="convex")
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $I$ )
t	A vantage point from which the RoC is captured
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
wd	Weak disposability vector indicating (an) undesirable output(s) ( $I$ by $s$ )
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
ftype	Frontier type "d" Dynamic frontier (default) "s" Static frontier
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

**Value**

\$eff_r	Efficiency at release (i.e., at each production date)
\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_past	RoC observed from the obsolete DMUs in the past
\$roc_avg	Average RoC
\$roc_local	Local RoC

**Author(s)**

Dong-Joon Lim, PhD

**References**

D.-J. Lim, Internal combustion engine race: naturally aspirated vs turbo/super-charged, *working paper* (2015).

**See Also**

[dm.hdf](#) Distance measure using HDF  
[roc.hdf](#) RoC calculation using HDF  
[map.soa.hdf](#) SOA mapping using HDF  
[target.arrival.hdf](#) Arrival target setting using HDF

**Examples**

```

# Load engine dataset
df <- dataset.engine.2015

# Subset for 8 cylinder TC-P engines
et <- subset(df, df[, 3] == 8 & df[, 8] == "TC-P")

# Parameters
x <- subset(et, select = 4)
y <- subset(et, select = 5 : 7)
d <- subset(et, select = 2)
w <- matrix(c(1, 0, 0), ncol = 3)

# Calc local Roc
roc.hdf(x, y, d, 2015, "vrs", w, "min")

```

roc.malmquist

*Malmquist Index: time-series productivity analysis***Description**

Employs distance measure over time to calculate the productivity changes.

**Usage**

```
roc.malmquist(xdata, ydata, tm=NULL, dm="dea", rts="crs", orientation,
              g=NULL, wd=NULL, ncv=NULL, env=NULL, cv="convex")
```

**Arguments**

xdata	Input(s) array ( $n$ by $m$ by $t$ )
ydata	Output(s) array ( $n$ by $s$ by $t$ )
tm	Tick mark of production dates (a vector length of $t$ )
dm	Distance measure to calculate the productivity "dea" Data Envelopment Analysis (default) "sbm" Slack Based Model "ddf" Directional Distance Function "hdf" Hyperbolic Distance Function "sf" Shortage Function

rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "n" Non-orientation "i" Input-orientation "o" Output-orientation
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $l$ by $s$ )
ncv	Non-controllable variable index(binary) for internal NDF ( $l$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $l$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

**Value**

\$cu	Catching Up (aka technical efficiency change: TEC) index
\$fs	Frontier Shift (FS) Index
\$mi	Malmquist Index

**Author(s)**

Dong-Joon Lim, PhD

**References**

R. Fare, S. Grosskopf, and C. A. K. Lovell, Production Frontiers. *Cambridge University Press*, 1994.

**See Also**

[dm.ddf](#) Distance measure using DDF  
[dm.dea](#) Distance measure using DEA  
[dm.hdf](#) Distance measure using HDF  
[dm.sbm](#) Distance measure using SBM  
[dm.sf](#) Distance measure using SF

**Examples**

```
# Load data
df <- array(c(4,      3,   9,  10,  7,  4,  3,  5,
              5,     12,  3,   8,  1,  4, 14,  3,
              1,     1,  1,   1,  1,  1,  1,  1,
```

```

3.4, 2, 10, 8, 10, 4, 1, 5,
6, 10, 3.5, 7, 2, 4, 12, 3,
1, 1, 1, 1, 1, 1, 1, 1,
2.8, 1.8, 8, 7, 10, 3, 1, 5,
5.7, 8.8, 2.8, 5, 2, 5, 9, 3,
1, 1, 1, 1, 1, 1, 1, 1,
2.2, 1.5, 8, 5, 8, 3, 1, 5,
6, 8, 2.3, 3.5, 2, 5, 7, 3,
1, 1, 1, 1, 1, 1, 1, 1),
c(8, 3, 4))

```

```

# Run
roc.malmquist(df[,1:2,], df[,3,], dm = "sbm", orientation = "n")

```

---

roc.sf *Rate of change (RoC) calculation using SF*

---

## Description

Employs `dm.sf` over time to calculate RoCs. This function is valid only when multiplicative form of directional vector is used.

## Usage

```

roc.sf(xdata, ydata, date, t,
       rts="crs", g=NULL, wd=NULL, sg="ssm", ftype="d", cv="convex")

```

## Arguments

<code>xdata</code>	Input(s) vector ( $n$ by $m$ )
<code>ydata</code>	Output(s) vector ( $n$ by $s$ )
<code>date</code>	Production date ( $n$ by $I$ )
<code>t</code>	A vantage point from which the RoC is captured
<code>rts</code>	Returns to scale assumption " <code>crs</code> " Constant RTS (default) " <code>vrs</code> " Variable RTS " <code>irs</code> " Increasing RTS " <code>drs</code> " Decreasing RTS
<code>g</code>	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), <code>xdata</code> & <code>ydata</code> will be used
<code>wd</code>	Weak disposability vector indicating (an) undesirable output(s) ( $I$ by $s$ )
<code>sg</code>	Employs second-stage optimization " <code>ssm</code> " Slack-sum maximization (default) " <code>max</code> " Date-sum maximization " <code>min</code> " Date-sum minimization

ftype	Frontier type "d" Dynamic frontier (default) "s" Static frontier
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

**Value**

\$eff_r	Efficiency at release (i.e., at each production date)
\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_past	RoC observed from the obsolete DMUs in the past
\$roc_avg	Average RoC
\$roc_local	Local RoC

**Author(s)**

Dong-Joon Lim, PhD

**References**

D.-J. Lim, Internal combustion engine race: naturally aspirated vs turbo/super-charged, *working paper* (2015).

**See Also**

[dm.sf](#) Distance measure using SF  
[roc.sf](#) RoC calculation using SF  
[map.soa.sf](#) SOA mapping using SF  
[target.arrival.sf](#) Arrival target setting using SF

**Examples**

```
# Reproduce Mercedes-Benz CLA45 AMG's local RoC in Table 5 in Lim, D-J. (2015)
# Load engine dataset
df <- dataset.engine.2015

# Subset for 4 cylinder engines
fce <- subset(df, df[, 3] == 4)

# Parameters
x <- subset(fce, select = 4)
y <- subset(fce, select = 5 : 7)
d <- subset(fce, select = 2)
g <- as.matrix(data.frame(0, y))
w <- matrix(c(1, 0, 0), ncol = 3)
```

```
# Calc local Roc
roc.sf(x, y, d, 2014, "crs", g, w, "min")$roc_local[348, ]
```

---

target.arrival.dea      *Arrival target setting using DEA*

---

### Description

Employs dm.dea over time to estimate the arrival of known specifications.

### Usage

```
target.arrival.dea(xdata, ydata, date, t, rts="crs", orientation,
                  sg="ssm", ftype="d", ncv=NULL, env=NULL, cv="convex")
```

### Arguments

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
t	A vantage point from which the RoC is captured
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
orientation	Orientation of the measurement "i" Input-orientation "o" Output-orientation
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
ftype	Frontier type "d" Dynamic frontier (default) "s" Static frontier
ncv	Non-controllable variable index(binary) for internal NDF ( $1$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $1$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)



**Value**

\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_avg	Average RoC
\$roc_local	Local RoC
\$roc_ind	Individualized RoC
\$arrival_avg	Estimated arrival using roc_avg
\$arrival_seg	Estimated arrival using roc_ind

**Author(s)**

Dong-Joon Lim, PhD

**References**

Lim, Dong-Joon, Timothy R. Anderson, and Oliver Lane Inman. "Choosing effective dates from multiple optima in Technology Forecasting using Data Envelopment Analysis (TFDEA)." *Technological Forecasting and Social Change* 88 (2014): 91~97.

Lim, Dong-Joon, and Timothy R. Anderson. Time series benchmarking analysis for new product scheduling: who are the competitors and how fast are they moving forward?. *Advances in DEA Theory and Applications: with Examples in Forecasting Models*. Wiley (*forthcoming*), 2016.

**See Also**

[dm.dea](#) Distance measure using DEA  
[roc.dea](#) RoC calculation using DEA  
[map.soa.dea](#) SOA mapping using DEA  
[target.arrival.dea](#) Arrival target setting using DEA  
[target.spec.dea](#) Spec target setting using DEA

**Examples**

```
# Reproduce Table 4 in Lim, D-J., and Timothy R. Anderson.(2016)
# Load airplane dataset
df <- dataset.airplane.2017

# ready
x <- data.frame(Flew = rep(1, 28))
y <- subset(df, select = 3 : 7)
d <- subset(df, select = 2)

# go
target.arrival.dea(x, y, d, 2007, "vrs", "o", "min", "d")$arrival_seg
```

---

target.arrival.hdf      *Arrival target setting using HDF*

---

### Description

Employs dm.hdf over time to estimate the arrival of known specifications.

### Usage

```
target.arrival.hdf(xdata, ydata, date, t, rts="crs",
                  wd=NULL, sg="ssm", ftype="d", cv="convex")
```

### Arguments

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
t	A vantage point from which the RoC is captured
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
ftype	Frontier type "d" Dynamic frontier (default) "s" Static frontier
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

### Value

\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_avg	Average RoC
\$roc_local	Local RoC
\$roc_ind	Individualized RoC
\$arrival_avg	Estimated arrival using roc_avg
\$arrival_seg	Estimated arrival using roc_ind

**Author(s)**

Dong-Joon Lim, PhD

**References**

Lim, Dong-Joon, et al. "Comparing technological advancement of hybrid electric vehicles (HEV) in different market segments." *Technological Forecasting and Social Change* 97 (2015): 140~153.

Lim, Dong-Joon, and Timothy R. Anderson. Time series benchmarking analysis for new product scheduling: who are the competitors and how fast are they moving forward?. *Advances in DEA Theory and Applications: with Examples in Forecasting Models*. Wiley (*forthcoming*), 2016.

**See Also**

[dm.hdf](#) Distance measure using HDF  
[roc.hdf](#) RoC calculation using HDF  
[map.soa.hdf](#) SOA mapping using HDF  
[target.arrival.hdf](#) Arrival target setting using HDF

**Examples**

```
# Estimate arrivals of MY2015 SC/TC 8 cylinder engines
# Load engine dataset
df <- dataset.engine.2015

# Subset for SC/TC 8 cylinder engines
stc.8 <- subset(df, grepl("^C..", df[, 8]) & df[, 3] == 8)

# Parameters
x <- subset(stc.8, select = 4)
y <- subset(stc.8, select = 5:7)
d <- subset(stc.8, select = 2)

# Generate an SOA map
target.arrival.hdf(x, y, d, 2014, "vrs")
```

---

target.arrival.sf      *Arrival target setting using SF*

---

**Description**

Employs `dm.sf` over time to estimate the arrival of known specifications. This function is valid only when multiplicative form of directional vector is used.

**Usage**

```
target.arrival.sf(xdata, ydata, date, t, rts="crs", g=NULL,
                  wd=NULL, sg="ssm", ftype="d", cv="convex")
```

**Arguments**

xdata	Input(s) vector ( $n$ by $m$ )
ydata	Output(s) vector ( $n$ by $s$ )
date	Production date ( $n$ by $1$ )
t	A vantage point from which the RoC is captured
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
g	Directional vector indicating a measurement direction ( $n$ by $(m+s)$ ) By default (NULL), xdata & ydata will be used
wd	Weak disposability vector indicating (an) undesirable output(s) ( $1$ by $s$ )
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
f type	Frontier type "d" Dynamic frontier (default) "s" Static frontier
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)

**Value**

\$eff_t	Efficiency at t
\$lambda_t	Intensity vector at t
\$eft_date	Effective date
\$roc_avg	Average RoC
\$roc_local	Local RoC
\$roc_ind	Individualized RoC
\$arrival_avg	Estimated arrival using roc_avg
\$arrival_seg	Estimated arrival using roc_ind

**Author(s)**

Dong-Joon Lim, PhD

**References**

- Lim, Dong-Joon, et al. "Comparing technological advancement of hybrid electric vehicles (HEV) in different market segments." *Technological Forecasting and Social Change* 97 (2015): 140~153.
- Lim, Dong-Joon, and Timothy R. Anderson. Time series benchmarking analysis for new product scheduling: who are the competitors and how fast are they moving forward?. *Advances in DEA Theory and Applications: with Examples in Forecasting Models*. Wiley (*forthcoming*), 2016.

**See Also**

[dm.sf](#) Distance measure using SF  
[roc.sf](#) RoC calculation using SF  
[map.soa.sf](#) SOA mapping using SF  
[target.arrival.sf](#) Arrival target setting using SF

**Examples**

```

# Estimate arrivals of MY2013 hev models
# Load hev dataset
df <- dataset.hev.2013

# ready
x <- subset(df, select = 3)
y <- subset(df, select = 4 : 6)
d <- subset(df, select = 2)
g <- data.frame(x, y)

# go
target.arrival.sf(x, y, d, 2012, "vrs", g)$arrival_seg
  
```

---

target.spec.dea	<i>Spec target setting using DEA</i>
-----------------	--------------------------------------

---

**Description**

Employs inverse DEA to estimate specifications(in/out-puts) to achieve a predetermined efficiency.

**Usage**

```
target.spec.dea(xdata, ydata, date=NULL, t=NULL, dt=NULL, dmU, et="c",
               alpha=NULL, beta=NULL, wv, rts="crs", sg="ssm", ftype="d",
               ncv=NULL, env=NULL, cv="convex", bound=TRUE)
```

**Arguments**

xdata	Input(s) vector ( <i>n</i> by <i>m</i> )
ydata	Output(s) vector ( <i>n</i> by <i>s</i> )
date	Production date ( <i>n</i> by <i>1</i> )
t	A vantage point from which the RoC is captured
dt	Delta <i>t</i> i.e., specs are estimated within PPS at <i>t+dt</i>
dmu	DMU whose inputs(or outputs) are to be estimated
et	Efficiency target; default value ("c") retains the current efficiency
alpha	Perturbed input(s) of designated DMU ( <i>1</i> by <i>m</i> )
beta	Perturbed output(s) of designated DMU ( <i>1</i> by <i>s</i> )

wv	Weight vector for scalarization ( $I$ by $m$ or $s$ )
rts	Returns to scale assumption "crs" Constant RTS (default) "vrs" Variable RTS "irs" Increasing RTS "drs" Decreasing RTS
sg	Employs second-stage optimization "ssm" Slack-sum maximization (default) "max" Date-sum maximization "min" Date-sum minimization
f type	Frontier type "d" Dynamic frontier (default) "s" Static frontier
ncv	Non-controllable variable index(binary) for internal NDF ( $I$ by $(m+s)$ )
env	Environment index for external NDF ( $n$ by $I$ )
cv	Convexity assumption "convex" Convexity holds (default) "fdh" Free disposal hull (this will override rts)
bound	Puts upper/lower bounds on alpha/beta if TRUE(default)

**Value**

\$alpha	Estimated input(s)
\$beta	Estimated output(s)
\$lambda	Intensity vector
\$xslack	Input slack
\$yslack	Output slack

**Author(s)**

Dong-Joon Lim, PhD

**References**

Lim, Dong-Joon, "Inverse DEA with frontier changes for new product target setting." *European Journal of Operational Research* 254.2 (2016): 510~516.

Wei, Quanling, Jianzhong Zhang, and Xiangsun Zhang. "An inverse DEA model for inputs/outputs estimate." *European Journal of Operational Research* 121.1 (2000): 151~163.

**See Also**

[dm.dea](#) Distance measure using DEA  
[roc.dea](#) RoC calculation using DEA  
[target.arrival.dea](#) Arrival target setting using DEA

**Examples**

```
# Reproduce Example 2 in Wei, Q. et al.(2000)
# ready
x <- matrix(c(1, 1, 1), 3)
y <- matrix(c(4, 8, 5, 8, 4, 5), 3)
a <- matrix(1.8, 1)
w <- matrix(c(0.5, 0.5), 1)

# go
target.spec.dea(x, y, dmu = 3, alpha = a, wv = w, rts = "crs")$beta

# Reproduce Table 4 in Lim, D-J. (2016)
# Load engine dataset
df <- dataset.engine.2015

# Subset for forced induction systems
fis <- subset(df, grepl("^C..", df[, 8]))

# ready
# Suppose one wants to estimate Porsche 911 turbo s' engine specs
# to retain its current competitiveness with downsized 3.5 litre engine in 2018.
# What might be the minimum specs to achieve this goal
# considering the technological changes we've seen so far?
# Plus, the CEO wants to put more emphasis on the torque improvement over HP.
d <- subset(fis, select = 2)
x <- subset(fis, select = 4)
y <- subset(fis, select = 6 : 7)
a <- as.matrix(3.5)
w <- matrix(c(0.3, 0.7), 1)

# go
target.spec.dea(x, y, d, 2015, 3, 262, alpha = a, wv = w, rts = "vrs", sg = "min")$beta
```

# Index

dataset.airplane.2017, 2  
dataset.engine.2015, 3  
dataset.hev.2013, 4  
dm.ddf, 5, 6, 8, 10, 12, 15, 29  
dm.dea, 6, 6, 8, 10, 12, 15, 26, 29, 33, 38  
dm.hdf, 6, 8, 8, 10, 12, 15, 28, 29, 35  
dm.mahalanobis, 10, 17  
dm.sbm, 6, 8, 10, 11, 12, 15, 29  
dm.sf, 6, 8, 10, 12, 13, 15, 29, 31, 37  
  
ma.aps.reg, 15  
map.corr, 16  
map.soa.ddf, 17, 18, 19, 21, 22, 24  
map.soa.dea, 18, 18, 19, 21, 22, 24, 26, 33  
map.soa.hdf, 18, 19, 20, 21, 22, 24, 28, 35  
map.soa.sbm, 18, 19, 21, 21, 22, 24  
map.soa.sf, 18, 19, 21, 22, 23, 24, 31, 37  
  
roc.dea, 24, 26, 33, 38  
roc.hdf, 26, 28, 35  
roc.malmquist, 28  
roc.sf, 30, 31, 37  
  
target.arrival.dea, 26, 32, 33, 38  
target.arrival.hdf, 28, 34, 35  
target.arrival.sf, 31, 35, 37  
target.spec.dea, 26, 33, 37