

Package ‘mfGARCH’

June 28, 2018

Title Mixed-Frequency GARCH Models

Version 0.1.5

Description Estimating GARCH-MIDAS (MIXed-DAta-Sampling) models (Engle, Ghysels, Sohn, 2013, <doi:10.1162/REST_a_00300>) and related statistical inference, accompanying the paper “Two are better than one: volatility forecasting using multiplicative component GARCH models” by Conrad and Kleen (2018, Working Paper, <doi:10.2139/ssrn.2752354>). The GARCH-MIDAS model decomposes the conditional variance of (daily) stock returns into a short- and long-term component, where the latter may depend on an exogenous covariate sampled at a lower frequency.

Depends R (>= 3.3.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.0.1

Imports Rcpp, graphics, stats, numDeriv, zoo

LinkingTo Rcpp

URL <https://github.com/onnoKleen/mfGARCH/>

BugReports <https://github.com/onnoKleen/mfGARCH/issues>

Suggests testthat, dplyr, ggplot2, covr, rmarkdown

NeedsCompilation yes

Author Onno Kleen [aut, cre]

Maintainer Onno Kleen <r@onnoKleen.de>

Repository CRAN

Date/Publication 2018-06-28 18:37:54 UTC

R topics documented:

df_financial	2
df_mfgarch	3

fit_mfgarch	4
plot_weighting_scheme	5
simulate_mfgarch	5
simulate_mfgarch_diffusion	6
Index	7

df_financial	<i>Stock returns and financial conditions.</i>
--------------	--

Description

A dataset containing the S&P 500 stock returns and the NFCI

Usage

df_financial

Format

A data frame with 11,306 rows and 5 variables:

date date

return daily S&P 500 log returns times 100

rv 5-minute realized variances

week a dummy for each year/week combination

nfc National Financial Conditions Index

Source

<https://github.com/onnokleen/mfGARCH/>

<https://de.finance.yahoo.com/>

<https://fred.stlouisfed.org/series/NFCI>

<https://realized.oxford-man.ox.ac.uk>

df_mfgarch	<i>Mixed-frequency data set.</i>
------------	----------------------------------

Description

A dataset containing the S&P 500 stock returns, realized variances and macroeconomic variables

Usage

df_mfgarch

Format

A data frame with 11,938 rows and 11 variables:

date date

return daily S&P 500 log returns times 100

open_close open-close returns

rv 5-minute realized variances

vix Cboe VIX

year_week a dummy for each year/week combination

dhousing changes in housing starts

dindpro changes in industrial production

nai NAI

nfcindex National Financial Conditions Index

year_month a dummy for each year/month combination

Source

<https://github.com/onnoKleen/mfGARCH/>

<https://de.finance.yahoo.com/>

<https://fred.stlouisfed.org>

<https://realized.oxford-man.ox.ac.uk>

fit_mfgarch	<i>This function estimates a multiplicative mixed-frequency GARCH model. For the sake of numerical stability, it is best to multiply log returns by 100.</i>
-------------	--

Description

This function estimates a multiplicative mixed-frequency GARCH model. For the sake of numerical stability, it is best to multiply log returns by 100.

Usage

```
fit_mfgarch(data, y, x = NULL, K = NULL, low.freq = "date",
  var.ratio.freq = NULL, gamma = TRUE, weighting = "beta.restricted",
  x.two = NULL, K.two = NULL, low.freq.two = NULL, weighting.two = NULL,
  multi.start = FALSE)
```

Arguments

data	data frame containing a column named date of type 'Date'.
y	name of high frequency dependent variable in df.
x	covariate employed in mfGARCH.
K	an integer specifying lag length K in the long-term component.
low.freq	a string of the low frequency variable in the df.
var.ratio.freq	specify a frequency column on which the variance ratio should be calculated.
gamma	if TRUE, an asymmetric GJR-GARCH is used as the short-term component. If FALSE, a simple GARCH(1,1) is employed.
weighting	specifies the weighting scheme employed in the long-term component. Options are "beta.restricted" (default) or "beta.unrestricted"
x.two	optional second covariate
K.two	lag length of optional second covariate
low.freq.two	low frequency of optional second covariate
weighting.two	specifies the weighting scheme employed in the optional second long-term component. Currently, the only option is "beta.restricted"
multi.start	if TRUE, optimization is carried out with multiple starting values

Examples

```
## Not run:
fit_mfgarch(data = df_financial, y = "return", x = "nfcf", low.freq = "week", K = 52)
fit_mfgarch(data = df_mfgarch, y = "return", x = "nfcf", low.freq = "year_week", K = 52,
  x.two = "dindpro", K.two = 12, low.freq.two = "year_month", weighting.two = "beta.restricted")

## End(Not run)
```

plot_weighting_scheme *This function plots the weighting scheme of an estimated GARCH-MIDAS model*

Description

This function plots the weighting scheme of an estimated GARCH-MIDAS model

Usage

```
plot_weighting_scheme(x)
```

Arguments

x mfGARCH object obtained by fit_mfgarch

simulate_mfgarch *This function simulates a GARCH-MIDAS model*

Description

This function simulates a GARCH-MIDAS model

Usage

```
simulate_mfgarch(n.days, mu, alpha, beta, gamma, m, theta, w1 = 1, w2, K, psi,
  sigma.psi, low.freq = 1, student.t = NULL)
```

Arguments

n.days	number of days
mu	mu
alpha	alpha
beta	beta
gamma	gamma
m	m
theta	theta
w1	w1
w2	w2
K	K
psi	psi
sigma.psi	sigma.psi
low.freq	number of days per low-frequency period
student.t	student.t

Examples

```
simulate_mfgarch(n.days = 200, mu = 0, alpha = 0.06, beta = 0.92, gamma = 0, m = 0,
theta = 0.1, w1 = 1, w2 = 3, K = 12, psi = 0.98, sigma.psi = 0.1, low.freq = 100, student.t = NULL)
```

```
simulate_mfgarch_diffusion
```

This function simulates a GARCH-MIDAS model where the short-term GARCH component is replaced by its diffusion limit, see Andersen (1998)

Description

This function simulates a GARCH-MIDAS model where the short-term GARCH component is replaced by its diffusion limit, see Andersen (1998)

Usage

```
simulate_mfgarch_diffusion(n.days, mu, alpha, beta, gamma, m, theta, w1 = 1,
w2, K, psi, sigma.psi, low.freq = 1, n.intraday = 288)
```

Arguments

n.days	number of days
mu	mu
alpha	alpha
beta	beta
gamma	gamma
m	m
theta	theta
w1	w1
w2	w2
K	K
psi	psi
sigma.psi	sigma.psi
low.freq	low.freq
n.intraday	n.intraday

Examples

```
## Not run: simulate_mfgarch_diffusion(n.days = 200, mu = 0, alpha = 0.06, beta = 0.92, gamma = 0, m = 0,
theta = 0.1, w1 = 1, w2 = 3, K = 12, psi = 0.98, sigma.psi = 0.1, low.freq = 10)
## End(Not run)
```

Index

*Topic **datasets**

df_financial, 2

df_mfgarch, 3

*Topic **fit_mfgarch**

fit_mfgarch, 4

*Topic **simulate_mfgarch**

simulate_mfgarch, 5

simulate_mfgarch_diffusion, 6

df_financial, 2

df_mfgarch, 3

fit_mfgarch, 4

plot_weighting_scheme, 5

simulate_mfgarch, 5

simulate_mfgarch_diffusion, 6