

Package ‘MPV’

June 7, 2018

Title Data Sets from Montgomery, Peck and Vining

Version 1.53

Author W.J. Braun

Description Most of this package consists of data sets from the textbook Introduction to Linear Regression Analysis (3rd ed), by Montgomery, Peck and Vining. Some additional data sets and functions are included.

Maintainer W.J. Braun <john.braun@ubc.ca>

LazyLoad true

LazyData true

Depends R (>= 2.0.1)

ZipData no

License Unlimited

NeedsCompilation no

Repository CRAN

Date/Publication 2018-06-07 19:20:01 UTC

R topics documented:

BioOxyDemand	3
cement	4
cigbutts	5
GANOVA	5
gasdata	6
GFplot	7
GRegplot	8
Juliet	9
motor	11
noisyimage	11
oldwash	12
p11.12	13

p11.15	14
p12.11	14
p12.12	15
p12.8	16
p13.1	17
p13.16	17
p13.2	18
p13.20	19
p13.3	19
p13.4	20
p13.5	21
p13.6	21
p13.7	22
p14.1	23
p14.2	23
p15.4	24
p2.10	25
p2.12	25
p2.13	26
p2.14	27
p2.15	28
p2.16	29
p2.7	30
p2.9	30
p4.18	31
p4.19	32
p4.20	33
p5.1	34
p5.10	34
p5.11	35
p5.2	36
p5.3	37
p5.4	37
p5.5	38
p7.1	39
p7.11	39
p7.15	40
p7.16	41
p7.19	41
p7.2	42
p7.4	43
p7.6	43
p8.11	44
p8.3	45
p9.10	45
pathoeg	46
PRESS	47
qqANOVA	48

quadline	48
Qyplot	49
softdrink	51
solar	51
stain	52
table.b1	53
table.b10	54
table.b11	55
table.b12	56
table.b13	56
table.b14	57
table.b2	58
table.b3	59
table.b4	60
table.b5	61
table.b6	62
table.b7	63
table.b8	64
table.b9	65
tarimage	66
tplot	66
Uplot	67
windWin80	68
Index	70

BioOxyDemand	<i>Biochemical Oxygen Demand</i>
--------------	----------------------------------

Description

The BioOxyDemand data frame has 14 rows and 2 columns.

Usage

```
data(BioOxyDemand)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

Source

Devore, J. L. (2000) *Probability and Statistics for Engineering and the Sciences (5th ed)*, Duxbury

Examples

```
plot(BioOxyDemand)
summary(lm(y ~ x, data = BioOxyDemand))
```

cement

Cement Data

Description

The cement data frame has 13 rows and 5 columns.

Usage

```
data(cement)
```

Format

This data frame contains the following columns:

y a numeric vector

x1 a numeric vector

x2 a numeric vector

x3 a numeric vector

x4 a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(cement)
pairs(cement)
```

cigbutts

Cigarette Butts

Description

On a university campus there are a number of areas designated for smoking. Outside of those areas, smoking is not permitted. One of the smoking areas is towards the north end of the campus near some parking lots and a large walkway towards one of the residences. Along the walkway, cigarette butts are visible in the nearby grass. Numbers of cigarette butts were counted at various distances from the smoking area in 200x80 square-cm quadrats located just west of the walkway.

Usage

```
data("cigbutts")
```

Format

A data frame with 15 observations on the following 2 variables.

distance distance from gazebo

count observed number of butts

GANOVA

Graphical ANOVA Plot

Description

Graphical analysis of one-way ANOVA data. It allows visualization of the usual F-test.

Usage

```
GANOVA(dataset, var.equal=TRUE, type="QQ")
```

Arguments

dataset A data frame, whose first column must be the factor variable and whose second column must be the response variable.

var.equal Logical: if TRUE, within-sample variances are assumed to be equal

type "QQ" or "hist"

Value

A QQ-plot or a histogram and rugplot

Author(s)

W. John Braun

Source

Braun, W.J. 2013. Naive Analysis of Variance. Journal of Statistics Education.

gasdata

Natural Gas Consumption in a Single-Family Residence

Description

This data frame contains the average monthly volume of natural gas used in the furnace of a 1600 square foot house located in London, Ontario, for each month from 2006 until 2011. It also contains the average temperature for each month, and a measure of degree days. Insulation was added to the roof on one occasions, the walls were insulated on a second occasion, and the mid-efficiency furnace was replaced with a high-efficiency furnace on a third occasion.

Usage

```
data("gasdata")
```

Format

A data frame with 70 observations on the following 9 variables.

month numeric 1=January, 12=December

degreedays numeric, Celsius

cubicmetres total volume of gas used in a month

dailyusage average amount of gas used per day

temp average temperature in Celsius

year numeric

I1 indicator that roof insulation is present

I2 indicator that wall insulation is present

I3 indicator that high efficiency furnace is present

Description

This function analyzes regression data graphically. It allows visualization of the usual F-test for significance of regression.

Usage

```
GFplot(X, y, plotIt=TRUE, sortTrt=FALSE, type="hist", includeIntercept=TRUE, labels=FALSE)
```

Arguments

X	The design matrix.
y	A numeric vector containing the response.
plotIt	Logical: if TRUE, a graph is drawn.
sortTrt	Logical: if TRUE, an attempt is made at sorting the predictor effects in descending order.
type	"QQ" or "hist"
includeIntercept	Logical: if TRUE, the intercept effect is plotted; otherwise, it is omitted from the plot.
labels	logical: if TRUE, names of predictor variables are used as labels; otherwise, the design matrix column numbers are used as labels

Value

A QQ-plot or a histogram and rugplot, or a list if plotIt=FALSE

Author(s)

W. John Braun

Source

Braun, W.J. 2013. Regression Analysis and the QR Decomposition. Preprint.

Examples

```
# Example 1
X <- p4.18[,-4]
y <- p4.18[,4]
GFplot(X, y, type="hist", includeIntercept=FALSE)
title("Evidence of Regression in the Jojoba Oil Data")
# Example 2
set.seed(4571)
```

```

Z <- matrix(rnorm(400), ncol=10)
A <- matrix(rnorm(81), ncol=9)
simdata <- data.frame(Z[,1], crossprod(t(Z[,-1]),A))
names(simdata) <- c("y", paste("x", 1:9, sep=""))
GFplot(simdata[, -1], simdata[, 1], type="hist", includeIntercept=FALSE)
title("Evidence of Regression in Simulated Data Set")
# Example 3
GFplot(table.b1[, -1], table.b1[, 1], type="hist", includeIntercept=FALSE)
title("Evidence of Regression in NFL Data Set")
# An example where stepwise AIC selects the complement
# of the set of variables that are actually in the true model:
X <- pathoeg[, -10]
y <- pathoeg[, 10]
par(mfrow=c(2,2))
GFplot(X, y)
GFplot(X, y, sortTrt=TRUE)
GFplot(X, y, type="QQ")
GFplot(X, y, sortTrt=TRUE, type="QQ")
X <- table.b1[, -1] # NFL data
y <- table.b1[, 1]
GFplot(X, y)

```

GRegplot

Graphical Regression Plot

Description

This function analyzes regression data graphically. It allows visualization of the usual F-test for significance of regression.

Usage

```
GRegplot(X, y, sortTrt=FALSE, includeIntercept=TRUE, type="hist")
```

Arguments

X	The design matrix.
y	A numeric vector containing the response.
sortTrt	Logical: if TRUE, an attempt is made at sorting the predictor effects in descending order.
includeIntercept	Logical: if TRUE, the intercept effect is plotted; otherwise, it is omitted from the plot.
type	Character: hist, for histogram; dot, for stripchart

Value

A histogram or dotplot and rugplot

Author(s)

W. John Braun

Source

Braun, W.J. 2014. Visualization of Evidence in Regression Analysis with the QR Decomposition. Preprint.

Examples

```
# Example 1
X <- p4.18[,-4]
y <- p4.18[,4]
GRegplot(X, y, includeIntercept=FALSE)
title("Evidence of Regression in the Jojoba Oil Data")
# Example 2
set.seed(4571)
Z <- matrix(rnorm(400), ncol=10)
A <- matrix(rnorm(81), ncol=9)
simdata <- data.frame(Z[,1], crossprod(t(Z[, -1]), A))
names(simdata) <- c("y", paste("x", 1:9, sep=""))
GRegplot(simdata[, -1], simdata[, 1], includeIntercept=FALSE)
title("Evidence of Regression in Simulated Data Set")
# Example 3
GRegplot(table.b1[, -1], table.b1[, 1], includeIntercept=FALSE)
title("Evidence of Regression in NFL Data Set")
# An example where stepwise AIC selects the complement
# of the set of variables that are actually in the true model:
X <- pathoeg[, -10]
y <- pathoeg[, 10]
par(mfrow=c(2, 1))
GRegplot(X, y)
GRegplot(X, y, sortTrt=TRUE)
X <- table.b1[, -1] # NFL data
y <- table.b1[, 1]
GRegplot(X, y)
```

 Juliet

Juliet

Description

Juliet has 28 rows and 9 columns. The data is of the input and output of the Spirit Still "Juliet" from Endless Summer Distillery. It is suggested to split the data by the Batch factor for ease of use.

Usage

Juliet

Format

The data frame contains the following 9 columns.

Batch a Factor determining how many times the volume has been through the still.

Vo11 Volume in litres, initial

P1 Percent alcohol present, initial

LAA1 Litres Absolute Alcohol initial, $Vo11 * P1$

Vo12 Volume in litres, final

P2 Percent alcohol present, final

LAA2 Litres Absolute Alcohol final, $Vo12 * P2$

Yield Percent yield obtained, $LAA2 / LAA1$

Date Character, Date of run

Details

The purpose of this information is to determine the optimal initial volume and percentage. The information is broken down by Batch. A batch factor 1 means that it is the first time the liquid has gone through the spirit still. The first run through the still should have the most loss due to the "heads" and "tails". Literature states that the first run through a spirit still should yield 70 percent. A batch factor 2 means that it is the second time the liquid has gone through the spirit still. A batch factor 3 means that it is the third time or more that the liquid has gone through the spirit still. Each subsequent distillation should result in a higher yield, never to exceed 95 percent.

Source

Charisse Woods, Endless Summer Distillery, (2015).

Examples

```
summary(Juliet)

#Split apart the Batch factor for easier use.
juliet<-split(Juliet,Juliet$Batch)
juliet1<-juliet$'1'
juliet2<-juliet$'2'
juliet3<-juliet$'3'

plot(LAA1~LAA2,data=Juliet)
plot(LAA1~LAA2,data=juliet1)
```

motor	<i>Motor Vibration Data</i>
-------	-----------------------------

Description

Noise measurements for 5 samples of motors, each sample based on a different brand of bearing.

Usage

```
data("motor")
```

Format

A data frame with 5 columns.

Brand 1 A numeric vector length 6

Brand 2 A numeric vector length 6

Brand 3 A numeric vector length 6

Brand 4 A numeric vector length 6

Brand 5 A numeric vector length 6

Source

Devore, J. and N. Farnum (2005) Applied Statistics for Engineers and Scientists. Thomson.

noisyimage	<i>noisy image</i>
------------	--------------------

Description

The noisyimage is a list. The third component is noisy version of the third component of [tarimage](#).

Usage

```
data(noisyimage)
```

Format

This list contains the following elements:

x a numeric vector having 101 elements.

y a numeric vector having 101 elements.

xy a numeric matrix having 101 rows and columns

Examples

```
with(noisyimage, image(x, y, xy))
```

oldwash	<i>oldwash</i>
---------	----------------

Description

The oldwash dataframe has 49 rows and 8 columns. The data are from the start up of a wash still considering the amount of time it takes to heat up to a specified temperature and possible influencing factors.

Usage

```
data("oldwash")
```

Format

A data frame with 49 observations on the following 8 variables.

Date character, the date of the run

startT degrees Celsius, numeric, initial temperature

endT degrees Celsius, numeric, final temperature

time in minutes, numeric, amount of time to reach final temperature

Vol in litres, numeric, amount of liquid in the tank (max 2000L)

alc numeric, the percentage of alcohol present in the liquid

who character, relates to the person who ran the still

batch factor with levels 1 = first time through, 2 = second time through

Details

The purpose of the wash still is to increase the percentage of alcohol and strip out unwanted particulate. It can take a long time to heat up and this can lead to problems in meeting production time limits.

Source

Charisse Woods, Endless Summer Distillery (2014)

Examples

```
oldwash.lm<-lm(log(time)~startT+endT+Vol+alc+who+batch,data=oldwash)
summary(oldwash.lm)
par(mfrow=c(2,2))
plot(oldwash.lm)

data2<-subset(oldwash,batch==2)
hist(data2$time)
data1<-subset(oldwash,batch==1)
```

```
hist(data1$time)

oldwash.lmc<-lm(time~startT+endT+Vol+alc+who+batch,data=data1)
summary(oldwash.lmc)
plot(oldwash.lmc)

oldwash.lmd<-lm(time~startT+endT+Vol+alc+who+batch,data=data2)
summary(oldwash.lmd)
plot(oldwash.lmd)
```

p11.12

Data For Problem 11-12

Description

The p11.12 data frame has 19 observations on satellite cost.

Usage

```
data(p11.12)
```

Format

This data frame contains the following columns:

cost first-unit satellite cost
x weight of the electronics suite

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Simpson and Montgomery (1998)

Examples

```
data(p11.12)
attach(p11.12)
plot(cost~x)
detach(p11.12)
```

p11.15

Data set for Problem 11-15

Description

The p11.15 data frame has 9 rows and 2 columns.

Usage

```
data(p11.15)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Ryan (1997), Stefanski (1991)

Examples

```
data(p11.15)
plot(p11.15)
attach(p11.15)
lines(lowess(x,y))
detach(p11.15)
```

p12.11

Data Set for Problem 12-11

Description

The p12.11 data frame has 44 observations on the fraction of active chlorine in a chemical product as a function of time after manufacturing.

Usage

```
data(p12.11)
```

Format

This data frame contains the following columns:

xi time

yi available chlorine

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p12.11)
plot(p12.11)
lines(lowess(p12.11))
```

p12.12

Data Set for Problem 12-12

Description

The p12.12 data frame has 18 observations on an chemical experiment. A nonlinear model relating concentration to reaction time and temperature with an additive error is proposed to fit these data.

Usage

```
data(p12.12)
```

Format

This data frame contains the following columns:

x1 reaction time (in minutes)

x2 temperature (in degrees Celsius)

y concentration (in grams/liter)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p12.12)
attach(p12.12)
# fitting the linearized model
logy.lm <- lm(I(log(y))~I(log(x1))+I(log(x2)))
summary(logy.lm)
plot(logy.lm, which=1) # checking the residuals
# fitting the nonlinear model
y.nls <- nls(y ~ theta1*I(x1^theta2)*I(x2^theta3), start=list(theta1=.95,
theta2=.76, theta3=.21))
summary(y.nls)
plot(resid(y.nls)~fitted(y.nls)) # checking the residuals
```

p12.8

Data Set for Problem 12-8

Description

The p12.8 data frame has 14 rows and 2 columns.

Usage

```
data(p12.8)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p12.8)
```

p13.1

Data Set for Problem 13-1

Description

The p13.1 data frame has 25 observation on the test-firing results for surface-to-air missiles.

Usage

```
data(p13.1)
```

Format

This data frame contains the following columns:

x target speed (in Knots)

y hit (=1) or miss (=0)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.1)
```

p13.16

Data Set for Problem 13-16

Description

The p13.16 data frame has 16 rows and 5 columns.

Usage

```
data(p13.16)
```

Format

This data frame contains the following columns:

X1 a numeric vector

X2 a numeric vector

X3 a numeric vector

X4 a numeric vector

Y a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

data(p13.16)

p13.2

Data Set for Problem 13-2

Description

The p13.2 data frame has 20 observations on home ownership.

Usage

data(p13.2)

Format

This data frame contains the following columns:

x family income

y home ownership (1 = yes, 0 = no)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

data(p13.2)

p13.20

Data Set for Problem 13-20

Description

The p13.20 data frame has 30 rows and 2 columns.

Usage

```
data(p13.20)
```

Format

This data frame contains the following columns:

yhat a numeric vector

resdev a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.20)
```

p13.3

Data Set for Problem 13-3

Description

The p13.3 data frame has 10 observations on the compressive strength of an alloy fastener used in aircraft construction.

Usage

```
data(p13.3)
```

Format

This data frame contains the following columns:

x load (in psi)

n sample size

r number failing

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.3)
```

p13.4

Data Set for Problem 13-4

Description

The p13.4 data frame has 11 observations on the effectiveness of a price discount coupon on the purchase of a two-litre beverage.

Usage

```
data(p13.4)
```

Format

This data frame contains the following columns:

x discount

n sample size

r number redeemed

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.4)
```

p13.5

Data Set for Problem 13-5

Description

The p13.5 data frame has 20 observations on new automobile purchases.

Usage

```
data(p13.5)
```

Format

This data frame contains the following columns:

x1 income

x2 age of oldest vehicle

y new purchase less than 6 months later (1=yes, 0=no)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.5)
```

p13.6

Data Set for Problem 13-6

Description

The p13.6 data frame has 15 observations on the number of failures of a particular type of valve in a processing unit.

Usage

```
data(p13.6)
```

Format

This data frame contains the following columns:

valve type of valve

numfail number of failures

months months

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p13.6)
```

p13.7

Data Set for Problem 13-7

Description

The p13.7 data frame has 44 observations on the coal mines of the Appalachian region of western Virginia.

Usage

```
data(p13.7)
```

Format

This data frame contains the following columns:

y number of fractures in upper seams of coal mines

x1 inner burden thickness (in feet), shortest distance between seam floor and the lower seam

x2 percent extraction of the lower previously mined seam

x3 lower seam height (in feet)

x4 time that the mine has been in operation (in years)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Myers (1990)

Examples

```
data(p13.7)
```

p14.1

Data Set for Problem 14-1

Description

The p14.1 data frame has 15 rows and 3 columns.

Usage

```
data(p14.1)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

time a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p14.1)
```

p14.2

Data Set for Problem 14-2

Description

The p14.2 data frame has 18 rows and 3 columns.

Usage

```
data(p14.2)
```

Format

This data frame contains the following columns:

t a numeric vector

xt a numeric vector

yt a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p14.2)
```

p15.4

Data Set for Problem 15-4

Description

The p15.4 data frame has 40 rows and 4 columns.

Usage

```
data(p15.4)
```

Format

This data frame contains the following columns:

x1 a numeric vector

x2 a numeric vector

y a numeric vector

set a factor with levels e and p

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p15.4)
```

p2.10

Data Set for Problem 2-10

Description

The p2.10 data frame has 26 observations on weight and systolic blood pressure for randomly selected males in the 25-30 age group.

Usage

```
data(p2.10)
```

Format

This data frame contains the following columns:

weight in pounds

sysbp systolic blood pressure

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p2.10)
attach(p2.10)
cor.test(weight, sysbp, method="pearson") # tests rho=0
                                           # and computes 95% CI for rho
                                           # using Fisher's Z-transform
```

p2.12

Data Set for Problem 2-12

Description

The p2.12 data frame has 12 observations on the number of pounds of steam used per month at a plant and the average monthly ambient temperature.

Usage

```
data(p2.12)
```

Format

This data frame contains the following columns:

temp ambient temperature (in degrees F)

usage usage (in thousands of pounds)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p2.12)
attach(p2.12)
usage.lm <- lm(usage ~ temp)
summary(usage.lm)
predict(usage.lm, newdata=data.frame(temp=58), interval="prediction")
detach(p2.12)
```

p2.13

Data Set for Problem 2-13

Description

The p2.13 data frame has 16 observations on the number of days the ozone levels exceeded 0.2 ppm in the South Coast Air Basin of California for the years 1976 through 1991. It is believed that these levels are related to temperature.

Usage

```
data(p2.13)
```

Format

This data frame contains the following columns:

days number of days ozone levels exceeded 0.2 ppm

index a seasonal meteorological index giving the seasonal average 850 millibar temperature.

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Davidson, A. (1993) Update on Ozone Trends in California's South Coast Air Basin. *Air Waste*, 43, 226-227.

Examples

```
data(p2.13)
attach(p2.13)
plot(days~index, ylim=c(-20,130))
ozone.lm <- lm(days ~ index)
summary(ozone.lm)
# plots of confidence and prediction intervals:
ozone.conf <- predict(ozone.lm, interval="confidence")
lines(sort(index), ozone.conf[order(index),2], col="red")
lines(sort(index), ozone.conf[order(index),3], col="red")
ozone.pred <- predict(ozone.lm, interval="prediction")
lines(sort(index), ozone.pred[order(index),2], col="blue")
lines(sort(index), ozone.pred[order(index),3], col="blue")
detach(p2.13)
```

p2.14

Data Set for Problem 2-14

Description

The p2.14 data frame has 8 observations on the molar ratio of sebacic acid and the intrinsic viscosity of copolyesters. One is interested in predicting viscosity from the sebacic acid ratio.

Usage

```
data(p2.14)
```

Format

This data frame contains the following columns:

ratio molar ratio

visc viscosity

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Hsuie, Ma, and Tsai (1995) Separation and Characterizations of Thermotropic Copolyesters of p-Hydroxybenzoic Acid, Sebacic Acid and Hydroquinone. Journal of Applied Polymer Science, 56, 471-476.

Examples

```
data(p2.14)
attach(p2.14)
plot(p2.14, pch=16, ylim=c(0,1))
visc.lm <- lm(visc ~ ratio)
summary(visc.lm)
visc.conf <- predict(visc.lm, interval="confidence")
lines(ratio, visc.conf[,2], col="red")
lines(ratio, visc.conf[,3], col="red")
visc.pred <- predict(visc.lm, interval="prediction")
lines(ratio, visc.pred[,2], col="blue")
lines(ratio, visc.pred[,3], col="blue")
detach(p2.14)
```

p2.15

Data Set for Problem 2-15

Description

The p2.15 data frame has 8 observations on the impact of temperature on the viscosity of toluene-tetralin blends. This particular data set deals with blends with a 0.4 molar fraction of toluene.

Usage

```
data(p2.15)
```

Format

This data frame contains the following columns:

temp temperature (in degrees Celsius)

visc viscosity (mPa s)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Byers and Williams (1987) Viscosities of Binary and Ternary Mixtures of Polynomatic Hydrocarbons. *Journal of Chemical and Engineering Data*, 32, 349-354.

Examples

```
data(p2.15)
attach(p2.15)
plot(visc ~ temp, pch=16)
visc.lm <- lm(visc ~ temp)
plot(visc.lm, which=1)
detach(p2.15)
```

p2.16

Data Set for Problem 2-16

Description

The p2.16 data frame has 33 observations on the pressure in a tank the volume of liquid.

Usage

```
data(p2.16)
```

Format

This data frame contains the following columns:

volume volume of liquid

pressure pressure in the tank

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Carroll and Spiegelman (1986) The Effects of Ignoring Small Measurement Errors in Precision Instrument Calibration. Journal of Quality Technology, 18, 170-173.

Examples

```
data(p2.16)
attach(p2.16)
plot(pressure ~ volume, pch=16)
pressure.lm <- lm(pressure ~ volume)
plot(pressure.lm, which=1)
summary(pressure.lm)
detach(p2.16)
```

p2.7

Data Set for Problem 2-7

Description

The p2.7 data frame has 20 observations on the purity of oxygen produced by a fractionation process. It is thought that oxygen purity is related to the percentage of hydrocarbons in the main condenser of the processing unit.

Usage

```
data(p2.7)
```

Format

This data frame contains the following columns:

purity oxygen purity (percentage)

hydro hydrocarbon (percentage)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p2.7)
attach(p2.7)
purity.lm <- lm(purity ~ hydro)
summary(purity.lm)
# confidence interval for mean purity at 1% hydrocarbon:
predict(purity.lm, newdata=data.frame(hydro = 1.00), interval="confidence")
detach(p2.7)
```

p2.9

Data Set for Problem 2-9

Description

The p2.9 data frame has 25 rows and 2 columns. See help on `softdrink` for details.

Usage

```
data(p2.9)
```

Format

This data frame contains the following columns:

y a numeric vector

x a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p2.9)
```

p4.18

Data Set for Problem 4-18

Description

The p4.18 data frame has 13 observations on an experiment to produce a synthetic analogue to jojoba oil.

Usage

```
data(p4.18)
```

Format

This data frame contains the following columns:

x1 reaction temperature

x2 initial amount of catalyst

x3 pressure

y yield

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Coteron, Sanchez, Matinez, and Aracil (1993) Optimization of the Synthesis of an Analogue of Jojoba Oil Using a Fully Central Composite Design. Canadian Journal of Chemical Engineering.

Examples

```
data(p4.18)
y.lm <- lm(y ~ x1 + x2 + x3, data=p4.18)
summary(y.lm)
y.lm <- lm(y ~ x1, data=p4.18)
```

p4.19

Data Set for Problem 4-19

Description

The p4.19 data frame has 14 observations on a designed experiment studying the relationship between abrasion index for a tire tread compound and three factors.

Usage

```
data(p4.19)
```

Format

This data frame contains the following columns:

- x1** hydrated silica level
- x2** silane coupling agent level
- x3** sulfur level
- y** abrasion index for a tire tread compound

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Derringer and Suich (1980) Simultaneous Optimization of Several Response Variables. Journal of Quality Technology.

Examples

```
data(p4.19)
attach(p4.19)
y.lm <- lm(y ~ x1 + x2 + x3)
summary(y.lm)
plot(y.lm, which=1)
y.lm <- lm(y ~ x1)
detach(p4.19)
```

p4.20

Data Set for Problem 4-20

Description

The p4.20 data frame has 26 observations on a designed experiment to determine the influence of five factors on the whiteness of rayon.

Usage

```
data(p4.20)
```

Format

This data frame contains the following columns:

acidtemp acid bath temperature

acidconc cascade acid concentration

watertemp water temperature

sulfconc sulfide concentration

amtbl amount of chlorine bleach

y a measure of the whiteness of rayon

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Myers and Montgomery (1995) Response Surface Methodology, pp. 267-268.

Examples

```
data(p4.20)
y.lm <- lm(y ~ acidtemp, data=p4.20)
summary(y.lm)
```

p5.1

Data Set for Problem 5-1

Description

The p5.1 data frame has 8 observations on the impact of temperature on the viscosity of toluene-tetralin blends.

Usage

```
data(p5.1)
```

Format

This data frame contains the following columns:

temp temperature

visc viscosity

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Byers and Williams (1987) Viscosities of Binary and Ternary Mixtures of Polyaromatic Hydrocarbons. Journal of Chemical and Engineering Data, 32, 349-354.

Examples

```
data(p5.1)
plot(p5.1)
```

p5.10

Data Set for Problem 5-10

Description

The p5.10 data frame has 27 observations on the effect of three factors on a printing machine's ability to apply coloring inks on package labels.

Usage

```
data(p5.10)
```

Format

This data frame contains the following columns:

x1 speed
x2 pressure
x3 distance
yi1 response 1
yi2 response 2
yi3 response 3
ybar.i average response
si standard deviation of the 3 responses

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.10)
attach(p5.10)
y.lm <- lm(ybar.i ~ x1 + x2 + x3)
plot(y.lm, which=1)
detach(p5.10)
```

p5.11

Data Set for Problem 5-11

Description

The p5.11 data frame has 8 observations on an experiment with a catapult.

Usage

```
data(p5.11)
```

Format

This data frame contains the following columns:

x1 hook
x2 arm length
x3 start angle
x4 stop angle
yi1 response 1
yi2 response 2
yi3 response 3

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.11)
attach(p5.11)
ybar.i <- apply(p5.11[,5:7], 1, mean)
sd.i <- apply(p5.11[,5:7], 1, sd)
y.lm <- lm(ybar.i ~ x1 + x2 + x3 + x4)
plot(y.lm, which=1)
detach(p5.11)
```

p5.2

Data Set for Problem 5-2

Description

The p5.2 data frame has 11 observations on the vapor pressure of water for various temperatures.

Usage

```
data(p5.2)
```

Format

This data frame contains the following columns:

temp temperature (K)

vapor vapor pressure (mm Hg)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.2)
plot(p5.2)
```

p5.3

Data Set for Problem 5-3

Description

The p5.3 data frame has 12 observations on the number of bacteria surviving in a canned food product and the number of minutes of exposure to 300 degree Fahrenheit heat.

Usage

```
data(p5.3)
```

Format

This data frame contains the following columns:

bact number of surviving bacteria

min number of minutes of exposure

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.3)
plot(bact~min, data=p5.3)
```

p5.4

Data Set for Problem 5-4

Description

The p5.4 data frame has 8 observations on 2 variables.

Usage

```
data(p5.4)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.4)
plot(y ~ x, data=p5.4)
```

p5.5

Data Set for Problem 5-5

Description

The p5.5 data frame has 14 observations on the average number of defects per 10000 bottles due to stones in the bottle wall and the number of weeks since the last furnace overhaul.

Usage

```
data(p5.5)
```

Format

This data frame contains the following columns:

defects a numeric vector

weeks a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p5.5)
defects.lm <- lm(defects~weeks, data=p5.5)
plot(defects.lm, which=1)
```

p7.1

Data Set for Problem 7-1

Description

The p7.1 data frame has 10 observations on a predictor variable.

Usage

```
data(p7.1)
```

Format

This data frame contains the following columns:

x a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.1)
attach(p7.1)
x2 <- x^2
detach(p7.1)
```

p7.11

Data Set for Problem 7-11

Description

The p7.11 data frame has 11 observations on production cost versus production lot size.

Usage

```
data(p7.11)
```

Format

This data frame contains the following columns:

x production lot size

y average production cost per unit

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.11)
plot(y ~ x, data=p7.11)
```

p7.15

Data Set for Problem 7-15

Description

The p7.15 data frame has 6 observations on vapor pressure of water at various temperatures.

Usage

```
data(p7.15)
```

Format

This data frame contains the following columns:

y vapor pressure (mm Hg)

x temperature (degrees Celsius)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.15)
y.lm <- lm(y ~ x, data=p7.15)
plot(y ~ x, data=p7.15)
abline(coef(y.lm))
plot(y.lm, which=1)
```

p7.16

Data Set for Problem 7-16

Description

The p7.16 data frame has 26 observations on the observed mole fraction solubility of a solute at a constant temperature.

Usage

```
data(p7.16)
```

Format

This data frame contains the following columns:

y negative logarithm of the mole fraction solubility

x1 dispersion partial solubility

x2 dipolar partial solubility

x3 hydrogen bonding Hansen partial solubility

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

(1991) Journal of Pharmaceutical Sciences 80, 971-977.

Examples

```
data(p7.16)  
pairs(p7.16)
```

p7.19

Data Set for Problem 7-19

Description

The p7.19 data frame has 10 observations on the concentration of green liquor and paper machine speed from a kraft paper machine.

Usage

```
data(p7.19)
```

Format

This data frame contains the following columns:

y green liquor (g/l)

x paper machine speed (ft/min)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

(1986) Tappi Journal.

Examples

```
data(p7.19)
y.lm <- lm(y ~ x + I(x^2), data=p7.19)
summary(y.lm)
```

p7.2

Data Set for Problem 7-2

Description

The p7.2 data frame has 10 observations on solid-fuel rocket propellant weight loss.

Usage

```
data(p7.2)
```

Format

This data frame contains the following columns:

x months since production

y weight loss (kg)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.2)
y.lm <- lm(y ~ x + I(x^2), data=p7.2)
summary(y.lm)
plot(y ~ x, data=p7.2)
```

p7.4

Data Set for Problem 7-4

Description

The p7.4 data frame has 12 observations on two variables.

Usage

```
data(p7.4)
```

Format

This data frame contains the following columns:

x a numeric vector

y a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.4)
y.lm <- lm(y ~ x + I(x^2), data = p7.4)
summary(y.lm)
```

p7.6

Data Set for Problem 7-6

Description

The p7.6 data frame has 12 observations on softdrink carbonation.

Usage

```
data(p7.6)
```

Format

This data frame contains the following columns:

y carbonation

x1 temperature

x2 pressure

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p7.6)
y.lm <- lm(y ~ x1 + I(x1^2) + x2 + I(x2^2) + I(x1*x2), data=p7.6)
summary(y.lm)
```

p8.11

Data Set for Problem 8-11

Description

The p8.11 data frame has 25 observations on the tensile strength of synthetic fibre used for men's shirts.

Usage

```
data(p8.11)
```

Format

This data frame contains the following columns:

y tensile strength

percent percentage of cotton

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Montgomery (2001)

Examples

```
data(p8.11)
y.lm <- lm(y ~ percent, data=p8.11)
model.matrix(y.lm)
```

p8.3

Data Set for Problem 8-3

Description

The p8.3 data frame has 25 observations on delivery times taken by a vending machine route driver.

Usage

```
data(p8.3)
```

Format

This data frame contains the following columns:

y delivery time (in minutes)

x1 number of cases of product stocked

x2 distance walked by route driver

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(p8.3)  
pairs(p8.3)
```

p9.10

Data Set for Problem 9-10

Description

The p9.10 data frame has 31 observations on the rut depth of asphalt pavements prepared under different conditions.

Usage

```
data(p9.10)
```

Format

This data frame contains the following columns:

y change in rut depth/million wheel passes (log scale)

x1 viscosity (log scale)

x2 percentage of asphalt in surface course

x3 percentage of asphalt in base course

x4 indicator

x5 percentage of fines in surface course

x6 percentage of voids in surface course

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Gorman and Toman (1966)

Examples

```
data(p9.10)
pairs(p9.10)
```

pathoeg

Pathological Example

Description

Artificial regression data which causes stepwise regression with AIC to produce a highly non-parsimonious model. The true model used to simulate the data has only one real predictor (x8).

Usage

```
pathoeg
```

Format

This data frame contains the following columns:

x1 a numeric vector

x2 a numeric vector

x3 a numeric vector

x4 a numeric vector

x5 a numeric vector
x6 a numeric vector
x7 a numeric vector
x8 a numeric vector
x9 a numeric vector
y a numeric vector

PRESS

PRESS statistic

Description

Computation of Allen's PRESS statistic for an lm object.

Usage

PRESS(x)

Arguments

x An lm object

Value

Allen's PRESS statistic.

Author(s)

W.J. Braun

See Also

lm

Examples

```
data(p4.18)
attach(p4.18)
y.lm <- lm(y ~ x1 + I(x1^2))
PRESS(y.lm)
detach(p4.18)
```

`qqANOVA`*QQ Plot for Analysis of Variance*

Description

This function is used to display the weight of the evidence against null main effects in data coming from a 1 factor design, using a QQ plot. In practice this method is often called via the function GANOVA.

Usage

```
qqANOVA(x, y, plot.it = TRUE, xlab = deparse(substitute(x)),  
        ylab = deparse(substitute(y)), ...)
```

Arguments

<code>x</code>	numeric vector of errors
<code>y</code>	numeric vector of scaled responses
<code>plot.it</code>	logical vector indicating whether to plot or not
<code>xlab</code>	character, x-axis label
<code>ylab</code>	character, y-axis label
<code>...</code>	any other arguments for the plot function

Value

A QQ plot is drawn.

Author(s)

W. John Braun

`quadline`*Quadratic Overlay*

Description

Overlays a quadratic curve to a fitted quadratic model.

Usage

```
quadline(lm.obj, ...)
```


Arguments

lm.obj A lm object (a quadratic fit)
 ... Other arguments to the lines function; e.g. col

Value

The function superimposes a quadratic curve onto an existing scatterplot.

Author(s)

W.J. Braun

See Also

lm

Examples

```
data(p4.18)
attach(p4.18)
y.lm <- lm(y ~ x1 + I(x1^2))
plot(x1, y)
quadline(y.lm)
detach(p4.18)
```

Qyplot

Analysis of Variance Plot for Regression

Description

This function analyzes regression data graphically. It allows visualization of the usual F-test for significance of regression.

Usage

```
Qyplot(X, y, plotIt=TRUE, sortTrt=FALSE, type="hist", includeIntercept=TRUE, labels=FALSE)
```

Arguments

X The design matrix.
 y A numeric vector containing the response.
 plotIt Logical: if TRUE, a graph is drawn.
 sortTrt Logical: if TRUE, an attempt is made at sorting the predictor effects in descending order.
 type "QQ" or "hist"

`includeIntercept` Logical: if TRUE, the intercept effect is plotted; otherwise, it is omitted from the plot.

`labels` logical: if TRUE, names of predictor variables are used as labels; otherwise, the design matrix column numbers are used as labels

Value

A QQ-plot or a histogram and rugplot, or a list if `plotIt=FALSE`

Author(s)

W. John Braun

Source

Braun, W.J. 2013. Regression Analysis and the QR Decomposition. Preprint.

Examples

```
# Example 1
X <- p4.18[,-4]
y <- p4.18[,4]
Qyplot(X, y, type="hist", includeIntercept=FALSE)
title("Evidence of Regression in the Jojoba Oil Data")
# Example 2
set.seed(4571)
Z <- matrix(rnorm(400), ncol=10)
A <- matrix(rnorm(81), ncol=9)
simdata <- data.frame(Z[,1], crossprod(t(Z[, -1]), A))
names(simdata) <- c("y", paste("x", 1:9, sep=""))
Qyplot(simdata[, -1], simdata[, 1], type="hist", includeIntercept=FALSE)
title("Evidence of Regression in Simulated Data Set")
# Example 3
Qyplot(table.b1[, -1], table.b1[, 1], type="hist", includeIntercept=FALSE)
title("Evidence of Regression in NFL Data Set")
# An example where stepwise AIC selects the complement
# of the set of variables that are actually in the true model:
X <- pathoeg[, -10]
y <- pathoeg[, 10]
par(mfrow=c(2,2))
Qyplot(X, y)
Qyplot(X, y, sortTrt=TRUE)
Qyplot(X, y, type="QQ")
Qyplot(X, y, sortTrt=TRUE, type="QQ")
X <- table.b1[, -1] # NFL data
y <- table.b1[, 1]
Qyplot(X, y)
```

`softdrink`*Softdrink Data*

Description

The softdrink data frame has 25 rows and 3 columns.

Usage

```
data(softdrink)
```

Format

This data frame contains the following columns:

y a numeric vector

x1 a numeric vector

x2 a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(softdrink)
```

`solar`*Solar Data*

Description

The solar data frame has 29 rows and 6 columns.

Usage

```
data(solar)
```

Format

This data frame contains the following columns:

total.heat.flux a numeric vector

insolation a numeric vector

focal.pt.east a numeric vector

focal.pt.south a numeric vector

focal.pt.north a numeric vector

time.of.day a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(solar)
```

stain

Stain Removal Data

Description

Data on an experiment to remove ketchup stains from white cotton fabric by soaking the stained fabric in one of five substrates for one hour. Remaining stains were scored visually and subjectively according to a 6-point scale (0 = completely clean, 5 = no change) The `stain` data frame has 15 rows and 2 columns.

Usage

```
data(stain)
```

Format

This data frame contains the following columns:

treatment a factor

response a numeric vector

Examples

```
data(stain)
```

table.b1	<i>Table B1</i>
----------	-----------------

Description

The table.b1 data frame has 28 observations on National Football League 1976 Team Performance.

Usage

```
data(table.b1)
```

Format

This data frame contains the following columns:

y Games won in a 14 game season

x1 Rushing yards

x2 Passing yards

x3 Punting average (yards/punt)

x4 Field Goal Percentage (FGs made/FGs attempted)

x5 Turnover differential (turnovers acquired - turnovers lost)

x6 Penalty yards

x7 Percent rushing (rushing plays/total plays)

x8 Opponents' rushing yards

x9 Opponents' passing yards

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b1)
attach(table.b1)
y.lm <- lm(y ~ x2 + x7 + x8)
summary(y.lm)
# over-all F-test:
y.null <- lm(y ~ 1)
anova(y.null, y.lm)
# partial F-test for x7:
y7.lm <- lm(y ~ x2 + x8)
anova(y7.lm, y.lm)
detach(table.b1)
```

`table.b10`*Table B10*

Description

The `table.b10` data frame has 40 observations on kinematic viscosity of a certain solvent system.

Usage

```
data(table.b10)
```

Format

This data frame contains the following columns:

x1 Ratio of 2-methoxyethanol to 1,2-dimethoxyethane

x2 Temperature (in degrees Celsius)

y Kinematic viscosity (.000001 m²/s)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Viscosimetric Studies on 2-Methoxyethanol + 1, 2-Dimethoxyethane Binary Mixtures from -10 to 80C. Canadian Journal of Chemical Engineering, 75, 494-501.

Examples

```
data(table.b10)
attach(table.b10)
y.lm <- lm(y ~ x1 + x2)
summary(y.lm)
detach(table.b10)
```

table.b11	<i>Table B11</i>
-----------	------------------

Description

The table.b11 data frame has 38 observations on the quality of Pinot Noir wine.

Usage

```
data(table.b11)
```

Format

This data frame contains the following columns:

Clarity a numeric vector

Aroma a numeric vector

Body a numeric vector

Flavor a numeric vector

Oakiness a numeric vector

Quality a numeric vector

Region a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b11)
attach(table.b11)
Quality.lm <- lm(Quality ~ Clarity + Aroma + Body + Flavor + Oakiness +
  factor(Region))
summary(Quality.lm)
detach(table.b11)
```

table.b12	<i>Table B12</i>
-----------	------------------

Description

The table.b12 data frame has 32 rows and 6 columns.

Usage

```
data(table.b12)
```

Format

This data frame contains the following columns:

temp a numeric vector

soaktime a numeric vector

soakpct a numeric vector

difftime a numeric vector

diffpct a numeric vector

pitch a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b12)
```

table.b13	<i>Table B13</i>
-----------	------------------

Description

The table.b13 data frame has 40 rows and 7 columns.

Usage

```
data(table.b13)
```


Format

This data frame contains the following columns:

y a numeric vector
x1 a numeric vector
x2 a numeric vector
x3 a numeric vector
x4 a numeric vector
x5 a numeric vector
x6 a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b13)
```

table.b14

Table B14

Description

The table.b14 data frame has 25 observations on the transient points of an electronic inverter.

Usage

```
data(table.b14)
```

Format

This data frame contains the following columns:

x1 width of the NMOS Device
x2 length of the NMOS Device
x3 width of the PMOS Device
x4 length of the PMOS Device
x5 a numeric vector
y transient point of PMOS-NMOS Inverters

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b14)
y.lm <- lm(y ~ x1 + x2 + x3 + x4, data=table.b14)
plot(y.lm, which=1)
```

table.b2

*Table B2***Description**

The table.b2 data frame has 29 rows and 6 columns.

Usage

```
data(table.b2)
```

Format

This data frame contains the following columns:

y a numeric vector

x1 a numeric vector

x2 a numeric vector

x3 a numeric vector

x4 a numeric vector

x5 a numeric vector

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

Examples

```
data(table.b2)
```

table.b3	<i>Table B3</i>
----------	-----------------

Description

The table.b3 data frame has observations on gasoline mileage performance for 32 different automobiles.

Usage

```
data(table.b3)
```

Format

This data frame contains the following columns:

y Miles/gallon

x1 Displacement (cubic in)

x2 Horsepower (ft-lb)

x3 Torque (ft-lb)

x4 Compression ratio

x5 Rear axle ratio

x6 Carburetor (barrels)

x7 No. of transmission speeds

x8 Overall length (in)

x9 Width (in)

x10 Weight (lb)

x11 Type of transmission (1=automatic, 0>manual)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Motor Trend, 1975

Examples

```
data(table.b3)
attach(table.b3)
y.lm <- lm(y ~ x1 + x6)
summary(y.lm)
# testing for the significance of the regression:
y.null <- lm(y ~ 1)
anova(y.null, y.lm)
# 95% CI for mean gas mileage:
predict(y.lm, newdata=data.frame(x1=275, x6=2), interval="confidence")
# 95% PI for gas mileage:
predict(y.lm, newdata=data.frame(x1=275, x6=2), interval="prediction")
detach(table.b3)
```

table.b4

Table B4

Description

The table.b4 data frame has 24 observations on property valuation.

Usage

```
data(table.b4)
```

Format

This data frame contains the following columns:

y sale price of the house (in thousands of dollars)

x1 taxes (in thousands of dollars)

x2 number of baths

x3 lot size (in thousands of square feet)

x4 living space (in thousands of square feet)

x5 number of garage stalls

x6 number of rooms

x7 number of bedrooms

x8 age of the home (in years)

x9 number of fireplaces

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Narula, S.C. and Wellington (1980) Prediction, Linear Regression and Minimum Sum of Relative Errors. *Technometrics*, 19, 1977.

Examples

```
data(table.b4)
attach(table.b4)
y.lm <- lm(y ~ x1 + x2 + x3 + x4 + x5 + x6 + x7 + x8 + x9)
summary(y.lm)
detach(table.b4)
```

table.b5

Data Set for Table B5

Description

The table.b5 data frame has 27 observations on liquefaction.

Usage

```
data(table.b5)
```

Format

This data frame contains the following columns:

- y** CO2
- x1** Space time (in min)
- x2** Temperature (in degrees Celsius)
- x3** Percent solvation
- x4** Oil yield (g/100g MAF)
- x5** Coal total
- x6** Solvent total
- x7** Hydrogen consumption

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) *Introduction to Linear Regression Analysis*. 3rd Edition, John Wiley and Sons.

References

(1978) Belle Ayr Liquefaction Runs with Solvent. *Industrial Chemical Process Design Development*, 17, 3.

Examples

```
data(table.b5)
attach(table.b5)
y.lm <- lm(y ~ x6 + x7)
summary(y.lm)
detach(table.b5)
```

table.b6

Data Set for Table B6

Description

The table.b6 data frame has 28 observations on a tube-flow reactor.

Usage

```
data(table.b6)
```

Format

This data frame contains the following columns:

y NbOCl3 concentration (g-mol/l)

x1 COCl2 concentration (g-mol/l)

x2 Space time (s)

x3 Molar density (g-mol/l)

x4 Mole fraction CO2

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

(1972) Kinetics of Chlorination of Niobium oxychloride by Phosgene in a Tube-Flow Reactor. Industrial and Engineering Chemistry, Process Design Development, 11(2).

Examples

```
data(table.b6)
# Partial Solution to Problem 3.9
attach(table.b6)
y.lm <- lm(y ~ x1 + x4)
summary(y.lm)
detach(table.b6)
```

`table.b7`*Data Set for Table B7*

Description

The `table.b7` data frame has 16 observations on oil extraction from peanuts.

Usage

```
data(table.b7)
```

Format

This data frame contains the following columns:

- x1** CO2 pressure (bar)
- x2** CO2 temperature (in degrees Celsius)
- x3** peanut moisture (percent by weight)
- x4** CO2 flow rate (L/min)
- x5** peanut particle size (mm)
- y** total oil yield

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Kilgo, M.B. An Application of Fractional Experimental Designs. Quality Engineering, 1, 19-23.

Examples

```
data(table.b7)
attach(table.b7)
# partial solution to Problem 3.11:
peanuts.lm <- lm(y ~ x1 + x2 + x3 + x4 + x5)
summary(peanuts.lm)
detach(table.b7)
```

`table.b8`*Table B8*

Description

The `table.b8` data frame has 36 observations on Clathrate formation.

Usage

```
data(table.b8)
```

Format

This data frame contains the following columns:

x1 Amount of surfactant (mass percentage)

x2 Time (min)

y Clathrate formation (mass percentage)

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Tanii, T., Minemoto, M., Nakazawa, K., and Ando, Y. Study on a Cool Storage System Using HCFC-14 lb Clathrate. Canadian Journal of Chemical Engineering, 75, 353-360.

Examples

```
data(table.b8)
attach(table.b8)
clathrate.lm <- lm(y ~ x1 + x2)
summary(clathrate.lm)
detach(table.b8)
```

`table.b9`*Data Set for Table B9*

Description

The `table.b9` data frame has 62 observations on an experimental pressure drop.

Usage

```
data(table.b9)
```

Format

This data frame contains the following columns:

- x1** Superficial fluid velocity of the gas (cm/s)
- x2** Kinematic viscosity
- x3** Mesh opening (cm)
- x4** Dimensionless number relating superficial fluid velocity of the gas to the superficial fluid velocity of the liquid
- y** Dimensionless factor for the pressure drop through a bubble cap

Source

Montgomery, D.C., Peck, E.A., and Vining, C.G. (2001) Introduction to Linear Regression Analysis. 3rd Edition, John Wiley and Sons.

References

Liu, C.H., Kan, M., and Chen, B.H. A Correlation of Two-Phase Pressure Drops in Screen-Plate Bubble Column. Canadian Journal of Chemical Engineering, 71, 460-463.

Examples

```
data(table.b9)
attach(table.b9)
# Partial Solution to Problem 3.13:
y.lm <- lm(y ~ x1 + x2 + x3 + x4)
summary(y.lm)
detach(table.b9)
```

tarimage	<i>target image</i>
----------	---------------------

Description

The tarimage is a list. Most of the values are 0, but there are small regions of 1's.

Usage

```
data(tarimage)
```

Format

This list contains the following elements:

x a numeric vector having 101 elements.

y a numeric vector having 101 elements.

xy a numeric matrix having 101 rows and columns

Examples

```
with(tarimage, image(x, y, xy))
```

tplot	<i>Graphical t Test for Regression</i>
-------	--

Description

This function analyzes regression data graphically. It allows visualization of the usual t-tests for individual regression coefficients.

Usage

```
tplot(X, y, plotIt=TRUE, type="hist", includeIntercept=TRUE)
```

Arguments

X The design matrix.

y A numeric vector containing the response.

plotIt Logical: if TRUE, a graph is drawn.

type "QQ" or "hist"

includeIntercept

Logical: if TRUE, the intercept effect is plotted; otherwise, it is omitted from the plot.

Value

A QQ-plot or a histogram and rugplot, or a list if plotIt=FALSE

Author(s)

W. John Braun

Examples

```
# Jojoba oil data set
X <- p4.18[,-4]
y <- p4.18[,4]
tplot(X, y, type="hist", includeIntercept=FALSE)
title("Tests for Individual Coefficients in the Jojoba Oil Regression")
# Simulated data set where none of the predictors are in the true model:
set.seed(4571)
Z <- matrix(rnorm(400), ncol=10)
A <- matrix(rnorm(81), ncol=9)
simdata <- data.frame(Z[,1], crossprod(t(Z[, -1]),A))
names(simdata) <- c("y", paste("x", 1:9, sep=""))
X <- simdata[,-1]
y <- simdata[,1]
tplot(X, y, type="hist", includeIntercept=FALSE)
title("Tests for Individual Coefficients for the Simulated Data Set")
# NFL Data set:
X <- table.b1[,-1]
y <- table.b1[,1]
tplot(X, y, type="hist", includeIntercept=FALSE)
title("Tests for Individual Coefficients for the NFL Data Set")
# Simulated Data set where x8 is the only predictor in the true model:
X <- pathoeg[,-10]
y <- pathoeg[,10]
par(mfrow=c(2,2))
tplot(X, y)
tplot(X, y, type="QQ")
```

Uplot

Plot of Multipliers in Regression ANOVA Plot

Description

This function graphically displays the coefficient multipliers used in the Regression Plot for the given predictor.

Usage

```
Uplot(X.qr, Xcolumn = 1, ...)
```

Arguments

<code>X.qr</code>	The design matrix or the QR decomposition of the design matrix.
<code>Xcolumn</code>	The column(s) of the design matrix under study; this can be either integer valued or a character string.
<code>...</code>	Additional arguments to <code>barchart</code> .

Value

A bar plot is displayed.

Author(s)

W. John Braun

Examples

```
# Jojoba oil data set
X <- p4.18[,-4]
Uplot(X, 1:4)
# NFL data set; see GFplot result first
X <- table.b1[,-1]
Uplot(X, c(2,3,9))
# In this example, x8 is the only predictor in
# the true model:
X <- pathoeg[,-10]
y <- pathoeg[,10]
pathoeg.F <- GFplot(X, y, plotIt=FALSE)
Uplot(X, "x8")
Uplot(X, 9) # same as above
Uplot(pathoeg.F$QR, 9) # same as above
X <- table.b1[,-1]
Uplot(X, c("x2", "x3", "x9"))
```

windWin80

Winnipeg Wind Speed

Description

The `windWin80` data frame has 366 observations on midnight and noon windspeed at the Winnipeg International Airport for the year 1980.

Usage

```
data(windWin80)
```

Format

This data frame contains the following columns:

h0 a numeric vector containing the wind speeds at midnight.

h12 a numeric vector containing the wind spees at the following noon.

Examples

```
data(windWin80)
ts.plot(windWin80$h12^2)
```

Index

*Topic **datasets**

BioOxyDemand, 3
cement, 4
cigbutts, 5
gasdata, 6
Juliet, 9
motor, 11
noisyimage, 11
oldwash, 12
p11.12, 13
p11.15, 14
p12.11, 14
p12.12, 15
p12.8, 16
p13.1, 17
p13.16, 17
p13.2, 18
p13.20, 19
p13.3, 19
p13.4, 20
p13.5, 21
p13.6, 21
p13.7, 22
p14.1, 23
p14.2, 23
p15.4, 24
p2.10, 25
p2.12, 25
p2.13, 26
p2.14, 27
p2.15, 28
p2.16, 29
p2.7, 30
p2.9, 30
p4.18, 31
p4.19, 32
p4.20, 33
p5.1, 34
p5.10, 34

p5.11, 35
p5.2, 36
p5.3, 37
p5.4, 37
p5.5, 38
p7.1, 39
p7.11, 39
p7.15, 40
p7.16, 41
p7.19, 41
p7.2, 42
p7.4, 43
p7.6, 43
p8.11, 44
p8.3, 45
p9.10, 45
pathoeg, 46
softdrink, 51
solar, 51
stain, 52
table.b1, 53
table.b10, 54
table.b11, 55
table.b12, 56
table.b13, 56
table.b14, 57
table.b2, 58
table.b3, 59
table.b4, 60
table.b5, 61
table.b6, 62
table.b7, 63
table.b8, 64
table.b9, 65
tarimage, 66
windWin80, 68

*Topic **graphics**

GANOVA, 5
GFplot, 7

- GRegplot, 8
- qqANOVA, 48
- Qyplot, 49
- tplot, 66
- Uplot, 67
- *Topic **models**
 - PRESS, 47
 - quadline, 48
- BioOxyDemand, 3
- cement, 4
- cigbutts, 5
- GANOVA, 5
- gasdata, 6
- GFplot, 7
- GRegplot, 8
- Juliet, 9
- motor, 11
- noisyimage, 11
- oldwash, 12
- p11.12, 13
- p11.15, 14
- p12.11, 14
- p12.12, 15
- p12.8, 16
- p13.1, 17
- p13.16, 17
- p13.2, 18
- p13.20, 19
- p13.3, 19
- p13.4, 20
- p13.5, 21
- p13.6, 21
- p13.7, 22
- p14.1, 23
- p14.2, 23
- p15.4, 24
- p2.10, 25
- p2.12, 25
- p2.13, 26
- p2.14, 27
- p2.15, 28
- p2.16, 29
- p2.7, 30
- p2.9, 30
- p4.18, 31
- p4.19, 32
- p4.20, 33
- p5.1, 34
- p5.10, 34
- p5.11, 35
- p5.2, 36
- p5.3, 37
- p5.4, 37
- p5.5, 38
- p7.1, 39
- p7.11, 39
- p7.15, 40
- p7.16, 41
- p7.19, 41
- p7.2, 42
- p7.4, 43
- p7.6, 43
- p8.11, 44
- p8.3, 45
- p9.10, 45
- pathoeg, 46
- PRESS, 47
- qqANOVA, 48
- quadline, 48
- Qyplot, 49
- softdrink, 51
- solar, 51
- stain, 52
- table.b1, 53
- table.b10, 54
- table.b11, 55
- table.b12, 56
- table.b13, 56
- table.b14, 57
- table.b2, 58
- table.b3, 59
- table.b4, 60
- table.b5, 61
- table.b6, 62
- table.b7, 63
- table.b8, 64
- table.b9, 65
- tarimage, 11, 66

tplot, [66](#)

Uplot, [67](#)

windWin80, [68](#)