

Package ‘eyetrackingR’

February 14, 2018

Type Package

Version 0.1.7

Title Eye-Tracking Data Analysis

Description A set of tools that address tasks along the pipeline from raw data to analysis and visualization for eye-tracking data. Offers several popular types of analyses, including linear and growth curve time analyses, onset-contingent reaction time analyses, as well as several non-parametric bootstrapping approaches.

URL <http://eyetracking-r.com>

BugReports <https://github.com/jwdink/eyetrackingR/issues>

Date 2018-2-14 12:15:02

Depends R (>= 3.2.0), dplyr (>= 0.7.4)

License MIT + file LICENSE

LazyData true

Imports broom (>= 0.3.7), ggplot2 (>= 2.0), lazyeval (>= 0.1.10), zoo (>= 1.7-12), tidyr (>= 0.3.1), purrr (>= 0.2.4)

Suggests pbapply, knitr, lme4 (>= 1.1-10), Matrix, testthat, rmarkdown, doMC, foreach

VignetteBuilder knitr

RoxygenNote 6.0.1

NeedsCompilation no

Author Jacob Dink [aut, cre],
Brock Ferguson [aut]

Maintainer Jacob Dink <jacobwdink@gmail.com>

Repository CRAN

Date/Publication 2018-02-14 21:41:27 UTC

R topics documented:

add_aoi	2
analyze_boot_splines	3
analyze_time_bins	5
analyze_time_clusters	6
clean_by_trackloss	8
describe_data	9
eyetrackingR	10
get_time_clusters	11
make_boot_splines_data	11
make_eyetrackingr_data	13
make_onset_data	14
make_switch_data	15
make_time_cluster_data	16
make_time_sequence_data	18
make_time_window_data	20
plot.bin_analysis	22
plot.boot_splines_analysis	22
plot.boot_splines_data	23
plot.cluster_analysis	24
plot.eyetrackingR_data_summary	24
plot.onset_data	25
plot.switch_data	25
plot.time_cluster_data	26
plot.time_sequence_data	26
plot.time_window_data	28
print.cluster_analysis	29
reclass	29
simulate_eyetrackingr_data	30
subset_by_window	31
summary.bin_analysis	33
summary.boot_splines_analysis	33
summary.cluster_analysis	34
summary.time_cluster_data	34
trackloss_analysis	35
word_recognition	35
Index	37

add_aoi	<i>Add an area-of-interest to your dataset, based on x-y coordinates and the AOI rectangle.</i>
---------	---

Description

Eyetracking-R requires that there is a column for each area-of-interest, specifying whether the gaze is within that area for each sample. This function creates an AOI column if needed.

Usage

```
add_aoi(data, aoi_dataframe, x_col, y_col, aoi_name, x_min_col = "L",
        x_max_col = "R", y_min_col = "T", y_max_col = "B")
```

Arguments

data	Your data
aoi_dataframe	A dataframe specifying the bounding-box for the AOI
x_col, y_col	What are the column names for the x and y coordinates in your dataset?
aoi_name	What is the name of this AOI?
x_min_col, x_max_col	What are the column names for the left and right edge of the AOI-bounding box? Default "L","R"
y_min_col, y_max_col	What are the column names for the top and bottom edge of the AOI-bounding box? Default "T","B"

Details

Many eyetracking software packages export your data with a column corresponding to each AOI; however, if your software does not do this, or if you had to define or revise your AOIs after running the experiment, then this function will add the necessary AOI columns for you. The function takes two dataframes: (1) your original data, (2) a dataframe specifying the bounding box for the AOI. The latter can specify a different bounding box for each trial, each subject, each image, or even each video-frame– anything you like. The two dataframes are simply joined by matching any columns they have in common (case sensitive!), so if there's a unique AOI for each "Trial" in the aoi_dataframe, and there's a "Trial" column in the data dataframe, then the unique AOI coordinates for each trial will be used.

Value

Dataset with a new column indicating whether gaze is in the AOI

analyze_boot_splines *Estimate confidence intervals for bootstrapped splines data*

Description

Deprecated. Performing this analysis should be done by calling analyze_time_bins(test="boot_splines").

Usage

```
analyze_boot_splines(data)

## S3 method for class 'boot_splines_data'
analyze_boot_splines(data)
```

Arguments

data The output of the boot_splines_data function

Details

Estimates a confidence interval over the difference between means (within- or between-subjects) from boot_splines_data. Confidence intervals are derived from the alpha argument in boot_splines_data (e.g., alpha = .05, CI=(.025,.975); alpha=.01, CI=(.005,.0995))

Value

A dataframe indicating means and CIs for each time-bin

Methods (by class)

- boot_splines_data:

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate','Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE )
response_window <- subset_by_window(data, window_start_time = 15500, window_end_time = 21000,
                                   rezero = FALSE)
response_time <- make_time_sequence_data(response_window, time_bin_size = 500, aois = "Animate",
                                         predictor_columns = "Sex",
                                         summarize_by = "ParticipantName")

# bootstrap resample 500 smoothed splines from the dataset,
# comparing females versus females at an alpha of .05
df_bootstrapped <- make_boot_splines_data(response_time,
                                         predictor_column = 'Sex',
                                         within_subj = FALSE,
                                         bs_samples = 500,
                                         alpha = .05,
                                         smoother = "smooth.spline")

# analyze the divergences that occurred
boot_splines_analysis <- analyze_boot_splines(df_bootstrapped)
summary(boot_splines_analysis)
```

```
analyze_time_bins      analyze_time_bins()
```

Description

Runs a test on each time-bin of `time_sequence_data`. Supports `t.test`, `wilcox.test`, `(g)lm`, and `(g)lmer`. Also includes support for the "bootstrapped-splines" test (see `?make_boot_splines_data` and [the divergence vignette](#) for more info). By default, this function uses 'proportion-looking' (Prop) as the DV, which can be changed by manually specifying the formula. Results can be plotted to see how test-results or parameters estimates vary over time. P-values can be adjusted for multiple comparisons with `p_adjust_method`.

Usage

```
analyze_time_bins(data, ...)

## S3 method for class 'time_sequence_data'
analyze_time_bins(data, predictor_column, test,
  threshold = NULL, alpha = NULL, aoi = NULL, formula = NULL,
  treatment_level = NULL, p_adjust_method = "none", quiet = FALSE, ...)
```

Arguments

<code>data</code>	The output of the 'make_time_sequence_data' function
<code>...</code>	Any other arguments to be passed to the selected 'test' function (e.g., <code>paired</code> , <code>var.equal</code> , etc.)
<code>predictor_column</code>	The variable whose test statistic you are interested in. If you are not interested in a predictor, but the intercept, you can enter "intercept" for this argument. Interaction terms are not currently supported.
<code>test</code>	What type of test should be performed in each time bin? Supports <code>t.test</code> , <code>wilcox.test</code> , <code>(g)lm</code> , and <code>(g)lmer</code> . Also includes support for the "bootstrapped-splines" test (see <code>?make_boot_splines_data</code> and the divergence vignette for more info).
<code>threshold</code>	Value of statistic used in determining significance
<code>alpha</code>	Alpha value for determining significance, ignored if <code>threshold</code> is given
<code>aoi</code>	Which AOI should be analyzed? If not specified (and dataframe has multiple AOIs), then AOI should be a predictor/covariate in your model (so 'formula' needs to be specified).
<code>formula</code>	What formula should be used for the test? Optional for all but <code>(g)lmer</code> , if unset will use <code>Prop ~ [predictor_column]</code> . Change this if you want to use a custom DV.
<code>treatment_level</code>	If your predictor is a factor, regression functions like 'lm' and 'lmer' by default will treatment-code it. One option is to sum-code this predictor yourself before

entering it into this function. Another is to use the ‘treatment_level’ argument, which specifies the level of the predictor. For example, you are testing a model where ‘Target’ is a predictor, which has two levels, ‘Animate’ and ‘Inanimate’. R will code ‘Animate’ as the reference level, and code ‘Inanimate’ as the treatment level. You’d therefore want to set ‘treatment_level = Inanimate’.

`p_adjust_method` Method to adjust p.values for multiple corrections (default="none"). See `p.adjust.methods`.

`quiet` Should messages and progress bars be suppressed? Default is to show

Value

A dataframe indicating the results of the test at each time-bin.

Methods (by class)

- `time_sequence_data`:

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
response_time <- make_time_sequence_data(data, time_bin_size = 250,
                                         predictor_columns = c("MCDI_Total"),
                                         aois = "Animate", summarize_by = "ParticipantName")
tb_analysis <- analyze_time_bins(response_time, predictor_column = "MCDI_Total",
                                test = "lm", threshold = 2)
summary(tb_analysis)
```

`analyze_time_clusters` *Bootstrap analysis of time-clusters.*

Description

Takes data whose time bins have been clustered by test-statistic (using the `make_time_cluster_data` function) and performs a permutation test (Maris & Oostenveld, 2007). This analysis takes a summed statistic for each cluster, and compares it to the "null" distribution of sum statistics obtained by shuffling/resampling the data and extracting the largest cluster from each resample.

Usage

```
analyze_time_clusters(data, ...)

## S3 method for class 'time_cluster_data'
analyze_time_clusters(data, within_subj,
  samples = 2000, formula = NULL, shuffle_by = NULL, parallel = FALSE,
  quiet = FALSE, ...)
```

Arguments

data	The output of the make_time_cluster_data function
...	Other args for to selected 'test' function; should be identical to those passed to make_time_cluster_data function
within_subj	Logical indicating whether to perform within-subjects bootstrap resampling.
samples	How many iterations should be performed in the bootstrap resampling procedure?
formula	Formula for test. Should be identical to that passed to make_time_cluster_data fxn (if arg ignored there, can be ignored here)
shuffle_by	Along which attribute should the data be resampled? Default is the predictor column. But if the predictor_column is numeric *and* within-subjects, then observations with the same predictor value could nevertheless correspond to distinct conditions/categories that should be shuffled separately. For example, when using vocabulary scores to predict looking behavior, a participant might get identical vocab scores for verbs and nouns; these are nevertheless distinct categories that should be re-assigned separately when bootstrap-resampling data. The 'shuffle_by' argument allows you to specify a column which indicates these kinds of distinct categories that should be resampled separately– but it's only needed if you've specified a numeric *and* within-subjects predictor column.
parallel	Use foreach for speed boost? By default off. May not work on Windows.
quiet	Display progress bar/messages? No progress bar when parallel=TRUE.

Value

A cluster-analysis object, which can be plotted and summarized to examine which temporal periods show a significant effect of the predictor variable

Methods (by class)

- time_cluster_data:

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
  participant_column = "ParticipantName",
  trial_column = "Trial",
  time_column = "TimeFromTrialOnset",
```

```

        trackloss_column = "TrackLoss",
        aoi_columns = c('Animate', 'Inanimate'),
        treat_non_aoi_looks_as_missing = TRUE )
response_window <- subset_by_window(data, window_start_time = 15500, window_end_time = 21000,
                                   rezero = FALSE)
response_time <- make_time_sequence_data(response_window, time_bin_size = 500, aois = "Animate",
                                         predictor_columns = "Sex")

time_cluster_data <- make_time_cluster_data(data = response_time, predictor_column = "SexM",
                                           aoi = "Animate", test = "lmer",
                                           threshold = 1.5,
                                           formula = LogitAdjusted ~ Sex + (1|Trial) + (1|ParticipantName))
summary(time_cluster_data)
plot(time_cluster_data)

# analyze time clusters in a non-parametric analysis
## Not run:
tc_analysis <- analyze_time_clusters(time_cluster_data, within_subj = FALSE,
                                    samples = 2000)

plot(tc_analysis)
summary(tc_analysis)

## End(Not run)

```

clean_by_trackloss *Clean data by removing high-trackloss trials/subjects.*

Description

Remove trials/participants with too much trackloss, with a customizable threshold.

Usage

```
clean_by_trackloss(data, participant_prop_thresh = 1, trial_prop_thresh = 1,
                  window_start_time = -Inf, window_end_time = Inf)
```

Arguments

data	Data already run through make_eyetrackingr_data
participant_prop_thresh	Maximum proportion of trackloss for participants
trial_prop_thresh	Maximum proportion of trackloss for trials
window_start_time, window_end_time	Time-window within which you want trackloss analysis to be based. Allows you to keep the entire trial window for data, but clean based on the trackloss within a subset of it

Value

Cleaned data

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)

# scrub all trials with greater than 25% trackloss, and all
# participants with greater than 25% trackloss on average
# during the timeperiod 15500-2100
data_clean <- clean_by_trackloss(data,
                                 participant_prop_thresh = .25,
                                 trial_prop_thresh = .25,
                                 window_start_time = 15500,
                                 window_end_time = 21000
)

# scrub all trials with greater than 25% trackloss, but leave participants with a high average
data_clean <- clean_by_trackloss(data,
                                 trial_prop_thresh = .25,
                                 window_start_time = 15500,
                                 window_end_time = 21000
)
```

describe_data

Describe dataset

Description

Returns descriptive statistics about a column of choice. A simple convenience function that wraps `dplyr::group_by` and `dplyr::summarize`, allowing a quick glance at the data.

Usage

```
describe_data(data, describe_column, group_columns, quantiles = c(0.025,
0.975))
```

Arguments

<code>data</code>	Data already run through <code>make_eyetrackingr_data</code>
<code>describe_column</code>	The column to return descriptive statistics about.
<code>group_columns</code>	Any columns to group by when calculating descriptive statistics (e.g., participants, conditions, etc.)
<code>quantiles</code>	Numeric vector of length two with quantiles to compute (default: <code>c(.025, .975)</code>).

Value

A dataframe giving descriptive statistics for the `describe_column`, including mean, SD, var, min, max, and number of trials

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
describe_data(data, describe_column = "Animate", group_columns = "ParticipantName")
```

 eyetrackingR

eyetrackingR: A package for cleaning, analyzing, and visualizing eye-tracking datasets

Description

This package addresses tasks along the pipeline from raw eye-tracking data to analysis and visualization. It offers several popular types of analyses, including linear and growth curve time analyses, onset-contingent reaction time analyses, and cluster mass analyses, as well as novel non-parametric approaches to time-series data.

Details

For more information and tutorials, visit eyetrackingR.com.

get_time_clusters *Get information about the clusters in a cluster-analysis*

Description

Get information about the clusters in a cluster-analysis

Usage

```
get_time_clusters(object)

## S3 method for class 'time_cluster_data'
get_time_clusters(object)

## S3 method for class 'cluster_analysis'
get_time_clusters(object)
```

Arguments

object The output of the analyze_time_clusters function

Value

A dataframe with information about the clusters

Methods (by class)

- time_cluster_data: Get time clusters dataframe
- cluster_analysis: Get time clusters dataframe

make_boot_splines_data
Bootstrap resample splines for time-series data.

Description

Deprecated. Performing this analysis should be done by calling analyze_time_bins(test="boot_splines").

Usage

```
make_boot_splines_data(data, predictor_column, within_subj, aoi, bs_samples,
  smoother, resolution, alpha, ...)

## S3 method for class 'time_sequence_data'
make_boot_splines_data(data, predictor_column,
  within_subj, aoi = NULL, bs_samples = 1000, smoother = "smooth.spline",
  resolution = NULL, alpha = 0.05, ...)
```



```

within_subj = FALSE,
bs_samples = 500,
alpha = .05,
smoother = "smooth.spline")

```

```
make_eyetrackingr_data
```

Convert raw data for use in eyetrackingR

Description

This should be the first function you use when using eyetrackingR for a project (potentially with the exception of ‘add_aoi’, if you need to add AOIs). This function takes your raw dataframe, as well as information about your dataframe. It confirms that all the columns are the right format, based on this information. Further if `treat_non_aoi_looks_as_missing` is set to TRUE, it converts non-AOI looks to missing data (see the "Preparing your data" vignette for more information).

Usage

```

make_eyetrackingr_data(data, participant_column, trackloss_column, time_column,
  trial_column, aoi_columns, treat_non_aoi_looks_as_missing,
  item_columns = NULL)

```

Arguments

<code>data</code>	Your original data. See details section below.
<code>participant_column</code>	Column name for participant identifier
<code>trackloss_column</code>	Column name indicating trackloss
<code>time_column</code>	Column name indicating time
<code>trial_column</code>	Column name indicating trial identifier
<code>aoi_columns</code>	Names of AOIs
<code>treat_non_aoi_looks_as_missing</code>	This is a logical indicating how you would like to perform "proportion-looking" calculations, which are central to eyetrackingR's eyetracking analyses. If set to TRUE, any samples that are not in any of the AOIs (defined with the <code>aoi_columns</code> argument) are treated as missing data; when it comes time for eyetrackingR to calculate proportion looking to an AOI, this will be calculated as "time looking to that AOI divided by time looking to all other AOIs." In contrast, if this parameter is set to FALSE, proportion looking to an AOI will be calculated as "time looking to that AOI divided by total time looking."
<code>item_columns</code>	Column names indicating items (optional)

Details

eyetrackingR is designed to deal with data in a (relatively) raw form, where each row specifies a sample. Each row should represent an equally spaced unit of time (e.g., if your eye-tracker's sample rate is 100hz, then each row corresponds to the eye-position every 10ms). This is in contrast to the more parsed data that the software bundled with eye-trackers can sometimes output (e.g., already parsed into saccades or fixations). For eyetrackingR, the simplest data is the best. This also maximizes compatibility: eyetrackingR will work with any eye-tracker's data (e.g., Eyelink, Tobii, etc.), since it requires the most basic format.

Value

Dataframe ready for use in eyetrackingR.

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
```

make_onset_data	<i>Make onset-contingent data.</i>
-----------------	------------------------------------

Description

Divide trials into which AOI participants started on. Calculate switches away from this AOI, using a rolling window to determine what length constitutes a switch. Augment original data with a column indicating whether each row is a switch-away sample.

Usage

```
make_onset_data(data, onset_time, fixation_window_length, target_aoi,
                distractor_aoi = NULL)
```

Arguments

data	The original (verified) data
onset_time	When to check for participants' "starting" AOI?
fixation_window_length	Which AOI is currently being fixated is determined by taking a rolling average of this length (ms). This is the width of window for rolling average.

target_aoi Which AOI is the target that should be switched *to*
 distractor_aoi Which AOI is the distractor that should be switched *from* (default = !target_aoi)

Value

Original dataframe augmented with column indicating switch away from target AOI

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
response_window <- subset_by_window(data, window_start_time = 15500, window_end_time = 21000,
                                   rezero = FALSE)
inanimate_trials <- subset(response_window, grepl('(Spoon|Bottle)', Trial))
onsets <- make_onset_data(inanimate_trials, onset_time = 15500,
                          fixation_window_length = 1, target_aoi='Inanimate')
```

make_switch_data *Summarize data into time-to-switch from initial AOI.*

Description

Take trials split by initial-AOI, and determine how quickly participants switch away from that AOI

Usage

```
make_switch_data(data, predictor_columns, summarize_by)

## S3 method for class 'onset_data'
make_switch_data(data, predictor_columns = NULL,
                 summarize_by = NULL)
```

Arguments

data The output of make_onset_data
 predictor_columns Variables/covariates of interest when analyzing time-to-switch
 summarize_by Should the data be summarized along, e.g., participants, items, etc.? If so, give column name(s) here. If left blank, will leave trials distinct. The former is needed for more traditional analyses (t.tests, ANOVAs), while the latter is preferable for mixed-effects models (lmer)

Value

A dataframe indicating initial AOI and time-to-switch from that AOI for each trial/subject/item/etc.

Methods (by class)

- onset_data:

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
response_window <- subset_by_window(data, window_start_time = 15500, window_end_time = 21000,
                                   rezero = FALSE)
inanimate_trials <- subset(response_window, grepl('(Spoon|Bottle)', Trial))
onsets <- make_onset_data(inanimate_trials, onset_time = 15500,
                         fixation_window_length = 100, target_aoi='Inanimate')

df_switch <- make_switch_data(onsets, predictor_columns = "MCDI_Total",
                             summarize_by = "ParticipantName")
plot(df_switch, "MCDI_Total")
```

make_time_cluster_data

Make data for cluster analysis.

Description

Takes data that has been summarized into time-bins by `make_time_sequence_data()`, finds adjacent time bins that pass some test-statistic threshold, and assigns these adjacent bins into groups (clusters). Output is ready for a cluster permutation-based analyses (Maris & Oostenveld, 2007). Supports `t.test`, `wilcox.test`, `(g)lm`, and `(g)lmer`. Also includes support for the "bootstrapped-splines" test (see `?make_boot_splines_data` and [the divergence vignette](#) for more info). By default, this function uses 'proportion-looking' (Prop) as the DV, which can be changed by manually specifying the formula.

Usage

```
make_time_cluster_data(data, ...)

## S3 method for class 'time_sequence_data'
```



```
make_time_cluster_data(data, predictor_column,
  aoi = NULL, test, threshold = NULL, formula = NULL,
  treatment_level = NULL, ...)
```

Arguments

<code>data</code>	The output of the <code>make_time_sequence_data</code> function
<code>...</code>	Any other arguments to be passed to the selected 'test' function (e.g., <code>paired</code> , <code>var.equal</code> , etc.)
<code>predictor_column</code>	The column name containing the variable whose test statistic you are interested in.
<code>aoi</code>	Which AOI should be analyzed? If not specified (and dataframe has multiple AOIs), then AOI should be a predictor/covariate in your model (so 'formula' needs to be specified).
<code>test</code>	What type of test should be performed in each time bin? Supports <code>t.test</code> , <code>(g)lm</code> , or <code>(g)lmer</code> . Also includes experimental support for the "bootstrapped-splines" test (see <code>?make_boot_splines_data</code> and the divergence vignette for more info). Does not support <code>wilcox.test</code> .
<code>threshold</code>	Time-bins with test-statistics greater than this amount will be grouped into clusters.
<code>formula</code>	What formula should be used for test? Optional (for all but <code>(g)lmer</code>), if unset uses <code>Prop ~ [predictor_column]</code>
<code>treatment_level</code>	If your predictor is a factor, regression functions like 'lm' and 'lmer' by default will treatment-code it. One option is to sum-code this predictor yourself before entering it into this function. Another is to use the 'treatment_level' argument, which specifies the level of the predictor. For example, you are testing a model where 'Target' is a predictor, which has two levels, 'Animate' and 'Inanimate'. R will code 'Animate' as the reference level, and code 'Inanimate' as the treatment level. You'd therefore want to set 'treatment_level = Inanimate'.

Value

The original data, augmented with information about clusters. Calling `summary` on this data will describe these clusters. The dataset is ready for the [analyze_time_clusters](#) method.

Methods (by class)

- `time_sequence_data`: Make data for time cluster analysis

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
  participant_column = "ParticipantName",
  trial_column = "Trial",
  time_column = "TimeFromTrialOnset",
```

```

        trackloss_column = "TrackLoss",
        aoi_columns = c('Animate', 'Inanimate'),
        treat_non_aoi_looks_as_missing = TRUE )
response_window <- subset_by_window(data, window_start_time = 15500, window_end_time = 21000,
                                   rezero = FALSE)

# identify clusters in the sequence data using a t-test with
# threshold t-value of 2

# (note: t-tests require a summarized dataset)
response_time <- make_time_sequence_data(response_window, time_bin_size = 500, aois = "Animate",
                                         predictor_columns = "Sex",
                                         summarize_by = "ParticipantName")

time_cluster_data <- make_time_cluster_data(data = response_time,
                                           predictor_column = "Sex",
                                           aoi = "Animate",
                                           test = "t.test",
                                           threshold = 2
)

# identify clusters in the sequence data using an lmer() random-effects
# model with a threshold t-value of 1.5.

# random-effects models don't require us to summarize
response_time <- make_time_sequence_data(response_window, time_bin_size = 500, aois = "Animate",
                                         predictor_columns = "Sex")

# but they do require a formula to be specified
time_cluster_data <- make_time_cluster_data(data = response_time,
                                           predictor_column = "SexM",
                                           aoi = "Animate",
                                           test = "lmer",
                                           threshold = 1.5,
                                           formula = LogitAdjusted ~ Sex + (1|Trial) + (1|ParticipantName)
)

```

```

make_time_sequence_data
      make_time_sequence_data()

```

Description

Creates time-bins and summarizes proportion-looking within each time-bin.

Usage

```

make_time_sequence_data(data, time_bin_size, aois = NULL,
                        predictor_columns = NULL, other_dv_columns = NULL, summarize_by = NULL)

```

Arguments

data	The output of make_eyetrackingr_data
time_bin_size	How large should each time bin be? Units are whatever units your time column is in
aois	Which AOI(s) is/are of interest? Defaults to all specified in make_eyetracking_r_data
predictor_columns	Which columns indicate predictor variables, and therefore should be preserved in grouping operations?
other_dv_columns	Within each time-bin, this function will calculate not only proportion- looking, but also the mean of any columns specified here.
summarize_by	Should the data be summarized along, e.g., participants, items, etc.? If so, give column name(s) here. If left blank, will leave trials distinct. The former is needed for more traditional analyses (t . test, ANOVA), while the latter is preferable for mixed-effects models (lmer)

Details

Aside from proportion looking (Prop), this function returns several columns useful for subsequent analysis:

- **LogitAdjusted** - The logit is defined as $\log(\text{Prop} / (1 - \text{Prop}))$. This transformation attempts to map bounded 0,1 data to the real number line. Unfortunately, for data that is exactly 0 or 1, this is undefined. One solution is add a very small value to any datapoints that equal 0, and subtract a small value to any datapoints that equal 1 (we use 1/2 the smallest nonzero value for this adjustment).
- **Elog** - Another way of calculating a corrected logit transformation is to add a small value epsilon to both the numerator and denominator of the logit equation (we use 0.5).
- **Weights** - These attempt to further correct the Elog transformation, since the variance of the logit depends on the mean. They can be used in a mixed effects model by setting the weights=Weights in lmer (note that this is the reciprocal of the weights calculated in [this empirical logit walkthrough](#), so you do *not* set weights = 1/Weights as done there.)
- **ArcSin** - The arcsine-root transformation of the raw proportions, defined as $\text{asin}(\sqrt{\text{Prop}})$
- **ot** - These columns (ot1-ot7) represent (centered) orthogonal time polynomials, needed for growth curve analysis. See [the vignette on growth curve models](#) for more details.

Value

Data binned into time-bins, with proportion-looking and transformations as well as orthogonal time-polynomials for growth curve analysis

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                             participant_column = "ParticipantName",
```

```

        trial_column = "Trial",
        time_column = "TimeFromTrialOnset",
        trackloss_column = "TrackLoss",
        aoi_columns = c('Animate','Inanimate'),
        treat_non_aoi_looks_as_missing = TRUE
    )

# bin data in 250ms bins, and generate a dataframe
# with a single AOI (Animate) predicted by Sex, and summarized by ParticipantName
response_time <- make_time_sequence_data(data,
                                         time_bin_size = 250,
                                         predictor_columns = c("Sex"),
                                         aois = "Animate",
                                         summarize_by = "ParticipantName"
)

# optionally specify other columns in the data
# to be included in the generated dataframe
# (e.g., for use in statistical models)
# bin data in 250ms bins, and generate a dataframe
# with Animate and MCDI_Total summarized by ParticipantName
response_time <- make_time_sequence_data(data,
                                         time_bin_size = 250,
                                         predictor_columns = c("Sex", "MCDI_Total"),
                                         aois = "Animate",
                                         summarize_by = "ParticipantName"
)

```

make_time_window_data *Make a dataset collapsing over a time-window*

Description

Collapse time across our entire window and return a dataframe ready for analyses

Usage

```
make_time_window_data(data, aois = NULL, predictor_columns = NULL,
                      other_dv_columns = NULL, summarize_by = NULL)
```

Arguments

data	The output of make_eyetrackingr_data
aois	Which AOI(s) is/are of interest? Defaults to all specified in make_eyetracking_r_data
predictor_columns	Which columns indicate predictor vars, and therefore should be preserved in grouping operations?

other_dv_columns	Within each participant/trial (or whatever is specified in summarize_by), this function will calculate not only proportion-looking, but also the mean of any columns specified here.
summarize_by	Should the data be summarized along, e.g., participants, items, etc.? If so, give column names here. If left blank, will leave trials distinct. The former is needed for more traditional analyses (t. test, ANOVA), while the latter is preferable for mixed-effects models (lmer)

Details

Aside from proportion looking (Prop), this function returns several columns useful for subsequent analysis:

- **LogitAdjusted** - The logit is defined as $\log(\text{Prop} / (1 - \text{Prop}))$. This transformation attempts to map bounded 0,1 data to the real number line. Unfortunately, for data that is exactly 0 or 1, this is undefined. One solution is add a very small value to any datapoints that equal 0, and subtract a small value to any datapoints that equal 1 (we use 1/2 the smallest nonzero value for this adjustment).
- **Elog** - Another way of calculating a corrected logit transformation is to add a small value epsilon to both the numerator and denominator of the logit equation (we use 0.5).
- **Weights** - These attempt to further correct the Elog transformation, since the variance of the logit depends on the mean. They can be used in a mixed effects model by setting the weights=Weights in lmer (note that this is the reciprocal of the weights calculated in [this empirical logit walkthrough](#), so you do *not* set weights = 1/Weights as done there.)
- **ArcSin** - The arcsine-root transformation of the raw proportions, defined as $\text{asin}(\sqrt{\text{Prop}})$

Value

Data with proportion-looking and transformations (logit, arc-sin, etc.)

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)

# generate a dataset summarizing an AOI (Animate) by ParticipantName
response_window_agg_by_sub <- make_time_window_data(data,
                                                    aois='Animate',
                                                    summarize_by = "ParticipantName"
)

# optionally included additional columns for use as predictors
```

```
# in later statistical models
response_window_agg_by_sub <- make_time_window_data(data,
                                                    aois='Animate',
                                                    predictor_columns=c('Age', 'MCDI_Total'),
                                                    summarize_by = "ParticipantName"
)

# plot the aggregated data for sanity check
plot(response_window_agg_by_sub, predictor_columns="Age", dv = "LogitAdjusted")
```

plot.bin_analysis *Plot test-statistic for each time-bin in a time-series*

Description

Plot the result from the analyze_time_bins function, with the statistic and threshold for each bin

Usage

```
## S3 method for class 'bin_analysis'
plot(x, type = NULL, ...)
```

Arguments

x	The output of analyze_time_bins
type	This function can plot the test-statistic ("statistic"), the parameter estimate +/- std. error ("estimate"), the p-value ("pvalue") or the negative-log-pvalue ("neg_log_pvalue"). When test gives critical-statistic, default is to plot the test-statistic. Otherwise, default is to plot the estimate. For wilcox, only p-values can be plotted.
...	Ignored

Value

A ggplot object

plot.boot_splines_analysis *Plot differences in bootstrapped-splines data*

Description

Plot the means and CIs of bootstrapped spline difference estimates and intervals (either within-subjects or between-subjects)

Usage

```
## S3 method for class 'boot_splines_analysis'  
plot(x, ...)
```

Arguments

x	The output of the analyze_boot_splines function
...	Ignored

Value

A ggplot object

plot.boot_splines_data
Plot bootstrapped-splines data

Description

Plot the means and CIs of bootstrapped splines (either within-subjects or between-subjects)

Usage

```
## S3 method for class 'boot_splines_data'  
plot(x, ...)
```

Arguments

x	The output of the make_boot_splines_data function
...	Ignored

Value

A ggplot object

plot.cluster_analysis *Visualize the results of a cluster analysis.*

Description

Plots the result of the bootstrapping cluster analysis. A histogram of the sum statistics for the shuffled (null) distribution, with the sum statistics for each of the clusters indicated by dashed lines.

Usage

```
## S3 method for class 'cluster_analysis'  
plot(x, ...)
```

Arguments

x	object returned by cluster_analysis()
...	Ignored

Value

A ggplot object

plot.eyetrackingR_data_summary
Plot some summarized data from eyetrackingR

Description

Plots the data returned from describe_data. Like that function, this is a convenient wrapper good for sanity checks.

Usage

```
## S3 method for class 'eyetrackingR_data_summary'  
plot(x, ...)
```

Arguments

x	The data returned by make_time_window_data()
...	Ignored

Value

A ggplot object

plot.onset_data *Plot onset-contingent data*

Description

Divide trials into which AOI participants started on; plot proportion looking away from that AOI.

Usage

```
## S3 method for class 'onset_data'
plot(x, predictor_columns = NULL, ...)
```

Arguments

x The output of the make_onset_data function
 predictor_columns Column(s) by which to facet the data. Maximum two columns. Will perform median split if numeric.
 ... Ignored

Value

A ggplot object

plot.switch_data *Plot mean switch-from-initial-AOI times.*

Description

Boxplot of mean switch time aggregated by subjects within each FirstAOI, potentially faceted by predictor_columns.

Usage

```
## S3 method for class 'switch_data'
plot(x, predictor_columns = NULL, ...)
```

Arguments

x The output of the make_switch_data function
 predictor_columns Column(s) by which to facet the data. Maximum two columns. Will perform median split if numeric.
 ... Ignored

Value

A ggplot object

plot.time_cluster_data

Plot test-statistic for each time-bin in a time-series, highlight clusters. Plot time_cluster_data, highlights clusters of above-threshold time-bins.

Description

Plot test-statistic for each time-bin in a time-series, highlight clusters. Plot time_cluster_data, highlights clusters of above-threshold time-bins.

Usage

```
## S3 method for class 'time_cluster_data'
plot(x, type = NULL, ...)
```

Arguments

x	The output of make_time_cluster_data
type	This function can plot the test-statistic ("statistic"), the parameter estimate +/- std. error ("estimate"), the p-value ("pvalue") or the negative-log-pvalue ("neg_log_pvalue"). When test gives critical-statistic, default is to plot the test-statistic. Otherwise, default is to plot the estimate. For wilcox, only p-values can be plotted; for boot-splines, p-values cannot be plotted.
...	Ignored

Value

A ggplot object

plot.time_sequence_data

Plot time-sequence data

Description

Plot the timecourse of looking. Each AOI will be plotted in a separate pane, and data can be split into groups by a predictor column. Data is collapsed by subject for plotting. Supports overlaying the predictions of a growth-curve mixed effects model on the data

Usage

```
## S3 method for class 'time_sequence_data'
plot(x, predictor_column = NULL, dv = "Prop",
     model = NULL, ...)
```

Arguments

x	Your data from make_time_sequence_data. Will be collapsed by subject for plotting (unless already collapsed by some other factor).
predictor_column	Data can be grouped by a predictor column (median split is performed if numeric)
dv	What measure of gaze do you want to use? (Prop, Elog, or ArcSin)
model	(Optional) A growth-curve mixed effects model (from lmer) that was used on the time_sequence_data. If model is given, this function will overlay the predictions of that model on the data
...	Ignored

Value

A ggplot object

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)
response_time <- make_time_sequence_data(data, time_bin_size = 250,
                                         predictor_columns = c("MCDI_Total"),
                                         aois = "Animate", summarize_by = "ParticipantName")

# visualize time results
plot(response_time, predictor_column = "MCDI_Total")
```

plot.time_window_data *Plot a time-window dataset*

Description

Plots the data returned from `make_time_window_data`. Data can be mapped onto (up to two) predictor columns. If no predictor columns are supplied, AOI is placed on the x-axis; otherwise, data for each AOI is set in a separate facet.

Usage

```
## S3 method for class 'time_window_data'
plot(x, predictor_columns = NULL, dv = "Prop",
     ...)
```

Arguments

<code>x</code>	The data returned by <code>make_time_window_data()</code>
<code>predictor_columns</code>	Up to two columns indicating predictors. The first maps to the X-axis, the second to group/color. If the latter is numeric, a median split is performed.
<code>dv</code>	Which dv should be used in plotting? Raw proportion-looking ("Prop"), empirical logit ("Elog"), or "ArcSin"?
<code>...</code>	Ignored

Details

Data are collapsed by-participants for plotting.

Value

A ggplot object

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE)
response_window_agg_by_sub <- make_time_window_data(data,
                                                    aois='Animate',
                                                    predictor_columns=c('Age', 'MCDI_Total'))

plot(response_window_agg_by_sub, predictor_columns="Age", dv = "LogitAdjusted")
```

```
print.cluster_analysis
```

Print Method for Cluster Analysis

Description

Print Method for Cluster Analysis

Usage

```
## S3 method for class 'cluster_analysis'  
print(x, ...)
```

Arguments

x	The output of the analyze_clusters function
...	Ignored

Value

Prints information about the bootstrapped null distribution, as well as information about each cluster.

```
reclass
```

Add the original class/attributes back onto result (usually of dplyr operation)

Description

Add the original class/attributes back onto result (usually of dplyr operation)

Usage

```
reclass(x, result, ...)
```

Arguments

x	The original object, class information you want to restore.
result	Some transformation of x, which may have removed its class/attributes.
...	Ignored

Value

The result, now with class/attribute information restored.

```
simulate_eyetrackingr_data
```

Simulate an eyetrackingR dataset

Description

This function creates an eyetrackingR dataset (i.e., already run through `make_eyetrackingr_data`). This can be helpful for examining the false-alarm and sensitivity of analysis-techniques via simulations.

Usage

```
simulate_eyetrackingr_data(num_participants = 16,  
  num_items_per_condition = 6, trial_length = 5000, pref = 0.5,  
  pref_window = c(1, trial_length), noisy_window = NULL, ...)
```

Arguments

<code>num_participants</code>	Number of participants
<code>num_items_per_condition</code>	Number of trials per-subject per-condition.
<code>trial_length</code>	How long is the trial (in ms)?
<code>pref</code>	Their preference between the two AOIs in the "high" condition, where 1 is 100 preference). In the "low" condition, their preference between the two AOIs is equal, so default is no effect of condition.
<code>pref_window</code>	Vector of length two, specifying start and end of time-window in which participants expressed the preference specified in <code>pref</code> . Default is the entire trial
<code>noisy_window</code>	Vector of length two, specifying start and end of time-window in which there was substantial trackloss during the trial.
<code>...</code>	Ignored

Value

Dataframe with eye-tracking data

subset_by_window *Extract a subset of the dataset within a time-window in each trial.*

Description

One of the more annoying aspects of preparing raw eyetracking data is filtering data down into the relevant window within the trial, since for many experiments the precise start and end time of this window can vary from trial to trial. This function allows for several approaches to subsetting data into the relevant time- window– see 'Details' below.

Usage

```
subset_by_window(data, rezero = TRUE, remove = TRUE,
  window_start_msg = NULL, window_end_msg = NULL, msg_col = NULL,
  window_start_col = NULL, window_end_col = NULL,
  window_start_time = NULL, window_end_time = NULL, quiet = FALSE)
```

Arguments

data	Your original dataset
rezero	Should the beginning of the window be considered the zero point of the timestamp? Default TRUE
remove	Should everything before the beginning and after the end of the window be removed? Default TRUE. If set to FALSE and rezero is set to FALSE, an error is thrown (since in this case, the function would not do anything).
window_start_msg	For method (1). A message that is present only in the row whose time corresponds to the trial start time. Common for eyetrackers that send a message at trial/stimuli start.
window_end_msg	For method (1). A message that is present only in the row whose time corresponds to the trial end time. Common for eyetrackers that send a message at trial-end/keypress/lookaway/etc.
msg_col	For method (1). If you are indicating the trial start/end with a message column, this is the name of that column.
window_start_col	For method (2). A column that gives the start time for each trial.
window_end_col	For method (2). A column that gives the end time for each trial.
window_start_time	For method (3). Number indicating a start time that applies to all trials.
window_end_time	For method (3). Number indicating an end time that applies to all trials.
quiet	Suppress messages? Default FALSE

Details

1. The trial start/end times can be indicated by a message that is sent (e.g., TRIAL_START) in a particular row for each trial. In this case, the timestamp of that row is used.
2. The trial start/end times can be indicated in by a column that specifies trial start/end times for each trial.
3. The trial start/end times can be indicated by the actual start and stop time, the same across all trials (the simplest case).

If you only have a start time but the end time doesn't need adjusting, then leave the end time argument blank; and vice versa.

This function can either rezero your data (the trial start time you select is the new zero-time-point), or not. The former is useful when performing initial data-cleaning (e.g., different trial-starts on each trial, as indicated by a message), and the latter is useful if you want to "zoom in" on a particular portion of your data while keeping obvious the fact that there were other parts of the trial (e.g., an image always appears 5000ms-7000ms in the trial, so for one analysis you are only interested in this portion).

Value

Subsetted data

Examples

```
data("word_recognition")
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)

# zoom in to 15500-21000ms
response_window <- subset_by_window(data,
                                    window_start_time = 15500,
                                    window_end_time = 21000, rezero = FALSE, remove = TRUE)

# zoom in to 15500-21000ms and re-zero so timestamps start at 0
response_window <- subset_by_window(data,
                                    window_start_time = 15500,
                                    window_end_time = 21000,
                                    rezero = TRUE,
                                    remove = TRUE)

# keep all data, but re-zero it
response_window <- subset_by_window(data,
                                    window_start_time = 0,
                                    rezero = TRUE,
                                    remove = FALSE)
```

summary.bin_analysis *Summary Method for Time-bin Analysis*

Description

Summary Method for Time-bin Analysis

Usage

```
## S3 method for class 'bin_analysis'  
summary(object, ...)
```

Arguments

object	The output of the analyze_time_bins function
...	Ignored

Value

Prints information about each run of statistically significant time-bins, separately for positive and negative

summary.boot_splines_analysis
Summary Method for Bootstrapped Splines Analysis

Description

Summary Method for Bootstrapped Splines Analysis

Usage

```
## S3 method for class 'boot_splines_analysis'  
summary(object, ...)
```

Arguments

object	The output of the boot_splines_data function
...	Ignored

Value

Prints a list of divergence-times.

`summary.cluster_analysis`*Summary Method for Cluster Analysis*

Description

Summary Method for Cluster Analysis

Usage

```
## S3 method for class 'cluster_analysis'  
summary(object, ...)
```

Arguments

<code>object</code>	The output of the <code>analyze_clusters</code> function
<code>...</code>	Ignored

Value

Prints information about the bootstrapped null distribution, as well as information about each cluster.

`summary.time_cluster_data`*Summary Method for Cluster Analysis*

Description

Summary Method for Cluster Analysis

Usage

```
## S3 method for class 'time_cluster_data'  
summary(object, ...)
```

Arguments

<code>object</code>	The output of the <code>analyze_clusters</code> function
<code>...</code>	Ignored

Value

Prints information about the bootstrapped null distribution, as well as information about each cluster.

trackloss_analysis *Analyze trackloss.*

Description

Get information on trackloss in your data.

Usage

```
trackloss_analysis(data)
```

Arguments

data The output of make_eyetrackingr_data

Value

A dataframe describing trackloss by-trial and by-participant

Examples

```
data(word_recognition)
data <- make_eyetrackingr_data(word_recognition,
                              participant_column = "ParticipantName",
                              trial_column = "Trial",
                              time_column = "TimeFromTrialOnset",
                              trackloss_column = "TrackLoss",
                              aoi_columns = c('Animate', 'Inanimate'),
                              treat_non_aoi_looks_as_missing = TRUE
)

tl_analysis <- trackloss_analysis(data)
```

word_recognition *Data collected in an infant eyetracking study*

Description

Data from a simple 2-alternative forced choice (2AFC) word recognition task administered to 19- and 24-month-olds. On each trial, infants were shown a picture of an animate object (e.g., a horse) and an inanimate object (e.g., a spoon). After inspecting the images, they disappeared and they heard a label referring to one of them (e.g., "The horse is nearby!"). Finally, the objects re-appeared on the screen and they were prompted to look at the target (e.g., "Look at the horse!").

Usage

word_recognition

Format

A data frame with 53940 rows and 10 variables:

ParticipantName Unique participant ID

Sex M or F

Age Age, in months

TrialNum Unique Trial Number

Trial Name of item shown on trial (also unique for each participant)

TimeFromTrialOnset Time within trial

Subphase Subphase within trial (see above)

TimeFromSubphaseOnset Time within subphase

AOI Which AOI are they looking at

Animate Are they looking at the animate AOI?

Inanimate Are they looking at the inanimate AOI?

TrackLoss Does current sample not have valid tracking data?

MCDI_Total Total vocabulary score on MCDI

MCDI_Nouns Noun vocabulary score on MCDI

MCDI_Verbs Verb vocabulary score on MCDI...

Source

Ferguson, B., Graf, E., & Waxman, S. R. (2014). Infants use known verbs to learn novel nouns: Evidence from 15- and 19-month-olds. *Cognition*, 131(1), 139-146.

Index

*Topic **datasets**

word_recognition, 35

add_aoi, 2

analyze_boot_splines, 3

analyze_time_bins, 5

analyze_time_clusters, 6, 17

clean_by_trackloss, 8

describe_data, 9

eyetrackingR, 10

eyetrackingR-package (eyetrackingR), 10

get_time_clusters, 11

make_boot_splines_data, 11

make_eyetrackingr_data, 13

make_onset_data, 14

make_switch_data, 15

make_time_cluster_data, 16

make_time_sequence_data, 18

make_time_window_data, 20

plot.bin_analysis, 22

plot.boot_splines_analysis, 22

plot.boot_splines_data, 23

plot.cluster_analysis, 24

plot.eyetrackingR_data_summary, 24

plot.onset_data, 25

plot.switch_data, 25

plot.time_cluster_data, 26

plot.time_sequence_data, 26

plot.time_window_data, 28

print.cluster_analysis, 29

reclass, 29

simulate_eyetrackingr_data, 30

subset_by_window, 31

summary.bin_analysis, 33

summary.boot_splines_analysis, 33

summary.cluster_analysis, 34

summary.time_cluster_data, 34

trackloss_analysis, 35

word_recognition, 35